

Maximum Permissible Exposure Report

1. Product Information

FCC ID	: 2AGKBKM9M1V1
EUT	: Android TV BOX
Test Model	: KM9
Additional Model	: KM1, KM1PRO, KM1PLUS, KM3, KM3PRO, KM3, PLUS, KM5, KM6, KM7, KM8, KM8 PRO, KM8 PLUS, KM9 PRO, KM9 PLUS, V1, V1 PRO, V1 PLUS, V2, V2 PRO, V2 PLUS, V3, V3 PRO, V3 PLUS, V5, V5 PRO, V5 PLUS, V6, V6 PRO, V6 PLUS, V7, V7 PRO, V7 PLUS, V8, V8 PRO, V8 PLUS, V9, V9 PRO, V9 PLUS, M1, M1 PRO, M2, M2 PRO, M3, M3 PRO, M5, M5 PRO, M6, M6 PRO, M7, M7 PRO, M8, M8 PRO, M9, M9 PRO, BDTVs01, BDTVs02, BDTVs03, BDTVsA1, BDTVsA2, BDTVsA3
Model Declaration	: PCB board, structure and internal of these model(s) are the same, So no additional models were tested.
Power Supply	: Power By Adapter: Model: KA1201A-0502000US Input: AC 100-240V, 50/60Hz, 0.4A Output: DC 5V/2A
Hardware Version	: REV:2.2
Software Version	: Android 9.0
Bluetooth	:
Frequency Range	: 2402 – 2480 MHz
Channel Number	: 79 Channels for Bluetooth 4.1 (BT Classics) 40 Channels for Bluetooth 4.1 (BT LE)
Modulation Type	: GFSK, $\pi/4$ -DQPSK, 8-DPSK for Bluetooth 4.1 (BT Classics) GFSK, for Bluetooth 4.1 (BT LE)
2.4G WLAN	:
Frequency Range	: 2412 – 2462 MHz
Channel Number	: 11 Channels for 20MHz bandwidth (2412~2462MHz) 7 Channels for 40MHz bandwidth (2422~2452MHz)
Modulation Type	: IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK)
WIFI 5GWLAN Band 1	:
Frequency Range	: 5180 – 5240 MHz
Channel Number	: 4 channels for 20MHz bandwidth (5180-5240MHz) 2 channels for 40MHz bandwidth (5190~5230MHz) 1 channels for 80MHz bandwidth (5210MHz)
Modulation Type	: IEEE 802.11a/n/ac: OFDM (64QAM, 16QAM, QPSK, BPSK)
WIFI 5GWLAN Band 3	:
Frequency Range	: 5745 – 5825 MHz
Channel Number	: 5 channels for 20MHz bandwidth (5745-5825MHz) 2 channels for 40MHz bandwidth (5755~5795MHz) 1 channels for 80MHz bandwidth (5775MHz)
Modulation Type	: IEEE 802.11a/n/ac: OFDM (64QAM, 16QAM, QPSK, BPSK)
Antenna Description	:
	: Internal Antenna, 3.0dBi (Max.) The BT, 2.4GWIFI and 5.2GWIFI and 5.8G WIFI shares the same antenna.
Exposure category	: General population/uncontrolled environment
EUT Type	: Production Unit
Device Type	: Mobile Device

2. Evaluation Method

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

In accordance with KDB447498D01 for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modelled or measured field strengths or power density, is ≤ 1.0 . The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency. Either the maximum peak or spatially averaged results from measurements or numerical simulations may be used to determine the MPE ratios. Spatial averaging does not apply when MPE is estimated using simple calculations based on far-field plane-wave equivalent conditions. The antenna installation and operating requirements for the host device must meet the minimum test separation distances required by all antennas, in both standalone and simultaneous transmission operations, to satisfy compliance.

3. Limit

3.1 Refer Evaluation Method

[ANSI C95.1-1999](#): IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

[FCC KDB publication 447498 D01 General 1 RF Exposure Guidance v06](#): Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

[FCC CFR 47 part1 1.1310](#): Radiofrequency radiation exposure limits.

[FCC CFR 47 part2 2.1091](#): Radiofrequency radiation exposure evaluation: mobile devices.

3.2 Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f ²)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f ²)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density

4. MPE Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S=PG/4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

5. Antenna Information

KM9 can only use antennas certificated as follows provided by manufacturer;

Internal Identification	Antenna type and antenna number	Operate frequency band	Maximum antenna gain
Antenna 0	Internal antenna	2 – 6 GHz	3.00 dBi

6. Conducted Power

[BT Classics]

Mode	Channel	Frequency (MHz)	Peak Conducted Output Power (dBm)
GFSK	0	2402	-1.181
	39	2441	-0.197
	78	2480	-1.077
π /4DQPSK	0	2402	-1.823
	39	2441	-0.515
	78	2480	-1.338
8DPSK	0	2402	-1.659
	39	2441	-0.373
	78	2480	-1.097

[BT LE]

Mode	Channel	Frequency (MHz)	Peak Conducted Output Power (dBm)
GFSK – BT LE	0	2402	-1.485
	19	2440	-0.249
	39	2480	-1.058

[2G4 WLAN]

Mode	Channel	Frequency (MHz)	Peak Conducted Output Power (dBm)
IEEE 802.11b	1	2412	14.25
	6	2437	14.88
	11	2462	14.86
IEEE 802.11g	1	2412	13.17
	6	2437	13.45
	11	2462	13.37
IEEE 802.11n HT20	1	2412	12.82
	6	2437	12.76
	11	2462	12.62
IEEE 802.11n HT40	3	2422	10.21
	6	2437	10.17
	9	2452	10.09

[5GHz WLAN Band 1]

Mode	Channel	Frequency (MHz)	Average Conducted Output Power (dBm)
IEEE 802.11a	36	5180	11.86
	40	5200	11.34
	48	5240	11.16
IEEE 802.11n HT20	36	5180	11.01
	40	5200	11.09
	48	5240	11.48
IEEE 802.11ac VHT20	36	5180	10.56
	40	5200	10.72
	48	5240	11.17
IEEE 802.11n HT40	38	5190	11.68
	46	5230	11.69
IEEE 802.11ac VHT40	38	5190	10.73
	46	5230	10.32
IEEE 802.11ac VHT80	42	5210	10.02

[5GHz WLAN Band 3]

Mode	Channel	Frequency (MHz)	Average Conducted Output Power (dBm)
IEEE 802.11a	149	5745	11.18
	157	5785	11.05
	165	5825	11.56
IEEE 802.11n HT20	149	5745	11.17
	157	5785	11.27
	165	5825	11.07
IEEE 802.11ac VHT20	149	5745	10.41
	157	5785	10.18
	165	5825	11.17
IEEE 802.11n HT40	151	5755	11.68
	159	5795	11.69
IEEE 802.11ac VHT40	151	5755	10.73
	159	5795	10.32
IEEE 802.11ac VHT80	155	5775	9.78

7. Manufacturing Tolerance

<i>BT Classics</i>			
GFSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	-1.0	0	-1.0
Tolerance \pm (dB)	1.0	1.0	1.0
$\pi/4$ -DQPSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	-1.0	0	-1.0
Tolerance \pm (dB)	1.0	1.0	1.0
8-DPSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	-1.0	0	-1.0
Tolerance \pm (dB)	1.0	1.0	1.0
<i>BT LE</i>			
GFSK (Peak)			
Channel	Channel 0	Channel 19	Channel 39
Target (dBm)	-1.0	0	-1.0
Tolerance \pm (dB)	1.0	1.0	1.0
2G4WLAN			
IEEE 802.11b (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	15.0	15.0	15.0
Tolerance \pm (dB)	1.0	1.0	1.0
IEEE 802.11g (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	14.0	14.0	14.0
Tolerance \pm (dB)	1.0	1.0	1.0
IEEE 802.11n HT20 (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	13.0	13.0	13.0
Tolerance \pm (dB)	1.0	1.0	1.0
IEEE 802.11n HT40 (Peak)			
Channel	Channel 3	Channel 6	Channel 9
Target (dBm)	11.0	11.0	11.0
Tolerance \pm (dB)	1.0	1.0	1.0
[5GHz WLAN Band 1]			
IEEE 802.11a (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	12.0	12.0	12.0
Tolerance \pm (dB)	1.0	1.0	1.0
IEEE 802.11n HT20 (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	12.0	12.0	12.0

Tolerance \pm (dB)	1.0	1.0	1.0
<i>IEEE 802.11ac VHT20 (Average)</i>			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	11.0	11.0	12.00
Tolerance \pm (dB)	1.0	1.0	1.0
<i>IEEE 802.11n HT40 (Average)</i>			
Channel	Channel 38	Channel 46	
Target (dBm)	12.0	12.0	
Tolerance \pm (dB)	1.0	1.0	
<i>IEEE 802.11ac VHT40 (Average)</i>			
Channel	Channel 38	Channel 46	
Target (dBm)	11.0	11.0	
Tolerance \pm (dB)	1.0	1.0	
<i>IEEE 802.11ac VHT80 (Average)</i>			
Channel	Channel 42		
Target (dBm)	11.0		
Tolerance \pm (dB)	1.0		
[5GHz WLAN Band 3]			
<i>IEEE 802.11a (Average)</i>			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	12.0	12.0	12.0
Tolerance \pm (dB)	1.0	1.0	1.0
<i>IEEE 802.11n HT20 (Average)</i>			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	12.0	12.0	12.0
Tolerance \pm (dB)	1.0	1.0	1.0
<i>IEEE 802.11ac VHT20 (Average)</i>			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	11.0	11.0	12.0
Tolerance \pm (dB)	1.0	1.0	1.0
<i>IEEE 802.11n HT40 (Average)</i>			
Channel	Channel 151	Channel 159	
Target (dBm)	12.0	12.0	
Tolerance \pm (dB)	1.0	1.0	
<i>IEEE 802.11ac VH40 (Average)</i>			
Channel	Channel 151	Channel 159	
Target (dBm)	11.0	11.0	
Tolerance \pm (dB)	1.0	1.0	
<i>IEEE 802.11ac HT80 (Average)</i>			
Channel	Channel 155		
Target (dBm)	10.0		
Tolerance \pm (dB)	1.0		

8. Measurement Results

8.1 Standalone MPE Evaluation

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance, $r = 20\text{cm}$, as well as the gain of the used antenna refer to antenna information, the RF power density can be obtained.

[Antenna 0]

[BT Classics]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	Duty Cycle	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW					
GFSK	1.00	1.2589	3.0000	1.9953	100%	0.0005	1.0000
$\pi/4$ -DQPSK	1.00	1.2589	3.0000	1.9953	100%	0.0005	1.0000
8-DPSK	1.00	1.2589	3.0000	1.9953	100%	0.0005	1.0000

[BT LE]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	Duty Cycle	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW					
GFSK	1.00	1.2589	3.0000	1.9953	100%	0.0005	1.0000

[2G4WLAN]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	Duty Cycle	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW					
IEEE 802.11b	16.00	39.8107	3.0000	1.9953	100%	0.0158	1.0000
IEEE 802.11g	15.00	31.6228	3.0000	1.9953	100%	0.0126	1.0000
IEEE 802.11n HT20	14.00	25.1189	3.0000	1.9953	100%	0.0100	1.0000
IEEE 802.11n HT40	12.00	15.5489	3.0000	1.9953	100%	0.0063	1.0000

[5GHz WLAN Band 1]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	Duty Cycle	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW					
IEEE 802.11a	13.00	19.9526	3.0000	1.9953	100%	0.0079	1.0000
IEEE 802.11n HT20	13.00	19.9526	3.0000	1.9953	100%	0.0079	1.0000
IEEE 802.11ac VHT20	13.00	19.9526	3.0000	1.9953	100%	0.0079	1.0000
IEEE 802.11n HT40	13.00	19.9526	3.0000	1.9953	100%	0.0079	1.0000
IEEE 802.11ac VHT40	12.00	15.8489	3.0000	1.9953	100%	0.0063	1.0000
IEEE 802.11ac VHT80	12.00	15.8489	3.0000	1.9953	100%	0.0063	1.0000

[5GHz WLAN Band 3]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	Duty Cycle	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW					
IEEE 802.11a	13.00	19.9526	3.0000	1.9953	100%	0.0079	1.0000
IEEE 802.11n HT20	13.00	19.9526	3.0000	1.9953	100%	0.0079	1.0000
IEEE 802.11ac VHT20	13.00	19.9526	3.0000	1.9953	100%	0.0079	1.0000
IEEE 802.11n HT40	13.00	19.9526	3.0000	1.9953	100%	0.0079	1.0000
IEEE 802.11ac VHT40	12.00	15.8489	3.0000	1.9953	100%	0.0063	1.0000
IEEE 802.11ac VHT80	11.00	12.5893	3.0000	1.9953	100%	0.0050	1.0000

Remark:

1. Output power including turn-up tolerance;
2. Output power was adjust to duty cycle at 100% if measured duty cycle less than 98%;
3. MPE evaluate distance is 20cm from user manual provide by manufacturer.

8.2 Simultaneous Transmission MPE Evaluation

The sample support one BT/WLAN modular and share same antenna, BT and WLAN can be active at the same time, but only with interleaving of packages switched on board level. That means that they don't transmit at the same time. No need consider simultaneous transmission;

9. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

-----THE END OF REPORT-----