

FCC TEST REPORT

For

BICOM INC.

Wireless Microphone

Model No.: SIMEON SPREK T

Prepared For : BICOM INC.
Address : #2F, 7, Yanghyeon-ro 405beon-gil, Jungwon-gu, Seongnam-si,
Gyeonggi-do, South Korea

Prepared By : Shenzhen Anbotech Compliance Laboratory Limited
Address : 1/F, Building D, Sogood Science and Technology Park, Sanwei
community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong,
China.518102
Tel: (86) 755-26066440 Fax: (86) 755-26014772

Report Number : SZAWW181122006-01
Date of Receipt : Nov. 22, 2018
Date of Test : Nov. 22~Dec. 21, 2018
Date of Report : Dec. 21, 2018

Contents

1. General Information.....	4
1.1. Client Information.....	4
1.2. Description of Device (EUT).....	4
1.3. Auxiliary Equipment Used During Test.....	4
1.4. Description of Test Modes.....	5
1.5. List of channels.....	6
1.6. Description of Test Setup.....	7
1.7. Test Equipment List.....	8
1.8. Description of Test Facility.....	9
1.9. Measurement Uncertainty.....	9
2. Summary of Test Results.....	10
3. Conducted Emission Test.....	11
3.1. Test Standard and Limit.....	11
3.2. Test Setup.....	11
3.3. Test Procedure.....	11
3.4. Test Data.....	11
4. Radiation Spurious Emission and Band Edge.....	16
4.1. Test Standard and Limit.....	16
4.2. Test Setup.....	17
4.3. Test Procedure.....	18
4.4. Test Data.....	18
5. 20dB Bandwidth Test.....	25
5.1. Test Standard and Limit.....	25
5.2. Test Setup.....	25
5.3. Test Procedure.....	25
5.4. Test Data.....	25
6. Antenna Requirement.....	28
6.1. Test Standard and Requirement.....	28
6.2. Antenna Connected Construction.....	28
APPENDIX I -- TEST SETUP PHOTOGRAPH.....	29
APPENDIX II -- EXTERNAL PHOTOGRAPH.....	31
APPENDIX III -- INTERNAL PHOTOGRAPH.....	35

TEST REPORT

Applicant : BICOM INC.
Manufacturer : BICOM INC.
Product Name : Wireless Microphone
Model No. : SIMEON SPREK T
Trade Mark : N.A.
Rating(s) : Input: DC 5V, 2A(with DC 3.7V, 650mAh Battery inside)

Test Standard(s) : FCC Part15 Subpart C, Paragraph 15.249
Test Method(s) : ANSI C63.10: 2013

The device described above is tested by Shenzhen Anbotek Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Shenzhen Anbotek Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the FCC Part 15 Subpart C requirements.


This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen Anbotek Compliance Laboratory Limited.

Date of Test


Nov. 22~Dec. 21, 2018

Prepared by




(Engineer / Oliay Yang)

Reviewer


(Supervisor / Snowy Meng)

Approved & Authorized Signer


(Manager / Sally Zhang)

1. General Information

1.1. Client Information

Applicant	:	BICOM INC.
Address	:	#2F, 7, Yanghyeon-ro 405beon-gil, Jungwon-gu, Seongnam-si, Gyeonggi-do, South Korea
Manufacturer	:	BICOM INC.
Address	:	#2F, 7, Yanghyeon-ro 405beon-gil, Jungwon-gu, Seongnam-si, Gyeonggi-do, South Korea
Factory	:	BICOM INC.
Address	:	#2F, 7, Yanghyeon-ro 405beon-gil, Jungwon-gu, Seongnam-si, Gyeonggi-do, South Korea

1.2. Description of Device (EUT)

Product Name	:	Wireless Microphone	
Model No.	:	SIMEON SPREK T	
Trade Mark	:	N.A.	
Test Power Supply	:	AC 240V, 60Hz for adapter/ AC 120V, 60Hz for adapter/ DC 3.7V battery inside	
Test Sample No.	:	S1(Normal Sample), S2(Engineering Sample)	
Product Description	:	Operation Frequency:	903MHz~927MHz
		Modulation Type:	FSK
		Antenna Type:	Shrapnel Antenna
		Antenna Gain(Peak):	0 dBi
Remark: 1)For a more detailed features description, please refer to the manufacturer’s specifications or the User’s Manual.			

1.3. Auxiliary Equipment Used During Test

Adapter	:	Manufacturer: Samsung M/N: ETA-U90CBC S/N: RT6FB17ZS/B-E Input: 100-240V~ 50-60Hz, 0.35A Output: DC 5V, 2A
---------	---	--

1.4. Description of Test Modes

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	CH01
Mode 2	CH13
Mode 3	CH25
Mode 4	Keeping TX+ Charging Mode

For Conducted Emission	
Final Test Mode	Description
Mode 4	Keeping TX+ Charging Mode

For Radiated Emission	
Final Test Mode	Description
Mode 1	CH01
Mode 2	CH13
Mode 3	CH25
Mode 4	Keeping TX+ Charging Mode



1.5. List of channels

Channel	Freq. (MHz)	Channel	Freq. (MHz)
01	903	14	916
02	904	15	917
03	905	16	918
04	906	17	919
05	907	18	920
06	908	19	921
07	909	20	922
08	910	21	923
09	911	22	924
10	912	23	925
11	913	24	926
12	914	25	927
13	915		

Note:

1. The engineering test program was provided and the EUT was programmed to be in continuously transmitting mode.
2. EUT built-in battery-powered, fully-charged battery use of the test battery.

1.6. Description of Test Setup



1.7. Test Equipment List

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	L.I.S.N. Artificial Mains Network	Rohde & Schwarz	ENV216	100055	Nov. 05, 2018	1 Year
2.	EMI Test Receiver	Rohde & Schwarz	ESPI3	101604	Nov. 05, 2018	1 Year
3.	RF Switching Unit	Compliance Direction	RSU-M2	38303	Nov. 05, 2018	1 Year
4.	Spectrum Analysis	Agilent	E4407B	US39390582	Nov. 05, 2018	1 Year
5.	MAX Spectrum Analysis	Agilent	N9020A	MY51170037	Nov. 05, 2018	1 Year
6.	Preamplifier	SKET Electronic	BK1G18G30D	KD17503	Nov. 05, 2018	1 Year
7.	Double Ridged Horn Antenna	Instruments corporation	GTH-0118	351600	Nov. 20, 2018	1 Year
8.	Bilog Broadband Antenna	Schwarzbeck	VULB9163	VULB 9163-289	Nov. 19, 2018	1 Year
9.	Loop Antenna	Schwarzbeck	FMZB1519B	00053	Nov. 20, 2018	1 Year
10.	Horn Antenna	A-INFO	LB-180400-K F	J211060628	Nov. 20, 2018	1 Year
11.	Pre-amplifier	SONOMA	310N	186860	Nov. 05, 2018	1 Year
12.	EMI Test Software EZ-EMC	SHURPLE	N/A	N/A	N/A	N/A
13.	RF Test Control System	YIHENG	YH3000	2017430	Nov. 05, 2018	1 Year
14.	Power Sensor	DAER	RPR3006W	15I00041SN045	Nov. 05, 2018	1 Year
15.	Power Sensor	DAER	RPR3006W	15I00041SN046	Nov. 05, 2018	1 Year
16.	MXA Spectrum Analysis	Agilent	N9020A	MY51170037	Nov. 05, 2018	1 Year
17.	MXG RF Vector Signal Generator	Agilent	N5182A	MY48180656	Nov. 05, 2018	1 Year
18.	Signal Generator	Agilent	E4421B	MY41000743	Nov. 05, 2018	1 Year
19.	DC Power Supply	IVYTECH	IV3605	1804D360510	Apr. 02, 2018	1 Year
20.	Constant Temperature Humidity Chamber	ZHONGJIAN	ZJ-KHWS80B	N/A	Nov. 01, 2018	1 Year

1.8. Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 184111

Shenzhen Anbotech Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No. 184111, July 31, 2017.

ISED-Registration No.: 8058A-1

Shenzhen Anbotech Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (ISED) Innovation, Science and Economic Development Canada. The acceptance letter from the ISED is maintained in our files. Registration 8058A-1, June 13, 2016.

Test Location

Shenzhen Anbotech Compliance Laboratory Limited,
1/F, Building D, Sogood Science and Technology Park, Sanwei community, Hangcheng Street, Bao'an District,
Shenzhen, Guangdong, China.518102

1.9. Measurement Uncertainty

Radiation Uncertainty	:	Ur = 4.1 dB (Horizontal)
		Ur = 4.3 dB (Vertical)
Conduction Uncertainty	:	Uc = 3.4dB

2. Summary of Test Results

Standard Section	Test Item	Result
15.203	Antenna Requirement	PASS
15.207	Conducted Emission	PASS
15.249	Spurious Emission	PASS
15.215(c)	20dB Bandwidth	PASS
15.249(c)	Band Edge	PASS
Remark: "N/A" is an abbreviation for Not Applicable.		


3. Conducted Emission Test

3.1. Test Standard and Limit

Test Standard	FCC Part15 Section 15.207		
Test Limit	Frequency	Maximum RF Line Voltage (dBuV)	
		Quasi-peak Level	Average Level
	150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
	500kHz~5MHz	56	46
	5MHz~30MHz	60	50

Remark: (1) *Decreasing linearly with logarithm of the frequency.
(2) The lower limit shall apply at the transition frequency.

3.2. Test Setup



3.3. Test Procedure

The EUT system is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to FCC ANSI C63.10-2013 on Conducted Emission Measurement.

The bandwidth of test receiver (ESCI) set at 9kHz.


The frequency range from 150kHz to 30MHz is checked.

3.4. Test Data

Please to see the following pages.

Conducted Emission Test Data


Test Site: 1# Shielded Room
Operating Condition: Keeping TX+ Charging Mode
Test Specification: AC 240V, 60Hz for adapter
Comment: Live Line
Tem.: 23.4°C Hum.: 56%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Over Limit (dB)	Detector	Remark
1	0.2260	24.93	19.89	44.82	62.59	-17.77	QP	
2	0.2260	9.76	19.89	29.65	52.59	-22.94	AVG	
3	0.3300	16.65	19.90	36.55	59.45	-22.90	QP	
4	0.3300	5.28	19.90	25.18	49.45	-24.27	AVG	
5	0.4340	3.59	19.95	23.54	47.18	-23.64	AVG	
6	0.6260	15.43	20.02	35.45	56.00	-20.55	QP	
7	0.8460	2.37	20.08	22.45	46.00	-23.55	AVG	
8	1.3980	15.21	20.13	35.34	56.00	-20.66	QP	
9	1.3980	2.38	20.13	22.51	46.00	-23.49	AVG	
10	1.9660	1.56	20.14	21.70	46.00	-24.30	AVG	
11	2.6580	13.57	20.15	33.72	56.00	-22.28	QP	
12	3.8180	14.43	20.18	34.61	56.00	-21.39	QP	

Conducted Emission Test Data


Test Site: 1# Shielded Room
Operating Condition: Keeping TX+ Charging Mode
Test Specification: AC 240V, 60Hz for adapter
Comment: Neutral Line
Tem.: 23.4℃ Hum.: 56%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Over Limit (dB)	Detector	Remark
1	0.1539	29.51	19.90	49.41	65.78	-16.37	QP	
2	0.3100	7.72	19.89	27.61	49.97	-22.36	AVG	
3	0.3379	20.81	19.91	40.72	59.25	-18.53	QP	
4	0.4540	4.42	19.96	24.38	46.80	-22.42	AVG	
5	0.6900	4.10	20.04	24.14	46.00	-21.86	AVG	
6	0.8059	20.24	20.07	40.31	56.00	-15.69	QP	
7	0.9140	19.25	20.10	39.35	56.00	-16.65	QP	
8	1.3220	2.77	20.13	22.90	46.00	-23.10	AVG	
9	1.4500	17.37	20.13	37.50	56.00	-18.50	QP	
10	1.9740	2.19	20.14	22.33	46.00	-23.67	AVG	
11	1.9820	16.17	20.14	36.31	56.00	-19.69	QP	
12	2.5780	0.96	20.15	21.11	46.00	-24.89	AVG	

Conducted Emission Test Data


Test Site: 1# Shielded Room
Operating Condition: Keeping TX+ Charging Mode
Test Specification: AC 120V, 60Hz for adapter
Comment: Live Line
Tem.: 23.4°C Hum.: 56%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Over Limit (dB)	Detector	Remark
1	0.1740	12.68	19.90	32.58	54.76	-22.18	AVG	
2	0.1780	28.22	19.90	48.12	64.57	-16.45	QP	
3	0.4180	3.00	19.94	22.94	47.49	-24.55	AVG	
4	0.4740	14.08	19.97	34.05	56.44	-22.39	QP	
5	0.6020	0.67	20.01	20.68	46.00	-25.32	AVG	
6	0.7220	13.65	20.05	33.70	56.00	-22.30	QP	
7	1.0500	-0.39	20.12	19.73	46.00	-26.27	AVG	
8	1.0940	12.92	20.12	33.04	56.00	-22.96	QP	
9	1.5500	-0.79	20.13	19.34	46.00	-26.66	AVG	
10	2.2060	-1.53	20.14	18.61	46.00	-27.39	AVG	
11	2.8260	11.01	20.16	31.17	56.00	-24.83	QP	
12	4.1940	10.51	20.19	30.70	56.00	-25.30	QP	

Conducted Emission Test Data

Test Site: 1# Shielded Room
Operating Condition: Keeping TX+ Charging Mode
Test Specification: AC 120V, 60Hz for adapter
Comment: Neutral Line
Tem.: 23.4℃ Hum.: 56%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Over Limit (dB)	Detector	Remark
1	0.1740	26.48	19.90	46.38	64.76	-18.38	QP	
2	0.1740	11.17	19.90	31.07	54.76	-23.69	AVG	
3	0.3460	5.32	19.91	25.23	49.06	-23.83	AVG	
4	0.4980	20.17	19.98	40.15	56.03	-15.88	QP	
5	0.6060	3.53	20.01	23.54	46.00	-22.46	AVG	
6	0.8220	16.19	20.07	36.26	56.00	-19.74	QP	
7	1.0940	16.55	20.12	36.67	56.00	-19.33	QP	
8	1.1460	1.89	20.12	22.01	46.00	-23.99	AVG	
9	1.4060	16.39	20.13	36.52	56.00	-19.48	QP	
10	1.4819	0.99	20.13	21.12	46.00	-24.88	AVG	
11	1.9340	0.63	20.14	20.77	46.00	-25.23	AVG	
12	1.9580	14.94	20.14	35.08	56.00	-20.92	QP	

4. Radiation Spurious Emission and Band Edge

4.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.209 and 15.205				
Test Limit	Frequency (MHz)	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz~0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz~88MHz	100	40.0	Quasi-peak	3
	88MHz~216MHz	150	43.5	Quasi-peak	3
	216MHz~960MHz	200	46.0	Quasi-peak	3
	960MHz~1000MHz	500	54.0	Quasi-peak	3
	Above 1000MHz	500	54.0	Average	3
		-	74.0	Peak	3
Remark: (1)The lower limit shall apply at the transition frequency. (2) 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.					

Test Standard	FCC Part15 C Section 15.249					
Test Limit	Fundamental frequency (MHz)	Field Strength	Limit (microvolts/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	902~928	Fundamental	50	94.0	Quasi-peak	3
		Harmonics	500	74.0	Average	3
			-	94.0	Peak	3
Remark: (1) 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.						

4.2. Test Setup




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz

4.3. Test Procedure

For below 1GHz: The EUT is placed on a turntable, which is 0.8m above the ground plane.

For above 1GHz: The EUT is placed on a turntable, which is 1.5m above the ground plane.

The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. Rotated the EUT through three orthogonal axes to determine the maximum emissions, both horizontal and vertical polarization of the antenna are set on test. The EUT is tested in 9*6*6 Chamber. The device is evaluated in xyz orientation.

For the radiated emission test above 1GHz:

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

For 9kHz to 150kHz, Set the spectrum analyzer as:

RBW = 200Hz, VBW =1kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 150kHz to 30MHz, Set the spectrum analyzer as:

RBW = 9KHz, VBW =30kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 30MHz to 1000MHz, Set the spectrum analyzer as:

RBW = 120KHz, VBW =300kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For above 1GHz,Set the spectrum analyzer as:

RBW =1MHz, VBW =1MHz, Detector= Peak, Trace mode= Max hold, Sweep- auto couple.

RBW =1MHz, VBW =10Hz, Detector= Average, Trace mode= Max hold, Sweep- auto couple.

4.4. Test Data

PASS


During the test, Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the X-axis is the worst case.

The test results of 9kHz-30MHz was attenuated more than 20dB below the permissible limits, so the results don't record in the report.

Note: The Low channel which is the worst case, only the worst case is recorded in the report.

Test Results (30~1000MHz)

Job No.: SZAWW181122006-01 Temp.(°C)/Hum.(%RH): 24.2°C/54%RH
Standard: FCC PART 15C Power Source: DC 3.7V battery inside
Test Mode: Keeping TX Mode Polarization: Horizontal



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	92.1388	56.38	-17.40	38.98	43.50	-4.52	QP	300	0	
2	98.1419	46.72	-15.94	30.78	43.50	-12.72	QP	300	54	
3	110.5687	42.73	-15.66	27.07	43.50	-16.43	QP	300	125	
4	159.7844	46.83	-17.88	28.95	43.50	-14.55	QP	300	196	
5	207.1226	45.15	-15.67	29.48	43.50	-14.02	QP	300	254	
6	903.5094	95.26	-3.71	91.55	94.00	-2.45	QP	300	360	

Job No.: SZAWW181122006-01


Temp.(°C)/Hum.(%RH): 24.2°C/54%RH

Standard: FCC PART 15C

Power Source: DC 3.7V battery inside

Test Mode: Keeping TX Mode

Polarization: Vertical



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	38.2120	42.59	-14.34	28.25	40.00	-11.75	QP	300	0	
2	92.1388	47.66	-17.40	30.26	43.50	-13.24	QP	300	74	
3	159.7844	48.38	-17.88	30.50	43.50	-13.00	QP	300	124	
4	208.5803	40.54	-15.63	24.91	43.50	-18.59	QP	300	196	
5	381.2487	38.11	-12.43	25.68	46.00	-20.32	QP	300	251	
6	903.4494	96.16	-3.71	92.45	94.00	-1.55	QP	300	360	

Harmonics Emissions CH01

Frequency	Antenna	Reading	Cable Loss	Ant Factor	Amplifier	Level	Limits	Margin	Det.
(MHz)	Pol.	(dBuV/m)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	Mode
1806.0000	H	49.85	7.39	28.73	26.31	59.66	74	-14.34	PK
1806.0000	H	40.20	7.39	28.73	26.31	50.01	54	-3.99	AV
2709.0000	H	48.50	8.10	29.71	27.01	59.30	74	-14.70	PK
2709.0000	H	37.85	8.10	29.71	27.01	48.65	54	-5.35	AV
3612.0000	H	--	--	--	--	--	--	--	PK
3612.0000	H	--	--	--	--	--	--	--	AV
1806.0000	V	45.14	7.39	28.73	26.31	54.95	74	-19.05	PK
1806.0000	V	38.91	7.39	28.73	26.31	48.72	54	-5.28	AV
2709.0000	V	45.33	8.10	29.71	27.01	56.13	74	-17.87	PK
2709.0000	V	37.33	8.10	29.71	27.01	48.13	54	-5.87	AV
3612.0000	V	--	--	--	--	--	--	--	PK
3612.0000	V	--	--	--	--	--	--	--	AV

CH13

Frequency	Antenna	Reading	Cable Loss	Ant Factor	Amplifier	Level	Limits	Margin	Det.
(MHz)	Pol.	(dBuV/m)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	Mode
1830.0000	H	50.67	7.39	28.73	26.31	60.48	74	-13.52	PK
1830.0000	H	39.50	7.39	28.73	26.31	49.31	54	-4.69	AV
2745.0000	H	48.14	8.10	29.71	27.01	58.94	74	-15.06	PK
2745.0000	H	38.02	8.10	29.71	27.01	48.82	54	-5.18	AV
3660.0000	H	--	--	--	--	--	--	--	PK
3660.0000	H	--	--	--	--	--	--	--	AV
1830.0000	V	46.13	7.39	28.73	26.31	55.94	74	-18.06	PK
1830.0000	V	39.25	7.39	28.73	26.31	49.06	54	-4.94	AV
2745.0000	V	46.03	8.10	29.71	27.01	56.83	74	-17.17	PK
2745.0000	V	37.87	8.10	29.71	27.01	48.67	54	-5.33	AV
3660.0000	V	--	--	--	--	--	--	--	PK
3660.0000	V	--	--	--	--	--	--	--	AV


CH25


Frequency	Antenna	Reading	Cable Loss	Ant Factor	Amplifier	Level	Limits	Margin	Det.
(MHz)	Pol.	(dBuV/m)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	Mode
1854.0000	H	49.92	7.39	28.73	26.31	59.73	74	-14.27	PK
1854.0000	H	39.94	7.39	28.73	26.31	49.75	54	-4.25	AV
2781.0000	H	47.99	8.10	29.71	27.01	58.79	74	-15.21	PK
2781.0000	H	37.68	8.10	29.71	27.01	48.48	54	-5.52	AV
3708.0000	H	--	--	--	--	--	--	--	PK
3708.0000	H	--	--	--	--	--	--	--	AV
1854.0000	V	45.39	7.39	28.73	26.31	55.20	74	-18.80	PK
1854.0000	V	38.32	7.39	28.73	26.31	48.13	54	-5.87	AV
2781.0000	V	46.02	8.10	29.71	27.01	56.82	74	-17.18	PK
2781.0000	V	37.80	8.10	29.71	27.01	48.60	54	-5.40	AV
3708.0000	V	--	--	--	--	--	--	--	PK
3708.0000	V	--	--	--	--	--	--	--	AV

Remark:

1. Level = Reading + Cable Loss+Ant Factor-Amplifier
2. "--" Mark indicated Background Noise Level

Radiated Band Edge:






5. 20dB Bandwidth Test

5.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.249
---------------	-----------------------------

5.2. Test Setup



5.3. Test Procedure


1. Place the EUT on the table and set it in the transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as:
 RBW = 100kHz, VBW $\geq$ 3*RBW = 300kHz,
 Detector= peak
 Trace mode= Max hold.
 Sweep- auto couple.
4. Mark the peak frequency and -20dB (upper and lower) frequency.
5. Repeat until all the rest channels are investigated.

5.4. Test Data


Test Item : 20dB Bandwidth
 Test Voltage : DC 3.7V battery inside
 Test Result : PASS

Test Mode : TX Mode
 Temperature : 24°C
 Humidity : 55%RH


Frequency (MHz)	Bandwidth (kHz)	Result
903	597.9	PASS
915	597.4	PASS
927	599.5	PASS



Test Mode: CH01



Test Mode: CH13



Test Mode: CH25


6. Antenna Requirement

6.1. Test Standard and Requirement

Test Standard	FCC Part15 Section 15.203
Requirement	1) 15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

6.2. Antenna Connected Construction

The antenna is a Shrapnel Antenna which permanently attached, and the best case gain of the antenna is 0 dBi. It complies with the standard requirement.




APPENDIX I -- TEST SETUP PHOTOGRAPH

Photo of Power Line Conducted Emission Test



Photo of Radiation Emission Test





APPENDIX II -- EXTERNAL PHOTOGRAPH













APPENDIX III -- INTERNAL PHOTOGRAPH







----- End of Report -----