MPE ESTIMATION FCC ID: 2AGM8-Q5

1, Limit for General Population/ Uncontrolled Exposures SAR Test Exclusion Thresholds for 100 MHz – 6 GHz and > 50 mm

| MHz | 50 | 60 | 70 | 80 | 90 | 100 | 110 | 120 | 130 | 140 | 150 | 160 | 170 | 180 | 190 | mm |
|------|-----|-----|-----|-----|-----|-----|-----|-----|-----|------|------|------|------|------|------|----|
| 100 | 474 | 481 | 487 | 494 | 501 | 507 | 514 | 521 | 527 | 534 | 541 | 547 | 554 | 561 | 567 | |
| 150 | 387 | 397 | 407 | 417 | 427 | 437 | 447 | 457 | 467 | 477 | 487 | 497 | 507 | 517 | 527 | |
| 300 | 274 | 294 | 314 | 334 | 354 | 374 | 394 | 414 | 434 | 454 | 474 | 494 | 514 | 534 | 554 | |
| 450 | 224 | 254 | 284 | 314 | 344 | 374 | 404 | 434 | 464 | 494 | 524 | 554 | 584 | 614 | 644 | |
| 835 | 164 | 220 | 275 | 331 | 387 | 442 | 498 | 554 | 609 | 665 | 721 | 776 | 832 | 888 | 943 | |
| 900 | 158 | 218 | 278 | 338 | 398 | 458 | 518 | 578 | 638 | 698 | 758 | 818 | 878 | 938 | 998 | |
| 1500 | 122 | 222 | 322 | 422 | 522 | 622 | 722 | 822 | 922 | 1022 | 1122 | 1222 | 1322 | 1422 | 1522 | mW |
| 1900 | 109 | 209 | 309 | 409 | 509 | 609 | 709 | 809 | 909 | 1009 | 1109 | 1209 | 1309 | 1409 | 1509 | |
| 2450 | 96 | 196 | 296 | 396 | 496 | 596 | 696 | 796 | 896 | 996 | 1096 | 1196 | 1296 | 1396 | 1496 | |
| 3600 | 79 | 179 | 279 | 379 | 479 | 579 | 679 | 779 | 879 | 979 | 1079 | 1179 | 1279 | 1379 | 1479 | |
| 5200 | 66 | 166 | 266 | 366 | 466 | 566 | 666 | 766 | 866 | 966 | 1066 | 1166 | 1266 | 1366 | 1466 | |
| 5400 | 65 | 165 | 265 | 365 | 465 | 565 | 665 | 765 | 865 | 965 | 1065 | 1165 | 1265 | 1365 | 1465 | |
| 5800 | 62 | 162 | 262 | 362 | 462 | 562 | 662 | 762 | 862 | 962 | 1062 | 1162 | 1262 | 1362 | 1462 | |

2, Estimation Result

| | Max PK | Tuna Un | Max Tune | | | | |
|----------|------------|--------------|-----------|------------|--------|--|--|
| Mode | Output | Tune Up | Up | Limit (mW) | Result | | |
| | power(dBm) | Power(dBm) | power(mW) | | | | |
| 2.4GWIFI | 16.79 | 16±1(17) | 50.12 | 596 | PASS | | |
| 5.2GWIFI | 14.36 | 14±1(15) | 31.62 | 566 | PASS | | |
| 5.8GWIFI | 17.10 | 16.5±1(17.5) | 56.23 | 562 | PASS | | |

Note: For 100 MHz to 6 GHz and test separation distances > 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following (also illustrated in Appendix B):

- 1) {[Power allowed at numeric threshold for 50 mm in step a)] + [(test separation distance
- 50 mm)·(f(MHz)/150)]} mW, for 100 MHz to 1500 MHz
- 2) {[Power allowed at numeric threshold for 50 mm in step a)] + [(test separation distance –

50mm)·10]} mW, for > 1500 MHz and ≤ 6 GHz

Note: The estimation distance is 10cm

Note: PK Output power= conducted power.

Conducted power see the test report HK2112034714-1E/2E/3E

2.4GWIFI antenna gain=0.56dBi

5GWIFI antenna gain=1.52dBi

when the minimum test separation distance is >10 cm, a distance of 10 cm is applied to determine RF Exposure test exclusion. The max power is 56.23mW which is< 562mW, SAR testing is not required.

----The End-----