



# MPE TEST REPORT

**Applicant** Sengled Co., Ltd.  
**FCC ID** 2AGN8-E1EG7F  
**Product** Sengled Smart Light Switch  
**Brand** sengled  
**Model** E1E-G7F  
**Report No.** R1904A0186-M1  
**Issue Date** May 31, 2019

TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **FCC 47 CFR Part 1 1.1310**. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

*Performed by: Yu Wang*

*Approved by: Guangchang Fan*

---

## TA Technology (Shanghai) Co., Ltd.

No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China

TEL: +86-021-50791141/2/3

FAX: +86-021-50791141/2/3-8000



## Table of Contents

|     |   |    |
|-----|---|----|
| 1   | Test Laboratory.....  | 3  |
| 1.1 | Notes of the Test Report.....                                   | 3  |
| 1.2 | Test facility.....  | 3  |
| 1.3 | Testing Location.....   | 4  |
| 1.4 | Laboratory Environment.....                                     | 4  |
| 2   | Description of Equipment under Test.....                        | 5  |
| 3   | Maximum conducted output power (measured) and antenna Gain..... | 6  |
| 4   | Test Result.....  | 7  |
|     | ANNEX A: The EUT Appearance.....                                | 10 |
|     | A.1 EUT Appearance.....   | 10 |

# 1 Test Laboratory

## 1.1 Notes of the Test Report

This report shall not be reproduced in full or partial, without the written approval of **TA technology (shanghai) co., Ltd.** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above.

## 1.2 Test facility

### **CNAS (accreditation number:L2264)**

TA Technology (Shanghai) Co., Ltd. has obtained the accreditation of China National Accreditation Service for Conformity Assessment (CNAS).

### **FCC (Designation number: CN1179, Test Firm Registration Number: 446626)**

TA Technology (Shanghai) Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements.

### **IC (recognition number is 8510A)**

TA Technology (Shanghai) Co., Ltd. has been listed by industry Canada to perform electromagnetic emission measurement.

### **VCCI (recognition number is C-4595, T-2154, R-4113, G-10766)**

TA Technology (Shanghai) Co., Ltd. has been listed by industry Japan to perform electromagnetic emission measurement.

### **A2LA (Certificate Number: 3857.01)**

TA Technology (Shanghai) Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform electromagnetic emission measurement.



### 1.3 Testing Location

Company: TA Technology (Shanghai) Co., Ltd.  
Address: No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China  
City: Shanghai  
Post code: 201201  
Country: P. R. China  
Contact: Xu Kai  
Telephone: +86-021-50791141/2/3  
Fax: +86-021-50791141/2/3-8000  
Website: <http://www.ta-shanghai.com>  
E-mail: [xukai@ta-shanghai.com](mailto:xukai@ta-shanghai.com)

### 1.4 Laboratory Environment

|   |                           |
|---|---------------------------|
| Temperature   | Min. = 18°C, Max. = 25 °C |
| Relative humidity   | Min. = 30%, Max. = 70%    |
| Ground system resistance  | < 0.5 $\Omega$            |
| Ambient noise is checked and found very low and in compliance with requirement of standards.<br>Reflection of surrounding objects is minimized and in compliance with requirement of standards. |                           |

## 2 Description of Equipment under Test

### Client Information

|                             |  |
|-----------------------------|--|
| <b>Applicant</b>            | Sengled Co., Ltd   |
| <b>Applicant address</b>    | Room 201/15, Building 1, No.498, Guoshoujing Road, Pilot Free Trade Zone, Shanghai, P.R. China |
| <b>Manufacturer</b>         | Sengled Co., Ltd   |
| <b>Manufacturer address</b> | Room 201/15, Building 1, No.498, Guoshoujing Road, Pilot Free Trade Zone, Shanghai, P.R. China |

### General Technologies

|                            |  |
|----------------------------|--|
| <b>Model</b>               | E1E-G7F  |
| <b>IMEI</b>                | /  |
| <b>Hardware Version</b>    | V1   |
| <b>Software Version</b>    | V3   |
| <b>Date of Testing:</b>    | April 23, 2019~ May 7, 2019  |
| <b>EUT Accessory</b>       |  |
| <b>Remote control base</b> | Manufacturer: Leqing City Huapai Electrical Science and Technology Limited Company |

### 3 Maximum conducted output power (measured) and antenna Gain

The numeric gain (G) of the antenna with a gain specified in dB is determined by

Numeric gain (G)= $10^{(\text{antenna gain}/10)}$

| Band   | Maximum Conducted Output Power (dBm) |      | Antenna Gain (dBi) | Numeric gain |
|--------|--------------------------------------|------|--------------------|--------------|
|        | (dBm)                                | (mW) |                    |              |
| Zigbee | 8.00                                 | 6.31 | -1.00              | 0.794        |

## 4 Test Result

According to section 1.1310 of FCC 47 CFR Part 1, limits for maximum permissible exposure (MPE) are as following

TABLE 1 – LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

| Frequency Range<br>(MHz)                                | Electric Field<br>Strength<br>(V/m) | Magnetic Field<br>Strength<br>(A/m) | Power Density<br>(mW/cm <sup>2</sup> ) | Averaging Time<br>(minutes) |
|---|-------------------------------------|-------------------------------------|--|-----------------------------|
| (A) Limits for Occupational/Controlled Exposures        |                                     |                                     |  |                             |
| 0.3-3.0 .....   | 614                                 | 1.63                                | *(100)                                 | 6                           |
| 3-30 .....  | 1842/f                              | 4.89/f                              | *(900/f <sup>2</sup> )                 | 6                           |
| 30-300 .....  | 61.4                                | 0.163                               | 1.0                                    | 6                           |
| 300-1500 .....  |                                     |                                     | f/300                                  | 6                           |
| 1500-100,000 .....                                      |                                     |                                     | 5                                      | 6                           |
| (B) Limits for General Population/Uncontrolled Exposure |                                     |                                     |  |                             |
| 0.3-1.34 .....  | 614                                 | 1.63                                | *(100)                                 | 30                          |
| 1.34-30 .....   | 824/f                               | 2.19/f                              | *(180/f <sup>2</sup> )                 | 30                          |
| 30-300 .....  | 27.5                                | 0.073                               | 0.2                                    | 30                          |
| 300-1500 .....  |                                     |                                     | f/1500                                 | 30                          |
| 1500-100,000 .....                                      |                                     |                                     | 1.0                                    | 30                          |

f = frequency in MHz

\* = Plane-wave equivalent power density

Note1. Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational / controlled limits apply provided he or she is made aware of the potential for exposure.

Note2: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.



The maximum permissible exposure for 300~1500 MHz is  $f/1500$ , for 1500~100,000MHz is 1.0. So

| Band   | The maximum permissible exposure |
|--------|----------------------------------|
| Zigbee | 1.0mW/cm <sup>2</sup>            |

**IMPORTANT NOTE:** To comply with the FCC RF exposure compliance requirements, the antenna(s) used for this transmitter must be installed to provide a separation distance of at least 20 cm from all persons and must not be co-located or operating in conjunction with any other antenna or transmitter. No change to the antenna or the device is permitted. Any change to the antenna or the device could result in the device exceeding the RF exposure requirements and void user's authority to operate the device.





**RF Exposure Calculations:**

The following information provides the minimum separation distance for the highest gain antenna provided. This calculation is based on the conducted power, considering maximum power and antenna gain. The formula shown in KDB 447498 D01 is used in the calculation.

Equation from KDB 447498 D01 General RF Exposure Guidance v06 (10/23/2015) is:

$$S = PG / 4\pi R^2$$

Where: S = power density (in appropriate units, e.g. mW/cm<sup>2</sup>)

P = Time-average maximum tune up procedure (in appropriate units, e.g., mW)

G = the numeric gain of the antenna

R = distance to the center of radiation of the antenna (20 cm = limit for MPE)

| Band  | PG (mW) | Test Result (mW/cm <sup>2</sup> ) | Limit Value (mW/cm <sup>2</sup> ) | The MPE ratio | Conclusion |
|---|---------|-----------------------------------|-----------------------------------|---------------|------------|
| Zigbee  | 5.012   | 0.001                             | 1.000                             | 0.001         | Pass       |
| Note: R = 20cm<br>$\pi = 3.1416$<br>The MPE ratio = Mac Test Result ÷ Limit Value |         |                                   |                                   |               |            |


Note: For transmitters, minimum separation distance is 20cm, even if calculations indicate MPE distance is less.

## ANNEX A: The EUT Appearance

### A.1 EUT Appearance



a: EUT



b: Remote control base

Picture 1 EUT