



## RF Exposure Evaluation Declaration

---

**FCC ID:** 2AGN8-P22N14

**APPLICANT:** Sengled Co., Ltd.


**Application Type:** Certification

**Product:** Solo Pro


**Model No.:** P22-N14

**Brand Name:** Sengled

**FCC Classification:** FCC Part 15 Spread Spectrum Transmitter(DSS)

Reviewed By :   
Manager

( Robin Wu )

Approved By :   
CEO

( Marlin Chen )



The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standards through the calibration of the equipment and evaluated measurement uncertainty herein.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Suzhou) Co., Ltd.

---

## Revision History

Report No.	Version	Description	Issue Date	Note
1608RSU00802	Rev. 01	Initial report	08-23-2016	Valid

## 1. PRODUCT INFORMATION

Product Name	Solo Pro
Model No.	P22-N14
Brand Name	Sengled
Bluetooth Specification	v2.1 + EDR
Operating Frequency	2402~2480MHz
Type of modulation	FHSS
Data Rate	1Mbps(GFSK), 2Mbps(Pi/4 DQPSK), 3Mbps (8DPSK)
Antenna Type	PCB Antenna
Antenna Gain	0.4dBi

## 2. RF Exposure Evaluation

### 2.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

#### LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	f/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	f/1500	6
1500-100,000	--	--	1	30

f= Frequency in MHz

Calculation Formula:  $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$

Where

$P_d$  = power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

G = gain of antenna in linear scale

$\pi$  = 3.1416

r = distance between observation point and center of the radiator in cm

$P_d$  is the limit of MPE, 1mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

## 2.2. Test Result of RF Exposure Evaluation

Product	Solo Pro
Test Item	RF Exposure Evaluation

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 0.4dBi for 2.4GHz in logarithm scale.

### For 2.4G ISM Band:

Test Mode	Frequency Band (MHz)	Maximum Output Power (dBm)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
Bluetooth	2402 ~ 2480	0.444	0.0002	1

### CONCULISON:

Therefore, the Max Power Density at R (20 cm) = 0.0002mW/cm<sup>2</sup> < 1mW/cm<sup>2</sup>.

So the EUT complies with the requirement.

\_\_\_\_\_ The End \_\_\_\_\_