

# FCC RF Test Report

## (U-NII)


**Applicant:** Autel Robotics Co., Ltd.

**Address of Applicant:** 18th Floor, Block C1, Nanshan iPark, No. 1001 Xueyuan Avenue, Nanshan District, Shenzhen, Guangdong, 518055, China

**Equipment Under Test (EUT)**

Product Name: Autel Tracker

Model No.: DFAT-1

Trade Mark: 

**FCC ID:** 2AGNTDFAT240958A





**Applicable Standards:** FCC CFR Title 47 Part 15E (§15.407)

**Date of Sample Receipt:** 06 Sep., 2022

**Date of Test:** 07 Sep., to 28 Sep., 2022

**Date of Report Issued:** 15 Nov., 2022

**Test Result:** PASS

<b>Tested by:</b>		<b>Date:</b>	15 Nov., 2022
<b>Reviewed by:</b>	 	<b>Date:</b>	15 Nov., 2022
<b>Approved by:</b>	 <b>Manager</b>	<b>Date:</b>	15 Nov., 2022

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in above the application standard version. Test results reported herein relate only to the item(s) tested.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

## 1 Version

Version No.	Date	Description
00	29 Sep., 2022	Original
01	15 Nov., 2022	Update page 14

## 2 Contents

Page

Cover Page .....	1
1 Version .....	2
2 Contents .....	3
3 General Information .....	4
3.1 Client Information .....	4
3.2 General Description of E.U.T. ....	4
3.3 Test Mode and Environment .....	5
3.4 Description of Test Auxiliary Equipment .....	5
3.5 Measurement Uncertainty .....	5
3.6 Additions to, Deviations, or Exclusions from the Method .....	5
3.7 Laboratory Facility .....	5
3.8 Laboratory Location .....	5
3.9 Test Instruments List .....	6
4 Measurement Setup and Procedure .....	7
4.1 Test Channel .....	7
4.2 Test Setup .....	8
4.3 Test Procedure .....	10
5 Test Results .....	11
5.1 Summary .....	11
5.1.1 Clause and Data Summary .....	11
5.1.2 Test Limit .....	12
5.2 Antenna requirement .....	14
5.3 AC Power Line Conducted Emission .....	15
5.4 Unwanted Emissions .....	17

### 3 General Information

#### 3.1 Client Information

Applicant:	Autel Robotics Co., Ltd.
Address:	18th Floor, Block C1, Nanshan iPark, No. 1001 Xueyuan Avenue, Nanshan District, Shenzhen, Guangdong, 518055, China
Manufacturer:	Autel Robotics Co., Ltd.
Address:	18th Floor, Block C1, Nanshan iPark, No. 1001 Xueyuan Avenue, Nanshan District, Shenzhen, Guangdong, 518055, China
Factory:	Autel Robotics Co., Ltd. Guangming Branch
Address:	No.701, Jixie Factory, Building 4, Yanxiang Technology Industrial Park, Gaoxin Road, Dongzhou Community, Guangming street, Guangming district, Shenzhen, Guangdong, China

#### 3.2 General Description of E.U.T.

Product Name:	Autel Tracker
Model No.:	DFAT-1
Operation Frequency:	5728.0MHz~5847.0MHz
Channel Numbers:	5728.0MHz~5847.0MHz 120 for 1.4MHz Bandwidth 110 for 10 MHz Bandwidth 102 for 20 MHz Bandwidth
Modulation Technology:	QPSK and 16QAM
Antenna Type:	ANT1: Directional antenna ANT2: Omnidirectional antenna
Antenna Gain:	ANT1: 10.9 dBi (declare by applicant) ANT2: 2.98 dBi (declare by applicant)
Antenna Transmit Mode:	MIMO (2TX, 2RX)
Power Supply:	Rechargeable Li-ion Battery DC22.2V,6550mAh
AC Adapter:	Adapter 1 Model: DF_CHARGER Input: AC100-240V, 50/60Hz, 4.0A Output: 26.4V, 7A Adapter 2 Model: DF_CHARGER Input: AC100-240V, 50/60Hz, 4.0A Output: 26.4V, 7A
Test Sample Condition:	The test samples were provided in good working order with no visible defects.

### 3.3 Test Mode and Environment

<b>Test Mode:</b>	
Transmitting mode:	Keep the EUT in continuous transmitting with modulation
<b>Operating Environment:</b>	
Temperature:	15°C ~ 35°C
Humidity:	20 % ~ 75 % RH
Atmospheric Pressure:	1008 mbar
Voltage:	Nominal: 22.2 Vdc, Extreme: Low 19.0 Vdc, High 25.2 Vdc

### 3.4 Description of Test Auxiliary Equipment

The EUT has been tested as an independent unit.
---

### 3.5 Measurement Uncertainty

Parameter	Expanded Uncertainty (Confidence of 95%(U = 2Uc(y)))
Conducted Emission for LISN (9kHz ~ 150kHz)	±3.11 dB
Conducted Emission for LISN (150kHz ~ 30MHz)	±2.62 dB
Radiated Emission (30MHz ~ 1GHz) (3m SAC)	±4.45 dB
Radiated Emission (1GHz ~ 18GHz) (3m SAC)	±5.34 dB
Radiated Emission (18GHz ~ 40GHz) (3m SAC)	±5.34 dB

*Note: All the measurement uncertainty value were shown with a coverage k=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.*

### 3.6 Additions to, Deviations, or Exclusions from the Method

No
----

### 3.7 Laboratory Facility

<p>The test facility is recognized, certified, or accredited by the following organizations:</p> <ul style="list-style-type: none"> <li>● <b>FCC - Designation No.: CN1211</b> JianYan Testing Group Shenzhen Co., Ltd. has been accredited as a testing laboratory by FCC(Federal Communications Commission). The test firm Registration No. is 727551.</li> <li>● <b>ISED – CAB identifier.: CN0021</b> The 3m Semi-anechoic chamber and 10m Semi-anechoic chamber of JianYan Testing Group Shenzhen Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1.</li> <li>● <b>CNAS - Registration No.: CNAS L15527</b> JianYan Testing Group Shenzhen Co., Ltd. is accredited to ISO/IEC 17025:2017 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L15527.</li> <li>● <b>A2LA - Registration No.: 4346.01</b> This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 General requirements for the competence of testing and calibration laboratories. The test scope can be found as below link: <a href="https://portal.a2la.org/scopepdf/4346-01.pdf">https://portal.a2la.org/scopepdf/4346-01.pdf</a></li> </ul>
--

### 3.8 Laboratory Location

<p>JianYan Testing Group Shenzhen Co., Ltd. Address: No.101, Building 8, Innovation Wisdom Port, No.155 Hongtian Road, Huangpu Community, Xinqiao Street, Bao'an District, Shenzhen, Guangdong, People's Republic of China. Tel: +86-755-23118282, Fax: +86-755-23116366 Email: info-JYTee@lets.com, Website: <a href="http://jyt.lets.com">http://jyt.lets.com</a></p>
---

### 3.9 Test Instruments List

Radiated Emission(3m SAC):					
Test Equipment	Manufacturer	Model No.	Manage No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
3m SAC	ETS	9m*6m*6m	WXJ001-1	04-14-2021	04-13-2024
Loop Antenna	Schwarzbeck	FMZB 1519 B	WXJ002-4	03-07-2022	03-06-2023
BiConiLog Antenna	Schwarzbeck	VULB9163	WXJ002	03-08-2022	03-07-2023
Horn Antenna	Schwarzbeck	BBHA9120D	WXJ002-2	03-08-2022	03-07-2023
Horn Antenna	Schwarzbeck	BBHA9170	WXJ002-5	04-07-2022	04-06-2023
Pre-amplifier (30MHz ~ 1GHz)	Schwarzbeck	BBV9743B	WXJ001-2	01-20-2022	01-19-2023
Pre-amplifier (1GHz ~ 18GHz)	SKET	LNPA_0118G-50	WXJ001-3	01-20-2022	01-19-2023
Pre-amplifier (18GHz ~ 40GHz)	RF System	TRLA-180400G45B	WXJ002-7	03-30-2022	03-29-2023
EMI Test Receiver	Rohde & Schwarz	ESRP7	WXJ003-1	03-05-2022	03-04-2023
Spectrum Analyzer	Rohde & Schwarz	FSP 30	WXJ004	01-20-2022	01-19-2023
Spectrum Analyzer	KEYSIGHT	N9010B	WXJ004-2	10-27-2021	10-26-2022
Coaxial Cable (30MHz ~ 1GHz)	JYTSZ	JYT3M-1G-NN-8M	WXG001-4	01-20-2022	01-19-2023
Coaxial Cable (1GHz ~ 18GHz)	JYTSZ	JYT3M-18G-NN-8M	WXG001-5	01-20-2022	01-19-2023
Coaxial Cable (18GHz ~ 40GHz)	JYTSZ	JYT3M-40G-SS-8M	WXG001-7	01-20-2022	01-19-2023
Band Reject Filter Group	Tonscend	JS0806-F	WXJ089	N/A	
Test Software	Tonscend	TS+	Version: 3.0.0.1		

Conducted Emission:					
Test Equipment	Manufacturer	Model No.	Manage No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
EMI Test Receiver	Rohde & Schwarz	ESR3	WXJ003-2	10-21-2021	10-20-2022
LISN	Schwarzbeck	NSLK 8127	QCJ001-13	02-24-2022	02-23-2023
LISN	Rohde & Schwarz	ESH3-Z5	WXJ005-1	03-30-2022	03-29-2023
LISN Coaxial Cable (9kHz ~ 30MHz)	JYTSZ	JYTCE-1G-NN-2M	WXG003-1	02-24-2022	02-23-2023
RF Switch	TOP PRECISION	RSU0301	WXG003	N/A	
Test Software	AUDIX	E3	Version: 6.110919b		

Conducted Method:					
Test Equipment	Manufacturer	Model No.	Manage No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
Spectrum Analyzer	Keysight	N9010B	WXJ004-3	10-27-2021	10-26-2022
DC Power Supply	Keysight	E3642A	WXJ025-2	N/A	
Temperature Humidity Chamber	ZHONG ZHI	CZ-A-80D	WXJ032-3	03-19-2021	03-18-2023
Power Detector Box	MWRFTTEST	MW100-PSB	WXJ007-4	11-19-2021	11-18-2022
RF Control Unit	MWRFTTEST	MW100-RFCB	WXG006	N/A	
Test Software	MWRFTTEST	MTS 8310	Version: 2.0.0.0		

## 4 Measurement Setup and Procedure

### 4.1 Test Channel

According to ANSI C63.10-2013 chapter 5.6.1 Table 4 requirement, select lowest channel, middle channel, and highest channel in the frequency range in which device operates for testing. The detailed frequency points are as follows:

#### 5.8GHz:

Operation Frequency each of channel for 1.4MHz Bandwidth							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	5728.0MHz	4	5731.0MHz	....	....	120	5847.0MHz
2	5729.0MHz	5	5732.0MHz	61	5788MHz		
3	5730.0MHz	6	5733.0MHz	....	....		

*Note:*

- Channel 1, 61 & 120 selected as Lowest, Middle and Highest channel.

Operation Frequency each of channel for 10MHz Bandwidth							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	5733.0MHz	4	5736.0MHz	....	....	109	5841.0MHz
2	5734.0MHz	5	5737.0MHz	56	5788.0MHz	110	5842.0MHz
3	5735.0MHz	6	5738.0MHz	....	....		

*Note:*

- Channel 1, 56 & 110 selected as Lowest, Middle and Highest channel.


Operation Frequency each of channel for 51 for 20MHz Bandwidth							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	5738.0MHz	4	5741.0MHz	....	....	101	5838.0MHz
2	5739.0MHz	5	5742.0MHz	52	5789.0MHz	102	5839.0MHz
3	5740.0MHz	6	5743.0MHz	....	....		

*Note:*

- Channel 1, 52 & 102 selected as Lowest, Middle and Highest channel.

## 4.2 Test Setup


### 1) Conducted emission measurement:




**Note:** The 0.8 m distance specified between EUT/AE/PSU and AMN/AAN, is applicable only to the EUT being measured. If the device is AE then it shall be >0.8 m.

### 2) Radiated emission measurement:

Below 1GHz (3m SAC)







### 4.3 Test Procedure

Test method	Test step
Conducted emission	<ol style="list-style-type: none"> <li>1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment.</li> <li>2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs).</li> <li>3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.</li> </ol>
Radiated emission	<p><b>For below 1GHz:</b></p> <ol style="list-style-type: none"> <li>1. The EUT was placed on the tabletop of a rotating table 0.8 m the ground at a 3 m semi anechoic chamber. The measurement distance from the EUT to the receiving antenna is 3 m.</li> <li>2. EUT works in each mode of operation that needs to be tested , and having the EUT continuously working, respectively on 3 axis (X, Y &amp; Z) and considered typical configuration to obtain worst position. The highest signal levels relative to the limit shall be determined by rotating the EUT from 0° to 360° and with varying the measurement antenna height between 1 m and 4 m in vertical and horizontal polarizations.</li> <li>3. Open the test software to control the test antenna and test turntable. Perform the test, save the test results, and export the test data.</li> </ol> <p><b>For above 1GHz:</b></p> <ol style="list-style-type: none"> <li>1. The EUT was placed on the tabletop of a rotating table 1.5 m the ground at a 3 m fully anechoic room. The measurement distance from the EUT to the receiving antenna is 3 m.</li> <li>2. EUT works in each mode of operation that needs to be tested , and having the EUT continuously working, respectively on 3 axis (X, Y &amp; Z) and considered typical configuration to obtain worst position. The highest signal levels relative to the limit shall be determined by rotating the EUT from 0° to 360° and with varying the measurement antenna height between 1 m and 4 m in vertical and horizontal polarizations.</li> <li>3. Open the test software to control the test antenna and test turntable. Perform the test, save the test results, and export the test data.</li> </ol>
Conducted test method	<ol style="list-style-type: none"> <li>1. The Wi-Fi antenna port of EUT was connected to the test port of the test system through an RF cable.</li> <li>2. The EUT is keeping in continuous transmission mode and tested in all modulation modes.</li> <li>3. Open the test software, prepare a test plan, and control the system through the software. After the test is completed, the test report is exported through the test software.</li> </ol>

## 5 Test Results

### 5.1 Summary

#### 5.1.1 Clause and Data Summary

Test items	Standard clause	Test data	Result
Antenna Requirement	15.203	See Section 5.2	Pass
AC Power Line Conducted Emission	15.207 15.407 (b)(9)	See Section 5.3	Pass
Duty Cycle	ANSI C63.10-2013	Appendix – 5.8G	Pass
Conducted Peak Output Power Power Spectral Density	15.407 (a)(3)(i)	Appendix – 5.8G	Pass
26dB Emission Bandwidth 99% Occupied Bandwidth	15.407 (a)(12)	Appendix – 5.8G	Pass
6dB Emission Bandwidth	15.407 (e)	Appendix – 5.8G	Pass
Unwanted Emissions	15.205 15.209 15.407 (b) (4), (9), (10)	See Section 5.4	Pass
Frequency Stability	15.407 (g)	Appendix – 5.8G	Pass
<b>Remark:</b> 1. Pass: The EUT complies with the essential requirements in the standard. 2. N/A: Not Applicable. 3. The cable insertion loss used by “RF Output Power” and other conduction measurement items is 1.0dB (provided by the customer).			
<b>Test Method:</b>	ANSI C63.10-2013 KDB 789033 D02 General U-NII Test Procedures New Rules v02r01		

### 5.1.2 Test Limit

Test items	Limit															
AC Power Line Conducted Emission	<table border="1"> <thead> <tr> <th data-bbox="603 280 898 342">Frequency (MHz)</th> <th colspan="2" data-bbox="898 280 1437 315">Limit (dBµV)</th> </tr> <tr> <td></td> <th data-bbox="898 315 1171 342">Quasi-Peak</th> <th data-bbox="1171 315 1437 342">Average</th> </tr> </thead> <tbody> <tr> <td data-bbox="603 342 898 371">0.15 – 0.5</td> <td data-bbox="898 342 1171 371">66 to 56 <small>Note 1</small></td> <td data-bbox="1171 342 1437 371">56 to 46 <small>Note 1</small></td> </tr> <tr> <td data-bbox="603 371 898 400">0.5 – 5</td> <td data-bbox="898 371 1171 400">56</td> <td data-bbox="1171 371 1437 400">46</td> </tr> <tr> <td data-bbox="603 400 898 430">5 – 30</td> <td data-bbox="898 400 1171 430">60</td> <td data-bbox="1171 400 1437 430">50</td> </tr> </tbody> </table> <p data-bbox="614 439 1313 463"><b>Note 1:</b> The limit level in dBµV decreases linearly with the logarithm of frequency.</p> <p data-bbox="614 465 1169 490"><b>Note 2:</b> The more stringent limit applies at transition frequencies.</p>	Frequency (MHz)	Limit (dBµV)			Quasi-Peak	Average	0.15 – 0.5	66 to 56 <small>Note 1</small>	56 to 46 <small>Note 1</small>	0.5 – 5	56	46	5 – 30	60	50
Frequency (MHz)	Limit (dBµV)															
	Quasi-Peak	Average														
0.15 – 0.5	66 to 56 <small>Note 1</small>	56 to 46 <small>Note 1</small>														
0.5 – 5	56	46														
5 – 30	60	50														
Conducted Peak Output Power  Power Spectral Density	<p data-bbox="577 512 963 542"><b>For the band 5.725-5.895 GHz:</b></p> <p data-bbox="577 551 1473 1055">For the band 5.725-5.850 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, Fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.</p>															
26dB Emission Bandwidth 99% Occupied Bandwidth	N/A															
6dB Emission Bandwidth	Within the 5.725-5.850 GHz and 5.850-5.895 GHz bands, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.															


<p>Unwanted Emissions</p>	<p>(1) <b>For transmitters operating solely in the 5.725-5.850 GHz band:</b> All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.</p> <p>(2) Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in § 15.209. The provisions of § 15.205 apply to intentional radiators operating under this section:</p> <table border="1" data-bbox="582 692 1455 1059"> <thead> <tr> <th rowspan="2">Frequency (MHz)</th> <th colspan="2">Limit (dBµV/m)</th> <th rowspan="2">Detector</th> </tr> <tr> <th>@ 3m</th> <th>@ 10m</th> </tr> </thead> <tbody> <tr> <td>30 – 88</td> <td>40.0</td> <td>30.0</td> <td>Quasi-peak</td> </tr> <tr> <td>88 – 216</td> <td>43.5</td> <td>33.5</td> <td>Quasi-peak</td> </tr> <tr> <td>216 – 960</td> <td>46.0</td> <td>36.0</td> <td>Quasi-peak</td> </tr> <tr> <td>960 – 1000</td> <td>54.0</td> <td>44.0</td> <td>Quasi-peak</td> </tr> </tbody> </table> <p><b>Note:</b> The more stringent limit applies at transition frequencies.</p> <table border="1" data-bbox="582 920 1455 1025"> <thead> <tr> <th rowspan="2">Frequency</th> <th colspan="2">Limit (dBµV/m) @ 3m</th> </tr> <tr> <th>Average</th> <th>Peake</th> </tr> </thead> <tbody> <tr> <td>Above 1 GHz</td> <td>54.0</td> <td>74.0</td> </tr> </tbody> </table> <p><b>Note:</b> The measurement bandwidth shall be 1 MHz or greater.</p>	Frequency (MHz)	Limit (dBµV/m)		Detector	@ 3m	@ 10m	30 – 88	40.0	30.0	Quasi-peak	88 – 216	43.5	33.5	Quasi-peak	216 – 960	46.0	36.0	Quasi-peak	960 – 1000	54.0	44.0	Quasi-peak	Frequency	Limit (dBµV/m) @ 3m		Average	Peake	Above 1 GHz	54.0	74.0
Frequency (MHz)	Limit (dBµV/m)		Detector																												
	@ 3m	@ 10m																													
30 – 88	40.0	30.0	Quasi-peak																												
88 – 216	43.5	33.5	Quasi-peak																												
216 – 960	46.0	36.0	Quasi-peak																												
960 – 1000	54.0	44.0	Quasi-peak																												
Frequency	Limit (dBµV/m) @ 3m																														
	Average	Peake																													
Above 1 GHz	54.0	74.0																													
<p>Frequency Stability</p>	<p>Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the users manual.</p>																														

## 5.2 Antenna requirement

<b>Standard requirement:</b>	FCC Part 15 C Section 15.203
<p>15.203 requirement:            An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</p>	
<b>E.U.T Antenna:</b>	
<p>The antenna 1 is an directional antenna, antenna 2 is an directional antenna antenna, the best case gain of the antenna1 is 10.9 dBi and the best case gain of the antenna2 is 2.98 dBi. See product internal photos for details.            Note: <i>Unequal antenna gains, with equal transmit powers. The transmit signals are correlated, then</i>            Directional gain = <math>10 \log[(10^{G_1/20} + 10^{G_2/20})^2 / N_{ant}]</math>; So Directional gain = 10.82dBi.</p>	

### 5.3 AC Power Line Conducted Emission

Product name:	Autel Tracker	Product model:	DFAT-1
Test by:	Mike	Test mode:	5.8G mode
Test frequency:	150 kHz ~ 30 MHz	Phase:	Line
Test voltage:	AC 120 V/60 Hz		



Trace: 19


	Freq	Read Level	LISN Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.162	32.91	0.04	0.01	32.96	65.34	-32.38	QP
2	0.194	29.36	0.05	0.03	29.44	63.84	-34.40	QP
3	0.471	8.15	0.05	0.03	8.23	46.49	-38.26	Average
4	0.471	31.58	0.05	0.03	31.66	56.49	-24.83	QP
5	9.603	31.67	0.21	0.12	32.00	50.00	-18.00	Average
6	9.603	44.58	0.21	0.12	44.91	60.00	-15.09	QP
7	14.672	18.62	0.29	0.13	19.04	50.00	-30.96	Average
8	16.661	29.95	0.31	0.16	30.42	60.00	-29.58	QP
9	19.950	12.83	0.34	0.19	13.36	50.00	-36.64	Average
10	22.775	15.43	0.36	0.16	15.95	50.00	-34.05	Average
11	26.699	12.34	0.39	0.20	12.93	50.00	-37.07	Average
12	26.699	28.47	0.39	0.20	29.06	60.00	-30.94	QP

**Remark:**

1. Level = Read level + LISN Factor + Cable Loss.



<b>Product name:</b>	Autel Tracker	<b>Product model:</b>	DFAT-1
<b>Test by:</b>	Mike	<b>Test mode:</b>	5.8G mode
<b>Test frequency:</b>	150 kHz ~ 30 MHz	<b>Phase:</b>	Neutral
<b>Test voltage:</b>	AC 120 V/60 Hz		



	Read Freq	Read Level	LISN Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.158	7.93	0.06	0.01	8.00	55.56	-47.56	Average
2	0.158	37.24	0.06	0.01	37.31	65.56	-28.25	QP
3	0.219	27.85	0.05	0.03	27.93	62.88	-34.95	QP
4	0.471	32.01	0.04	0.03	32.08	56.49	-24.41	QP
5	0.474	7.86	0.04	0.03	7.93	46.45	-38.52	Average
6	9.352	31.99	0.20	0.12	32.31	50.00	-17.69	Average
7	9.552	43.67	0.20	0.12	43.99	60.00	-16.01	QP
8	13.989	16.36	0.26	0.12	16.74	50.00	-33.26	Average
9	15.970	16.19	0.28	0.16	16.63	50.00	-33.37	Average
10	16.750	30.58	0.29	0.16	31.03	60.00	-28.97	QP
11	29.371	12.90	0.45	0.21	13.56	50.00	-36.44	Average
12	29.371	30.33	0.45	0.21	30.99	60.00	-29.01	QP

**Remark:**


1. Level = Read level + LISN Factor + Cable Loss.



### 5.4 Unwanted Emissions

Below 1GHz:

<b>Product Name:</b>	Autel Tracker	<b>Product Model:</b>	DFAT-1
<b>Test By:</b>	Mike	<b>Test mode:</b>	5.8G mode
<b>Test Frequency:</b>	30 MHz ~ 1 GHz	<b>Polarization:</b>	Vertical
<b>Test Voltage:</b>	AC 120/60Hz		




Suspected Data List								
NO.	Freq. [MHz]	Reading[dBµV/m]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Trace	Polarity
1	54.9315	47.87	34.68	-13.19	40.00	5.32	PK	Vertical
2	84.9075	53.94	36.32	-17.62	40.00	3.68	PK	Vertical
3	94.8995	52.61	37.28	-15.33	43.50	6.22	PK	Vertical
4	104.988	53.39	38.91	-14.48	43.50	4.59	PK	Vertical
5	124.972	58.56	41.03	-17.53	43.50	2.47	PK	Vertical
6	134.964	58.94	40.73	-18.21	43.50	2.77	PK	Vertical

**Remark:**

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).

<b>Product Name:</b>	Autel Tracker	<b>Product Model:</b>	DFAT-1
<b>Test By:</b>	Mike	<b>Test mode:</b>	5.8G mode
<b>Test Frequency:</b>	30 MHz ~ 1 GHz	<b>Polarization:</b>	Horizontal
<b>Test Voltage:</b>	AC 120/60Hz		



Suspected Data List								
NO.	Freq. [MHz]	Reading[dBµV/m]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Trace	Polarity
1	134.964	50.99	32.78	-18.21	43.50	10.72	PK	Horizontal
2	174.932	50.26	32.89	-17.37	43.50	10.61	PK	Horizontal
3	191.909	47.57	31.83	-15.74	43.50	11.67	PK	Horizontal
4	216.161	49.59	34.75	-14.84	46.00	11.25	PK	Horizontal
5	236.630	54.50	40.17	-14.33	46.00	5.83	PK	Horizontal
6	306.186	49.94	37.08	-12.86	46.00	8.92	PK	Horizontal

**Remark:**

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).

**Above 1GHz**

5.8G-1.4M-QPSK						
Test channel: Lowest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
5650.00	45.61	17.02	62.63	68.20	5.57	Vertical
5700.00	45.18	17.13	62.31	105.20	42.89	Vertical
5720.00	45.52	17.21	62.73	110.80	48.07	Vertical
5725.00	59.38	17.23	76.61	122.20	45.59	Vertical
11476.00	53.19	7.21	60.40	74.00	13.60	Vertical
5650.00	46.02	17.02	63.04	68.20	5.16	Horizontal
5700.00	44.92	17.13	62.05	105.20	43.15	Horizontal
5720.00	44.99	17.21	62.20	110.80	48.60	Horizontal
5725.00	48.74	17.23	65.97	122.20	56.23	Horizontal
11476.00	51.81	7.21	59.02	74.00	14.98	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
11476.00	43.69	7.21	50.90	54.00	3.10	Vertical
11476.00	43.63	7.21	50.84	54.00	3.16	Horizontal
Test channel: Highest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
5850.00	52.23	17.55	69.78	122.20	52.42	Vertical
5855.00	45.80	17.55	63.35	110.80	47.45	Vertical
5875.00	43.40	17.57	60.97	105.20	44.23	Vertical
5925.00	44.40	17.37	61.77	68.20	6.43	Vertical
11678.00	53.26	7.09	60.35	74.00	13.65	Vertical
5850.00	44.83	17.55	62.38	122.20	59.82	Horizontal
5855.00	44.70	17.55	62.25	110.80	48.55	Horizontal
5875.00	44.55	17.57	62.12	105.20	43.08	Horizontal
5925.00	45.61	17.37	62.98	68.20	5.22	Horizontal
11678.00	51.11	7.09	58.20	74.00	15.80	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
11678.00	43.26	7.09	50.35	54.00	3.65	Vertical
11678.00	43.17	7.09	50.26	54.00	3.74	Horizontal
<b>Remark:</b>						
1. Level = Reading + Factor.						
2. Test Frequency up to 40GHz, and the emission levels of other frequencies are lower than the limit 20dB, not show in test report.						

5.8G-1.4M-16QAM						
Test channel: Lowest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
5650.00	45.77	17.02	62.79	68.20	5.41	Vertical
5700.00	45.55	17.13	62.68	105.20	42.52	Vertical
5720.00	45.48	17.21	62.69	110.80	48.11	Vertical
5725.00	61.13	17.23	78.36	122.20	43.84	Vertical
11476.00	53.26	7.21	60.47	74.00	13.53	Vertical
5650.00	45.51	17.02	62.53	68.20	5.67	Horizontal
5700.00	45.75	17.13	62.88	105.20	42.32	Horizontal
5720.00	45.15	17.21	62.36	110.80	48.44	Horizontal
5725.00	47.54	17.23	64.77	122.20	57.43	Horizontal
11476.00	51.17	7.21	58.38	74.00	15.62	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
11476.00	43.19	7.21	50.40	54.00	3.60	Vertical
11476.00	43.56	7.21	50.77	54.00	3.23	Horizontal
Test channel: Highest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
5850.00	50.81	17.55	68.36	122.20	53.84	Vertical
5855.00	45.45	17.55	63.00	110.80	47.80	Vertical
5875.00	44.75	17.57	62.32	105.20	42.88	Vertical
5925.00	44.16	17.37	61.53	68.20	6.67	Vertical
11678.00	53.24	7.09	60.33	74.00	13.67	Vertical
5850.00	44.82	17.55	62.37	122.20	59.83	Horizontal
5855.00	44.53	17.55	62.08	110.80	48.72	Horizontal
5875.00	44.50	17.57	62.07	105.20	43.13	Horizontal
5925.00	44.40	17.37	61.77	68.20	6.43	Horizontal
11678.00	51.30	7.09	58.39	74.00	15.61	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
11678.00	43.11	7.09	50.20	54.00	3.80	Vertical
11678.00	42.95	7.09	50.04	54.00	3.96	Horizontal
<b>Remark:</b>						
1. Level = Reading + Factor.						
2. Test Frequency up to 40GHz, and the emission levels of other frequencies are lower than the limit 20dB, not show in test report.						

5.8G-10M-QPSK						
Test channel: Lowest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dB $\mu$ V)	Factor (dB)	Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Polarization
5650.00	41.80	17.02	58.82	68.20	9.38	Vertical
5700.00	41.09	17.13	58.22	105.20	46.98	Vertical
5720.00	68.24	17.21	85.45	110.80	25.35	Vertical
5725.00	77.28	17.23	94.51	122.20	27.69	Vertical
11476.00	53.19	7.21	60.40	74.00	13.60	Vertical
5650.00	39.38	17.02	56.40	68.20	11.80	Horizontal
5700.00	39.58	17.13	56.71	105.20	48.49	Horizontal
5720.00	54.34	17.21	71.55	110.80	39.25	Horizontal
5725.00	63.43	17.23	80.66	122.20	41.54	Horizontal
11476.00	50.95	7.21	58.16	74.00	15.84	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dB $\mu$ V)	Factor (dB)	Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Polarization
11476.00	43.09	7.21	50.30	54.00	3.70	Vertical
11476.00	42.67	7.21	49.88	54.00	4.12	Horizontal
Test channel: Highest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dB $\mu$ V)	Factor (dB)	Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Polarization
5850.00	68.26	17.55	85.81	122.20	36.39	Vertical
5855.00	58.89	17.55	76.44	110.80	34.36	Vertical
5875.00	39.09	17.57	56.66	105.20	48.54	Vertical
5925.00	38.61	17.37	55.98	68.20	12.22	Vertical
11678.00	53.46	7.09	60.55	74.00	13.45	Vertical
5850.00	55.09	17.55	72.64	122.20	49.56	Horizontal
5855.00	46.16	17.55	63.71	110.80	47.09	Horizontal
5875.00	38.17	17.57	55.74	105.20	49.46	Horizontal
5925.00	38.86	17.37	56.23	68.20	11.97	Horizontal
11678.00	52.19	7.09	59.28	74.00	14.72	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dB $\mu$ V)	Factor (dB)	Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Polarization
11678.00	43.52	7.09	50.61	54.00	3.39	Vertical
11678.00	43.21	7.09	50.30	54.00	3.70	Horizontal
<b>Remark:</b>						
1. Level = Reading + Factor.						
2. Test Frequency up to 40GHz, and the emission levels of other frequencies are lower than the limit 20dB, not show in test report.						

5.8G-10M-16QAM						
Test channel: Lowest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
5650.00	41.29	17.02	58.31	68.20	9.89	Vertical
5700.00	42.18	17.13	59.31	105.20	45.89	Vertical
5720.00	67.74	17.21	84.95	110.80	25.85	Vertical
5725.00	77.05	17.23	94.28	122.20	27.92	Vertical
11476.00	53.06	7.21	60.27	74.00	13.73	Vertical
5650.00	40.15	17.02	57.17	68.20	11.03	Horizontal
5700.00	39.81	17.13	56.94	105.20	48.26	Horizontal
5720.00	54.09	17.21	71.30	110.80	39.50	Horizontal
5725.00	64.05	17.23	81.28	122.20	40.92	Horizontal
11476.00	51.28	7.21	58.49	74.00	15.51	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
11476.00	43.66	7.21	50.87	54.00	3.13	Vertical
11476.00	42.77	7.21	49.98	54.00	4.02	Horizontal
Test channel: Highest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
5850.00	68.65	17.55	86.20	122.20	36.00	Vertical
5855.00	57.38	17.55	74.93	110.80	35.87	Vertical
5875.00	38.73	17.57	56.30	105.20	48.90	Vertical
5925.00	38.69	17.37	56.06	68.20	12.14	Vertical
11678.00	53.26	7.09	60.35	74.00	13.65	Vertical
5850.00	54.62	17.55	72.17	122.20	50.03	Horizontal
5855.00	45.11	17.55	62.66	110.80	48.14	Horizontal
5875.00	39.98	17.57	57.55	105.20	47.65	Horizontal
5925.00	39.03	17.37	56.40	68.20	11.80	Horizontal
11678.00	52.49	7.09	59.58	74.00	14.42	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
11678.00	43.49	7.09	50.58	54.00	3.42	Vertical
11678.00	42.58	7.09	49.67	54.00	4.33	Horizontal
<b>Remark:</b>						
1. Level = Reading + Factor.						
2. Test Frequency up to 40GHz, and the emission levels of other frequencies are lower than the limit 20dB, not show in test report.						

5.8G-20M-QPSK						
Test channel: Lowest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
5650.00	39.80	17.02	56.82	68.20	11.38	Vertical
5700.00	50.99	17.13	68.12	105.20	37.08	Vertical
5720.00	71.44	17.21	88.65	110.80	22.15	Vertical
5725.00	73.62	17.23	90.85	122.20	31.35	Vertical
11476.00	53.26	7.21	60.47	74.00	13.53	Vertical
5650.00	39.31	17.02	56.33	68.20	11.87	Horizontal
5700.00	41.04	17.13	58.17	105.20	47.03	Horizontal
5720.00	57.54	17.21	74.75	110.80	36.05	Horizontal
5725.00	58.61	17.23	75.84	122.20	46.36	Horizontal
11476.00	51.24	7.21	58.45	74.00	15.55	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
11476.00	43.12	7.21	50.33	54.00	3.67	Vertical
11476.00	42.56	7.21	49.77	54.00	4.23	Horizontal
Test channel: Highest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
5850.00	67.49	17.55	85.04	122.20	37.16	Vertical
5855.00	64.69	17.55	82.24	110.80	28.56	Vertical
5875.00	42.08	17.57	59.65	105.20	45.55	Vertical
5925.00	38.93	17.37	56.30	68.20	11.90	Vertical
11678.00	53.15	7.09	60.24	74.00	13.76	Vertical
5850.00	54.68	17.55	72.23	122.20	49.97	Horizontal
5855.00	51.27	17.55	68.82	110.80	41.98	Horizontal
5875.00	39.05	17.57	56.62	105.20	48.58	Horizontal
5925.00	39.10	17.37	56.47	68.20	11.73	Horizontal
11678.00	51.35	7.09	58.44	74.00	15.56	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
11678.00	42.98	7.09	50.07	54.00	3.93	Vertical
11678.00	42.68	7.09	49.77	54.00	4.23	Horizontal
<b>Remark:</b>						
1. Level = Reading + Factor.						
2. Test Frequency up to 40GHz, and the emission levels of other frequencies are lower than the limit 20dB, not show in test report.						

5.8G-20M-16QAM						
Test channel: Lowest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
5650.00	40.24	17.02	57.26	68.20	10.94	Vertical
5700.00	50.86	17.13	67.99	105.20	37.21	Vertical
5720.00	71.15	17.21	88.36	110.80	22.44	Vertical
5725.00	74.76	17.23	91.99	122.20	30.21	Vertical
11476.00	53.33	7.21	60.54	74.00	13.46	Vertical
5650.00	40.22	17.02	57.24	68.20	10.96	Horizontal
5700.00	39.92	17.13	57.05	105.20	48.15	Horizontal
5720.00	56.28	17.21	73.49	110.80	37.31	Horizontal
5725.00	60.64	17.23	77.87	122.20	44.33	Horizontal
11476.00	51.08	7.21	58.29	74.00	15.71	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
11476.00	43.08	7.21	50.29	54.00	3.71	Vertical
11476.00	42.62	7.21	49.83	54.00	4.17	Horizontal
Test channel: Highest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
5850.00	67.66	17.55	85.21	122.20	36.99	Vertical
5855.00	64.88	17.55	82.43	110.80	28.37	Vertical
5875.00	44.10	17.57	61.67	105.20	43.53	Vertical
5925.00	38.83	17.37	56.20	68.20	12.00	Vertical
11678.00	50.26	7.09	57.35	74.00	16.65	Vertical
5850.00	54.88	17.55	72.43	122.20	49.77	Horizontal
5855.00	51.32	17.55	68.87	110.80	41.93	Horizontal
5875.00	38.65	17.57	56.22	105.20	48.98	Horizontal
5925.00	39.56	17.37	56.93	68.20	11.27	Horizontal
11678.00	52.69	7.09	59.78	74.00	14.22	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
11678.00	43.17	7.09	50.26	54.00	3.74	Vertical
11678.00	42.59	7.09	49.68	54.00	4.32	Horizontal
<b>Remark:</b>						
1. Level = Reading + Factor.						
2. Test Frequency up to 40GHz, and the emission levels of other frequencies are lower than the limit 20dB, not show in test report.						

-----End of report-----