

# TEST REPORT

**Application No.:** SHEM2007005982CR  
**FCC ID:** 2AGOFRC421A  
**Applicant:** HCS (Suzhou) Limited  
**Address of Applicant:** 19F-20F, Building B-3rd, No.209 Zhuyuan Road, New District, Suzhou, 215011, China  
**Factory:** WUJIANG CENTURY BILLION ELECTRONIC TECHNOLOGY CO., LTD  
**Address of Factory:** No.149 West Tun Cun Road Tongli Town Wujiang Suzhou Jiangsu People's Republic of China 215216

**Equipment Under Test (EUT):**

**EUT Name:** Remote Control  
**Model No.:** RC4213801/02BR, RC4213401/02BR, RC4213402/02BR, RC4213403/02BR, Babylon RCU, RC421XXXX/XXR, RC421XXXX/XXBR  
 ("X"=0-9."B"means packed with battery) ☐

☐ Please refer to section 2 of this report which indicates which model was actually tested and which were electrically identical.

**Standard(s) :** 47 CFR Part 15, Subpart B

**Date of Receipt:** 2020-07-20

**Date of Test:** 2020-09-16 to 2020-11-26

**Date of Issue:** 2020-11-26

|                     |              |
|---------------------|--------------|
| <b>Test Result:</b> | <b>Pass*</b> |
|---------------------|--------------|

\* In the configuration tested, the EUT complied with the standards specified above.

*Parlam Zhan*



Parlam Zhan  
E&E Section Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
**Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com**

| Revision Record |             |            |        |
|-----------------|-------------|------------|--------|
| Version         | Description | Date       | Remark |
| 00              | Original    | 2020-11-26 | /      |
|                 |             |            |        |
|                 |             |            |        |

|                          |  |  |  |
|--------------------------|--|--|--|
| Authorized for issue by: |  |  |  |
|                          |  |   |  |
|                          |  | <hr/> Bill Wu / Project Engineer   |  |
|                          |  |  |  |
|                          |  | <hr/> Parlam Zhan / Reviewer   |  |

## 2 Test Summary

| Emission Part                   |                           |                 |             |        |
|---------------------------------|---------------------------|-----------------|-------------|--------|
| Item                            | Standard                  | Method          | Requirement | Result |
| Radiated Emissions (30MHz-1GHz) | 47 CFR Part 15, Subpart B | ANSI C63.4:2014 | Class B     | Pass   |
| Radiated Emissions (above 1GHz) | 47 CFR Part 15, Subpart B | ANSI C63.4:2014 | Class B     | Pass   |

| InternalSource     | UpperFrequency   |
|--------------------|--|
| Below 1.705MHz     | 30MHz  |
| 1.705MHz to 108MHz | 1GHz   |
| 108MHz to 500MHz   | 2GHz   |
| 500MHz to 1GHz     | 5GHz   |
| Above 1GHz         | 5th harmonic of the highest frequency or 40GHz, whichever is lower |

### Declaration of EUT Family Grouping:

Note: There are series models mentioned in this report, and they are the similar in electrical and electronic characters. Only the model RC4213403/02BR was tested since their differences were the model number , the cosmetic (color /painting/printed) and keys number.

### 3 Contents

|   | Page |
|---|------|
| 1 COVER PAGE.....                               | 1    |
| 2 TEST SUMMARY .....                            | 3    |
| 3 CONTENTS.....                                 | 4    |
| 4 GENERAL INFORMATION.....                      | 5    |
| 4.1 DETAILS OF E.U.T. ....                      | 5    |
| 4.2 DESCRIPTION OF SUPPORT UNITS .....          | 5    |
| 4.3 MEASUREMENT UNCERTAINTY.....                | 5    |
| 4.4 TEST LOCATION.....                          | 6    |
| 4.5 TEST FACILITY.....                          | 6    |
| 4.6 DEVIATION FROM STANDARDS .....              | 6    |
| 4.7 ABNORMALITIES FROM STANDARD CONDITIONS..... | 6    |
| 5 EQUIPMENT LIST.....                           | 7    |
| 6 EMISSION TEST RESULTS .....                   | 8    |
| 6.1 RADIATED EMISSIONS (30MHZ-1GHZ) .....       | 8    |
| 6.2 RADIATED EMISSIONS (ABOVE 1GHZ) .....       | 11   |

## 4 General Information

### 4.1 Details of E.U.T.

Power supply: DC 3.0V By 2\*AAA size batteries

Test voltage: DC 3.0V

### 4.2 Description of Support Units

| Description | Manufacturer | Model No. | Serial No. |
|-------------|--------------|-----------|------------|
| Laptop      | Lenovo       | L440      | /          |
| Dongle      | CSR          | /         | /          |
| Gateway     | HCS          | /         | /          |

### 4.3 Measurement Uncertainty

| No. | Item   | Measurement Uncertainty  |
|-----|--|--------------------------|
| 1   | Conducted Emission at mains port using AMN             | 2.6dB (9kHz to 150kHz)   |
|     |  | 2.4dB (150kHz to 30MHz)  |
| 2   | Conducted Emission at mains port using VP              | 1.8 dB (9kHz to 30MHz)   |
| 3   | Conducted Emission at telecommunication port using AAN | 4.2 dB (150kHz to 30MHz) |
| 4   | Radiated Power   | 3.2dB                    |
| 5   | Radiated Emission                                      | 4.5dB (30MHz-1GHz)       |
|     |  | 5.1dB (1GHz-6GHz)        |
|     |  | 5.4dB (6GHz-18GHz)       |
| 6   | Radiated Disturbance (disturbance current in a LLAS)   | 2.4dB (9kHz to 30MHz)    |

Note: The measurement uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

#### 4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. E&E Lab

588 West Jindu Road, Xinqiao, Songjiang, 201612 Shanghai, China

Tel: +86 21 6191 5666

Fax: +86 21 6191 5678

No tests were sub-contracted.

#### 4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L0599)**

CNAS has accredited SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. to ISO/IEC 17025:2017 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **NVLAP (LAB CODE: 201034-0)**

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP).

- **FCC (Designation Number: CN5033)**

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been recognized as an accredited testing laboratory.

- **ISED (CAB Identifier: CN0020)**

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. EMC Laboratory has been recognized by Innovation, Science and Economic Development Canada (ISED) as an accredited testing laboratory.

- **VCCI (Member No.: 3061)**

The 3m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-13868, C-14336, T-12221, G-10830 respectively.

#### 4.6 Deviation from Standards

None

#### 4.7 Abnormalities from Standard Conditions

None

## 5 Equipment List

| <b>Radiated Emissions (30MHz-1GHz)</b> |                     |                   |                     |                 |                     |
|--|---------------------|-------------------|---------------------|-----------------|---------------------|
| <b>Equipment</b>                       | <b>Manufacturer</b> | <b>Model No</b>   | <b>Inventory No</b> | <b>Cal Date</b> | <b>Cal Due Date</b> |
| EMI test receiver                      | Rohde & Schwarz     | ESU40             | SHEM051-1           | 2019-12-20      | 2020-12-19          |
| CONTROLLER                             | INNCO               | CO200             | SHEM047-1           | N/A             | N/A                 |
| ANTENNA MAST                           | INNCO               | MA400-EP          | SHEM047-2           | N/A             | N/A                 |
| TURN DEVICE                            | INNCO               | DE 3600-RH        | SHEM047-3           | N/A             | N/A                 |
| Broadband UHF-VHF ANTENNA              | SCHWARZBECK         | VULB9168          | SHEM048-1           | 2019-10-14      | 2021-10-13          |
| Semi/Fully Anechoic                    | ST                  | 11*6*6M           | SHEM078-2           | 2020-05-25      | 2023-05-24          |
| Low Amplifier                          | CLAVIIO             | BDLNA-0001-412010 | SHEM164-1           | 2020-08-13      | 2021-08-12          |

| <b>Radiated Emissions (above 1GHz)</b> |                     |                      |                     |                 |                     |
|--|---------------------|----------------------|---------------------|-----------------|---------------------|
| <b>Equipment</b>                       | <b>Manufacturer</b> | <b>Model No</b>      | <b>Inventory No</b> | <b>Cal Date</b> | <b>Cal Due Date</b> |
| EMI test receiver                      | Rohde & Schwarz     | ESU40                | SHEM051-1           | 2019-12-20      | 2020-12-19          |
| CONTROLLER                             | INNCO               | CO200                | SHEM047-1           | N/A             | N/A                 |
| ANTENNA MAST                           | INNCO               | MA400-EP             | SHEM047-2           | N/A             | N/A                 |
| TURN DEVICE                            | INNCO               | DE 3600-RH           | SHEM047-3           | N/A             | N/A                 |
| Double ridged broadband horn ANTENNA   | SCHWARZBECK         | BBHA9120D            | SHEM050-1           | 2019-10-14      | 2021-10-13          |
| High-amplifier                         | SCHWARZBECK         | SCU-F0118-G40-BZ4-CS | SHEM050-2           | 2019-12-20      | 2020-12-19          |
| Semi/Fully Anechoic                    | ST                  | 11*6*6M              | SHEM078-2           | 2020-05-25      | 2023-05-24          |

| <b>General used equipment</b> |                             |                 |                     |                 |                     |
|-------------------------------|-----------------------------|-----------------|---------------------|-----------------|---------------------|
| <b>Equipment</b>              | <b>Manufacturer</b>         | <b>Model No</b> | <b>Inventory No</b> | <b>Cal Date</b> | <b>Cal Due Date</b> |
| Digital pressure meter        | YONGZHI                     | DYM3-01         | SHEM082-1           | 2018-01-25      | 2021-01-24          |
| Temperature&humidity recorder | ShangHai weather meter work | ZJ 1-2B         | SHEM042-1~6         | 2020-09-11      | 2021-09-10          |
| Digital Multimeter            | FLUKE                       | 17B             | SHEM043-3           | 2020-09-09      | 2021-09-08          |
| Autoformer regulator          | Guangzhou bao de            | TDGC2-5KVA      | SHEM150-1           | N/A             | N/A                 |
| Multi-purpose tong tester     | FLUKE                       | 316             | SHEM001-1           | 2019-12-20      | 2020-12-19          |

## 6 Emission Test Results

### 6.1 Radiated Emissions (30MHz-1GHz)

Test Requirement: 47 CFR Part 15, Subpart B

Test Method: ANSI C63.4:2014

Frequency Range: 30MHz to 1GHz

Measurement Distance: 3m

Limit:

30MHz -88MHz 40.0(dB $\mu$ V/m) quasi-peak

88MHz-216MHz 43.5(dB $\mu$ V/m) quasi-peak

216MHz-960MHz 46.0(dB $\mu$ V/m) quasi-peak

960MHz-1000MHz 54.0(dB $\mu$ V/m) quasi-peak

Detector: Peak for pre-scan (120kHz resolution bandwidth) 30M to1000MHz

#### 6.1.1 E.U.T. Operation

Operating Environment:

Temperature: 22 °C Humidity: 50 % RH Atmospheric Pressure: 1020 mbar

Pretest these mode to find the worst case:


a:BT mode\_Keep the EUT paring with the Dongle via BT function,And then keep pressing the buttons of the EUT continuous.

b:ZigBee mode\_Keep the EUT paring with the gateway via BT function,And then keep pressing the buttons of the EUT continuous.

c:IR mode\_Keep the EUT power on and press the IR buttons of the EUT continuous

The worst case for final test: a:BT mode\_Keep the EUT paring with the Dongle via BT function,And then keep pressing the buttons of the EUT continuous.

#### 6.1.2 Test Setup Diagram




#### 6.1.3 Measurement Data

An initial pre-scan was performed in the chamber using the spectrum analyser in peak detection mode. Quasi-peak measurements were conducted based on the peak sweep graph. The EUT was measured by BiConiLog antenna with 2 orthogonal polarities.



Mode:a; Polarization:Horizontal




Antenna Polarity :Horizontal  
 EUT/Project :5982CR  
 Test mode :a

|   | Read Freq | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Emission Level | Limit Line | Over Limit | Remark |
|---|-----------|------------|----------------|------------|---------------|----------------|------------|------------|--------|
|   | MHz       | dBuv       | dB/m           | dB         | dB            | dBuv/m         | dBuv/m     | dB         |        |
| 1 | 41.96     | 23.06      | 13.80          | 1.09       | 27.14         | 10.81          | 40.00      | -29.19     | QP     |
| 2 | 47.64     | 24.45      | 13.22          | 1.21       | 27.12         | 11.76          | 40.00      | -28.24     | QP     |
| 3 | 154.88    | 22.77      | 13.40          | 2.18       | 26.85         | 11.50          | 43.50      | -32.00     | QP     |
| 4 | 729.73    | 24.06      | 23.08          | 5.87       | 28.03         | 24.98          | 46.00      | -21.02     | QP     |
| 5 | 862.97    | 25.25      | 24.27          | 6.26       | 27.74         | 28.04          | 46.00      | -17.96     | QP     |
| 6 | 960.16    | 25.91      | 24.40          | 6.57       | 27.53         | 29.35          | 54.00      | -24.65     | QP     |

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Mode:a; Polarization:Vertical



Antenna Polarity :Vertical  
 EUT/Project :5982CR  
 Test mode :a

|   | Read Freq | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Emission Level | Limit Line | Over Limit | Remark |
|---|-----------|------------|----------------|------------|---------------|----------------|------------|------------|--------|
|   | MHz       | dBuv       | dB/m           | dB         | dB            | dBuv/m         | dBuv/m     | dB         |        |
| 1 | 39.07     | 24.87      | 13.98          | 1.02       | 27.13         | 12.74          | 40.00      | -27.26     | QP     |
| 2 | 52.74     | 26.35      | 12.73          | 1.30       | 27.09         | 13.29          | 40.00      | -26.71     | QP     |
| 3 | 160.49    | 22.83      | 13.36          | 2.22       | 26.84         | 11.57          | 43.50      | -31.93     | QP     |
| 4 | 737.18    | 24.55      | 22.53          | 5.91       | 28.05         | 24.94          | 46.00      | -21.06     | QP     |
| 5 | 832.81    | 25.93      | 23.42          | 6.23       | 27.78         | 27.80          | 46.00      | -18.20     | QP     |
| 6 | 955.29    | 26.75      | 24.45          | 6.55       | 27.52         | 30.23          | 46.00      | -15.77     | QP     |

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

## 6.2 Radiated Emissions (above 1GHz)

|                       |   |
|-----------------------|---|
| Test Requirement:     | 47 CFR Part 15, Subpart B   |
| Test Method:          | ANSI C63.4:2014   |
| Frequency Range:      | Above 1GHz  |
| Measurement Distance: | 3m  |
| Limit:                |   |
| Above 1GHz            | 74(dBμV/m) peak, 54(dBμV/m) average                               |
| Detector:             | Peak for pre-scan (1000kHz resolution bandwidth) 1000M to18000MHz |

### 6.2.1 E.U.T. Operation

Operating Environment:


Temperature: 22 °C Humidity: 50 % RH Atmospheric Pressure: 1020 mbar

Pretest these mode to find the worst case:

- a:BT mode\_Keep the EUT paring with the Dongle via BT function,And then keep pressing the buttons of the EUT continuous.
- b:ZigBee mode\_ Keep the EUT paring with the gateway via BT function,And then keep pressing the buttons of the EUT continuous.
- c:IR mode\_Keep the EUT power on and press the IR buttons of the EUT continuous

The worst case for final test: a:BT mode\_Keep the EUT paring with the Dongle via BT function,And then keep pressing the buttons of the EUT continuous.


### 6.2.2 Test Setup Diagram



### 6.2.3 Measurement Data

An initial pre-scan was performed in the chamber using the spectrum analyser in peak detection mode. Average measurements were conducted based on the peak sweep graph. The EUT was measured by Horn antenna with 2 orthogonal polarities.

Mode:a; Polarization:Horizontal




Antenna Polarity :HORIZONTAL  
 EUT/Project :5982CR  
 Test mode :a

|      | Read      | Antenna | Cable | Preamp | Emission | Limit  | Over  |                |
|------|-----------|---------|-------|--------|----------|--------|-------|----------------|
| Freq | Level     | Factor  | Loss  | Factor | Level    | Line   | Limit | Remark         |
| MHz  | dBuV      | dB/m    | dB    | dB     | dBuV/m   | dBuV/m | dB    |                |
| 1    | 4653.771  | 31.84   | 30.92 | 9.52   | 42.47    | 29.81  | 54.00 | -24.19 Average |
| 2    | 4653.771  | 42.85   | 30.92 | 9.52   | 42.47    | 40.82  | 74.00 | -33.18 Peak    |
| 3    | 10545.010 | 24.58   | 39.73 | 14.89  | 42.29    | 36.91  | 54.00 | -17.09 Average |
| 4    | 10545.010 | 36.50   | 39.73 | 14.89  | 42.29    | 48.83  | 74.00 | -25.17 Peak    |
| 5    | 11533.480 | 23.67   | 39.75 | 15.25  | 42.74    | 35.93  | 54.00 | -18.07 Average |
| 6    | 11533.480 | 35.73   | 39.75 | 15.25  | 42.74    | 47.99  | 74.00 | -26.01 Peak    |
| 7    | 14618.170 | 25.71   | 41.60 | 17.55  | 41.72    | 43.14  | 54.00 | -10.86 Average |
| 8    | 14618.170 | 36.30   | 41.60 | 17.55  | 41.72    | 53.73  | 74.00 | -20.27 Peak    |
| 9    | 17286.170 | 24.25   | 41.70 | 18.83  | 40.59    | 44.19  | 54.00 | -9.81 Average  |
| 10   | 17286.170 | 34.54   | 41.70 | 18.83  | 40.59    | 54.48  | 74.00 | -19.52 Peak    |
| 11   | 18000.000 | 21.76   | 50.80 | 18.62  | 40.80    | 50.38  | 54.00 | -3.62 Average  |
| 12   | 18000.000 | 33.91   | 50.80 | 18.62  | 40.80    | 62.53  | 74.00 | -11.47 Peak    |

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Mode:a; Polarization:Vertical



Antenna Polarity :VERTICAL  
 EUT/Project :5982CR  
 Test mode :a

|      | Read      | Antenna | Cable | Preamp | Emission | Limit  | Over  |                |
|------|-----------|---------|-------|--------|----------|--------|-------|----------------|
| Freq | Level     | Factor  | Loss  | Factor | Level    | Line   | Limit | Remark         |
| MHz  | dBuV      | dB/m    | dB    | dB     | dBuV/m   | dBuV/m | dB    |                |
| 1    | 1100.079  | 45.56   | 24.18 | 4.33   | 42.48    | 31.59  | 54.00 | -22.41 Average |
| 2    | 1100.079  | 58.99   | 24.18 | 4.33   | 42.48    | 45.02  | 74.00 | -28.98 Peak    |
| 3    | 1162.182  | 45.53   | 24.35 | 4.47   | 42.47    | 31.88  | 54.00 | -22.12 Average |
| 4    | 1162.182  | 57.88   | 24.35 | 4.47   | 42.47    | 44.23  | 74.00 | -29.77 Peak    |
| 5    | 2656.331  | 40.31   | 27.93 | 6.88   | 42.32    | 32.80  | 54.00 | -21.20 Average |
| 6    | 2656.331  | 52.18   | 27.93 | 6.88   | 42.32    | 44.67  | 74.00 | -29.33 Peak    |
| 7    | 11076.100 | 21.67   | 40.06 | 15.28  | 42.18    | 34.83  | 54.00 | -19.17 Average |
| 8    | 11076.100 | 35.82   | 40.06 | 15.28  | 42.18    | 48.98  | 74.00 | -25.02 Peak    |
| 9    | 14575.970 | 25.38   | 41.70 | 17.40  | 41.72    | 42.76  | 54.00 | -11.24 Average |
| 10   | 14575.970 | 36.66   | 41.70 | 17.40  | 41.72    | 54.04  | 74.00 | -19.96 Peak    |
| 11   | 18000.000 | 21.65   | 50.80 | 18.62  | 40.80    | 50.27  | 54.00 | -3.73 Average  |
| 12   | 18000.000 | 33.58   | 50.80 | 18.62  | 40.80    | 62.20  | 74.00 | -11.80 Peak    |

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor