



# RF EXPOSURE EVALUATION REPORT

FCC ID : 2AG0Z-R2KM  
Equipment : VR Headset  
Brand Name :  **oculus**  
Model Name : DX45JH  
Applicant : Facebook Technologies, LLC  
1 Hacker Way, Menlo Park, CA 94025, USA  
Standard : 47 CFR Part 2.1093  
FCC KDB 447498 D01 v06

We, SPORTON INTERNATIONAL INC has been evaluated in accordance with 47 CFR Part 2.1093 for the device and pass the limit.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The results in this variant report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.



Approved by: Cona Huang / Deputy Manager

**SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory**  
No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



## Table of Contents

- 1. General Information ..... 3
- 1.1 Description of Device Under Test (DUT) ..... 3
- 2. Maximum RF output power among production units ..... 3
- 3. RF Exposure Evaluation ..... 4


## History of this test report

Report No.	Version	Description	Issued Date
FA892722	Rev. 01	Initial issue of report	Nov. 29, 2018



**1. General Information**

**1.1 Description of Device Under Test (DUT)**

Product Feature & Specification	
DUT Type	VR Headset
Brand Name	
Model Name	DX45JH
FCC ID	2AGOZ-R2KM
Wireless Technology and Frequency Range	GFSK: 2402 MHz ~ 2478 MHz
Mode	GFSK
DUT Stage	Identical Prototype

**Remark:** The above DUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

**Reviewed by:** Jason Wang

**Report Producer:** Wan Liu

**2. Maximum RF output power among production units**

Mode	Average Power(dBm)
GFSK	4



### 3. RF Exposure Evaluation

Bluetooth Max Power (dBm)	mW	Separation Distance (mm)	Frequency (GHz)	Exclusion Thresholds
4	2.51	5	2.48	0.79

**Note:**

1. Per KDB 447498 D01v06 the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and ≤ 7.5 for 10-g extremity SAR

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

**Conclusion:** Per KDB 447498 D01v06, when the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion. The test exclusion threshold is 0.79 which is ≤ 3, SAR testing is not required.