

RF Exposure Evaluation Report

FCC ID : 2AGOZ-W7Z
EQUIPMENT : Charging Dock
Brand Name : Meta
Model Name : W7Z
Applicant : META PLATFORMS TECHNOLOGIES, LLC
1 HACKER WAY, MENLO PARK, CA, 94025, USA
Manufacturer : META PLATFORMS TECHNOLOGIES, LLC
1 HACKER WAY, MENLO PARK, CA, 94025, USA
STANDARD : FCC CFR 47 part 1, 1.1307(b) and 1.1310
KDB 680106 D01v03r01

We, Sporton International Inc. (Kunshan), would like to declare that the tested sample has been evaluated in accordance with the test procedures given in KDB 680106 D01v03r01 and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.



Approved by: Si Zhang

Sporton International Inc. (Kunshan)

No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300
People's Republic of China



Table of Contents

1. DESCRIPTION OF EQUIPMENT UNDER TEST (EUT)	4
2. ADMINISTRATION DATA	4
3. RF EXPOSURE LIMIT INTRODUCTION	5
4. KDB 680106 D01 SECTION 5B EQUIPMENT APPROVAL CONSIDERATIONS.....	6
5. TEST MODE	6
6. MEASUREMENT EQUIPMENT.....	6
7. SUPPORT UNIT USED IN TEST CONFIGURATION AND SYSTEM	6
8. RF EXPOSURE EVALUATION	7



Revision History

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FA333001	Rev. 01	Initial issue of report	Jun. 30, 2023



1. Description of Equipment Under Test (EUT)

Table with Product Feature & Specification header and rows for EUT Type, Brand Name, Model Name, FCC ID, S/N, Frequency Range, Modulation Type, Antenna Type, HW Version, SW Version, EUT Stage, Date of Test, and Remark.

Table with Declaration of Conformity and Comments and Explanations sections.

2. Administration Data

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Table with Testing Laboratory header and rows for Test Firm, Test Site Location, and Test Site No. with sub-headers for Sporton Site No., FCC Designation No., and FCC Test Firm Registration No.



3. RF Exposure Limit Introduction

§ 1.1310 The criteria listed in table 1 shall be used to evaluate the environmental impact of human exposure to radio frequency(RF) radiation as specified in § 1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of § 2.1093 of this chapter.

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	* 100	6
3.0-30	1842/f	4.89/f	* 900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	* 100	30
1.34-30	824/f	2.19/f	* 180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

(1) Occupational/controlled exposure limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when a person is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure. The phrase fully aware in the context of applying these exposure limits means that an exposed person has received written and/or verbal information fully explaining the potential for RF exposure resulting from his or her employment. With the exception of transient persons, this phrase also means that an exposed person has received appropriate training regarding work practices relating to controlling or mitigating his or her exposure. Such training is not required for transient persons, but they must receive written and/or verbal information and notification (for example, using signs) concerning their exposure potential and appropriate means available to mitigate their exposure. The phrase exercise control means that an exposed person is allowed to and knows how to reduce or avoid exposure by administrative or engineering controls and work practices, such as use of personal protective equipment or time averaging of exposure.

(2) General population/uncontrolled exposure limits apply in situations in which the general public may be exposed, or in which persons who are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.



4. KDB 680106 D01 Section 5B Equipment Approval Considerations

Requirement	Devices
(1) Power transfer frequency is less than 1 MHz.	Yes. Operating Frequency is less than 1MHz
(2) Output power from each primary coil is less than or equal to 15 watts.	Yes. The each coil maximum power is 2.5W
(3) The system may consist of more than one source primary coil, charging one or more clients. If more than one primary coil is present, the coil pairs may be powered on at the same time.	The system included two primary coils and the device is designed to charge a single client.
(4) Client device is placed directly in contact with the transmitter.	Yes. The client device is placed directly in contact with the transmitter.
(5) Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion).	Yes. It is a Mobile device.
(6) The aggregate H-field strengths anywhere at or beyond 15 cm surrounding the device, and 20 cm away from the surface from all coils that by design can simultaneously transmit, and while those coils are simultaneously energized, are demonstrated to be less than 50% of the applicable MPE limit.	The measurement was taken based on KDB 680106 D01. The H-Field worst case leakage of mobile condition is 23.85%.

Note:The inductive wireless power transfer device meets all of the above requirements.

5. Test Mode

This device has been tested in the following charging conditions as below:

Test Mode	Test Setup Configuration	Charging Current Condition
TM1	Test w/ Client Device installed	< 1% Battery status
TM2	Test w/ Client Device installed	50% Battery status
TM3	Test w/ Client Device installed	Near 100% Battery status

6. Measurement Equipment

Instrument	Manufacturer	Model No.	Serial No.	Freq Rang	Last Cal.	Due Date
Electric and Magnetic field Probe-Analyzer	Narda S.T.S / PMM	EHP 200AC	180ZX11026	3KHz~30MHz	Aug, 05, 2022	Aug, 04, 2023

7. Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Controller	Meta	Light:V6P Right:S2Y	2AGOZ-V6P (Left) 2AGOZ-S2Y (Right)	N/A	N/A



8. RF Exposure Evaluation

1. The device power transfer frequency is less than 1MHz and the output power from each primary coil is less than or equal to 15 watts and the system just one source primary coil and the client device is placed directly in contact with the transmitter and the device is meet mobile exposure condution also the test result is compliance with applicable MPE limit.
2. The equipment under test was placed on a wooden desk inside of shield room. The isotropic field probe was used to measure the field strength for 6 EUT surfaces. The detailed setup photo please refer to Test Setup Photo.
3. Per KDB 680106 D01v03r01 and 202010 TCB workshop, RF exposure should be evaluation at 15 cm surrounding the device and 20 cm away from the surface from all coils. Emissions between 100 kHz to 300 kHz should be assessed versus the limits at 300 kHz in Table 1 of Section 1.1310: 614 V/m for E-field strengths and 1.63 A/m for H-field strengths.

Charging Dock with Left hand controller						
Position	E-Field measurement (V/m)					
Distance	A(15cm)	B(15cm)	C(15cm)	D(15cm)	E(15cm)	F(20cm)
TM1	0.7344	0.9447	1.1251	0.7764	0.9212	1.0151
TM2	0.7514	0.9994	1.2531	0.7851	1.1511	1.1541
TM3	0.8459	1.0541	1.2984	0.8106	1.2349	1.1988
E-Field Limit						
Maximum Average (V/m)		Percentage(%)		RF Exposure limit (V/m)		
1.2984		0.21		614		
Position	H-Field measurement (A/m)					
Distance	A(15cm)	B(15cm)	C(15cm)	D(15cm)	E(15cm)	F(20cm)
TM1	0.1722	0.0637	0.2979	0.0727	0.1245	0.2514
TM2	0.2253	0.0621	0.3541	0.0851	0.1985	0.3085
TM3	0.2561	0.0781	0.3888	0.1235	0.2596	0.3459
H-Field Limit						
Maximum Average (A/m)		Percentage(%)		RF Exposure limit (A/m)		
0.3888		23.85		1.63		



Charging Dock with Right hand controller							
Position	E-Field measurement (V/m)						
	Distance	A(15cm)	B(15cm)	C(15cm)	D(15cm)	E(15cm)	F(20cm)
TM1		0.7019	0.8244	1.0484	0.7634	0.9889	0.9851
TM2		0.7546	0.8195	1.0931	0.8756	0.9951	0.9899
TM3		0.7681	0.8944	1.1521	0.9045	1.0546	1.0254
E-Field Limit							
Maximum Average (V/m)		Percentage(%)			RF Exposure limit (V/m)		
1.1521		0.19			614		
Position	H-Field measurement (A/m)						
	Distance	A(15cm)	B(15cm)	C(15cm)	D(15cm)	E(15cm)	F(20cm)
TM1		0.1731	0.0641	0.2123	0.0628	0.1811	0.1997
TM2		0.1945	0.0581	0.2981	0.0789	0.2098	0.2135
TM3		0.2059	0.0745	0.3564	0.0894	0.2135	0.2245
H-Field Limit							
Maximum Average (A/m)		Percentage(%)			RF Exposure limit (A/m)		
0.3564		21.87			1.63		

Conclusion:

The field strength limit refers to Part 1.1310 and the test result of exposure evaluation is compliant with 50% of the MPE limit then a PAG is not required.

Test Engineer : Light Wang

-----THE END-----