

FCC Part 15C Measurement and Test Report

For

Shenzhen RF-Link Technology Co.,Ltd

Bldg56A,6/F,Baotian Rd3, Xixiang Town,Baoan District, ShenZhen, China

FCC ID: 2AGQ3-8821

FCC Rule(s): FCC Part 15.247

Product Description: WIFI+BT module

Tested Model: RL-EM02G-8821CE

Report No.: WTH20H03010817W-3

Sample Receipt Date: 2020-03-17

Tested Date: 2020-03-17 to 2020-04-08

Issued Date: 2020-04-08

Tested By: Jason Su / Engineer

Reviewed By: Silin Chen / EMC Manager

Approved & Authorized By: Jandy So / PSQ Manager

Prepared By:

Jason Su
Silin Chen
Jandy So

Shenzhen SEM Test Technology Co., Ltd.

1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road,
Bao'an District, Shenzhen, P.R.C. (518101)

Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen SEM Test Technology Co., Ltd.

TABLE OF CONTENTS

1. GENERAL INFORMATION	4
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
1.2 TEST STANDARDS	5
1.3 TEST METHODOLOGY	5
1.4 TEST FACILITY	5
1.5 EUT SETUP AND TEST MODE	6
1.6 MEASUREMENT UNCERTAINTY	7
1.7 TEST EQUIPMENT LIST AND DETAILS	8
2. SUMMARY OF TEST RESULTS	10
3. RF EXPOSURE	11
3.1 STANDARD APPLICABLE	11
3.2 TEST RESULT	11
4. ANTENNA REQUIREMENT	12
4.1 STANDARD APPLICABLE	12
4.2 EVALUATION INFORMATION	12
5. POWER SPECTRAL DENSITY	13
5.1 STANDARD APPLICABLE	13
5.2 TEST PROCEDURE	13
5.3 SUMMARY OF TEST RESULTS/PLOTS	13
6. DTS BANDWIDTH	18
6.1 STANDARD APPLICABLE	18
6.2 TEST PROCEDURE	18
6.3 SUMMARY OF TEST RESULTS/PLOTS	18
7. RF OUTPUT POWER	23
7.1 STANDARD APPLICABLE	23
7.2 TEST PROCEDURE	23
7.3 SUMMARY OF TEST RESULTS/PLOTS	23
8. FIELD STRENGTH OF SPURIOUS EMISSIONS	29
8.1 STANDARD APPLICABLE	29
8.2 TEST PROCEDURE	29
8.3 CORRECTED AMPLITUDE & MARGIN CALCULATION	30
8.4 SUMMARY OF TEST RESULTS/PLOTS	30
9. OUT OF BAND EMISSIONS	34
9.1 STANDARD APPLICABLE	34
9.2 TEST PROCEDURE	34
9.3 SUMMARY OF TEST RESULTS/PLOTS	35
10. CONDUCTED EMISSIONS	50
10.1 TEST PROCEDURE	50
10.2 BASIC TEST SETUP BLOCK DIAGRAM	50
10.3 TEST RECEIVER SETUP	50
10.4 SUMMARY OF TEST RESULTS/PLOTS	50

Report version

Version No.	Date of issue	Description
Rev.00	2020-04-08	Original
/	/	/

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant: Shenzhen RF-Link Technology Co.,Ltd
Address of applicant: Bldg56A,6/F,Baotian Rd3, Xixiang Town,Baoan District, ShenZhen, China

Manufacturer: Shenzhen RF-Link Technology Co.,Ltd
Address of manufacturer: Bldg56A,6/F,Baotian Rd3, Xixiang Town,Baoan District, ShenZhen, China

General Description of EUT	
Product Name:	WIFI+BT module
Trade Name:	RF-LINK
Model No.:	RL-EM02G-8821CE
Adding Model(s):	/
Rated Voltage:	DC 3.3V
<i>Note: The test data is gathered from a production sample provided by the manufacturer.</i>	

Technical Characteristics of EUT	
Support Standards:	802.11b, 802.11g, 802.11n
Frequency Range:	2412-2462MHz for 802.11b/g/n-HT20 2422-2452MHz for 802.11n-HT40
RF Output Power:	21.71dBm (Conducted)
Type of Modulation:	DBPSK,BPSK,DQPSK,QPSK,16QAM,64QAM
Quantity of Channels:	11 for 802.11b/g/n-HT20 7 for 802.11n-HT40
Channel Separation:	5MHz
Type of Antenna:	Integral Antenna
Antenna Gain:	2dBi

1.2 Test Standards

The tests were performed according to following standards:

FCC Rules Part 15.247: Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.

558074 D01 15.247 Meas Guidance v05r02: Guidance For Compliance Measurements On Digital Transmission System, Frequency Hopping Spread Spectrum System, And Hybrid System Devices Operating Under Section 15.247 Of The Fcc Rules.

ANSI C63.10-2013: American National Standard for Testing Unlicensed Wireless Devices.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, KDB 558074 D01 15.247 Meas Guidance v05r02.

The equipment under test (EUT) was configured to measure its highest possible emission level. The test modes were adapted accordingly in reference to the Operating Instructions.

1.4 Test Facility

Address of the test laboratory

Laboratory: Shenzhen SEM Test Technology Co., Ltd.

Address: 1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road, Bao'an District, Shenzhen, P.R.C. (518101)

FCC – Registration No.: 125990

Shenzhen SEM Test Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. The Designation Number is CN5010, and Test Firm Registration Number is 125990.

Industry Canada (IC) Registration No.: 11464A

The 3m Semi-anechoic chamber of Shenzhen SEM Test Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.

1.5 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, with a duty cycle equal to 100%, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	802.11b	Low:2412MHz, Middle:2437MHz,High:2462MHz
TM2	802.11g	Low:2412MHz, Middle:2437MHz,High:2462MHz
TM3	802.11n-HT20	Low:2412MHz, Middle:2437MHz,High:2462MHz
TM4	802.11n-HT40	Low:2422MHz, Middle:2437MHz,High:2452MHz

Test Conditions	
Temperature:	22~25 °C
Relative Humidity:	50~56 %.
ATM Pressure:	1019 mbar

EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Accessories Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number
/	/	/	/
/	/	/	/

1.6 Measurement Uncertainty

Measurement uncertainty		
Parameter	Conditions	Uncertainty
RF Output Power	Conducted	$\pm 0.42\text{dB}$
Occupied Bandwidth	Conducted	$\pm 1.5\%$
Power Spectral Density	Conducted	$\pm 1.8\text{dB}$
Conducted Spurious Emission	Conducted	$\pm 2.17\text{dB}$
Conducted Emissions	Conducted	9-150kHz $\pm 3.74\text{dB}$
		0.15-30MHz $\pm 3.34\text{dB}$
Transmitter Spurious Emissions	Radiated	30-200MHz $\pm 4.52\text{dB}$
		0.2-1GHz $\pm 5.56\text{dB}$
		1-6GHz $\pm 3.84\text{dB}$
		6-18GHz $\pm 3.92\text{dB}$

1.7 Test Equipment List and Details

No.	Description	Manufacturer	Model	Serial No.	Cal Date	Due Date
SEMT-1072	Spectrum Analyzer	Agilent	E4407B	MY41440400	2019-04-30	2020-04-29
SEMT-1031	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/035	2019-04-30	2020-04-29
SEMT-1007	EMI Test Receiver	Rohde & Schwarz	ESVB	825471/005	2019-04-30	2020-04-29
SEMT-1008	Amplifier	Agilent	8447F	3113A06717	2019-04-30	2020-04-29
SEMT-1043	Amplifier	C&D	PAP-1G18	2002	2019-04-30	2020-04-29
SEMT-1011	Broadband Antenna	Schwarz beck	VULB9163	9163-333	2019-05-05	2021-05-04
SEMT-1042	Horn Antenna	ETS	3117	00086197	2019-05-05	2021-05-04
SEMT-1121	Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170582	2019-05-05	2021-05-04
SEMT-1069	Loop Antenna	Schwarz beck	FMZB 1516	9773	2019-05-05	2021-05-04
SEMT-1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2019-04-30	2020-04-29
SEMT-1003	L.I.S.N	Schwarz beck	NSLK8126	8126-224	2019-04-30	2020-04-29
SEMT-1002	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2019-04-30	2020-04-29
SEMT-1168	Pre-amplifier	Direction Systems Inc.	PAP-0126	14141-12838	2019-04-30	2020-04-29
SEMT-1169	Pre-amplifier	Direction Systems Inc.	PAP-2640	14145-14153	2019-04-30	2020-04-29
SEMT-1163	Spectrum Analyzer	Rohde & Schwarz	FSP40	100612	2019-04-30	2020-04-29
SEMT-1170	DRG Horn Antenna	A.H. SYSTEMS	SAS-574	571	2019-05-05	2021-05-04
SEMT-1166	Power Limiter	Agilent	N9356B	MY45450376	2019-04-30	2020-04-29
SEMT-1048	RF Limiter	ATTEN	AT-BSF-2400~2500	/	2019-04-30	2020-04-29
SEMT-1076	RF Switcher	Top Precision	RCS03-A2	/	2019-04-30	2020-04-29
SEMT-C001	Cable	Zheng DI	LL142-07-07-10M(A)	/	2020-03-18	2021-03-17
SEMT-C002	Cable	Zheng DI	ZT40-2.92J-2.92J-6M	/	2020-03-18	2021-03-17
SEMT-C003	Cable	Zheng DI	ZT40-2.92J-2.92J-2.5M	/	2020-03-18	2021-03-17
SEMT-C004	Cable	Zheng DI	2M0RFC	/	2020-03-18	2021-03-17
SEMT-C005	Cable	Zheng DI	1M0RFC	/	2020-03-18	2021-03-17
SEMT-C006	Cable	Zheng DI	1M0RFC	/	2020-03-18	2021-03-17

Software List			
Description	Manufacturer	Model	Version
EMI Test Software (Radiated Emission)*	Farad	EZ-EMC	RA-03A1
EMI Test Software (Conducted Emission)*	Farad	EZ-EMC	RA-03A1

*Remark: indicates software version used in the compliance certification testing

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§2.1093	RF Exposure	Compliant
§15.203;15.247(b)(4)(i)	Antenna Requirement	Compliant
§15.205	Restricted Band of Operation	Compliant
§15.207(a)	Conducted Emission	Compliant
§15.247(e)	Power Spectral Density	Compliant
§15.247(a)(2)	DTS Bandwidth	Compliant
§15.247(b)(3)	RF Output Power	Compliant
§15.209(a)	Radiated Emission	Compliant
§15.247(d)	Band Edge (Out of Band Emissions)	Compliant

N/A: not applicable

3. RF Exposure

3.1 Standard Applicable

According to §1.1307 and §2.1093, the portable transmitter must comply the RF exposure requirements.

3.2 Test Result

This product complied with the requirement of the RF exposure, please see the RF Exposure Report.

4. Antenna Requirement

4.1 Standard Applicable

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

4.2 Evaluation Information

This product has an integral PCB antenna, fulfill the requirement of this section.

5. Power Spectral Density

5.1 Standard Applicable

According to 15.247(a)(1)(iii), for digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

5.2 Test Procedure




According to the KDB 558074 D01 v05r02 Subclause 8.4 and ANSI C63.10-2013 Subclause 11.10.3, such specifications require that the same method as used to determine the conducted output power shall also be used to determine the power spectral density. The test method of power spectral density as below:




- a) Set instrument center frequency to DTS channel center frequency.
- b) Set span to at least 1.5 times the OBW.
- c) Set RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- d) Set VBW $\geq 3 \times \text{RBW}$.
- e) Detector = power averaging (RMS) or sample detector (when RMS not available).
- f) Ensure that the number of measurement points in the sweep $\geq 2 \times \text{span}/\text{RBW}$.
- g) Sweep time = auto couple.
- h) Employ trace averaging (RMS) mode over a minimum of 100 traces.
- i) Use the peak marker function to determine the maximum amplitude level.
- j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat (note that this may require zooming in on the emission of interest and reducing the span in order to meet the minimum measurement point requirement as the RBW is reduced).




5.3 Summary of Test Results/Plots




Test Mode	Test Channel MHz	Power Spectral Density dBm/3kHz	Limit dBm/3kHz
802.11b_11Mbps	2412	-8.83	8
	2437	-8.15	8
	2462	-10.14	8
802.11g_54Mbps	2412	-14.76	8
	2437	-12.26	8
	2462	-12.36	8
802.11n-HT20_MCS7	2412	-13.76	8
	2437	-13.00	8
	2462	-14.02	8
802.11n-HT40_MCS7	2422	-18.73	8
	2437	-17.31	8
	2452	-16.11	8

Please refer to the following test plots:

<p>802.11b-Low</p>	 <p> CENTER FREQUENCY 2.412 GHz Ref 20 dBm *Att 30 dB *RBW 3 kHz VBW 10 kHz Marker 1 (T1) -8.83 dBm 2.41122000 GHz SWT 3.4 s 20 Offset 2.5 dB 3 MHz/ Span 30 MHz Date: 24.MAR.2020 09:15:57 </p>
<p>802.11b-Middle</p>	 <p> MARKER 1 2.43622 GHz Ref 20 dBm *Att 30 dB *RBW 3 kHz VBW 10 kHz Marker 1 (T1) -8.15 dBm 2.43622000 GHz SWT 3.4 s 20 Offset 2.5 dB 3 MHz/ Span 30 MHz Date: 24.MAR.2020 09:19:05 </p>
<p>802.11b-High</p>	 <p> MARKER 1 2.46044 GHz Ref 20 dBm *Att 30 dB *RBW 3 kHz VBW 10 kHz Marker 1 (T1) -10.14 dBm 2.46044000 GHz SWT 3.4 s 20 Offset 2.5 dB 3 MHz/ Span 30 MHz Date: 24.MAR.2020 09:29:01 </p>

<p>802.11g-Low</p>	 <p>MARKER 1 2.40948 GHz Ref 20 dBm Att 30 dB</p> <p>*RBW 3 kHz *Marker 1 (T1) -14.76 dBm VBW 10 kHz SWT 3.4 s 2.409480000 GHz</p> <p>20 Offset 2.5 dB</p> <p>Center 2.412 GHz 3 MHz/ Span 30 MHz</p> <p>Date: 24.MAR.2020 09:21:52</p>
<p>802.11g-Middle</p>	 <p>MARKER 1 2.43232 GHz Ref 20 dBm Att 30 dB</p> <p>*RBW 3 kHz *Marker 1 (T1) -12.26 dBm VBW 10 kHz SWT 3.4 s 2.432320000 GHz</p> <p>20 Offset 2.5 dB</p> <p>Center 2.437 GHz 3 MHz/ Span 30 MHz</p> <p>Date: 24.MAR.2020 09:24:27</p>
<p>802.11g-High</p>	 <p>MARKER 1 2.4545 GHz Ref 20 dBm Att 30 dB</p> <p>*RBW 3 kHz *Marker 1 (T1) -12.36 dBm VBW 10 kHz SWT 3.4 s 2.454500000 GHz</p> <p>20 Offset 2.5 dB</p> <p>Center 2.462 GHz 3 MHz/ Span 30 MHz</p> <p>Date: 24.MAR.2020 09:23:43</p>

<p>802.11n-HT20-Low</p>	 <p>MARKER 1 2.41644 GHz Ref 20 dBm Att 30 dB</p> <p>*RBW 3 kHz VBW 10 kHz SWT 3.4 s</p> <p>Marker 1 (T1) -13.76 dBm 2.416440000 GHz</p> <p>20 Offset 2.5 dB</p> <p>Center 2.412 GHz 3 MHz/ Span 30 MHz</p> <p>Date: 24.MAR.2020 09:25:25</p>
<p>802.11n-HT20-Middle</p>	 <p>MARKER 1 2.44198 GHz Ref 20 dBm Att 30 dB</p> <p>*RBW 3 kHz VBW 10 kHz SWT 3.4 s</p> <p>Marker 1 (T1) -13.00 dBm 2.441980000 GHz</p> <p>20 Offset 2.5 dB</p> <p>Center 2.437 GHz 3 MHz/ Span 30 MHz</p> <p>Date: 24.MAR.2020 09:26:02</p>
<p>802.11n-HT20-High</p>	 <p>MARKER 1 2.4569 GHz Ref 20 dBm Att 30 dB</p> <p>*RBW 3 kHz VBW 10 kHz SWT 3.4 s</p> <p>Marker 1 (T1) -14.02 dBm 2.456900000 GHz</p> <p>20 Offset 2.5 dB</p> <p>Center 2.462 GHz 3 MHz/ Span 30 MHz</p> <p>Date: 24.MAR.2020 09:26:48</p>

<p>802.11n-HT40-Low</p>	 <p>MARKER 1 2.41072 GHz Ref 20 dBm Att 30 dB</p> <p>*RBW 3 kHz VBW 10 kHz SWT 6.8 s</p> <p>Marker 1 (T1) -18.73 dBm 2.410720000 GHz</p> <p>20 Offset 2.5 dB</p> <p>Center 2.422 GHz 6 MHz/ Span 60 MHz</p> <p>Date: 24.MAR.2020 09:28:25</p>
<p>802.11n-HT40-Middle</p>	 <p>MARKER 1 2.42452 GHz Ref 20 dBm Att 30 dB</p> <p>*RBW 3 kHz VBW 10 kHz SWT 6.8 s</p> <p>Marker 1 (T1) -17.31 dBm 2.424520000 GHz</p> <p>20 Offset 2.5 dB</p> <p>Center 2.437 GHz 6 MHz/ Span 60 MHz</p> <p>Date: 24.MAR.2020 09:29:22</p>
<p>802.11n-HT40-High</p>	 <p>MARKER 1 2.4394 GHz Ref 20 dBm Att 30 dB</p> <p>*RBW 3 kHz VBW 10 kHz SWT 6.8 s</p> <p>Marker 1 (T1) -16.11 dBm 2.439400000 GHz</p> <p>20 Offset 2.5 dB</p> <p>Center 2.452 GHz 6 MHz/ Span 60 MHz</p> <p>Date: 24.MAR.2020 09:30:20</p>

6. DTS Bandwidth

6.1 Standard Applicable

According to 15.247(a)(2), systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

6.2 Test Procedure


According to the KDB 558074 D01 v05r02 Subclause 8.2 and ANSI C63.10-2013 Subclause 11.8.1, the test method of DTS Bandwidth as below:




- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.




6.3 Summary of Test Results/Plots




Test Mode	Test Channel MHz	6 dB Bandwidth MHz	Limit kHz
802.11b_11Mbps	2412	10.32	≥ 500
	2437	10.68	≥ 500
	2462	10.44	≥ 500
802.11g_54Mbps	2412	16.56	≥ 500
	2437	16.26	≥ 500
	2462	16.50	≥ 500
802.11n-HT20_MCS7	2412	17.46	≥ 500
	2437	17.58	≥ 500
	2462	17.64	≥ 500
802.11n-HT40_MCS7	2422	35.88	≥ 500
	2437	36.12	≥ 500
	2452	36.12	≥ 500

Please refer to the following test plots:



<p>802.11g-Low</p>	 <p>DELTA MARKER 2 16.56 MHz Ref 22.5 dBm Att 30 dB *RBW 100 kHz VEW 300 kHz SWT 5 ms Delta 2 [T1] -0.99 dB 16.560000000 MHz</p> <p>Masker 1 [T1] -3.19 dBm 2.403720000 GHz</p> <p>Masker J [T1] 1.93 dBm 2.405700000 GHz</p> <p>D1 -4.09 dBm</p> <p>Center 2.412 GHz 3 MHz/ Span 30 MHz</p> <p>Date: 1.JAN.2000 07:11:51</p>
<p>802.11g-Middle</p>	 <p>DELTA MARKER 2 16.26 MHz Ref 22.5 dBm Att 30 dB *RBW 100 kHz VEW 300 kHz SWT 5 ms Delta 2 [T1] 1.01 dB 16.260000000 MHz</p> <p>Masker 1 [T1] -2.35 dBm 2.428720000 GHz</p> <p>Masker J [T1] 3.79 dBm 2.430760000 GHz</p> <p>D1 -2.21 dBm</p> <p>Center 2.437 GHz 3 MHz/ Span 30 MHz</p> <p>Date: 1.JAN.2000 07:14:10</p>
<p>802.11g-High</p>	 <p>DELTA MARKER 2 16.5 MHz Ref 22.5 dBm Att 30 dB *RBW 100 kHz VEW 300 kHz SWT 5 ms Delta 2 [T1] 0.60 dB 16.500000000 MHz</p> <p>Masker 1 [T1] -2.49 dBm 2.453720000 GHz</p> <p>Masker J [T1] 2.67 dBm 2.455700000 GHz</p> <p>D1 -3.33 dBm</p> <p>Center 2.462 GHz 3 MHz/ Span 30 MHz</p> <p>Date: 1.JAN.2000 07:17:36</p>

<p>802.11n-HT20-Low</p>	 <p>DELTA MARKER 2 17.46 MHz *RBW 100 kHz Delta 2 [T1] Ref 22.5 dBm *Att 30 dB VEW 300 kHz 0.73 dB SWT 5 ms 17.46000000 MHz</p> <p>Masker 1 [T1] -3.85 dBm Marker 3 [T1] 2.14 dBm Marker 4 [T1] 2.40570000 GHz D1 -3.85 dBm Lvl</p> <p>Center 2.412 GHz 3 MHz/ Span 30 MHz</p> <p>Date: 1.JAN.2000 07:28:20</p>
<p>802.11n-HT20-Middle</p>	 <p>DELTA MARKER 2 17.58 MHz *RBW 100 kHz Delta 2 [T1] Ref 22.5 dBm *Att 30 dB VEW 300 kHz -0.42 dB SWT 5 ms 17.58000000 MHz</p> <p>Masker 1 [T1] -2.40 dBm Marker 3 [T1] 2.77 dBm Marker 4 [T1] 2.43070000 GHz D1 -3.20 dBm Lvl</p> <p>Center 2.437 GHz 3 MHz/ Span 30 MHz</p> <p>Date: 1.JAN.2000 07:30:11</p>
<p>802.11n-HT20-High</p>	 <p>DELTA MARKER 2 17.64 MHz *RBW 100 kHz Delta 2 [T1] Ref 22.5 dBm *Att 30 dB VEW 300 kHz 1.02 dB SWT 5 ms 17.64000000 MHz</p> <p>Masker 1 [T1] -3.89 dBm Marker 3 [T1] 1.65 dBm Marker 4 [T1] 2.45570000 GHz D1 -4.33 dBm Lvl</p> <p>Center 2.462 GHz 3 MHz/ Span 30 MHz</p> <p>Date: 1.JAN.2000 07:32:09</p>

<p>802.11n-HT40-Low</p>	 <p>DELTA MARKER 2 35.88 MHz Ref 20 dBm Att 30 dB *RBW 100 kHz VSW 300 kHz SWT 10 ms Delta 2 [T1] -2.68 dB 35.88000000 MHz</p> <p>Marker 1 [T1] -5.08 dBm 2.42200000 GHz Marker 3 [T1] -2.128 dBm 2.43700000 GHz</p> <p>Center 2.422 GHz 6 MHz/ Span 60 MHz</p> <p>Date: 1.JAN.2000 00:17:50</p>
<p>802.11n-HT40-Middle</p>	 <p>DELTA MARKER 2 36.12 MHz Ref 20 dBm Att 30 dB *RBW 100 kHz VSW 300 kHz SWT 10 ms Delta 2 [T1] -0.58 dB 36.12000000 MHz</p> <p>Marker 1 [T1] -6.08 dBm 2.43700000 GHz Marker 3 [T1] -1.37 dBm 2.42200000 GHz</p> <p>Center 2.437 GHz 6 MHz/ Span 60 MHz</p> <p>Date: 1.JAN.2000 00:21:35</p>
<p>802.11n-HT40-High</p>	 <p>DELTA MARKER 2 36.12 MHz Ref 20 dBm Att 30 dB *RBW 100 kHz VSW 300 kHz SWT 10 ms Delta 2 [T1] 0.28 dB 36.12000000 MHz</p> <p>Marker 1 [T1] -7.18 dBm 2.45200000 GHz Marker 3 [T1] -2.113 dBm 2.43700000 GHz</p> <p>Center 2.452 GHz 6 MHz/ Span 60 MHz</p> <p>Date: 1.JAN.2000 00:24:50</p>

7. RF Output Power

7.1 Standard Applicable

According to 15.247(b)(3), for systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands: 1 Watt.

7.2 Test Procedure




According to the KDB-558074 D01 v05r02 Subclause 8.3.2.2 and ANSI C63.10-2013 Subclause 11.9.2.2, when this option is exercised, the measured power is to be referenced to the OBW rather than the DTS bandwidth




- a) Set span to at least 1.5 times the OBW.
- b) Set RBW = 1-5% of the OBW, not to exceed 1 MHz.
- c) Set VBW $\geq 3 \times$ RBW.
- d) Number of points in sweep $\geq 2 \times$ span / RBW. (This gives bin-to-bin spacing \leq RBW/2, so that narrowband signals are not lost between frequency bins.)
- e) Sweep time = auto.
- f) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.
- g) If transmit duty cycle < 98 %, use a sweep trigger with the level set to enable triggering only on full power pulses. The transmitter shall operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle ≥ 98 %, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to “free run” .
- h) Trace average at least 100 traces in power averaging (i.e., RMS) mode.
- i) Compute power by integrating the spectrum across the OBW of the signal using the instrument’s band power measurement function, with band limits set equal to the OBW band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.




7.3 Summary of Test Results/Plots




Test Mode	Frequency MHz	Reading dBm	Output Power mW	Limit mW
802.11b _ 11Mbps	2412	21.71	148.25	1000
	2437	20.05	101.16	1000
	2462	19.82	95.94	1000
802.11g_54Mbps	2412	17.96	62.52	1000
	2437	19.18	82.79	1000
	2462	18.31	67.76	1000
802.11n HT20_MCS7	2412	17.94	62.23	1000
	2437	18.33	68.08	1000
	2462	17.94	62.23	1000
802.11n HT40_MCS7	2422	16.65	46.24	1000
	2437	16.51	44.77	1000
	2452	14.88	30.76	1000

Please refer to the following test plots:

<p>802.11b-Low 11Mbps</p>	 <p>Center Frequency: 2.412 GHz Power: 21.71 dBm Bandwidth: 20 MHz Date: 2.APR.2020 16:16:53</p>
<p>802.11b-Middle 11Mbps</p>	 <p>Center Frequency: 2.442 GHz Power: 20.05 dBm Bandwidth: 20 MHz Date: 2.APR.2020 16:20:38</p>
<p>802.11b-High 11Mbps</p>	 <p>Center Frequency: 2.462 GHz Power: 19.82 dBm Bandwidth: 20 MHz Date: 8.APR.2020 15:43:25</p>

<p>802.11g-Low 54Mbps</p>	 <p>Center Frequency: 2.412 GHz Power: 17.96 dBm Date: 2.APR.2020 16:22:40</p>
<p>802.11g-Middle 54Mbps</p>	 <p>Center Frequency: 2.442 GHz Power: 19.18 dBm Date: 2.APR.2020 16:23:12</p>
<p>802.11g-High 54Mbps</p>	 <p>Center Frequency: 2.462 GHz Power: 18.31 dBm Date: 8.APR.2020 15:44:28</p>

<p>802.11n-HT20-Low MCS7</p>	 <p>Center Frequency: 2.412 GHz</p> <p>Power: 17.94 dBm</p> <p>Date: 2.APR.2020 16:24:21</p>
<p>802.11n-HT20-Middle MCS7</p>	 <p>Center Frequency: 2.442 GHz</p> <p>Power: 18.33 dBm</p> <p>Date: 2.APR.2020 16:24:57</p>
<p>802.11n-HT20-High MCS7</p>	 <p>Center Frequency: 2.462 GHz</p> <p>Power: 17.94 dBm</p> <p>Date: 8.APR.2020 15:45:45</p>

<p>802.11n-HT40-Low MCS7</p>	 <p>Date: 2.APR.2020 16:28:46</p>
<p>802.11n-HT40-Middle MCS7</p>	 <p>Date: 2.APR.2020 16:29:41</p>
<p>802.11n-HT40-High MCS7</p>	 <p>Date: 8.APR.2020 15:48:30</p>

8. Field Strength of Spurious Emissions

8.1 Standard Applicable


According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).


The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

8.2 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.205 15.247(a) and FCC Part 15.209 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle. The spacing between the peripherals was 10 cm.





Frequency :9kHz-30MHz
 RBW=10KHz,
 VBW =30KHz
 Sweep time= Auto
 Trace = max hold
 Detector function = peak

Frequency :30MHz-1GHz
 RBW=120KHz,
 VBW=360KHz
 Sweep time= Auto
 Trace = max hold
 Detector function = peak, QP

Frequency :Above 1GHz
 RBW=1MHz,
 VBW=3MHz(Peak), 10Hz(AV)
 Sweep time= Auto
 Trace = max hold
 Detector function = peak, AV

8.3 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Ant. Factor} + \text{Cable Loss} - \text{Ampl. Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dB μ V means the emission is 6dB μ V below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15 Limit}$$


8.4 Summary of Test Results/Plots


Note: 1.This EUT was tested in 3 orthogonal positions and the worst case position data was reported.

2. Below 1 GHz, Have pre-scan all modulation mode, found the 802.11b modulation Low channel which it was worst case, so only the worst case's data on the test report.

3.Above 1 GHz, Have pre-scan all modulation mode, found the 802.11b modulation which it was worst case, so only the worst case's data on the test report

➤ Spurious Emissions Below 1GHz





- Spurious Emissions Above 1GHz
- Test Mode: 802.11b_11Mbps (worst case)

Frequency (MHz)	Reading (dBuV/m)	Correct dB	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Polar H/V	Detector
Low Channel-2412MHz							
4824.000	56.08	-3.87	52.21	74	-21.79	H	PK
4824.000	41.72	-3.87	37.85	54	-16.15	H	AV
7236.000	62.09	1.14	63.23	74	-10.77	H	PK
7236.000	42.75	1.19	43.94	54	-10.06	H	AV
4824.000	61.93	-3.86	58.07	74	-15.93	V	PK
4824.000	46.88	-3.86	43.02	54	-10.98	V	AV
7236.000	59.23	1.10	60.33	74	-13.67	V	PK
7236.000	45.19	1.10	46.29	54	-7.71	V	AV
Middle Channel-2437MHz							
4874.000	59.13	-3.74	55.39	74	-18.61	H	PK
4874.000	43.53	-3.74	39.79	54	-14.21	H	AV
7311.000	58.44	1.47	59.91	74	-14.09	H	PK
7311.000	43.43	1.47	44.90	54	-9.10	H	AV
4874.000	61.07	-3.74	57.33	74	-16.67	V	PK
4874.000	51.39	-3.74	47.65	54	-6.35	V	AV
7311.000	64.07	1.47	65.54	74	-8.46	V	PK
7311.000	41.19	1.47	42.66	54	-11.34	V	AV
High Channel-2462MHz							
4924.000	56.00	-3.59	52.41	74	-21.59	H	PK
4924.000	40.02	-3.59	36.43	54	-17.57	H	AV
7386.000	56.88	1.79	58.67	74	-15.33	H	PK
7386.000	42.74	1.79	44.53	54	-9.47	H	AV
4924.000	63.00	-3.59	59.41	74	-14.59	V	PK
4924.000	47.83	-3.59	44.24	54	-9.76	V	AV
7386.000	63.59	1.79	65.38	74	-8.62	V	PK
7386.000	44.86	1.79	46.65	54	-7.35	V	AV

Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics, other than listed in the table above are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

9. Out of Band Emissions

9.1 Standard Applicable

According to §15.247 (d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

9.2 Test Procedure

According to the KDB 558074 D01 v05r02 Subclause 8.4 and ANSI C63.10-2013 Subclause 11.11, the emissions in nonrestricted frequency bands test method as follows:

- a) Set the center frequency and span to encompass frequency range to be measured.
- b) Set the RBW = 100 kHz.
- c) Set the VBW $\geq [3 \times \text{RBW}]$.
- d) Detector = peak.
- e) Sweep time = auto couple.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use the peak marker function to determine the maximum amplitude level.

According to the KDB 558074 D01 v05r02 Subclause 8.5 and ANSI C63.10-2013 Subclause 11.12, the emissions in restricted frequency bands test method as follows:

A. Radiated emission measurements:

Set span = wide enough to capture the peak level of the emission operating on the channel closest to the bandedge, as well as any modulation products which fall outside of the authorized band of operation (2310MHz to 2420MHz for low bandedge, 2460MHz to 2500MHz for the high bandedge)

RBW = 1MHz, VBW = 1MHz for peak value measured

RBW = 1MHz, VBW = 10Hz for average value measured

Sweep = auto; Detector function = peak/average; Trace = max hold

All the trace to stabilize, set the marker on the emission at the bandedge, or on the highest modulation product outside of the band, if this level is greater than that at the bandedge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission. Those emission must comply with the 15.209 limit for fall in the restricted bands listed in section 15.205. Note that the method of measurement KDB publication number: 913591 may be used for the radiated bandedge measurements.

B. Antenna-port conducted measurements

Peak emission levels are measured by setting the instrument as follows:

- a) RBW = as specified in Table 9/
- b) VBW $\geq [3 \times \text{RBW}]$.
- c) Detector = peak.
- d) Sweep time = auto.
- e) Trace mode = max hold.
- f) Allow sweeps to continue until the trace stabilizes. (Note that the required measurement time may be lengthened for low-duty-cycle applications.)

Table 9—RBW as a function of frequency

Frequency	RBW
9 kHz to 150 kHz	200 Hz to 300 Hz
0.15 MHz to 30 MHz	9 kHz to 10 kHz
30 MHz to 1000 MHz	100 kHz to 120 kHz
>1000 MHz	1 MHz

If the peak-detected amplitude can be shown to comply with the average limit, then it is not necessary to perform a separate average measurement.


Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in section 8.1. Report the three highest emissions relative to the limit.

9.3 Summary of Test Results/Plots


Note: We have tested the all modes, and recorded the worst cases (802.11b Vertical) in the report

➤ Radiated test

802.11b_11Mbps			
Test Channel	Low	Polarity:	Vertical(worst case)



802.11b_11Mbps			
Test Channel	High	Polarity:	Vertical(worst case)




Site: Polarization: **Vertical** Temperature: 26
 Limit: FCC PART 15 Class B Radiation(PK) 1-6G Power: DC 3.3V Humidity: 60 %
 EUT:
 M/N: RL-EM02G-8821CE
 Mode:
 Note: B-2462M

No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measurement dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	2483.500	44.22	0.99	45.21	73.90	-28.69	peak	
2 *	2483.500	32.41	0.99	33.40	53.90	-20.50	AVG	
3	2500.000	44.75	1.04	45.79	73.90	-28.11	peak	
4	2500.000	32.23	1.04	33.27	53.90	-20.63	AVG	


➤ Conducted test

802.11b_11Mbps


Low



Date: 24.MAR.2020 10:05:06




Date: 24.MAR.2020 10:34:35




Date: 24.MAR.2020 10:37:13

802.11b_11Mbps

Middle






Date: 24.MAR.2020 10:39:05



Date: 24.MAR.2020 10:40:32

802.11b_11Mbps


High




Date: 24.MAR.2020 10:43:36

802.11g_54Mbps


Low



Date: 24.MAR.2020 10:14:26





Date: 24.MAR.2020 10:48:19



Date: 24.MAR.2020 10:49:38




802.11g_54Mbps

Middle



802.11g_54Mbps




High



Date: 24.MAR.2020 10:56:52

802.11n-HT20_MCS7



Low



Date: 24.MAR.2020 11:04:28




802.11n-HT20_MCS7

Middle



802.11n-HT20_MCS7


High




Date: 24.MAR.2020 11:10:02

802.11n-HT40_MCS7


Low



Date: 24.MAR.2020 10:25:32





Date: 24.MAR.2020 11:13:17



Date: 24.MAR.2020 11:14:08

802.11n-HT40_MCS7




Middle



Date: 24.MAR.2020 11:16:50

802.11n-HT40_MCS7

High



Date: 24.MAR.2020 11:18:30


10. Conducted Emissions

10.1 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle. The spacing between the peripherals was 10 cm.

10.2 Basic Test Setup Block Diagram





10.3 Test Receiver Setup

During the conducted emission test, the test receiver was set with the following configurations:

Start Frequency	150 kHz
Stop Frequency	30 MHz
Sweep Speed	Auto
IF Bandwidth.....	10 kHz
Quasi-Peak Adapter Bandwidth	9 kHz
Quasi-Peak Adapter Mode	Normal

10.4 Summary of Test Results/Plots





***** END OF REPORT *****