

# FCC TEST REPORT

For

**NFC Android Reader**

**Model Number: FX205F**

**FCC ID: 2AGQIFX205**

**Report Number : WT198003466**

Test Laboratory : Shenzhen Academy of Metrology and Quality Inspection  
Site Location : NETC Building, No.4 Tongfa Rd., Xili, Nanshan, Shenzhen, China  
Tel : 0086-755-86928965  
Fax : 0086-755-86009898-31396  
Web : [www.smq.com.cn](http://www.smq.com.cn)  
E-mail : [emcrf@smq.com.cn](mailto:emcrf@smq.com.cn)

## TEST REPORT DECLARATION

Applicant : FAMOCO SAS  
Address : 59 avenue Victor Hugo Paris, France  
Manufacturer : FAMOCO SAS  
Address : 59 avenue Victor Hugo Paris, France  
EUT Description : NFC Android Reader  
Model No : FX205F  
Trade mark : FAMOCO  
Serial Number : /  
FCC ID : 2AGQIFX205

Test Standards:

**FCC Part 15.207, 15.209, 15.247(2018)**

The EUT described above is tested by Shenzhen Academy of Metrology and Quality Inspection EMC Laboratory to determine the maximum emissions from the EUT. Shenzhen Academy of Metrology and Quality Inspection EMC Laboratory is assumed full responsibility for the accuracy of the test results. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with FCC Rules Part 15.207, 15.209, 15.247 .

The test report is valid for above tested sample only and shall not be reproduced in part without written approval of the laboratory.

Project Engineer:	 _____ (Chen Silin 陈司林)	Date:	<u>Jul.23, 2019</u>
Checked by:	 _____ (Lin Yixiang 林奕翔)	Date:	<u>Jul.23, 2019</u>
Approved by:	 _____ (Lin Bin 林斌)	Date:	<u>Jul.23, 2019</u>

## TABLE OF CONTENTS

<b>TEST REPORT DECLARATION .....</b>	<b>2</b>
<b>1. TEST RESULTS SUMMARY .....</b>	<b>5</b>
<b>2. GENERAL INFORMATION .....</b>	<b>6</b>
2.1. Report information.....	6
2.2. Laboratory Accreditation and Relationship to Customer .....	6
2.3. Measurement Uncertainty.....	7
<b>3. PRODUCT DESCRIPTION .....</b>	<b>8</b>
3.1. EUT Description.....	8
3.2. Related Submittal(s) / Grant (s) .....	9
3.3. Block Diagram of EUT Configuration .....	9
3.4. Operating Condition of EUT.....	9
3.5. Directional Antenna Gain .....	9
3.6. Support Equipment List.....	10
3.7. Test Conditions.....	10
3.8. Special Accessories.....	10
3.9. Equipment Modifications .....	10
<b>4. TEST EQUIPMENT USED .....</b>	<b>11</b>
<b>5. DUTY CYCLE .....</b>	<b>12</b>
5.1. LIMITS OF DUTY CYCLE.....	12
5.2. TEST PROCEDURE.....	12
5.3. TEST SETUP .....	12
5.4. TEST DATA.....	12
<b>6. 6DB BANDWIDTH MEASUREMENT .....</b>	<b>15</b>
6.1. LIMITS OF 6dB BANDWIDTH MEASUREMENT .....	15
6.2. TEST PROCEDURE.....	15
6.3. TEST SETUP .....	15
6.4. Test Data .....	16
<b>7. MAXIMUM CONDUCTED OUTPUT POWER MEASUREMENT .....</b>	<b>23</b>
7.1. LIMITS OF Maximum Conducted Output Power Measurement.....	23

7.2.	TEST PROCEDURE.....	23
7.3.	TEST SETUP .....	23
7.4.	TEST DATA.....	23
<b>8.</b>	<b>MAXIMUM POWER SPECTRAL DENSITY LEVEL MEASUREMENT .....</b>	<b>31</b>
8.1.	LIMITS OF Maximum Power Spectral Density Level Measurement.....	31
8.2.	TEST PROCEDURE.....	31
8.3.	TEST DATA.....	31
<b>9.</b>	<b>CONDUCTED BANDEDGE AND SPURIOUS MEASUREMENT .....</b>	<b>39</b>
9.1.	LIMITS OF Conducted Bandedge and Spurious Measurement.....	39
9.2.	TEST PROCEDURE.....	39
9.3.	TEST DATA.....	40
<b>10.</b>	<b>RADIATED BANDEDGE AND SPURIOUS MEASUREMENT.....</b>	<b>56</b>
10.1.	LIMITS OF Radiated Bandedge and Spurious Measurement .....	56
10.2.	TEST PROCEDURE.....	56
10.3.	TEST DATA.....	57
<b>11.</b>	<b>CONDUCTED EMISSION TEST FOR AC POWER PORT MEASUREMENT .....</b>	<b>119</b>
11.1.	Test Standard and Limit .....	119
11.2.	Test Procedure .....	119
11.3.	Test Arrangement.....	119
11.4.	Test Data .....	119
<b>12.</b>	<b>ANTENNA REQUIREMENTS .....</b>	<b>126</b>

## 1. TEST RESULTS SUMMARY

Table 1 Test Results Summary

Test Items	FCC Rules	Test Results
6dB DTS bandwidth measurement	15.247 (a) (2)	Pass
Maximum Peak Conducted Power	15.247 (b) (3)	Pass
Maximum Power Spectral Density Level	15.247 (3)	Pass
Conducted Bandedge and Spurious	15.247 (d)	Pass
Radiated Bandedge and Spurious	15.247 (d) 15.209 15.205	Pass
Conducted emission test for AC power port	15.207	Pass
Antenna Requirement	15.203	Pass

Remark: "N/A" means "Not applicable."

## 2. GENERAL INFORMATION

### 2.1. Report information

This report is not a certificate of quality; it only applies to the sample of the specific product/equipment given at the time of its testing. The results are not used to indicate or imply that they are application to the similar items. In addition, such results must not be used to indicate or imply that SMQ approves recommends or endorses the manufacture, supplier or use of such product/equipment, or that SMQ in any way guarantees the later performance of the product/equipment.

The sample/s mentioned in this report is/are supplied by Applicant, SMQ therefore assumes no responsibility for the accuracy of information on the brand name, model number, origin of manufacture or any information supplied.

Additional copies of the report are available to the Applicant at an additional fee. No third part can obtain a copy of this report through SMQ, unless the applicant has authorized SMQ in writing to do so.

### 2.2. Laboratory Accreditation and Relationship to Customer

The testing report were performed by the Shenzhen Academy of Metrology and quality Inspection EMC Laboratory (Guangdong EMC compliance testing center), in their facilities located at NETC Building, No.4 Tongfa Rd., Xili, Nanshan, Shenzhen, China. At the time of testing, Laboratory is accredited by the following organizations:

China National Accreditation Service for Conformity Assessment (CNAS) accredits the Laboratory for conformance to FCC standards, EMC international standards and EN standards. The Registration Number is CNAS L0579.

The Laboratory is Accredited Testing Laboratory of FCC with Designation number CN1165 and Site registration number 582918.

The Laboratory is registered to perform emission tests with Innovation, Science and Economic Development (ISED), and the registration number is 11177A.

### 2.3.Measurement Uncertainty

Conducted Emission  
9kHz~30MHz 3.5dB

Radiated Emission  
30MHz~1000MHz 4.5dB  
1GHz~26.5GHz 4.6dB

### 3. PRODUCT DESCRIPTION

#### 3.1. EUT Description

Description : NFC Android Reader  
 Manufacturer : FAMOCO SAS  
 Model Number : FX205F  
 Operate Frequency : 2.412GHz~2.462GHz  
 Antenna Designation : PIFA antenna:1.3 dBi

Remark: --

WLAN :

Table 2 Working Frequency List(802.11b, 802.11g,802.11n HT20)

Channel	Frequency	Channel	Frequency
1	2412MHz	8	2447MHz
2	2417MHz	9	2452MHz
3	2422MHz	10	2457MHz
4	2427MHz	11	2462MHz
5	2432MHz	---	---
6	2437MHz	---	---
7	2442MHz	---	---

Table 3 Working Frequency List(802.11n HT40)

Channel	Frequency	Channel	Frequency
3	2422MHz	8	2447MHz
4	2427MHz	9	2452MHz
5	2432MHz	---	---
6	2437MHz	---	---
7	2442MHz	---	---



### 3.2. Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for FCC ID: **2AGQIFX205** filing to comply with Section 15.207, 15.209, 15.247 of the FCC Part 15, Subpart C Rules.

### 3.3. Block Diagram of EUT Configuration



Figure 1 EUT setup

### 3.4. Operating Condition of EUT

The Radiated spurious emission measurements were carried out in semi-anechoic chamber with 3-meter test range, and EUT is rotated on three test planes to find out the worst emission (X plane).

Worst-case mode and channel used for 30-1000 MHz radiated and power line conducted emissions was the mode and channel with the highest output power.

Worst-case data rates as provided by the client were:

802.11b mode: 1 Mbps

802.11g mode: 6 Mbps

802.11n HT20 mode: MCS0

802.11n HT40 mode: MCS0

802.11b and 802.11g operates in SISO mode. For SISO conducted measurements, the modes tested in this report will be considered as a worst case mode.

802.11n operate in SISO mode. For SISO conducted measurements, the modes tested in this report will be considered as a worst case mode.

### 3.5. Directional Antenna Gain

Directional gain need NOT to be considered.

### 3.6. Support Equipment List

Table 4 Support Equipment List

Name	Model No	S/N	Manufacturer
Adapter 1 for EUT	HJ528-0500200	--	Good Fortune (Dongguan) Electronics & Technology Co., Ltd.
Adapter 2 for EUT	HJ-0500200W2-US	--	Shenzhen Huajin Electronics Co., LTD.

### 3.7. Test Conditions

Date of test : Jun.20, 2019 - Jul.15, 2019

Date of EUT Receive : Jun.20, 2019

Temperature: 20 ~ 25 °C

Relative Humidity: 42-56%

### 3.8. Special Accessories

Not available for this EUT intended for grant.

### 3.9. Equipment Modifications

Not available for this EUT intended for grant.

#### 4. TEST EQUIPMENT USED

Table 5 Test Equipment

No.	Equipment	Manufacturer	Model No.	Last Cal.	Cal. Interval
SB2603	EMI Test Receiver	Rohde & Schwarz	ESCS30	Feb.20, 2019	1 Year
SB2604	AMN	Rohde & Schwarz	ESH2-Z5	Feb.20, 2019	1 Year
SB9054/04	EMI Test Receiver	Rohde & Schwarz	ESU8	Sep.03, 2018	1 Year
SB8501/09	EMI Test Receiver	Rohde & Schwarz	ESU40	Mar.11, 2019	1 Year
SB8501/04	Bilog Antenna	Schwarzbeck	VULB9163	Jun.01, 2019	1 Year
SB5472/02	Bilog Antenna	Schwarzbeck	VULB9163	Jun.01, 2019	1 Year
SB3435	Horn Antenna	Rohde & Schwarz	HF906	Jan.01, 2018	1 Year
SB8501/11	Horn Antenna	ETS-Lindgren	3160-09	Jan.21,2017	3 Years
SB12724/11	Loop Antenna	Rohde & Schwarz	HFH2-Z2	Jun.26, 2019	1 Year
SB8501/17	Preamplifier	Rohde & Schwarz	SCU-18	Feb.20, 2019	1 Year
SB8501/16	Preamplifier	Rohde & Schwarz	SCU-26	Feb.18, 2019	1 Year
SB8501/14	Preamplifier	Rohde & Schwarz	SCU-03	Feb.20, 2019	1 Year
SB11873/01	Power Sensor	Rohde & Schwarz	OSP120+OSP -B157	Feb.21, 2019	1 Year
SB9060	Signal Analyzer	Rohde & Schwarz	FSQ40	Feb.21, 2019	1 Year
--	Radiated Test Software	Rohde & Schwarz	EMC 32 8.50.0	--	--
--	AC Line Conducted Test Software	Rohde & Schwarz	ES-K1 V1.71	--	--

## 5. DUTY CYCLE

### 5.1. LIMITS OF DUTY CYCLE

None; for reporting purposes only

### 5.2. TEST PROCEDURE

1. Set span = Zero
2. RBW = 10MHz
3. VBW = 10MHz,
4. Detector = Peak

### 5.3. TEST SETUP




### 5.4. TEST DATA

Table 6 Duty Cycle Test Data


Mode	On Time (ms)	Duty Cycle(%)	Duty Factor	1/T Minimum VBW (kHz)
802.11b	8.38	99.6	0.02	0.01
802.11g	1.39	97.3	0.1	1
802.11n HT20	1.30	97.2	0.1	1
802.11N HT40	0.65	94.7	0.24	1

# 802.11b




Date: 1.JUL.2019 13:02:38

# 802.11g




Date: 2.JUL.2019 11:28:19

# 802.11n HT20



Date: 2.JUL.2019 11:54:26

# 802.11n HT40



Date: 2.JUL.2019 12:25:28

## 6. 6DB BANDWIDTH MEASUREMENT

### 6.1. LIMITS OF 6dB BANDWIDTH MEASUREMENT

CFR 47 (FCC) part 15.247 (a) (2)

### 6.2. TEST PROCEDURE

ANSI C63.10-2013 Clause 11.8

The transmitter output was connected to the spectrum analyzer.

a) Set RBW = 100 kHz.

b) Set the VBW  $\geq$  [3  $\times$  RBW].

c) Detector = Peak.

d) Trace mode = max hold.

e) Sweep = auto couple.

f) Allow the trace to stabilize.

g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

### 6.3. TEST SETUP




**6.4. Test Data**

**Table 7 6dB Bandwidth Test Data**

TestMode	Channel	6dB Bandwidth [MHz]	Verdict
802.11b	2412	9.640	PASS
	2437	9.120	PASS
	2462	9.640	PASS
802.11g	2412	15.800	PASS
	2437	15.160	PASS
	2462	15.760	PASS
802.11n HT20	2412	16.400	PASS
	2437	15.160	PASS
	2462	16.400	PASS
802.11n HT40	2422	35.600	PASS
	2437	28.960	PASS
	2452	35.280	PASS




11B\_2412




Date: 1.JUL.2019 14:45:56

11B\_2437




Date: 1.JUL.2019 13:03:26

11B\_2462




Date: 1.JUL.2019 14:49:03

11G\_2412




Date: 2.JUL.2019 11:18:00

11G\_2437




Date: 2.JUL.2019 11:29:37

11G\_2462




Date: 2.JUL.2019 11:34:30

11N20\_2412




Date: 2.JUL.2019 11:45:23

11N20\_2437




Date: 2.JUL.2019 11:55:16

### 11N20\_2462




Date: 2.JUL.2019 12:01:37

### 11N40\_2422




Date: 2.JUL.2019 12:11:23

### 11N40\_2437



Date: 2.JUL.2019 12:28:36

### 11N40\_2452



Date: 2.JUL.2019 12:35:10

## 7. MAXIMUM CONDUCTED OUTPUT POWER MEASUREMENT

### 7.1. LIMITS OF Maximum Conducted Output Power Measurement

CFR 47 (FCC) part 15.247 (b) (3)

### 7.2. TEST PROCEDURE

ANSI C63.10-2013 Clause 11.9

The following procedure can be used when the maximum available RBW of the instrument is less than the DTS bandwidth:

a) Set the RBW = 1 MHz.

b) Set the VBW  $\geq$  [3  $\times$  RBW].

c) Set the span  $\geq$  [1.5  $\times$  DTS bandwidth].

d) Detector = peak.

e) Sweep time = auto couple.

f) Trace mode = max hold.

g) Allow trace to fully stabilize.

h) Use the instrument's band/channel power measurement function with the band limits set equal to the DTS bandwidth edges (for some instruments, this may require a manual override to select the peak detector). If the instrument does not have a band power function, then sum the spectrum levels (in linear power units) at intervals equal to the RBW extending across the DTS channel bandwidth.

### 7.3. TEST SETUP




### 7.4. TEST DATA

Table 8 Maximum Conducted Output Power

TestMode	Channel	Meas.Level [dBm]	Limit [dBm]	Verdict
802.11b	2412	17.20	30	PASS
	2437	18.02	30	PASS
	2462	18.17	30	PASS
802.11g	2412	18.10	30	PASS
	2437	20.97	30	PASS
	2462	21.01	30	PASS
802.11n HT20	2412	18.21	30	PASS
	2437	20.77	30	PASS
	2462	20.99	30	PASS
802.11n HT40	2422	20.07	30	PASS
	2437	20.81	30	PASS
	2452	20.15	30	PASS




### 11B\_2412




Date: 1.JUL.2019 14:46:36

### 11B\_2437




Date: 1.JUL.2019 13:03:52

### 11B\_2462




Date: 1.JUL.2019 14:49:29

### 11G\_2412




Date: 2.JUL.2019 11:18:26

### 11G\_2437




Date: 2.JUL.2019 11:30:03

### 11G\_2462




Date: 2.JUL.2019 11:34:56

### 11N20\_2412




Date: 2.JUL.2019 11:48:45

### 11N20\_2437




Date: 2.JUL.2019 11:55:51

### 11N20\_2462




Date: 2.JUL.2019 12:02:03

### 11N40\_2422




Date: 2.JUL.2019 12:15:33

### 11N40\_2437



Date: 2.JUL.2019 12:29:02

### 11N40\_2452



Date: 2.JUL.2019 12:35:36

## 8. MAXIMUM POWER SPECTRAL DENSITY LEVEL MEASUREMENT

### 8.1. LIMITS OF Maximum Power Spectral Density Level Measurement

CFR 47 (FCC) part 15.247 (e)

### 8.2. TEST PROCEDURE

ANSI C63.10-2013 Clause 11.10

The transmitter output was connected to the spectrum analyzer.

a) Set analyzer center frequency to DTS channel center frequency.

b) Set the span to 1.5 times the DTS bandwidth.

c) Set RBW to:  $3\text{kHz} \leq \text{RBW} \leq 100\text{ kHz}$ .

d) Set VBW  $\geq 3 \times \text{RBW}$ .

e) Detector = peak.

f) Sweep time = auto couple.

g) Trace mode = max hold.

h) Allow trace to fully stabilize.

i) Use the peak marker function to determine the maximum amplitude level within the RBW.

j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

### 8.3. TEST DATA


Table 9 Maximum Power Spectral Density Level

TestMode	Channel	Maximum Power Spectral Density Level [dBm]	Limit [dBm]	Verdict
802.11b	2412	-3.56	8	PASS
	2437	4.15	8	PASS
	2462	-3.19	8	PASS
802.11g	2412	-7.66	8	PASS
	2437	-5.99	8	PASS
	2462	-6.51	8	PASS
802.11n HT20	2412	-8.91	8	PASS
	2437	-3.86	8	PASS
	2462	-6.5	8	PASS
802.11n HT40	2422	-7.96	8	PASS
	2437	-7.43	8	PASS
	2452	-8.56	8	PASS






### 11B1\_2462




Date: 1.JUL.2019 14:50:54

### 11G\_2412




Date: 2.JUL.2019 11:19:26

11G\_2437




Date: 2.JUL.2019 11:31:03

11G\_2462




Date: 2.JUL.2019 11:35:57

11N20\_2412




Date: 2.JUL.2019 11:49:45

11N20\_2437




Date: 2.JUL.2019 11:56:59

### 11N20\_2462




Date: 2.JUL.2019 12:03:03

### 11N40\_2422




Date: 2.JUL.2019 12:17:25

### 11N40\_2437



Date: 2.JUL.2019 12:30:54

### 11N40\_2452



Date: 2.JUL.2019 12:37:29

## 9. CONDUCTED BANDEGE AND SPURIOUS MEASURMENT

### 9.1. LIMITS OF Conducted Bandedge and Spurious Measurement

CFR 47 (FCC) part 15.247 (d)

### 9.2. TEST PROCEDURE

ANSI C63.10-2013 Clause 11.11

The transmitter output was connected to the spectrum analyzer.

Establish a reference level by using the following procedure:


- a) Set instrument center frequency to DTS channel center frequency.
- b) Set the span to  $\geq 1.5$  times the DTS bandwidth.
- c) Set the RBW = 100 kHz.
- d) Set the VBW  $\geq 3 \times$  RBW.
- e) Detector = peak.
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum PSD level.

Emission level measurement

- a) Set the center frequency and span to encompass frequency range to be measured.
- b) Set the RBW = 100 kHz.
- c) Set the VBW  $\geq 3 \times$  RBW.
- d) Detector = peak.
- e) Sweep time = auto couple.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use the peak marker function to determine the maximum amplitude level.


**Test Result : ALL emission outside of 2400-2483.5 are lower at least 20dB than fundamental frequency.**

### 9.3. TEST DATA






### 11B\_2437\_Reference




Date: 1.JUL.2019 13:06:18

### 11B\_2437\_30~26500




Date: 1.JUL.2019 13:07:02

### 11B\_2462\_Reference




Date: 1.JUL.2019 14:52:20

### 11B\_2462\_30~26500




Date: 1.JUL.2019 14:53:04

### 11G\_2412\_0~Reference




Date: 2.JUL.2019 11:20:59

### 11G\_2412\_30~26500




Date: 2.JUL.2019 11:21:43

### 11G\_2437\_Reference




Date: 2.JUL.2019 11:32:36

### 11G\_2437 30~26500




Date: 2.JUL.2019 11:33:20

### 11G\_2462\_Reference




Date: 2.JUL.2019 11:37:27

### 11G\_2462\_30~26500




Date: 2.JUL.2019 11:38:11

### 11N20\_2412\_Reference




Date: 2.JUL.2019 11:53:17

### 11N20\_2412\_30~26500




Date: 2.JUL.2019 11:54:01

### 11N20\_2437\_Reference




Date: 2.JUL.2019 11:59:23

### 11N20\_2437\_30~26500




Date: 2.JUL.2019 12:00:07

### 11N20\_2462\_Reference



Date: 2.JUL.2019 12:04:33


### 11N20\_2462\_30~26500



Date: 2.JUL.2019 12:05:17




### 11N40\_2422\_Reference




Date: 2.JUL.2019 12:24:02

### 11N40\_2422\_30~26500




Date: 2.JUL.2019 12:24:46

### 11N40\_2437\_Reference




Date: 2.JUL.2019 12:33:06

### 11N40\_2437\_30~26500




Date: 2.JUL.2019 12:33:50

### 11N40\_2452\_Reference



Date: 2.JUL.2019 12:40:25


### 11N40SISO\_Ant1\_2452\_30~26500



Date: 2.JUL.2019 12:41:09


### Band-edge for RF Conducted Emissions

#### 11B\_Low\_2412




Date: 1.JUL.2019 12:50:16

#### 11B\_High\_2462




Date: 1.JUL.2019 14:51:10

### 11G\_Low\_2412




Date: 2.JUL.2019 11:19:42

### 11G\_High\_2462




Date: 2.JUL.2019 11:36:12

### 11N20\_Low\_2412




Date: 2.JUL.2019 11:50:01

### 11N20\_High\_2462




Date: 2.JUL.2019 12:03:19

### 11N40\_Low\_2422



Date: 2.JUL.2019 12:17:41

### 11N40\_High\_2452



Date: 2.JUL.2019 12:37:44

## 10. RADIATED BANDEDGE AND SPURIOUS MEASUREMENT

### 10.1. LIMITS OF Radiated Bandedge and Spurious Measurement

Table 10 Radiation Emission Test Limit for FCC (9KHz-1GHz)

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
960~1000	500	3

Table 11 Radiation Emission Test Limit for FCC (Above 1G)

Frequency (MHz)	(dBuV/m) (at 3 meters)	
	PEAK	AVERAGE
Above 1000	74	54

\* The lower limit shall apply at the transition frequency.

\* The test distance is 3m.

### 10.2. TEST PROCEDURE

ANSI C63.10-2013 Clause 11.12

1. The testing follows the guidelines in ANSI C63.10-2013.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. For measurement below 1GHz, the EUT was placed on a turntable with 0.8 meter, above ground. For measurement above 1 GHz, test at FAR, the EUT is placed on a non-conductive table, which is 1.5 meter above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
7. Use the following spectrum analyzer settings:
  - (1) Span shall wide enough to fully capture the emission being measured;
  - (2) Set RBW=100 kHz for  $f < 1$  GHz; VBW  $\geq$  RBW; Sweep = auto; Detector



function = peak; Trace = max hold;  
 (3) Set RBW = 1 MHz, VBW= 3MHz for f > 1 GHz for peak measurement.  
 Set RBW = 1 MHz, and 1/T (on time) for average measurement.

### 10.3.TEST DATA

Adaptor: 1#  
 9kHz-30MHz

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

Table 12 Radiated Emission Test Data 9k Hz-30MHz

Frequency MHz	Cable Loss(dB)	Antenna Factor(dB)	Readings(dBµV/m)	Level(dBµV/m)	Polarity(H/V)	Turntable Angle(deg)	Antenna Height(m)	Limits(dBµV/m)	Margin(dB)
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--

30MHz-1GHz

Worst case is shown below for 30MHz-1GHz only.

The emissions don't show in following result tables are more than 20dB below the limits.

Table 13 Radiated Emission Test Data 30MHz-1GHz

Frequency (MHz)	Cable Loss +preamp (dB)	Antenna Factor (dB)	Readings (dBµV/m)	Level (dBµV/m)	Polarity (H/V)	Limits (dBµV/m)	Margin (dB)	Note
42.416	0.8	13.6	6.7	21.1	H	40	18.9	QP
48.915	0.7	13.6	7.1	21.4	H	40	18.6	QP
98.967	1.1	12.8	6.8	20.7	H	43.5	22.8	QP
148.146	1.4	10.5	8.5	20.4	H	43.5	23.1	QP
264.061	1.9	12.1	9.1	23.1	H	46	22.9	QP
558.844	2.9	16.6	8.7	28.2	H	46	17.8	QP
33.201	0.7	12.3	11.8	24.8	V	40	15.2	QP
38.148	0.7	12.3	15.6	28.6	V	40	11.4	QP
53.474	0.7	13.3	8.6	22.6	V	40	17.4	QP
93.729	1.1	11.9	7.7	20.7	V	43.5	22.8	QP
146.109	1.4	10.5	9.7	21.6	V	43.5	21.9	QP
190.341	1.6	10.6	9.9	22.1	V	43.5	21.4	QP

Adaptor: 2#

9kHz-30MHz

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

Table 14 Radiated Emission Test Data 9k Hz-30MHz

Frequency MHz	Cable Loss(dB)	Antenna Factor(dB)	Readings(dBμV/m)	Level(dBμV/m)	Polarity(H/V)	Turntable Angle(deg)	Antenna Height(m)	Limits(dBμV/m)	Margin(dB)
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--

30MHz-1GHz

Worst case is shown below for 30MHz-1GHz only.

The emissions don't show in following result tables are more than 20dB below the limits.

Table 15 Radiated Emission Test Data 30MHz-1GHz


Frequency (MHz)	Cable Loss +preamp (dB)	Antenna Factor (dB)	Readings (dBμV/m)	Level (dBμV/m)	Polarity (H/V)	Limits (dBμV/m)	Margin (dB)	Note
30.291	0.6	12.3	10.9	23.8	V	40	16.2	QP
33.201	0.7	12.3	11.4	24.4	V	40	15.6	QP
38.730	0.7	12.3	10.7	23.7	V	40	16.3	QP
171.814	1.5	9.0	16.4	26.9	V	43.5	16.6	QP
197.422	1.7	10.6	18.5	30.8	V	43.5	12.7	QP
206.734	1.7	10.6	16.0	28.3	V	43.5	15.2	QP
41.543	0.7	13.6	1.5	15.8	H	40	24.2	QP
57.259	0.8	13.0	2.3	16.1	H	40	23.9	QP
103.041	1.2	13.2	2.9	17.3	H	43.5	26.2	QP
149.116	1.5	10.5	10.5	22.5	H	43.5	21.0	QP
242.527	1.8	12.1	11.0	24.9	H	46.0	21.1	QP
268.329	2.0	12.1	8.3	22.4	H	46.0	23.6	QP

Remark: Emission level (dBuV)=Read Value(dBuV/m) + Antenna Factor(dB)+ Cable Loss +preamp(dB)

## Radiated Emission


EUT Name: FX205F  
Operating Condition: Charging and Transmitting  
Test site: SMQ NETC EMC Lab.  
Antenna Position: Vertical & Horizontal  
Comment: AC 120V/60Hz  
Adaptor: 1#

Field strength 30M-1GHz 1F 3m chamber



(Horizontal)

Field strength 30M-1GHz 1F 3m chamber




(Vertical)

## Radiated Emission


EUT Name: FX205F  
Operating Condition: Charging and Transmitting  
Test site: SMQ NETC EMC Lab.  
Antenna Position: Vertical & Horizontal  
Comment: AC 120V/60Hz  
Adaptor: 2#

Field strength 30M-1GHz 1F 3m chamber



(Horizontal)

Field strength 30M-1GHz 1F 3m chamber



(Vertical)

1-18G

11b

Ch1


## Radiated Emission

### EUT Information

EUT Model Name: FX205F  
Operation mode: Wifi 11b CH1  
Test Voltage:  
Comment:

### Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Horizontal  
Operator Name:  
Comment:




# Radiated Emission

## EUT Information

EUT Model Name: FX205F  
Operation mode: Wifi 11b CH1  
Test Voltage:  
Comment:

## Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Vertical  
Operator Name:  
Comment:



1-18G

11b

CH6


## Radiated Emission

### EUT Information

EUT Model Name: FX205F  
Operation mode: Wifi 11b CH6  
Test Voltage:  
Comment:

### Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Horizontal  
Operator Name:  
Comment:




# Radiated Emission

## EUT Information

EUT Model Name: FX205F  
Operation mode: Wifi 11b CH6  
Test Voltage:  
Comment:

## Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Vertical  
Operator Name:  
Comment:





1-18G

11b

CH11


## Radiated Emission

### EUT Information

EUT Model Name: FX205F  
Operation mode: Wifi 11b CH11  
Test Voltage:  
Comment:

### Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Horizontal  
Operator Name:  
Comment:




# Radiated Emission

## EUT Information

EUT Model Name: FX205F  
Operation mode: Wifi 11b CH11  
Test Voltage:  
Comment:

## Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Vertical  
Operator Name:  
Comment:



1-18G

11g

CH1


## Radiated Emission

### EUT Information

EUT Model Name: FX205F  
Operation mode: Wifi 11g CH1  
Test Voltage:   
Comment:

### Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Horizontal  
Operator Name:  
Comment:




# Radiated Emission

## EUT Information

EUT Model Name: FX205F  
Operation mode: Wifi 11g CH1  
Test Voltage:  
Comment:

## Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Vertical  
Operator Name:  
Comment:



1-18G

11g

CH6


## Radiated Emission

### EUT Information

EUT Model Name: FX205F  
Operation mode: Wifi 11g CH6  
Test Voltage:  
Comment:

### Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Horizontal  
Operator Name:  
Comment:




# Radiated Emission

## EUT Information

EUT Model Name: FX205F  
Operation mode: Wifi 11g CH6  
Test Voltage:  
Comment:

## Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Vertical  
Operator Name:  
Comment:



1-18G

11g

CH11


## Radiated Emission

### EUT Information

EUT Model Name: FX205F  
Operation mode: Wifi 11g CH11  
Test Voltage:  
Comment:

### Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Horizontal  
Operator Name:  
Comment:




# Radiated Emission

## EUT Information

EUT Model Name: M FX205F  
Operation mode: Wifi 11g CH11  
Test Voltage:  
Comment:

## Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Vertical  
Operator Name:  
Comment:





1-18G  
11n-HT20  
CH1


## Radiated Emission

### EUT Information

EUT Model Name: FX205F  
Operation mode: 11n HT20 CH1  
Test Voltage:  
Comment:

### Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Horizontal  
Operator Name:  
Comment:




# Radiated Emission

## EUT Information

EUT Model Name: FX205F  
Operation mode: Wifi 11n HT20 CH1  
Test Voltage:  
Comment:

## Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Vertical  
Operator Name:  
Comment:



1-18G  
11n-HT20  
CH6


## Radiated Emission

### EUT Information

EUT Model Name: FX205F  
Operation mode: Wifi 11n HT20 CH6  
Test Voltage:  
Comment:

### Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Horizontal  
Operator Name:  
Comment:




# Radiated Emission

## EUT Information

EUT Model Name: FX205F  
Operation mode: 11n HT20 CH6  
Test Voltage:  
Comment:

## Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Vertical  
Operator Name:  
Comment:



1-18G  
11n-HT20  
CH11


## Radiated Emission

### EUT Information

EUT Model Name: FX205F  
Operation mode: 11n HT20 CH11  
Test Voltage:  
Comment:

### Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Horizontal  
Operator Name:  
Comment:




# Radiated Emission

## EUT Information

EUT Model Name: FX205F  
Operation mode: 11n HT20 CH11  
Test Voltage:  
Comment:

## Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Vertical  
Operator Name:  
Comment:



1-18G  
11n-HT40  
CH3


## Radiated Emission

### EUT Information

EUT Model Name: FX205F  
Operation mode: 11n HT40 CH3  
Test Voltage:   
Comment:

### Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Horizontal  
Operator Name:  
Comment:




# Radiated Emission

## EUT Information

EUT Model Name: FX205F  
Operation mode: 11n HT40 CH3  
Test Voltage:  
Comment:

## Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Vertical  
Operator Name:  
Comment:





1-18G  
11n-HT40  
CH6


## Radiated Emission

### EUT Information

EUT Model Name: FX205F  
Operation mode: 11n HT40 CH6  
Test Voltage:  
Comment:

### Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Horizontal  
Operator Name:  
Comment:




# Radiated Emission

## EUT Information

EUT Model Name: FX205F  
Operation mode: 11n HT40 CH6  
Test Voltage:  
Comment:

## Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Vertical  
Operator Name:  
Comment:



1-18G  
11n-HT40  
CH9


## Radiated Emission

### EUT Information

EUT Model Name: FX205F  
Operation mode: 11n HT40 CH9  
Test Voltage:  
Comment:

### Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Horizontal  
Operator Name:  
Comment:




# Radiated Emission

## EUT Information

EUT Model Name: FX205F  
Operation mode: 11n HT40 CH9  
Test Voltage:  
Comment:

## Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Vertical  
Operator Name:  
Comment:



18-26.5G  
(Worst Case at 802.11b CH6)


## Radiated Emission

### EUT Information

EUT Model Name: FX205F  
Operation mode: Wifi 11b CH6  
Test Voltage:  
Comment:

### Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Horizontal  
Operator Name:  
Comment:




# Radiated Emission

## EUT Information

EUT Model Name: FX205F  
Operation mode: Wifi 11b CH6  
Test Voltage:  
Comment:

## Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Vertical  
Operator Name:  
Comment:



Band edge

11b

CH1


## Radiated Emission

### EUT Information

EUT Model Name: FX205F  
Operation mode: Wifi 11b CH1  
Test Voltage:  
Comment:

### Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Horizontal  
Operator Name:  
Comment:




# Radiated Emission

## EUT Information

EUT Model Name: FX205F  
Operation mode: Wifi 11b CH1  
Test Voltage:  
Comment:

## Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Vertical  
Operator Name:  
Comment:






# Radiated Emission

## EUT Information

EUT Model Name: FX205F  
Operation mode: Wifi 11b CH1  
Test Voltage:  
Comment:

## Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Horizontal  
Operator Name:  
Comment:




# Radiated Emission

## EUT Information

EUT Model Name: FX205F  
Operation mode: Wifi 11b CH1  
Test Voltage:  
Comment:

## Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Vertical  
Operator Name:  
Comment:



Band edge

11g

CH1


## Radiated Emission

### EUT Information

EUT Model Name: FX205F  
Operation mode: Wifi 11g CH1  
Test Voltage:   
Comment:

### Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Horizontal  
Operator Name:  
Comment:




# Radiated Emission

## EUT Information

EUT Model Name: FX205F  
Operation mode: Wifi 11g CH1  
Test Voltage:  
Comment:

## Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Vertical  
Operator Name:  
Comment:




# Radiated Emission

## EUT Information

EUT Model Name: FX205F  
Operation mode: Wifi 11g CH1  
Test Voltage:  
Comment:

## Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Horizontal  
Operator Name:  
Comment:




# Radiated Emission

## EUT Information

EUT Model Name: FX205F  
Operation mode: Wifi 11g CH1  
Test Voltage:  
Comment:

## Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Vertical  
Operator Name:  
Comment:



Band edge

11n-HT20

CH1


## Radiated Emission

### EUT Information

EUT Model Name: FX205F  
Operation mode: Wifi 11n HT20 CH1  
Test Voltage:  
Comment:

### Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Horizontal  
Operator Name:  
Comment:




# Radiated Emission

## EUT Information

EUT Model Name: FX205F  
Operation mode: Wifi 11n HT20 CH1  
Test Voltage:  
Comment:

## Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Vertical  
Operator Name:  
Comment:






# Radiated Emission

## EUT Information

EUT Model Name: FX205F  
Operation mode: Wifi 11n HT20 CH1  
Test Voltage:  
Comment:

## Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Horizontal  
Operator Name:  
Comment:




# Radiated Emission

## EUT Information

EUT Model Name: FX205F  
Operation mode: Wifi 11n HT20 CH1  
Test Voltage:  
Comment:

## Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Vertical  
Operator Name:  
Comment:



Band edge

11n-HT40

CH3


## Radiated Emission

### EUT Information

EUT Model Name: FX205F  
Operation mode: Wifi 11n HT40 CH3  
Test Voltage:   
Comment:

### Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Horizontal  
Operator Name:  
Comment:




# Radiated Emission

## EUT Information

EUT Model Name: FX205F  
Operation mode: Wifi 11n HT40 CH3  
Test Voltage:  
Comment:

## Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Vertical  
Operator Name:  
Comment:




# Radiated Emission

## EUT Information

EUT Model Name: FX205F  
Operation mode: Wifi 11n HT40 CH3  
Test Voltage:  
Comment:

## Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Horizontal  
Operator Name:  
Comment:




# Radiated Emission

## EUT Information

EUT Model Name: FX205F  
Operation mode: Wifi 11n HT40 CH3  
Test Voltage:  
Comment:

## Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Vertical  
Operator Name:  
Comment:



Band edge

11b

CH11


## Radiated Emission

### EUT Information

EUT Model Name: FX205F  
Operation mode: Wifi 11b CH11  
Test Voltage:  
Comment:

### Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Horizontal  
Operator Name:  
Comment:




# Radiated Emission

## EUT Information

EUT Model Name: FX205F  
Operation mode: Wifi 11b CH11  
Test Voltage:  
Comment:

## Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Vertical  
Operator Name:  
Comment:






# Radiated Emission

## EUT Information

EUT Model Name: FX205F  
Operation mode: Wifi 11b CH11  
Test Voltage:  
Comment:

## Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Horizontal  
Operator Name:  
Comment:




# Radiated Emission

## EUT Information

EUT Model Name: FX205F  
Operation mode: Wifi 11b CH11  
Test Voltage:  
Comment:

## Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Vertical  
Operator Name:  
Comment:



Band edge

11g

CH11


## Radiated Emission

### EUT Information

EUT Model Name: FX205F  
Operation mode: Wifi 11g CH11  
Test Voltage:  
Comment:

### Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Horizontal  
Operator Name:  
Comment:




# Radiated Emission

## EUT Information

EUT Model Name: FX205F  
Operation mode: Wifi 11g CH11  
Test Voltage:  
Comment:

## Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Vertical  
Operator Name:  
Comment:




# Radiated Emission

## EUT Information

EUT Model Name: FX205F  
Operation mode: Wifi 11g CH11  
Test Voltage:  
Comment:

## Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Horizontal  
Operator Name:  
Comment:




# Radiated Emission

## EUT Information

EUT Model Name: FX205F  
Operation mode: Wifi 11g CH11  
Test Voltage:  
Comment:

## Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Vertical  
Operator Name:  
Comment:



Band edge

11n-HT20

CH11


## Radiated Emission

### EUT Information

EUT Model Name: FX205F  
Operation mode: Wifi 11n HT20 CH11  
Test Voltage:  
Comment:

### Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Horizontal  
Operator Name:  
Comment:




# Radiated Emission

## EUT Information

EUT Model Name: FX205F  
Operation mode: Wifi 11n HT20 CH11  
Test Voltage:  
Comment:

## Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Vertical  
Operator Name:  
Comment:






# Radiated Emission

## EUT Information

EUT Model Name: FX205F  
Operation mode: Wifi 11n HT20 CH11  
Test Voltage:  
Comment:

## Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Horizontal  
Operator Name:  
Comment:




# Radiated Emission

## EUT Information

EUT Model Name: FX205F  
Operation mode: Wifi 11n HT20 CH11  
Test Voltage:  
Comment:

## Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Vertical  
Operator Name:  
Comment:



Band edge

11n-HT40

CH9


## Radiated Emission

### EUT Information

EUT Model Name: FX205F  
Operation mode: Wifi 11n HT40 CH9  
Test Voltage:  
Comment:

### Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Horizontal  
Operator Name:  
Comment:




# Radiated Emission

## EUT Information

EUT Model Name: FX205F  
Operation mode: Wifi 11n HT20 CH11  
Test Voltage:  
Comment:

## Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Vertical  
Operator Name:  
Comment:




# Radiated Emission

## EUT Information

EUT Model Name: FX205F  
Operation mode: Wifi 11n HT20 CH11  
Test Voltage:  
Comment:

## Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Horizontal  
Operator Name:  
Comment:




# Radiated Emission

## EUT Information

EUT Model Name: FX205F  
Operation mode: Wifi 11n HT20 CH11  
Test Voltage:  
Comment:

## Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Vertical  
Operator Name:  
Comment:



# 11. CONDUCTED EMISSION TEST FOR AC POWER PORT MEASUREMENT

## 11.1. Test Standard and Limit

### 11.1.1. Test Standard

FCC Part 15 15.207

### 11.1.2. Test Limit

Table 16 Conducted Disturbance Test Limit

Frequency	Maximum RF Line Voltage (dB $\mu$ V)	
	Quasi-peak Level	Average Level
150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
500kHz~5MHz	56	46
5MHz~30MHz	60	50

\* Decreasing linearly with logarithm of the frequency

\* The lower limit shall apply at the transition frequency.

## 11.2. Test Procedure

The EUT is put on a table of non-conducting material that is 80cm high. The vertical conducting wall of shielding is located 40cm to the rear of the EUT. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.). A EMI test receiver (R&S Test Receiver ESCS30) is used to test the emissions form both sides of AC line. According to the requirements of ANSI C63.10-2013. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-Peak and average detector mode.

The bandwidth of EMI test receiver is set at 9kHz.

## 11.3. Test Arrangement

The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application. The detailed information refers to test picture.

## 11.4. Test Data

The emissions don't show in below are too low against the limits. Refer to the test curves.

**Table 17 Conducted Emission Test Data**

Model No.: FX205F								
Test mode: Charging and Transmitting								
Adaptor:1#								
	Frequency (MHz)	Correction Factor (dB)	Quasi-Peak			Average		
			Reading (dBµV)	Emission Level (dBµV)	Limits (dBµV)	Reading (dBµV)	Emission Level (dBµV)	Limits (dBµV)
Line	0.150	9.7	37.0	46.7	66	20.6	30.3	56
	0.178	9.7	37.8	47.5	64.6	22.2	31.9	54.6
	0.214	9.7	35.5	45.2	63.0	18.9	28.6	53.0
	0.510	9.8	36.7	46.5	56	19.6	29.4	46
	0.582	9.8	37.2	47.0	56	20.0	29.8	46
	0.950	9.8	31.7	41.5	56	16.8	26.6	46
Neutral	0.150	9.7	36.2	45.9	66	18.8	28.5	56
	0.178	9.7	35.5	45.2	64.6	19.3	29.0	54.6
	0.546	9.8	35.1	44.9	56	17.6	27.4	46
	0.582	9.8	33.9	43.7	56	16.3	26.1	46
	2.646	9.9	27.9	37.8	56	14.2	24.1	46
	10.368	9.9	27.3	37.2	60	13.5	23.4	50

**Table 18 Conducted Emission Test Data**


Model No.: FX205F								
Test mode: Charging and Transmitting								
Adaptor:2#								
	Frequency (MHz)	Correction Factor (dB)	Quasi-Peak			Average		
			Reading (dBµV)	Emission Level (dBµV)	Limits (dBµV)	Reading (dBµV)	Emission Level (dBµV)	Limits (dBµV)
Line	0.150	9.7	37.8	47.5	66	20.3	30.0	56
	0.218	9.7	34.2	43.9	62.9	19.5	29.2	52.9
	0.290	9.7	31.8	41.5	60.5	16.2	25.9	50.5
	0.654	9.8	35.7	45.5	56	25.5	35.3	46
	2.730	9.9	30.5	40.4	56	18.2	28.1	46
	13.412	9.9	29.7	39.6	60	15.7	26.5	50
	18.052	9.9	30.7	40.6	60	19.1	29.0	50
Neutral	0.166	9.7	32.0	41.7	65.2	15.1	24.8	55.2
	0.674	9.8	27.8	37.6	56	17.4	27.2	46
	0.730	9.8	31.1	40.9	56	19.2	29.0	46
	2.786	9.9	27.0	36.9	56	15.3	25.2	46
	13.600	9.9	28.1	38.0	60	14.6	24.5	50




	18.972	9.9	31.7	41.6	60	18.3	28.2	50
--	--------	-----	------	------	----	------	------	----

- REMARKS: 1. Emission level (dBuV) =Read Value (dBuV) + Correction Factor (dB)
2. Correction Factor (dB) =LISN Factor (dB) + Cable Factor (dB) +Limiter Factor (dB)
3. The other emission levels were very low against the limit.


EUT: FX205F  
Manufacturer:  
Operating Condition: Charging and Transmitting  
Test Site:  
Operator:  
Test Specification: L  
Comment: AC 120V/60Hz  
Adaptor: 1#




EUT: FX205F  
Manufacturer:  
Operating Condition: Charging and Transmitting  
Test Site:  
Operator:  
Test Specification: N  
Comment: AC 120V/60Hz  
Adaptor: 1#



EUT: FX205F  
Manufacturer:  
Operating Condition: Charging and Transmitting  
Test Site:  
Operator:  
Test Specification: L  
Comment: AC 120V/60Hz  
Adaptor: 2#



EUT: FX205F  
Manufacturer:  
Operating Condition: Charging and Transmitting  
Test Site:  
Operator:  
Test Specification: N  
Comment: AC 120V/60Hz  
Adaptor: 2#



## 12. ANTENNA REQUIREMENTS

According to Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

The EUT has a built in antenna which is integrated inside the enclosure, this is permanently attached antenna and meets the requirements of this section.

END OF REPORT