

# RF Exposure Evaluation

## FCC ID: 2AGUA-EXPLORERS

### 1. Client Information

**Applicant** : HK ELEPHONE COMMUNICATION TECH CO.,LIMITED  
**Address** : UNIT 04, 7/F BRIGHT WAY TOWER NO.33 MONG KOK RD KL, HONGKONG  
**Manufacturer** : HK ELEPHONE COMMUNICATION TECH CO.,LIMITED  
**Address** : UNIT 04, 7/F BRIGHT WAY TOWER NO.33 MONG KOK RD KL, HONGKONG

### 2. General Description of EUT

<b>EUT Name</b>	:	Action camera
<b>Models No.</b>	:	Explorer S
<b>Model Difference</b>	:	N/A
<b>Product Description</b>	Operation Frequency:	802.11b/g/n(HT20): 2412MHz~2462MHz
	Number of Channel:	802.11b/g/n(HT20):11 channels <b>see note(3)</b>
	RF Output Power:	802.11b: 9.34 dBm 802.11g: 9.15 dBm 802.11n (HT20): 9.13 dBm
	Antenna Gain:	2.11 dBi Internal Antenna
	Modulation Type:	802.11b: DSSS(CCK, DQPSK, DBPSK) 802.11g/n:OFDM(BPSK,QPSK,16QAM, 64QAM)
	Bit Rate of Transmitter:	802.11b:11/5.5/2/1 Mbps 802.11g:54/48/36/24/18/12/9/6 Mbps 802.11n:up to 150Mbps
<b>Power Supply</b>	:	DC power by USB cable. DC power by Li-ion battery.
<b>Power Rating</b>	:	DC 5.0V by USB cable. DC 3.7V by 900mAh Li-ion battery.
<b>Connecting I/O Port(S)</b>	:	Please refer to the User's Manual

**Note:** More test information about the EUT please refer the RF Test Report.



## SAR Test Exclusion Calculations

1. FCC: According to KDB 447498 D01 Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies v06.

(1) Clause 4.3: General SAR test reduction and exclusion guidance

Sub clause 4.31: Standalone SAR test exclusion considerations

1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6GHz at test separation distance  $\leq 5$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation, mm})] * [\sqrt{f_{(\text{GHz})}}] \leq 3.0$  for 1-g SAR

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation, mm})] * [\sqrt{f_{(\text{GHz})}}] \leq 7.5.0$  for 10-g SAR

2. Calculation:

Test separation: 5mm						
WiFi Mode(802.11b)						
Frequency (GHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (dbm)	Max power of tune up tolerance (mw)	Calculation Value	Threshold Value
2.412	9.34	9±0.5	9.5	8.913	2.768	3.0
2.437	9.28	9±0.5	9.5	8.913	2.783	3.0
2.462	9.31	9±0.5	9.5	8.913	2.797	3.0
WiFi Mode(802.11g)						
Frequency (GHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (dbm)	Max power of tune up tolerance (mw)	Calculation Value	Threshold Value
2.412	9.12	9±0.5	9.5	8.913	2.768	3.0
2.437	9.08	9±0.5	9.5	8.913	2.783	3.0
2.462	9.15	9±0.5	9.5	8.913	2.797	3.0
WiFi Mode(802.11n(HT20))						
Frequency (GHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (dbm)	Max power of tune up tolerance (mw)	Calculation Value	Threshold Value
2.412	9.09	9±0.5	9.5	8.913	2.768	3.0
2.437	9.13	9±0.5	9.5	8.913	2.783	3.0
2.462	9.06	9±0.5	9.5	8.913	2.797	3.0

So standalone SAR measurements are not required.

-----END OF REPORT-----