## FCC ID: 2AGV5-OJBCR701YZ

### **RF EXPOSURE EVALUATION**

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) Radiation as specified in §1.1307(b)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)							
(A) Limits for Occupational/Controlled Exposure											
0.3-3.0	614	1.63	*100	6							
3.0-30	1842/1	4.89/1	*900/f <sup>2</sup>	6							
30-300	61.4	0.163	1.0	6							
300-1,500			f/300	6							
1,500-100,000			5	6							
(B) Limits for General Population/Uncontrolled Exposure											
0.3-1.34	614	1.63	*100	30							
1.34-30	824/1	2.19/1	*180/f <sup>2</sup>	30							
30-300	27.5	0.073	0.2	30							
300-1,500			f/1500	30							
1,500-100,000			1.0	30							

f = frequency in MHz \* = Plane-wave equivalent power density

#### MPE Calculation Method

Friis transmission formula:  $Pd=(Pout^*G) \setminus (4^*pi^*R^2)$ Where Pd= Power density in mW/cm<sup>2</sup> Pout=output power to antenna in mW G= Numeric gain of the antenna relative to isotropic antenna

Pi=3.14115926

R= distance between observation point and center of the radiator in cm(20cm)

Pd the limit of MPE, 1mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

# Measurement Result WIFI:

Operation Frequency: Zigbee: 2405MHz~2480MHz Power density limited: 1mW/ cm<sup>2</sup> Antenna Type: PCB Antenna; Antenna gain: 1dBi; R=20cm mW=10^(dBm/10) Antenna gain Numeric=10^(dBi/10)= 10^(1/10)=1.26

Channel Freq. (MHz)	modulation	conducted power	Tune-up power	Мах		Antenna	Evaluation result at 20cm	Power density Limits
		(dBm)	(dBm)	tune-up power		Gain	Power	
				(dBm)	(mW)	Numeric	density(m	(mW/cm2)
2405		-3.38	-4±1	-3	0.5011872	1.26	0.00013	1
2440	Zigbee	-4.09	-4±1	-3	0.5011872	1.26	0.00013	1
2480		-4.51	-4±1	-3	0.5011872	1.26	0.00013	1

#### Conclusion:

For the max result :  $0.0005011872 \le 1.0 \text{ mW/ cm}^2$ , No SAR is required. Compliance Rf exposure evaluation.

Jason chen

Signature:

**Date:** 2017-09-05

NAME AND TITLE (Please print or type): Jason Chen/Manager

**COMPANY** (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen 518126P.R. China.