

## MPE ESTIMATION

FCC ID: 2AGZ8DRW243R

### 1. Limit for Portable Equipment Exposure

Frequency	1-g SAR
100MHz-6GHz	3.0

According to 447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR.

Where  $f(\text{GHz})$  is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

### 2. Estimation Result

Frequency	Reading result(dB $\mu$ V/m)	PK Output Power (dBm)	Output Power(mW)	Test Separation Distance (mm)	Measurement Result	1-g SAR
GFSK 2458 MHz	94.79	-0.41	0.91	5	0.2853	3.0

Note: PK Output Power (dBm)= Reading result(dB $\mu$ V/m)-95.2  
Reading result see the test report 23062905ER-61.

The SAR evaluation is not required.

-----The End-----