

# FCC RADIO TEST REPORT

**FCC ID: 2AGZ8DRW313**

**Sample : RC DRONE**

**Trade Mark : N/A**

**Main Model : DRW313**

**Additional Model : N/A**

**Report No. : UNIA24060318ER-61**

**Prepared for**

**DOWELLIN TOYS FACTORY**

**1 Road FengXin ChengHai District, ShanTou City,GuangDong, China**

**Prepared by**

**Shenzhen United Testing Technology Co., Ltd.**

**D101&D401, No. 107, Kaicheng High-Tech Park, Taoyuan Community,  
Dalang Sub-District, Longhua District, Shenzhen, Guangdong, China**

## TEST RESULT CERTIFICATION

**Applicant** ..... : DOWELLIN TOYS FACTORY  
**Address** ..... : 1 Road FengXin ChengHai District, ShanTou City,GuangDong,  
China

**Manufacturer** ..... : DOWELLIN TOYS FACTORY  
**Address** ..... : 1 Road FengXin ChengHai District, ShanTou City,GuangDong,  
China

### Product description

**Product** ..... : RC DRONE  
**Trade Mark** ..... : N/A  
**Model Name** ..... : DRW313

**Test Methods** ..... : FCC Rules and Regulations Part 15 Subpart C Section 15.249,  
ANSI C63.10: 2013

This device described above has been tested by Shenzhen United Testing Technology Co., Ltd., and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report. This report shall not be reproduced except in full, without the written approval, this document may be altered or revised by Shenzhen United Testing Technology Co., Ltd., personnel only, and shall be noted in the revision of the document.

### Date of Test

**Date (s) of performance of tests** ..... : Jul. 05, 2024 ~ Jul. 16, 2024  
**Date of Issue** ..... : Jul. 17, 2024  
**Test Result** ..... : Pass

Prepared by:

Jason Ye/Editor

Reviewer:

Kelly Cheng/Supervisor

Approved & Authorized Signer:

Liuze/Manager

Table of Contents

Page

|  |           |
|--|-----------|
| <b>1 TEST SUMMARY .....</b>                              | <b>4</b>  |
| <b>2 GENERAL INFORMATION .....</b>                       | <b>6</b>  |
| 2.1 GENERAL DESCRIPTION OF EUT .....                     | 6         |
| 2.2 CARRIER FREQUENCY OF CHANNELS .....                  | 7         |
| 2.3 TEST MODE .....                                      | 7         |
| 2.4 TEST SETUP .....                                     | 8         |
| 2.5 DESCRIPTION TEST PERIPHERAL AND EUT PERIPHERAL ..... | 8         |
| 2.6 MEASUREMENT INSTRUMENTS LIST .....                   | 9         |
| <b>3 CONDUCTED EMISSION .....</b>                        | <b>10</b> |
| 3.1 TEST LIMIT .....                                     | 10        |
| 3.2 TEST SETUP .....                                     | 10        |
| 3.3 TEST PROCEDURE .....                                 | 11        |
| 3.4 TEST RESULT .....                                    | 11        |
| <b>4 RADIATED EMISSION .....</b>                         | <b>12</b> |
| 4.1 TEST LIMIT .....                                     | 12        |
| 4.2 TEST SETUP .....                                     | 13        |
| 4.3 TEST PROCEDURE .....                                 | 14        |
| 4.4 TEST RESULT .....                                    | 14        |
| <b>5 BAND EDGE .....</b>                                 | <b>20</b> |
| 5.1 TEST LIMIT .....                                     | 20        |
| 5.2 TEST PROCEDURE .....                                 | 20        |
| 5.3 TEST RESULT .....                                    | 20        |
| <b>6 20DB BANDWIDTH .....</b>                            | <b>23</b> |
| 6.1 TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION) .....    | 23        |
| 6.2 MEASUREMENT EQUIPMENT USED .....                     | 23        |
| 6.3 TEST PROCEDURE .....                                 | 23        |
| 6.4 TEST RESULT .....                                    | 23        |
| <b>7 ANTENNA REQUIREMENT .....</b>                       | <b>26</b> |
| <b>8 PHOTO OF TEST .....</b>                             | <b>27</b> |
| 8.1 RADIATED EMISSION .....                              | 27        |
| 8.2 RF CONDUCTED .....                                   | 28        |

# 1 TEST SUMMARY

## 1.1 TEST PROCEDURES AND RESULTS

| ITEM                | STANGARD               | RESULT    |
|---------------------|------------------------|-----------|
| CONDUCTED EMISSION  | FCC Part 15.207        | N/A       |
| RADIATED EMISSION   | FCC Part 15.209/15.249 | COMPLIANT |
| BAND EDGE           | FCC Part 15.249/15.205 | COMPLIANT |
| 20dB BANDWIDTH      | FCC Part 15.215        | COMPLIANT |
| ANTENNA REQUIREMENT | FCC Part 15.203        | COMPLIANT |

## 1.2 TEST FACILITY

Test Firm : Shenzhen United Testing Technology Co., Ltd.  
 Address : D101&D401, No. 107, Kaicheng High-Tech Park, Taoyuan Community, Dalang Sub-District, Longhua District, Shenzhen, Guangdong, China

The testing quality ability of our laboratory meet with "Quality Law of People's Republic of China" Clause 19.The testing quality system of our laboratory meets with ISO/IEC-17025 requirements. This approval result is accepted by MRA of APLAC.

Our test facility is recognized, certified, or accredited by the following organizations:

A2LA Certificate Number: 4747.01

The EMC Laboratory has been accredited by A2LA, and in compliance with ISO/IEC 17025:2017 General Requirements for testing Laboratories.

FCC Registration Number: 674885

The EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications commission.

IC Registration Number: 31584

The EMC Laboratory has been registered and fully described in a report filed with the (IC) Industry Canada.

### 1.3 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement  $y \pm U$ , where expanded uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately 95 %.

**A. Conducted Measurement:**

| Test Site | Method | Measurement Frequency Range | U, (dB) | NOTE |
|-----------|--------|-----------------------------|---------|------|
| UNI       | ANSI   | 9kHz ~ 150kHz               | 2.96    |      |
|           |        | 150kHz ~ 30MHz              | 2.44    |      |

**B. Radiated Measurement:**

| Test Site | Method | Measurement Frequency Range | U, (dB) | NOTE |
|-----------|--------|-----------------------------|---------|------|
| UNI       | ANSI   | 9kHz ~ 30MHz                | 2.50    |      |
|           |        | 30MHz ~ 1000MHz             | 4.80    |      |
|           |        | Above 1000MHz               | 4.13    |      |

## 2 GENERAL INFORMATION

### 2.1 GENERAL DESCRIPTION OF EUT

|                                       |                      |
|---------------------------------------|----------------------|
| <b>Product:</b>                       | RC DRONE             |
| <b>Trade Mark:</b>                    | N/A                  |
| <b>Main Model:</b>                    | DRW313               |
| <b>Additional Model:</b>              | N/A                  |
| <b>Model Difference:</b>              | N/A                  |
| <b>FCC ID:</b>                        | 2AGZ8DRW313          |
| <b>Frequency Range:</b>               | 2455MHz-2475MHz      |
| <b>Number of Channels:</b>            | 21CH                 |
| <b>Field Strength of Fundamental:</b> | 85.80dBuV/m(Peak)@3m |
| <b>Modulation Type:</b>               | GFSK                 |
| <b>Antenna Type:</b>                  | Internal Antenna     |
| <b>Antenna Gain:</b>                  | 0.17dBi              |
| <b>Battery:</b>                       | DC 6V                |
| <b>Adapter:</b>                       | N/A                  |
| <b>Power Source:</b>                  | DC 6V from battery   |

## 2.2 CARRIER FREQUENCY OF CHANNELS

| Channel List |                 |         |                 |         |                 |         |                 |
|--------------|-----------------|---------|-----------------|---------|-----------------|---------|-----------------|
| Channel      | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) |
| 01           | 2455            | 07      | 2461            | 13      | 2467            | 19      | 2473            |
| 02           | 2456            | 08      | 2462            | 14      | 2468            | 20      | 2474            |
| 03           | 2457            | 09      | 2463            | 15      | 2469            | 21      | 2475            |
| 04           | 2458            | 10      | 2464            | 16      | 2470            |         |                 |
| 05           | 2459            | 11      | 2465            | 17      | 2471            |         |                 |
| 06           | 2460            | 12      | 2466            | 18      | 2472            |         |                 |

## 2.3 TEST MODE

The EUT was programmed to be in continuously transmitting mode.


| Channel List   |             |                      |
|----------------|-------------|----------------------|
| Test Channel   | EUT Channel | Test Frequency (MHz) |
| Low channel    | CH01        | 2455                 |
| Middle channel | CH11        | 2465                 |
| High channel   | CH21        | 2475                 |

## 2.4 TEST SETUP

Operation of EUT during Radiation testing:



Operation of EUT during RF Conducted testing:



## 2.5 DESCRIPTION TEST PERIPHERAL AND EUT PERIPHERAL

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

| Item | Equipment | Mfr/Brand | Model/Type No. | Note |
|------|-----------|-----------|----------------|------|
| E-1  | RC DRONE  | N/A       | DRW313         | EUT  |

Note:

1. The support equipment was authorized by Declaration of Confirmation.
2. For detachable type I/O cable should be specified the length in cm in 『Length』 column.
3. “YES” is means “shielded” “with core”; “NO” is means “unshielded” “without core”.



## 2.6 MEASUREMENT INSTRUMENTS LIST

| Item                           | Equipment                           | Manufacturer  | Model No.    | Serial No.    | Calibrated until |
|--------------------------------|-------------------------------------|---------------|--------------|---------------|------------------|
| Radiated Emissions Measurement |                                     |               |              |               |                  |
| 1                              | Radiated Emission Test Software     | EZ-EMC        | Ver.CCS-03A1 | N/A           | N/A              |
| 2                              | Horn Antenna                        | Sunol         | DRH-118      | A101415       | 2025.07.14       |
| 3                              | Broadband Hybrid Antenna            | Sunol         | JB1          | A090215       | 2025.07.28       |
| 4                              | PREAMP                              | HP            | 8449B        | 3008A00160    | 2025.06.11       |
| 5                              | PREAMP                              | HP            | 8447D        | 2944A07999    | 2025.06.11       |
| 6                              | EMI TEST RECEIVER                   | Rohde&Schwarz | ESR3         | 101891        | 2025.06.11       |
| 7                              | VECTOR Signal Generator             | Rohde&Schwarz | SMU200A      | 101521        | 2025.06.11       |
| 8                              | Signal Generator                    | Agilent       | E4421B       | MY4335105     | 2025.06.11       |
| 9                              | MXA Signal Analyzer                 | Agilent       | N9020A       | MY50510140    | 2025.06.11       |
| 10                             | MXA Signal Analyzer                 | Keysight      | N9020A       | MY51110104    | 2025.06.11       |
| 11                             | RF Power sensor                     | DARE          | RPR3006W     | 15I00041SNO88 | 2025.06.11       |
| 12                             | RF Power sensor                     | DARE          | RPR3006W     | 15I00041SNO89 | 2025.06.11       |
| 13                             | RF power divider                    | Anritsu       | K241B        | 992289        | 2025.06.11       |
| 14                             | Wideband radio communication tester | Rohde&Schwarz | CMW500       | 154987        | 2025.06.11       |
| 15                             | Active Loop Antenna                 | Com-Power     | AL-130R      | 10160009      | 2025.06.11       |
| 16                             | Broadband Hybrid Antennas           | Schwarzbeck   | VULB9163     | VULB9163#958  | 2024.09.22       |
| 17                             | Horn Antenna                        | Schwarzbeck   | BBHA9120D    | 9120D-1680    | 2025.07.14       |
| 18                             | Horn Antenna                        | A-INFOMW      | LB-180400-KF | J211060660    | 2025.07.14       |
| 19                             | Microwave Broadband Preamplifier    | Schwarzbeck   | BBV 9721     | 100472        | 2024.09.22       |
| 20                             | Signal Generator                    | Agilent       | N5183A       | MY47420153    | 2024.09.22       |
| 21                             | Spectrum Analyzer                   | Rohde&Schwarz | FSP 40       | 100501        | 2024.09.22       |
| 22                             | Power Meter                         | KEYSIGHT      | N1911A       | MY50520168    | 2024.09.22       |
| 23                             | Frequency Meter                     | VICTOR        | VC2000       | 997406086     | 2024.09.22       |
| 24                             | DC Power Source                     | HYELEC        | HY5020E      | 055161818     | 2024.09.22       |

### 3 CONDUCTED EMISSION

#### 3.1 TEST LIMIT


For unintentional device, according to § 15.207(a) Line Conducted Emission Limits is as following

| Frequency (MHz) | Maximum RF Line Voltage (dB $\mu$ V) |      |         |        |
|-----------------|--------------------------------------|------|---------|--------|
|                 | CLASS A                              |      | CLASS B |        |
|                 | Q.P.                                 | Ave. | Q.P.    | Ave.   |
| 0.15~0.50       | 79                                   | 66   | 66~56*  | 56~46* |
| 0.50~5.00       | 73                                   | 60   | 56      | 46     |
| 5.00~30.0       | 73                                   | 60   | 60      | 50     |

\* Decreasing linearly with the logarithm of the frequency.

For intentional device, according to §15.207(a) Line Conducted Emission Limit is same as above table.

#### 3.2 TEST SETUP



### 3.3 TEST PROCEDURE

1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is placed on a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10.
2. Support equipment, if needed, was placed as per ANSI C63.10.
3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
4. If a EUT received DC power from the USB Port of Notebook PC, the PC's adapter received AC120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
5. All support equipments received AC power from a second LISN, if any.
6. The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.

### 3.4 TEST RESULT

N/A

Remark:

The EUT is powered by battery.

## 4 RADIATED EMISSION

### 4.1 TEST LIMIT

For unintentional device, according to § 15.209(a), except for Class B digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

| Frequency         | Field strength (microvolt/meter) | Limit (dBuV/m ) | Remark     | Measurement distance (m) |
|-------------------|----------------------------------|-----------------|------------|--------------------------|
| 0.009MHz-0.490MHz | 2400/F (kHz)                     | -               | Quasi-peak | 300                      |
| 0.490MHz-1.705MHz | 24000/F (kHz)                    | -               | Quasi-peak | 30                       |
| 1.705MHz-30MHz    | 30                               | -               | Quasi-peak | 30                       |
| 30MHz-88MHz       | 100                              | 40.0            | Quasi-peak | 3                        |
| 88MHz-216MHz      | 150                              | 43.5            | Quasi-peak | 3                        |
| 216MHz-960MHz     | 200                              | 46.0            | Quasi-peak | 3                        |
| 960MHz-1GHz       | 500                              | 54.0            | Quasi-peak | 3                        |
| Above 1GHz        | 500                              | 54.0            | Average    | 3                        |
|                   |                                  | 74.0            | Peak       | 3                        |


For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emissions from intentional radiators at a distance of 3 meters shall not exceed the above table.

Limit: (Field strength of the fundamental signal)


| Frequency         | Limit (dBuV/m @3m) | Remark        |
|-------------------|--------------------|---------------|
| 2400MHz-2483.5MHz | 94.0               | Average Value |
|                   | 114.0              | Peak Value    |

## 4.2 TEST SETUP


### 1. Radiated Emission Test-Up Frequency Below 30MHz



### 2. Radiated Emission Test-Up Frequency 30MHz~1GHz



### 3. Radiated Emission Test-Up Frequency Above 1GHz



### 4.3 TEST PROCEDURE

1. Below 1GHz measurement the EUT is placed on turntable which is 0.8m above ground plane. And above 1GHz measurement EUT was placed on low permittivity and low tangent turn table which is 1.5m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.
7. The test frequency range from 9kHz to 25GHz per FCC PART 15.33(a).

Note:

For battery operated equipment, the equipment tests shall be performed using a new battery.

### 4.4 TEST RESULT


PASS

Remark:

1. All modes were test at Low, Middle, and High channel, only the worst result of GFSK Low Channel was reported for below 1GHz test.
2. By preliminary testing and verifying three axis (X, Y and Z) position of EUT transmitted status, it was found that "X axis" position was the worst, and test data recorded in this report.
3. Radiated emission test from 9kHz to 10th harmonic of fundamental was verified, and no emission found except system noise floor in 9kHz to 30MHz and not recorded in this report.


Below 1GHz Test Results:

|               |                                     |                    |            |
|---------------|-------------------------------------|--------------------|------------|
| Temperature:  | 24°C                                | Relative Humidity: | 48%        |
| Test Date:    | Jul. 09, 2023                       | Pressure:          | 1010hPa    |
| Test Voltage: | DC 4.5V                             | Phase:             | Horizontal |
| Test Mode:    | Transmitting mode of GFSK 2455.0MHz |                    |            |



| No. | Frequency (MHz) | Reading (dBuV) | Correction factor(dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Degree (deg.) | Height (cm) | Remark |
|-----|-----------------|----------------|-------------------------|-----------------|----------------|-------------|---------------|-------------|--------|
| 1   | 69.1141         | 37.74          | -20.90                  | 16.84           | 40.00          | -23.16      | 123           | 100         | peak   |
| 2   | 432.5457        | 38.36          | -12.26                  | 26.10           | 46.00          | -19.90      | 147           | 100         | peak   |
| 3   | 520.8881        | 34.66          | -10.85                  | 23.81           | 46.00          | -22.19      | 89            | 100         | peak   |
| 4   | 782.3453        | 34.66          | -7.38                   | 27.28           | 46.00          | -18.72      | 67            | 100         | peak   |
| 5   | 890.7278        | 34.64          | -5.33                   | 29.31           | 46.00          | -16.69      | 145           | 100         | peak   |
| 6*  | 948.7610        | 33.75          | -4.30                   | 29.45           | 46.00          | -16.55      | 185           | 100         | peak   |

|               |                                     |                    |          |
|---------------|-------------------------------------|--------------------|----------|
| Temperature:  | 24°C                                | Relative Humidity: | 48%      |
| Test Date:    | Jul. 09, 2023                       | Pressure:          | 1010hPa  |
| Test Voltage: | DC 4.5V                             | Phase:             | Vertical |
| Test Mode:    | Transmitting mode of GFSK 2455.0MHz |                    |          |



| No. | Frequency (MHz) | Reading (dBuV) | Correction factor(dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Degree (deg.) | Height (cm) | Remark |
|-----|-----------------|----------------|-------------------------|-----------------|----------------|-------------|---------------|-------------|--------|
| 1*  | 44.1202         | 41.98          | -17.66                  | 24.32           | 40.00          | -15.68      | 121           | 100         | peak   |
| 2   | 56.9912         | 40.68          | -21.30                  | 19.38           | 40.00          | -20.62      | 237           | 100         | peak   |
| 3   | 78.4133         | 44.59          | -20.60                  | 23.99           | 40.00          | -16.01      | 211           | 100         | peak   |
| 4   | 90.5374         | 44.77          | -20.25                  | 24.52           | 43.50          | -18.98      | 159           | 100         | peak   |
| 5   | 432.5457        | 38.09          | -12.26                  | 25.83           | 46.00          | -20.17      | 133           | 100         | peak   |
| 6   | 869.1302        | 33.94          | -5.44                   | 28.50           | 46.00          | -17.50      | 146           | 100         | peak   |

Remark: Result = Reading Level + Factor, Margin = Result – Limit  
 Factor = Ant. Factor + Cable Loss – Pre-amplifier

Remark:

1. Measuring frequencies from 9 kHz to the 1 GHz, Radiated emission test from 9kHz to 30MHz was verified, and no any emission was found except system noise floor.
2. \* denotes emission frequency which appearing within the Restricted Bands specified in provision of 15.205, then the general radiated emission limits in 15.209 apply.
3. The IF bandwidth of EMI Test Receiver between 30MHz to 1GHz was 120kHz, 1 MHz for measuring above 1 GHz, below 30MHz was 10kHz.



Above 1 GHz Test Results:

CH01 (2455.0MHz)

Horizontal:

| Frequency<br>(MHz) | Reading Result<br>(dBμV) | Factor<br>(dB) | Emission Level<br>(dBμV/m) | Limits<br>(dBμV/m) | Margin<br>(dB) | Detector<br>Type |
|--------------------|--------------------------|----------------|----------------------------|--------------------|----------------|------------------|
| 2455               | 91.64                    | -5.84          | 85.8                       | 114                | -28.2          | PK               |
| 2455               | 71.36                    | -5.84          | 65.52                      | 94                 | -28.48         | AV               |
| 4910               | 48.6                     | -3.64          | 44.96                      | 74                 | -29.04         | PK               |
| 4910               | 28.47                    | -3.64          | 24.83                      | 54                 | -29.17         | AV               |
| 7365               | 45.49                    | -0.95          | 44.54                      | 74                 | -29.46         | PK               |
| 7365               | 25.21                    | -0.95          | 24.26                      | 54                 | -29.74         | AV               |

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier. Margin = Absolute Level – Limit

Vertical:

| Frequency<br>(MHz) | Reading Result<br>(dBμV) | Factor<br>(dB) | Emission Level<br>(dBμV/m) | Limits<br>(dBμV/m) | Margin<br>(dB) | Detector<br>Type |
|--------------------|--------------------------|----------------|----------------------------|--------------------|----------------|------------------|
| 2455               | 91.43                    | -5.84          | 85.59                      | 114                | -28.41         | PK               |
| 2455               | 71.15                    | -5.84          | 65.31                      | 94                 | -28.69         | AV               |
| 4910               | 48.48                    | -3.64          | 44.84                      | 74                 | -29.16         | PK               |
| 4910               | 28.23                    | -3.64          | 24.59                      | 54                 | -29.41         | AV               |
| 7365               | 45.17                    | -0.95          | 44.22                      | 74                 | -29.78         | PK               |
| 7365               | 24.66                    | -0.95          | 23.71                      | 54                 | -30.29         | AV               |

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier. Margin = Absolute Level – Limit

CH11 (2465.0MHz)  
Horizontal:

| Frequency | Reading Result | Factor | Emission Level | Limits   | Margin | Detector |
|-----------|----------------|--------|----------------|----------|--------|----------|
| (MHz)     | (dBµV)         | (dB)   | (dBµV/m)       | (dBµV/m) | (dB)   | Type     |
| 2465      | 91.31          | -5.71  | 85.6           | 114      | -28.4  | PK       |
| 2465      | 71.04          | -5.71  | 65.33          | 94       | -28.67 | AV       |
| 4930      | 48.2           | -3.51  | 44.69          | 74       | -29.31 | PK       |
| 4930      | 28.11          | -3.51  | 24.6           | 54       | -29.4  | AV       |
| 7395      | 45.12          | -0.82  | 44.3           | 74       | -29.7  | PK       |
| 7395      | 24.86          | -0.82  | 24.04          | 54       | -29.96 | AV       |

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier. Margin = Absolute Level – Limit

Vertical:

| Frequency | Reading Result | Factor | Emission Level | Limits   | Margin | Detector |
|-----------|----------------|--------|----------------|----------|--------|----------|
| (MHz)     | (dBµV)         | (dB)   | (dBµV/m)       | (dBµV/m) | (dB)   | Type     |
| 2465      | 91.03          | -5.71  | 85.32          | 114      | -28.68 | PK       |
| 2465      | 70.86          | -5.71  | 65.15          | 94       | -28.85 | AV       |
| 4930      | 48.02          | -3.51  | 44.51          | 74       | -29.49 | PK       |
| 4930      | 27.84          | -3.51  | 24.33          | 54       | -29.67 | AV       |
| 7395      | 44.77          | -0.82  | 43.95          | 74       | -30.05 | PK       |
| 7395      | 24.25          | -0.82  | 23.43          | 54       | -30.57 | AV       |

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier. Margin = Absolute Level – Limit

CH21 (2475.0MHz)

Horizontal:

| Frequency | Reading Result | Factor | Emission Level | Limits   | Margin | Detector |
|-----------|----------------|--------|----------------|----------|--------|----------|
| (MHz)     | (dBμV)         | (dB)   | (dBμV/m)       | (dBμV/m) | (dB)   | Type     |
| 2475      | 91.02          | -5.65  | 85.37          | 114      | -28.63 | PK       |
| 2475      | 70.74          | -5.65  | 65.09          | 94       | -28.91 | AV       |
| 4950      | 48.05          | -3.43  | 44.62          | 74       | -29.38 | PK       |
| 4950      | 27.93          | -3.43  | 24.5           | 54       | -29.5  | AV       |
| 7425      | 44.99          | -0.75  | 44.24          | 74       | -29.76 | PK       |
| 7425      | 24.57          | -0.75  | 23.82          | 54       | -30.18 | AV       |

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier. Margin = Absolute Level – Limit

Vertical:

| Frequency | Reading Result | Factor | Emission Level | Limits   | Margin | Detector |
|-----------|----------------|--------|----------------|----------|--------|----------|
| (MHz)     | (dBμV)         | (dB)   | (dBμV/m)       | (dBμV/m) | (dB)   | Type     |
| 2475      | 90.75          | -5.63  | 85.12          | 114      | -28.88 | PK       |
| 2475      | 70.47          | -5.65  | 64.82          | 94       | -29.18 | AV       |
| 4950      | 47.78          | -3.43  | 44.35          | 74       | -29.65 | PK       |
| 4950      | 27.55          | -3.43  | 24.12          | 54       | -29.88 | AV       |
| 7425      | 44.5           | -0.75  | 43.75          | 74       | -30.25 | PK       |
| 7425      | 23.96          | -0.75  | 23.21          | 54       | -30.79 | AV       |

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier. Margin = Absolute Level – Limit

Remark:

1. Measuring frequencies from 1 GHz to the 25 GHz.
2. "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency.
3. \* denotes emission frequency which appearing within the Restricted Bands specified in provision of 15.205, then the general radiated emission limits in 15.209 apply.
4. Data of measurement within this frequency range shown "---" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. The IF bandwidth of EMI Test Receiver between 30MHz to 1GHz was 120kHz, 1 MHz for measuring above 1 GHz, below 30MHz was 10kHz. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for peak measurement with peak detector at frequency above 1GHz. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average measurement with peak detection at frequency above 1GHz.
6. When the test results of Peak Detected below the limits of Average Detected, the Average Detected is not need completed. For example: Top Channel at Fundamental 73.16dBuV/m(PK Value) <93.98(AV Limit), at harmonic 53.20 dBuV/m(PK Value) <54 dBuV/m(AV Limit), the Average Detected not need to completed.
7. All modes of operation were investigated and the worst-case emissions of π/4 DQPSK are reported.
8. For fundamental frequency, RBW >20dB BW, VBW>=3XRBW, PK detector for PK value, AV detector for AV value.

## 5 BAND EDGE

### 5.1 TEST LIMIT

FCC PART 15.249(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

### 5.2 TEST PROCEDURE

The band edge compliance of RF radiated emission should be measured by following the guidance in ANSI C63.10 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization etc. Set RBW to 1MHz and VBM to 3MHz to measure the peak field strength and set RBW to 1MHz and VBW to 10Hz to measure the average radiated field strength. Peak detector is for both.

### 5.3 TEST RESULT

PASS

Operation Mode: TX CH01 (2455.0MHz)

Horizontal:

| Frequency<br>(MHz) | Reading Result<br>(dBμV) | Factor<br>(dB) | Emission Level<br>(dBμV/m) | Limits<br>(dBμV/m) | Margin<br>(dB) | Detector<br>Type |
|--------------------|--------------------------|----------------|----------------------------|--------------------|----------------|------------------|
| 2310               | 57.08                    | -5.81          | 51.27                      | 74                 | -22.73         | PK               |
| 2310               | /                        | -5.81          | /                          | 54                 | /              | AV               |
| 2390               | 57.27                    | -5.84          | 51.43                      | 74                 | -22.57         | PK               |
| 2390               | /                        | -5.84          | /                          | 54                 | /              | AV               |
| 2400               | 57.03                    | -5.84          | 51.19                      | 74                 | -22.81         | PK               |
| 2400               | /                        | -5.84          | /                          | 54                 | /              | AV               |

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Vertical:

| Frequency<br>(MHz) | Reading Result<br>(dBμV) | Factor<br>(dB) | Emission Level<br>(dBμV/m) | Limits<br>(dBμV/m) | Margin<br>(dB) | Detector<br>Type |
|--------------------|--------------------------|----------------|----------------------------|--------------------|----------------|------------------|
| 2310               | 56.87                    | -5.81          | 51.06                      | 74                 | -22.94         | PK               |
| 2310               | /                        | -5.81          | /                          | 54                 | /              | AV               |
| 2390               | 57                       | -5.84          | 51.16                      | 74                 | -22.84         | PK               |
| 2390               | /                        | -5.84          | /                          | 54                 | /              | AV               |
| 2400               | 57.19                    | -5.84          | 51.35                      | 74                 | -22.65         | PK               |
| 2400               | /                        | -5.84          | /                          | 54                 | /              | AV               |

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Operation Mode: TX CH21 (2475.0MHz)

Horizontal:

| Frequency<br>(MHz) | Reading Result<br>(dBµV) | Factor<br>(dB) | Emission Level<br>(dBµV/m) | Limits<br>(dBµV/m) | Margin<br>(dB) | Detector<br>Type |
|--------------------|--------------------------|----------------|----------------------------|--------------------|----------------|------------------|
| 2483.5             | 55.73                    | -5.65          | 50.08                      | 74                 | -23.92         | PK               |
| 2483.5             | /                        | -5.65          | /                          | 54                 | /              | AV               |
| 2500               | 56.93                    | -5.72          | 51.21                      | 74                 | -22.79         | PK               |
| 2500               | /                        | -5.72          | /                          | 54                 | /              | AV               |

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Vertical:

| Frequency<br>(MHz) | Reading Result<br>(dBµV) | Factor<br>(dB) | Emission Level<br>(dBµV/m) | Limits<br>(dBµV/m) | Margin<br>(dB) | Detector<br>Type |
|--------------------|--------------------------|----------------|----------------------------|--------------------|----------------|------------------|
| 2483.5             | 57.33                    | -5.65          | 51.68                      | 74                 | -22.32         | PK               |
| 2483.5             | /                        | -5.65          | /                          | 54                 | /              | AV               |
| 2500               | 56.8                     | -5.72          | 51.08                      | 74                 | -22.92         | PK               |
| 2500               | /                        | -5.72          | /                          | 54                 | /              | AV               |


Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Note:

1. Since the peak value is less than the average limit, the average value does not reflected in the report.

## 6 20dB BANDWIDTH

### 6.1 TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)



### 6.2 MEASUREMENT EQUIPMENT USED

Refer to Section 3.3.

### 6.3 TEST PROCEDURE

1. The RF output of EUT was connected to the spectrum analyzer by RF cable. The path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously.
3. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 30 kHz. Set the Video bandwidth (VBW) = 100 kHz. In order to make an accurate measurement.
4. For 20dB Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1-5% of the emission bandwidth and set the Video bandwidth (VBW)  $\geq 3 * RBW$ .
5. Measure and record the results in the test report.


### 6.4 TEST RESULT

PASS

GFSK Modulation:


| Channel        | Frequency (MHz) | 20dB Bandwidth (MHz) | Result |
|----------------|-----------------|----------------------|--------|
| Low Channel    | 2455.00         | 1.495                | PASS   |
| Middle Channel | 2465.00         | 1.185                | PASS   |
| High Channel   | 2475.00         | 1.213                | PASS   |

CH01: 2455.00MHz





CH11: 2465.00MHz



CH21: 2475.00MHz



## 7 ANTENNA REQUIREMENT


Standard Applicable:

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

Antenna Connected Construction


The antenna used in this product is an Internal Antenna, The directional gains of antenna used for transmitting is 0.17dBi.

ANTENNA:




## 8 PHOTO OF TEST

### 8.1 RADIATED EMISSION




30MHz-1000MHz



Above 1GHz

## 8.2 RF CONDUCTED



\*\*\*End of Report\*\*\*