



## FCC 47 CFR PART 15 SUBPART C

for

**Aerial photography equipment**

**Model: A10, A10+, A10pro, A10plus, A10A, A10P, A10S, A10W,  
A11, A12, SPARROW**

**Brand: AEE**

**Test Report Number:  
C161104Z02-RP1**

**Issued Date: November 22, 2016**

Issued for

**Shenzhen AEE Aviation Technology Co., Ltd.**

**AEE Hi-Tech Park, Tangtou Crossroads, Shiyan Town, Bao'an District  
Shenzhen, P.R.C.**

Issued by:

**Compliance Certification Services (Shenzhen) Inc.**

No.10-1 Mingkeda Logistics park, No.18, Huanguan South Rd.,  
Guan Lan Town, Baoan District, Shenzhen, China

TEL: 86-755-28055000

FAX: 86-755-28055221



TESTING CERT #2861.01

**Note:** This report shall not be reproduced except in full, without the written approval of Compliance Certification Services (Shenzhen) Inc. This document may be altered or revised by Compliance Certification Services (Shenzhen) Inc. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF, A2LA, NVLAP, NIST or any government agencies. The test results in the report only apply to the tested sample.



## Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	November 22, 2016	Initial Issue	ALL	Sabrina Wang



## TABLE OF CONTENTS

<b>1 TEST CERTIFICATION</b>	<b>4</b>
<b>2 TEST RESULT SUMMARY</b>	<b>5</b>
<b>3 EUT DESCRIPTION</b>	<b>6</b>
<b>4 TEST METHODOLOGY</b>	<b>7</b>
4.1. DESCRIPTION OF TEST MODES	7
<b>5 SETUP OF EQUIPMENT UNDER TEST</b>	<b>8</b>
5.1. DESCRIPTION OF SUPPORT UNITS	8
5.2. CONFIGURATION OF SYSTEM UNDER TEST	8
<b>6 FACILITIES AND ACCREDITATIONS</b>	<b>9</b>
6.1. FACILITIES	9
6.2. ACCREDITATIONS	9
6.3. MEASUREMENT UNCERTAINTY	9
<b>7 FCC PART 15.247 REQUIREMENTS</b>	<b>10</b>
7.1. POWER LINE CONDUCTED EMISSIONS MEASUREMENT	10
7.2. SPURIOUS EMISSIONS MEASUREMENT	15
7.3. 6dB BANDWIDTH MEASUREMENT	51
7.4. ANTENNA GAIN	61
7.5. PEAK OUTPUT POWER	63
7.6. BAND EDGES MEASUREMENT	66
7.7. PEAK POWER SPECTRAL DENSITY MEASUREMENT	84



## 1 TEST CERTIFICATION

Product	Aerial photography equipment
Model	A10, A10+, A10pro, A10plus, A10A, A10P, A10S, A10W, A11, A12, SPARROW
Brand	AEE
Tested	November 4~22, 2016
Applicant	Shenzhen AEE Aviation Technology Co., Ltd. AEE Hi-Tech Park, Tangtou Crossroads, Shiyan Town, Bao'an District Shenzhen, P.R.C.
Manufacturer	Shenzhen AEE Aviation Technology Co., Ltd. AEE Hi-Tech Park, Tangtou Crossroads, Shiyan Town, Bao'an District Shenzhen, P.R.C.

APPLICABLE STANDARDS			
Standard	Test Type	Standard	Test Type
15.207(a)	Power Line Conducted Emissions	15.247(d) 15.209(a)	● Spurious Emissions ● Conducted Measurement ● Radiated Emissions
15.247(a)(2)	6dB Bandwidth Measurement	15.247(b)(3) 15.247(b)(4)	Peak Power Measurement
15.247(d)	Band Edges Measurement	15.247(e)	Peak Power Spectral Density

### We hereby certify that:

The above equipment was tested by Compliance Certification Services (Shenzhen) Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in **ANSI C63.10: 2013** and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 15.207, 15.209, 15.247.

The test results of this report relate only to the tested sample EUT identified in this report.

Approved by:

Sunday Hu  
Supervisor of EMC Dept.  
Compliance Certification Services (Shenzhen) Inc.

Reviewed by:

Ruby Zhang  
Supervisor of Report Dept.  
Compliance Certification Services (Shenzhen) Inc.



## 2 TEST RESULT SUMMARY

APPLICABLE STANDARDS			
Standard	Test Type	Result	Remark
15.247(a)(2)	6dB Bandwidth Measurement	Pass	Meet the requirement of limit.
15.247(b)(3) 15.247(b)(4)	Peak Power Measurement	Pass	Meet the requirement of limit.
15.247(d)	Band Edges Measurement	Pass	Meet the requirement of limit.
15.247(e)	Peak Power Spectral Density	Pass	Meet the requirement of limit.
15.247(d) 15.209(a)	● Spurious Emissions ● Conducted Measurement ● Radiated Emissions	Pass	Meet the requirement of limit.
15.207(a)	Power line Conducted Emissions	Pass	Meet the requirement of limit.

Note: 1. The statements of test result on the above are decided by the request of test standard only; the measurement uncertainties are not factored into this compliance determination.

2. The information of measurement uncertainty is available upon the customer's request.



### 3 EUT DESCRIPTION

Product	Aerial photography equipment
Model Number	A10, A10+, A10pro, A10plus, A10A, A10P, A10S, A10W, A11, A12, SPARROW
Brand	AEE
Model Discrepancy	The models are identical to each other except the model name different.
Identify Number	C161104Z02-RP1
Received Date	November 4, 2016
Power Supply	DC7.4V supply by the Lithium Battery
Battery Spec.	AEE / AD05 DC7.4V, 1200mAh
Transmit Power	IEEE 802.11b mode: 22.35dBm IEEE 802.11g mode: 21.97dBm IEEE 802.11n HT20 MHz mode: 22.14Bm IEEE 802.11n HT40 MHz mode: 22.36dBm
Modulation Technique	IEEE 802.11b mode: DSSS(CCK,QPSK, BPSK) IEEE 802.11g mode: OFDM (BPSK/QPSK/16QAM/64QAM) IEEE 802.11n HT20 MHz mode: OFDM (BPSK/QPSK/16QAM/64QAM) IEEE 802.11n HT40 MHz mode: OFDM (BPSK/QPSK/16QAM/64QAM)
Transmit Data Rate	IEEE 802.11b: 11Mbps(CCK) with fall back rates of 5.5/2/1Mbps IEEE 802.11g: 54Mbps with fall back rates of 48/36/24/18/12/9 /6Mbps IEEE 802.11n HT20: 65Mbps with fall back rates of 65/58.5/52/ 39/26/19.5/13/6.5Mbps IEEE 802.11n HT40: 130Mbps with fall back rates of 130/121.5/108/ 81/54/40.5/27/13.5Mbps
Number of Channels	IEEE 802.11b mode: 11 Channels IEEE 802.11g mode: 11 Channels IEEE 802.11n HT20 MHz mode: 11 Channels IEEE 802.11n HT40 MHz mode: 7 Channels
Antenna Specification	Internal Antenna with 1.29dBi gain (Max)
Channels Spacing	IEEE 802.11b/g ,802.11n HT20/HT40 : 5MHz
Temperature Range	0°C ~ +50°C
Hardware Version	A10 _M_ V1.3
Software Version	AEE ZONE V1.97

**Note:** 1. The sample selected for test was engineering sample that approximated to production product and was provided by manufacturer.

2. This submittal(s) (test report) is intended for FCC ID: **2AGZG-010001** filing to comply with Section 15.207, 15.209 and 15.247 of the FCC Part 15, Subpart C Rules.



## 4 TEST METHODOLOGY

### 4.1. DESCRIPTION OF TEST MODES

The EUT has been tested under operating condition.

Software used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Test Item	Test mode	Worse mode
Conducted Emission	<b>Mode 1:</b> Charge	<input checked="" type="checkbox"/>
Radiated Emission	<b>Mode 1:</b> TX	<input checked="" type="checkbox"/>

After verification, all tests were carried out with the worst case test modes as shown below except radiated spurious emission below 1GHz, which worst case was in normal link mode only, and power line conducted emission below 30MHz, which worst case was in normal link mode.

IEEE802.11b mode: Channel Low (2412MHz), Channel Mid (2437MHz) and Channel High (2462MHz) with 1Mbps data rate were chosen for full testing.

IEEE802.11g mode: Channel Low (2412MHz), Channel Mid (2437MHz) and Channel High (2462MHz) with 6Mbps data rate were chosen for full testing.

IEEE 802.11n HT20 MHz mode: Channel Low (2412MHz), Channel Mid(2437MHz) and Channel High (2462MHz) with 6.5Mbps data rate were chosen for full testing.

IEEE 802.11n HT40 MHz mode: Channel Low (2422MHz), Channel Mid (2437MHz) and Channel High (2452MHz) with 13.5Mbps data rate were chosen for full testing.



## 5 SETUP OF EQUIPMENT UNDER TEST

### 5.1. DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

No.	Equipment	Model No.	Serial No.	FCC ID	Brand	Data Cable	Power Cord
1	Notebook	Probook 5310M	N/A	DoC	HP	Shielded 2.30m	Shielded 1.70m (AC Cable) Unshielded 1.80m (DC Cable)

**Note:**

Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

### 5.2. CONFIGURATION OF SYSTEM UNDER TEST

See test photographs attached in Appendix II for the actual connections between EUT and support equipment.





## 6 FACILITIES AND ACCREDITATIONS

### 6.1. FACILITIES

All measurement facilities used to collect the measurement data are located at **No.10-1 Mingkeda Logistics park, No.18, Huanguan South Rd., Guan Lan Town, Baoan District, Shenzhen, China**

The sites are constructed in conformance with the requirements of ANSI C63.10, ANSI C63.7 and CISPR Publication 22. All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

### 6.2. ACCREDITATIONS

Our laboratories are accredited and approved by the following accreditation body according to ISO/IEC 17025.

<b>USA</b>	<b>A2LA</b>
<b>China</b>	<b>CNAS</b>

The measuring facility of laboratories has been authorized or registered by the following approval agencies.

<b>USA</b>	<b>FCC</b>
<b>Japan</b>	<b>VCCI (C-4815,R-4320,T-2317, G-10624)</b>
<b>Canada</b>	<b>INDUSTRY CANADA</b>

Copies of granted accreditation certificates are available for downloading from our web site, <http://www.ccssz.com>

### 6.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Parameter	Uncertainty
Radiated Emission, 30 to 200 MHz Test Site : 966(2)	+/-3.6880dB
Radiated Emission, 200 to 1000 MHz Test Site : 966(2)	+/-3.6695dB
Radiated Emission, 1 to 8 GHz	+/-5.1782dB
Radiated Emission, 8 to 18 GHz	+/-5.2173dB
Conducted Emissions	+/-3.6836dB
Band Width	178kHz
Peak Output Power MU	+/-1.906dB
Band Edge MU	+/-0.182dB
Channel Separation MU	416.178Hz
Duty Cycle MU	0.054ms
Frequency Stability MU	226Hz

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

The measured result is above (below) the specification limit by a margin less than the measurement uncertainty; it is therefore not possible to state compliance based on the 95% level of confidence. However, the result indicates that compliance (non-compliance) is more probable than non-compliance (with the specification limit).



## 7 FCC PART 15.247 REQUIREMENTS

### 7.1. POWER LINE CONDUCTED EMISSIONS MEASUREMENT

#### 7.1.1. LIMITS OF CONDUCTED EMISSIONS MEASUREMENT

According to §15.207(a), except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50  $\mu$ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency Range (MHz)	Limits (dB $\mu$ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56*	56 to 46*
0.50 to 5	56	46
5 to 30	60	50

**NOTE:**

- (1) The lower limit shall apply at the transition frequencies.
- (2) The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
- (3) All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

#### 7.1.2. TEST INSTRUMENTS

Conducted Emission Test Site					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
EMI TEST RECEIVER	ROHDE&SCHWARZ	ESCI	100783	02/21/2016	02/20/2017
LISN(EUT)	ROHDE&SCHWARZ	ENV216	101543-WX	02/21/2016	02/20/2017
LISN	EMCO	3825/2	8901-1459	02/21/2016	02/20/2017
Temp. / Humidity Meter	VICTOR	HTC-1	N/A	02/21/2016	02/20/2017
Test S/W	FARAD	EZ-EMC/ CCS-3A1-CE			

- NOTE:** 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.  
2. N.C.R = No Calibration Request.




### 7.1.3. TEST PROCEDURES (please refer to measurement standard)

- The EUT and Support equipment, if needed, was placed on a non-conducted table, which is 0.8m above the ground plane and 0.4m away from the conducted wall.
- The test equipment EUT installed received AC main power, through a Line Impedance Stabilization Network (LISN), which supplied power source and was grounded to the ground plane. All support equipment power received from a second LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- The EUT test program was started. Emissions were measured on each current carrying line of the EUT using an EMI Test Receiver connected to the LISN powering the EUT.
- The frequency range from 150 kHz to 30 MHz was searched. The test data of the worst-case condition(s) was recorded. Emission levels under limit 20dB were not recorded.



#### 7.1.4. TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

#### 7.1.5. DATA SAMPLE

Frequency (MHz)	QuasiPeak Reading (dBuV)	Average Reading (dBuV)	Correction Factor (dB)	QuasiPeak Result (dBuV)	Average Result (dBuV)	QuasiPeak Limit (dBuV)	Average Limit (dBuV)	QuasiPeak Margin (dB)	Average Margin (dB)	Remark (Pass/Fail)
XXXXXX	32.69	25.65	11.52	44.21	37.17	65.78	55.79	-21.57	-18.62	Pass

Factor = Insertion loss of LISN + Cable Loss

Result = Quasi-peak Reading/ Average Reading + Factor


Limit = Limit stated in standard

Margin = Result (dBuV) – Limit (dBuV)



## 7.1.6. TEST RESULTS

Model No.	A10	RBW,VBW	9 kHz
Environmental Conditions	22°C, 45% RH	Test Mode	Mode 1
Tested by	David Dong	Line	L1
Test Date	November 20, 2016		




Frequency (MHz)	QuasiPeak Reading (dBuV)	Average Reading (dBuV)	Correction Factor (dB)	QuasiPeak Result (dBuV)	Average Result (dBuV)	QuasiPeak Limit (dBuV)	Average Limit (dBuV)	QuasiPeak Margin (dB)	Average Margin (dB)	Remark (Pass/Fail)	Line (L1/L2)
0.2420	18.45	2.15	19.64	38.09	21.79	62.02	52.03	-23.93	-30.24	Pass	L1
0.4540	15.66	0.34	19.63	35.29	19.97	56.80	46.80	-21.51	-26.83	Pass	L1
0.7500	13.72	-1.92	19.78	33.50	17.86	56.00	46.00	-22.50	-28.14	Pass	L1
5.8100	15.37	2.08	19.67	35.04	21.75	60.00	50.00	-24.96	-28.25	Pass	L1
10.5780	18.22	5.71	20.12	38.34	25.83	60.00	50.00	-21.66	-24.17	Pass	L1
13.9580	14.33	1.53	19.96	34.29	21.49	60.00	50.00	-25.71	-28.51	Pass	L1

REMARKS: L1 = Line One (Live Line)



Model No.	A10	RBW,VBW	9 kHz
Environmental Conditions	22°C, 45% RH	Test Mode	Mode 1
Tested by	David Dong	Line	L2
Test Date	November 20, 2016		



Frequency (MHz)	QuasiPeak Reading (dBuV)	Average Reading (dBuV)	Correction Factor (dB)	QuasiPeak Result (dBuV)	Average Result (dBuV)	QuasiPeak Limit (dBuV)	Average Limit (dBuV)	QuasiPeak Margin (dB)	Average Margin (dB)	Remark (Pass/Fail)	Line (L1/L2)
0.2420	20.11	5.22	19.73	39.84	24.95	62.02	52.03	-22.18	-27.08	Pass	L2
0.4580	18.76	3.91	19.64	38.40	23.55	56.73	46.73	-18.33	-23.18	Pass	L2
1.4420	14.66	4.53	19.74	34.40	24.27	56.00	46.00	-21.60	-21.73	Pass	L2
2.0820	14.65	2.95	19.72	34.37	22.67	56.00	46.00	-21.63	-23.33	Pass	L2
5.8100	17.37	0.37	19.73	37.10	20.10	60.00	50.00	-22.90	-29.90	Pass	L2
10.8300	24.57	8.91	20.08	44.65	28.99	60.00	50.00	-15.35	-21.01	Pass	L2

REMARKS: L2 = Line Two (Neutral Line)



## **7.2. SPURIOUS EMISSIONS MEASUREMENT**

### **7.2.1. CONDUCTED EMISSIONS MEASUREMENT**

#### **7.2.1.1. LIMITS OF CONDUCTED EMISSIONS MEASUREMENT**

§15.247(d) specifies that in any 100 kHz bandwidth outside of the authorized frequency band, the power shall be attenuated according to the following conditions:

If the peak output power procedure is used to measure the fundamental emission power to demonstrate compliance to 15.247(b)(3) requirements, then the peak conducted output power measured within any 100 kHz outside the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum measured in-band peak PSD level.

If the average output power procedure is used to measure the fundamental emission power to demonstrate compliance to 15.247(b)(3) requirements, then the power in any 100 kHz outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum measured in-band average PSD level.

In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in 15.209(a) (see Section 15.205(c)).

#### **7.2.1.2. TEST INSTRUMENTS**

<b>Name of Equipment</b>	<b>Manufacturer</b>	<b>Model</b>	<b>Serial Number</b>	<b>Last Calibration</b>	<b>Due Calibration</b>
Spectrum Analyzer	Agilent	N9010A	MY55370330	02/21/2016	02/20/2017

#### **7.2.1.3. TEST PROCEDURE** (please refer to measurement standard)

Conducted RF measurements of the transmitter output were made to confirm that the EUT antenna port conducted emissions meet the specified limit and to identify any spurious signals that require further investigation or measurements on the radiated emissions site.

The transmitter output is connected to the spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 300 kHz.

Measurements are made over the 10MHz to 26GHz range with the transmitter set to the lowest, middle, and highest channels. No emission found between lowest internal used/generated frequency to 10MHz, it is only recorded 10MHz to 26GHz.




## 7.2.1.4. TEST RESULTS


## Test Plot

## IEEE 802.11b mode

## CH Low (10MHz ~26.5GHz)




## CH Low (2.31GHz ~2.43GHz)








### CH Mid (10MHz ~26.5GHz)




### CH Mid (2.387GHz ~2.487GHz)





### CH High (10MHz ~26.5GHz)




### CH High (2.45GHz ~2.5GHz)






## IEEE 802.11g mode

### CH Low (10MHz ~26.5GHz)




### CH Low (2.31GHz ~2.43GHz)






### CH Mid (10MHz ~26.5GHz)




### CH Mid (2.387GHz ~2.487GHz)






### CH High (10MHz ~26.5GHz)




### CH High (2.45GHz ~2.5GHz)






IEEE 802.11n HT20 MHz mode

**CH Low (10MHz ~26.5GHz)**




**CH Low (2.31GHz ~2.43GHz)**






### CH Mid (10MHz ~26.5GHz)




### CH Mid (2.387GHz ~2.487GHz)





### CH High (10MHz ~26.5GHz)



### CH High (2.45GHz ~2.5GHz)









## IEEE 802.11n HT40 MHz mode

### CH Low (10MHz ~26.5GHz)




### CH Low (2.31GHz ~2.45GHz)






### CH Mid (10MHz ~26.5GHz)




### CH Mid (2.387GHz ~2.487GHz)






### CH High (10MHz ~26.5GHz)



### CH High (2.43GHz ~2.5GHz)





## 7.2.2. RADIATED EMISSIONS MEASUREMENT

### 7.2.2.1. LIMITS OF RADIATED EMISSIONS MEASUREMENT

According to §15.209(a), except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (mV/m)	Measurement Distance (m)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100*	3
88-216	150*	3
216-960	200*	3
Above 960	500	3

**Remark:** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

1. In the emission table above, the tighter limit applies at the band edges.

Frequency (MHz)	Field Strength ( $\mu\text{V/m}$ at 3-meter)	Field Strength (dB $\mu\text{V/m}$ at 3-meter)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54

**NOTE:**(1) The lower limit shall apply at the transition frequencies.  
(2) Emission level (dB $\mu\text{V/m}$ ) = 20 log Emission level ( $\mu\text{V/m}$ ).

**7.2.2.2. TEST INSTRUMENTS**

Radiated Emission Test Site 966 (2)					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
PSA Series Spectrum Analyzer	Agilent	E4446A	US44300399	02/21/2016	02/20/2017
EMI TEST RECEIVER	ROHDE&SCHWARZ	ESCI	100783	02/21/2016	02/20/2017
Amplifier	EMEC	EM330	060661	03/18/2016	03/17/2017
High Noise Amplifier	Agilent	8449B	3008A01838	02/21/2016	02/20/2017
Loop Antenna	COM-POWER	AL-130	121044	09/25/2016	09/24/2017
Bilog Antenna	SCHAFFNER	CBL6143	5082	02/21/2016	02/20/2017
Horn Antenna	SCHWARZBECK	BBHA9120	D286	02/28/2016	02/27/2017
Board-Band Horn Antenna	Schwarzbeck	BBHA 9170	9170-497	02/28/2016	02/27/2017
Turn Table	N/A	N/A	N/A	N.C.R	N.C.R
Antenna Tower	SUNOL	TLT2	N/A	N.C.R	N.C.R
Controller	Sunol Sciences	SC104V	022310-1	N.C.R	N.C.R
Controller	CT	N/A	N/A	N.C.R	N.C.R
Temp. / Humidity Meter	Anymetre	JR913	N/A	02/21/2016	02/20/2017
Test S/W	FARAD	LZ-RF / CCS-SZ-3A2			

**NOTE:** 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.  
2. The FCC Site Registration number is 101879.  
3. N.C.R = No Calibration Required.

**7.2.2.3. Measuring Instruments and Setting**

The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP/AVG
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP/AVG
Start ~ Stop Frequency	30MHz~1000MHz / RB 100kHz for QP

**7.2.2.4. TEST PROCEDURE** (please refer to measurement standard)**1) Sequence of testing 9 kHz to 30 MHz****Setup:**

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 0.8 m height is used.
- If the EUT is a floor standing device, it is placed on the ground.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

**Pre measurement:**

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna height is 0.8 meter.
- At each turntable position the analyzer sweeps with peak detection to find the maximum of all emissions



**Final measurement:**

--- Identified emissions during the pre measurement the software maximizes by rotating the turntable position ( $0^{\circ}$  to  $360^{\circ}$ ) and by rotating the elevation axes ( $0^{\circ}$  to  $360^{\circ}$ ).

--- The final measurement will be done in the position (turntable and elevation) causing the highest emissions with QPK detector.

--- The final levels, frequency, measuring time, bandwidth, turntable position, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the pre measurement and the limit will be stored.

**2) Sequence of testing 30 MHz to 1 GHz**

**Setup:**

--- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.

--- If the EUT is a tabletop system, a table with 0.8 m height is used, which is placed on the ground plane.

--- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.

--- Auxiliary equipment and cables were positioned to simulate normal operation conditions

--- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.

--- The measurement distance is 3 meter.

--- The EUT was set into operation.

**Pre measurement:**

--- The turntable rotates from  $0^{\circ}$  to  $315^{\circ}$  using  $45^{\circ}$  steps.

--- The antenna is polarized vertical and horizontal.

--- The antenna height changes from 1 to 3 meter.

--- At each turntable position, antenna polarization and height the analyzer sweeps three times in peak to find the maximum of all emissions.



**Final measurement:**

- The final measurement will be performed with minimum the six highest peaks.
- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position ( $\pm 45^\circ$ ) and antenna movement between 1 and 4 meter.
- The final measurement will be done with QP detector with an EMI receiver.
- The final levels, frequency, measuring time, bandwidth, antenna height, antenna polarization, turntable angle, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.

**3) Sequence of testing 1 GHz to 18 GHz**

**Setup:**

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 1.5 m height is used.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

**Pre measurement:**

- The turntable rotates from  $0^\circ$  to  $315^\circ$  using  $45^\circ$  steps.
- The antenna is polarized vertical and horizontal.
- The antenna height scan range is 1 meter to 2.5 meter.
- At each turntable position and antenna polarization the analyzer sweeps with peak detection to find the maximum of all emissions.





**Final measurement:**

- The final measurement will be performed with minimum the six highest peaks.
- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position ( $\pm 45^\circ$ ) and antenna movement between 1 and 4 meter. This procedure is repeated for both antenna polarizations.
- The final measurement will be done in the position (turntable, EUT-table and antenna polarization) causing the highest emissions with Peak and Average detector.
- The final levels, frequency, measuring time, bandwidth, turntable position, EUT-table position, antenna polarization, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the pre measurement with marked maximum final measurements and the limit will be stored.

**4) Sequence of testing above 18 GHz**

**Setup:**

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 1.5 m height is used.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 1 meter.
- The EUT was set into operation.

**Pre measurement:**

- The antenna is moved spherical over the EUT in different polarisations of the antenna.


**Final measurement:**

- The final measurement will be performed at the position and antenna orientation for all detected emissions that were found during the premeasurements with Peak and Average detector.
- The final levels, frequency, measuring time, bandwidth, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement and the limit will be stored.




## 7.2.2.5. TEST SETUP

### Below 30MHz




### Below 1 GHz





**Above 1 GHz**



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

**7.2.2.6. DATA SAPLE****Below 1GHz**

Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
XXXX	36.37	-12.20	24.17	40.00	-15.83	V	QP

Frequency (MHz) = Emission frequency in MHz  
 Reading (dBuV) = Uncorrected Analyzer / Receiver reading  
 Correct Factor (dB/m) = Antenna factor + Cable loss – Amplifier gain  
 Result (dBuV/m) = Reading (dBuV) + Corr. Factor (dB/m)  
 Limit (dBuV/m) = Limit stated in standard  
 Margin (dB) = Result (dBuV/m) – Limit (dBuV/m)  
 Q.P. = Quasi-peak Reading

**Above 1GHz**

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
XXXX	62.09	-11.42	50.67	74.00	-23.33	V	Peak
XXXX	49.78	-11.42	38.36	54.00	-15.64	V	AVG

Frequency (MHz) = Emission frequency in MHz  
 Reading (dBuV) = Uncorrected Analyzer / Receiver reading  
 Correction Factor (dB/m) = Antenna factor + Cable loss – Amplifier gain  
 Result (dBuV/m) = Reading (dBuV) + Corr. Factor (dB/m)  
 Limit (dBuV/m) = Limit stated in standard  
 Margin (dB) = Result (dBuV/m) – Limit (dBuV/m)  
 Peak = Peak Reading  
 AVG = Average Reading

**Calculation Formula**

Margin (dB) = Result (dBuV/m) – Limits (dBuV/m)  
 Result (dBuV/m) = Reading (dBuV) + Correction Factor

**7.2.2.7. TEST RESULTS****Below 1 GHz****Test Mode:** TX**Tested by:** Saber Huang**Ambient temperature:** 24°C**Relative humidity:** 52% RH**Date:** November 16, 2016

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
263.7700	39.58	-20.13	19.45	46.00	-26.55	V	QP
359.8000	51.66	-17.42	34.24	46.00	-11.76	V	QP
408.3000	39.34	-15.69	23.65	46.00	-22.35	V	QP
455.8300	39.59	-15.30	24.29	46.00	-21.71	V	QP
551.8600	33.49	-13.13	20.36	46.00	-25.64	V	QP
600.3600	37.84	-12.86	24.98	46.00	-21.02	V	QP
240.4900	47.57	-21.48	26.09	46.00	-19.91	H	QP
263.7700	49.04	-20.13	28.91	46.00	-17.09	H	QP
312.2700	48.64	-19.12	29.52	46.00	-16.48	H	QP
359.8000	58.79	-17.42	41.37	46.00	-4.63	H	QP
600.3600	49.01	-12.86	36.15	46.00	-9.85	H	QP
749.7400	36.74	-11.19	25.55	46.00	-20.45	H	QP

**\*\*Remark:** 1. No emission found between lowest internal used/ generated frequency to 30MHz.


2. Pre-scan all mode and recorded the worst case results in this report (802.11b (Low Channel))

**Notes:**


- Radiated emissions measured in frequency range from 9kHz to 1GHz were made with an instrument using Quasi-peak detector mode.
- Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- The IF bandwidth of Receiver between 30MHz to 1GHz was 120kHz.
- |                        |  |
|------------------------|--|
| Frequency (MHz).       | = Emission frequency in MHz                    |
| Reading (dBuV/m)       | = Receiver reading                             |
| Correction Factor (dB) | = Antenna factor + Cable loss – Amplifier gain |
| Limit (dBuV/m)         | = Limit stated in standard                     |
| Margin (dB)            | = Measured (dBuV/m) – Limits (dBuV/m)          |
| Antenna Pol e(H/V)     | = Current carrying line of reading             |



## Vertical



## Horizontal



**Above 1 GHz****Test Mode:** TX / IEEE 802.11b(CH Low)**Tested by:** Saber Huang**Ambient temperature:** 24°C **Relative humidity:** 52% RH **Date:** November 16, 2016

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1504.000	50.53	-6.87	43.66	74.00	-30.34	V	peak
1990.000	53.31	-5.06	48.25	74.00	-25.75	V	peak
2512.000	45.76	-2.24	43.52	74.00	-30.48	V	peak
3358.000	44.17	-0.76	43.41	74.00	-30.59	V	peak
4825.000	47.75	4.41	52.16	74.00	-21.84	V	peak
4825.000	45.27	4.41	49.68	54.00	-4.32	V	AVG
6103.000	41.41	6.25	47.66	74.00	-26.34	V	peak
1171.000	51.13	-7.90	43.23	74.00	-30.77	H	Peak
1504.000	48.46	-6.87	41.59	74.00	-32.41	H	Peak
1990.000	47.87	-5.06	42.81	74.00	-31.19	H	Peak
2503.000	46.46	-2.25	44.21	74.00	-29.79	H	peak
4825.000	46.07	4.41	50.48	74.00	-23.52	H	peak
6265.000	41.46	6.51	47.97	74.00	-26.03	H	Peak

**REMARKS:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).

**Test Mode:** TX / IEEE 802.11b (CH Mid)**Tested by:** Saber Huang**Ambient temperature:** 24°C**Relative humidity:** 52% RH**Date:** November 16, 2016

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1738.000	52.30	-6.40	45.90	74.00	-28.10	V	Peak
1999.000	51.48	-5.01	46.47	74.00	-27.53	V	Peak
3322.000	44.73	-0.82	43.91	74.00	-30.09	V	Peak
4987.000	41.68	4.94	46.62	74.00	-27.38	V	Peak
6832.000	41.96	7.43	49.39	74.00	-24.61	V	Peak
8047.000	40.84	9.62	50.46	74.00	-23.54	V	Peak
1999.000	48.62	-5.01	43.61	74.00	-30.39	H	Peak
2521.000	45.84	-2.22	43.62	74.00	-30.38	H	Peak
4303.000	42.64	2.66	45.30	74.00	-28.70	H	Peak
5248.000	42.24	5.42	47.66	74.00	-26.34	H	Peak
6292.000	42.24	6.55	48.79	74.00	-25.21	H	Peak
7210.000	41.00	8.11	49.11	74.00	-24.89	H	Peak

**REMARKS:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).





Test Mode: TX / IEEE 802.11b (CH High)

Tested by: Saber Huang

Ambient temperature: 24°C

Relative humidity: 52% RH

Date: November 16, 2016

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1738.000	55.41	-6.40	49.01	74.00	-24.99	V	Peak
1999.000	51.55	-5.01	46.54	74.00	-27.46	V	Peak
3826.000	42.75	0.86	43.61	74.00	-30.39	V	Peak
5014.000	42.01	5.00	47.01	74.00	-26.99	V	Peak
5293.000	42.21	5.50	47.71	74.00	-26.29	V	Peak
6535.000	41.76	6.95	48.71	74.00	-25.29	V	Peak
1999.000	47.98	-5.01	42.97	74.00	-31.03	H	Peak
3349.000	44.29	-0.77	43.52	74.00	-30.48	H	Peak
4843.000	41.77	4.47	46.24	74.00	-27.76	H	Peak
6229.000	41.75	6.45	48.20	74.00	-25.80	H	Peak
6553.000	42.06	6.98	49.04	74.00	-24.96	H	Peak
7273.000	41.03	8.23	49.26	74.00	-24.74	H	Peak

## REMARKS:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



Test Mode: TX / IEEE 802.11g(CH Low)

Tested by: Saber Huang

Ambient temperature: 24°C Relative humidity: 52% RH Date: November 16, 2016

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1504.000	49.60	-6.87	42.73	74.00	-31.27	V	Peak
1990.000	51.00	-5.06	45.94	74.00	-28.06	V	Peak
3331.000	44.26	-0.80	43.46	74.00	-30.54	V	Peak
5149.000	43.56	5.25	48.81	74.00	-25.19	V	Peak
6319.000	40.84	6.60	47.44	74.00	-26.56	V	Peak
7336.000	40.97	8.36	49.33	74.00	-24.67	V	Peak
1990.000	48.60	-5.06	43.54	74.00	-30.46	H	Peak
3070.000	44.73	-1.24	43.49	74.00	-30.51	H	Peak
4411.000	42.38	3.04	45.42	74.00	-28.58	H	Peak
5491.000	41.44	5.85	47.29	74.00	-26.71	H	Peak
6652.000	41.30	7.14	48.44	74.00	-25.56	H	Peak
7642.000	40.64	8.95	49.59	74.00	-24.41	H	Peak

**REMARKS:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).

**Test Mode:** TX / IEEE 802.11g (CH Mid)**Tested by:** Saber Huang**Ambient temperature:** 24°C**Relative humidity:** 52% RH**Date:** November 16, 2016

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1999.000	49.38	-5.01	44.37	74.00	-29.63	V	Peak
2836.000	45.19	-1.66	43.53	74.00	-30.47	V	Peak
3916.000	43.30	1.24	44.54	74.00	-29.46	V	Peak
5653.000	41.66	5.93	47.59	74.00	-26.41	V	Peak
6544.000	41.44	6.96	48.40	74.00	-25.60	V	Peak
7615.000	40.06	8.90	48.96	74.00	-25.04	V	Peak
1999.000	47.22	-5.01	42.21	74.00	-31.79	H	Peak
2512.000	47.15	-2.24	44.91	74.00	-29.09	H	Peak
3799.000	43.51	0.74	44.25	74.00	-29.75	H	Peak
5095.000	42.28	5.15	47.43	74.00	-26.57	H	Peak
6553.000	40.82	6.98	47.80	74.00	-26.20	H	Peak
7705.000	41.21	9.07	50.28	74.00	-23.72	H	Peak

**REMARKS:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



Test Mode: TX / IEEE 802.11g (CH High)

Tested by: Saber HuangAmbient temperature: 24°C Relative humidity: 52% RH Date: November 16, 2016

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
2242.000	46.55	-3.67	42.88	74.00	-31.12	V	Peak
2548.000	46.50	-2.17	44.33	74.00	-29.67	V	Peak
4843.000	42.28	4.47	46.75	74.00	-27.25	V	Peak
5734.000	42.05	5.97	48.02	74.00	-25.98	V	Peak
6877.000	41.11	7.50	48.61	74.00	-25.39	V	Peak
7570.000	40.78	8.81	49.59	74.00	-24.41	V	Peak
1999.000	49.77	-5.01	44.76	74.00	-29.24	H	Peak
2512.000	46.14	-2.24	43.90	74.00	-30.10	H	Peak
4006.000	42.80	1.61	44.41	74.00	-29.59	H	Peak
5464.000	42.76	5.81	48.57	74.00	-25.43	H	Peak
6571.000	41.14	7.01	48.15	74.00	-25.85	H	Peak
7768.000	41.74	9.20	50.94	74.00	-23.06	H	Peak

**REMARKS:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).

Test Mode: TX / IEEE 802.11n HT20 MHz (CH Low)Tested by: Saber HuangAmbient temperature: 24°CRelative humidity: 52% RHDate: November 16, 2016

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
2809.000	44.52	-1.70	42.82	74.00	-31.18	V	Peak
4024.000	42.22	1.67	43.89	74.00	-30.11	V	Peak
4618.000	41.69	3.73	45.42	74.00	-28.58	V	Peak
5662.000	41.65	5.94	47.59	74.00	-26.41	V	Peak
6814.000	41.48	7.40	48.88	74.00	-25.12	V	Peak
7318.000	41.02	8.32	49.34	74.00	-24.66	V	Peak
1999.000	47.23	-5.01	42.22	74.00	-31.78	H	Peak
2890.000	45.72	-1.56	44.16	74.00	-29.84	H	Peak
4348.000	42.06	2.81	44.87	74.00	-29.13	H	Peak
5410.000	41.90	5.71	47.61	74.00	-26.39	H	Peak
6139.000	42.52	6.31	48.83	74.00	-25.17	H	Peak
7255.000	41.61	8.20	49.81	74.00	-24.19	H	Peak

**REMARKS:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



Test Mode: TX / IEEE 802.11n HT20 MHz (CH Mid)

Tested by: Saber Huang

Ambient temperature: 24°C

Relative humidity: 52% RH

Date: November 16, 2016

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
2242.000	45.44	-3.67	41.77	74.00	-32.23	V	Peak
2494.000	46.52	-2.29	44.23	74.00	-29.77	V	Peak
4609.000	42.36	3.71	46.07	74.00	-27.93	V	Peak
4870.000	41.72	4.56	46.28	74.00	-27.72	V	Peak
5473.000	41.36	5.82	47.18	74.00	-26.82	V	Peak
7219.000	40.96	8.13	49.09	74.00	-24.91	V	Peak
1990.000	47.93	-5.06	42.87	74.00	-31.13	H	Peak
3214.000	44.09	-1.00	43.09	74.00	-30.91	H	Peak
4888.000	42.37	4.61	46.98	74.00	-27.02	H	Peak
5806.000	41.54	6.00	47.54	74.00	-26.46	H	Peak
7210.000	40.78	8.11	48.89	74.00	-25.11	H	Peak
7957.000	40.85	9.57	50.42	74.00	-23.58	H	Peak

**REMARKS:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).

**Test Mode:** TX / EEE 802.11n HT20 MHz (CH High)**Tested by:** Saber Huang**Ambient temperature:** 24°C**Relative humidity:** 52% RH**Date:** November 16, 2016

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1999.000	52.07	-5.01	47.06	74.00	-26.94	V	Peak
3331.000	44.95	-0.80	44.15	74.00	-29.85	V	Peak
4582.000	42.04	3.62	45.66	74.00	-28.34	V	Peak
5212.000	41.62	5.36	46.98	74.00	-27.02	V	Peak
5437.000	42.71	5.76	48.47	74.00	-25.53	V	Peak
7354.000	40.68	8.39	49.07	74.00	-24.93	V	Peak
1504.000	48.59	-6.87	41.72	74.00	-32.28	H	Peak
2539.000	46.50	-2.19	44.31	74.00	-29.69	H	Peak
3358.000	44.14	-0.76	43.38	74.00	-30.62	H	Peak
4303.000	42.20	2.66	44.86	74.00	-29.14	H	Peak
5221.000	41.21	5.37	46.58	74.00	-27.42	H	Peak
6166.000	41.08	6.35	47.43	74.00	-26.57	H	Peak

**REMARKS:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



Test Mode: TX/ IEEE 802.11n HT40 MHz (CH Low)Tested by: Saber HuangAmbient temperature: 24°CRelative humidity: 52% RHDate: November 16, 2016

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1999.000	47.30	-5.01	42.29	74.00	-31.71	V	Peak
3718.000	43.20	0.40	43.60	74.00	-30.40	V	Peak
4420.000	42.98	3.07	46.05	74.00	-27.95	V	Peak
5113.000	41.62	5.18	46.80	74.00	-27.20	V	Peak
6364.000	40.64	6.67	47.31	74.00	-26.69	V	Peak
7444.000	40.59	8.57	49.16	74.00	-24.84	V	Peak
1999.000	48.97	-5.01	43.96	74.00	-30.04	H	Peak
2530.000	45.60	-2.21	43.39	74.00	-30.61	H	Peak
3925.000	42.25	1.27	43.52	74.00	-30.48	H	Peak
4897.000	41.40	4.64	46.04	74.00	-27.96	H	Peak
5644.000	40.96	5.93	46.89	74.00	-27.11	H	Peak
7138.000	41.72	7.97	49.69	74.00	-24.31	H	Peak

**REMARKS:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



**Test Mode:** TX / IEEE 802.11n HT40 MHz (CH Mid)**Tested by:** Saber Huang**Ambient temperature:** 24°C**Relative humidity:** 52% RH**Date:** November 16, 2016

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
2512.000	47.04	-2.24	44.80	74.00	-29.20	V	Peak
3754.000	42.72	0.55	43.27	74.00	-30.73	V	Peak
4888.000	41.63	4.61	46.24	74.00	-27.76	V	Peak
5410.000	41.16	5.71	46.87	74.00	-27.13	V	Peak
6067.000	41.01	6.19	47.20	74.00	-26.80	V	Peak
6661.000	41.31	7.15	48.46	74.00	-25.54	V	Peak
1162.000	50.23	-7.94	42.29	74.00	-31.71	H	Peak
1990.000	47.84	-5.06	42.78	74.00	-31.22	H	Peak
2512.000	46.26	-2.24	44.02	74.00	-29.98	H	Peak
4456.000	41.97	3.20	45.17	74.00	-28.83	H	Peak
5716.000	41.15	5.96	47.11	74.00	-26.89	H	Peak
7894.000	40.26	9.44	49.70	74.00	-24.30	H	Peak

**REMARKS:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).

Test Mode: TX/ IEEE 802.11n HT40 MHz (CH High)Tested by: Saber HuangAmbient temperature: 24°CRelative humidity: 52% RHDate: November 16, 2016

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1504.000	50.17	-6.87	43.30	74.00	-30.70	V	Peak
1990.000	52.78	-5.06	47.72	74.00	-26.28	V	Peak
2818.000	45.69	-1.69	44.00	74.00	-30.00	V	Peak
4843.000	42.48	4.47	46.95	74.00	-27.05	V	Peak
5113.000	42.54	5.18	47.72	74.00	-26.28	V	Peak
6634.000	40.32	7.11	47.43	74.00	-26.57	V	Peak
2v242.000	44.38	-3.67	40.71	74.00	-33.29	H	Peak
2557.000	44.91	-2.16	42.75	74.00	-31.25	H	Peak
3241.000	43.50	-0.96	42.54	74.00	-31.46	H	Peak
4312.000	42.06	2.69	44.75	74.00	-29.25	H	Peak
4870.000	43.18	4.56	47.74	74.00	-26.26	H	Peak
6409.000	40.72	6.74	47.46	74.00	-26.54	H	Peak

**REMARKS:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



### 7.3. 6dB BANDWIDTH MEASUREMENT

#### 7.3.1. LIMITS

According to §15.247(a)(2), systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz. The minimum 6 dB bandwidth shall be at least 500 kHz.

#### 7.3.2. TEST INSTRUMENTS


Name of Equipment	Manufacturer	Model	Serial Number	Last Calibration	Calibration Due
Spectrum Analyzer	Agilent	N9010A	MY52221469	02/21/2016	02/20/2017

#### 7.3.3. TEST PROCEDURES (please refer to measurement standard)

##### 8.1 Option 2:

The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described above (i.e., RBW = 100 kHz, VBW  $\geq$  3 RBW, peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be  $\geq$  6 dB.

#### 7.3.4. TEST SETUP



**7.3.5. TEST RESULTS***No non-compliance noted***Test Data****Test mode: IEEE 802.11b**

Channel	Frequency (MHz)	Bandwidth (kHz)	Limit (kHz)	Test Result
Low	2412	10080	>500	PASS
Mid	2437	10100		PASS
High	2462	10080		PASS

**Test mode: IEEE 802.11g**

Channel	Frequency (MHz)	Bandwidth (kHz)	Limit (kHz)	Test Result
Low	2412	16590	>500	PASS
Mid	2437	16590		PASS
High	2462	16590		PASS

**Test mode: IEEE 802.11n HT20 MHz**

Channel	Frequency (MHz)	Bandwidth (kHz)	Limit (kHz)	Test Result
Low	2412	17830	>500	PASS
Mid	2437	17830		PASS
High	2462	17830		PASS

**Test mode: IEEE 802.11n HT40 MHz**


Channel	Frequency (MHz)	Bandwidth (kHz)	Limit (kHz)	Test Result
Low	2422	36320	>500	PASS
Mid	2437	36330		PASS
High	2452	36310		PASS




## Test Plot


### IEEE 802.11b mode

#### 6dB Bandwidth (CH Low)



#### 6dB Bandwidth (CH Mid)










## IEEE 802.11g mode

### 6dB Bandwidth (CH Low)



### 6dB Bandwidth (CH Mid)












## IEEE 802.11n HT20 MHz mode

### 6dB Bandwidth (CH Low)



### 6dB Bandwidth (CH Mid)










## IEEE 802.11n HT40 MHz mode

### 6dB Bandwidth (CH Low)



### 6dB Bandwidth (CH Mid)







## 7.4. ANTENNA GAIN

### MEASUREMENT

The antenna gain of the complete system is calculated by the difference of radiated power in EIRP and the conducted power of the module. For normal WLAN devices, the DSSS mode is used.

### MEASUREMENT PARAMETERS

Measurement parameter	
Detector	Peak
Sweep time	Auto
Resolution bandwidth	3 MHz
Video bandwidth	3 MHz
Trace-Mode	Max hold

### LIMITS

FCC	IC
Antenna Gain	
6 dBi	



## TEST RESULTS

### IEEE 802.11b mode

$T_{nom}$	$V_{nom}$	Lowest channel 2412MHz	Middle channel 2437MHz	Highest channel 2462MHz
Conducted power [dBm/MHz] Measured with DSSS modulation		18.79	20.03	22.35
Radiated power [dBm/MHz] Measured with DSSS modulation		20.05	21.25	22.86
Gain [dBi] Calculated		1.26	1.22	0.51
Measurement uncertainty		$\pm 1.5$ dB (cond.) / $\pm 3$ dB (rad.)		



## 7.5. PEAK OUTPUT POWER

### 7.5.1. LIMITS

The maximum peak output power of the intentional radiator shall not exceed the following:

1. According to §15.247(b)(3), for systems using digital modulation in the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz: 1 Watt.
2. According to §15.247(b)(4), the conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### 7.5.2. TEST INSTRUMENTS

Name of Equipment	Manufacturer	Model	Serial Number	Last Calibration	Calibration Due
Power Meter	Anritsu	ML2495A	1204003	02/21/2016	02/20/2017
Power Sensor	Anritsu	MA2411B	1126150	02/21/2016	02/20/2017

### 7.5.3. TEST PROCEDURES (please refer to measurement standard)

#### 9.1.1 RBW $\geq$ DTS bandwidth


This procedure shall be used when the measurement instrument has available a resolution bandwidth that is greater than the *DTS bandwidth*.

- a) Set the RBW  $\geq$  DTS bandwidth.
- b) Set VBW  $\geq$  3 RBW.
- c) Set span  $\geq$  3 x RBW
- d) Sweep time = auto couple.
- e) Detector = peak.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use peak marker function to determine the peak amplitude level.

#### 9.1.2 PKPM1 Peak power meter method

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

### 7.5.4. TEST SETUP



**7.5.5. TEST RESULTS***No non-compliance noted***Test Data****Test mode: IEEE 802.11b**

Channel	Frequency (MHz)	Output Power (dBm)	Output Power (W)	Peak / AVG	Limit (W)	Result
Low	2412	18.79	0.07568	Peak	1	PASS
Mid	2437	20.03	0.10069			PASS
High	2462	22.35	0.17179			PASS
Low	2412	16.31	0.04276	AVG	1	PASS
Mid	2437	17.74	0.05943			PASS
High	2462	18.96	0.07870			PASS

**Test mode: IEEE 802.11g**

Channel	Frequency (MHz)	Output Power (dBm)	Output Power (W)	Peak / AVG	Limit (W)	Result
Low	2412	21.85	0.15311	Peak	1	PASS
Mid	2437	21.97	0.15740			PASS
High	2462	21.78	0.15066			PASS
Low	2412	12.67	0.01849	AVG	1	PASS
Mid	2437	12.44	0.01754			PASS
High	2462	12.19	0.01656			PASS

**Test mode: IEEE 802.11n HT20 MHz**

Channel	Frequency (MHz)	Output Power (dBm)	Output Power (W)	Peak / AVG	Limit (W)	Result
Low	2412	21.46	0.13996	Peak	1	PASS
Mid	2437	21.60	0.14454			PASS
High	2462	22.14	0.16368			PASS
Low	2412	12.42	0.01746	AVG	1	PASS
Mid	2437	12.92	0.01959			PASS
High	2462	13.43	0.02203			PASS





Test mode: IEEE 802.11n HT40 MHz

Channel	Frequency (MHz)	Output Power (dBm)	Output Power (W)	Peak / AVG	Limit (W)	Result
Low	2422	21.45	0.13964	Peak	1	PASS
Mid	2437	21.61	0.14488			PASS
High	2452	22.36	0.17219			PASS
Low	2422	11.59	0.01442	AVG	1	PASS
Mid	2437	12.27	0.01687			PASS
High	2452	12.73	0.01875			PASS



## 7.6. BAND EDGES MEASUREMENT

### 7.6.1. LIMITS

According to §15.247(d), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in 15.209(a) (see Section 15.205(c)).

### 7.6.2. TEST INSTRUMENTS

Radiated Emission Test Site 966 (2)					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
PSA Series Spectrum Analyzer	Agilent	E4446A	US44300399	02/21/2016	02/20/2017
EMI TEST RECEIVER	ROHDE&SCHWARZ	ESCI	100783	02/21/2016	02/20/2017
Amplifier	EMEC	EM330	060661	03/18/2016	03/17/2017
High Noise Amplifier	Agilent	8449B	3008A01838	02/21/2016	02/20/2017
Loop Antenna	COM-POWER	AL-130	121044	09/25/2016	09/24/2017
Bilog Antenna	SCHAFFNER	CBL6143	5082	02/21/2016	02/20/2017
Horn Antenna	SCHWARZBECK	BBHA9120	D286	02/28/2016	02/27/2017
Board-Band Horn Antenna	Schwarzbeck	BBHA 9170	9170-497	02/28/2016	02/27/2017
Turn Table	N/A	N/A	N/A	N.C.R	N.C.R
Antenna Tower	SUNOL	TLT2	N/A	N.C.R	N.C.R
Controller	Sunol Sciences	SC104V	022310-1	N.C.R	N.C.R
Controller	CT	N/A	N/A	N.C.R	N.C.R
Temp. / Humidity Meter	Anymetre	JR913	N/A	02/21/2016	02/20/2017
Test S/W	FARAD	LZ-RF / CCS-SZ-3A2			


**NOTE:** 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

2. The FCC Site Registration number is 101879.

3. N.C.R = No Calibration Required.

**7.6.3. TEST PROCEDURES** (please refer to measurement standard)

1. The EUT is placed on a turntable, which is 1.5m above the ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.
4. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:
  - (a) PEAK: RBW=1MHz / VBW=3MHz / Sweep=AUTO
  - (b) AVERAGE: RBW=1MHz / VBW=10Hz / Sweep=AUTO / Detector=PEAK
5. Repeat the procedures until all the PEAK and AVERAGE versus POLARIZATION are

**7.6.4. TEST SETUP**




## 7.6.5. TEST RESULTS

Test Plot

IEEE 802.11b mode

Band Edges (CH Low)




No.	Frequency (MHz)	Reading (dBuV)	Corrected (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Pole
1	2390.0000	46.63	-6.60	53.23	74.00	-20.77	Peak	Vertical
2	2390.0000	34.62	-6.60	41.22	54.00	-12.78	Average	Vertical




Detector mode: Peak

Polarity: Horizontal



Detector mode: Average



Polarity: Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Corrected (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Pole
1	2390.0000	46.20	-6.60	52.80	74.00	-21.20	Peak	Horizontal
2	2390.0000	34.53	-6.60	41.13	54.00	-12.87	Average	Horizontal



## Band Edges (CH High)



No.	Frequency (MHz)	Reading (dBuV)	Corrected (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Pole
1	2483.5000	48.32	-6.24	54.56	74.00	-19.44	Peak	Vertical
2	2483.5000	35.94	-6.24	42.18	54.00	-11.83	Average	Vertical




Detector mode: Peak

Polarity: Horizontal



Detector mode: Average

Polarity: Horizontal





No.	Frequency (MHz)	Reading (dBμV)	Corrected (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Pole
1	2483.5000	48.95	-6.24	55.19	74.00	-18.82	Peak	Horizontal
2	2483.5000	36.13	-6.24	42.37	54.00	-11.63	Average	Horizontal




## IEEE 802.11g mode

## Band Edges (CH Low)



No.	Frequency (MHz)	Reading (dBuV)	Corrected (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Pole
1	2390.0000	46.33	-6.60	52.93	74.00	-21.07	Peak	Vertical
2	2390.0000	34.63	-6.60	41.23	54.00	-12.77	Average	Vertical







No.	Frequency (MHz)	Reading (dBuV)	Corrected (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Pole
1	2390.0000	48.12	-6.60	54.72	74.00	-19.28	Peak	Horizontal
2	2390.0000	34.56	-6.60	41.16	54.00	-12.84	Average	Horizontal



### Band Edges (CH High)



No.	Frequency (MHz)	Reading (dBuV)	Corrected (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Pole
1	2483.5000	53.81	-6.24	60.05	74.00	-13.95	Peak	Vertical
2	2483.5000	35.83	-6.24	42.07	54.00	-11.93	Average	Vertical




## Detector mode: Peak

## Polarity: Horizontal



## Detector mode: Average

## Polarity: Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Corrected (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Pole
1	2483.5000	55.75	-6.24	61.99	74.00	-12.01	Peak	Horizontal
2	2483.5000	36.03	-6.24	42.27	54.00	-11.73	Average	Horizontal




## IEEE 802.11n HT20 MHz mode

## Band Edges (CH Low)


Detector mode: Peak

Polarity: Vertical




Detector mode: Average

Polarity: Vertical




No.	Frequency (MHz)	Reading (dBuV)	Corrected (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Pole
1	2390.0000	48.17	-6.60	54.77	74.00	-19.23	Peak	Vertical
2	2390.0000	34.68	-6.60	41.28	54.00	-12.72	Average	Vertical




No.	Frequency (MHz)	Reading (dBuV)	Corrected (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Pole
1	2390.0000	47.41	-6.60	54.01	74.00	-19.99	Peak	Horizontal
2	2390.0000	34.53	-6.60	41.13	54.00	-12.87	Average	Horizontal



## Band Edges (CH High)



No.	Frequency (MHz)	Reading (dBuV)	Corrected (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Pole
1	2483.5000	54.43	-6.24	60.67	74.00	-13.33	Peak	Vertical
2	2483.5000	36.02	-6.24	42.26	54.00	-11.74	Average	Vertical




No.	Frequency (MHz)	Reading (dBuV)	Corrected (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Pole
1	2483.5000	54.69	-6.24	60.93	74.00	-13.07	Peak	Horizontal
2	2483.5000	36.24	-6.24	42.48	54.00	-11.52	Average	Horizontal




## IEEE 802.11n HT40 MHz mode

## Band Edges (CH Low)



No.	Frequency (MHz)	Reading (dBuV)	Corrected (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Pole
1	2390.0000	46.86	-6.60	53.46	74.00	-20.54	Peak	Vertical
2	2390.0000	34.83	-6.60	41.43	54.00	-12.57	Average	Vertical







No.	Frequency (MHz)	Reading (dBuV)	Corrected (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Pole
1	2390.0000	46.18	-6.60	52.78	74.00	-21.22	Peak	Horizontal
2	2390.0000	34.64	-6.60	41.24	54.00	-12.76	Average	Horizontal




## Band Edges (CH High)




No.	Frequency (MHz)	Reading (dBuV)	Corrected (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Pole
1	2483.5000	50.61	-6.24	56.85	74.00	-17.15	Peak	Vertical
2	2483.5000	36.14	-6.24	42.38	54.00	-11.62	Average	Vertical



Detector mode: Peak Polarity: Horizontal



Detector mode: Average Polarity: Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Corrected (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Pole
1	2483.5000	50.93	-6.24	57.17	74.00	-16.83	Peak	Horizontal
2	2483.5000	36.42	-6.24	42.66	54.00	-11.34	Average	Horizontal



## 7.7. PEAK POWER SPECTRAL DENSITY MEASUREMENT

### 7.7.1. LIMITS

According to §15.247(e), for digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

According to §15.247(f), the digital modulation operation of the hybrid system, with the frequency hopping turned off, shall comply with the power density requirements of paragraph (d) of this section.

### 7.7.2. TEST INSTRUMENTS

Name of Equipment	Manufacturer	Model	Serial Number	Last Calibration	Calibration Due
Spectrum Analyzer	Agilent	N9010A	MY52221469	02/21/2016	02/20/2017


### 7.7.3. TEST PROCEDURES (please refer to measurement standard)

§15.247(e) specifies a conducted power spectral density (PSD) limit of 8 dBm in any 3 kHz band segment within the fundamental EBW during any time interval of continuous transmission. The same method as used to determine the conducted output power shall be used to determine the power spectral density (i.e., if peak-detected fundamental power was measured then use the peak PSD procedure and if average fundamental power was measured then use the average PSD procedure).

### 10.2 Method PKPSD (peak PSD)

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS bandwidth.
3. Set the RBW to:  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ .
4. Set the VBW  $\geq 3 \times \text{RBW}$ .
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

### 7.7.4. TEST SETUP



**7.7.5. TEST RESULTS***No non-compliance noted***Test Data****Test mode: IEEE 802.11b**

Channel	Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Test Result
Low	2412	-5.965	8	PASS
Mid	2437	-5.815		PASS
High	2462	-5.904		PASS

**Test mode: IEEE 802.11g**

Channel	Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Test Result
Low	2412	-6.778	8	PASS
Mid	2437	-7.069		PASS
High	2462	-6.598		PASS

**Test mode: IEEE 802.11n HT20 MHz**

Channel	Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Test Result
Low	2412	-6.975	8	PASS
Mid	2437	-6.695		PASS
High	2462	-6.389		PASS

**Test mode: IEEE 802.11n HT40 MHz**


Channel	Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Test Result
Low	2422	-6.924	8	PASS
Mid	2437	-6.853		PASS
High	2452	-6.232		PASS




## Test Plot


### IEEE 802.11b mode

#### PPSD (CH Low)



#### PPSD (CH Mid)









## IEEE 802.11g mode


### PPSD (CH Low)



### PPSD (CH Mid)












## IEEE 802.11n HT20 MHz mode

### PPSD (CH Low)



### PPSD (CH Mid)








## IEEE 802.11n HT40 MHz mode

### PPSD (CH Low)



### PPSD (CH Mid)

