

# ISED SAR Test Report

**ISED ID: 21203-LS35X**

**FCC ID: 2AGZWLS35X**

**Project No.** : 1808T008  
**Equipment** : Wireless Headset  
**Model Name** : LS35X  
**Applicant** : LucidSound Inc.  
**Address** : 5939 Darwin Ct.  
Suite 100  
Carlsbad, CA 92008  
United States

**Date of Receipt** : Aug, 02. 2018  
**Date of Test** : Oct, 23. 2018  
**Issued Date** : Oct, 29. 2018  
**Tested by** : BTL Inc.

**PREPARED BY** :

(Morrison Huang)

**APPROVED BY** :

(Herbert Liu)

## **B T L I N C .**

No. 68-1, Ln. 169, Sec.2, Datong Rd., Xizhi Dist.,  
New Taipei City 221, Taiwan  
TEL:+886-2-2657-3299 FAX: +886-2-2657-3331



### **Declaration**

**BTL** represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with standards traceable to international standard(s) and/or national standard(s).

**BTL's** reports apply only to the specific samples tested under conditions. It is manufacture's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. **BTL** shall have no liability for any declarations, inferences or generalizations drawn by the client or others from **BTL** issued reports.

**BTL's** report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

This report is the confidential property of the client. As a mutual protection to the clients, the public and **BTL-self**, extracts from the test report shall not be reproduced except in full with **BTL's** authorized written approval.

**BTL's** laboratory quality assurance procedures are in compliance with the **ISO Guide17025** requirements, and accredited by the conformity assessment authorities listed in this test report.

### **Limitation**

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.

<b>Table of Contents</b>	<b>Page</b>
<b>1. GENERAL SUMMARY</b>	<b>5</b>
<b>2. RF EMISSIONS MEASUREMENT</b>	<b>6</b>
2.1. TEST FACILITY	6
<b>3. GENERAL INFORMATION</b>	<b>9</b>
3.1. STATEMENT OF COMPLIANCE	9
3.2. GENERAL DESCRIPTION OF EUT	10
3.3. LABORATORY ENVIRONMENT	10
3.4. MAIN TEST INSTRUMENTS	11
<b>4. SAR MEASUREMENTS SYSTEM CONFIGURATION</b>	<b>12</b>
4.1. SAR MEASUREMENT SET-UP	12
4.2. DASY5E-FIELDPROBESYSTEM	13
<b>5. SYSTEM VERIFICATION PROCEDURE</b>	<b>21</b>
5.1. TISSUE VERIFICATION	21
5.2. SYSTEM CHECK	23
5.3. SYSTEM CHECK PROCEDURE	23
<b>6. SAR MEASUREMENT VARIABILITY AND UNCERTAINTY</b>	<b>24</b>
6.1. SAR MEASUREMENT VARIABILITY	24
<b>7. OPERATIONAL CONDITIONS DURING TEST</b>	<b>25</b>
7.1. SAR TEST CONFIGURATION	25
7.1.1. WLAN TEST CONFIGURATION	25
7.2. 2.4G SAR TEST REQUIREMENTS	25
7.2 TEST POSITION	26
<b>8. TEST RESULT</b>	<b>27</b>
8.1. CONDUCTED POWER RESULTS	27
8.2. SAR TEST RESULTS	30
<b>APPENDIX</b>	<b>33</b>
<b>1. TEST LAYOUT</b>	<b>33</b>
Appendix A. SAR Plots of System Verification	
Appendix B. SAR Plots of SAR Measurement	
Appendix C. Calibration Certificate for Probe and Dipole	
Appendix D. Photographs of the Test Set-Up	

### REPORT ISSUED HISTORY

Report Version	Description	Issued Date
R00	Original Issue	Oct. 29, 2018

## 1. GENERAL SUMMARY

Equipment	Wireless Headset
Brand Name	LucidSound
Model Name	LS35X
Manufacturer	Ampacs corp.
Address	3F., No.19-3, Sanchong Rd., Nangang Dist., Taipei City 11501, Taiwan
Factory	YiXin Electronics Co.
Address	Dong Guan YiXin Electronics Co.
Standard(s)	<p><b>RSS-102 Issue 5</b> Radio Frequency (RF) Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands)</p> <p><b>IEEE Std 1528-2013</b> Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques</p> <p><b>KDB447498 D01</b> General RF Exposure Guidance v06</p> <p><b>KDB248227 D01</b> 802. 11 Wi-Fi SAR v02r02</p> <p><b>KDB865664 D01</b> SAR measurement 100 MHz to 6 GHz v01r04</p>

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.

The test data, data evaluation, and equipment configuration contained in our test report (Ref No. BTL- ISED SAR-1808T008) were obtained utilizing the test procedures, test instruments, test sites that has been accredited by the Authority of TAF according to the ISO-17025 quality assessment standard and technical standard(s).

## 2. RF EMISSIONS MEASUREMENT

### 2.1. TEST FACILITY

The test facilities used to collect the test data in this report is **SAR room** at the location of No. 68-1, Ln. 169, Sec.2, Datong Rd., Xizhi Dist., New Taipei City 221, Taiwan..

## 2.2. MEASUREMENT UNCERTAINTY

Uncertainty Budget for Frequency range of 300 MHz to 3 GHz

Error Description	Uncertainty Value (± %)	Probability Distribution	Divisor	Ci (1g)	Ci (10g)	Standard Uncertainty (10g)	Vi V <sub>eff</sub>
<b>Measurement System</b>							
Probe Calibration	6.0	Normal	1	1	1	± 6.0 %	∞
Axial Isotropy	4.7	Rectangular	√3	0.7	0.7	± 1.9 %	∞
Hemispherical Isotropy	9.6	Rectangular	√3	0.7	0.7	± 3.9 %	∞
Boundary Effects	1.0	Rectangular	√3	1	1	± 0.6 %	∞
Linearity	4.7	Rectangular	√3	1	1	± 2.7 %	∞
Detection Limits	1	Rectangular	√3	1	1	± 0.6 %	∞
Modulation response	2.4	Rectangular	√3	1	1	±1.4 %	∞
Readout Electronics	0.3	Normal	1	1	1	± 0.3 %	∞
Response Time	0.8	Rectangular	√3	1	1	± 0.5 %	∞
Integration Time	2.6	Rectangular	√3	1	1	± 1.5 %	∞
RF Ambient – Noise	3.0	Rectangular	√3	1	1	± 1.7 %	∞
RF Ambient– Reflections	3.0	Rectangular	√3	1	1	± 1.7 %	∞
Probe Positioner	0.4	Rectangular	√3	1	1	± 0.2 %	∞
Probe Positioning	2.9	Rectangular	√3	1	1	± 1.7 %	∞
Max.SAR Evaluation	2.0	Rectangular	√3	1	1	± 1.2 %	∞
<b>Test Sample Related</b>							
Device Positioning	2.2	Normal	1	1	1	± 2.2 %	145
Device Holder	1.6	Normal	1	1	1	± 1.6 %	5
Power Drift	5.0	Rectangular	√3	1	1	± 2.9 %	∞
<b>Phantom and Setup</b>							
Phantom Production Tolerances	6.1	Rectangular	√3	1	1	±3.5 %	∞
SAR correction	1.9	Rectangular	√3	1	0.84	± 0.9 %	∞
Liquid Conductivity (mea.)	2.5	Rectangular	√3	0.78	0.71	± 1.0 %	∞
Liquid Permittivity (mea.)	2.5	Rectangular	√3	0.26	0.26	± 0.4 %	∞
Temp. unc. – Conductivity	3.4	Rectangular	√3	0.78	0.71	± 1.4 %	∞
Temp. unc. – Permittivity	0.4	Rectangular	√3	0.23	0.26	± 0.1 %	∞
<b>Combined Standard Uncertainty (K = 1)</b>						± 10.5 %	361
<b>Expanded Uncertainty (K = 2)</b>						± 21.0 %	

Uncertainty Budget for Frequency range of 3 GHz to 6 GHz

Uncertainty Budget for Frequency range of 300 MHz to 3 GHz Error Description	Uncertainty Value (± %)	Probability Distribution	Divisor	Ci (10g)	Standard Uncertainty (10g)	Vi V <sub>eff</sub>
<b>Measurement System</b>						
Probe Calibration	6.0	Normal	1	1	± 6.55 %	∞
Axial Isotropy	4.7	Rectangular	√3	0.7	± 1.9 %	∞
Hemispherical Isotropy	9.6	Rectangular	√3	0.7	± 3.9 %	∞
Boundary Effects	1.0	Rectangular	√3	1	± 1.2 %	∞
Linearity	4.7	Rectangular	√3	1	± 2.7 %	∞
Detection Limits	1	Rectangular	√3	1	± 0.6 %	∞
Modulation response	2.4	Rectangular	√3	1	± 1.4 %	∞
Readout Electronics	0.3	Normal	1	1	± 0.3 %	∞
Response Time	0.8	Rectangular	√3	1	± 0.5 %	∞
Integration Time	2.6	Rectangular	√3	1	± 1.5 %	∞
RF Ambient – Noise	3.0	Rectangular	√3	1	± 1.7 %	∞
RF Ambient– Reflections	3.0	Rectangular	√3	1	± 1.7 %	∞
Probe Positioner	0.4	Rectangular	√3	1	± 0.5 %	∞
Probe Positioning	2.9	Rectangular	√3	1	± 3.9 %	∞
Max.SAR Evaluation	2.0	Rectangular	√3	1	± 2.3 %	∞
<b>Test Sample Related</b>						
Device Positioning	2.2	Normal	1	1	± 2.2 %	145
Device Holder	1.6	Normal	1	1	± 1.6 %	5
Power Drift	5.0	Rectangular	√3	1	± 2.9 %	∞
<b>Phantom and Setup</b>						
Phantom Production Tolerances	± 3.8 %	Rectangular	√3	1	± 3.5 %	∞
SAR correction	± 0.9 %	Rectangular	√3	0.84	± 0.9 %	∞
Liquid Conductivity (mea.)	± 1.0 %	Rectangular	√3	0.71	± 1.0 %	∞
Liquid Permittivity (mea.)	± 0.4 %	Rectangular	√3	0.26	± 0.4 %	∞
Temp. unc. – Conductivity	± 1.4 %	Rectangular	√3	0.71	± 1.4 %	∞
Temp. unc. – Permittivity	± 0.1 %	Rectangular	√3	0.26	± 0.1 %	∞
<b>Combined Standard Uncertainty (K = 1)</b>					± 11.7 %	748
<b>Expanded Uncertainty (K = 2)</b>					± 23.4 %	



### 3. GENERAL INFORMATION

#### 3.1. STATEMENT OF COMPLIANCE

Equipment Class	Mode	Highest Head SAR-1g (W/kg)
DTS	WLAN2.4G	<0.001
NII	WLAN5.3G	<0.001
	WLAN5.6G	0.014
	WLAN5.8G	<0.001

Note:

- 1) The device is in compliance with Specific Absorption Rate(SAR)for general population uncontrolled exposure limits according to the RSS-102 Issue 5, ,the NCRP Report Number 86 for uncontrolled environment and had been tested in accordance with the measurement methods and procedures specified in IEEE Std 1528-2013 .

### 3.2. GENERAL DESCRIPTION OF EUT

Equipment	LucidSound				
Model Name	LS35X				
Modulation	WiFi(DSSS/OFDM)				
Operation Frequency Range(s)	WiFi2.4G 802.11b/g/n HT20	2412~2462 MHz			
	WiFi5.2G 802.11a/n HT20	5150-5250 MHz			
	WiFi5.3G 802.11a/n HT20	5250-5350 MHz			
	WiFi5.6G 802.11a/n HT20	5470-5725 MHz			
	WiFi5.8G 802.11a/n HT20	5725-5850 MHz			
<b>Information</b>					
Antenna Gain	Operating Band	Peak Gian (dBi)	Product Description	Model No.	Vendor
	WIFI2.4G	3.98	Chip	WAN7020LD25N04	ONEWAVE
	WIFI5.2G	3.83	Chip	WAN7020LD25N04	ONEWAVE
	WIFI5.2G	3.83	Chip	WAN7020LD25N04	ONEWAVE
	WIFI5.6G	4.73	Chip	WAN7020LD25N04	ONEWAVE
	WIFI5.8G	5.02	Chip	WAN7020LD25N04	ONEWAVE

### 3.3. LABORATORY ENVIRONMENT

Temperature	Min. = 18°C, Max. = 25°C
Relative humidity	Min. = 30%, Max. = 70%
Ground system resistance	< 0.5Ω
Ambient noise is checked and found very low and in compliance with requirement of standards.	
Reflection of surrounding objects is minimized and in compliance with requirement of standards.	

### 3.4. MAIN TEST INSTRUMENTS

Item	Equipment	Manufacturer	Model	Serial No.	Cal. Date	Cal. Interval
1	E-field Probe	Speag	EX3DV4	7396	May. 29, 2018	1 Year
2	Data Acquisition Electronics	Speag	DAE4	1390	May. 11, 2018	1 Year
3	System Validation Dipole	Speag	D2450V2	919	Jun. 11, 2018	3 Year
4	System Validation Dipole	Speag	D5GHzV2	1160	Jun. 20, 2018	3 Year
5	Twin Sam Phantom	Speag	Twin Sam Phantom V5.0	1896	N/A	N/A
6	ENA Network Analyzer	Keysight	E5071C	MY46524658	Dec. 14, 2017	1 Year
7	EXG-B RF Vector Signal Generator	keysight	N5172B	MY56200462	April. 23, 2018	1 Year
8	Spectrym Analyzer	Keysight	N9020A	MY52091060	Mar. 06, 2018	1 Year
9	Power Meter	Anritsu	ML2495A	1128008	Oct. 01, 2018	1 Year
10	Power Sensor	Anritsu	MA2411B	1126001	Oct. 01, 2018	1 Year
11	Power Meter	Anritsu	ML2487A	6K00004714	Sep. 06. 2018	1 Year
12	Power Sensor	Anritsu	MA2411A	34138	Sep. 06. 2018	1 Year
13	Dielectric Assessment Kit	Speag	DAK-3.5	1226	Dec. 09, 2015	N/A
14	Dual directional coupler	Woken	TS-PCC0M-05	107090019	May 15, 2018	1 Year
15	Power Amplifier	Mini-Circuits	ZVE-2W-272+	N650001538	N/A	Note 1
16	Power Amplifier	Mini-Circuits	ZVE-8G+	N628801631	N/A	Note 1

Remark:

1. "N/A" denotes no model name, serial No. or calibration specified.
2. \* These test equipments have been recalibrated between the test periods. All these test equipments were within the valid period when the tests were performed.
3. 1) Per KDB865664 D01 requirements for dipole calibration, the test laboratory has adopted three-year extended calibration interval. Each measured dipole is expected to evaluate with the following criteria at least on annual interval in Appendix C.
  - a) There is no physical damage on the dipole;
  - b) System check with specific dipole is within 10% of calibrated value;
  - c) The most recent return-loss result , measured at least annually, deviates by no more than 20% from the previous measurement;
  - d) The most recent measurement of the real or imaginary parts of the impedance, measured at least annually is within 5Ω from the previous measurement.
- 2) Network analyzer probe calibration against air, distilled water and a short block performed before measuring liquid parameters.


## 4. SAR MEASUREMENTS SYSTEM CONFIGURATION

### 4.1. SAR MEASUREMENT SET-UP

The DASY5 system for performing compliance tests consists of the following items:

1. A standard high precision 6-axis robot (Stäubli RX family) with controller and software. An arm extension for accommodating the data acquisition electronics (DAE).
2. A dosimetric probe, i.e. an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.
3. A data acquisition electronic (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
4. A unit to operate the optical surface detector which is connected to the EOC.
5. The Electro-Optical Coupler (EOC) performs the conversion from the optical into a digital electric signal of the DAE. The EOC is connected to the DASY5 measurement server.
6. The DASY5 measurement server, which performs all real-time data evaluation for field measurements and surface detection, controls robot movements and handles safety operation. A computer operating Windows 7
7. DASY5 software and SEMCAD data evaluation software.
8. Remote control with teach panel and additional circuitry for robot safety such as warning lamps, etc.
9. The generic twin phantom enabling the testing of left-hand and right-hand usage.
10. The device holder for handheld mobile phones.
11. Tissue simulating liquid mixed according to the given recipes.
12. System validation dipoles allowing to validate the proper functioning of the system.

#### 4.1.1. Test Setup Layout




## 4.2. DASY5E-FIELDPROBESYSTEM

The SAR measurements were conducted with the dosimetric probe EX3DV4 (manufactured by SPEAG), designed in the classical triangular configuration and optimized for dosimetric evaluation.

### 4.2.1. EX3DV4 PROBE SPECIFICATION

Construction	Symmetrical design with triangular core Interleaved sensors Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)
Calibration	ISO/IEC 17025 calibration service available
Frequency	10 MHz to 6 GHz Linearity: $\pm 0.2$ dB (30 MHz to 6 GHz)
Directivity	$\pm 0.3$ dB in HSL (rotation around probe axis) $\pm 0.5$ dB in tissue material (rotation normal to probe axis)
Dynamic Range	10 $\mu$ W/g to > 100 mW/g Linearity: $\pm 0.2$ dB
Dimensions	Overall length: 330 mm (Tip: 20 mm) Tip diameter: 2.5 mm (Body: 12 mm) Distance from probe tip to dipole centers: 1.0 mm



EX3DV4 E-field Probe

#### 4.2.2. E-FIELD PROBE CALIBRATION

Each probe is calibrated according to a dosimetric assessment procedure with accuracy better than  $\pm 10\%$ . The spherical isotropy was evaluated and found to be better than  $\pm 0.25\text{dB}$ . The sensitivity parameters (NormX, NormY, NormZ), the diode compression parameter (DCP) and the conversion factor (ConvF) of the probe are tested.

The free space E-field from amplified probe outputs is determined in a test chamber. This is performed in a TEM cell for frequencies below 1 GHz, and in a wave guide above 1 GHz for free space. For the free space calibration, the probe is placed in the volumetric center of the cavity and at the proper orientation with the field. The probe is then rotated 360 degrees.

E-field temperature correlation calibration is performed in a flat phantom filled with the appropriate simulated brain tissue. The measured free space E-field in the medium correlates to temperature rise in a dielectric medium. For temperature correlation calibration a RF transparent thermistor-based temperature probe is used in conjunction with the E-field probe.

$$\text{SAR} = C \frac{\Delta T}{\Delta t}$$

Where:  $\Delta t$  = Exposure time (30 seconds),

C = Heat capacity of tissue (brain or muscle),

$\Delta T$  = Temperature increase due to RF exposure.

Or 
$$\text{SAR} = \frac{|E|^2 \sigma}{\rho}$$

Where:  $\sigma$  = Simulated tissue conductivity,

$\rho$  = Tissue density (kg/m<sup>3</sup>).

### 4.2.3. OTHER TEST EQUIPMENT

#### 4.2.3.1. Device Holder for Transmitters

**Construction:** Simple but effective and easy-to-use extension for Mounting Device that facilitates the testing of larger devices (e.g., laptops, cameras, etc.) It is light weight and fits easily on the upper part of the Mounting Device in place of the phone positioner. The extension is fully compatible with the Twin SAM, ELI4 and SAM v6.0 Phantoms.

**Material:** POM, Acrylic glass, Foam

#### 4.2.3.2 Phantom

Model	ELI4 Phantom	
Construction	Phantom for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI is fully compatible with the IEC 62209-2 standard and all known tissue simulating liquids. ELI has been optimized regarding its performance and can be integrated into our standard phantom tables. A cover prevents evaporation of the liquid. Reference markings on the phantom allow installation of the complete setup, including all predefined phantom positions and measurement grids, by teaching three points. The phantom is compatible with all SPEAG dosimetric probes and dipoles.	
Shell Thickness	2±0.1 mm	
Filling Volume	Approx. 30 liters	
Dimensions	Length: 600 mm ; Width: 190mm Height: adjustable feet	
Available	Special	

Model	Twin SAM	
Construction	The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom defined in IEEE 1528 and IEC 62209-1. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by teaching three points with the robot.	
Shell Thickness	2 ± 0.2 mm	
Filling Volume	Approx. 25 liters	
Dimensions	Length: 1000mm; Width: 500mm Height: adjustable feet	
Available	Special	

#### 4.2.4. SCANNING PROCEDURE

The DASY5 installation includes predefined files with recommended procedures for measurements and validation. They are read-only document files and destined as fully defined but unmeasured masks. All test positions (head or body-worn) are tested with the same configuration of test steps differing only in the grid definition for the different test positions.

The “reference” and “drift” measurements are located at the beginning and end of the batch process. They measure the field drift at one single point in the liquid over the complete procedure. The indicated drift is mainly the variation of the DUT’s output power and should vary max.  $\pm 5\%$ .

The “surface check” measurement tests the optical surface detection system of the DASY5 system by repeatedly detecting the surface with the optical and mechanical surface detector and comparing the results. The output gives the detecting heights of both systems, the difference between the two systems and the standard deviation of the detection repeatability. Air bubbles or refraction in the liquid due to separation of the sugar-water mixture gives poor repeatability (above  $\pm 0.1\text{mm}$ ). To prevent wrong results tests are only executed when the liquid is free of air bubbles. The difference between the optical surface detection and the actual surface depends on the probe and is specified with each probe. (It does not depend on the surface reflectivity or the probe angle to the surface within  $\pm 30^\circ$ .)

- Area Scan

The “area scan” measures the SAR above the DUT or verification dipole on a parallel plane to the surface. It is used to locate the approximate location of the peak SAR with 2D spline interpolation. The robot performs a stepped movement along one grid axis while the local electrical field strength is measured by the probe. The probe is touching the surface of the SAM during acquisition of measurement values. The standard scan uses large grid spacing for faster measurement. Standard grid spacing for head measurements is 15 mm in x- and y- dimension( $\leq 2\text{GHz}$ ) · 12 mm in x- and y- dimension(2-4 GHz) and 10mm in x- and y- dimension(4-6GHz). If a finer resolution is needed, the grid spacing can be reduced. Grid spacing and orientation have no influence on the SAR result. For special applications where the standard scan method does not find the peak SAR within the grid, e.g. mobile phones with flip cover, the grid can be adapted in orientation.

- Zoom Scan

A “zoom scan” measures the field in a volume around the 2D peak SAR value acquired in the previous “coarse” scan. This is a fine grid with maximum scan spatial resolution:  $\Delta x_{\text{zoom}}, \Delta y_{\text{zoom}} \leq 2\text{GHz} - \leq 8\text{mm}$ , 2-4GHz -  $\leq 5\text{mm}$  and 4-6 GHz -  $\leq 4\text{mm}$ ;  $\Delta z_{\text{zoom}} \leq 3\text{GHz} - \leq 5\text{mm}$ , 3-4 GHz -  $\leq 4\text{mm}$  and 4-6GHz -  $\leq 2\text{mm}$  where the robot additionally moves the probe along the z-axis away from the bottom of the Phantom. DASY is also able to perform repeated zoom scans if more than 1 peak is found during area scan. In this document, the evaluated peak 1g and 10g averaged SAR values are shown in the 2D-graphics in Appendix B. Test results relevant for the specified standard (see chapter 1.4.) are shown in table form in chapter 7.2.

A Z-axis scan measures the total SAR value at the x-and y-position of the maximum SAR value found during the cube scan. The probe is moved away in z-direction from the bottom of the SAM phantom in 2 mm steps. This measurement shows the continuity of the liquid and can - depending in the field strength – also show the liquid depth.



The following table summarizes the area scan and zoom scan resolutions per FCC KDB 865664D01:

Frequency	Maximun Area Scan resolution ( $\Delta x_{area}, \Delta y_{area}$ )	Maximun Zoom Scan spatial resolution ( $\Delta x_{Zoom}, \Delta y_{Zoom}$ )	Maximun Zoom Scan spatial resolution			Minimum zoom scan volume (x,y,z)
			Uniform Grid	Graded Grad		
			$\Delta z_{Zoom}(n)$	$\Delta z_{Zoom}(1)^*$	$\Delta z_{Zoom}(n>1)^*$	
≤2GHz	≤15mm	≤8mm	≤5mm	≤4mm	≤1.5* $\Delta z_{Zoom}(n-1)$	≥30mm
2-3GHz	≤12mm	≤5mm	≤5mm	≤4mm	≤1.5* $\Delta z_{Zoom}(n-1)$	≥30mm
3-4GHz	≤12mm	≤5mm	≤4mm	≤3mm	≤1.5* $\Delta z_{Zoom}(n-1)$	≥28mm
4-5GHz	≤10mm	≤4mm	≤3mm	≤2.5mm	≤1.5* $\Delta z_{Zoom}(n-1)$	≥25mm
5-6GHz	≤10mm	≤4mm	≤2mm	≤2mm	≤1.5* $\Delta z_{Zoom}(n-1)$	≥22mm

#### 4.2.5. SPATIAL PEAK SAR EVALUATION

The spatial peak SAR - value for 1 and 10 g is evaluated after the Cube measurements have been done. The basis of the evaluation are the SAR values measured at the points of the fine cube grid consisting of 5 x 5 x 7 points( with 8mm horizontal resolution) or 7 x 7 x 7 points( with 5mm horizontal resolution) or 8 x 8 x 7 points( with 4mm horizontal resolution). The algorithm that finds the maximal averaged volume is separated into three different stages.

- The data between the dipole center of the probe and the surface of the phantom are extrapolated. This data cannot be measured since the center of the dipole is 2.7 mm away from the tip of the probe and the distance between the surface and the lowest measuring point is about 1 mm (see probe calibration sheet). The extrapolated data from a cube measurement can be visualized by selecting “Graph Evaluated”.
- The maximum interpolated value is searched with a straight-forward algorithm. Around this maximum the SAR - values averaged over the spatial volumes (1g or 10 g) are computed using the 3d-spline interpolation algorithm. If the volume cannot be evaluated (i.e., if a part of the grid was cut off by the boundary of the measurement area) the evaluation will be started on the corners of the bottom plane of the cube.
- All neighboring volumes are evaluated until no neighboring volume with a higher average value is found.

#### Extrapolation

The extrapolation is based on a least square algorithm [W. Gander, Computermathematik,p.168-180]. Through the points in the first 3 cm along the z-axis, polynomials of order four are calculated. These polynomials are then used to evaluate the points between the surface and the probe tip. The points, calculated from the surface, have a distance of 1 mm from each other.

#### Interpolation

The interpolation of the points is done with a 3d-Spline. The 3d-Spline is composed of three one-dimensional splines with the "Not a knot"-condition [W. Gander, Computer mathematik, p.141-150] (x, y and z -direction) [Numerical Recipes in C, Second Edition, p.123ff ].

#### Volume Averaging

At First the size of the cube is calculated. Then the volume is integrated with the trapezoidal algorithm. 8000 points (20x20x20) are interpolated to calculate the average.

#### Advanced Extrapolation

DASY5 uses the advanced extrapolation option which is able to compensats boundary effects on E-field probes.

## 4.2.6. DATA STORAGE AND EVALUATION

### 4.2.6.1 Data Storage

The DASY5 software stores the acquired data from the data acquisition electronics as raw data (in microvolt readings from the probe sensors), together with all necessary software parameters for the data evaluation (probe calibration data, liquid parameters and device frequency and modulation data) in measurement files with the extension “.DAE4”. The software evaluates the desired unit and format for output each time the data is visualized or exported. This allows verification of the complete software setup even after the measurement and allows correction of incorrect parameter settings. For example, if a measurement has been performed with a wrong crest factor parameter in the device setup, the parameter can be corrected afterwards and the data can be re-evaluated.

The measured data can be visualized or exported in different units or formats, depending on the selected probe type ([V/m], [A/m], [°C], [mW/g], [mW/cm<sup>2</sup>], [dBrel], etc.). Some of these units are not available in certain situations or show meaningless results, e.g., a SAR output in a lossless media will always be zero. Raw data can also be exported to perform the evaluation with other software packages.

#### 4.2.7. Data Evaluation by SEMCAD

The SEMCAD software automatically executes the following procedures to calculate the field units from the microvolt readings at the probe connector. The parameters used in the evaluation are stored in the configuration modules of the software:

Probe parameters:	Sensitivity	Normi, a <sub>i0</sub> , a <sub>i1</sub> , a <sub>i2</sub>
	Conversion factor	ConvF <sub>i</sub>
	Diode compression point	Dcp <sub>i</sub>
Device parameters:	Frequency	f
	Crest factor	cf
Media parameters:	Conductivity	.
	Density	.

These parameters must be set correctly in the software. They can be found in the component documents or they can be imported into the software from the configuration files issued for the DASYS5 components. In the direct measuring mode of the multi meter option, the parameters of the actual system setup are used. In the scan visualization and export modes, the parameters stored in the corresponding document files are used.

The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics.

If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power. The formula for each channel can be given as:

$$V_i = U_i + U_i^2 \cdot cf / dcp_i$$

With	V <sub>i</sub> = compensated signal of channel i	(i = x, y, z)
	U <sub>i</sub> = input signal of channel i	(i = x, y, z)
	cf = crest factor of exciting field	(DASY parameter)
	dcp <sub>i</sub> = diode compression point	(DASY parameter)

From the compensated input signals the primary field data for each channel can be evaluated:

$$\text{E-field probes: } E_i = ( V_i / \text{Norm}_i \cdot \text{ConvF} )^{1/2}$$

$$\text{H-field probes: } H_i = ( V_i )^{1/2} \cdot ( a_{i0} + a_{i1} f + a_{i2} f^2 ) / f$$

With  $V_i$  = compensated signal of channel i ( i = x, y, z )

$\text{Norm}_i$  = sensor sensitivity of channel i ( i = x, y, z )  
[mV/(V/m)<sup>2</sup>] for E-field Probes

$\text{ConvF}$  = sensitivity enhancement in solution

$a_{ij}$  = sensor sensitivity factors for H-field probes

$f$  = carrier frequency [GHz]

$E_i$  = electric field strength of channel i in V/m

$H_i$  = magnetic field strength of channel i in A/m

The RSS value of the field components gives the total field strength (Hermitian magnitude):

$$E_{\text{tot}} = (E_X^2 + E_Y^2 + E_Z^2)^{1/2}$$

The primary field data are used to calculate the derived field units.

$$\text{SAR} = (E_{\text{tot}})^2 \cdot \sigma / (\rho \cdot 1000)$$

With  $\text{SAR}$  = local specific absorption rate in mW/g

$E_{\text{tot}}$  = total field strength in V/m

= conductivity in [mho/m] or [Siemens/m]

= equivalent tissue density in g/cm<sup>3</sup>

Note that the density is normally set to 1 (or 1.06), to account for actual brain density rather than the density of the simulation liquid. The power flow density is calculated assuming the excitation field to be a free space field.

$$P_{\text{pwe}} = E_{\text{tot}}^2 / 3770 \text{ or } P_{\text{pwe}} = H_{\text{tot}}^2 \cdot 37.7$$

With  $P_{\text{pwe}}$  = equivalent power density of a plane wave in mW/cm<sup>2</sup>

$E_{\text{tot}}$  = total field strength in V/m

$H_{\text{tot}}$  = total magnetic field strength in A/m

## 5. SYSTEM VERIFICATION PROCEDURE

### 5.1. TISSUE VERIFICATION

The simulating liquids should be checked at the beginning of a series of SAR measurements to determine if the dielectric parameters are within the tolerances of the specified target values. The measured conductivity and relative permittivity should be within  $\pm 5\%$  of the target values.

The following materials are used for producing the tissue-equivalent materials.

Tissue Type	Bactericide	DGBE	HEC	NaCl	Sucrose	Triton X-100	Water	Diethylene Glycol Mono-hexylether
Head 2450	-	45.0	-	0.1	-	-	54.9	-
Head 5G	-	-	-	-	-	17.2	65.5	17.3

Salt: 99+% Pure Sodium Chloride; Sugar: 98+% Pure Sucrose; Water: De-ionized, 16M + resistivity  
 HEC: Hydroxyethyl Cellulose; DGBE: 99+% Di(ethylene glycol) butyl ether, [2-(2-butoxyethoxy)ethanol]  
 Triton X-100 (ultra pure): Polyethylene glycol mono [4-(1,1,3,3-tetramethylbutyl)phenyl]ether

Tissue Verification									
Tissue Type	Frequency (MHz)	Liquid Temp. (°C)	Conductivity ( $\sigma$ )	Permittivity ( $\epsilon_r$ )	Targeted Conductivity ( $\sigma$ )	Targeted Permittivity ( $\epsilon_r$ )	Deviation Conductivity ( $\sigma$ ) (%)	Deviation Permittivity ( $\epsilon_r$ ) (%)	Date
Head	2450	22.5	1.878	38.208	1.80	39.2	4.33	-2.53	Oct. 23, 2018
Head	5300	22.5	4.816	35.929	4.76	35.9	1.18	0.08	Oct. 23, 2018
Head	5500	22.5	5.037	35.468	4.96	35.6	1.55	-0.37	Oct. 23, 2018
Head	5600	22.5	5.157	35.252	5.07	35.5	1.72	-0.70	Oct. 23, 2018
Head	5800	22.5	5.411	34.813	5.27	35.3	2.68	-1.38	Oct. 23, 2018

Note:

- 1) The dielectric parameters of the tissue-equivalent liquid should be measured under similar ambient conditions and within 2 °C of the conditions expected during the SAR evaluation to satisfy protocol requirements.
- 2) KDB 865664 was ensured to be applied for probe calibration frequencies greater than or equal to 50MHz of the EUT frequencies.
- 3) The above measured tissue parameters were used in the DASY software to perform interpolation via the DASY software to determine actual dielectric parameters at the test frequencies. The SAR test plots may slightly differ from the table above since the DASY rounds to three significant digits.

<Low/Middle/High Channel for Liquid Validation>

CH	Frequency	Conductivity	Permittivity	Conductivity	Permittivity	Delta ( $\sigma$ )	Delta ( $\epsilon_r$ )	Limit (%)	Date
	(MHz)	( $\sigma$ )	( $\epsilon_r$ )	Target ( $\sigma$ )	Target ( $\sigma$ )	(%)	(%)		
1	2412	1.832	38.35	1.77	39.27	-2.35	3.67	$\pm 5$	Oct. 23, 2018
6	2437	1.862	38.25	1.79	39.22	-2.48	4.16	$\pm 5$	Oct. 23, 2018
11	2462	1.878	38.18	1.81	39.18	-2.57	4.37	$\pm 5$	Oct. 23, 2018
52	5260	1.891	36.06	4.72	35.94	0.33	0.86	$\pm 5$	Oct. 23, 2018
60	5300	4.760	35.93	4.76	35.90	0.08	1.18	$\pm 5$	Oct. 23, 2018
64	5320	4.816	35.90	4.78	35.88	0.05	1.44	$\pm 5$	Oct. 23, 2018
100	5500	4.849	35.47	4.96	35.60	-0.37	1.53	$\pm 5$	Oct. 23, 2018
112	5560	5.036	35.35	5.03	35.54	-0.52	2.13	$\pm 5$	Oct. 23, 2018
140	5700	5.133	35.02	5.17	35.40	-1.07	2.17	$\pm 5$	Oct. 23, 2018
149	5745	5.158	34.87	5.22	35.35	-1.37	2.29	$\pm 5$	Oct. 23, 2018
157	5785	5.282	34.83	5.26	35.31	-1.35	2.85	$\pm 5$	Oct. 23, 2018
165	5825	5.334	34.73	5.30	35.27	-1.52	2.53	$\pm 5$	Oct. 23, 2018

### 5.2. SYSTEM CHECK


The system check is performed for verifying the accuracy of the complete measurement system and performance of the software. The system check is performed with tissue equivalent material according to IEEE P1528 (described above). The following table shows system check results for all frequency bands and tissue liquids used during the tests.

System Check	Date	Frequency (MHz)	Targeted SAR-1g (W/kg)	Measured SAR-1g (W/kg)	normalized SAR-1g (W/kg)	Deviation (%)	Dipole S/N
Head	Oct. 23, 2018	2450	50.80	13.30	53.20	4.72	919
Head	Oct. 23, 2018	5300	72.30	7.51	75.10	3.87	1160
Head	Oct. 23, 2018	5500	76.20	7.86	78.60	3.15	1160
Head	Oct. 23, 2018	5600	77.70	8.08	80.80	3.99	1160
Head	Oct. 23, 2018	5800	76.60	7.96	79.60	3.92	1160

### 5.3. SYSTEM CHECK PROCEDURE

The system check is performed by using a system check dipole which is positioned parallel to the planar part of the SAM phantom at the reference point. The distance of the dipole to the SAM phantom is determined by a plexiglass spacer. The dipole is connected to the signal source consisting of signal generator and amplifier via a directional coupler, N-connector cable and adaption to SMA. It is fed with a power of 250 mW (below 5GHz) or 100mW (above 5GHz). To adjust this power a power meter is used. The power sensor is connected to the cable before the system check to measure the power at this point and do adjustments at the signal generator. At the outputs of the directional coupler both return loss as well as forward power are controlled during the system check to make sure that emitted power at the dipole is kept constant. This can also be checked by the power drift measurement after the test.

System check results have to be equal or near the values determined during dipole calibration (target SAR in table above) with the relevant liquids and test system ( $\pm 10\%$ ).



## 6. SAR MEASUREMENT VARIABILITY AND UNCERTAINTY

### 6.1. SAR MEASUREMENT VARIABILITY

Per KDB865664 D01 SAR measurement 100 MHz to 6 GHz, SAR measurement variability must be assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. The additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

- 1) Repeated measurement is not required when the original highest measured SAR is  $< 0.80$  W/kg; steps 2) through 4) do not apply.
- 2) When the original highest measured SAR is  $\geq 0.80$  W/kg, repeat that measurement once.
- 3) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is  $> 1.20$  or when the original or repeated measurement is  $\geq 1.45$  W/kg (~ 10% from the 1-g SAR limit).
- 4) Perform a third repeated measurement only if the original, first or second repeated measurement is  $\geq 1.5$  W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is  $> 1.20$ .

The same procedures should be adapted for measurements according to extremity and occupational exposure limits by applying a factor of 2.5 for extremity exposure and a factor of 5 for occupational exposure to the corresponding SAR thresholds.

The detailed repeated measurement results are shown in Section 8.2.



## 7. OPERATIONAL CONDITIONS DURING TEST

### 7.1. SAR TEST CONFIGURATION

#### 7.1.1. WLAN TEST CONFIGURATION

For WLAN SAR testing, WLAN engineering testing software installed on the DUT can provide continuous transmitting RF signal.

Mode	802.11b	802.11g	802.11n_HT20	802.11a	802.11n_HT20
Duty cycle	100%				
Crest factor	1				

For WLAN SAR testing, a communication link is set up with the test mode software for WIFI mode test. During the test, at the each test frequency channel, the EUT is operated at the RF continuous emission mode. The RF signal utilized in SAR measurement has 100% duty cycle and its crest factor is 1. The test procedures in KDB 248227 D01 are applied.

### 7.2. 2.4G SAR Test Requirements

#### 802.11b DSSS SAR Test Requirements

SAR is measured for 2.4 GHz 802.11b DSSS using either a fixed test position or, when applicable, the initial test position procedure. SAR test reduction is determined according to the following:

- 1) When the reported SAR of the highest measured maximum output power channel for the exposure configuration is  $\leq 0.8$  W/kg, no further SAR testing is required for 802.11b DSSS in that exposure configuration.
- 2) When the reported SAR is  $> 0.8$  W/kg, SAR is required for that exposure configuration using the next highest measured output power channel. When any reported SAR is  $> 1.2$  W/kg, SAR is required for the third channel; i.e., all channels require testing.

#### 2.4 GHz 802.11g/n OFDM SAR Test Exclusion Requirements

When SAR measurement is required for 2.4 GHz 802.11g/n OFDM configurations, the measurement and test reduction procedures for OFDM are applied. SAR is not required for the following 2.4 GHz OFDM conditions.



- 1) When KDB Publication 447498 SAR test exclusion applies to the OFDM configuration.
- 2) When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is  $\leq 1.2$  W/kg.

#### SAR Test Requirements for OFDM configurations

When SAR measurement is required for 2.4 GHz 802.11g/n OFDM configurations, each standalone And frequency aggregated band is considered separately for SAR test reduction. In applying the initial test configuration and subsequent test configuration procedures, the 802.11 transmission configuration with the highest specified maximum output power and the channel within a test configuration with the highest measured maximum output power should be clearly distinguished to apply the procedures.

## 7.2 TEST POSITION

The location of the antenna inside EUT is as below.



## 8. TEST RESULT

### 8.1. CONDUCTED POWER RESULTS

Per RSS-102 Issue 5, the SAR evaluation is required if the separation distance between the user and/or bystander and the antenna and/or radiating element of the device is less than or equal to 20 cm, except when the device operates at or below the applicable output power level (adjusted for tune-up tolerance) for the specified separation distance defined in Table 1

**Table 1: SAR evaluation – Exemption limits for routine evaluation based on frequency and separation distance**

Frequency (MHz)	Exemption Limits (mW)				
	At separation distance of $\leq 5$ mm	At separation distance of 10 mm	At separation distance of 15 mm	At separation distance of 20 mm	At separation distance of 25 mm
$\leq 300$	71 mW	101 mW	132 mW	162 mW	193 mW
450	52 mW	70 mW	88 mW	106 mW	123 mW
835	17 mW	30 mW	42 mW	55 mW	67 mW
1900	7 mW	10 mW	18 mW	34 mW	60 mW
2450	4 mW	7 mW	15 mW	30 mW	52 mW
3500	2 mW	6 mW	16 mW	32 mW	55 mW
5800	1 mW	6 mW	15 mW	27 mW	41 mW

Frequency (MHz)	Exemption Limits (mW)				
	At separation distance of 30 mm	At separation distance of 35 mm	At separation distance of 40 mm	At separation distance of 45 mm	At separation distance of $\geq 50$ mm
$\leq 300$	223 mW	254 mW	284 mW	315 mW	345 mW
450	141 mW	159 mW	177 mW	195 mW	213 mW
835	80 mW	92 mW	105 mW	117 mW	130 mW
1900	99 mW	153 mW	225 mW	316 mW	431 mW
2450	83 mW	123 mW	173 mW	235 mW	309 mW
3500	86 mW	124 mW	170 mW	225 mW	290 mW
5800	56 mW	71 mW	85 mW	97 mW	106 mW

### 8.1.1. CONDUCTED POWER MEASUREMENTS OF WIFI 2.4G

Mode	Channel	Frequency(MHz)	Data Rate (Mbps)	Tune up	Average Power (dBm)	SAR Test (Yes/No)
802.11b	1	2412	1	10	9.45	Yes
	6	2437		10	9.34	
	11	2462		10	9.64	
802.11g	1	2412	6	10	9.50	No
	6	2437		10	9.32	
	11	2462		10	9.49	
802.11n HT20	1	2412	6.5	10	9.55	No
	6	2437		10	9.32	
	11	2462		10	9.41	

Note: The conducted power of WIFI is measured with RMS detector.

### 8.1.2. CONDUCTED POWER MEASUREMENTS OF WIFI 5G

Mode	Channel	Frequency(MHz)	Data Rate (Mbps)	Tune up	Average Power (dBm)	SAR Test (Yes/No)
802.11a	36	5180	6	8.00	7.35	No
	40	5200		8.00	7.51	
	44	5220		8.00	7.42	
	48	5240		8.00	7.58	
802.11n HT20	36	5180	6.5	8.00	7.74	YES
	40	5200		8.00	7.59	
	44	5220		8.00	7.62	
	48	5240		8.00	7.40	

Mode	Channel	Frequency(MHz)	Data Rate (Mbps)	Tune up	Average Power (dBm)	SAR Test (Yes/No)
802.11a	52	5260	6	8.00	7.54	No
	56	5280		8.00	7.39	
	60	5300		8.00	7.53	
	64	5320		8.00	7.46	
802.11n HT20	52	5260	6.5	8.00	7.64	YES
	56	5280		8.00	7.22	
	60	5300		8.00	7.32	
	64	5320		8.00	7.31	

Mode	Channel	Frequency(MHz)	Data Rate (Mbps)	Tune up	Average Power (dBm)	SAR Test (Yes/No)
802.11a	100	5500	6	8.00	7.54	No
	104	5520		8.00	7.61	
	108	5540		8.00	7.31	
	112	5560		8.00	7.34	
	116	5580		8.00	7.51	
	132	5660		8.00	7.61	
	136	5680		8.00	7.66	
	140	5700		8.00	7.71	
802.11n HT20	100	5500	6.5	8.00	7.71	YES
	104	5520		8.00	7.42	
	108	5540		8.00	7.46	
	112	5560		8.00	7.62	
	116	5580		8.00	7.52	
	132	5660		8.00	7.66	
	136	5680		8.00	7.61	
	140	5700		8.00	7.74	

Mode	Channel	Frequency(MHz)	Data Rate (Mbps)	Tune up	Average Power (dBm)	SAR Test (Yes/No)
802.11a	149	5745	6	8.00	7.46	YES
	153	5765		8.00	7.42	
	157	5785		8.00	7.58	
	161	5805		8.00	7.51	
	165	5825		8.00	7.46	
802.11n HT20	149	5745	6.5	8.00	7.43	No
	153	5765		8.00	7.43	
	157	5785		8.00	7.48	
	161	5805		8.00	7.45	
	165	5825		8.00	7.38	

## 8.2. SAR TEST RESULTS

### General Notes:

- 1) Per KDB447498 D01, all measurement SAR results are scaled to the maximum tune-up tolerance limit to demonstrate compliant.
- 2) Per KDB447498 D01, testing of other required channels within the operating mode of a frequency band is not required when the reported 1-g or 10-g SAR for the mid-band or highest output power channel is:  $\leq 0.8$  W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is  $\leq 100$  MHz. When the maximum output power variation across the required test channels is  $> \frac{1}{2}$  dB, instead of the middle channel, the highest output power channel must be used.
- 3) Per KDB865664 D01, for each frequency band, repeated SAR measurement is required only when the measured SAR is  $\geq 0.8$  W/kg; if the deviation among the repeated measurement is  $\leq 20\%$ , and the measured SAR  $< 1.45$  W/kg, only one repeated measurement is required.

### 8.2.1. WLAN Notes:

- 1) For exposure conditions with multiple test positions, such as handset operating next to the ear, devices with hotspot mode, procedures for initial test position can be applied. Using the transmission mode determined by the DSSS procedure or initial test configuration, area scans are measured for all positions in an exposure condition. The test position with the highest extrapolated (peak) SAR is used as the initial test position. When the reported SAR of the initial test position is  $\leq 0.4$  W/kg, further SAR measurement is not required for the other (remaining) test positions. Otherwise, SAR is evaluated at the subsequent highest peak SAR position until the reported SAR result is  $\leq 0.8$  W/kg or all test positions are measured.
- 2) Justification for test configurations for WLAN per KDB Publication 248227 for 2.4GHz WIFI single transmission chain operations, the highest measured maximum output power Channel for DSSS was selected for SAR measurement. SAR for OFDM modes (2.4GHz 802.11g/n) was not required due to the maximum allowed powers and the highest reported DSSS SAR. See Section 7.1 for more information.

#### ✧ U-NII-1 and U-NII-2A Band

For devices that operate in both U-NII-1 and U-NII-2A bands, when the same maximum output power is specified for both bands, begin SAR measurement in U-NII-2A band by applying the OFDM SAR requirements. If the highest reported SAR for a test configuration is  $\leq 1.2$  W/kg, SAR is not required for U-NII-1 band for that configuration (802.11 mode and exposure condition); otherwise, both bands are tested independently for SAR. When different maximum output power is specified for the bands, begin SAR measurement in the band with higher specified maximum output power. The highest reported SAR for the tested configuration is adjusted by the ratio of lower to higher specified maximum output power for the two bands. When the adjusted SAR is  $\leq 1.2$  W/kg, SAR is not required for the band with lower maximum output power in that test configuration; otherwise, both bands are tested independently for SAR.

#### ✧ U-NII-2C, U-NII-3 Bands

The frequency range covered by these bands is 380 MHz (5.47 – 5.85 GHz), which requires a minimum of at least two SAR probe calibration frequency points to support SAR measurements. When Terminal Doppler Weather Radar (TDWR) restriction applies, the channels at 5.60 – 5.65 GHz in U-NII-2C band must be disabled with acceptable mechanisms and documented in the equipment certification.

Unless band gap channels are permanently disabled, they must be considered for SAR testing. To maintain SAR measurement accuracy and to facilitate test reduction, the channels in U-NII-2C band above 5.65 GHz may be grouped with the 5.8 GHz channels in U-NII-3 or §15.247 band to enable two SAR probe calibration frequency points to cover the bands, including the band gap channels. 11 When band gap channels are supported and the bands are not aggregated for SAR testing, band gap channels must be considered independently in each band according to the normally required OFDM SAR measurement and probe calibration frequency points requirements.

### 8.2.2.OFDM TRANSMISSION MODE AND SAR TEST CHANNEL SELECTION

For the 2.4GHz and 5GHz bands, when the same maximum output power was specified for multiple OFDM transmission mode configurations in a frequency band or aggregated band, SAR is measured using the configuration with the largest channel bandwidth, lowest order modulation and lowest data rate. When the maximum output power of a channel is the same for equivalent OFDM configurations(for example 802.11a,802.11n and 802.11ac,or 802.11g and 802.11n,with the same channel bandwidth, modulation, and data rate, etc.),the lower order 802.11 mode(i.e.802.11a then 802.11n and 802.11ac,or 802.11g then 802.11n) is used for SAR measurement. When the maximum output power are the same for multiple test channels, either according to the default or additional power measurement requirements, SAR is measured using the channel closest to the middle of the frequency band or aggregated band. When there are multiple channels with the same maximum output power, SAR is measured using the higher number channel.

### 8.2.3. SAR MEASUREMENT RESULT

#### Head SAR WIFI 2.4G test result

Test No.	Band	Channel	Test Position	microphone	Maximum Tune-up (dBm)	Conducted Power (dBm)	Power Drift	SAR 1g	SAR 10g	Scaling Factor	Scaled 1g SAR
1	802.11b	11	Right Cheek	-	10	9.64	0	<0.001	<0.001	1.086	<0.001
2	802.11b	11	Left Cheek	-	10	9.64	0	<0.001	<0.001	1.086	<0.001
3	802.11b	11	Right Cheek	V	10	9.64	0	<0.001	<0.001	1.086	<0.001
4	802.11b	11	Left Cheek	V	10	9.64	0	<0.001	<0.001	1.086	<0.001
5	802.11b	1	Left Cheek	-	10	9.45	0	<0.001	<0.001	1.135	<0.001
6	802.11b	6	Left Cheek	-	10	9.34	0	<0.001	<0.001	1.164	<0.001

Note: The area scan SAR result value <0.001, can not find zoom scan cube.

#### Head SAR WIFI 5G test result

Test No.	Band	Channel	Test Position	microphone	Maximum Tune-up (dBm)	Conducted Power (dBm)	Power Drift	SAR 1g	SAR 10g	Scaling Factor	Scaled 1g SAR
13	802.11n_HT20	52	Right Cheek	-	8	7.64	0	<0.001	<0.001	1.086	<0.001
14	802.11n_HT20	52	Left Cheek	-	8	7.64	0	<0.001	<0.001	1.086	<0.001
15	802.11n_HT20	52	Right Cheek	V	8	7.64	0	<0.001	<0.001	1.086	<0.001
16	802.11n_HT20	52	Left Cheek	V	8	7.64	0	<0.001	<0.001	1.086	<0.001
17	802.11n_HT20	60	Left Cheek	-	8	7.32	0	<0.001	<0.001	1.169	<0.001
18	802.11n_HT20	64	Left Cheek	-	8	7.31	0	<0.001	<0.001	1.172	<0.001
19	802.11n_HT20	100	Right Cheek	-	8	7.71	0	<0.001	<0.001	1.069	<0.001
20	802.11n_HT20	100	Left Cheek	-	8	7.71	0.09	0.013	0.0061	1.069	0.014
21	802.11n_HT20	100	Right Cheek	V	8	7.71	0	<0.001	<0.001	1.069	<0.001
22	802.11n_HT20	100	Left Cheek	V	8	7.71	0.03	0.01	0.0042	1.069	0.011
23	802.11n_HT20	112	Left Cheek	-	8	7.62	0.02	<0.001	<0.001	1.091	<0.001
24	802.11n_HT20	140	Left Cheek	-	8	7.74	0.01	<0.001	<0.001	1.062	<0.001
25	802.11a	157	Right Cheek	-	8	7.58	0	<0.001	<0.001	1.102	<0.001
26	802.11a	157	Left Cheek	-	8	7.58	0.02	<0.001	<0.001	1.102	<0.001
27	802.11a	157	Right Cheek	V	8	7.58	0	<0.001	<0.001	1.102	<0.001
28	802.11a	157	Left Cheek	V	8	7.58	0.05	<0.001	<0.001	1.102	<0.001
29	802.11a	149	Left Cheek	-	8	7.46	-0.02	<0.001	<0.001	1.132	<0.001
30	802.11a	165	Left Cheek	-	8	7.46	-0.02	<0.001	<0.001	1.132	<0.001

Note: The area scan SAR result value <0.001, can not find zoom scan cube.



## APPENDIX

### 1. Test Layout

#### Specific Absorption Rate Test Layout




#### Liquid depth in the flat Phantom ( $\geq 15\text{cm}$ depth)

HSL(2450MHz)



HSL(5GHz)



## **Appendix A. SAR Plots of System Verification**

(Pls See Appendix A.)

## **Appendix B. SAR Plots of SAR Measurement**

(Pls See Appendix B.)

## **Appendix C. Calibration Certificate for Probe and Dipole**

(Pls See Appendix C.)

## **Appendix D. Photographs of the Test Set-Up**

(Pls See Appendix D.)

---

**End**