

TEST REPORT

Application No.: SZCR2406002103MO
Applicant: Shanghai Sunmi Technology Co.,Ltd.
Address of Applicant: Room 505,No.388,Song Hu Road,Yang Pu District,Shanghai,China
Manufacturer: Shanghai Sunmi Technology Co.,Ltd.
Address of Manufacturer: Room 505,No.388,Song Hu Road,Yang Pu District,Shanghai,China
Equipment Under Test (EUT):
EUT Name: Smart module
Model No.: QLB12-20
Trade Mark: SUNMI
FCC ID: 2AH2524QLB1220
Standard(s) : 47 CFR Part 15, Subpart E 15.407
Date of Receipt: 2024-06-04
Date of Test: 2024-07-08 to 2024-08-09
Date of Issue: 2024-08-09

Test Result:	Pass*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.

Kenx. Xu

Keny Xu

EMC Laboratory Manager



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch EMC Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.ssgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR240600210304

Page: 2 of 426

Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2024-08-09		Original

Authorized for issue by:				
		Donjon Huang		
		Donjon Huang/Project Engineer		
		Eric Fu		
		Eric Fu/Reviewer		



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

2 Test Summary

Radio Spectrum Technical Requirement				
Item	Standard	Method	Requirement	Result
Antenna Requirement	47 CFR Part 15, Subpart E 15.407	N/A	47 CFR Part 15, Subpart C 15.203	Pass
Transmission in the Absence of Data		N/A	47 CFR Part 15, Subpart E 15.407 (c)	Pass

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
Conducted Emissions at AC Power Line (150kHz-30MHz)	47 CFR Part 15, Subpart E 15.407	ANSI C63.10 (2013) Section 6.2	47 CFR Part 15, Subpart C 15.207 & Subpart E 15.407 b(9)	Pass
Maximum Conducted output power		KDB 789033 D02 II E	47 CFR Part 15, Subpart E 15.407 (a)	Pass
Radiated Emissions (Below 1GHz)		KDB 789033 D02 II G	47 CFR Part 15, Subpart C 15.209 & Subpart E 15.407(b)	Pass
Radiated Emissions (Above 1GHz)		KDB 789033 D02 II G	47 CFR Part 15, Subpart C 15.209 & Subpart E 15.407(b)	Pass
Radiated Emissions which fall in the restricted bands		KDB 789033 D02 II G	47 CFR Part 15, Subpart C 15.209 & Subpart E 15.407(b)	Pass
Channel Move Time		KDB 905462 D02 Section 7.8.3	KDB 905462 D02 Section 5.1	Pass
Duty Cycle		KDB 789033 II B 1	KDB 789033 D02 II B 1	Pass
99% Bandwidth		KDB 789033 II D	N/A	Pass
26dB Emission bandwidth		KDB 789033 D02 II C 1	47 CFR Part 15, Subpart E 15.407 (a)	Pass
Minimum 6 dB bandwidth (5.725-5.85 GHz band)		KDB 789033 D02 II C 2	47 CFR Part 15, Subpart E 15.407 (e)	Pass
Peak Power spectrum density		KDB 789033 D02 II F	47 CFR Part 15, Subpart E 15.407 (a)	Pass
Frequency Stability		ANSI C63.10 (2013) Section 6.8	47 CFR Part 15, Subpart E 15.407 (g)	Pass
Non-occupancy period		KDB 905462 D02 Section 7.8.3	KDB 905462 D02 Section 5.1	Pass
Channel Closing Transmission Time		KDB 905462 D02 Section 7.8.3	KDB 905462 D02 Section 5.1	Pass



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

3 Contents

	Page
1 Cover Page	1
2 Test Summary	3
3 Contents	4
4 General Information	7
4.1 Details of E.U.T.	7
4.2 Description of Support Units	8
4.3 Measurement Uncertainty	8
4.4 Test Location	9
4.5 Test Facility	9
4.6 Deviation from Standards	9
4.7 Abnormalities from Standard Conditions	9
5 Equipment List	10
6 Radio Spectrum Technical Requirement	13
6.1 Antenna Requirement	13
6.1.1 Test Requirement:	13
6.1.2 Conclusion	13
6.2 Transmission in the Absence of Data	14
6.2.1 Test Requirement:	14
6.2.2 Conclusion	14
7 Radio Spectrum Matter Test Results	15
7.1 Conducted Emissions at AC Power Line (150kHz-30MHz)	15
7.1.1 E.U.T. Operation	15
7.1.2 Test Mode Description	15
7.1.3 Test Setup Diagram	16
7.1.4 Measurement Procedure and Data	16
7.2 Maximum Conducted output power	19
7.2.1 E.U.T. Operation	19
7.2.2 Test Mode Description	19
7.2.3 Test Setup Diagram	20
7.2.4 Measurement Procedure and Data	20
7.3 Radiated Emissions (Below 1GHz)	21
7.3.1 E.U.T. Operation	21
7.3.2 Test Mode Description	21
7.3.3 Test Setup Diagram	22
7.3.4 Measurement Procedure and Data	23
7.4 Radiated Emissions (Above 1GHz)	26
7.4.1 E.U.T. Operation	26
7.4.2 Test Mode Description	26
7.4.3 Test Setup Diagram	27



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR240600210304

Page: 5 of 426

7.4.4	Measurement Procedure and Data.....	28
7.5	Radiated Emissions which fall in the restricted bands	147
7.5.1	E.U.T. Operation	147
7.5.2	Test Mode Description	148
7.5.3	Test Setup Diagram	148
7.5.4	Measurement Procedure and Data.....	149
7.6	Channel Move Time	244
7.6.1	E.U.T. Operation	244
7.6.2	Test Mode Description	245
7.6.3	Test Setup Diagram	245
7.6.4	Measurement Procedure and Data.....	246
7.7	Duty Cycle	247
7.7.1	E.U.T. Operation	247
7.7.2	Test Mode Description	247
7.7.3	Test Setup Diagram	247
7.7.4	Measurement Procedure and Data.....	247
7.8	99% Bandwidth	248
7.8.1	E.U.T. Operation	248
7.8.2	Test Mode Description	248
7.8.3	Test Setup Diagram	249
7.8.4	Measurement Procedure and Data.....	249
7.9	26dB Emission bandwidth	250
7.9.1	E.U.T. Operation	250
7.9.2	Test Mode Description	250
7.9.3	Test Setup Diagram	251
7.9.4	Measurement Procedure and Data.....	251
7.10	Minimum 6 dB bandwidth (5.725-5.85 GHz band)	252
7.10.1	E.U.T. Operation.....	252
7.10.2	Test Mode Description.....	252
7.10.3	Test Setup Diagram.....	252
7.10.4	Measurement Procedure and Data	252
7.11	Peak Power spectrum density.....	253
7.11.1	E.U.T. Operation.....	253
7.11.2	Test Mode Description.....	253
7.11.3	Test Setup Diagram.....	254
7.11.4	Measurement Procedure and Data	254
7.12	Frequency Stability.....	255
7.12.1	E.U.T. Operation.....	255
7.12.2	Test Mode Description.....	255
7.12.3	Test Setup Diagram.....	256
7.12.4	Measurement Procedure and Data	256
7.13	Non-occupancy period	257
7.13.1	E.U.T. Operation.....	257
7.13.2	Test Mode Description.....	257
7.13.3	Test Setup Diagram.....	258
7.13.4	Measurement Procedure and Data	259
7.14	Channel Closing Transmission Time	260
7.14.1	E.U.T. Operation.....	260
7.14.2	Test Mode Description.....	260
7.14.3	Test Setup Diagram.....	261



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch
 No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR240600210304

Page: 6 of 426

7.14.4	Measurement Procedure and Data	262
8	Test Setup Photo	263
9	EUT Constructional Details (EUT Photos)	264
10	Appendix.....	265



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing, Calibration Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

4 General Information

4.1 Details of E.U.T.

EUT Description:	Smart module	
Model No.:	QLB12-20	
Trade Mark:	SUNMI	
Hardware Version:	R1.0	
Software Version:	SG656VWFNUR01A08	
Power Supply:	Power from the Mainboard: Mainboard Power by DC 12V 3A from DC Port Adapter model: GQ36-120300-AX Input: 100-240V~50/60Hz, 1A Max Output: DC 12V3A	
WLAN Mode Supported:	802.11a:	20 MHz channel bandwidth
	802.11n:	20 MHz / 40 MHz channel bandwidth
	802.11ac:	20 MHz / 40 MHz / 80 MHz channel bandwidth
Operation Frequency:	5150MHz to 5250MHz 5250MHz to 5350MHz 5470MHz to 5725MHz 5725MHz to 5850MHz	
Modulation Type:	802.11a:	OFDM (BPSK, QPSK, 16QAM, 64QAM)
	802.11n:	OFDM (BPSK, QPSK, 16QAM, 64QAM)
	802.11ac:	OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM)
Channel Spacing:	20MHz:	802.11a/n(HT20)/ac(VHT20)
	40MHz:	802.11n(HT40)/ac(VHT40)
	80MHz:	802.11ac(VHT80)
Antenna Type:	External Antenna	
Antenna Gain:	5150MHz to 5250MHz: 3dBi; 5250MHz to 5350MHz: 3dBi; 5470MHz to 5725MHz: 3dBi; 5725MHz to 5850MHz: 3dBi;	
	Note: The antenna gain are derived from the gain information report provided by the manufacturer.	
Smart System:	☒ SISO	802.11a/n/ac
TPC Function:	☒ Support, ☐ Not Support	
DFS Function:	☐ Master	



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR240600210304

Page: 8 of 426

	☐ Slave with radar detection	☒ Slave without radar detection
RF Cable:	1.5dB	
Remark: As above information is provided and confirmed by the applicant. SGS is not liable to the accuracy, suitability, reliability or/and integrity of the information.		

4.2 Description of Support Units

Description	Manufacturer	Model No.
Mother board*	Sunmi	SMART-5G-EVB_V1.3
Adapter*	Dong Guan City GangQi Electronic Co.,Ltd	GQ36-120300-AX
Test Software	Qualcomm	QRCT4 tool
*Remark: The above the information of table are provided by client.		

4.3 Measurement Uncertainty

Test Item	Measurement Uncertainty
Conducted Emissions at AC Power Line (150kHz-30MHz)	$\pm 3.1\text{dB}$
Maximum Conducted output power	$\pm 0.75\text{dB}$
Radiated Emissions (Below 1GHz)	$\pm 6.0\text{dB}$ for 3m; $\pm 5.0\text{dB}$ for 10m
Radiated Emissions (Above 1GHz)	$\pm 4.6\text{dB}$ (1-18GHz); $\pm 4.8\text{dB}$ (18-40GHz)
Radiated Emissions which fall in the restricted bands	$\pm 6.0\text{dB}$ (below 1GHz); $\pm 4.6\text{dB}$ (above 1GHz);
Duty Cycle	$\pm 0.37\%$
99% Bandwidth	$\pm 3\%$
26dB Emission bandwidth	$\pm 3\%$
Minimum 6 dB bandwidth (5.725-5.85 GHz band)	$\pm 3\%$
Peak Power spectrum density	$\pm 2.84\text{dB}$
Frequency Stability	$\pm 7.25 \times 10^{-8}$

Remark:
 The U_{lab} (lab Uncertainty) is less than $U_{\text{CISPR/ETSI}}$ (CISPR/ETSI Uncertainty), so the test results
 – compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
 – non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR240600210304

Page: 9 of 426

4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China. 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• A2LA (Certificate No. 3816.01)

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

• VCCI (Member No. 1937)

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen EMC laboratory have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

• FCC –Designation Number: CN1336

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1336. Test Firm Registration Number: 787754.

• Innovation, Science and Economic Development Canada

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0006.

IC#: 4620C.

4.6 Deviation from Standards

None

4.7 Abnormalities from Standard Conditions

None



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch EMC Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.ssgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

5 Equipment List

Conducted Emissions at AC Power Line (150kHz-30MHz)					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Shielding Room	ZhongYu Electron	GB-88	SEM001-06	2022-05-14	2025-05-13
EMI Test Receiver	Rohde&Schwarz	ESCI	SEM004-02	2024-03-14	2025-03-13
Matching Pad	N/A	N/A	SEM021-23	2024-03-20	2025-03-19
Matching Pad	N/A	N/A	SEM021-24	2024-03-20	2025-03-19
Measurement Software	AUDIX	e3 V8.2014-6-27a	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM024-01	2024-07-06	2025-07-05
LISN	Rohde&Schwarz	ENV216	SEM007-01	2023-09-19	2024-09-18
LISN	ETS-LINDGREN	3816/2	SEM007-02	2024-03-14	2025-03-13

Maximum Conducted output power					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Power Sensor	TST PASS	TSPS2023R	SEM009-26	2024-03-27	2025-03-26
Power Sensor	KEYSIGHT	U2021XA	SEM009-16	2024-03-14	2025-03-13
DC Power Supply	Chroma	62012P-80-60	SEM011-11	2023-10-19	2024-10-18
MXA Signal Analyzer	KEYSIGHT	N9020A	SEM004-19	2024-03-14	2025-03-13
Signal Generator	KEYSIGHT	N5173B	SEM006-05	2023-09-19	2024-09-18
Measurement Software	TST PASS	TST PASS V2.0	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-01	2024-07-06	2025-07-05
Attenuator	Huber+Suhner	6620_SMA-50-1	SEM021-09	2024-03-27	2025-03-26
Programmable Temperature & Humidity Chamber	Votsch Industrietechnik GmbH	VT 4002	SEM002-15	2024-03-19	2025-03-18

Radiated Emissions (Below 1GHz)					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Loop Antenna	ETS-Lindgren	6502	SEM003-08	2023-11-20	2025-11-19
3m Semi-Anechoic Chamber	ETS-LINDGREN	N/A	SEM001-01	2023-06-19	2026-06-18
MXE EMI Receiver	Agilent Technologies	N9038A	SEM004-15	2023-10-19	2024-10-18
BiConiLog Antenna	ETS-LINDGREN	3142C	SEM003-01	2023-09-16	2025-09-15
Pre-Amplifier	Agilent Technologies	8447D	SEM005-01	2024-03-14	2025-03-13
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM025-01	2024-07-06	2025-07-05



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR240600210304

Page: 11 of 426

Radiated Emissions (Above 1GHz)					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
3m Fully-Anechoic Chamber	AUDIX	N/A	SEM001-02	2024-05-11	2027-05-10
Signal Analyzer	Rohde & Schwarz	FSV40	SEM008-04	2024-03-15	2025-03-14
Horn Antenna	Rohde&Schwarz	HF907	SEM003-07	2023-07-23	2025-07-22
Microwave system amplifier	Agilent	83017A	SEM005-25	2023-09-19	2024-09-18
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM026-01	2024-07-06	2025-07-05
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	SEM003-15	2022-08-10	2024-08-09
Pre-Amplifier	Compliance Directions Systems Inc.	PAP-2640-50	SEM005-08	2024-03-15	2025-03-14

Radiated Emissions which fall in the restricted bands					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
3m Fully-Anechoic Chamber	AUDIX	N/A	SEM001-02	2024-05-11	2027-05-10
Signal Analyzer	Rohde & Schwarz	FSV40	SEM008-04	2024-03-15	2025-03-14
Horn Antenna	Rohde&Schwarz	HF907	SEM003-07	2023-07-23	2025-07-22
Microwave system amplifier	Agilent	83017A	SEM005-25	2023-09-19	2024-09-18
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM026-01	2024-07-06	2025-07-05

Channel Move Time					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Manual Step Attenuator	KEYSIGHT	8494B	SEM021-05	2024-03-27	2025-03-26
Manual Step Attenuator	KEYSIGHT	8496B	SEM021-06	2024-03-27	2025-03-26
Measurement Software	KEYSIGHT	Signal Studio for DFS Radar Profiles V2.2.0.0	N/A	N/A	N/A
Measurement Software	Agilent	ISMonitor10	N/A	N/A	N/A
MXG Vector Signal Generator	Agilent	N5182A	SEM006-21	2024-03-27	2025-03-26
MXA Signal Analyzer	KEYSIGHT	N9020A	SEM004-22	2024-03-14	2025-03-13



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch
No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR240600210304

Page: 12 of 426

RF Conducted Test					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
DC Power Supply	Chroma	62012P-80-60	SEM011-11	2023-10-19	2024-10-18
MXA Signal Analyzer	KEYSIGHT	N9020A	SEM004-19	2024-03-14	2025-03-13
Signal Generator	KEYSIGHT	N5173B	SEM006-05	2023-09-19	2024-09-18
Measurement Software	TST PASS	TST PASS V2.0	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-01	2024-07-06	2025-07-05
Attenuator	Huber+Suhner	6620_SMA-50-1	SEM021-09	2024-03-27	2025-03-26
Programmable Temperature & Humidity Chamber	Votsch Industrietechnik GmbH	VT 4002	SEM002-15	2024-03-19	2025-03-18
Manual Step Attenuator	KEYSIGHT	8494B	SEM021-05	2024-03-27	2025-03-26
Manual Step Attenuator	KEYSIGHT	8496B	SEM021-06	2024-03-27	2025-03-26
MXG Vector Signal Generator	Agilent	N5182A	SEM006-21	2024-03-27	2025-03-26
MXA Signal Analyzer	KEYSIGHT	N9020A	SEM004-22	2024-03-14	2025-03-13

General used equipment					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Humidity/ Temperature Indicator	deli	8838	SEM002-32	2024-07-24	2025-07-23
Humidity/ Temperature Indicator	deli	8838	SEM002-33	2024-07-24	2025-07-23
Barometer	Changchun Meteorological Industry Factory	DYM3	SEM002-01	2024-03-18	2025-03-17



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing & Calibration Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

6 Radio Spectrum Technical Requirement

6.1 Antenna Requirement

6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203

6.1.2 Conclusion

15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:

The antenna is an External Antenna, and the connection port is fixed with glue, and the antenna cannot be replaced.

The best case gain of the antenna is

5150MHz to 5250MHz: 3dBi;*

5250MHz to 5350MHz: 3dBi;*

5470MHz to 5725MHz: 3dBi;*

5725MHz to 5850MHz: 3dBi;*

**Note:*

The antenna gain are derived from the gain information report provided by the manufacturer.

Remark:

As above information is provided and confirmed by the applicant. SGS is not liable to the accuracy, suitability, reliability or/and integrity of the information.

6.2 Transmission in the Absence of Data

6.2.1 Test Requirement:

47 CFR Part 15, Subpart E 15.407 (c)

6.2.2 Conclusion

Standard Requirement:

The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signalling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals.

Applicants shall include in their application for equipment authorization a description of how this requirement is met.

EUT Details:

WIFI chip support automatically discontinue transmission in case of either absence of information to transmit or operational failure, if the chip detect absence of information to transmit or operational failure, it will be automatically shut off.



7 Radio Spectrum Matter Test Results

7.1 Conducted Emissions at AC Power Line (150kHz-30MHz)

Test Requirement 47 CFR Part 15, Subpart C 15.207 & Subpart E 15.407 b(9)

Test Method: ANSI C63.10 (2013) Section 6.2

Limit:

Frequency of emission(MHz)	Conducted limit(dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

7.1.1 E.U.T. Operation

Operating Environment:

Temperature: 23.5 °C

Humidity: 45.5 % RH


Atmospheric Pressure: 1020 mbar

7.1.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	09	TX mode (U-NII-1) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n/ac 20/40/80, Only the data of worst case is recorded in the report.
Pre-scan	10	TX mode (U-NII-2A) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n/ac 20/40/80, Only the data of worst case is recorded in the report.
Pre-scan	11	TX mode (U-NII-2C) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n/ac 20/40/80, Only the data of worst case is recorded in the report.
Pre-scan	12	TX mode (U-NII-3) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n/ac 20/40/80, Only the data of worst case is recorded in the report.



7.1.3 Test Setup Diagram



7.1.4 Measurement Procedure and Data

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50μH + 5ohm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

Remark: Level=Read Level+ Cable Loss+ LISN Factor


SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR240600210304

Page: 17 of 426

Test Mode: 09; Line: Live line



Site : Shielding Room
Condition: Line
Job No. : 02103MO
Test mode: 09

	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1 *	0.1844	0.02	9.92	34.01	43.95	64.28	-20.33	QP
2 *	0.1844	0.02	9.92	18.63	28.57	54.28	-25.71	Average
3	0.2442	0.03	9.97	25.02	35.02	61.95	-26.93	QP
4	0.2442	0.03	9.97	12.54	22.54	51.95	-29.41	Average
5	0.3731	0.03	10.03	18.65	28.71	58.43	-29.72	QP
6	0.3731	0.03	10.03	12.18	22.24	48.43	-26.19	Average
7	1.7071	0.07	10.00	10.49	20.56	56.00	-35.44	QP
8	1.7071	0.07	10.00	4.40	14.47	46.00	-31.53	Average
9	2.0768	0.07	10.01	9.59	19.67	56.00	-36.33	QP
10	2.0768	0.07	10.01	2.79	12.87	46.00	-33.13	Average
11	11.1977	0.18	10.26	8.39	18.83	60.00	-41.17	QP
12	11.1977	0.18	10.26	2.14	12.58	50.00	-37.42	Average


SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR240600210304

Page: 18 of 426

Test Mode: 09; Line: Neutral Line



Site : Shielding Room
Condition: Neutral
Job No. : 02103MO
Test mode: 09

	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.1624	0.02	9.89	36.61	46.52	65.34	-18.82	QP
2	0.1624	0.02	9.89	20.40	30.31	55.34	-25.03	Average
3	0.2197	0.03	9.92	28.58	38.53	62.83	-24.30	QP
4	0.2197	0.03	9.92	15.59	25.54	52.83	-27.29	Average
5 *	0.3771	0.03	9.92	30.45	40.40	58.34	-17.94	QP
6 *	0.3771	0.03	9.92	22.54	32.49	48.34	-15.85	Average
7	0.5020	0.04	9.92	11.79	21.75	56.00	-34.25	QP
8	0.5020	0.04	9.92	6.60	16.56	46.00	-29.44	Average
9	2.0990	0.07	9.96	12.10	22.13	56.00	-33.87	QP
10	2.0990	0.07	9.96	5.05	15.08	46.00	-30.92	Average
11	10.5079	0.18	10.28	10.33	20.79	60.00	-39.21	QP
12	10.5079	0.18	10.28	3.81	14.27	50.00	-35.73	Average



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

7.2 Maximum Conducted output power

Test Requirement 47 CFR Part 15, Subpart E 15.407 (a)

Test Method: KDB 789033 D02 II E

Limit:

Frequency band(MHz)	Limit
5150-5250	≤1W(30dBm) for master device
	≤250mW(24dBm) for client device
5250-5350	≤250mW(24dBm) or 11dBm+10logB*
5470-5725	≤250mW(24dBm) or 11dBm+10logB*
5725-5850	≤1W(30dBm)
Remark:	* Where B is the 26dB emission bandwidth in MHz. The maximum conducted output power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage.

7.2.1 E.U.T. Operation

Operating Environment:

Temperature: 24.4 °C

Humidity: 44.8 % RH

Atmospheric Pressure: 1020 mbar

7.2.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	09	TX mode (U-NII-1)_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n/ac 20/40/80, Only the data of worst case is recorded in the report.
Final test	10	TX mode (U-NII-2A) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n/ac 20/40/80, Only the data of worst case is recorded in the report.
Final test	11	TX mode (U-NII-2C) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n/ac 20/40/80, Only the data of worst case is recorded in the report.
Final test	12	TX mode (U-NII-3) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n/ac 20/40/80, Only the data of worst case is recorded in the report.




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

7.2.3 Test Setup Diagram



7.2.4 Measurement Procedure and Data

Note: Since the verify power the same operating range bandwidth and smaller power can be covered by the higher power.

Please Refer to Appendix for Details

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR240600210304

Page: 21 of 426

7.3 Radiated Emissions (Below 1GHz)

Test Requirement 47 CFR Part 15, Subpart C 15.209 & Subpart E 15.407(b)

Test Method: KDB 789033 D02 II G

Measurement Distance: 3m

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
960-1000	500	3

7.3.1 E.U.T. Operation

Operating Environment:

Temperature: 20.2 °C

Humidity: 45.2 % RH

Atmospheric Pressure: 1020 mbar

7.3.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	09	TX mode (U-NII-1)_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n/ac 20/40/80, Only the data of worst case is recorded in the report.
Pre-scan	10	TX mode (U-NII-2A) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n/ac 20/40/80, Only the data of worst case is recorded in the report.
Pre-scan	11	TX mode (U-NII-2C) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n/ac 20/40/80, Only the data of worst case is recorded in the report.
Pre-scan	12	TX mode (U-NII-3) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.


Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing & Calibration Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

		is the worst case of IEEE 802.11n/ac 20/40/80, Only the data of worst case is recorded in the report.
--	--	---

7.3.3 Test Setup Diagram



7.3.4 Measurement Procedure and Data


- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using quasi-peak method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- i. Repeat above procedures until all frequencies measured was complete.

Remark:

1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
2. For emission below 1GHz, through the pre-scan found the worst case is the lowest channel of 802.11a. Only the worst case is recorded in the report.
3. Scan from 9kHz to 30MHz, the disturbance below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
4. The disturbance below 1GHz was very low and the harmonics were the highest point could be found when testing, so only the above harmonics had been displayed.



Test Mode: 09; Polarity: Horizontal




Site : chamber
Condition: 3m HORIZONTAL
Job No. : 02127MO
Test Mode: 09

	Ant	Cable	Preamp	Read		Limit	Over	
Freq	Factor	Loss	Factor	Level	Level	Line	Limit	Remark
MHz	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB	
1	30.00	21.20	0.64	27.79	22.81	16.86	40.00	-23.14 QP
2	90.54	11.77	1.13	27.62	31.50	16.78	40.00	-23.22 QP
3	197.89	14.08	1.72	27.18	38.29	26.91	40.00	-13.09 QP
4 q	286.98	16.96	2.11	26.80	42.17	34.44	47.00	-12.56 QP
5	582.74	24.05	3.15	27.90	26.31	25.61	47.00	-21.39 QP
6	955.44	28.10	4.23	26.37	23.10	29.06	47.00	-17.94 QP



Test Mode: 09; Polarity: Vertical



Site : chamber
Condition: 3m VERTICAL
Job No. : 02127MO
Test Mode: 09

		Ant	Cable	Preamp	Read		Limit	Over	
	Freq	Factor	Loss	Factor	Level	Level	Line	Limit	Remark
	MHz	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB	
1	q	40.42	16.20	0.75	27.76	35.85	25.04	40.00	-14.96 QP
2		109.03	12.00	1.24	27.55	34.80	20.49	40.00	-19.51 QP
3		182.56	14.17	1.64	27.24	36.33	24.90	40.00	-15.10 QP
4		294.11	17.36	2.14	26.77	39.02	31.75	47.00	-15.25 QP
5		495.93	22.84	2.88	27.55	28.34	26.51	47.00	-20.49 QP
6		945.44	28.26	4.21	26.44	23.53	29.56	47.00	-17.44 QP



7.4 Radiated Emissions (Above 1GHz)

Test Requirement 47 CFR Part 15, Subpart C 15.209 & Subpart E 15.407(b)

Test Method: KDB 789033 D02 II G

Measurement Distance: 3m

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
Above 1GHz	500	3
*(1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz. (2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz. (3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz. (4) For transmitters operating in the 5.725-5.85 GHz band: (i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge. Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.		

7.4.1 E.U.T. Operation

Operating Environment:

Temperature: 23.3 °C

Humidity: 54.9 % RH

Atmospheric Pressure: 1020 mbar

7.4.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	09	TX mode (U-NII-1)_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.


Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

		found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n/ac 20/40/80, Only the data of worst case is recorded in the report.
Final test	10	TX mode (U-NII-2A) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n/ac 20/40/80, Only the data of worst case is recorded in the report.
Final test	11	TX mode (U-NII-2C) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n/ac 20/40/80, Only the data of worst case is recorded in the report.
Final test	12	TX mode (U-NII-3) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n/ac 20/40/80, Only the data of worst case is recorded in the report.

7.4.3 Test Setup Diagram



7.4.4 Measurement Procedure and Data

- a. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- i. Repeat above procedures until all frequencies measured was complete.

Remark:

1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
2. Scan from 18GHz to 40GHz, the disturbance above 18GHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
3. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.
4. The disturbance above 18GHz were very low and the harmonics were the highest point could be found when testing, so only the above harmonics had been displayed.
5. For devices with multiple operating modes, measurements on the middle channel is used to determine the worst-case mode(s). Only the worst case mode with the highest output power and the mode with the highest output power spectral density for each modulation family (e.g., OFDM and direct sequence spread spectrum) is recorded in the test report.


SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR240600210304

Page: 29 of 426

Test Mode: 09; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:Low



Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5180 TX RSE
Note : 5G WIFI 11A

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1282.193	3.79	24.91	38.35	39.39	29.74	68.20	-38.46	peak
2	1615.754	4.21	26.64	38.40	39.23	31.68	74.00	-42.32	peak
3	3415.787	6.45	32.21	36.12	36.56	39.10	68.20	-29.10	peak
4	4291.977	7.01	33.97	35.88	36.71	41.81	74.00	-32.19	peak
5	10360.000	11.14	37.10	37.54	34.84	45.54	68.20	-22.66	peak
6	15540.000	13.79	41.10	37.23	30.26	47.92	74.00	-26.08	peak




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com


Test Mode: 09; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:Low



Site : chamber
 Condition: 3m VERTICAL
 Job No : 02877MO/02103MO
 Mode : 5180 TX RSE
 Note : 5G WIFI 11A

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1129.072	3.58	23.82	38.33	40.04	29.11	74.00	-44.89	peak
2	1494.455	4.03	26.64	38.39	39.52	31.80	74.00	-42.20	peak
3	3299.344	6.35	31.21	36.13	37.53	38.96	68.20	-29.24	peak
4	4367.058	7.10	34.54	35.82	36.17	41.99	74.00	-32.01	peak
5	10360.000	11.14	37.10	37.54	34.77	45.47	68.20	-22.73	peak
6	15540.000	13.79	41.10	37.23	30.11	47.77	74.00	-26.23	peak

Test Mode: 09; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:middle




Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5200 TX RSE
Note : 5G WIFI 11A

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1274.802	3.78	24.95	38.35	39.69	30.07	68.20	-38.13	peak
2	1565.191	4.14	26.94	38.40	39.31	31.99	74.00	-42.01	peak
3	3376.523	6.42	32.26	36.12	36.85	39.41	68.20	-28.79	peak
4	4341.886	7.07	34.34	35.84	36.65	42.22	74.00	-31.78	peak
5	10400.000	11.20	37.10	37.56	35.55	46.29	68.20	-21.91	peak
6	15600.000	13.86	41.10	37.26	30.45	48.15	74.00	-25.85	peak




Test Mode: 09; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:middle



Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5200 TX RSE
Note : 5G WIFI 11A

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1162.182	3.63	24.02	38.33	39.86	29.18	74.00	-44.82	peak
2	1644.019	4.25	26.36	38.41	39.40	31.60	68.20	-36.60	peak
3	3376.523	6.42	32.26	36.12	37.29	39.85	68.20	-28.35	peak
4	4379.699	7.11	34.64	35.81	36.38	42.32	74.00	-31.68	peak
5	10400.000	11.20	37.10	37.56	35.04	45.78	68.20	-22.42	peak
6	15600.000	13.86	41.10	37.26	31.38	49.08	74.00	-24.92	peak

Test Mode: 09; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5240 TX RSE
Note : 5G WIFI 11A

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1238.483	3.73	24.94	38.35	39.49	29.81	74.00	-44.19	peak
2	1663.137	4.27	26.27	38.41	40.17	32.30	74.00	-41.70	peak
3	3475.541	6.50	31.70	36.12	36.56	38.64	68.20	-29.56	peak
4	4242.641	6.95	33.80	35.91	37.64	42.48	74.00	-31.52	peak
5	10480.000	11.33	37.26	37.60	35.29	46.28	68.20	-21.92	peak
6	15720.000	14.01	41.22	37.31	30.44	48.36	74.00	-25.64	peak



Test Mode: 09; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5240 TX RSE
Note : 5G WIFI 11A

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1271.123	3.77	24.97	38.35	39.47	29.86	68.20	-38.34	peak
2	1697.129	4.32	26.21	38.41	40.09	32.21	74.00	-41.79	peak
3	3475.541	6.50	31.70	36.12	36.91	38.99	68.20	-29.21	peak
4	4341.886	7.07	34.34	35.84	36.33	41.90	74.00	-32.10	peak
5	10480.000	11.33	37.26	37.60	35.39	46.38	68.20	-21.82	peak
6	15720.000	14.01	41.22	37.31	30.81	48.73	74.00	-25.27	peak




Test Mode: 09; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:Low



Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5180 TX RSE
Note : 5G WIFI 11N20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1242.068	3.74	24.99	38.35	39.33	29.71	68.20	-38.49	peak
2	1682.477	4.30	26.24	38.41	39.90	32.03	74.00	-41.97	peak
3	3386.297	6.42	32.32	36.12	36.47	39.09	68.20	-29.11	peak
4	4417.841	7.16	34.59	35.78	36.17	42.14	68.20	-26.06	peak
5	10360.000	11.14	37.10	37.54	34.66	45.36	68.20	-22.84	peak
6	15540.000	13.79	41.10	37.23	29.98	47.64	74.00	-26.36	peak


Test Mode: 09; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:Low



Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5180 TX RSE
Note : 5G WIFI 11N20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1210.174	3.70	24.54	38.34	39.53	29.43	74.00	-44.57	peak
2	1682.477	4.30	26.24	38.41	39.84	31.97	74.00	-42.03	peak
3	3485.601	6.51	31.66	36.12	36.86	38.91	68.20	-29.29	peak
4	4316.859	7.04	34.13	35.86	36.95	42.26	74.00	-31.74	peak
5	10360.000	11.14	37.10	37.54	35.03	45.73	68.20	-22.47	peak
6	15540.000	13.79	41.10	37.23	30.25	47.91	74.00	-26.09	peak

Test Mode: 09; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:middle




Site : chamber
 Condition: 3m HORIZONTAL
 Job No : 02877MO/02103MO
 Mode : 5200 TX RSE
 Note : 5G WIFI 11N20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1274.802	3.78	24.95	38.35	38.79	29.17	68.20	-39.03	peak
2	1672.779	4.29	26.25	38.41	39.56	31.69	74.00	-42.31	peak
3	3425.675	6.46	32.09	36.12	37.09	39.52	68.20	-28.68	peak
4	4109.872	6.79	33.16	36.01	37.73	41.67	74.00	-32.33	peak
5	10400.000	11.20	37.10	37.56	35.05	45.79	68.20	-22.41	peak
6	15600.000	13.86	41.10	37.26	31.47	49.17	74.00	-24.83	peak



Test Mode: 09; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:middle



Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5200 TX RSE
Note : 5G WIFI 11N20


		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1293.359	3.80	24.84	38.36	39.21	29.49	68.20	-38.71	peak
2	1702.042	4.33	26.22	38.42	39.83	31.96	74.00	-42.04	peak
3	3357.061	6.40	32.14	36.12	36.60	39.02	74.00	-34.98	peak
4	4316.859	7.04	34.13	35.86	37.53	42.84	74.00	-31.16	peak
5	10400.000	11.20	37.10	37.56	35.77	46.51	68.20	-21.69	peak
6	15600.000	13.86	41.10	37.26	30.92	48.62	74.00	-25.38	peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com
No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com


Test Mode: 09; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:High



Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5240 TX RSE
Note : 5G WIFI 11N20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1267.454	3.77	25.00	38.35	39.27	29.69	68.20	-38.51	peak
2	1677.621	4.29	26.24	38.41	40.58	32.70	74.00	-41.30	peak
3	3308.894	6.36	31.36	36.13	37.60	39.19	68.20	-29.01	peak
4	4145.664	6.83	33.73	35.99	37.27	41.84	74.00	-32.16	peak
5	10480.000	11.33	37.26	37.60	34.57	45.56	68.20	-22.64	peak
6	15720.000	14.01	41.22	37.31	30.15	48.07	74.00	-25.93	peak


Test Mode: 09; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:High



Site : chamber
 Condition: 3m VERTICAL
 Job No : 02877MO/02103MO
 Mode : 5240 TX RSE
 Note : 5G WIFI 11N20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1129.072	3.58	23.82	38.33	40.31	29.38	74.00	-44.62	peak
2	1682.477	4.30	26.24	38.41	39.90	32.03	74.00	-41.97	peak
3	3495.691	6.52	31.62	36.12	37.10	39.12	68.20	-29.08	peak
4	4354.454	7.08	34.44	35.83	36.40	42.09	74.00	-31.91	peak
5	10480.000	11.33	37.26	37.60	35.08	46.07	68.20	-22.13	peak
6	15720.000	14.01	41.22	37.31	30.40	48.32	74.00	-25.68	peak


Test Mode: 09; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:Low



Site : chamber
 Condition: 3m HORIZONTAL
 Job No : 02877MO/02103MO
 Mode : 5190 TX RSE
 Note : 5G WIFI 11N40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1172.303	3.64	24.12	38.33	39.72	29.15	74.00	-44.85	peak
2	1663.137	4.27	26.27	38.41	40.17	32.30	74.00	-41.70	peak
3	3445.535	6.47	31.85	36.12	37.14	39.34	68.20	-28.86	peak
4	4430.628	7.17	34.43	35.77	35.79	41.62	68.20	-26.58	peak
5	10380.000	11.17	37.10	37.55	35.08	45.80	68.20	-22.40	peak
6	15570.000	13.83	41.10	37.25	29.88	47.56	74.00	-26.44	peak


Test Mode: 09; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:Low



Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5190 TX RSE
Note : 5G WIFI 11N40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1196.264	3.68	24.36	38.34	39.51	29.21	74.00	-44.79	peak
2	1697.129	4.32	26.21	38.41	39.46	31.58	74.00	-42.42	peak
3	3386.297	6.42	32.32	36.12	36.59	39.21	68.20	-28.99	peak
4	4329.354	7.05	34.23	35.85	36.15	41.58	74.00	-32.42	peak
5	10380.000	11.17	37.10	37.55	35.44	46.16	68.20	-22.04	peak
6	15570.000	13.83	41.10	37.25	30.11	47.79	74.00	-26.21	peak

Test Mode: 09; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5230 TX RSE
Note : 5G WIFI 11N40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1217.190	3.71	24.64	38.34	39.61	29.62	74.00	-44.38	peak
2	1702.042	4.33	26.22	38.42	39.35	31.48	74.00	-42.52	peak
3	3485.601	6.51	31.66	36.12	37.25	39.30	68.20	-28.90	peak
4	4443.453	7.19	34.28	35.77	36.25	41.95	68.20	-26.25	peak
5	10460.000	11.30	37.22	37.59	35.05	45.98	68.20	-22.22	peak
6	15690.000	13.97	41.19	37.30	30.64	48.50	74.00	-25.50	peak



Test Mode: 09; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5230 TX RSE
Note : 5G WIFI 11N40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1289.627	3.80	24.86	38.36	38.92	29.22	68.20	-38.98	peak
2	1677.621	4.29	26.24	38.41	39.93	32.05	74.00	-41.95	peak
3	3465.510	6.49	31.74	36.12	36.80	38.91	68.20	-29.29	peak
4	4157.664	6.85	33.80	35.98	37.30	41.97	74.00	-32.03	peak
5	10460.000	11.30	37.22	37.59	34.94	45.87	68.20	-22.33	peak
6	15690.000	13.97	41.19	37.30	31.31	49.17	74.00	-24.83	peak



Test Mode: 09; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5180 TX RSE
Note : 5G WIFI 11AC20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1282.193	3.79	24.91	38.35	39.52	29.87	68.20	-38.33	peak
2	1692.231	4.31	26.22	38.41	40.49	32.61	74.00	-41.39	peak
3	3455.508	6.48	31.78	36.12	37.30	39.44	68.20	-28.76	peak
4	4354.454	7.08	34.44	35.83	36.41	42.10	74.00	-31.90	peak
5	10360.000	11.14	37.10	37.54	35.00	45.74	68.20	-22.46	peak
6	15540.000	13.79	41.10	37.23	30.00	47.66	74.00	-26.34	peak



Test Mode: 09; Polarity: Vertical; Modulation:802.11ac; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5180 TX RSE
Note : 5G WIFI 11AC20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1175.697	3.65	24.16	38.34	45.75	35.22	74.00	-38.78	peak
2	1663.137	4.27	26.27	38.41	40.21	32.34	74.00	-41.66	peak
3	3405.929	6.44	32.33	36.12	36.08	38.73	68.20	-29.47	peak
4	4392.376	7.13	34.74	35.80	35.84	41.91	74.00	-32.09	peak
5	10360.000	11.14	37.10	37.54	34.98	45.68	68.20	-22.52	peak
6	15540.000	13.79	41.10	37.23	30.36	48.02	74.00	-25.98	peak




Test Mode: 09; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:20MHz; Channel:middle



Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5200 TX RSE
Note : 5G WIFI 11AC20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1249.269	3.75	25.09	38.35	38.83	29.32	68.20	-38.88	peak
2	1677.621	4.29	26.24	38.41	39.69	31.81	74.00	-42.19	peak
3	3386.297	6.42	32.32	36.12	36.48	39.10	68.20	-29.10	peak
4	4304.400	7.02	34.04	35.87	36.99	42.18	74.00	-31.82	peak
5	10400.000	11.20	37.10	37.56	34.88	45.62	68.20	-22.58	peak
6	15600.000	13.86	41.10	37.26	30.59	48.29	74.00	-25.71	peak


Test Mode: 09; Polarity: Vertical; Modulation:802.11ac; Bandwidth:20MHz; Channel:middle



Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5200 TX RSE
Note : 5G WIFI 11AC20

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1271.123	3.77	24.97	38.35	38.68	29.07	68.20	-39.13	peak
2	1667.951	4.28	26.26	38.41	39.73	31.86	74.00	-42.14	peak
3	3425.675	6.46	32.09	36.12	36.72	39.15	68.20	-29.05	peak
4	4316.859	7.04	34.13	35.86	36.94	42.25	74.00	-31.75	peak
5	10400.000	11.20	37.10	37.56	35.69	46.43	68.20	-21.77	peak
6	15600.000	13.86	41.10	37.26	30.90	48.60	74.00	-25.40	peak


Test Mode: 09; Polarity: Horizontal; Modulation: 802.11ac; Bandwidth: 20MHz; Channel: High



Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5240 TX RSE
Note : 5G WIFI 11AC20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1282.193	3.79	24.91	38.35	38.62	28.97	68.20	-39.23	peak
2	1648.778	4.25	26.31	38.41	39.60	31.75	68.20	-36.45	peak
3	3465.510	6.49	31.74	36.12	37.32	39.43	68.20	-28.77	peak
4	4206.011	6.91	33.80	35.94	37.29	42.06	74.00	-31.94	peak
5	10480.000	11.33	37.26	37.60	34.82	45.81	68.20	-22.39	peak
6	15720.000	14.01	41.22	37.31	30.61	48.53	74.00	-25.47	peak

Test Mode: 09; Polarity: Vertical; Modulation:802.11ac; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5240 TX RSE
Note : 5G WIFI 11AC20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1278.492	3.78	24.93	38.35	38.80	29.16	68.20	-39.04	peak
2	1677.621	4.29	26.24	38.41	39.85	31.97	74.00	-42.03	peak
3	3405.929	6.44	32.33	36.12	36.58	39.23	68.20	-28.97	peak
4	4169.698	6.86	33.80	35.97	37.51	42.20	74.00	-31.80	peak
5	10480.000	11.33	37.26	37.60	35.10	46.09	68.20	-22.11	peak
6	15720.000	14.01	41.22	37.31	30.48	48.40	74.00	-25.60	peak



Test Mode: 09; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:40MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5190 TX RSE
Note : 5G WIFI 11AC40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1289.627	3.80	24.86	38.36	38.81	29.11	68.20	-39.09	peak
2	1677.621	4.29	26.24	38.41	40.11	32.23	74.00	-41.77	peak
3	3405.929	6.44	32.33	36.12	36.37	39.02	68.20	-29.18	peak
4	4279.589	6.99	33.92	35.89	36.89	41.91	74.00	-32.09	peak
5	10380.000	11.17	37.10	37.55	34.97	45.69	68.20	-22.51	peak
6	15570.000	13.83	41.10	37.25	30.43	48.11	74.00	-25.89	peak



Test Mode: 09; Polarity: Vertical; Modulation:802.11ac; Bandwidth:40MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5190 TX RSE
Note : 5G WIFI 11AC40

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1271.123	3.77	24.97	38.35	39.14	29.53	68.20	-38.67	peak
2	1667.951	4.28	26.26	38.41	39.50	31.63	74.00	-42.37	peak
3	3337.710	6.38	31.88	36.13	36.85	38.98	74.00	-35.02	peak
4	4316.859	7.04	34.13	35.86	36.27	41.58	74.00	-32.42	peak
5	10380.000	11.17	37.10	37.55	35.19	45.91	68.20	-22.29	peak
6	15570.000	13.83	41.10	37.25	29.97	47.65	74.00	-26.35	peak



Test Mode: 09; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:40MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5230 TX RSE
Note : 5G WIFI 11AC40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1152.148	3.62	23.92	38.33	39.78	28.99	74.00	-45.01	peak
2	1653.550	4.26	26.29	38.41	40.00	32.14	68.20	-36.06	peak
3	3455.508	6.48	31.78	36.12	36.90	39.04	68.20	-29.16	peak
4	4341.886	7.07	34.34	35.84	36.24	41.81	74.00	-32.19	peak
5	10460.000	11.30	37.22	37.59	35.29	46.22	68.20	-21.98	peak
6	15690.000	13.97	41.19	37.30	31.03	48.89	74.00	-25.11	peak




Test Mode: 09; Polarity: Vertical; Modulation:802.11ac; Bandwidth:40MHz; Channel:High



Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5230 TX RSE
Note : 5G WIFI 11AC40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1297.103	3.81	24.82	38.36	39.21	29.48	68.20	-38.72	peak
2	1677.621	4.29	26.24	38.41	40.20	32.32	74.00	-41.68	peak
3	3425.675	6.46	32.09	36.12	37.02	39.45	68.20	-28.75	peak
4	4279.589	6.99	33.92	35.89	37.76	42.78	74.00	-31.22	peak
5	10460.000	11.30	37.22	37.59	35.37	46.30	68.20	-21.90	peak
6	15690.000	13.97	41.19	37.30	30.45	48.31	74.00	-25.69	peak

Test Mode: 09; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:80MHz; Channel:middle




Site : chamber
 Condition: 3m HORIZONTAL
 Job No : 02877MO/02103MO
 Mode : 5210 TX RSE
 Note : 5G WIFI 11AC80

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1242.068	3.74	24.99	38.35	38.73	29.11	68.20	-39.09	peak
2	1667.951	4.28	26.26	38.41	40.78	32.91	74.00	-41.09	peak
3	3386.297	6.42	32.32	36.12	35.90	38.52	68.20	-29.68	peak
4	4354.454	7.08	34.44	35.83	36.70	42.39	74.00	-31.61	peak
5	10420.000	11.23	37.14	37.57	35.34	46.14	68.20	-22.06	peak
6	15630.000	13.90	41.13	37.27	30.30	48.06	74.00	-25.94	peak




Test Mode: 09; Polarity: Vertical; Modulation:802.11ac; Bandwidth:80MHz; Channel:middle



Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5210 TX RSE
Note : 5G WIFI 11AC80

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1278.492	3.78	24.93	38.35	39.50	29.86	68.20	-38.34	peak
2	1697.129	4.32	26.21	38.41	39.50	31.62	74.00	-42.38	peak
3	3396.098	6.43	32.38	36.12	36.49	39.18	68.20	-29.02	peak
4	4316.859	7.04	34.13	35.86	37.07	42.38	74.00	-31.62	peak
5	10420.000	11.23	37.14	37.57	35.58	46.38	68.20	-21.82	peak
6	15630.000	13.90	41.13	37.27	30.21	47.97	74.00	-26.03	peak

Test Mode: 10; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5260 TX RSE
Note : 5G WIFI 11A

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1252.885	3.75	25.08	38.35	39.05	29.53	68.20	-38.67	peak
2	1634.543	4.23	26.45	38.41	39.62	31.89	68.20	-36.31	peak
3	3465.510	6.49	31.74	36.12	37.18	39.29	68.20	-28.91	peak
4	4157.664	6.85	33.80	35.98	37.41	42.08	74.00	-31.92	peak
5	10520.000	11.37	37.30	37.62	34.73	45.78	68.20	-22.42	peak
6	15780.000	14.08	41.28	37.33	29.36	47.39	74.00	-26.61	peak




Test Mode: 10; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:Low



Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5260 TX RSE
Note : 5G WIFI 11A

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1168.920	3.64	24.09	38.33	39.56	28.96	74.00	-45.04	peak
2	1692.231	4.31	26.22	38.41	39.89	32.01	74.00	-41.99	peak
3	3425.675	6.46	32.09	36.12	36.24	38.67	68.20	-29.53	peak
4	4443.453	7.19	34.28	35.77	36.17	41.87	68.20	-26.33	peak
5	10520.000	11.37	37.30	37.62	34.29	45.34	68.20	-22.86	peak
6	15780.000	14.08	41.28	37.33	30.10	48.13	74.00	-25.87	peak


Test Mode: 10; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:middle



Site : chamber
 Condition: 3m HORIZONTAL
 Job No : 02877MO/02103MO
 Mode : 5300 TX RSE
 Note : 5G WIFI 11A

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1109.660	3.56	23.74	38.32	39.89	28.87	74.00	-45.13	peak
2	1702.042	4.33	26.22	38.42	39.66	31.79	74.00	-42.21	peak
3	3465.510	6.49	31.74	36.12	37.81	39.92	68.20	-28.28	peak
4	4469.214	7.22	33.97	35.75	37.11	42.55	68.20	-25.65	peak
5	10600.000	11.43	37.30	37.66	35.60	46.67	68.20	-21.53	peak
6	15900.000	14.23	41.40	37.38	28.72	46.97	74.00	-27.03	peak

Test Mode: 10; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:middle




Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5300 TX RSE
Note : 5G WIFI 11A

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1206.682	3.69	24.49	38.34	39.28	29.12	74.00	-44.88	peak
2	1620.431	4.21	26.60	38.40	39.07	31.48	74.00	-42.52	peak
3	3328.077	6.37	31.71	36.13	37.07	39.02	68.20	-29.18	peak
4	4316.859	7.04	34.13	35.86	36.56	41.87	74.00	-32.13	peak
5	10600.000	11.43	37.30	37.66	35.45	46.52	68.20	-21.68	peak
6	15900.000	14.23	41.40	37.38	28.45	46.70	74.00	-27.30	peak



Test Mode: 10; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5320 TX RSE
Note : 5G WIFI 11A

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1260.149	3.76	25.04	38.35	38.76	29.21	68.20	-38.99	peak
2	1687.347	4.31	26.23	38.41	39.89	32.02	74.00	-41.98	peak
3	3445.535	6.47	31.85	36.12	37.35	39.55	68.20	-28.65	peak
4 p	4417.841	7.16	34.59	35.78	35.94	41.91	68.20	-26.29	peak
5	10640.000	11.45	37.22	37.68	35.71	46.70	74.00	-27.30	peak
6	15960.000	14.30	41.52	37.40	29.26	47.68	74.00	-26.32	peak




Test Mode: 10; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:High



Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5320 TX RSE
Note : 5G WIFI 11A

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1182.513	3.66	24.23	38.34	41.80	31.35	74.00	-42.65	peak
2	1682.477	4.30	26.24	38.41	40.12	32.25	74.00	-41.75	peak
3	3425.675	6.46	32.09	36.12	36.34	38.77	68.20	-29.43	peak
4 p	4417.841	7.16	34.59	35.78	36.10	42.07	68.20	-26.13	peak
5	10640.000	11.45	37.22	37.68	35.57	46.56	74.00	-27.44	peak
6	15960.000	14.30	41.52	37.40	29.26	47.68	74.00	-26.32	peak

Test Mode: 10; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5260 TX RSE
Note : 5G WIFI 11N20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1182.513	3.66	24.23	38.34	42.70	32.25	74.00	-41.75	peak
2	1677.621	4.29	26.24	38.41	39.79	31.91	74.00	-42.09	peak
3	3465.510	6.49	31.74	36.12	36.81	38.92	68.20	-29.28	peak
4	4354.454	7.08	34.44	35.83	36.34	42.03	74.00	-31.97	peak
5	10520.000	11.37	37.30	37.62	35.09	46.14	68.20	-22.06	peak
6	15780.000	14.08	41.28	37.33	29.39	47.42	74.00	-26.58	peak




Test Mode: 10; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:Low



Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5260 TX RSE
Note : 5G WIFI 11N20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1182.513	3.66	24.23	38.34	43.16	32.71	74.00	-41.29	peak
2	1672.779	4.29	26.25	38.41	39.99	32.12	74.00	-41.88	peak
3	3445.535	6.47	31.85	36.12	37.18	39.38	68.20	-28.82	peak
4	4456.315	7.20	34.12	35.76	36.23	41.79	68.20	-26.41	peak
5	10520.000	11.37	37.30	37.62	35.06	46.11	68.20	-22.09	peak
6	15780.000	14.08	41.28	37.33	29.10	47.13	74.00	-26.87	peak

Test Mode: 10; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:middle




Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5300 TX RSE
Note : 5G WIFI 11N20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1182.513	3.66	24.23	38.34	42.46	32.01	74.00	-41.99	peak
2	1644.019	4.25	26.36	38.41	40.02	32.22	68.20	-35.98	peak
3	3465.510	6.49	31.74	36.12	36.94	39.05	68.20	-29.15	peak
4	4193.872	6.89	33.80	35.95	37.18	41.92	74.00	-32.08	peak
5	10600.000	11.43	37.30	37.66	35.85	46.92	68.20	-21.28	peak
6	15900.000	14.23	41.40	37.38	28.51	46.76	74.00	-27.24	peak



Test Mode: 10; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:middle




Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5300 TX RSE
Note : 5G WIFI 11N20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1182.513	3.66	24.23	38.34	42.97	32.52	74.00	-41.48	peak
2	1682.477	4.30	26.24	38.41	39.73	31.86	74.00	-42.14	peak
3	3405.929	6.44	32.33	36.12	36.90	39.55	68.20	-28.65	peak
4	4341.886	7.07	34.34	35.84	36.36	41.93	74.00	-32.07	peak
5	10600.000	11.43	37.30	37.66	35.44	46.51	68.20	-21.69	peak
6	15900.000	14.23	41.40	37.38	28.66	46.91	74.00	-27.09	peak



Test Mode: 10; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5320 TX RSE
Note : 5G WIFI 11N20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1260.149	3.76	25.04	38.35	38.94	29.39	68.20	-38.81	peak
2	1702.042	4.33	26.22	38.42	40.73	32.86	74.00	-41.14	peak
3	3425.675	6.46	32.09	36.12	36.73	39.16	68.20	-29.04	peak
4	4329.354	7.05	34.23	35.85	36.36	41.79	74.00	-32.21	peak
5	10640.000	11.45	37.22	37.68	35.86	46.85	74.00	-27.15	peak
6	p15960.000	14.30	41.52	37.40	28.86	47.28	74.00	-26.72	peak




Test Mode: 10; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:High



Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5320 TX RSE
Note : 5G WIFI 11N20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1182.513	3.66	24.23	38.34	42.78	32.33	74.00	-41.67	peak
2	1697.129	4.32	26.21	38.41	39.66	31.78	74.00	-42.22	peak
3	3495.691	6.52	31.62	36.12	36.83	38.85	68.20	-29.35	peak
4	4405.090	7.14	34.74	35.79	35.51	41.60	68.20	-26.60	peak
5	10640.000	11.45	37.22	37.68	35.88	46.87	74.00	-27.13	peak
6	p15960.000	14.30	41.52	37.40	28.98	47.40	74.00	-26.60	peak

Test Mode: 10; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5270 TX RSE
Note : 5G WIFI 11N40

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1278.492	3.78	24.93	38.35	38.52	28.88	68.20	-39.32	peak
2	1677.621	4.29	26.24	38.41	39.58	31.70	74.00	-42.30	peak
3	3435.590	6.47	31.97	36.12	36.67	38.99	68.20	-29.21	peak
4	4367.058	7.10	34.54	35.82	35.95	41.77	74.00	-32.23	peak
5	10540.000	11.39	37.30	37.63	35.73	46.79	68.20	-21.41	peak
6	15810.000	14.12	41.31	37.34	28.57	46.66	74.00	-27.34	peak



Test Mode: 10; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:Low



Site : chamber
 Condition: 3m VERTICAL
 Job No : 02877MO/02103MO
 Mode : 5270 TX RSE
 Note : 5G WIFI 11N40


	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1293.359	3.80	24.84	38.36	38.63	28.91	68.20	-39.29	peak
2	1687.347	4.31	26.23	38.41	39.98	32.11	74.00	-41.89	peak
3	3465.510	6.49	31.74	36.12	36.72	38.83	68.20	-29.37	peak
4	4405.090	7.14	34.74	35.79	36.62	42.71	68.20	-25.49	peak
5	10540.000	11.39	37.30	37.63	35.19	46.25	68.20	-21.95	peak
6	15810.000	14.12	41.31	37.34	28.90	46.99	74.00	-27.01	peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com
 No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com


Test Mode: 10; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:High



Site : chamber
 Condition: 3m HORIZONTAL
 Job No : 02877MO/02103MO
 Mode : 5310 TX RSE
 Note : 5G WIFI 11N40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1179.100	3.65	24.19	38.34	40.51	30.01	74.00	-43.99	peak
2	1611.091	4.20	26.69	38.40	38.96	31.45	74.00	-42.55	peak
3	3475.541	6.50	31.70	36.12	36.92	39.00	68.20	-29.20	peak
4	4329.354	7.05	34.23	35.85	36.90	42.33	74.00	-31.67	peak
5	10620.000	11.44	37.26	37.67	35.69	46.72	74.00	-27.28	peak
6	15930.000	14.27	41.46	37.39	28.84	47.18	74.00	-26.82	peak

Test Mode: 10; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5310 TX RSE
Note : 5G WIFI 11N40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1152.148	3.62	23.92	38.33	39.68	28.89	74.00	-45.11	peak
2	1682.477	4.30	26.24	38.41	39.62	31.75	74.00	-42.25	peak
3	3357.061	6.40	32.14	36.12	36.00	38.42	74.00	-35.58	peak
4	4316.859	7.04	34.13	35.86	37.55	42.86	74.00	-31.14	peak
5	10620.000	11.44	37.26	37.67	35.88	46.91	74.00	-27.09	peak
6	p15930.000	14.27	41.46	37.39	28.62	46.96	74.00	-27.04	peak



Test Mode: 10; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5260 TX RSE
Note : 5G WIFI 11AC20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1249.269	3.75	25.09	38.35	38.67	29.16	68.20	-39.04	peak
2	1663.137	4.27	26.27	38.41	39.77	31.90	74.00	-42.10	peak
3	3465.510	6.49	31.74	36.12	37.23	39.34	68.20	-28.86	peak
4	4341.886	7.07	34.34	35.84	36.23	41.80	74.00	-32.20	peak
5	10520.000	11.37	37.30	37.62	35.02	46.07	68.20	-22.13	peak
6	15780.000	14.08	41.28	37.33	29.21	47.24	74.00	-26.76	peak



Test Mode: 10; Polarity: Vertical; Modulation:802.11ac; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5260 TX RSE
Note : 5G WIFI 11AC20

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1297.103	3.81	24.82	38.36	38.71	28.98	68.20	-39.22	peak
2	1639.274	4.24	26.41	38.41	39.67	31.91	68.20	-36.29	peak
3	3435.590	6.47	31.97	36.12	36.34	38.66	68.20	-29.54	peak
4	4354.454	7.08	34.44	35.83	36.34	42.03	74.00	-31.97	peak
5	10520.000	11.37	37.30	37.62	35.05	46.10	68.20	-22.10	peak
6	15780.000	14.08	41.28	37.33	29.11	47.14	74.00	-26.86	peak




Test Mode: 10; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:20MHz; Channel:middle



Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5300 TX RSE
Note : 5G WIFI 11AC20

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1252.885	3.75	25.08	38.35	39.09	29.57	68.20	-38.63	peak
2	1644.019	4.25	26.36	38.41	39.64	31.84	68.20	-36.36	peak
3	3357.061	6.40	32.14	36.12	36.48	38.90	74.00	-35.10	peak
4	4354.454	7.08	34.44	35.83	36.13	41.82	74.00	-32.18	peak
5	10600.000	11.43	37.30	37.66	35.23	46.30	68.20	-21.90	peak
6	15900.000	14.23	41.40	37.38	28.94	47.19	74.00	-26.81	peak


Test Mode: 10; Polarity: Vertical; Modulation:802.11ac; Bandwidth:20MHz; Channel:middle



Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5300 TX RSE
Note : 5G WIFI 11AC20

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1274.802	3.78	24.95	38.35	39.50	29.88	68.20	-38.32	peak
2	1677.621	4.29	26.24	38.41	40.18	32.30	74.00	-41.70	peak
3	3405.929	6.44	32.33	36.12	36.79	39.44	68.20	-28.76	peak
4	4169.698	6.86	33.80	35.97	37.23	41.92	74.00	-32.08	peak
5	10600.000	11.43	37.30	37.66	35.65	46.72	68.20	-21.48	peak
6	15900.000	14.23	41.40	37.38	28.19	46.44	74.00	-27.56	peak

Test Mode: 10; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5320 TX RSE
Note : 5G WIFI 11AC20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1234.909	3.73	24.89	38.35	40.00	30.27	74.00	-43.73	peak
2	1663.137	4.27	26.27	38.41	39.83	31.96	74.00	-42.04	peak
3	3485.601	6.51	31.66	36.12	37.23	39.28	68.20	-28.92	peak
4	4304.400	7.02	34.04	35.87	36.56	41.75	74.00	-32.25	peak
5	10640.000	11.45	37.22	37.68	35.03	46.02	74.00	-27.98	peak
6	p15960.000	14.30	41.52	37.40	28.80	47.22	74.00	-26.78	peak



Test Mode: 10; Polarity: Vertical; Modulation:802.11ac; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5320 TX RSE
Note : 5G WIFI 11AC20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1249.269	3.75	25.09	38.35	38.81	29.30	68.20	-38.90	peak
2	1615.754	4.21	26.64	38.40	38.93	31.38	74.00	-42.62	peak
3	3465.510	6.49	31.74	36.12	36.68	38.79	68.20	-29.41	peak
4 p	4417.841	7.16	34.59	35.78	35.97	41.94	68.20	-26.26	peak
5	10640.000	11.45	37.22	37.68	35.44	46.43	74.00	-27.57	peak
6	15960.000	14.30	41.52	37.40	28.95	47.37	74.00	-26.63	peak




Test Mode: 10; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:40MHz; Channel:Low



Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5270 TX RSE
Note : 5G WIFI 11AC40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1267.454	3.77	25.00	38.35	39.08	29.50	68.20	-38.70	peak
2	1682.477	4.30	26.24	38.41	39.93	32.06	74.00	-41.94	peak
3	3425.675	6.46	32.09	36.12	36.35	38.78	68.20	-29.42	peak
4	4430.628	7.17	34.43	35.77	36.68	42.51	68.20	-25.69	peak
5	10540.000	11.39	37.30	37.63	34.64	45.70	68.20	-22.50	peak
6	15810.000	14.12	41.31	37.34	29.57	47.66	74.00	-26.34	peak

Test Mode: 10; Polarity: Vertical; Modulation:802.11ac; Bandwidth:40MHz; Channel:Low



Site : chamber
 Condition: 3m VERTICAL
 Job No : 02877MO/02103MO
 Mode : 5270 TX RSE
 Note : 5G WIFI 11AC40


	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1267.454	3.77	25.00	38.35	38.42	28.84	68.20	-39.36	peak
2	1682.477	4.30	26.24	38.41	39.37	31.50	74.00	-42.50	peak
3	3376.523	6.42	32.26	36.12	36.14	38.70	68.20	-29.50	peak
4	4329.354	7.05	34.23	35.85	36.98	42.41	74.00	-31.59	peak
5	10540.000	11.39	37.30	37.63	34.95	46.01	68.20	-22.19	peak
6	15810.000	14.12	41.31	37.34	29.32	47.41	74.00	-26.59	peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com
 No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Test Mode: 10; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:40MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5310 TX RSE
Note : 5G WIFI 11AC40

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1227.791	3.72	24.79	38.34	39.17	29.34	74.00	-44.66	peak
2	1634.543	4.23	26.45	38.41	39.66	31.93	68.20	-36.27	peak
3	3445.535	6.47	31.85	36.12	37.16	39.36	68.20	-28.84	peak
4	4316.859	7.04	34.13	35.86	36.68	41.99	74.00	-32.01	peak
5	10620.000	11.44	37.26	37.67	35.37	46.40	74.00	-27.60	peak
6	p15930.000	14.27	41.46	37.39	28.54	46.88	74.00	-27.12	peak



Test Mode: 10; Polarity: Vertical; Modulation:802.11ac; Bandwidth:40MHz; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5310 TX RSE
Note : 5G WIFI 11AC40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1260.149	3.76	25.04	38.35	39.60	30.05	68.20	-38.15	peak
2	1677.621	4.29	26.24	38.41	40.92	33.04	74.00	-40.96	peak
3	3376.523	6.42	32.26	36.12	36.54	39.10	68.20	-29.10	peak
4	4367.058	7.10	34.54	35.82	35.88	41.70	74.00	-32.30	peak
5	10620.000	11.44	37.26	37.67	35.80	46.83	74.00	-27.17	peak
6	p15930.000	14.27	41.46	37.39	28.51	46.85	74.00	-27.15	peak




Test Mode: 10; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:80MHz; Channel:middle



Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5290 TX RSE
Note : 5G WIFI 11AC80

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1300.858	3.81	24.79	38.36	39.32	29.56	74.00	-44.44	peak
2	1648.778	4.25	26.31	38.41	39.34	31.49	68.20	-36.71	peak
3	3465.510	6.49	31.74	36.12	38.16	40.27	68.20	-27.93	peak
4	4354.454	7.08	34.44	35.83	36.25	41.94	74.00	-32.06	peak
5	10580.000	11.41	37.30	37.65	35.67	46.73	68.20	-21.47	peak
6	15870.000	14.19	41.37	37.37	28.52	46.71	74.00	-27.29	peak


Test Mode: 10; Polarity: Vertical; Modulation:802.11ac; Bandwidth:80MHz; Channel:middle



Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5290 TX RSE
Note : 5G WIFI 11AC80

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1179.100	3.65	24.19	38.34	39.51	29.01	74.00	-44.99	peak
2	1702.042	4.33	26.22	38.42	40.43	32.56	74.00	-41.44	peak
3	3435.590	6.47	31.97	36.12	36.84	39.16	68.20	-29.04	peak
4	4430.628	7.17	34.43	35.77	36.00	41.83	68.20	-26.37	peak
5	10580.000	11.41	37.30	37.65	35.84	46.90	68.20	-21.30	peak
6	15870.000	14.19	41.37	37.37	28.70	46.89	74.00	-27.11	peak


Test Mode: 11; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:Low



Site : chamber
 Condition: 3m HORIZONTAL
 Job No : 02877MO/02103MO
 Mode : 5500 TX RSE
 Note : 5G WIFI 11A

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1179.100	3.65	24.19	38.34	39.19	28.69	74.00	-45.31	peak
2	1697.129	4.32	26.21	38.41	40.46	32.58	74.00	-41.42	peak
3	3425.675	6.46	32.09	36.12	36.33	38.76	68.20	-29.44	peak
4	4169.698	6.86	33.80	35.97	37.15	41.84	74.00	-32.16	peak
5	11000.000	11.68	37.50	37.84	33.91	45.25	74.00	-28.75	peak
6	p16500.000	13.99	42.10	37.47	28.14	46.76	68.20	-21.44	peak


Test Mode: 11; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:Low



Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5500 TX RSE
Note : 5G WIFI 11A

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1297.103	3.81	24.82	38.36	39.47	29.74	68.20	-38.46	peak
2	1702.042	4.33	26.22	38.42	39.28	31.41	74.00	-42.59	peak
3	3396.098	6.43	32.38	36.12	35.80	38.49	68.20	-29.71	peak
4	4291.977	7.01	33.97	35.88	36.78	41.88	74.00	-32.12	peak
5	11000.000	11.68	37.50	37.84	34.59	45.93	74.00	-28.07	peak
6	p16500.000	13.99	42.10	37.47	28.25	46.87	68.20	-21.33	peak


Test Mode: 11; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:middle



Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5580 TX RSE
Note : 5G WIFI 11A

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1189.368	3.67	24.29	38.34	39.48	29.10	74.00	-44.90	peak
2	1677.621	4.29	26.24	38.41	39.87	31.99	74.00	-42.01	peak
3	3357.061	6.40	32.14	36.12	37.53	39.95	74.00	-34.05	peak
4	4443.453	7.19	34.28	35.77	36.25	41.95	68.20	-26.25	peak
5	11160.000	11.77	37.62	37.79	33.97	45.57	74.00	-28.43	peak
6	p16740.000	14.15	42.78	37.49	28.78	48.22	68.20	-19.98	peak


Test Mode: 11; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:middle



Site : chamber
 Condition: 3m VERTICAL
 Job No : 02877MO/02103MO
 Mode : 5580 TX RSE
 Note : 5G WIFI 11A

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1274.802	3.78	24.95	38.35	38.56	28.94	68.20	-39.26	peak
2	1682.477	4.30	26.24	38.41	39.87	32.00	74.00	-42.00	peak
3	3396.098	6.43	32.38	36.12	36.49	39.18	68.20	-29.02	peak
4	4304.400	7.02	34.04	35.87	36.72	41.91	74.00	-32.09	peak
5	11160.000	11.77	37.62	37.79	33.68	45.28	74.00	-28.72	peak
6	16740.000	14.15	42.78	37.49	29.56	49.00	68.20	-19.20	peak


Test Mode: 11; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:High



Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5700 TX RSE
Note : 5G WIFI 11A

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1148.823	3.61	23.90	38.33	40.40	29.58	74.00	-44.42	peak
2	1697.129	4.32	26.21	38.41	39.69	31.81	74.00	-42.19	peak
3	3465.510	6.49	31.74	36.12	36.47	38.58	68.20	-29.62	peak
4	4430.628	7.17	34.43	35.77	36.83	42.66	68.20	-25.54	peak
5	11400.000	11.90	37.70	37.72	35.10	46.98	74.00	-27.02	peak
6	17100.000	14.44	43.10	37.53	27.88	47.89	68.20	-20.31	peak


Test Mode: 11; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:High



Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5700 TX RSE
Note : 5G WIFI 11A

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1234.909	3.73	24.89	38.35	38.93	29.20	74.00	-44.80	peak
2	1687.347	4.31	26.23	38.41	39.48	31.61	74.00	-42.39	peak
3	3435.590	6.47	31.97	36.12	36.71	39.03	68.20	-29.17	peak
4	4329.354	7.05	34.23	35.85	36.19	41.62	74.00	-32.38	peak
5	11400.000	11.90	37.70	37.72	35.12	47.00	74.00	-27.00	peak
6	17100.000	14.44	43.10	37.53	28.11	48.12	68.20	-20.08	peak


Test Mode: 11; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:Low



Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5500 TX RSE
Note : 5G WIFI 11N20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1238.483	3.73	24.94	38.35	39.30	29.62	74.00	-44.38	peak
2	1702.042	4.33	26.22	38.42	39.23	31.36	74.00	-42.64	peak
3	3475.541	6.50	31.70	36.12	37.09	39.17	68.20	-29.03	peak
4	4304.400	7.02	34.04	35.87	36.78	41.97	74.00	-32.03	peak
5	11000.000	11.68	37.50	37.84	34.28	45.62	74.00	-28.38	peak
6	p16500.000	13.99	42.10	37.47	28.04	46.66	68.20	-21.54	peak

Test Mode: 11; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5500 TX RSE
Note : 5G WIFI 11N20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1220.714	3.71	24.69	38.34	38.93	28.99	74.00	-45.01	peak
2	1682.477	4.30	26.24	38.41	39.71	31.84	74.00	-42.16	peak
3	3328.077	6.37	31.71	36.13	37.38	39.33	68.20	-28.87	peak
4	4341.886	7.07	34.34	35.84	35.98	41.55	74.00	-32.45	peak
5	11000.000	11.68	37.50	37.84	34.36	45.70	74.00	-28.30	peak
6	p16500.000	13.99	42.10	37.47	28.36	46.98	68.20	-21.22	peak




Test Mode: 11; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:middle



Site : chamber
 Condition: 3m HORIZONTAL
 Job No : 02877MO/02103MO
 Mode : 5580 TX RSE
 Note : 5G WIFI 11N20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1238.483	3.73	24.94	38.35	38.27	28.59	74.00	-45.41	peak
2	1639.274	4.24	26.41	38.41	39.47	31.71	68.20	-36.49	peak
3	3495.691	6.52	31.62	36.12	37.04	39.06	68.20	-29.14	peak
4	4443.453	7.19	34.28	35.77	36.57	42.27	68.20	-25.93	peak
5	11160.000	11.77	37.62	37.79	33.95	45.55	74.00	-28.45	peak
6	p16740.000	14.15	42.78	37.49	29.14	48.58	68.20	-19.62	peak


Test Mode: 11; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:middle



Site : chamber
 Condition: 3m VERTICAL
 Job No : 02877MO/02103MO
 Mode : 5580 TX RSE
 Note : 5G WIFI 11N20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1289.627	3.80	24.86	38.36	39.03	29.33	68.20	-38.87	peak
2	1611.091	4.20	26.69	38.40	39.59	32.08	74.00	-41.92	peak
3	3445.535	6.47	31.85	36.12	36.36	38.56	68.20	-29.64	peak
4	4304.400	7.02	34.04	35.87	36.41	41.60	74.00	-32.40	peak
5	11160.000	11.77	37.62	37.79	34.79	46.39	74.00	-27.61	peak
6	16740.000	14.15	42.78	37.49	28.98	48.42	68.20	-19.78	peak


Test Mode: 11; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:High



Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5700 TX RSE
Note : 5G WIFI 11N20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1182.513	3.66	24.23	38.34	44.32	33.87	74.00	-40.13	peak
2	1583.392	4.16	26.87	38.40	39.43	32.06	74.00	-41.94	peak
3	3445.535	6.47	31.85	36.12	36.76	38.96	68.20	-29.24	peak
4	4417.841	7.16	34.59	35.78	35.71	41.68	68.20	-26.52	peak
5	11400.000	11.90	37.70	37.72	34.88	46.76	74.00	-27.24	peak
6	17100.000	14.44	43.10	37.53	27.80	47.81	68.20	-20.39	peak

Test Mode: 11; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5700 TX RSE
Note : 5G WIFI 11N20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1227.791	3.72	24.79	38.34	38.93	29.10	74.00	-44.90	peak
2	1672.779	4.29	26.25	38.41	39.47	31.60	74.00	-42.40	peak
3	3337.710	6.38	31.88	36.13	36.79	38.92	74.00	-35.08	peak
4	4329.354	7.05	34.23	35.85	36.23	41.66	74.00	-32.34	peak
5	11400.000	11.90	37.70	37.72	34.54	46.42	74.00	-27.58	peak
6	p17100.000	14.44	43.10	37.53	27.74	47.75	68.20	-20.45	peak



Test Mode: 11; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:Low




Site : chamber
 Condition: 3m HORIZONTAL
 Job No : 02877MO/02103MO
 Mode : 5510 TX RSE
 Note : 5G WIFI 11N40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1256.512	3.76	25.06	38.35	38.92	29.39	68.20	-38.81	peak
2	1663.137	4.27	26.27	38.41	39.53	31.66	74.00	-42.34	peak
3	3337.710	6.38	31.88	36.13	37.24	39.37	74.00	-34.63	peak
4	4145.664	6.83	33.73	35.99	37.22	41.79	74.00	-32.21	peak
5	11020.000	11.69	37.50	37.83	34.24	45.60	74.00	-28.40	peak
6	16530.000	14.01	42.16	37.47	27.56	46.26	68.20	-21.94	peak




Test Mode: 11; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:Low



Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5510 TX RSE
Note : 5G WIFI 11N40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1282.193	3.79	24.91	38.35	39.32	29.67	68.20	-38.53	peak
2	1677.621	4.29	26.24	38.41	39.63	31.75	74.00	-42.25	peak
3	3376.523	6.42	32.26	36.12	36.41	38.97	68.20	-29.23	peak
4	4417.841	7.16	34.59	35.78	35.63	41.60	68.20	-26.60	peak
5	11020.000	11.69	37.50	37.83	33.89	45.25	74.00	-28.75	peak
6	p16530.000	14.01	42.16	37.47	27.99	46.69	68.20	-21.51	peak


Test Mode: 11; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:middle



Site : chamber
 Condition: 3m HORIZONTAL
 Job No : 02877MO/02103MO
 Mode : 5550 TX RSE
 Note : 5G WIFI 11N40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1168.920	3.64	24.09	38.33	40.03	29.43	74.00	-44.57	peak
2	1639.274	4.24	26.41	38.41	39.40	31.64	68.20	-36.56	peak
3	3435.590	6.47	31.97	36.12	37.34	39.66	68.20	-28.54	peak
4	4254.921	6.96	33.82	35.90	37.59	42.47	74.00	-31.53	peak
5	11100.000	11.73	37.50	37.81	35.73	47.15	74.00	-26.85	peak
6	16650.000	14.09	42.50	37.48	28.23	47.34	68.20	-20.86	peak


Test Mode: 11; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:middle



Site : chamber
 Condition: 3m VERTICAL
 Job No : 02877MO/02103MO
 Mode : 5550 TX RSE
 Note : 5G WIFI 11N40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1278.492	3.78	24.93	38.35	38.45	28.81	68.20	-39.39	peak
2	1682.477	4.30	26.24	38.41	39.70	31.83	74.00	-42.17	peak
3	3485.601	6.51	31.66	36.12	37.03	39.08	68.20	-29.12	peak
4	4430.628	7.17	34.43	35.77	36.22	42.05	68.20	-26.15	peak
5	11100.000	11.73	37.50	37.81	34.71	46.13	74.00	-27.87	peak
6	16650.000	14.09	42.50	37.48	28.04	47.15	68.20	-21.05	peak


Test Mode: 11; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:High



Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5670 TX RSE
Note : 5G WIFI 11N40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1182.513	3.66	24.23	38.34	45.25	34.80	74.00	-39.20	peak
2	1667.951	4.28	26.26	38.41	39.80	31.93	74.00	-42.07	peak
3	3435.590	6.47	31.97	36.12	37.14	39.46	68.20	-28.74	peak
4	4169.698	6.86	33.80	35.97	37.11	41.80	74.00	-32.20	peak
5	11340.000	11.86	37.76	37.74	34.18	46.06	74.00	-27.94	peak
6	17010.000	14.33	43.10	37.51	28.27	48.19	68.20	-20.01	peak

Test Mode: 11; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5670 TX RSE
Note : 5G WIFI 11N40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1271.123	3.77	24.97	38.35	39.23	29.62	68.20	-38.58	peak
2	1702.042	4.33	26.22	38.42	39.82	31.95	74.00	-42.05	peak
3	3357.061	6.40	32.14	36.12	36.65	39.07	74.00	-34.93	peak
4	4329.354	7.05	34.23	35.85	36.31	41.74	74.00	-32.26	peak
5	11340.000	11.86	37.76	37.74	34.14	46.02	74.00	-27.98	peak
6	p17010.000	14.33	43.10	37.51	28.35	48.27	68.20	-19.93	peak



Test Mode: 11; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5500 TX RSE
Note : 5G WIFI 11AC20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1182.513	3.66	24.23	38.34	44.21	33.76	74.00	-40.24	peak
2	1629.825	4.23	26.50	38.41	39.40	31.72	68.20	-36.48	peak
3	3366.778	6.41	32.20	36.12	36.43	38.92	68.20	-29.28	peak
4	4482.150	7.23	33.81	35.74	36.62	41.92	68.20	-26.28	peak
5	11000.000	11.68	37.50	37.84	33.96	45.30	74.00	-28.70	peak
6	p16500.000	13.99	42.10	37.47	27.70	46.32	68.20	-21.88	peak




Test Mode: 11; Polarity: Vertical; Modulation:802.11ac; Bandwidth:20MHz; Channel:Low



Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5500 TX RSE
Note : 5G WIFI 11AC20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1289.627	3.80	24.86	38.36	38.71	29.01	68.20	-39.19	peak
2	1658.337	4.27	26.28	38.41	39.79	31.93	68.20	-36.27	peak
3	3366.778	6.41	32.20	36.12	36.52	39.01	68.20	-29.19	peak
4	4329.354	7.05	34.23	35.85	36.17	41.60	74.00	-32.40	peak
5	11000.000	11.68	37.50	37.84	34.36	45.70	74.00	-28.30	peak
6	p16500.000	13.99	42.10	37.47	28.36	46.98	68.20	-21.22	peak


Test Mode: 11; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:20MHz; Channel:middle



Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5580 TX RSE
Note : 5G WIFI 11AC20

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1293.359	3.80	24.84	38.36	39.08	29.36	68.20	-38.84	peak
2	1677.621	4.29	26.24	38.41	39.62	31.74	74.00	-42.26	peak
3	3415.787	6.45	32.21	36.12	36.24	38.78	68.20	-29.42	peak
4	4304.400	7.02	34.04	35.87	37.25	42.44	74.00	-31.56	peak
5	11160.000	11.77	37.62	37.79	33.43	45.03	74.00	-28.97	peak
6	p16740.000	14.15	42.78	37.49	29.24	48.68	68.20	-19.52	peak


Test Mode: 11; Polarity: Vertical; Modulation:802.11ac; Bandwidth:20MHz; Channel:middle



Site : chamber
 Condition: 3m VERTICAL
 Job No : 02877MO/02103MO
 Mode : 5580 TX RSE
 Note : 5G WIFI 11AC20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1148.823	3.61	23.90	38.33	40.02	29.20	74.00	-44.80	peak
2	1644.019	4.25	26.36	38.41	39.28	31.48	68.20	-36.72	peak
3	3376.523	6.42	32.26	36.12	36.53	39.09	68.20	-29.11	peak
4	4379.699	7.11	34.64	35.81	36.19	42.13	74.00	-31.87	peak
5	11160.000	11.77	37.62	37.79	34.12	45.72	74.00	-28.28	peak
6	16740.000	14.15	42.78	37.49	28.63	48.07	68.20	-20.13	peak


Test Mode: 11; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:20MHz; Channel:High



Site : chamber
 Condition: 3m HORIZONTAL
 Job No : 02877MO/02103MO
 Mode : 5700 TX RSE
 Note : 5G WIFI 11AC20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1182.513	3.66	24.23	38.34	46.59	36.14	74.00	-37.86	peak
2	1702.042	4.33	26.22	38.42	39.52	31.65	74.00	-42.35	peak
3	3425.675	6.46	32.09	36.12	36.51	38.94	68.20	-29.26	peak
4	4456.315	7.20	34.12	35.76	36.33	41.89	68.20	-26.31	peak
5	11400.000	11.90	37.70	37.72	35.13	47.01	74.00	-26.99	peak
6	17100.000	14.44	43.10	37.53	27.19	47.20	68.20	-21.00	peak

Test Mode: 11; Polarity: Vertical; Modulation:802.11ac; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5700 TX RSE
Note : 5G WIFI 11AC20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1260.149	3.76	25.04	38.35	38.63	29.08	68.20	-39.12	peak
2	1697.129	4.32	26.21	38.41	39.73	31.85	74.00	-42.15	peak
3	3465.510	6.49	31.74	36.12	36.62	38.73	68.20	-29.47	peak
4	4316.859	7.04	34.13	35.86	36.43	41.74	74.00	-32.26	peak
5	11400.000	11.90	37.70	37.72	34.89	46.77	74.00	-27.23	peak
6	17100.000	14.44	43.10	37.53	27.34	47.35	68.20	-20.85	peak



Test Mode: 11; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:40MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5510 TX RSE
Note : 5G WIFI 11AC40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1182.513	3.66	24.23	38.34	45.96	35.51	74.00	-38.49	peak
2	1634.543	4.23	26.45	38.41	39.66	31.93	68.20	-36.27	peak
3	3485.601	6.51	31.66	36.12	36.44	38.49	68.20	-29.71	peak
4	4304.400	7.02	34.04	35.87	36.69	41.88	74.00	-32.12	peak
5	11020.000	11.69	37.50	37.83	34.26	45.62	74.00	-28.38	peak
6	p16530.000	14.01	42.16	37.47	27.74	46.44	68.20	-21.76	peak



Test Mode: 11; Polarity: Vertical; Modulation:802.11ac; Bandwidth:40MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5510 TX RSE
Note : 5G WIFI 11AC40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1109.660	3.56	23.74	38.32	40.14	29.12	74.00	-44.88	peak
2	1644.019	4.25	26.36	38.41	39.89	32.09	68.20	-36.11	peak
3	3445.535	6.47	31.85	36.12	37.01	39.21	68.20	-28.99	peak
4	4430.628	7.17	34.43	35.77	36.53	42.36	68.20	-25.84	peak
5	11020.000	11.69	37.50	37.83	34.09	45.45	74.00	-28.55	peak
6	p16530.000	14.01	42.16	37.47	27.28	45.98	68.20	-22.22	peak




Test Mode: 11; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:40MHz; Channel:middle



Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5550 TX RSE
Note : 5G WIFI 11AC40

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1182.513	3.66	24.23	38.34	46.14	35.69	74.00	-38.31	peak
2	1697.129	4.32	26.21	38.41	39.61	31.73	74.00	-42.27	peak
3	3455.508	6.48	31.78	36.12	36.63	38.77	68.20	-29.43	peak
4	4482.150	7.23	33.81	35.74	36.97	42.27	68.20	-25.93	peak
5	11100.000	11.73	37.50	37.81	35.09	46.51	74.00	-27.49	peak
6	p16650.000	14.09	42.50	37.48	28.50	47.61	68.20	-20.59	peak


Test Mode: 11; Polarity: Vertical; Modulation:802.11ac; Bandwidth:40MHz; Channel:middle



Site : chamber
 Condition: 3m VERTICAL
 Job No : 02877MO/02103MO
 Mode : 5550 TX RSE
 Note : 5G WIFI 11AC40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1238.483	3.73	24.94	38.35	38.80	29.12	74.00	-44.88	peak
2	1697.129	4.32	26.21	38.41	39.72	31.84	74.00	-42.16	peak
3	3415.787	6.45	32.21	36.12	36.53	39.07	68.20	-29.13	peak
4	4329.354	7.05	34.23	35.85	36.47	41.90	74.00	-32.10	peak
5	11100.000	11.73	37.50	37.81	34.34	45.76	74.00	-28.24	peak
6	16650.000	14.09	42.50	37.48	27.76	46.87	68.20	-21.33	peak


Test Mode: 11; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:40MHz; Channel:High



Site : chamber
 Condition: 3m HORIZONTAL
 Job No : 02877MO/02103MO
 Mode : 5670 TX RSE
 Note : 5G WIFI 11AC40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1182.513	3.66	24.23	38.34	46.64	36.19	74.00	-37.81	peak
2	1672.779	4.29	26.25	38.41	39.34	31.47	74.00	-42.53	peak
3	3465.510	6.49	31.74	36.12	36.58	38.69	68.20	-29.51	peak
4	4354.454	7.08	34.44	35.83	36.38	42.07	74.00	-31.93	peak
5	11340.000	11.86	37.76	37.74	34.86	46.74	74.00	-27.26	peak
6	17010.000	14.33	43.10	37.51	28.35	48.27	68.20	-19.93	peak

Test Mode: 11; Polarity: Vertical; Modulation:802.11ac; Bandwidth:40MHz; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5670 TX RSE
Note : 5G WIFI 11AC40

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1293.359	3.80	24.84	38.36	39.29	29.57	68.20	-38.63	peak
2	1606.441	4.19	26.74	38.40	39.63	32.16	74.00	-41.84	peak
3	3455.508	6.48	31.78	36.12	36.43	38.57	68.20	-29.63	peak
4	4181.768	6.88	33.80	35.96	37.04	41.76	74.00	-32.24	peak
5	11340.000	11.86	37.76	37.74	34.06	45.94	74.00	-28.06	peak
6	p17010.000	14.33	43.10	37.51	27.54	47.46	68.20	-20.74	peak



Test Mode: 11; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:80MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5530 TX RSE
Note : 5G WIFI 11AC80

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1182.513	3.66	24.23	38.34	46.39	35.94	74.00	-38.06	peak
2	1629.825	4.23	26.50	38.41	39.90	32.22	68.20	-35.98	peak
3	3376.523	6.42	32.26	36.12	35.96	38.52	68.20	-29.68	peak
4	4291.977	7.01	33.97	35.88	36.74	41.84	74.00	-32.16	peak
5	11060.000	11.71	37.50	37.82	34.58	45.97	74.00	-28.03	peak
6	p16590.000	14.05	42.28	37.47	29.39	48.25	68.20	-19.95	peak




Test Mode: 11; Polarity: Vertical; Modulation:802.11ac; Bandwidth:80MHz; Channel:Low



Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5530 TX RSE
Note : 5G WIFI 11AC80

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1263.796	3.77	25.02	38.35	38.82	29.26	68.20	-38.94	peak
2	1648.778	4.25	26.31	38.41	39.51	31.66	68.20	-36.54	peak
3	3366.778	6.41	32.20	36.12	36.37	38.86	68.20	-29.34	peak
4	4304.400	7.02	34.04	35.87	37.30	42.49	74.00	-31.51	peak
5	11060.000	11.71	37.50	37.82	35.77	47.16	74.00	-26.84	peak
6	p16590.000	14.05	42.28	37.47	28.45	47.31	68.20	-20.89	peak


Test Mode: 11; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:80MHz; Channel:High



Site : chamber
 Condition: 3m HORIZONTAL
 Job No : 02877MO/02103MO
 Mode : 5610 TX RSE
 Note : 5G WIFI 11AC80

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1168.920	3.64	24.09	38.33	39.62	29.02	74.00	-44.98	peak
2	1653.550	4.26	26.29	38.41	39.44	31.58	68.20	-36.62	peak
3	3465.510	6.49	31.74	36.12	36.43	38.54	68.20	-29.66	peak
4	4341.886	7.07	34.34	35.84	36.14	41.71	74.00	-32.29	peak
5	11220.000	11.80	37.72	37.77	33.95	45.70	74.00	-28.30	peak
6	p16830.000	14.21	42.99	37.50	28.97	48.67	68.20	-19.53	peak

Test Mode: 11; Polarity: Vertical; Modulation:802.11ac; Bandwidth:80MHz; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5610 TX RSE
Note : 5G WIFI 11AC80

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1203.199	3.69	24.44	38.34	39.41	29.20	74.00	-44.80	peak
2	1692.231	4.31	26.22	38.41	39.85	31.97	74.00	-42.03	peak
3	3396.098	6.43	32.38	36.12	36.49	39.18	68.20	-29.02	peak
4	4316.859	7.04	34.13	35.86	36.76	42.07	74.00	-31.93	peak
5	11220.000	11.80	37.72	37.77	34.70	46.45	74.00	-27.55	peak
6	p16830.000	14.21	42.99	37.50	28.36	48.06	68.20	-20.14	peak



Test Mode: 12; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5745 TX RSE
Note : 5G WIFI 11A

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1203.199	3.69	24.44	38.34	39.46	29.25	74.00	-44.75	peak
2	1687.347	4.31	26.23	38.41	39.83	31.96	74.00	-42.04	peak
3	3415.787	6.45	32.21	36.12	36.67	39.21	68.20	-28.99	peak
4	4254.921	6.96	33.82	35.90	37.00	41.88	74.00	-32.12	peak
5	11490.000	11.94	37.79	37.69	31.44	43.48	74.00	-30.52	peak
6	p17235.000	14.59	43.03	37.55	28.42	48.49	68.20	-19.71	peak




Test Mode: 12; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:Low



Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5745 TX RSE
Note : 5G WIFI 11A

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1282.193	3.79	24.91	38.35	39.19	29.54	68.20	-38.66	peak
2	1663.137	4.27	26.27	38.41	39.36	31.49	74.00	-42.51	peak
3	3465.510	6.49	31.74	36.12	36.90	39.01	68.20	-29.19	peak
4	4316.859	7.04	34.13	35.86	37.39	42.70	74.00	-31.30	peak
5	11490.000	11.94	37.79	37.69	31.96	44.00	74.00	-30.00	peak
6	p17235.000	14.59	43.03	37.55	27.47	47.54	68.20	-20.66	peak


Test Mode: 12; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:middle



Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5785 TX RSE
Note : 5G WIFI 11A

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1231.345	3.72	24.84	38.35	38.98	29.19	74.00	-44.81	peak
2	1702.042	4.33	26.22	38.42	39.81	31.94	74.00	-42.06	peak
3	3386.297	6.42	32.32	36.12	36.37	38.99	68.20	-29.21	peak
4	4367.058	7.10	34.54	35.82	35.89	41.71	74.00	-32.29	peak
5	11570.000	11.95	37.73	37.67	32.40	44.41	74.00	-29.59	peak
6	p17355.000	14.73	43.26	37.56	28.89	49.32	68.20	-18.88	peak


Test Mode: 12; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:middle



Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5785 TX RSE
Note : 5G WIFI 11A

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1182.513	3.66	24.23	38.34	45.87	35.42	74.00	-38.58	peak
2	1634.543	4.23	26.45	38.41	39.36	31.63	68.20	-36.57	peak
3	3445.535	6.47	31.85	36.12	36.55	38.75	68.20	-29.45	peak
4	4316.859	7.04	34.13	35.86	37.39	42.70	74.00	-31.30	peak
5	11570.000	11.95	37.73	37.67	31.47	43.48	74.00	-30.52	peak
6	p17355.000	14.73	43.26	37.56	28.26	48.69	68.20	-19.51	peak

Test Mode: 12; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5825 TX RSE
Note : 5G WIFI 11A

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1179.100	3.65	24.19	38.34	39.40	28.90	74.00	-45.10	peak
2	1639.274	4.24	26.41	38.41	40.01	32.25	68.20	-35.95	peak
3	3485.601	6.51	31.66	36.12	36.90	38.95	68.20	-29.25	peak
4	4242.641	6.95	33.80	35.91	37.07	41.91	74.00	-32.09	peak
5	11650.000	11.95	37.80	37.65	31.68	43.78	74.00	-30.22	peak
6	p17475.000	14.86	43.40	37.58	27.10	47.78	68.20	-20.42	peak



Test Mode: 12; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5825 TX RSE
Note : 5G WIFI 11A

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1199.726	3.68	24.40	38.34	39.32	29.06	74.00	-44.94	peak
2	1687.347	4.31	26.23	38.41	39.16	31.29	74.00	-42.71	peak
3	3366.778	6.41	32.20	36.12	36.29	38.78	68.20	-29.42	peak
4	4218.186	6.92	33.80	35.93	37.13	41.92	74.00	-32.08	peak
5	11650.000	11.95	37.80	37.65	31.80	43.90	74.00	-30.10	peak
6	17475.000	14.86	43.40	37.58	27.09	47.77	68.20	-20.43	peak




Test Mode: 12; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:Low



Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5745 TX RSE
Note : 5G WIFI 11N20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1278.492	3.78	24.93	38.35	38.68	29.04	68.20	-39.16	peak
2	1682.477	4.30	26.24	38.41	40.13	32.26	74.00	-41.74	peak
3	3386.297	6.42	32.32	36.12	36.22	38.84	68.20	-29.36	peak
4	4495.125	7.24	33.66	35.73	36.45	41.62	68.20	-26.58	peak
5	11490.000	11.94	37.79	37.69	32.31	44.35	74.00	-29.65	peak
6	p17235.000	14.59	43.03	37.55	27.89	47.96	68.20	-20.24	peak


Test Mode: 12; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:Low



Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5745 TX RSE
Note : 5G WIFI 11N20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1152.148	3.62	23.92	38.33	39.74	28.95	74.00	-45.05	peak
2	1629.825	4.23	26.50	38.41	39.47	31.79	68.20	-36.41	peak
3	3465.510	6.49	31.74	36.12	36.64	38.75	68.20	-29.45	peak
4	4354.454	7.08	34.44	35.83	35.89	41.58	74.00	-32.42	peak
5	11490.000	11.94	37.79	37.69	31.64	43.68	74.00	-30.32	peak
6	p17235.000	14.59	43.03	37.55	27.91	47.98	68.20	-20.22	peak

Test Mode: 12; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:middle




Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5785 TX RSE
Note : 5G WIFI 11N20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1168.920	3.64	24.09	38.33	39.69	29.09	74.00	-44.91	peak
2	1702.042	4.33	26.22	38.42	39.77	31.90	74.00	-42.10	peak
3	3495.691	6.52	31.62	36.12	36.65	38.67	68.20	-29.53	peak
4	4291.977	7.01	33.97	35.88	36.34	41.44	74.00	-32.56	peak
5	11570.000	11.95	37.73	37.67	32.20	44.21	74.00	-29.79	peak
6	p17355.000	14.73	43.26	37.56	27.73	48.16	68.20	-20.04	peak




Test Mode: 12; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:middle



Site : chamber
 Condition: 3m VERTICAL
 Job No : 02877MO/02103MO
 Mode : 5785 TX RSE
 Note : 5G WIFI 11N20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1242.068	3.74	24.99	38.35	38.84	29.22	68.20	-38.98	peak
2	1687.347	4.31	26.23	38.41	39.24	31.37	74.00	-42.63	peak
3	3465.510	6.49	31.74	36.12	36.96	39.07	68.20	-29.13	peak
4	4469.214	7.22	33.97	35.75	36.55	41.99	68.20	-26.21	peak
5	11570.000	11.95	37.73	37.67	31.67	43.68	74.00	-30.32	peak
6	17355.000	14.73	43.26	37.56	28.15	48.58	68.20	-19.62	peak

Test Mode: 12; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5825 TX RSE
Note : 5G WIFI 11N20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1231.345	3.72	24.84	38.35	39.13	29.34	74.00	-44.66	peak
2	1639.274	4.24	26.41	38.41	39.05	31.29	68.20	-36.91	peak
3	3445.535	6.47	31.85	36.12	36.68	38.88	68.20	-29.32	peak
4	4304.400	7.02	34.04	35.87	36.42	41.61	74.00	-32.39	peak
5	11650.000	11.95	37.80	37.65	32.18	44.28	74.00	-29.72	peak
6	p17475.000	14.86	43.40	37.58	27.30	47.98	68.20	-20.22	peak




Test Mode: 12; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:High



Site : chamber
 Condition: 3m VERTICAL
 Job No : 02877MO/02103MO
 Mode : 5825 TX RSE
 Note : 5G WIFI 11N20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1274.802	3.78	24.95	38.35	38.45	28.83	68.20	-39.37	peak
2	1601.804	4.19	26.78	38.40	39.57	32.14	74.00	-41.86	peak
3	3435.590	6.47	31.97	36.12	36.40	38.72	68.20	-29.48	peak
4	4443.453	7.19	34.28	35.77	36.38	42.08	68.20	-26.12	peak
5	11650.000	11.95	37.80	37.65	31.97	44.07	74.00	-29.93	peak
6	17475.000	14.86	43.40	37.58	27.58	48.26	68.20	-19.94	peak


Test Mode: 12; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:Low



Site : chamber
 Condition: 3m HORIZONTAL
 Job No : 02877MO/02103MO
 Mode : 5755 TX RSE
 Note : 5G WIFI 11N40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1260.149	3.76	25.04	38.35	38.64	29.09	68.20	-39.11	peak
2	1682.477	4.30	26.24	38.41	39.89	32.02	74.00	-41.98	peak
3	3435.590	6.47	31.97	36.12	36.84	39.16	68.20	-29.04	peak
4	4329.354	7.05	34.23	35.85	36.43	41.86	74.00	-32.14	peak
5	11510.000	11.95	37.79	37.69	31.78	43.83	74.00	-30.17	peak
6	17265.000	14.62	43.06	37.55	27.52	47.65	68.20	-20.55	peak

Test Mode: 12; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5755 TX RSE
Note : 5G WIFI 11N40

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1260.149	3.76	25.04	38.35	38.82	29.27	68.20	-38.93	peak
2	1648.778	4.25	26.31	38.41	39.62	31.77	68.20	-36.43	peak
3	3445.535	6.47	31.85	36.12	36.83	39.03	68.20	-29.17	peak
4	4482.150	7.23	33.81	35.74	36.29	41.59	68.20	-26.61	peak
5	11510.000	11.95	37.79	37.69	31.68	43.73	74.00	-30.27	peak
6	p17265.000	14.62	43.06	37.55	27.63	47.76	68.20	-20.44	peak




Test Mode: 12; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:High



Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5795 TX RSE
Note : 5G WIFI 11N40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1282.193	3.79	24.91	38.35	38.34	28.69	68.20	-39.51	peak
2	1615.754	4.21	26.64	38.40	39.37	31.82	74.00	-42.18	peak
3	3495.691	6.52	31.62	36.12	36.64	38.66	68.20	-29.54	peak
4	4367.058	7.10	34.54	35.82	35.89	41.71	74.00	-32.29	peak
5	11590.000	11.95	37.71	37.67	32.17	44.16	74.00	-29.84	peak
6	p17385.000	14.76	43.35	37.57	27.65	48.19	68.20	-20.01	peak


Test Mode: 12; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:High



Site : chamber
 Condition: 3m VERTICAL
 Job No : 02877MO/02103MO
 Mode : 5795 TX RSE
 Note : 5G WIFI 11N40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1274.802	3.78	24.95	38.35	38.90	29.28	68.20	-38.92	peak
2	1677.621	4.29	26.24	38.41	39.89	32.01	74.00	-41.99	peak
3	3455.508	6.48	31.78	36.12	36.71	38.85	68.20	-29.35	peak
4	4354.454	7.08	34.44	35.83	36.39	42.08	74.00	-31.92	peak
5	11590.000	11.95	37.71	37.67	31.79	43.78	74.00	-30.22	peak
6	17385.000	14.76	43.35	37.57	27.96	48.50	68.20	-19.70	peak


Test Mode: 12; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:20MHz; Channel:Low



Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5745 TX RSE
Note : 5G WIFI 11AC20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1182.513	3.66	24.23	38.34	41.71	31.26	74.00	-42.74	peak
2	1644.019	4.25	26.36	38.41	39.42	31.62	68.20	-36.58	peak
3	3465.510	6.49	31.74	36.12	36.99	39.10	68.20	-29.10	peak
4	4267.237	6.98	33.87	35.89	36.75	41.71	74.00	-32.29	peak
5	11490.000	11.94	37.79	37.69	32.20	44.24	74.00	-29.76	peak
6	p17235.000	14.59	43.03	37.55	27.84	47.91	68.20	-20.29	peak

Test Mode: 12; Polarity: Vertical; Modulation:802.11ac; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5745 TX RSE
Note : 5G WIFI 11AC20

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1182.513	3.66	24.23	38.34	45.73	35.28	74.00	-38.72	peak
2	1702.042	4.33	26.22	38.42	39.17	31.30	74.00	-42.70	peak
3	3435.590	6.47	31.97	36.12	36.87	39.19	68.20	-29.01	peak
4	4157.664	6.85	33.80	35.98	37.00	41.67	74.00	-32.33	peak
5	11490.000	11.94	37.79	37.69	31.41	43.45	74.00	-30.55	peak
6	p17235.000	14.59	43.03	37.55	27.63	47.70	68.20	-20.50	peak



Test Mode: 12; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:20MHz; Channel:middle




Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5785 TX RSE
Note : 5G WIFI 11AC20

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1271.123	3.77	24.97	38.35	38.37	28.76	68.20	-39.44	peak
2	1667.951	4.28	26.26	38.41	39.84	31.97	74.00	-42.03	peak
3	3485.601	6.51	31.66	36.12	37.65	39.70	68.20	-28.50	peak
4	4316.859	7.04	34.13	35.86	36.69	42.00	74.00	-32.00	peak
5	11570.000	11.95	37.73	37.67	32.33	44.34	74.00	-29.66	peak
6	p17355.000	14.73	43.26	37.56	27.84	48.27	68.20	-19.93	peak



Test Mode: 12; Polarity: Vertical; Modulation:802.11ac; Bandwidth:20MHz; Channel:middle




Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5785 TX RSE
Note : 5G WIFI 11AC20

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1172.303	3.64	24.12	38.33	39.99	29.42	74.00	-44.58	peak
2	1702.042	4.33	26.22	38.42	39.30	31.43	74.00	-42.57	peak
3	3347.371	6.39	32.05	36.12	36.37	38.69	74.00	-35.31	peak
4	4304.400	7.02	34.04	35.87	36.58	41.77	74.00	-32.23	peak
5	11570.000	11.95	37.73	37.67	31.80	43.81	74.00	-30.19	peak
6	p17355.000	14.73	43.26	37.56	27.92	48.35	68.20	-19.85	peak




Test Mode: 12; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:20MHz; Channel:High



Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5825 TX RSE
Note : 5G WIFI 11AC20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1260.149	3.76	25.04	38.35	38.51	28.96	68.20	-39.24	peak
2	1687.347	4.31	26.23	38.41	39.36	31.49	74.00	-42.51	peak
3	3425.675	6.46	32.09	36.12	36.14	38.57	68.20	-29.63	peak
4	4341.886	7.07	34.34	35.84	36.15	41.72	74.00	-32.28	peak
5	11650.000	11.95	37.80	37.65	31.60	43.70	74.00	-30.30	peak
6	p17475.000	14.86	43.40	37.58	27.83	48.51	68.20	-19.69	peak

Test Mode: 12; Polarity: Vertical; Modulation:802.11ac; Bandwidth:20MHz; Channel:High



Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5825 TX RSE
Note : 5G WIFI 11AC20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1245.663	3.74	25.04	38.35	38.53	28.96	68.20	-39.24	peak
2	1639.274	4.24	26.41	38.41	39.37	31.61	68.20	-36.59	peak
3	3415.787	6.45	32.21	36.12	36.40	38.94	68.20	-29.26	peak
4	4329.354	7.05	34.23	35.85	36.71	42.14	74.00	-31.86	peak
5	11650.000	11.95	37.80	37.65	31.67	43.77	74.00	-30.23	peak
6	p17475.000	14.86	43.40	37.58	27.81	48.49	68.20	-19.71	peak




SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR240600210304

Page: 141 of 426

Test Mode: 12; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:40MHz; Channel:Low



Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5755 TX RSE
Note : 5G WIFI 11AC40


	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1300.858	3.81	24.79	38.36	39.29	29.53	74.00	-44.47	peak
2	1702.042	4.33	26.22	38.42	40.04	32.17	74.00	-41.83	peak
3	3495.691	6.52	31.62	36.12	36.60	38.62	68.20	-29.58	peak
4	4379.699	7.11	34.64	35.81	35.99	41.93	74.00	-32.07	peak
5	11510.000	11.95	37.79	37.69	32.05	44.10	74.00	-29.90	peak
6	p17265.000	14.62	43.06	37.55	27.41	47.54	68.20	-20.66	peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com
 No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com


Test Mode: 12; Polarity: Vertical; Modulation:802.11ac; Bandwidth:40MHz; Channel:Low



Site : chamber
 Condition: 3m VERTICAL
 Job No : 02877MO/02103MO
 Mode : 5755 TX RSE
 Note : 5G WIFI 11AC40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1260.149	3.76	25.04	38.35	38.00	28.45	68.20	-39.75	peak
2	1702.042	4.33	26.22	38.42	39.50	31.63	74.00	-42.37	peak
3	3386.297	6.42	32.32	36.12	36.65	39.27	68.20	-28.93	peak
4	4354.454	7.08	34.44	35.83	36.18	41.87	74.00	-32.13	peak
5	11510.000	11.95	37.79	37.69	32.14	44.19	74.00	-29.81	peak
6	p17265.000	14.62	43.06	37.55	27.98	48.11	68.20	-20.09	peak

Test Mode: 12; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:40MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5795 TX RSE
Note : 5G WIFI 11AC40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1282.193	3.79	24.91	38.35	38.68	29.03	68.20	-39.17	peak
2	1697.129	4.32	26.21	38.41	40.01	32.13	74.00	-41.87	peak
3	3495.691	6.52	31.62	36.12	37.75	39.77	68.20	-28.43	peak
4	4193.872	6.89	33.80	35.95	36.93	41.67	74.00	-32.33	peak
5	11590.000	11.95	37.71	37.67	31.28	43.27	74.00	-30.73	peak
6	p17385.000	14.76	43.35	37.57	29.10	49.64	68.20	-18.56	peak




Test Mode: 12; Polarity: Vertical; Modulation:802.11ac; Bandwidth:40MHz; Channel:High



Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5795 TX RSE
Note : 5G WIFI 11AC40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1289.627	3.80	24.86	38.36	39.43	29.73	68.20	-38.47	peak
2	1677.621	4.29	26.24	38.41	39.32	31.44	74.00	-42.56	peak
3	3223.928	6.28	32.52	36.13	36.11	38.78	68.20	-29.42	peak
4	4430.628	7.17	34.43	35.77	35.97	41.80	68.20	-26.40	peak
5	11590.000	11.95	37.71	37.67	31.25	43.24	74.00	-30.76	peak
6	p17385.000	14.76	43.35	37.57	27.92	48.46	68.20	-19.74	peak


Test Mode: 12; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:80MHz; Channel:middle



Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5775 TX RSE
Note : 5G WIFI 11AC80

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1138.904	3.60	23.86	38.33	39.94	29.07	74.00	-44.93	peak
2	1697.129	4.32	26.21	38.41	39.33	31.45	74.00	-42.55	peak
3	3357.061	6.40	32.14	36.12	36.40	38.82	74.00	-35.18	peak
4	4341.886	7.07	34.34	35.84	36.04	41.61	74.00	-32.39	peak
5	11550.000	11.95	37.75	37.68	32.34	44.36	74.00	-29.64	peak
6	p17325.000	14.69	43.17	37.56	28.80	49.10	68.20	-19.10	peak

Test Mode: 12; Polarity: Vertical; Modulation:802.11ac; Bandwidth:80MHz; Channel:middle



Site : chamber
 Condition: 3m VERTICAL
 Job No : 02877MO/02103MO
 Mode : 5775 TX RSE
 Note : 5G WIFI 11AC80

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1227.791	3.72	24.79	38.34	38.66	28.83	74.00	-45.17	peak
2	1592.571	4.18	26.83	38.40	39.00	31.61	74.00	-42.39	peak
3	3445.535	6.47	31.85	36.12	36.58	38.78	68.20	-29.42	peak
4	4316.859	7.04	34.13	35.86	36.57	41.88	74.00	-32.12	peak
5	11550.000	11.95	37.75	37.68	31.68	43.70	74.00	-30.30	peak
6	p17325.000	14.69	43.17	37.56	28.43	48.73	68.20	-19.47	peak

7.5 Radiated Emissions which fall in the restricted bands

Test Requirement 47 CFR Part 15, Subpart C 15.209 & Subpart E 15.407(b)

Test Method: KDB 789033 D02 II G

Measurement Distance: 3m

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

*(1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

(2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

(3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

(4) For transmitters operating in the 5.725-5.85 GHz band:

(i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

7.5.1 E.U.T. Operation

Operating Environment:

Temperature: 23.3 °C

Humidity: 54.9 % RH

Atmospheric Pressure: 1020 mbar



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

7.5.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	09	TX mode (U-NII-1) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n/ac 20/40/80, Only the data of worst case is recorded in the report.
Final test	10	TX mode (U-NII-2A) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n/ac 20/40/80, Only the data of worst case is recorded in the report.
Final test	11	TX mode (U-NII-2C) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n/ac 20/40/80, Only the data of worst case is recorded in the report.
Final test	12	TX mode (U-NII-3) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n/ac 20/40/80, Only the data of worst case is recorded in the report.


7.5.3 Test Setup Diagram



7.5.4 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
 - b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
 - c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
 - d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
 - e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
 - f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
 - g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
 - h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
 - i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
 - j. Repeat above procedures until all frequencies measured was complete.
- Remark: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor

Test Mode: 09; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:Low



Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5180 Band edge
: 5G WIFI 11A


		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5119.050	18.79	33.96	35.33	43.22	60.64	74.00	-13.36	peak
2	5149.980	18.83	33.90	35.31	41.70	59.12	74.00	-14.88	peak
3 p	5180.000	18.88	33.96	35.29	93.76	111.31	68.20	43.11	peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Test Mode: 09; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5180 Band edge
: 5G WIFI 11A

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 q 5149.357	18.83	33.90	35.31	31.53	48.95	54.00	-5.05	Average
2 5149.980	18.83	33.90	35.31	31.11	48.53	54.00	-5.47	Average
3 5180.000	18.88	33.96	35.29	85.01	102.56	-----	-----	Average




Test Mode: 09; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:Low



Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5180 Band edge
: 5G WIFI 11A

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5103.963	18.77	33.99	35.33	43.08	60.51	74.00	-13.49	Peak
2	5149.980	18.83	33.90	35.31	41.86	59.28	74.00	-14.72	Peak
3 p	5180.000	18.88	33.96	35.29	80.62	98.17	68.20	29.97	Peak

Test Mode: 09; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:Low



Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5180 Band edge
: 5G WIFI 11A


		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 q 5123.724	18.80	33.95	35.32	31.10	48.53	54.00	-5.47	Average
2 5149.980	18.83	33.90	35.31	30.72	48.14	54.00	-5.86	Average
3 5180.000	18.88	33.96	35.29	71.64	89.19	-----	-----	Average



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


Test Mode: 09; Polarity: Horizontal; Modulation: 802.11a; Bandwidth: 20MHz; Channel: High



Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5240 Band edge
: 5G WIFI 11A

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 p	5240.000	18.96	34.08	35.26	93.80	111.58	68.20	43.38 peak
2	5350.020	19.11	34.40	35.21	42.19	60.49	74.00	-13.51 peak
3	5354.754	19.12	34.42	35.21	42.72	61.05	74.00	-12.95 peak

Test Mode: 09; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5240 Band edge
: 5G WIFI 11A

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 5240.000	18.96	34.08	35.26	85.40	103.18	-----	-----	Average
2 5350.020	19.11	34.40	35.21	30.51	48.81	54.00	-5.19	Average
3 q 5350.362	19.11	34.40	35.21	30.88	49.18	54.00	-4.82	Average




Test Mode: 09; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:High



Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5240 Band edge
: 5G WIFI 11A

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 p	5240.000	18.96	34.08	35.26	81.74	99.52	68.20	31.32 Peak
2	5350.020	19.11	34.40	35.21	42.22	60.52	74.00	-13.48 Peak
3	5355.321	19.12	34.42	35.21	43.06	61.39	74.00	-12.61 Peak


Test Mode: 09; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:High



Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5240 Band edge
: 5G WIFI 11A

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5240.000	18.96	34.08	35.26	73.01	90.79	-----	----- Average
2	5350.020	19.11	34.40	35.21	30.69	48.99	54.00	-5.01 Average
3 q	5355.179	19.12	34.42	35.21	30.73	49.06	54.00	-4.94 Average

Test Mode: 09; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5180 Band edge
: 5G WIFI 11AC20

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5119.547	18.79	33.96	35.33	43.69	61.11	74.00	-12.89	peak
2	5149.980	18.83	33.90	35.31	41.86	59.28	74.00	-14.72	peak
3 p	5180.000	18.88	33.96	35.29	91.13	108.68	68.20	40.48	peak



Test Mode: 09; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5180 Band edge
: 5G WIFI 11AC20

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 q 5143.960	18.83	33.91	35.31	31.47	48.90	54.00	-5.10	Average
2 5149.980	18.83	33.90	35.31	30.88	48.30	54.00	-5.70	Average
3 5180.000	18.88	33.96	35.29	82.41	99.96	-----	-----	Average




Test Mode: 09; Polarity: Vertical; Modulation:802.11ac; Bandwidth:20MHz; Channel:Low



Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5180 Band edge
: 5G WIFI 11AC20

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5125.117	18.80	33.95	35.32	43.71	61.14	74.00	-12.86	Peak
2	5149.980	18.83	33.90	35.31	42.33	59.75	74.00	-14.25	Peak
3 p	5180.000	18.88	33.96	35.29	82.27	99.82	68.20	31.62	Peak

Test Mode: 09; Polarity: Vertical; Modulation:802.11ac; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5180 Band edge
: 5G WIFI 11AC20

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 q 5100.099	18.76	34.00	35.34	31.20	48.62	54.00	-5.38	Average
2 5149.980	18.83	33.90	35.31	30.72	48.14	54.00	-5.86	Average
3 5180.000	18.88	33.96	35.29	68.84	86.39	-----	-----	Average




Test Mode: 09; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:20MHz; Channel:High



Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5240 Band edge
: 5G WIFI 11AC20

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 p	5240.000	18.96	34.08	35.26	91.64	109.42	68.20	41.22 peak
2	5350.020	19.11	34.40	35.21	41.43	59.73	74.00	-14.27 peak
3	5351.778	19.11	34.41	35.21	42.69	61.00	74.00	-13.00 peak

Test Mode: 09; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:20MHz; Channel:High



Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5240 Band edge
: 5G WIFI 11AC20

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 5240.000	18.96	34.08	35.26	82.88	100.66	-----	-----	Average
2 5350.020	19.11	34.40	35.21	30.44	48.74	54.00	-5.26	Average
3 q 5353.053	19.11	34.41	35.21	30.89	49.20	54.00	-4.80	Average


SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR240600210304

Page: 164 of 426


Test Mode: 09; Polarity: Vertical; Modulation:802.11ac; Bandwidth:20MHz; Channel:High



Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5240 Band edge
: 5G WIFI 11AC20

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 p	5240.000	18.96	34.08	35.26	85.36	103.14	68.20	34.94 Peak
2	5350.020	19.11	34.40	35.21	41.99	60.29	74.00	-13.71 Peak
3	5350.787	19.11	34.40	35.21	43.34	61.64	74.00	-12.36 Peak

Test Mode: 09; Polarity: Vertical; Modulation:802.11ac; Bandwidth:20MHz; Channel:High



Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5240 Band edge
: 5G WIFI 11AC20


		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5240.000	18.96	34.08	35.26	70.28	88.06	-----	----- Average
2	5350.020	19.11	34.40	35.21	30.64	48.94	54.00	-5.06 Average
3 q	5356.738	19.12	34.43	35.20	30.76	49.11	54.00	-4.89 Average



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


Test Mode: 09; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:40MHz; Channel:Low



Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5190 Band edge
: 5G WIFI 11AC40

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5147.426	18.83	33.91	35.31	46.65	64.08	74.00	-9.92 peak
2	5149.980	18.83	33.90	35.31	45.77	63.19	74.00	-10.81 peak
3 p	5190.000	18.89	33.98	35.29	88.57	106.15	68.20	37.95 peak

Test Mode: 09; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:40MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5190 Band edge
: 5G WIFI 11AC40

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5149.222	18.83	33.90	35.31	34.78	52.20	54.00	-1.80 Average
2 q	5149.980	18.83	33.90	35.31	35.20	52.62	54.00	-1.38 Average
3	5190.000	18.89	33.98	35.29	79.44	97.02	-----	----- Average




Test Mode: 09; Polarity: Vertical; Modulation:802.11ac; Bandwidth:40MHz; Channel:Low



Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5190 Band edge
: 5G WIFI 11AC40

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5110.330	18.78	33.98	35.33	43.86	61.29	74.00	-12.71 Peak
2	5149.980	18.83	33.90	35.31	42.33	59.75	74.00	-14.25 Peak
3 p	5190.000	18.89	33.98	35.29	75.73	93.31	68.20	25.11 Peak

Test Mode: 09; Polarity: Vertical; Modulation:802.11ac; Bandwidth:40MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5190 Band edge
: 5G WIFI 11AC40

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 q 5114.729	18.78	33.97	35.33	31.07	48.49	54.00	-5.51	Average
2 5149.980	18.83	33.90	35.31	30.95	48.37	54.00	-5.63	Average
3 5190.000	18.89	33.98	35.29	67.64	85.22	-----	-----	Average




Test Mode: 09; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:40MHz; Channel:High



Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5230 Band edge
: 5G WIFI 11AC40

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 p	5230.000	18.95	34.06	35.27	89.55	107.29	68.20	39.09	peak
2	5350.020	19.11	34.40	35.21	41.65	59.95	74.00	-14.05	peak
3	5351.235	19.11	34.40	35.21	42.55	60.85	74.00	-13.15	peak

Test Mode: 09; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:40MHz; Channel:High



Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5230 Band edge
: 5G WIFI 11AC40


		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5230.000	18.95	34.06	35.27	80.11	97.85	-----	----- Average
2	5350.020	19.11	34.40	35.21	30.68	48.98	54.00	-5.02 Average
3 q	5353.993	19.12	34.42	35.21	30.74	49.07	54.00	-4.93 Average



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Test Mode: 09; Polarity: Vertical; Modulation:802.11ac; Bandwidth:40MHz; Channel:High



Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5230 Band edge
: 5G WIFI 11AC40


		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 p	5230.000	18.95	34.06	35.27	76.35	94.09	68.20	25.89 Peak
2	5350.020	19.11	34.40	35.21	41.49	59.79	74.00	-14.21 Peak
3	5357.889	19.12	34.43	35.20	42.52	60.87	74.00	-13.13 Peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Test Mode: 09; Polarity: Vertical; Modulation:802.11ac; Bandwidth:40MHz; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5230 Band edge
: 5G WIFI 11AC40

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5230.000	18.95	34.06	35.27	67.84	85.58	-----	----- Average
2	5350.020	19.11	34.40	35.21	30.70	49.00	54.00	-5.00 Average
3 q	5360.000	19.12	34.44	35.20	30.82	49.18	54.00	-4.82 Average




Test Mode: 09; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:80MHz; Channel:middle



Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5210 Band edge
: 5G WIFI 11AC80

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
5144.316	18.83	33.91	35.31	45.14	62.57	74.00	-11.43	peak
5210.000	18.92	34.02	35.28	82.65	100.31	68.20	32.11	peak
5351.212	19.11	34.40	35.21	42.87	61.17	74.00	-12.83	peak


Test Mode: 09; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:80MHz; Channel:middle



Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5210 Band edge
: 5G WIFI 11AC80

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 q	5143.037	18.82	33.91	35.31	33.75	51.17	54.00	-2.83 Average
2	5210.000	18.92	34.02	35.28	73.93	91.59	-----	----- Average
3	5353.607	19.11	34.41	35.21	30.84	49.15	54.00	-4.85 Average


Test Mode: 09; Polarity: Vertical; Modulation:802.11ac; Bandwidth:80MHz; Channel:middle



Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5210 Band edge
: 5G WIFI 11AC80

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5137.414	18.82	33.93	35.32	43.49	60.92	74.00	-13.08	Peak
2 p	5210.000	18.92	34.02	35.28	79.77	97.43	68.20	29.23	Peak
3	5351.478	19.11	34.41	35.21	41.99	60.30	74.00	-13.70	Peak


Test Mode: 09; Polarity: Vertical; Modulation:802.11ac; Bandwidth:80MHz; Channel:middle



Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5210 Band edge
: 5G WIFI 11AC80

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5135.371	18.81	33.93	35.32	31.20	48.62	54.00	-5.38 Average
2	5210.000	18.92	34.02	35.28	61.25	78.91	-----	----- Average
3 q	5352.809	19.11	34.41	35.21	30.98	49.29	54.00	-4.71 Average

Test Mode: 10; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5260 Band edge
: 5G WIFI 11A

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5104.956	18.77	33.99	35.33	43.70	61.13	74.00	-12.87	peak
2	5149.980	18.83	33.90	35.31	41.69	59.11	74.00	-14.89	peak
3 p	5260.000	18.99	34.12	35.25	92.75	110.61	68.20	42.41	peak




Test Mode: 10; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:Low



Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5260 Band edge
: 5G WIFI 11A

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 q	5127.849	18.80	33.94	35.32	31.06	48.48	54.00	-5.52 Average
2	5149.980	18.83	33.90	35.31	30.88	48.30	54.00	-5.70 Average
3	5260.000	18.99	34.12	35.25	84.25	102.11	-----	----- Average


Test Mode: 10; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:Low



Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5260 Band edge
: 5G WIFI 11A

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5103.539	18.77	33.99	35.33	42.61	60.04	74.00	-13.96	Peak
2	5149.980	18.83	33.90	35.31	42.05	59.47	74.00	-14.53	Peak
3 p	5260.000	18.99	34.12	35.25	92.45	110.31	68.20	42.11	Peak


Test Mode: 10; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:Low



Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5260 Band edge
: 5G WIFI 11A

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 q 5124.470	18.80	33.95	35.32	31.12	48.55	54.00	-5.45	Average
2 5149.980	18.83	33.90	35.31	30.56	47.98	54.00	-6.02	Average
3 5260.000	18.99	34.12	35.25	71.17	89.03	-----	-----	Average


Test Mode: 10; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:High



Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5320 Band edge
: 5G WIFI 11A

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 p 5320.000	19.07	34.28	35.22	92.89	111.02	68.20	42.82	peak
2 5350.020	19.11	34.40	35.21	41.86	60.16	74.00	-13.84	peak
3 5375.829	19.14	34.50	35.20	43.74	62.18	74.00	-11.82	peak

Test Mode: 10; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5320 Band edge
: 5G WIFI 11A

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 5320.000	19.07	34.28	35.22	84.43	102.56	-----	----- Average
2 5350.020	19.11	34.40	35.21	31.29	49.59	54.00	-4.41 Average
3 q 5395.863	19.17	34.58	35.19	31.24	49.80	54.00	-4.20 Average



Test Mode: 10; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:High



Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5320 Band edge
: 5G WIFI 11A


		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 p 5320.000	19.07	34.28	35.22	79.59	97.72	68.20	29.52	Peak
2 5350.020	19.11	34.40	35.21	41.35	59.65	74.00	-14.35	Peak
3 5383.572	19.16	34.53	35.19	43.28	61.78	74.00	-12.22	Peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Test Mode: 10; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:High



Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5320 Band edge
: 5G WIFI 11A


		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 5320.000	19.07	34.28	35.22	70.75	88.88	-----	-----	Average
2 5350.020	19.11	34.40	35.21	30.54	48.84	54.00	-5.16	Average
3 q 5386.592	19.16	34.55	35.19	31.09	49.61	54.00	-4.39	Average



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


Test Mode: 10; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:20MHz; Channel:Low



Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5260 Band edge
: 5G WIFI 11AC20

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5137.640	18.82	33.92	35.32	42.72	60.14	74.00	-13.86	peak
2	5149.980	18.83	33.90	35.31	41.91	59.33	74.00	-14.67	peak
3 p	5260.000	18.99	34.12	35.25	91.19	109.05	68.20	40.85	peak

Test Mode: 10; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:20MHz; Channel:Low



Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5260 Band edge
: 5G WIFI 11AC20


		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 q 5131.229	18.81	33.94	35.32	30.93	48.36	54.00	-5.64	Average
2 5149.980	18.83	33.90	35.31	30.47	47.89	54.00	-6.11	Average
3 5260.000	18.99	34.12	35.25	82.92	100.78	-----	-----	Average



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


Test Mode: 10; Polarity: Vertical; Modulation:802.11ac; Bandwidth:20MHz; Channel:Low



Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5260 Band edge
: 5G WIFI 11AC20

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5103.539	18.77	33.99	35.33	43.00	60.43	74.00	-13.57	Peak
2	5149.980	18.83	33.90	35.31	41.36	58.78	74.00	-15.22	Peak
3 p	5260.000	18.99	34.12	35.25	78.54	96.40	68.20	28.20	Peak


Test Mode: 10; Polarity: Vertical; Modulation:802.11ac; Bandwidth:20MHz; Channel:Low



Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5260 Band edge
: 5G WIFI 11AC20

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 q 5106.904	18.77	33.99	35.33	31.08	48.51	54.00	-5.49	Average
2 5149.980	18.83	33.90	35.31	30.81	48.23	54.00	-5.77	Average
3 5260.000	18.99	34.12	35.25	69.65	87.51	-----	-----	Average


Test Mode: 10; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:20MHz; Channel:High



Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5320 Band edge
: 5G WIFI 11AC20

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 p 5320.000	19.07	34.28	35.22	91.40	109.53	68.20	41.33	peak
2 5350.020	19.11	34.40	35.21	42.59	60.89	74.00	-13.11	peak
3 5392.435	19.17	34.57	35.19	42.94	61.49	74.00	-12.51	peak

Test Mode: 10; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:20MHz; Channel:High



Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5320 Band edge
: 5G WIFI 11AC20


		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 5320.000	19.07	34.28	35.22	83.19	101.32	-----	-----	Average
2 q 5350.020	19.11	34.40	35.21	31.55	49.85	54.00	-4.15	Average
3 5382.767	19.15	34.53	35.19	31.31	49.80	54.00	-4.20	Average



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


Test Mode: 10; Polarity: Vertical; Modulation:802.11ac; Bandwidth:20MHz; Channel:High



Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5320 Band edge
: 5G WIFI 11AC20

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 p	5320.000	19.07	34.28	35.22	87.05	105.18	68.20	36.98 Peak
2	5350.020	19.11	34.40	35.21	42.45	60.75	74.00	-13.25 Peak
3	5382.365	19.15	34.53	35.19	43.00	61.49	74.00	-12.51 Peak

Test Mode: 10; Polarity: Vertical; Modulation:802.11ac; Bandwidth:20MHz; Channel:High



Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5320 Band edge
: 5G WIFI 11AC20


		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 5320.000	19.07	34.28	35.22	69.08	87.21	-----	-----	Average
2 5350.020	19.11	34.40	35.21	30.68	48.98	54.00	-5.02	Average
3 q 5395.460	19.17	34.58	35.19	31.07	49.63	54.00	-4.37	Average



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


Test Mode: 10; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:40MHz; Channel:Low



Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5270 Band edge
: 5G WIFI 11AC40

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5130.499	18.81	33.94	35.32	43.24	60.67	74.00	-13.33	peak
2	5149.980	18.83	33.90	35.31	41.11	58.53	74.00	-15.47	peak
3 p	5270.000	19.00	34.14	35.25	87.73	105.62	68.20	37.42	peak

Test Mode: 10; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:40MHz; Channel:Low



Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5270 Band edge
: 5G WIFI 11AC40


		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 q 5148.093	18.83	33.90	35.31	31.02	48.44	54.00	-5.56	Average
2 5149.980	18.83	33.90	35.31	30.59	48.01	54.00	-5.99	Average
3 5270.000	19.00	34.14	35.25	79.30	97.19	-----	-----	Average



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


Test Mode: 10; Polarity: Vertical; Modulation:802.11ac; Bandwidth:40MHz; Channel:Low



Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5270 Band edge
: 5G WIFI 11AC40

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5120.247	18.79	33.96	35.33	43.15	60.57	74.00	-13.43	Peak
2	5149.980	18.83	33.90	35.31	41.70	59.12	74.00	-14.88	Peak
3 p	5270.000	19.00	34.14	35.25	75.95	93.84	68.20	25.64	Peak


Test Mode: 10; Polarity: Vertical; Modulation:802.11ac; Bandwidth:40MHz; Channel:Low



Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5270 Band edge
: 5G WIFI 11AC40

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 q	5105.889	18.77	33.99	35.33	31.14	48.57	54.00	-5.43 Average
2	5149.980	18.83	33.90	35.31	30.54	47.96	54.00	-6.04 Average
3	5270.000	19.00	34.14	35.25	66.96	84.85	-----	----- Average

Test Mode: 10; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:40MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5310 Band edge
: 5G WIFI 11AC40

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 p	5310.000	19.06	34.24	35.23	88.95	107.02	68.20	38.82 peak
2	5350.020	19.11	34.40	35.21	46.26	64.56	74.00	-9.44 peak
3	5353.962	19.12	34.42	35.21	46.42	64.75	74.00	-9.25 peak




Test Mode: 10; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:40MHz; Channel:High



Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5310 Band edge
: 5G WIFI 11AC40

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5310.000	19.06	34.24	35.23	80.00	98.07	-----	Average
2	5350.020	19.11	34.40	35.21	34.88	53.18	54.00	-0.82 Average
3 q	5350.474	19.11	34.40	35.21	35.02	53.32	54.00	-0.68 Average


Test Mode: 10; Polarity: Vertical; Modulation:802.11ac; Bandwidth:40MHz; Channel:High



Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5310 Band edge
: 5G WIFI 11AC40

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 p	5310.000	19.06	34.24	35.23	88.42	106.49	68.20	38.29 Peak
2	5350.020	19.11	34.40	35.21	45.73	64.03	74.00	-9.97 Peak
3	5350.955	19.11	34.40	35.21	47.19	65.49	74.00	-8.51 Peak

Test Mode: 10; Polarity: Vertical; Modulation:802.11ac; Bandwidth:40MHz; Channel:High



Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5310 Band edge
: 5G WIFI 11AC40


		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5310.000	19.06	34.24	35.23	66.73	84.80	-----	----- Average
2	5350.020	19.11	34.40	35.21	30.79	49.09	54.00	-4.91 Average
3 q	5399.150	19.18	34.60	35.18	30.86	49.46	54.00	-4.54 Average



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


Test Mode: 10; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:80MHz; Channel:middle



Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5290 Band edge
: 5G WIFI 11AC80

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5111.089	18.78	33.98	35.33	42.93	60.36	74.00	-13.64	peak
2 p	5290.000	19.03	34.18	35.24	83.30	101.27	68.20	33.07	peak
3	5352.676	19.11	34.41	35.21	44.64	62.95	74.00	-11.05	peak


Test Mode: 10; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:80MHz; Channel:middle



Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5290 Band edge
: 5G WIFI 11AC80

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5109.337	18.78	33.98	35.33	31.06	48.49	54.00	-5.51 Average
2	5290.000	19.03	34.18	35.24	74.81	92.78	-----	----- Average
3 q	5352.981	19.11	34.41	35.21	33.79	52.10	54.00	-1.90 Average

Test Mode: 10; Polarity: Vertical; Modulation:802.11ac; Bandwidth:80MHz; Channel:middle



Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5290 Band edge
: 5G WIFI 11AC80

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 5133.340	18.81	33.93	35.32	42.89	60.31	74.00	-13.69	Peak
2 p 5290.000	19.03	34.18	35.24	70.95	88.92	68.20	20.72	Peak
3 5351.146	19.11	34.40	35.21	42.43	60.73	74.00	-13.27	Peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com
No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com


SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR240600210304

Page: 205 of 426

Test Mode: 10; Polarity: Vertical; Modulation:802.11ac; Bandwidth:80MHz; Channel:middle



Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5290 Band edge
: 5G WIFI 11AC80

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 5140.681	18.82	33.92	35.32	31.01	48.43	54.00	-5.57	Average
2 5290.000	19.03	34.18	35.24	62.27	80.24	-----	-----	Average
3 q 5358.798	19.12	34.44	35.20	30.90	49.26	54.00	-4.74	Average




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing Services Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Test Mode: 11; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:Low



Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5500 Band edge
: 5G WIFI 11A


		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5455.592	19.25	34.68	35.16	43.30	62.07	74.00	-11.93	peak
2	5464.592	19.26	34.64	35.15	43.29	62.04	68.20	-6.16	peak
3 p	5500.000	19.31	34.50	35.13	91.10	109.78	68.20	41.58	peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


Test Mode: 11; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:Low



Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5500 Band edge
: 5G WIFI 11A

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 q 5450.199	19.24	34.70	35.16	31.24	50.02	54.00	-3.98	Average
2 5500.000	19.31	34.50	35.13	82.61	101.29	-----	-----	Average


Test Mode: 11; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:Low



Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5500 Band edge
: 5G WIFI 11A

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5456.312	19.25	34.67	35.16	43.61	62.37	74.00	-11.63 Peak
2	5461.230	19.26	34.66	35.15	43.80	62.57	68.20	-5.63 peak
3 p	5500.000	19.31	34.50	35.13	79.48	98.16	68.20	29.96 Peak


Test Mode: 11; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:Low



Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5500 Band edge
: 5G WIFI 11A

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 q 5456.791	19.25	34.67	35.16	31.16	49.92	54.00	-4.08	Average
2 5500.000	19.31	34.50	35.13	70.65	89.33	-----	-----	Average

Test Mode: 11; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:High



Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5700 Band edge
: 5G WIFI 11A


		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 p 5700.000		19.44	34.30	35.04	90.12	108.82	68.20	40.62 peak
2 5725.000		19.46	34.25	35.03	42.54	61.22	68.20	-6.98 peak
3 5760.463		19.48	34.22	35.01	44.50	63.19	68.20	-5.01 peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


Test Mode: 11; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:High



Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5700 Band edge
: 5G WIFI 11A

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB		dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 p 5700.000	19.44	34.30	35.04	79.38	98.08	68.20	29.88	Peak
2 5725.000	19.46	34.25	35.03	42.70	61.38	68.20	-6.82	Peak
3 5763.983	19.48	34.23	35.01	44.26	62.96	68.20	-5.24	Peak


Test Mode: 11; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:20MHz; Channel:Low



Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5500 Band edge
: 5G WIFI 11AC20

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5400.475	19.18	34.60	35.18	43.56	62.16	74.00	-11.84	peak
2	5465.793	19.26	34.64	35.15	43.17	61.92	68.20	-6.28	peak
3 p	5500.000	19.31	34.50	35.13	90.08	108.76	68.20	40.56	peak


Test Mode: 11; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:20MHz; Channel:Low



Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5500 Band edge
: 5G WIFI 11AC20

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 q 5454.633	19.25	34.68	35.16	31.28	50.05	54.00	-3.95	Average
2 5500.000	19.31	34.50	35.13	81.48	100.16	-----	-----	Average

Test Mode: 11; Polarity: Vertical; Modulation:802.11ac; Bandwidth:20MHz; Channel:Low



Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5500 Band edge
: 5G WIFI 11AC20

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5451.517	19.25	34.69	35.16	42.92	61.70	74.00	-12.30	Peak
2	5469.038	19.27	34.62	35.15	42.72	61.46	68.20	-6.74	peak
3 p	5500.000	19.31	34.50	35.13	89.68	108.36	68.20	40.16	Peak


SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR240600210304

Page: 215 of 426

Test Mode: 11; Polarity: Vertical; Modulation:802.11ac; Bandwidth:20MHz; Channel:Low



Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5500 Band edge
: 5G WIFI 11AC20


		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 q 5449.121	19.24	34.70	35.16	31.00	49.78	54.00	-4.22	Average
2 5500.000	19.31	34.50	35.13	69.49	88.17	-----	-----	Average



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com
No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.ssgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com


Test Mode: 11; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:20MHz; Channel:High



Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5700 Band edge
: 5G WIFI 11AC20

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 p 5700.000	19.44	34.30	35.04	88.32	107.02	68.20	38.82	peak
2 5725.000	19.46	34.25	35.03	42.98	61.66	68.20	-6.54	peak
3 5739.189	19.47	34.22	35.02	44.29	62.96	68.20	-5.24	peak


Test Mode: 11; Polarity: Vertical; Modulation:802.11ac; Bandwidth:20MHz; Channel:High



Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5700 Band edge
: 5G WIFI 11AC20

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 p	5700.000	19.44	34.30	35.04	77.76	96.46	68.20	28.26 Peak
2	5725.000	19.46	34.25	35.03	42.66	61.34	68.20	-6.86 Peak
3	5739.891	19.47	34.22	35.02	44.01	62.68	68.20	-5.52 Peak

Test Mode: 11; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:40MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5510 Band edge
: 5G WIFI 11AC40

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5408.853	19.19	34.62	35.18	43.41	62.04	74.00	-11.96	peak
2	5469.412	19.27	34.62	35.15	44.24	62.98	68.20	-5.22	peak
3 p	5510.000	19.32	34.54	35.13	86.27	105.00	68.20	36.80	peak




Test Mode: 11; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:40MHz; Channel:Low



Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5510 Band edge
: 5G WIFI 11AC40

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 q 5456.827	19.25	34.67	35.16	31.42	50.18	54.00	-3.82	Average
2 5510.000	19.32	34.54	35.13	77.72	96.45	-----	-----	Average

Test Mode: 11; Polarity: Vertical; Modulation:802.11ac; Bandwidth:40MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5510 Band edge
: 5G WIFI 11AC40

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5440.092	19.23	34.68	35.16	43.82	62.57	74.00	-11.43	Peak
2	5469.972	19.27	34.62	35.15	42.78	61.52	68.20	-6.68	peak
3 p	5510.000	19.32	34.54	35.13	74.64	93.37	68.20	25.17	Peak



Test Mode: 11; Polarity: Vertical; Modulation:802.11ac; Bandwidth:40MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5510 Band edge
: 5G WIFI 11AC40

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 q	5455.291	19.25	34.68	35.16	30.98	49.75	54.00	-4.25 Average
2	5510.000	19.32	34.54	35.13	65.86	84.59	-----	----- Average




Test Mode: 11; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:40MHz; Channel:High



Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5670 Band edge
: 5G WIFI 11AC40

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 p	5670.000	19.42	34.36	35.05	85.87	104.60	68.20	36.40 peak
2	5725.000	19.46	34.25	35.03	42.63	61.31	68.20	-6.89 peak
3	5735.670	19.46	34.23	35.02	43.83	62.50	68.20	-5.70 peak

Test Mode: 11; Polarity: Vertical; Modulation:802.11ac; Bandwidth:40MHz; Channel:High



Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5670 Band edge
: 5G WIFI 11AC40

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 p	5670.000	19.42	34.36	35.05	75.93	94.66	68.20	26.46 Peak
2	5725.000	19.46	34.25	35.03	42.87	61.55	68.20	-6.65 Peak
3	5740.031	19.47	34.22	35.02	44.42	63.09	68.20	-5.11 Peak




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing & Calibration Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Test Mode: 11; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:80MHz; Channel:Low



Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5530 Band edge
: 5G WIFI 11AC80

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5410.812	19.19	34.62	35.18	43.09	61.72	74.00	-12.28 peak
2	5462.509	19.26	34.65	35.15	43.52	62.28	68.20	-5.92 peak
3 p	5530.000	19.33	34.62	35.12	81.43	100.26	68.20	32.06 peak




SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR240600210304

Page: 225 of 426

Test Mode: 11; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:80MHz; Channel:Low



Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5530 Band edge
: 5G WIFI 11AC80

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 q 5457.138	19.25	34.67	35.15	32.02	50.79	54.00	-3.21	Average
2 5530.000	19.33	34.62	35.12	72.57	91.40	-----	-----	Average




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com


Test Mode: 11; Polarity: Vertical; Modulation:802.11ac; Bandwidth:80MHz; Channel:Low



Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5530 Band edge
: 5G WIFI 11AC80

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5402.657	19.18	34.61	35.18	43.41	62.02	74.00	-11.98 Peak
2	5462.509	19.26	34.65	35.15	42.86	61.62	68.20	-6.58 peak
3 p	5530.000	19.33	34.62	35.12	77.15	95.98	68.20	27.78 Peak


Test Mode: 11; Polarity: Vertical; Modulation:802.11ac; Bandwidth:80MHz; Channel:Low



Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5530 Band edge
: 5G WIFI 11AC80

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 q 5448.913	19.24	34.70	35.16	30.91	49.69	54.00	-4.31	Average
2 5530.000	19.33	34.62	35.12	60.70	79.53	-----	-----	Average


Test Mode: 11; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:80MHz; Channel:High



Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5610 Band edge
: 5G WIFI 11AC80

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 p 5610.000	19.38	34.64	35.08	82.89	101.83	68.20	33.63	peak
2 5734.409	19.46	34.23	35.02	43.49	62.16	68.20	-6.04	peak


Test Mode: 11; Polarity: Vertical; Modulation:802.11ac; Bandwidth:80MHz; Channel:High



Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5610 Band edge
: 5G WIFI 11AC80

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 p 5610.000	19.38	34.64	35.08	80.05	98.99	68.20	30.79	Peak
2 5738.869	19.47	34.22	35.02	43.78	62.45	68.20	-5.75	Peak

Test Mode: 12; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:Low



Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5745 Band edge
: 5G WIFI 11A


		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 p 5642.628	19.40	34.44	35.07	43.06	61.83	68.20	-6.37	peak
2 5715.000	19.45	34.27	35.03	42.69	61.38	109.40	-48.02	peak
3 5725.000	19.46	34.25	35.03	47.27	65.95	122.20	-56.25	peak
4 5745.000	19.47	34.21	35.02	90.34	109.00	-----	-----	peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Test Mode: 12; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:Low



Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5745 Band edge
: 5G WIFI 11A

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 p	5644.150	19.41	34.44	35.06	43.00	61.79	68.20	-6.41 peak
2	5715.000	19.45	34.27	35.03	42.34	61.03	109.40	-48.37 peak
3	5725.000	19.46	34.25	35.03	43.98	62.66	122.20	-59.54 peak
4	5745.000	19.47	34.21	35.02	80.49	99.15	-----	----- peak




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing & Calibration Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Test Mode: 12; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5825 Band edge
: 5G WIFI 11A

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 5825.000	19.52	34.35	34.98	91.21	110.10	-----	-----	peak
2 5850.000	19.54	34.40	34.97	44.15	63.12	122.20	-59.08	peak
3 5860.000	19.54	34.44	34.96	44.65	63.67	109.40	-45.73	peak
4 p 5934.643	19.59	34.67	34.93	45.11	64.44	68.20	-3.76	peak



Test Mode: 12; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:High




Site : chamber
 Condition: 3m VERTICAL
 Job No : 02877MO/02103MO
 Mode : 5825 Band edge
 : 5G WIFI 11A

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 5825.000	19.52	34.35	34.98	81.44	100.33	-----	-----	peak
2 5850.000	19.54	34.40	34.97	43.35	62.32	122.20	-59.88	peak
3 5860.000	19.54	34.44	34.96	44.25	63.27	109.40	-46.13	peak
4 p 5931.195	19.59	34.66	34.93	45.28	64.60	68.20	-3.60	peak



Test Mode: 12; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:20MHz; Channel:Low



Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5745 Band edge
: 5G WIFI 11AC20


		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 p 5641.798	19.40	34.45	35.07	43.22	62.00	68.20	-6.20	peak
2 5715.000	19.45	34.27	35.03	43.09	61.78	109.40	-47.62	peak
3 5725.000	19.46	34.25	35.03	48.40	67.08	122.20	-55.12	peak
4 5745.000	19.47	34.21	35.02	89.80	108.46	-----	-----	peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Test Mode: 12; Polarity: Vertical; Modulation:802.11ac; Bandwidth:20MHz; Channel:Low



Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5745 Band edge
: 5G WIFI 11AC20


		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 p	5642.075	19.40	34.45	35.07	43.22	62.00	68.20	-6.20 peak
2	5715.000	19.45	34.27	35.03	42.38	61.07	109.40	-48.33 peak
3	5725.000	19.46	34.25	35.03	44.49	63.17	122.20	-59.03 peak
4	5745.000	19.47	34.21	35.02	79.81	98.47	-----	----- peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Test Mode: 12; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:20MHz; Channel:High



Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5825 Band edge
: 5G WIFI 11AC20


		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5825.000	19.52	34.35	34.98	91.02	109.91	-----	----- peak
2	5850.000	19.54	34.40	34.97	43.97	62.94	122.20	-59.26 peak
3	5860.000	19.54	34.44	34.96	44.09	63.11	109.40	-46.29 peak
4 p	5925.713	19.58	34.65	34.93	44.81	64.11	68.20	-4.09 peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Test Mode: 12; Polarity: Vertical; Modulation:802.11ac; Bandwidth:20MHz; Channel:High



Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5825 Band edge
: 5G WIFI 11AC20


		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5825.000	19.52	34.35	34.98	89.40	108.29	-----	----- peak
2	5850.000	19.54	34.40	34.97	44.34	63.31	122.20	-58.89 peak
3	5860.000	19.54	34.44	34.96	44.08	63.10	109.40	-46.30 peak
4 p	5936.996	19.59	34.67	34.93	45.10	64.43	68.20	-3.77 peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Test Mode: 12; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:40MHz; Channel:Low



Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5755 Band edge
: 5G WIFI 11AC40


		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 p 5648.263	19.41	34.41	35.06	43.38	62.14	68.20	-6.06	peak
2 5715.000	19.45	34.27	35.03	54.68	73.37	109.40	-36.03	peak
3 5725.000	19.46	34.25	35.03	58.38	77.06	122.20	-45.14	peak
4 5755.000	19.48	34.21	35.01	88.64	107.32	-----	-----	peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Test Mode: 12; Polarity: Vertical; Modulation:802.11ac; Bandwidth:40MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5755 Band edge
: 5G WIFI 11AC40

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 p	5642.294	19.40	34.45	35.07	42.87	61.65	68.20	-6.55 peak
2	5715.000	19.45	34.27	35.03	52.99	71.68	109.40	-37.72 peak
3	5725.000	19.46	34.25	35.03	57.97	76.65	122.20	-45.55 peak
4	5755.000	19.48	34.21	35.01	87.86	106.54	-----	----- peak



Test Mode: 12; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:40MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5795 Band edge
: 5G WIFI 11AC40

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5795.000	19.50	34.29	34.99	88.20	107.00	-----	----- peak
2	5850.000	19.54	34.40	34.97	44.67	63.64	122.20	-58.56 peak
3	5860.000	19.54	34.44	34.96	45.19	64.21	109.40	-45.19 peak
4 p	5931.385	19.59	34.66	34.93	45.26	64.58	68.20	-3.62 peak



Test Mode: 12; Polarity: Vertical; Modulation:802.11ac; Bandwidth:40MHz; Channel:High



Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5795 Band edge
: 5G WIFI 11AC40


		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5795.000	19.50	34.29	34.99	86.47	105.27	-----	----- peak
2	5850.000	19.54	34.40	34.97	44.06	63.03	122.20	-59.17 peak
3	5860.000	19.54	34.44	34.96	43.86	62.88	109.40	-46.52 peak
4 p	5931.385	19.59	34.66	34.93	45.16	64.48	68.20	-3.72 peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Test Mode: 12; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:80MHz; Channel:middle




Site : chamber
Condition: 3m HORIZONTAL
Job No : 02877MO/02103MO
Mode : 5775 Band edge
: 5G WIFI 11AC80

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5724.088	19.46	34.25	35.03	49.75	68.43	120.12	-51.69 peak
2	5775.000	19.49	34.25	35.00	83.03	101.77	-----	----- peak
3	5853.349	19.54	34.41	34.97	47.19	66.17	114.56	-48.39 peak
4 p	5927.180	19.59	34.65	34.93	44.28	63.59	68.20	-4.61 peak



Test Mode: 12; Polarity: Vertical; Modulation:802.11ac; Bandwidth:80MHz; Channel:middle



Site : chamber
Condition: 3m VERTICAL
Job No : 02877MO/02103MO
Mode : 5775 Band edge
: 5G WIFI 11AC80

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5724.691	19.46	34.25	35.03	43.98	62.66	121.50	-58.84	peak
2	5775.000	19.49	34.25	35.00	72.62	91.36	-----	-----	peak
3	5851.808	19.54	34.41	34.97	43.75	62.73	118.08	-55.35	peak
4 p	5938.429	19.59	34.68	34.93	44.71	64.05	68.20	-4.15	peak



7.6 Channel Move Time

Test Requirement KDB 905462 D02 Section 5.1
Test Method: KDB 905462 D02 Section 7.8.3

Limit:

Test item	Limit	Applicability	
		Master Device or client with Radar Detection	Client without Radar Detection
Non-occupancy period	Minimum 30 minutes	Yes	Not required
Channel Availability Check Time	60 seconds	Yes	Not required
Channel Move Time	10 seconds See Note 1.	Yes	Yes
Channel Closing Transmission Time	200 milliseconds + an aggregate of 60 milliseconds over remaining 10 second period. See Notes 1 and 2.	Yes	Yes
U-NII Detection Bandwidth	Minimum 100% of the U-NII 99% transmission power bandwidth. See Note 3.	Yes	Not required

Note 1: Channel Move Time and the Channel Closing Transmission Time should be performed with Radar Type 0. The measurement timing begins at the end of the Radar Type 0 burst.

Note 2: The Channel Closing Transmission Time is comprised of 200 milliseconds starting at the beginning of the Channel Move Time plus any additional intermittent control signals required to facilitate a Channel move (an aggregate of 60 milliseconds) during the remainder of the 10 second period. The aggregate duration of control signals will not count quiet periods in between transmissions.

Note 3: During the U-NII Detection Bandwidth detection test, radar type 0 should be used. For each frequency step the minimum percentage of detection is 90 percent. Measurements are performed with no data traffic.

7.6.1 E.U.T. Operation

Operating Environment:

Temperature: 25.0 °C Humidity: 43.4 % RH Atmospheric Pressure: 1020 mbar




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com
No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

7.6.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	13	Normal operating_Keep the EUT communication with the companion device.

7.6.3 Test Setup Diagram



7.6.4 Measurement Procedure and Data

- 1) The radar pulse generator is setup to provide a pulse at frequency that the master and client are operating. A type 0 radar pulse with a 1us pulse width and a 1428us PRI is used for the testing.
- 2) The vector signal generator is adjusted to provide the radar burst (18 pulses) at the level of approximately -61dBm at the antenna port of the master device.
- 3) A trigger is provided from the pulse generator to the DFS monitoring system in order to capture the traffic and the occurrence of the radar pulse.
- 4) EUT will associate with the master at channel. The file "iperf.exe" specified by the FCC is streamed from the PC 2 through the master and the client device to the PC 1 and played in full motion video using Media Player Classic Ver. 6.4.8.6 in order to properly load the network for the entire period of the test.
- 5) When radar burst with a level equal to the DFS Detection Threshold +1dB is generated on the operating channel of the U-NII device. At time T0 the radar waveform generator sends a burst of pulse of the radar waveform at Detection Threshold +1dB.
- 6) Observe the transmissions of the EUT at the end of the radar Burst on the Operating Channel. Measure and record the transmissions from the UUT during the observation time (Channel Move Time). One 15 seconds plot is reported for the Short Pulse Radar Type 0. The plot for the Short Pulse Radar Types start at the end of the radar burst. The Channel Move Time will be calculated based on the zoom in 600ms plot of the Short Pulse Radar Type.
- 7) Measurement of the aggregate duration of the Channel Closed Transmission Time method. With the spectrum analyzer set to zero span tuned to the center frequency of the EUT operating channel at the radar simulated frequency, peak detection, and max hold, the dwell time per bin is given by: $Dwell (0.3ms) = S (12000ms) / B (4000)$; where Dwell is the dwell time per spectrum analyzer sampling bin, S is sweep time and B is the number of spectrum analyzer sampling bins. An upper bound of the aggregate duration of the intermittent control signals of Channel Closing Transmission Time is calculated by: $C (ms) = N \times Dwell (0.3ms)$; where C is the Closing Time, N is the number of spectrum analyzer sampling bins (intermittent control signals) showing a U-NII transmission and Dwell is the dwell time per bin.
- 8) Measurement the EUT for more than 30 minutes following the channel move time to verify that no transmission or beacons occur on this channel.

Please Refer to Appendix for Details

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR240600210304

Page: 247 of 426

7.7 Duty Cycle

Test Requirement KDB 789033 D02 II B 1

Test Method: KDB 789033 II B 1

7.7.1 E.U.T. Operation

Operating Environment:

Temperature: 24.4 °C

Humidity: 44.8 % RH

Atmospheric Pressure: 1020 mbar

7.7.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	09	TX mode (U-NII-1) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n/ac 20/40/80, Only the data of worst case is recorded in the report.
Final test	10	TX mode (U-NII-2A) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n/ac 20/40/80, Only the data of worst case is recorded in the report.
Final test	11	TX mode (U-NII-2C) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n/ac 20/40/80, Only the data of worst case is recorded in the report.
Final test	12	TX mode (U-NII-3) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n/ac 20/40/80, Only the data of worst case is recorded in the report.

7.7.3 Test Setup Diagram

7.7.4 Measurement Procedure and Data

Please Refer to Appendix for Details

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR240600210304

Page: 248 of 426

7.8 99% Bandwidth

Test Requirement N/A
Test Method: KDB 789033 II D

7.8.1 E.U.T. Operation

Operating Environment:
Temperature: 24.4 °C Humidity: 44.8 % RH Atmospheric Pressure: 1020 mbar

7.8.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	09	TX mode (U-NII-1) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n/ac 20/40/80, Only the data of worst case is recorded in the report.
Final test	10	TX mode (U-NII-2A) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n/ac 20/40/80, Only the data of worst case is recorded in the report.
Final test	11	TX mode (U-NII-2C) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n/ac 20/40/80, Only the data of worst case is recorded in the report.
Final test	12	TX mode (U-NII-3) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n/ac 20/40/80, Only the data of worst case is recorded in the report.




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

7.8.3 Test Setup Diagram



7.8.4 Measurement Procedure and Data

Please Refer to Appendix for Details

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR240600210304

Page: 250 of 426

7.9 26dB Emission bandwidth

Test Requirement 47 CFR Part 15, Subpart E 15.407 (a)

Test Method: KDB 789033 D02 II C 1

7.9.1 E.U.T. Operation

Operating Environment:

Temperature: 24.4 °C

Humidity: 44.8 % RH

Atmospheric Pressure: 1020 mbar

7.9.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	09	TX mode (U-NII-1) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n/ac 20/40/80, Only the data of worst case is recorded in the report.
Final test	10	TX mode (U-NII-2A) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n/ac 20/40/80, Only the data of worst case is recorded in the report.
Final test	11	TX mode (U-NII-2C) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n/ac 20/40/80, Only the data of worst case is recorded in the report.
Final test	12	TX mode (U-NII-3) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n/ac 20/40/80, Only the data of worst case is recorded in the report.




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

7.9.3 Test Setup Diagram



7.9.4 Measurement Procedure and Data

Please Refer to Appendix for Details

7.10 Minimum 6 dB bandwidth (5.725-5.85 GHz band)

Test Requirement 47 CFR Part 15, Subpart E 15.407 (e)

Test Method: KDB 789033 D02 II C 2

Limit:

Frequency band(MHz)	Limit
5725-5850	≥500 kHz

7.10.1 E.U.T. Operation

Operating Environment:

Temperature: 24.4 °C


Humidity: 44.8 % RH

Atmospheric Pressure: 1020 mbar

7.10.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	12	TX mode (U-NII-3) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n/ac 20/40/80, Only the data of worst case is recorded in the report.

7.10.3 Test Setup Diagram



7.10.4 Measurement Procedure and Data

Please Refer to Appendix for Details

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR240600210304

Page: 253 of 426

7.11 Peak Power spectrum density

Test Requirement 47 CFR Part 15, Subpart E 15.407 (a)

Test Method: KDB 789033 D02 II F

Limit:

Frequency band(MHz)	Limit
5150-5250	≤17dBm in 1MHz for master device
	≤11dBm in 1MHz for client device
5250-5350	≤11dBm in 1MHz for client device
5470-5725	≤11dBm in 1MHz for client device
5725-5850	≤30dBm in 500 kHz
Remark:	The maximum power spectral density is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test.

7.11.1 E.U.T. Operation

Operating Environment:

Temperature: 24.4 °C

Humidity: 44.8 % RH

Atmospheric Pressure: 1020 mbar

7.11.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	09	TX mode (U-NII-1) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n/ac 20/40/80, Only the data of worst case is recorded in the report.
Final test	10	TX mode (U-NII-2A) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n/ac 20/40/80, Only the data of worst case is recorded in the report.
Final test	11	TX mode (U-NII-2C) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n/ac 20/40/80, Only the data of worst case is recorded in the report.
Final test	12	TX mode (U-NII-3) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n/ac 20/40/80, Only the data of worst case is recorded in the report.




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

7.11.3 Test Setup Diagram



7.11.4 Measurement Procedure and Data

Please Refer to Appendix for Details

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR240600210304

Page: 255 of 426

7.12 Frequency Stability

Test Requirement 47 CFR Part 15, Subpart E 15.407 (g)

Test Method: ANSI C63.10 (2013) Section 6.8

7.12.1 E.U.T. Operation

Operating Environment:

Temperature: 24.4 °C

Humidity: 44.8 % RH

Atmospheric Pressure: 1020 mbar

7.12.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	09	TX mode (U-NII-1) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n/ac 20/40/80, Only the data of worst case is recorded in the report.
Final test	10	TX mode (U-NII-2A) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n/ac 20/40/80, Only the data of worst case is recorded in the report.
Final test	11	TX mode (U-NII-2C) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n/ac 20/40/80, Only the data of worst case is recorded in the report.
Final test	12	TX mode (U-NII-3) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n/ac 20/40/80, Only the data of worst case is recorded in the report.




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

7.12.3 Test Setup Diagram



7.12.4 Measurement Procedure and Data

Please Refer to Appendix for Details

7.13 Non-occupancy period

Test Requirement KDB 905462 D02 Section 5.1
Test Method: KDB 905462 D02 Section 7.8.3

Limit:

Test item	Limit	Applicability	
		Master Device or client with Radar Detection	Client without Radar Detection
Non-occupancy period	Minimum 30 minutes	Yes	Not required
Channel Availability Check Time	60 seconds	Yes	Not required
Channel Move Time	10 seconds See Note 1.	Yes	Yes
Channel Closing Transmission Time	200 milliseconds + an aggregate of 60 milliseconds over remaining 10 second period. See Notes 1 and 2.	Yes	Yes
U-NII Detection Bandwidth	Minimum 100% of the U-NII 99% transmission power bandwidth. See Note 3.	Yes	Not required

Note 1: Channel Move Time and the Channel Closing Transmission Time should be performed with Radar Type 0. The measurement timing begins at the end of the Radar Type 0 burst.

Note 2: The Channel Closing Transmission Time is comprised of 200 milliseconds starting at the beginning of the Channel Move Time plus any additional intermittent control signals required to facilitate a Channel move (an aggregate of 60 milliseconds) during the remainder of the 10 second period. The aggregate duration of control signals will not count quiet periods in between transmissions.

Note 3: During the U-NII Detection Bandwidth detection test, radar type 0 should be used. For each frequency step the minimum percentage of detection is 90 percent. Measurements are performed with no data traffic.

7.13.1 E.U.T. Operation

Operating Environment:

Temperature: 25.0 °C Humidity: 43.4 % RH Atmospheric Pressure: 1020 mbar

7.13.2 Test Mode Description

Pre-scan /	Mode	Description
------------	------	-------------



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

7.13.4 Measurement Procedure and Data

- 1) The radar pulse generator is setup to provide a pulse at frequency that the master and client are operating. A type 0 radar pulse with a 1us pulse width and a 1428us PRI is used for the testing.
- 2) The vector signal generator is adjusted to provide the radar burst (18 pulses) at the level of approximately -61dBm at the antenna port of the master device.
- 3) A trigger is provided from the pulse generator to the DFS monitoring system in order to capture the traffic and the occurrence of the radar pulse.
- 4) EUT will associate with the master at channel. The file "iperf.exe" specified by the FCC is streamed from the PC 2 through the master and the client device to the PC 1 and played in full motion video using Media Player Classic Ver. 6.4.8.6 in order to properly load the network for the entire period of the test.
- 5) When radar burst with a level equal to the DFS Detection Threshold +1dB is generated on the operating channel of the U-NII device. At time T0 the radar waveform generator sends a burst of pulse of the radar waveform at Detection Threshold +1dB.
- 6) Observe the transmissions of the EUT at the end of the radar Burst on the Operating Channel. Measure and record the transmissions from the UUT during the observation time (Channel Move Time). One 15 seconds plot is reported for the Short Pulse Radar Type 0. The plot for the Short Pulse Radar Types start at the end of the radar burst. The Channel Move Time will be calculated based on the zoom in 600ms plot of the Short Pulse Radar Type.
- 7) Measurement of the aggregate duration of the Channel Closed Transmission Time method. With the spectrum analyzer set to zero span tuned to the center frequency of the EUT operating channel at the radar simulated frequency, peak detection, and max hold, the dwell time per bin is given by: $Dwell (0.3ms) = S (12000ms) / B (4000)$; where Dwell is the dwell time per spectrum analyzer sampling bin, S is sweep time and B is the number of spectrum analyzer sampling bins. An upper bound of the aggregate duration of the intermittent control signals of Channel Closing Transmission Time is calculated by: $C (ms) = N \times Dwell (0.3ms)$; where C is the Closing Time, N is the number of spectrum analyzer sampling bins (intermittent control signals) showing a U-NII transmission and Dwell is the dwell time per bin.
- 8) Measurement the EUT for more than 30 minutes following the channel move time to verify that no transmission or beacons occur on this channel.

Please Refer to Appendix for Details

7.14 Channel Closing Transmission Time

Test Requirement KDB 905462 D02 Section 5.1
Test Method: KDB 905462 D02 Section 7.8.3

Limit:

Test item	Limit	Applicability	
		Master Device or client with Radar Detection	Client without Radar Detection
Non-occupancy period	Minimum 30 minutes	Yes	Not required
Channel Availability Check Time	60 seconds	Yes	Not required
Channel Move Time	10 seconds See Note 1.	Yes	Yes
Channel Closing Transmission Time	200 milliseconds + an aggregate of 60 milliseconds over remaining 10 second period. See Notes 1 and 2.	Yes	Yes
U-NII Detection Bandwidth	Minimum 100% of the U-NII 99% transmission power bandwidth. See Note 3.	Yes	Not required

Note 1: Channel Move Time and the Channel Closing Transmission Time should be performed with Radar Type 0. The measurement timing begins at the end of the Radar Type 0 burst.

Note 2: The Channel Closing Transmission Time is comprised of 200 milliseconds starting at the beginning of the Channel Move Time plus any additional intermittent control signals required to facilitate a Channel move (an aggregate of 60 milliseconds) during the remainder of the 10 second period. The aggregate duration of control signals will not count quiet periods in between transmissions.

Note 3: During the U-NII Detection Bandwidth detection test, radar type 0 should be used. For each frequency step the minimum percentage of detection is 90 percent. Measurements are performed with no data traffic.

7.14.1 E.U.T. Operation

Operating Environment:

Temperature: 25.0 °C Humidity: 43.4 % RH Atmospheric Pressure: 1020 mbar

7.14.2 Test Mode Description

Pre-scan /	Mode	Description
------------	------	-------------



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

7.14.4 Measurement Procedure and Data

- 1) The radar pulse generator is setup to provide a pulse at frequency that the master and client are operating. A type 0 radar pulse with a 1us pulse width and a 1428us PRI is used for the testing.
- 2) The vector signal generator is adjusted to provide the radar burst (18 pulses) at the level of approximately -61dBm at the antenna port of the master device.
- 3) A trigger is provided from the pulse generator to the DFS monitoring system in order to capture the traffic and the occurrence of the radar pulse.
- 4) EUT will associate with the master at channel. The file "iperf.exe" specified by the FCC is streamed from the PC 2 through the master and the client device to the PC 1 and played in full motion video using Media Player Classic Ver. 6.4.8.6 in order to properly load the network for the entire period of the test.
- 5) When radar burst with a level equal to the DFS Detection Threshold +1dB is generated on the operating channel of the U-NII device. At time T0 the radar waveform generator sends a burst of pulse of the radar waveform at Detection Threshold +1dB.
- 6) Observe the transmissions of the EUT at the end of the radar Burst on the Operating Channel. Measure and record the transmissions from the UUT during the observation time (Channel Move Time). One 15 seconds plot is reported for the Short Pulse Radar Type 0. The plot for the Short Pulse Radar Types start at the end of the radar burst. The Channel Move Time will be calculated based on the zoom in 600ms plot of the Short Pulse Radar Type.
- 7) Measurement of the aggregate duration of the Channel Closed Transmission Time method. With the spectrum analyzer set to zero span tuned to the center frequency of the EUT operating channel at the radar simulated frequency, peak detection, and max hold, the dwell time per bin is given by: $Dwell (0.3ms) = S (12000ms) / B (4000)$; where Dwell is the dwell time per spectrum analyzer sampling bin, S is sweep time and B is the number of spectrum analyzer sampling bins. An upper bound of the aggregate duration of the intermittent control signals of Channel Closing Transmission Time is calculated by: $C (ms) = N \times Dwell (0.3ms)$; where C is the Closing Time, N is the number of spectrum analyzer sampling bins (intermittent control signals) showing a U-NII transmission and Dwell is the dwell time per bin.
- 8) Measurement the EUT for more than 30 minutes following the channel move time to verify that no transmission or beacons occur on this channel.

Please Refer to Appendix for Details

8 Test Setup Photo

Please refer to Appendix A.1-WLAN Setup Photos.



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing Center Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

9 EUT Constructional Details (EUT Photos)

Refer to Appendix - Photographs of EUT Constructional Details for SZCR2406002103MO.

10 Appendix

1. Duty Cycle

1.1 Test Result

1.1.1 Ant1

Ant1							
Mode	TX Type	Frequency (MHz)	T_on (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	Max. DC Variation (%)
802.11a	SISO	5180	2.030	2.065	98.31	0.07	0.03
		5200	2.030	2.064	98.35	0.07	0.03
		5240	2.030	2.064	98.35	0.07	0.04
		5260	2.029	2.064	98.30	0.07	0.04
		5300	2.030	2.064	98.35	0.07	0.04
		5320	2.030	2.064	98.35	0.07	0.03
		5500	2.030	2.065	98.31	0.07	0.04
		5580	2.030	2.064	98.35	0.07	0.03
		5700	2.030	2.064	98.35	0.07	0.04
		5745	2.029	2.064	98.30	0.07	0.04
		5785	2.030	2.065	98.31	0.07	0.04
		5825	2.030	2.065	98.31	0.07	0.03
802.11n (HT20)	SISO	5180	1.890	1.925	98.18	0.08	0.03
		5200	1.889	1.925	98.13	0.08	0.03
		5240	1.890	1.925	98.18	0.08	0.03
		5260	1.890	1.925	98.18	0.08	0.03
		5300	1.890	1.925	98.18	0.08	0.00
		5320	1.890	1.926	98.13	0.08	0.03
		5500	1.890	1.925	98.18	0.08	0.03
		5580	1.890	1.925	98.18	0.08	0.03
		5700	1.890	1.925	98.18	0.08	0.03
		5745	1.890	1.925	98.18	0.08	0.00
		5785	1.889	1.924	98.18	0.08	0.03
		5825	1.890	1.925	98.18	0.08	0.03
802.11n (HT40)	SISO	5190	0.930	0.964	96.47	0.16	0.03
		5230	0.929	0.964	96.37	0.16	0.03
		5270	0.929	0.964	96.37	0.16	0.00
		5310	0.929	0.964	96.37	0.16	0.03

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR240600210304

Page: 266 of 426

		5510	0.929	0.964	96.37	0.16	0.03
		5550	0.929	0.964	96.37	0.16	0.00
		5670	0.929	0.964	96.37	0.16	0.03
		5755	0.929	0.964	96.37	0.16	0.00
		5795	0.929	0.964	96.37	0.16	0.00
802.11ac (VHT20)	SISO	5180	1.901	1.937	98.14	0.08	0.03
		5200	1.902	1.938	98.14	0.08	0.03
		5240	1.902	1.938	98.14	0.08	0.03
		5260	1.901	1.937	98.14	0.08	0.04
		5300	1.902	1.937	98.19	0.08	0.03
		5320	1.902	1.937	98.19	0.08	0.03
		5500	1.901	1.936	98.19	0.08	0.03
		5580	1.902	1.937	98.19	0.08	0.03
		5700	1.902	1.937	98.19	0.08	0.03
		5745	1.902	1.937	98.19	0.08	0.03
		5785	1.901	1.936	98.19	0.08	0.03
		5825	1.902	1.938	98.14	0.08	0.03
802.11ac (VHT40)	SISO	5190	0.937	0.972	96.40	0.16	0.00
		5230	0.937	0.972	96.40	0.16	0.03
		5270	0.937	0.972	96.40	0.16	0.00
		5310	0.937	0.972	96.40	0.16	0.00
		5510	0.938	0.972	96.50	0.15	0.00
		5550	0.937	0.972	96.40	0.16	0.00
		5670	0.937	0.972	96.40	0.16	0.00
		5755	0.937	0.972	96.40	0.16	0.03
		5795	0.937	0.972	96.40	0.16	0.03
802.11ac (VHT80)	SISO	5210	0.457	0.492	92.89	0.32	0.00
		5290	0.456	0.492	92.68	0.33	0.03
		5530	0.457	0.492	92.89	0.32	0.03
		5610	0.457	0.492	92.89	0.32	0.03
		5775	0.457	0.492	92.89	0.32	0.07



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.


Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing & Inspection Laboratory


No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

1.2 Test Graph


1.2.1 Ant1




802.11a_MCH_5200MHz_Ant1_NTNV




802.11a_HCH_5240MHz_Ant1_NTNV




802.11a_LCH_5260MHz_Ant1_NTNV




802.11a_MCH_5300MHz_Ant1_NTNV




802.11a_HCH_5320MHz_Ant1_NTNV




802.11a_LCH_5500MHz_Ant1_NTNV




802.11a_MCH_5580MHz_Ant1_NTNV




802.11a_HCH_5700MHz_Ant1_NTNV




802.11a_LCH_5745MHz_Ant1_NTNV




802.11a_MCH_5785MHz_Ant1_NTNV




802.11a_HCH_5825MHz_Ant1_NTNV




802.11n(HT20)_LCH_5180MHz_Ant1_NTNV




802.11n(HT20)_MCH_5200MHz_Ant1_NTNV




802.11n(HT20)_HCH_5240MHz_Ant1_NTNV




802.11n(HT20)_LCH_5260MHz_Ant1_NTNV




802.11n(HT20)_MCH_5300MHz_Ant1_NTNV




802.11n(HT20)_HCH_5320MHz_Ant1_NTNV




802.11n(HT20)_LCH_5500MHz_Ant1_NTNV




802.11n(HT20)_MCH_5580MHz_Ant1_NTNV




802.11n(HT20)_HCH_5700MHz_Ant1_NTNV




802.11n(HT20)_LCH_5745MHz_Ant1_NTNV




802.11n(HT20)_MCH_5785MHz_Ant1_NTNV




802.11n(HT20)_HCH_5825MHz_Ant1_NTNV




802.11n(HT40)_LCH_5190MHz_Ant1_NTNV




802.11n(HT40)_HCH_5230MHz_Ant1_NTNV



802.11n(HT40)_LCH_5270MHz_Ant1_NTNV



802.11n(HT40)_HCH_5310MHz_Ant1_NTNV




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing & Calibration Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

802.11n(HT40)_LCH_5510MHz_Ant1_NTNV



802.11n(HT40)_MCH_5550MHz_Ant1_NTNV




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing & Calibration Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com


802.11n(HT40)_HCH_5670MHz_Ant1_NTNV



802.11n(HT40)_LCH_5755MHz_Ant1_NTNV



802.11n(HT40)_HCH_5795MHz_Ant1_NTNV



802.11ac(VHT20)_LCH_5180MHz_Ant1_NTNV

