



Compliance Certification Services (Kunshan) Inc.

CCSEM-TRF-001 Rev. 02 Sep 01, 2023

Report No.: KSCR240100008109

Page: 1 of 11

1 Cover Page

RF Exposure Evaluation Report

Application No.: KSCR2401000081AT
FCC ID: 2AH25T1731
IC: 22621-T1731
Applicant: Shanghai Sunmi Technology Co.,Ltd.
Address of Applicant: Room 505, No.388 Song Hu Road, Yang Pu District, Shanghai, China
Manufacturer: Shanghai Sunmi Technology Co.,Ltd.
Address of Manufacturer: Room 505, No.388 Song Hu Road, Yang Pu District, Shanghai, China
Equipment Under Test (EUT):
EUT Name: POS System
Model No.: T1731
Trade Mark: SUNMI
Standard(s) : FCC Rules 47 CFR §2.1091
KDB 447498 D04 interim General RF Exposure Guidance v01
RSS-102 Issue 5 Amendment 1 (February 2, 2021)
Date of Receipt: 2024-01-12
Date of Test: 2024-03-19 to 2024-04-08
Date of Issue: 2024-04-08

Test Result:	Pass*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein.

Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.





Compliance Certification Services (Kunshan) Inc.

CCSEM-TRF-001 Rev. 02 Sep 01, 2023

Report No.: KSCR240100008109

Page: 2 of 11

<i>Revision Record</i>			
<i>Version</i>	<i>Description</i>	<i>Date</i>	<i>Remark</i>
00	Original	2024-04-08	/

Authorized for issue by:			
Tested By			
	<hr/> Damon_Zhou/Project Engineer		
Approved By			
	<hr/> Terry Hou /Reviewer		



Compliance Certification Services (Kunshan) Inc.

CCSEM-TRF-001 Rev. 02 Sep 01, 2023

Report No.: KSCR240100008109

Page: 3 of 11

2 Contents

	Page
1 Cover Page	1
2 Contents	3
3 General Information	4
3.1 General Description of E.U.T.	4
3.2 Details of E.U.T.	4
3.3 Test Location.....	7
3.4 Test Facility	7
4 FCC Radiofrequency radiation exposure limits	8
5 IC Radiofrequency radiation exposure limits:	9
6 Measurement and Calculation	10
6.1 Maximum transmit power	10
6.2 MPE Calculation.....	10

3 General Information

3.1 General Description of E.U.T.

Power supply:	DC 24V,2.5A by Adapter Adapter model: CYSE65-240250 INPUT: AC 100-240V,50/60Hz,1.7A OUTPUT: DC 24V,2.5A,60W
Serial Number:	DE17D3CL10022
Firmware Version:	D3mini_IO_V2.0

3.2 Details of E.U.T.

BLE

Operation Frequency:	2402MHz to 2480MHz
Bluetooth Version:	V5.0 Dual mode
Modulation Type:	GFSK
Number of Channels:	40
Channel Spacing:	2MHz
Antenna Type:	Internal Antenna
Antenna Gain:	1.01 dBi(Provided by the manufacturer)

BT

Operation Frequency:	2402MHz to 2480MHz
Bluetooth Version:	V5.0 Dual mode
Modulation Type:	GFSK, pi/4DQPSK, 8DPSK
Number of Channels:	79
Channel Spacing:	1MHz
Spectrum Spread Technology:	Frequency Hopping Spread Spectrum(FHSS)
Antenna Type:	Internal Antenna
Antenna Gain:	1.01 dBi(Provided by the manufacturer)

13.56MHz

Operation Frequency:	13.56MHz
Modulation Type:	ASK
Antenna Type:	Loop Antenna

2.4G WLAN

Operation Frequency:	802.11b/g/n(HT20): 2412MHz to 2462MHz 802.11n(HT40): 2422MHz to 2452MHz
Modulation Type:	802.11b: DSSS (CCK, DQPSK, DBPSK) 802.11g/n: OFDM (64QAM, 16QAM, QPSK, BPSK)
Number of Channels:	802.11b/g/n(HT20):11;802.11n(HT40):7
Channel Spacing:	5MHz
Antenna Type:	Internal Antenna
Antenna Gain:	1.01 dBi(Provided by the manufacturer)

5G WLAN

Operation Frequency/Number of channels (20MHz):	U-NII-1: 5180-5240MHz (4 Channels) U-NII-2A: 5260-5320MHz (4 Channels) U-NII-2C: 5500-5700MHz (11 Channels) U-NII-3: 5745-5825MHz (5 Channels)
Operation Frequency/Number of channels/(40MHz):	U-NII-1: 5190-5230MHz (2 Channels) U-NII-2A: 5270-5310MHz (2 Channels) U-NII-2C: 5510-5670MHz (5 Channels) U-NII-3: 5755-5795MHz (2 Channels)
Operation Frequency/Number of channels (80MHz):	U-NII-1: 5210MHz (1 Channel) U-NII-2A: 5290MHz (1 Channels) U-NII-2C: 5530-5610MHz (2 Channels) U-NII-3: 5775MHz (1 Channel)
Modulation Type:	802.11a: OFDM (64QAM, 16QAM, QPSK, BPSK) 802.11n: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM)
Channel Spacing:	802.11a/n/ac20: 20MHz; 802.11n/ac40: 40MHz; 802.11ac80: 80MHz
DFS Function:	Slave without Radar detection
Antenna Type:	Internal Antenna
Antenna Gain:	U-NII-1:1.98dBi, U-NII-2A:2.07dBi, U-NII-2C:2.08dBi, U-NII-3:2.12dBi (Provided by the manufacturer)

2G

Support Network:	GSM, GPRS, EGPRS
Operation Frequency Band:	GSM850/GSM1900
Modulation Type:	GMSK for GSM/GPRS/EGPRS 8PSK for EGPRS
GPRS Class:	8/10/12
EGPRS Class:	8/10/12
Antenna Type:	Internal Antenna
Antenna Gain:	GSM850: -0.36dBi (Provided by the manufacturer) GSM1900: 3.62dBi (Provided by the manufacturer)

Compliance Certification Services (Kunshan) Inc.

CCSEM-TRF-001 Rev. 02 Sep 01, 2023

Report No.: KSCR240100008109

Page: 6 of 11

3G

Operation Frequency Band:	UMTS B2, B4, B5
Modulation Type:	UL QPSK, BPSK DL QPSK, BPSK
Antenna Type:	Internal Antenna
Antenna Gain:	UMTS B2: 3.62dBi (Provided by the manufacturer) UMTS B4: 3.09dBi (Provided by the manufacturer) UMTS B5: -0.36dBi (Provided by the manufacturer)

4G

LTE Operation Frequency Band:	LTE Band 2,4,5,7,12,13,17,25,26,30,38,40,41,66,71
Modulation Type:	QPSK, 16QAM, 64QAM
Antenna Type:	Internal Antenna
Antenna Gain:	Band 2:3.62dBi(Provided by the manufacturer) Band 4: 3.09dBi(Provided by the manufacturer) Band 5: -0.36dBi(Provided by the manufacturer) Band 7: 3.56dBi(Provided by the manufacturer) Band 12: -0.22dBi(Provided by the manufacturer) Band 13: 0.33dBi(Provided by the manufacturer) Band 17: -0.22dBi(Provided by the manufacturer) Band 25: 3.62dBi(Provided by the manufacturer) Band 26: -0.36dBi(Provided by the manufacturer) Band 30: 3.47dBi(Provided by the manufacturer) Band 38: 4.38dBi(Provided by the manufacturer) Band 40: 3.47dBi(Provided by the manufacturer) Band 41: 4.38dBi(Provided by the manufacturer) Band 66: 3.09dBi(Provided by the manufacturer) Band 71: -1.11dBi(Provided by the manufacturer)

3.3 Test Location

All tests were performed at:

Compliance Certification Services (Kunshan) Inc.

No.10 Weiye Rd, Innovation park, Eco&Tec, Development Zone, Kunshan City, Jiangsu, China.

Tel: +86 512 5735 5888 Fax: +86 512 5737 0818

No tests were sub-contracted.

Note:

- 1.SGS is not responsible for wrong test results due to incorrect information (e.g. max. clock frequency, highest internal frequency, antenna gain, cable loss, etc) is provided by the applicant. (if applicable).
- 2.SGS is not responsible for the authenticity, integrity and the validity of the conclusion based on results of the data provided by applicant. (if applicable).
3. Sample source: sent by customer.

3.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **A2LA**

Compliance Certification Services (Kunshan) Inc. is accredited by the American Association for Laboratory Accreditation (A2LA). Certificate No. 2541.01.

- **FCC**

Compliance Certification Services (Kunshan) Inc. has been recognized as an accredited testing laboratory. Designation Number: CN1172.

- **ISED**

Compliance Certification Services (Kunshan) Inc. has been recognized by Innovation, Science and Economic Development Canada (ISED) as an accredited testing laboratory. Company Number: 2324E

- **VCCI**

The 3m and 10m Semi-anechoic chamber and Shielded Room of Compliance Certification Services (Kunshan) Inc. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-20134, R-11600, C-11707, T-11499, G-10216 respectively.

4 FCC Radiofrequency radiation exposure limits

According to §1.1310, The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part 1.1307(b)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(i) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*(100)	≤6
3.0-30	1842/f	4.89/f	*(900/f ²)	<6
30-300	61.4	0.163	1.0	<6
300-1,500			f/300	<6
1,500-100,000			5	<6
(ii) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	<30
1.34-30	824/f	2.19/f	*(180/f ²)	<30
30-300	27.5	0.073	0.2	<30
300-1,500			f/1500	<30
1,500-100,000			1.0	<30

5 IC Radiofrequency radiation exposure limits:

According to RSS-102 section 2.5.2, RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

below 20 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);

- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $4.49/f^{0.5}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $1.31 \times 10^{-2} f^{0.6834}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance).

For 2.4G device, the limit of worse case is 2.68 W, For 5G device, the limit of worse case is 4.53W

For GSM850, the limit of worse case is 1.29W, For GSM1900, the limit of worse case is 2.24W,

For UMTS B2, the limit of worse case is 2.24W, For UMTS B4, the limit of worse case is 2.12W,

For UMTS B5, the limit of worse case is 1.29W, For LTE B2, the limit of worse case is 2.14W,

For LTE B4, the limit of worse case is 2.12W, For LTE B5, the limit of worse case is 1.29W,

For LTE B7, the limit of worse case is 2.75W, For LTE B12, the limit of worse case is 1.15W,

For LTE B13, the limit of worse case is 1.24W, For LTE B17, the limit of worse case is 1.16W,

For LTE B25, the limit of worse case is 2.24W, For LTE B26, the limit of worse case is 1.29W,

For LTE B30, the limit of worse case is 2.60W, For LTE B38, the limit of worse case is 2.80W,

For LTE B40, the limit of worse case is 2.60W, For LTE B41, the limit of worse case is 2.75W,

For LTE B66, the limit of worse case is 2.12W, For LTE B71, the limit of worse case is 1.11W,

6 Measurement and Calculation

6.1 Maximum transmit power

The Power Data is based on the RF Test Report KSCR240100008101, KSCR240100008102, KSCR240100008103, KSCR240100008104, KSCR240100008105, KSCR240100008106, KSCR240100008107, KSCR240100008108, KSCR240100008201, KSCR240100008202, KSCR240100008203.

6.2 MPE Calculation

According to the formula $S=P/4\pi R^2$, we can calculate S which is MPE.

Note:

- 1) P (mW)
- 2) R = distance to the center of radiation of antenna (in centimeter)

For FCC

Test Mode	Max Average power (dBm)	Max Tune up (dBm)	Max Tune up (W)	Antenna Gain (dBi)	Operation Distance R(cm)	Power Density (mW/cm ²)	Limit of Power Density S(mW/cm ²) for FCC	Result
GSM850	24.22	24.50	281.84	-0.36	20	0.052	0.55	Pass
GSM1900	20.03	20.50	112.20	3.62	20	0.051	1	Pass
UMTS B2	24.54	25.00	316.23	3.62	20	0.145	1	Pass
UMTS B4	24.86	25.00	316.23	3.09	20	0.128	1	Pass
UMTS B5	24.38	24.50	316.23	-0.36	20	0.052	0.55	Pass
LTE B2	24.22	24.50	281.84	3.62	20	0.129	1	Pass
LTE B4	23.57	24.00	281.84	3.09	20	0.102	1	Pass
LTE B5	24.30	24.50	281.84	-0.36	20	0.052	0.549	Pass
LTE B7	24.27	24.50	281.84	3.56	20	0.127	1	Pass
LTE B12	23.91	24.00	281.84	-0.22	20	0.048	0.466	Pass
LTE B13	23.49	24.00	281.84	0.33	20	0.054	0.518	Pass
LTE B17	24.18	24.50	251.19	-0.22	20	0.053	0.469	Pass
LTE B25	23.86	24.00	251.19	3.62	20	0.115	1	Pass
LTE B26	23.77	24.00	281.84	-0.36	20	0.046	0.543	Pass
LTE B30	20.34	20.50	112.20	3.47	20	0.050	1	Pass
LTE B38	24.58	25.00	316.23	4.38	20	0.172	1	Pass
LTE B40	19.33	20.00	100.00	3.47	20	0.044	1	Pass
LTE B41	23.75	24.50	281.84	4.38	20	0.154	1	Pass
LTE B66	24.52	25.00	354.81	3.09	20	0.128	1	Pass
LTE B71	23.80	24.00	281.84	-1.11	20	0.039	0.442	Pass

Remark:

For GMS850&GSM1900

The averaged power calculated method are shown as below:

Averaged power=Maximum burst averaged power (1 Tx Slot)+(10lg(1/8))dB

Averaged power=Maximum burst averaged power (2 Tx Slot)+(10lg(2/8))dB

Averaged power=Maximum burst averaged power (3 Tx Slot)+(10lg(3/8))dB

Averaged power=Maximum burst averaged power (4 Tx Slot)+(10lg(4/8))dB

So the max Average power for GSM850 is 33.35-9.03=24.22dBm

The max Average power for GSM 1900 is 29.06-9.03=20.03dBm



Compliance Certification Services (Kunshan) Inc.

CCSEM-TRF-001 Rev. 02 Sep 01, 2023

Report No.: KSCR240100008109

Page: 11 of 11

Test Mode	Max Tune up (dBm)	Max Tune up (W)	Antenna Gain (dBi)	Operation Distance R(cm)	Power Density (mW/cm ²)	Limit of Power Density S(mW/cm ²) for FCC	Result
Bluetooth	10.00	0.010	1.01	20	0.003	1	Pass
2.4G WLAN	17.50	0.056	1.01	20	0.014	1	Pass
5G WLAN	15.50	0.035	2.12	20	0.012	1	Pass

13.56MHz: 63.54dBuV/m@3m=0.0007mW

For FCC:

The 2.4GHz WLAN,BT,5GHz WLAN ,WWAN and 13.56MHz can transmit simultaneously, but the maximum rate of MPE is $0.014/1+0.003/1+0.012/1+0.172/1+0.0007/1=0.174\leq 1$. So the device is exclusion from SAR test.

For IC:

The 2.4GHz WLAN,BT,5GHz WLAN ,WWAN and 13.56MHz can transmit simultaneously, but the maximum rate of MPE is $0.056/2.68+0.010/2.68+0.035/4.53+0.282/1.16+0.0007/1000=0.276\leq 1$. So the device is exclusion from SAR test.

--End of the Report--