




Band Edges (802.11ax 40M-MIMO, CH54)




Band Edges (802.11ax 40M-MIMO, CH62)




Band Edges (802.11ax 40M-MIMO, CH102)




Band Edges (802.11ax 40M-MIMO, CH134)




Band Edges (802.11ax 80M-MIMO, CH42)





### Chongqing Academy of Information and Communication Technology


Address: No. 8, Yuma Road, Chayuan New City, Nan'an District, Chongqing, P. R. China, 401336  
 Tel: 0086-23-88069965 FAX: 0086-23-88608777



### Chongqing Academy of Information and Communication Technology

Address: No. 8, Yuma Road, Chayuan New City, Nan'an District, Chongqing, P. R. China, 401336  
 Tel: 0086-23-88069965 FAX: 0086-23-88608777

Secondary supply (S11 L15B1)



Note:

1. Only data in worst mode is provided.
2. Horizontal and vertical polarity is all have been tested, the result of them is synthesized in the above data diagram.

**Chongqing Academy of Information and Communication Technology**

Address: No. 8, Yuma Road, Chayuan New City, Nan'an District, Chongqing, P. R. China, 401336  
 Tel: 0086-23-88069965 FAX: 0086-23-88608777

### 6.8 Transmitter Spurious Emission

<b>Specifications:</b>	15.209 & 15.407(b)
<b>DUT Serial Number:</b>	S8 S11
<b>Test conditions:</b>	Ambient Temperature:20°C Relative Humidity:40% Air pressure: 90kPa
<b>Test Results:</b>	Pass

#### Limit Level Construction:

##### Below 1G

Frequency of emission (MHz)	Field strength(dBμV/m)	Measurement distance(m)
0.009-0.490	129-94	3
0.490-1.705	74-63	3
1.705-30	70	3
30-88	40.0	3
88-216	43.5	3
216-960	46.0	3
Above 960	54.0	3

Note: for frequency range below 960MHz, the limit in 15.209 is defined in 10m test distance. The limit used above is calculated from 10m to 3m.

##### Above 1G, non-restricted band

Standard	EIRP Limit
15.407(b)	-27dBm/MHz

##### Above 1G, Restricted band

Standard	EIRP Limit	
15.407(b)	-27dBm/MHz	
15.209	Peak	74dBμV/m
	Average	54dBμV/m

$$EIRP[dBm] = E[dB\mu V/m] + 20 \log(d[m]) - 104.7$$

$$E[dB\mu V/m] = EIRP[dBm] - 20 \log(d[m]) + 104.7$$

$$E[dB\mu V/m] = EIRP[dBm] + 95.2 = 68.2, \text{ for } d = 3m$$

#### Measurement Uncertainty:

### Chongqing Academy of Information and Communication Technology

Address: No. 8, Yuma Road, Chayuan New City, Nan'an District, Chongqing, P. R. China, 401336  
Tel: 0086-23-88069965 FAX:0086-23-88608777

Measurement Uncertainty	30MHz-1000MHz: 4.09 dB(MAX) (k=2). 1000MHz-6000MHz : 4.84 dB (k=2). 6000MHz-18000MHz : 4.52 dB (k=2). 18GHz-26.5GHz: 6.19 dB (k=2). 26.5GHz-40GHz: 6.03 dB (k=2).
-------------------------	---

**Test Procedure:**

The measurement is made according to KDB 789033

Set the spectrum analyzer in the following:

**Procedure for Unwanted Emissions Measurements below 1000 MHz:**

- a) Follow the requirements in II.G.3. "General Requirements for Unwanted Emissions Measurements."
- b) Compliance shall be demonstrated using CISPR quasi-peak detection; however, peak detection is permitted as an alternative to quasi-peak detection.

Detector: Peak and Quasi-Peak

RBW=100kHz / VBW=300kHz / Sweep=AUTO

**Procedure for Unwanted Maximum Emissions Measurements above 1000 MHz:**

- a) Follow the requirements in II.G.3, "General Requirements for Unwanted Emissions Measurements."
- b) Maximum emission levels are measured by setting the analyzer as follows:

(i) RBW = 1 MHz.

(ii) VBW  $\geq$  3 MHz.

(iii) Detector = Peak.

(iv) Sweep time = auto.

(v) Trace mode = max hold.

(vi) Allow sweeps to continue until the trace stabilizes. Note that if the transmission is not continuous, the time required for the trace to stabilize will increase by a factor of approximately 1/x, where x is the duty cycle. For example, at 50% duty cycle, the measurement time will increase by a factor of two relative to measurement time for continuous transmission.

**Procedures for Average Unwanted Emissions Measurements above 1000 MHz:**

- a) Follow the requirements in section II.G.3., "General Requirements for Unwanted Emissions Measurements."

**Chongqing Academy of Information and Communication Technology**

Address: No. 8, Yuma Road, Chayuan New City, Nan'an District, Chongqing, P. R. China, 401336  
Tel: 0086-23-88069965 FAX: 0086-23-88608777

**Report No.: I23W00036-WIFI 5G RF-FCC**

b) Average emission levels shall be measured using one of the following two methods.

c) Method AD (Average Detection): Primary method

(i) RBW = 1 MHz.

(ii) VBW  $\geq$  3 MHz.

(iii) Detector = power averaging (rms), if span/(# of points in sweep)  $\leq$  RBW/2. Satisfying this condition may require increasing the number of points in the sweep or reducing the span. If the condition is not satisfied, the detector mode shall be set to peak.

(iv) Averaging type = power averaging (rms)

As an alternative, the detector and averaging type may be set for linear voltage averaging. Some instruments require linear display mode in order to use linear voltage averaging. Log or dB averaging shall not be used.

(v) Sweep time = auto.

(vi) Perform a trace average of at least 100 traces if the transmission is continuous. If the transmission is not continuous, the number of traces shall be increased by a factor of 1/x, where x is the duty cycle. For example, with 50% duty cycle, at least 200 traces shall be averaged. (If a specific emission is demonstrated to be continuous—i.e., 100% duty cycle—rather than turning on and off with the transmit cycle, at least 100 traces shall be averaged.)

(vii) If tests are performed with the EUT transmitting at a duty cycle less than 98%, a correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100% duty cycle. The correction factor is computed as follows:

If power averaging (rms) mode was used in step (iv) above, the correction factor is  $10 \log (1/x)$ , where x is the duty cycle. For example, if the transmit duty cycle was 50%, then 3 dB must be added to the measured emission levels.

If linear voltage averaging mode was used in step (iv) above, the correction factor is  $20 \log (1/x)$ , where x is the duty cycle. For example, if the transmit duty cycle was 50%, then 6 dB must be added to the measured emission levels.

If a specific emission is demonstrated to be continuous (100% duty cycle) rather than turning on and off with the transmit cycle, no duty cycle correction is required for that emission.

Portable, small, lightweight, or modular devices that may be handheld, worn on the body, or placed on a table during operation shall be positioned on a non-conducting platform, the top of which is 80 cm above the

**Chongqing Academy of Information and Communication Technology**

Address: No. 8, Yuma Road, Chayuan New City, Nan'an District, Chongqing, P. R. China, 401336  
Tel: 0086-23-88069965 FAX: 0086-23-88608777



## Report No.: I23W00036-WIFI 5G RF-FCC

reference ground plane. The preferred area occupied by the EUT arrangement is 1 m by 1.5 m, For emissions testing at or below 1 GHz, the table height shall be 80 cm above the reference ground plane. For emission measurements above 1 GHz, the table height shall be 1.5 m. but it may be larger or smaller to accommodate various sized EUTs. For testing purposes, ceiling- and wall-mounted devices also shall be positioned on a tabletop (see also ANSI C63.10-2013 section 6.3.4 and 6.3.5). In making any tests involving handheld, body-worn, or ceiling-mounted equipment, it is essential to recognize that the measured levels may be dependent on the orientation (attitude) of the three orthogonal axes of the EUT. Thus, exploratory tests as specified in 8.3.1 shall be carried out for various axes orientations to determine the attitude having maximum or near-maximum emission level.

The EUT was placed on a non-conductive table. Below 18GHz , the measurement antenna was placed at a distance of 3 meters from the EUT. Above 18GHz , the measurement antenna was placed at a distance of 1 meter from the EUT. During the tests, the antenna height varied from 1m to 4m and the EUT azimuth were varied from 0° to 360° in order to identify the maximum level of emissions from the EUT. This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations.

Remark:

1. Factor= Antenna Factor + Cable Loss (-Amplifier, is employed)
2. Measured level= Original Receiver Reading + Factor
3. Margin = Limit – Measured level
4. If the PK measured level is lower than AV limit, the AV test can be elided

Note:


1. The out-of- limit signal in the picture is the main frequency signal.
2. Only data in worst mode is provided.
3. Sweep the whole frequency band through the range from 30MHz to the 10th harmonic of the carrier, the Emissions in the frequency band 18GHz-40GHz is more than 20dB below the limit are not report.
4. The test data below 30MHz is more than 20dB lower than the limit value, so it is not provided in the report.
5. Horizontal and vertical polarity is all have been tested, the result of them is synthesized in the above data diagram.

## Chongqing Academy of Information and Communication Technology


Address: No. 8,Yuma Road, Chayuan New City, Nan'an District, Chongqing, P. R. China,401336  
Tel: 0086-23-88069965 FAX:0086-23-88608777

### Test Setup


#### Below 30MHz Test Setup



#### Below 1GHz Test Setup



#### Above 1GHz Test Setup




## Chongqing Academy of Information and Communication Technology

Address: No. 8, Yuma Road, Chayuan New City, Nan'an District, Chongqing, P. R. China, 401336  
Tel: 0086-23-88069965 FAX: 0086-23-88608777


**Measurement Results:**

Mainly Supply (S8 L15A1)




**Chongqing Academy of Information and Communication Technology**

Address: No. 8, Yuma Road, Chayuan New City, Nan'an District, Chongqing, P. R. China, 401336  
 Tel: 0086-23-88069965 FAX: 0086-23-88608777



**Chongqing Academy of Information and Communication Technology**


Address: No. 8, Yuma Road, Chayuan New City, Nan'an District, Chongqing, P. R. China, 401336  
 Tel: 0086-23-88069965 FAX: 0086-23-88608777




**Chongqing Academy of Information and Communication Technology**

Address: No. 8, Yuma Road, Chayuan New City, Nan'an District, Chongqing, P. R. China, 401336  
 Tel: 0086-23-88069965 FAX: 0086-23-88608777


Radiated Spurious Emission  
(802.11n 20M-MIMO, ch36, 18GHz-26.5GHz)




Radiated Spurious Emission  
(802.11n 20M-MIMO, ch36, 26.5 GHz-40 GHz)




Radiated Spurious Emission  
(802.11n 20M-MIMO, ch52, 30MHz-1GHz)




Radiated Spurious Emission  
(802.11n 20M-MIMO, ch52, 1 GHz-8 GHz)









Radiated Spurious Emission  
(802.11n 20M-MIMO, ch52, 8GHz-18GHz)




Radiated Spurious Emission  
(802.11n 20M-MIMO, ch52, 18GHz-26.5GHz)





**Chongqing Academy of Information and Communication Technology**


Address: No. 8, Yuma Road, Chayuan New City, Nan'an District, Chongqing, P. R. China, 401336  
Tel: 0086-23-88069965 FAX: 0086-23-88608777



**Chongqing Academy of Information and Communication Technology**


Address: No. 8, Yuma Road, Chayuan New City, Nan'an District, Chongqing, P. R. China, 401336  
 Tel: 0086-23-88069965 FAX: 0086-23-88608777






**Chongqing Academy of Information and Communication Technology**


Address: No. 8, Yuma Road, Chayuan New City, Nan'an District, Chongqing, P. R. China, 401336  
 Tel: 0086-23-88069965 FAX: 0086-23-88608777




Radiated Spurious Emission  
(802.11ac 20M-MIMO, ch36, 18GHz-26.5GHz)




Radiated Spurious Emission  
(802.11ac 20M-MIMO, ch36, 26.5 GHz-40 GHz)




Radiated Spurious Emission  
(802.11ac 20M-MIMO, ch52, 30MHz-1GHz)




Radiated Spurious Emission  
(802.11ac 20M-MIMO, ch52, 1 GHz-8 GHz)




Radiated Spurious Emission  
(802.11ac 20M-MIMO, ch52, 8GHz-18GHz)




Radiated Spurious Emission  
(802.11ac 20M-MIMO, ch52, 18GHz-26.5GHz)




**Radiated Spurious Emission**  
(802.11ac 20M-MIMO, ch52, 26.5 GHz-40 GHz)




**Radiated Spurious Emission**  
(802.11ac 20M-MIMO, ch100, 30MHz-1GHz)




**Radiated Spurious Emission**  
(802.11ac 20M-MIMO, ch100, 1 GHz-8 GHz)




**Radiated Spurious Emission**  
(802.11ac 20M-MIMO, ch100, 8GHz-18GHz)




**Radiated Spurious Emission**  
(802.11ac 20M-MIMO, ch100, 18GHz-26.5GHz)



**Radiated Spurious Emission**  
(802.11ac 20M-MIMO, ch100, 26.5 GHz-40 GHz)





**Chongqing Academy of Information and Communication Technology**

Address: No. 8, Yuma Road, Chayuan New City, Nan'an District, Chongqing, P. R. China, 401336  
Tel: 0086-23-88069965 FAX: 0086-23-88608777