



# TEST REPORT

**No. I18D00233-EMC01**

*For*

**Client : Shanghai Sunmi Technology  
Co.,Ltd.**

**Production: Wireless data POS System**

**Model Name : T5921**

**Brand Name: SUNMI**

**FCC ID: 2AH25T5921**

**Hardware Version: QP1665\_MB\_PCB\_V1**

**Software Version: zqp1665\_V002\_181121**

**Issued date: 2019-01-10**

## NOTE

1. The test results in this test report relate only to the devices specified in this report.
2. This report shall not be reproduced except in full without the written approval of China Telecommunication Technology Labs.
3. The measurement uncertainty is not taken into account when deciding conformity, and the results of measurement (or the average of measurement results) are directly used as the criterion for the stating conformity.

**Test Laboratory:**

East China Institute of Telecommunications

Add: 7-8F, G Area, No.668, Beijing East Road, Huangpu District, Shanghai, P. R. China

Tel: +862163843300

FAX: +862163843301

E-Mail: [welcome@ecit.org.cn](mailto:welcome@ecit.org.cn)

**Revision Version**

<b>Report Number</b>	<b>Revision</b>	<b>Date</b>	<b>Memo</b>
I18D00233-EMC01	00	2019-01-10	Initial creation of test report

## CONTENTS

1. TEST LABORATORY .....	6
1.1. TESTING LOCATION .....	6
1.2. TESTING ENVIRONMENT .....	6
1.3. PROJECT DATA.....	6
1.4. SIGNATURE.....	6
2. CLIENT INFORMATION .....	7
2.1. APPLICANT INFORMATION.....	7
2.2. MANUFACTURER INFORMATION.....	7
3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE) .....	8
3.1. ABOUT EUT.....	8
3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST .....	8
3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST .....	8
4. REFERENCE DOCUMENTS.....	9
4.1. REFERENCE DOCUMENTS FOR TESTING .....	9
5. TEST RESULTS.....	10
5.1. SUMMARY OF TEST RESULTS.....	10
5.2. STATEMENTS.....	10
6. TEST EQUIPMENTS UTILIZED.....	11
6.1 RADIATED EMISSION EQUIPMENTS LIST.....	11
6.2 AC CONDUCTED EMISSION EQUIPMENTS LIST .....	11
7. SYSTEM CONFIGURATION DURING TEST.....	12
7.1 TEST MODE.....	12
7.2 CONNECTION DIAGRAM OF TEST SYSTEM.....	13
8. MEASUREMENT RESULTS.....	14
8.1 RADIATED EMISSION 30MHZ-18GHZ.....	14

**8.2 AC CONDUCTED EMISSION..... 18**

## 1. Test Laboratory

### 1.1. Testing Location

Company Name: ECIT Shanghai, East China Institute of Telecommunications  
Address: 7F, G Area, No. 668, Beijing East Road, Huangpu District, Shanghai,  
P. R. China  
Postal Code: 200001  
Telephone: 86-21-63843300  
Fax: 86-21-63843301  
FCC registration No: 958356


### 1.2. Testing Environment

Normal Temperature: 15-35°C  
Relative Humidity: 30-60%RH

### 1.3. Project data

Project Leader: Yu Anlu  
Testing Start Date: 2018-12-15  
Testing End Date: 2018-12-26


### 1.4. Signature



\_\_\_\_\_  
**Qin Yabin**  
(Prepared this test report)



\_\_\_\_\_  
**You Jinjun**  
(Reviewed this test report)



\_\_\_\_\_  
**Zheng Zhongbin**  
(Approved this test report)

## 2. Client Information

### 2.1. Applicant Information

Company Name: Shanghai Sunmi Technology Co.,Ltd.  
Address : Room 505, KIC Plaza, No.388 Song Hu Road, Yang Pu District,  
Shanghai, China  
Telephone: 18721763396  
Postcode: 200433

### 2.2. Manufacturer Information

Company Name: Shanghai Sunmi Technology Co.,Ltd.  
Address : Room 505, KIC Plaza, No.388 Song Hu Road, Yang Pu District,  
Shanghai, China  
Telephone: 18721763396  
Postcode: 200433

### 3. Equipment under Test (EUT) and Ancillary Equipment (AE)

#### 3.1. About EUT

EUT Description	Wireless data POS System
Model name	T5921
GSM Frequency Band	GSM850/GSM900/GSM1800/GSM1900
WCDMA Frequency Band	WCDMA BAND I / II / IV / V
CDMA Frequency Band	BC0/BC1
LTE Frequency Band	LTE BAND 2/4/7/17/28
Additional Communication Function	BT3.0,BLE, 4.2;WIFI 802.11a/b/g/n; NFC;

#### 3.2. Internal Identification of EUT used during the test

EUT ID*	SN or IMEI	HW Version	SW Version	Date of receipt
N07	/	QP1665_MB_PCB _V1	zqp1665_V002 _181121	2018-12-15

\*EUT ID: is used to identify the test sample in the lab internally.

#### 3.3. Internal Identification of AE used during the test

AE ID*	Description	Model	SN
CA07	Adapter	TPA-23A0502000UU01	/
UA05	USB Cable	/	/
AE1	Desktop PC	OptiPlex 790 DT	X8RP1 A01 APCC
AE2	Notebook PC	DELL Latitude E5250	/
AE3	LAN Cable	/	/
AE4	VGA Cable	/	/
AE5	RS232 Cable	/	/
AE6	Keyboard	KB212-B	CN-0Y88XT-65890-12I -005Q-A00
AE7	Mouse	MS111-P	CN-011D3V-71581-19 J-1A64
AE8	Monitor	Dell E1709Wc	/

\*AE ID: is used to identify the test sample in the lab internally.



## 4. Reference Documents

### 4.1. Reference Documents for testing

The following documents listed in this section are referred for testing.

Reference	Title	Version
FCC Part 15, Subpart B	Radio frequency devices	10-1-17 Edition
ANSI C63.4	Method of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz	2014

## 5. Test Results

### 5.1. Summary of Test Results

Items	Test List	Clause in FCC rules	Verdict
1	Radiated Emission	15.109(a)	Pass
2	AC Conducted Emission	15.107(a)	Pass

### 5.2. Statements

The Wireless data POS System, supporting GSM/WCDMA/LTE.etc, manufactured by Shanghai Sunmi Technology Co.,Ltd..a new product for testing. ECIT performed test cases which identified with Pass/Fail/Inc result in section 5.1.

ECIT has verified that the compliance of the tested device specified in section 3 of this test report is successfully evaluated according to the procedure and test methods as defined in type certification requirement listed in section 4 of this test report.

## 6. Test Equipments Utilized

### 6.1 Radiated Emission Equipments list

No.	Name	Type	Series Number	Producer	Cal. Date	Cal. interval
1	Universal Radio Communication	CMU200	123126	R&S	2018-05-11	1 Year
2	Test Receiver	ESU40	100307	R&S	2018-05-11	1 Year
3	Trilog Antenna	VULB9163	VULB9163-515	Schwarzbeck	2017-02-25	3 Year
4	Double Ridged Guide	ETS-3117	00135890	ETS	2017-01-11	3 Year
5	EMI Test Software	EMC32 V9.15	NA	R&S	NA	NA

### 6.2 AC Conducted Emission Equipments list


No.	Name	Type	Series Number	Producer	Cal. Date	Cal. interval
1	Universal Radio	CMU200	123123	R&S	2018-05-11	1 Year
2	Test Receiver	ESCI	101235	R&S	2018-05-11	1 Year
3	2-Line V-Network	ENV216	101380	R&S	2018-05-11	1 Year
4	EMI Test Software	EMC32 V10.35.02	NA	R&S	NA	NA

## 7. System Configuration during Test


### 7.1 Test Mode

Test Item	Function Type
AC Conducted Emission	Mode 1: USB cable (Data Link with PC) <Figure 1> Mode 2: Adapter charging <Figure 2>
Radiated Emission	Mode 1: USB cable (Data Link with PC) <Figure 1> Mode 2: Adapter charging <Figure 2>
Remark: 1. All test modes are performed, only the worst cases test data are recorded in this report. 2. Data Link with PC means data application transferred mode between EUT and PC.	

### 7.2 Connection Diagram of Test System



<Figure 1>



<Figure 2>

## 8. Measurement Results

Only the worst test result was shown in this report.

### 8.1 Radiated Emission 30MHz-18GHz

#### Method of Measurement

For 30MHz -1000MHz, the EUT was placed on the top of a rotating 0.8-m table above the ground at a semi-anechoic chamber. The distance between the EUT and the received antenna was 3 meters. The table was rotated 360 degree and the received antenna mounted on a variable-height antenna tower was varied from 1m to 4m to find the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna were set during the measurement. Tested in accordance with the procedures of ANSI C63.4-2014, section 8.3.

For 1000MHz -18000MHz, The maximal emission value was acquired by adjusting the antenna height, The table was rotated 360 degree to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna were set during the measurement.

#### Limits for Radiated Emission at a measuring distance of 3m

Frequency Range (MHz)	Quasi-Peak (dBuV/m)
30-88	40
88-216	43.5
216-960	46
Above 960	54

Frequency Range (MHz)	Peak (dBuV/m)	Average (dBuV/m)
Above 1000	74	54

#### Test conditions

Frequency Range (MHz)	RBW/VBW	Sweep Time (s)
30-1000	120kHz/300kHz	Auto
1000-18000	1MHz/3MHz	Auto


#### Uncertainty Measurement

The measurement uncertainty is 4.98dB (30MHz -1000MHz) and 5.06dB (1GHz -18GHz) (k=2)

## Test Results

Mode 1: USB cable (Data Link with PC)

Frequency Range: 30MHz – 1GHz



## Final\_Result

Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (s)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
34.508675	12.73	40.00	27.27	1000.0	120.000	100.0	V	141.0	-22.0
66.457611	25.84	40.00	14.16	1000.0	120.000	175.0	H	-27.0	-24.1
67.653245	20.37	40.00	19.63	1000.0	120.000	225.0	H	-20.0	-24.4
232.430392	24.57	46.00	21.43	1000.0	120.000	104.0	H	20.0	-23.6
398.646245	18.45	46.00	27.55	1000.0	120.000	218.0	H	7.0	-19.4
479.981373	26.63	46.00	19.37	1000.0	120.000	196.0	V	-28.0	-17.6


Note:

1. Emission level(QP)=Raw value by receiver + Corr(Antenna factor + cable loss - preamplifier gain)
2. The raw value is used to calculate by software which is not shown in the sheet.
3. Margin=limit value – emission level.

Mode 1: USB cable (Data Link with PC)

Frequency Range:

1GHz –18GHz, Horizontal



### Final Result

Frequency (MHz)	MaxPeak (dBuV/m)	Average (dBuV/m)	Limit (dBuV/m)	Margin	Meas. Time	Bandwidth	Height	Po	Azimuth	Corr. (dB)
14100.400000	54.20	---	74.00	19.80	100.0	1000.000	100.0	H	340.0	19.3
14100.400000	---	42.18	54.00	11.82	100.0	1000.000	100.0	H	340.0	19.3
14997.200000	---	42.26	54.00	11.74	100.0	1000.000	200.0	H	6.0	20.2
14997.200000	55.35	---	74.00	18.65	100.0	1000.000	200.0	H	6.0	20.2
15457.400000	---	42.40	54.00	11.60	100.0	1000.000	100.0	H	122.0	21.2
15457.400000	54.48	---	74.00	19.52	100.0	1000.000	100.0	H	122.0	21.2
16081.800000	---	44.60	54.00	9.40	100.0	1000.000	200.0	H	130.0	22.5
16081.800000	56.85	---	74.00	17.15	100.0	1000.000	200.0	H	130.0	22.5
17095.800000	---	44.66	54.00	9.34	100.0	1000.000	100.0	H	214.0	24.0
17095.800000	56.61	---	74.00	17.39	100.0	1000.000	100.0	H	214.0	24.0


Note:

1. Emission level(peak or average)=Raw value by receiver + Corr(Antenna factor+ cable loss - preamplifier gain)
2. The raw value is used to calculate by software which is not shown in the sheet.
3. Margin=limit value – emission level.



Frequency Range:

1GHz –18GHz, Vertical



### Final Result

Frequency (MHz)	MaxPeak (dBuV/m)	Average (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Meas. Time	Bandwidth (h)	Height (t)	Po (l)	Azimuth	Corr. (dB)
13709.800000	54.35	---	74.00	19.65	100.0	1000.000	100.0	V	27.0	18.8
13709.800000	---	42.43	54.00	11.57	100.0	1000.000	100.0	V	27.0	18.8
15038.800000	54.10	---	74.00	19.90	100.0	1000.000	200.0	V	0.0	20.4
15038.800000	---	42.00	54.00	12.00	100.0	1000.000	200.0	V	0.0	20.4
15981.000000	56.72	---	74.00	17.28	100.0	1000.000	100.0	V	110.0	22.2
15981.000000	---	44.02	54.00	9.98	100.0	1000.000	100.0	V	110.0	22.2
16293.200000	55.78	---	74.00	18.22	100.0	1000.000	100.0	V	91.0	22.6
16293.200000	---	43.49	54.00	10.51	100.0	1000.000	100.0	V	91.0	22.6
17023.800000	57.00	---	74.00	17.00	100.0	1000.000	100.0	V	318.0	23.8
17023.800000	---	44.81	54.00	9.19	100.0	1000.000	100.0	V	318.0	23.8
17785.400000	55.74	---	74.00	18.26	100.0	1000.000	100.0	V	110.0	24.3
17785.400000	---	43.63	54.00	10.37	100.0	1000.000	100.0	V	110.0	24.3

Note:

1. Emission level(peak or average)=Raw value by receiver + Corr(Antenna factor+ cable loss - preamplifier gain)
2. The raw value is used to calculate by software which is not shown in the sheet.
3. Margin=limit value – emission level.

## 8.2 AC Conducted Emission

### Method of Measurement

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies with the band 150 kHz to 30MHz shall not exceed the limits. Both lines of the power mains connected to the EUT were checked for maximum conducted interference. Tested in accordance with the procedures of ANSI C63.4-2014, section 7.3

### Limit of AC Conducted Emission

Frequency Range (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency

### Test Condition in Charging Mode

Voltage (V)	Frequency (Hz)	RBW	Sweep Time (s)
120	60	9 kHz	Auto


### Uncertainty Measurement

The measurement uncertainty is 3.66dB (k=2).

### Test Results

Mode 2: Adapter charging

Frequency Range: 150kHz – 30MHz



Frequency (MHz)	QuasiPeak (dBµ V)	Average (dBµ V)	Limit (dBµ V)	Margin (dB)	Meas. Time	Bandwidth (kHz)	Line	Filter	Corr. (dB)
0.388800	41.72	---	58.09	16.37	1000.0	9.000	N	ON	9.7
0.388800	---	28.57	48.09	19.52	1000.0	9.000	N	ON	9.7
0.586556	46.47	---	56.00	9.53	1000.0	9.000	L1	ON	9.7
0.586556	---	36.28	46.00	9.72	1000.0	9.000	L1	ON	9.7
0.642525	45.73	---	56.00	10.27	1000.0	9.000	L1	ON	9.7
0.642525	---	36.22	46.00	9.78	1000.0	9.000	L1	ON	9.7
1.179825	37.40	---	56.00	18.60	1000.0	9.000	L1	ON	9.7
1.179825	---	27.91	46.00	18.09	1000.0	9.000	L1	ON	9.7
2.105175	36.43	---	56.00	19.57	1000.0	9.000	L1	ON	9.7
2.105175	---	25.59	46.00	20.41	1000.0	9.000	L1	ON	9.7
3.284250	36.60	---	56.00	19.40	1000.0	9.000	L1	ON	9.7
3.284250	---	25.29	46.00	20.71	1000.0	9.000	L1	ON	9.7

Note:

1. Emission level(quasi-peak or Average peak)=Raw value by receiver + Corr(Insertion loss+ cable loss)
2. The raw value is used to calculate by software which is not shown in the sheet.
3. Margin=limit value – emission level.
4. L1 and N line is all have been tested, the result of them is synthesized in the above data diagram.

\*\*\*\*\*END OF REPORT\*\*\*\*\*