



No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan
District Shenzhen, China 518057

Telephone: +86 (0) 755 2601 2053
Fax: +86 (0) 755 2671 0594
Email: ee.shenzhen@sgs.com

Report No.: SZEM160300137401
Page: 1 of 20

FCC Test Report

Application No.: SZEM1603001374PS
Applicant: TURISPORT SL (miniBatt Europe)
Manufacturer: TURISPORT SL (miniBatt Europe)
Factory: Shenzhen Canpow Technology Co., Ltd
Equipment Under Test (EUT):
EUT Name: Wireless Charger Medium Power
Model No.: FI80
Trade Mark: MINIBATT
FCC ID: 2AH26-MINIBATT-FI80
Standards: 47 CFR PART 18: 2015
Date of Receipt: 2016-03-30
Date of Test: 2016-05-03 to 2016-05-04
Date of Issue: 2016-05-17

Test Result :	PASS*
----------------------	--------------

* In the configuration tested, the EUT detailed in this report complied with the standards specified above.

Authorized Signature:



Jack Zhang
EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only



**SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch**

Report No.: SZEM160300137401

Page: 2 of 20

2 Test Summary

Test	Test Requirement	Test Method	Class / Severity	Result
Conducted Emission (150 kHz to 30 MHz)	47 CFR PART 18: 2015	FCC OST/ MP-5:1986	18.307(a)	Pass
Radiated Emission (9 kHz to 30MHz)	47 CFR PART 18: 2015	FCC OST/ MP-5:1986	18.305(b)	Pass



3 Contents

	Page
1 COVER PAGE	1
2 TEST SUMMARY	2
3 CONTENTS	3
4 GENERAL INFORMATION.....	4
4.1 CLIENT INFORMATION.....	4
4.2 GENERAL DESCRIPTION OF EUT.....	4
4.3 DESCRIPTION OF SUPPORT UNITS.....	4
4.4 DETAILS OF TEST MODE.....	4
4.5 TEST LOCATION.....	5
4.6 TEST FACILITY.....	5
4.7 DEVIATION FROM STANDARDS.....	5
4.8 ABNORMALITIES FROM STANDARD CONDITIONS.....	5
5 EQUIPMENT LIST.....	6
6 TEST RESULTS	8
6.1 CONDUCTED EMISSIONS.....	8
6.2 RADIATED EMISSIONS.....	12
7 PHOTOGRAPHS.....	16
7.1 CONDUCTED EMISSION TEST SETUP.....	16
7.2 RADIATED EMISSION TEST SETUP.....	16
7.3 EUT CONSTRUCTIONAL DETAILS.....	17-20



4 General Information

4.1 Client Information

Applicant:	TURISPORT SL (miniBatt Europe)
Address of Applicant:	Avda. Sant Julià 159-167 Nave 2, Pol. Ind. EL Congost 08403 Granollers (Barcelona), SPAIN, VAT: ESB-08882151
Manufacturer:	TURISPORT SL (miniBatt Europe)
Address of Manufacturer:	Avda. Sant Julià 159-167 Nave 2, Pol. Ind. EL Congost 08403 Granollers (Barcelona), SPAIN, VAT: ESB-08882151
Factory:	Shenzhen Canpow Technology Co., Ltd,
Address of Factory:	4th floor of building B,Hongshengyuan Industry Zone, No.339 Bulong Road, Bantian Town, Longgang District, Shenzhen,China.

4.2 General Description of EUT

Product Name:	Wireless Charger Medium Power
Model No.:	Fi80
Trade Mark:	MINIBATT
Sample Type:	wireless charging transmitter
Operation Frequency:	110-205kHz
Antenna Type	Loop antenna
Power Supply:	DC 5V from USB port

4.3 Description of Support Units

The EUT has been tested with associated equipment below.

Description	Manufacturer	Model No.
Adapter	Apple	A1357 W010A051
Mobile phone	Xiaomi	MI2A
Adapter	Provided by client	N/A
DC Electronic load	Provided by Client	10W

4.4 Details of Test Mode

mode 1	Normal operation(5W load)
mode 2	Normal operation(10W load)



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM160300137401
Page: 5 of 20

4.5 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch E&E Lab,

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China.
518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

4.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L2929)**

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

- **VCCI**

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-823, R-4188, T-1153 and C-2383 respectively.

- **FCC – Registration No.: 556682**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 556682.

- **Industry Canada (IC)**

Two 3m Semi-anechoic chambers and the 10m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1, 4620C-2, 4620C-3.

4.7 Deviation from Standards

None.

4.8 Abnormalities from Standard Conditions

None.



**SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch**

Report No.: SZEM160300137401
Page: 6 of 20

5 Equipment List

Conducted Emission						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. date (yyyy-mm-dd)	Cal.Due date (yyyy-mm-dd)
1	Shielding Room	ZhongYu Electron	GB-88	SEM001-06	2016-05-13	2017-05-13
2	LISN	Rohde & Schwarz	ENV216	SEM007-01	2015-10-09	2016-10-09
3	LISN	ETS-LINDGREN	3816/2	SEM007-02	2016-04-25	2017-04-25
4	8 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN-T8-02	EMC0120	2015-08-30	2016-08-30
5	4 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN-T4-02	EMC0121	2015-08-30	2016-08-30
6	2 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN-T2-02	EMC0122	2015-08-30	2016-08-30
7	EMI Test Receiver	Rohde & Schwarz	ESCI	SEM004-02	2016-04-25	2017-04-25

RE in Chamber						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. date (yyyy-mm-dd)	Cal.Due date (yyyy-mm-dd)
1	10m Semi-Anechoic Chamber	SAEMC	FSAC1018	SEM001-03	2015-08-01	2016-08-01
2	EMI Test Receiver (9k-3GHz)	Rohde & Schwarz	ESCI	SEM004-01	2016-04-25	2017-04-25
3	Trilog-Broadband Antenna(30M-1GHz)	Schwarzbeck	VULB9168	SEM003-17	2016-01-26	2017-01-26
4	Pre-amplifier	Sonoma Instrument Co	310N	SEM005-03	2016-04-25	2017-04-25
5	Loop Antenna	Beijing Daze	ZN30401	SEM003-09	2015-05-13	2018-05-13



**SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch**

Report No.: SZEM160300137401

Page: 7 of 20


General used equipment						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. date (yyyy-mm-dd)	Cal.Due date (yyyy-mm-dd)
1	Humidity/ Temperature Indicator	Shanghai Meteorological Industry Factory	ZJ1-2B	SEM002-03	2015-10-12	2016-10-12
2	Humidity/ Temperature Indicator	Shanghai Meteorological Industry Factory	ZJ1-2B	SEM002-04	2015-10-12	2016-10-12
3	Humidity/ Temperature Indicator	Mingle	N/A	SEM002-08	2015-10-12	2016-10-12
4	Barometer	Changchun Meteorological Industry Factory	DYM3	SEM002-01	2015-05-13	2016-05-13



6 Test Results

6.1 Conducted Emissions

Test Requirement:	47 CFR PART 18		
Test Frequency Range:	150kHz to 30MHz		
Limit:	Frequency range (MHz)	Limit (dBuV)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
* Decreases with the logarithm of the frequency.			
Test Procedure:	<ol style="list-style-type: none"> 1) The mains terminal disturbance voltage test was conducted in a shielded room. 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50Ω/50μH + 5Ω linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded. 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane, 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2. 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed on conducted measurement. 		

<p>Test Setup:</p>	
<p>Test Mode:</p>	<p>Wireless charge mode. Mode 1 & 2. The worst case (Mode 2) is reported only.</p>
<p>Instruments Used:</p>	<p>Refer to section 5 for details</p>
<p>Test Results:</p>	<p>Pass</p>

Measurement Data

An initial pre-scan was performed on the live and neutral lines with peak detector.


Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.



**SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch**

Report No.: SZEM160300137401
Page: 10 of 20

Live Line: Mode 2



Site : Shielding Room
Condition : CE LINE
Job.No : 1374PS
Mode : 2


	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.17772	0.02	9.60	26.90	36.52	64.59	-28.07	QP
2	0.17772	0.02	9.60	16.20	25.82	54.59	-28.77	Average
3 @	0.54068	0.01	9.60	24.80	34.41	46.00	-11.59	Average
4	0.54068	0.01	9.60	29.70	39.31	56.00	-16.69	QP
5	0.94809	0.02	9.62	23.50	33.14	56.00	-22.86	QP
6	0.94809	0.02	9.62	16.50	26.14	46.00	-19.86	Average
7	2.596	0.02	9.62	20.30	29.94	46.00	-16.06	Average
8	2.596	0.02	9.62	32.30	41.94	56.00	-14.06	QP
9 @	4.900	0.01	9.65	39.90	49.56	56.00	-6.44	QP
10 @	4.900	0.01	9.65	28.30	37.96	46.00	-8.04	Average
11	7.446	0.01	9.68	37.70	47.39	60.00	-12.61	QP
12	7.446	0.01	9.68	23.70	33.39	50.00	-16.61	Average



**SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch**

Report No.: SZEM160300137401
Page: 11 of 20


Neutral Line:



Site : Shielding Room
Condition : CE NEUTRAL
Job.No : 1374PS
Mode : 2

	Freq	Cable Loss	LISN Factor	Read Level	Limit Level	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dB	
1	0.16155	0.02	9.61	30.30	39.93	65.38	-25.46 QP
2	0.16155	0.02	9.61	16.20	25.83	55.38	-29.56 Average
3	0.40831	0.01	9.62	23.20	32.83	57.68	-24.85 QP
4	0.40831	0.01	9.62	17.20	26.83	47.68	-20.85 Average
5	0.54644	0.01	9.63	27.80	37.44	56.00	-18.56 QP
6	0.54644	0.01	9.63	17.70	27.34	46.00	-18.66 Average
7	3.346	0.02	9.67	28.60	38.29	56.00	-17.71 QP
8	3.346	0.02	9.67	14.90	24.59	46.00	-21.41 Average
9	4.874	0.01	9.72	33.50	43.23	56.00	-12.77 QP
10	4.874	0.01	9.72	22.30	32.03	46.00	-13.97 Average
11	7.687	0.01	9.75	34.00	43.76	60.00	-16.24 QP
12	7.687	0.01	9.75	23.50	33.26	50.00	-16.74 Average

6.2 Radiated Emissions

Test Requirement:	47 CFR PART 18			
Test Site:	Measurement Distance: 10m (Semi-Anechoic Chamber)			
Receiver Setup:	Frequency	Detector	RBW	VBW
	9kHz~150kHz	Quasi-peak	200Hz	≥RBW
	150kHz~30MHz	Quasi-peak	9kHz	≥RBW
	30MHz~1GHz	Quasi-peak	100kHz	≥RBW
Limit:	Frequency	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009-30MHz	53.0	Quasi-peak	10
	30MHz-88MHz	40.0	Quasi-peak	3
	88MHz-216MHz	43.5	Quasi-peak	3
	216MHz-1000MHz	46.0	Quasi-peak	3
Remark:According to the article 18.305(b), The operating frequency is non-ISM frequency;the RF Power generated by equipment is below 500(watts); According to the clause 18.305(c), the EUT belongs to Consumer equipment.				
Test Setup:				
				
Figure 1. Below 30MHz				
Test Procedure:	<p>a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10 meter semi-anechoic chamber(30MHz-1000MHz) and 10 meter semi-anechoic chamber(9kHz-30MHz). The table was rotated 360 degrees to determine the position of the highest radiation.</p> <p>b. The EUT was set 10 meters(30MHz-1000MHz) and 10 meter(9kHz-30MHz) away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</p> <p>c. Above 30MHz:The Analyzer/Receiver scanned from 30MHz to 1000MHz.The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</p> <p>d. Below 30MHz: The Analyzer/Receiver scanned from 9kHz to 30MHz.The antenna height is 2 meters above the ground to determine the maximum value of the field strength.</p>			



**SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch**

Report No.: SZEM160300137401

Page: 13 of 20


	<p>e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 2 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.</p> <p>f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</p> <p>g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</p> <p>h. Repeat above procedures until all frequencies measured was complete.</p> <p>i. Measurement Requirement: According to the clause 18.305(c)notes 2. At frequencies at or above 30MHz: $Limit_{3m}(dBuV) = Limit_{xm}(dBuV) + 20\log(xm/3m)$ At frequencies below 30MHz: $Limit_{10m}(dBuV) = Limit_{xm}(dBuV) + 20\log(xm/3m)$ Remark: x replace the number 10,30,300.</p>
Test Mode:	Wireless charge mode. Mode 1 & 2 . The worst case (mode 2) is reported only.
Instruments Used:	Refer to section 5 for details
Test Results:	Pass



**SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch**

Report No.: SZEM160300137401
Page: 14 of 20

0.009MHz-30MHz




Condition: 10m
Job No. : 1374PS
Test Mode: TX mode

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	0.01	0.30	21.80	32.08	53.24	43.26	53.06	-9.80
2	0.02	0.22	17.21	32.49	56.80	41.74	53.06	-11.32
3	0.02	0.19	15.89	32.50	55.63	39.21	53.06	-13.85
4	0.04	0.15	13.80	32.50	57.36	38.81	53.06	-14.25
5	0.06	0.10	12.79	32.51	55.49	35.87	53.06	-17.19
6	0.10	0.05	12.98	32.52	53.38	33.89	53.06	-19.17



**SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch**

Report No.: SZEM160300137401
Page: 15 of 20



Condition: 10m
Job No. : 1374PS
Test Mode: TX mode

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	0.15	0.07	12.80	32.50	64.15	44.52	53.06	-8.54
2	0.28	0.09	12.74	32.52	58.95	39.26	53.06	-13.80
3	0.39	0.10	12.61	32.51	57.68	37.88	53.06	-15.18
4	0.97	0.23	12.78	32.45	51.95	32.51	53.06	-20.55
5	1.79	0.32	12.55	32.46	47.38	27.79	53.06	-25.27
6	22.90	0.71	10.32	32.53	39.13	17.63	53.06	-35.43

Remark:

1:The loop antenna rotated about both Vertical and Horizontal to find the maximum emission,So only the worst position(Horizontal) was report.

2:According to the clause 2.3 of MP-5:1986, the highest frequency is 205kHz, So the Range of frequency measurements is 9kHz to 30MHz.


7 Photographs

Test Model No.: Fi80

7.1 Conducted Emission Test Setup



7.2 Radiated Emission Test Setup



7.3 EUT Constructional Details



