INGICS TECHNOLOGY CO., LTD. 1F., No.22, Aly. 2, Ln. 253, Jinmen St., Banqiao Dist., New Taipei City 22071, Taiwan

Federal Communications Commission Authorization and Evaluation Division Equipment Authorization Branch 7435 Oakland Mills Road Columbia, MD 21046

Applicant's declaration concerning RF Radiation Exposure

We hereby indicate that the product Product description: BLE-WiFi Gateway

Model No: iGS01

The equipment complies with FCC RF radiation exposure limits set forth for an uncontrolled environment. The integral antennas used for this transmitter must not be co-located or operating in conjunction with any other antenna or transmitter within the host device.

A safety statement concerning minimum separation distances from enclosure of the Product: BLE-WiFi Gateway

will be integrated in the user's manual to provide end-users with transmitter operating conditions for satisfying RF exposure compliance.

The appropriate information can be drawn from the test report no: W6M21602-15593-C-1 and the accompanying calculations.

Company: INGICS TECHNOLOGY CO., LTD.

Address: 1F., No.22, Aly. 2, Ln. 253, Jinmen St., Banqiao Dist.,

New Taipei City 22071, Taiwan

Date: 2016-04-22

Signature: A. Jan

Registration number: W6M21602-15593-C-1

FCC ID: 2AH2IIGS01

3.2 Equivalent isotropic radiated power

FCC Rule: 15.247(b)(3)

max. conducted output power = 15.13 dBm

Limit: EIRP = +36 dBm for Antenna gain < 6dBi

Test equipment used: ETSTW-RE 055

3.3 RF Exposure Compliance Requirements

FCC OET Bulletin 65 Edition 97.01 determines the equations for predicting RF fields and applicable limits.

The prediction for power density in the far-field but will over-predict power density in the near field, where it could be used for walking a "worst case" or conservative prediction.

S – Power Density

P – Output power ERP

R-Distance

D – Cable Loss

AG – Antenna Gain

Item	Unit	Value	Remarks
P	mW	32.5837	Peak value
D	dB		
AG	dBi	2	
G		1.5849	Calculated Value
R	cm	20	Assumed value
S	mW/cm ²	0.0103	Calculated value

Limits:

Limit for General Population / Uncontrolled Exposure			
Frequency (MHz)	Power Density (mW/cm ²)		
1500 – 100.000	1.0		