# INGICS TECHNOLOGY CO., LTD. 2F., No.15-2, Changshou St., Shulin Dist., New Taipei City 238 Taiwan

Federal Communications Commission Authorization and Evaluation Division Equipment Authorization Branch 7435 Oakland Mills Road Columbia, MD 21046

## Applicant's declaration concerning RF Radiation Exposure

We hereby indicate that the product Product description: BLE-WiFi Gateway

Model No: iGS01S

The equipment complies with FCC RF radiation exposure limits set forth for an uncontrolled environment. The integral antennas used for this transmitter must not be co-located or operating in conjunction with any other antenna or transmitter within the host device.

A safety statement concerning minimum separation distances from enclosure of the Product: BLE-WiFi Gateway will be integrated in the user's manual to provide end-users with transmitter operating conditions for satisfying RF exposure compliance.

The appropriate information can be drawn from the test report no: W6M21803-17914-C-1 and the accompanying calculations.

Company: INGICS TECHNOLOGY CO., LTD.

A. K. Jan

Address: 2F., No.15-2, Changshou St., Shulin Dist., New Taipei City 238 Taiwan

Date: 2018-04-11

Signature

Registration number: W6M21803-17914-C-1

FCC ID: 2AH2IIGS01S IC: 21379-IGS01S

### 3.2 Equivalent isotropic radiated power

FCC Rule: 15.247(b)(3)

EIRP = max. conducted output power+Antenna gian

EIRP = 15.15 dBm + 2.11 dBi = 17.26 dBm

Limit: EIRP = +36 dBm for Antenna gain < 6 dBi

Test equipment used: ETSTW-RE 055

### 3.3 RF Exposure Compliance Requirements

FCC OET Bulletin 65 Edition 97.01 determines the equations for predicting RF fields and applicable limits.

The prediction for power density in the far-field but will over-predict power density in the near field, where it could be used for walking a "worst case" or conservative prediction.

$$S = \frac{PG}{4 \pi R^2}$$

S – Power Density

P – Output power ERP

R – Distance

D – Cable Loss

AG – Antenna Gain

Item	Unit	Value	Remarks
P	mW	32.7341	Peak value
D	dB		
AG	dBi	2.11	
G		1.6255	Calculated Value
R	cm	20	Assumed value
S	mW/cm <sup>2</sup>	0.0106	Calculated value

#### Limits:

Limit for General Population / Uncontrolled Exposure			
Frequency (MHz)	Power Density (mW/cm <sup>2</sup> )		
1500 – 100.000	1.0		