



SAR Exemption Evaluation Report

Product Name : GEYE REMOTE
Model No. : 8387342, 117832, 2224490
FCC ID : 2AH2PGERE17BL

Applicant : DECATHLON USA LLC
Address : 2415 3rd Street, Suite 231
San Francisco
94107, California
United States of America

Date of Receipt : Jul. 13, 2017
Issued Date : Jul. 18, 2018
Report No. : 1772086R-RF-US-P20V02
Report Version : V3.1

The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standard through the calibration of the equipment and evaluated measurement uncertainty herein.

This report must not be used to claim product endorsement by TAF, A2LA or any agency of the government.

The test report shall not be reproduced without the written approval of DEKRA Testing & Certification (Suzhou) Co., Ltd.

Test Report Certification

Issued Date : Jul. 18, 2018

Report No. : 1772086R-RF-US-P20V02





Product Name : GEYE REMOTE
Applicant : DECATHLON USA LLC


Address : 2415 3rd Street, Suite 231
San Francisco
94107, California
United States of America

Manufacturer : DECATHLON SA
Address : 4 Boulevard de Mons- 59650 Villeneuve D'Ascq-FRANCE
Model No. : 8387342, 117832, 2224490
FCC ID : 2AH2PGERE17BL
Brand Name : Decathlon
EUT Voltage : DC 3.7V
Test Voltage : DC 3.7V
Applicable Standard : KDB 447498D01V06
FCC Part1.1310

Test Result : Complied
Performed Location : DEKRA Testing & Certification (Suzhou) Co., Ltd.
No.99 Hongye Rd., Suzhou Industrial Park, Suzhou, 215006,
Jiangsu, China
TEL: +86-512-6251-5088 / FAX: +86-512-6251-5098
FCC Designation Number: CN1199

Documented By : 
(Adm. Specialist: Kathy Feng)

Reviewed By : 
(Senior Engineer: Jack Zhang)

Approved By : 
(Engineering Manager: Harry Zhao)

1. RF Exposure Evaluation

1.1.Limits

According to **KDB 447498 D01 General RF Exposure Guidance v06**

4.3.1 Standalone SAR test exclusion considerations

1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

2) At 100 MHz to 6 GHz and for test separation distances > 50 mm, the SAR test exclusion threshold is determined according to the following, and as illustrated in Appendix B:

- a) $[\text{Power allowed at numeric threshold for 50 mm in step 1}) + (\text{test separation distance} - 50 \text{ mm}) \cdot (f(\text{MHz})/150)] \text{ mW, at 100 MHz to 1500 MHz}$
- b) $[\text{Power allowed at numeric threshold for 50 mm in step 1}) + (\text{test separation distance} - 50 \text{ mm}) \cdot 10] \text{ mW at } > 1500 \text{ MHz and } \leq 6 \text{ GHz}$

3) The 1-g and 10-g SAR test exclusion thresholds for below 100 MHz at test separation distances ≤ 50 mm are determined by:

- a) The power threshold at the corresponding test separation distance at 100 MHz in step 2) is multiplied by $[1 + \log(100/f(\text{MHz}))]$ for test separation distances > 50 mm and < 200 mm
- b) The power threshold determined by the equation in a) for 50 mm and 100 MHz is multiplied by $\frac{1}{2}$ for test separation distances ≤ 50 mm
- c) SAR measurement procedures are not established below 100 MHz. When SAR test exclusion cannot be applied, a KDB inquiry is required to determine SAR evaluation requirements for any test results to be acceptable. Note: when the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

1.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 18°C and 78% RH.

1.3. Test Result of RF Exposure Evaluation

Product Name	:	GEYE REMOTE
Test Item	:	RF Exposure Evaluation
Test Site	:	AC-6

● Antenna Gain:

Model No.		N/A								
Antenna manufacturer		N/A								
Antenna Delivery		<input checked="" type="checkbox"/>	1*TX+1*RX		<input type="checkbox"/>	2*TX+2*RX		<input type="checkbox"/>	3*TX+3*RX	
Antenna technology		<input checked="" type="checkbox"/>	SISO							
		<input type="checkbox"/>	MIMO	<input type="checkbox"/>	Basic					
				<input type="checkbox"/>	CDD					
				<input type="checkbox"/>	Sectorized					
				<input type="checkbox"/>	Beam-forming					
Antenna Type		<input type="checkbox"/>	External	<input type="checkbox"/>	Dipole					
				<input type="checkbox"/>	Sectorized					
		<input checked="" type="checkbox"/>	Internal	<input type="checkbox"/>	PIFA					
				<input type="checkbox"/>	PCB					
				<input type="checkbox"/>	Ceramic Chip Antenna					
				<input checked="" type="checkbox"/>	Monopole Antenna					
		Antenna Technology		Ant Gain (dBi)						
<input checked="" type="checkbox"/>	SISO	0								

Based on The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm and the formula below:

$$\text{Estimated SAR} = \sqrt{f(\text{GHz})} * \frac{(\text{Max Power of channel, mW})}{\text{Min. Separation Distance, mm}}$$

Band	Exposure Condition	Pmax	Pmax	Distance	f(GHz)	calculation result	Stand-alone Test exclusion threshold	SAR Test
		(dBm)	(mw)	(mm)				
BT	limb	4.75	2.985	5	2.402	0.925	7.50	No

Conclusion: 2402MHz-2480MHz SAR was not required.

_____ The End _____