



Telecommunication Certification Body
UL VS Ltd
Unit 3, Horizon
Wade Road
Kingsland Business Park
Basingstoke, Hampshire
RG24 8AH
United Kingdom

September 19th, 2019

FCC ID: 2AH88-785

Subject: **RF Exposure Analysis**

To Whom it may concern:

Analysis for FCC portable use

Standalone SAR test exclusion considerations are defined in KDB 447498 D01, Chapter 4.3.1 where the 1-g head or body and 10-g extremity SAR exclusion threshold is defined by the following formula:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] * [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

For the Digipass® FIDO Touch the maximum conducted output power is -14dBm (-16dBm with a tolerance of $\pm 2\text{dB}$) (0.040mW) at 2.4GHz

Applying the above data using the given KDB 447498 D01 formula, and minimum separation distance of 5mm, the following results:

$$(1\text{mW} / 5\text{ mm}) \times \sqrt{2.4\text{ GHz}} = 0.3$$

(i.e.: ≤ 3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR)

Conclusion

This demonstrates the Digipass® FIDO Touch meets the criteria for 1-g head / body and 10-g extremity SAR test exemption.

Best regards,

A handwritten signature in blue ink, appearing to read "Mark Hoyt".

Mark Hoyt
Chief Financial Officer