



# **FCC RADIO TEST REPORT-BT**

## **FCC ID: 2AH8Q-HT7**

**Product:** HOMTOM Smart phone

**Trade Name:** HOMTOM

**Model No.:** HT7

**Serial Model:** HT3, HT3pro, HT7pro

**Report No.:** NTEK-2016NT04155179F3

**Issue Date:** 04 May. 2016

### **Prepared for**

ShenZhen Zhouji Hengtong technology Co.,Ltd.  
A Floor 3,Building A2,Enet Digital Industries Park, NO.22, Dafu  
Industries Area, Aobei Community, Guanlan, Longhua New  
District,Shenzhen, China

### **Prepared by**

NTEK TESTING TECHNOLOGY CO., LTD.  
1/F, Building E, Fenda Science Park, Sanwei Community,  
Xixiang Street Bao'an District, Shenzhen, P.R. China  
Tel.: +86-0755-61156588  
Fax.: +86-0755-61156599  
Website:www.ntek.org.cn

## TABLE OF CONTENTS

<b>1</b>	<b>TEST RESULT CERTIFICATION .....</b>	<b>3</b>
<b>2</b>	<b>SUMMARY OF TEST RESULTS.....</b>	<b>4</b>
<b>3</b>	<b>FACILITIES AND ACCREDITATIONS .....</b>	<b>5</b>
3.1	FACILITIES.....	5
3.2	LABORATORY ACCREDITATIONS AND LISTINGS .....	5
3.3	MEASUREMENT UNCERTAINTY .....	5
<b>4</b>	<b>GENERAL DESCRIPTION OF EUT .....</b>	<b>6</b>
<b>5</b>	<b>DESCRIPTION OF TEST MODES .....</b>	<b>8</b>
<b>6</b>	<b>SETUP OF EQUIPMENT UNDER TEST .....</b>	<b>10</b>
6.1	BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM.....	10
6.2	SUPPORT EQUIPMENT.....	11
6.3	EQUIPMENTS LIST FOR ALL TEST ITEMS.....	12
<b>7</b>	<b>TEST REQUIREMENTS .....</b>	<b>13</b>
7.1	CONDUCTED EMISSIONS TEST .....	13
7.2	RADIATED SPURIOUS EMISSION .....	18
7.3	6DB BANDWIDTH.....	29
7.4	20DB BANDWIDTH.....	37
7.5	DUTY CYCLE.....	41
7.6	MAXIMUM OUTPUT POWER.....	45
7.7	POWER SPECTRAL DENSITY .....	53
7.8	CONDUCTED BAND EDGE MEASUREMENT.....	61
7.9	ANTENNA APPLICATION .....	67



### 1 TEST RESULT CERTIFICATION

Applicant's name .....	ShenZhen Zhouji Hengtong technology Co.,Ltd.
Address .....	A Floor 3,Building A2,Enet Digital Industries Park, NO.22, Dafu Industries Area, Aobei Community, Guanlan, Longhua New District,Shenzhen, China
Manufacture's Name .....	ShenZhen Zhouji Hengtong technology Co.,Ltd.
Address .....	A Floor 3,Building A2,Enet Digital Industries Park, NO.22, Dafu Industries Area, Aobei Community, Guanlan, Longhua New District,Shenzhen, China
Product description	
Product name .....	HOMTOM Smart phone
Model and/or type reference .....	HT7
Serial Model .....	HT3, HT3pro, HT7pro

Measurement Procedure Used:

APPLICABLE STANDARDS	
APPLICABLE STANDARD/ TEST PROCEDURE	TEST RESULT
FCC 47 CFR Part 2, Subpart J:2015 FCC 47 CFR Part 15, Subpart C:2015 KDB 174176 D01 Line Conducted FAQ v01r01 ANSI C63.10-2013 FCC KDB 558074 D01 DTS Meas Guidance v03r04	Complied

This device described above has been tested by NTEK Testing Technology Co., Ltd., and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of NTEK Testing Technology Co., Ltd., this document may be altered or revised by NTEK Testing Technology Co., Ltd., personnel only, and shall be noted in the revision of the document.

The test results of this report relate only to the tested sample identified in this report.

Date of Test : 15 Apr. 2016 ~ 04 May.2016

Testing Engineer : Susan  
(Susan Su)

Technical Manager : Jason chen  
(Jason Chen)

Authorized Signatory : Sam . chen  
(Sam Chen)

**2 SUMMARY OF TEST RESULTS**

<b>FCC Part15 (15.247), Subpart C</b>			
<b>Standard Section</b>	<b>Test Item</b>	<b>Verdict</b>	<b>Remark</b>
15.207	Conducted Emission	PASS	
15.247 (a)(2)	6dB Bandwidth	PASS	
15.247 (b)	Maximum Output Power	PASS	
15.247 (c)	Radiated Spurious Emission	PASS	
15.247 (d)	Power Spectral Density	PASS	
15.205	Band Edge Emission	PASS	
15.203	Antenna Requirement	PASS	

Remark:

1. "N/A" denotes test is not applicable in this Test Report.
2. All test items were verified and recorded according to the standards and without any deviation during the test.
3. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

### 3 FACILITIES AND ACCREDITATIONS

#### 3.1 FACILITIES

All measurement facilities used to collect the measurement data are located at 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District, Shenzhen P.R. China.

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.10 and CISPR Publication 22.

#### 3.2 LABORATORY ACCREDITATIONS AND LISTINGS

Site Description  
EMC Lab.

: Accredited by CNAS, 2014.09.04  
The certificate is valid until 2017.09.03  
The Laboratory has been assessed and proved to be in compliance with CNAS-CL01:2006 (identical to ISO/IEC 17025:2005)  
The Certificate Registration Number is L5516.

Accredited by Industry Canada, August 29, 2012  
The Certificate Registration Number is 9270A-1.

Accredited by FCC, September 6, 2013  
The Certificate Registration Number is 238937.

Name of Firm : NTEK Testing Technology Co., Ltd  
Site Location : 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District, Shenzhen P.R. China.

#### 3.3 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement  $y \pm U$ , where expanded uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 1.38\text{dB}$
2	RF power, conducted	$\pm 0.16\text{dB}$
3	Spurious emissions, conducted	$\pm 0.21\text{dB}$
4	All emissions, radiated(<1G)	$\pm 4.68\text{dB}$
5	All emissions, radiated(>1G)	$\pm 4.89\text{dB}$
6	Temperature	$\pm 0.5^\circ\text{C}$
7	Humidity	$\pm 2\%$

#### 4 GENERAL DESCRIPTION OF EUT

Product Feature and Specification	
Equipment	HOMTOM Smart phone
Trade Name	HOMTOM
FCC ID	2AH8Q-HT7
Model No.	HT7
Serial Model	HT3, HT3pro, HT7pro
Model Difference	All the model are the same circuit and RF module,except the model No.and colour.
Operating Frequency	2412-2462MHz for 802.11b/g/11n(HT20)/11n(HT40);
Modulation	DSSS with DBPSK/DQPSK/CCK for 802.11b; OFDM with BPSK/QPSK/16QAM/64QAM for 802.11g/n;
Number of Channels	11 channels for 802.11b/g/11n(HT20);
Antenna Type	FPCB Antenna
Antenna Gain	1 dBi
Power supply	<input checked="" type="checkbox"/> DC supply: DC 3.8V/3000mAh from Li-ion Battery or DC 5V from USB Port.
	<input checked="" type="checkbox"/> Adapter supply: Model: HT6 Input: 100-240V Output: 5.0V $\overline{\text{---}}$ 1000mA
HW Version	N/A
SW Version	N/A

Note: Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.



## 5 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

Test of channel included the lowest and middle and highest frequency to perform the test, then record on this report.

Those data rates (802.11b: 1 Mbps; 802.11g: 6 Mbps; 802.11n (HT20): MCS0; 802.11n (HT40): MCS0) were used for all test.

The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement –X, Y, and Z-plane. The Y-plane results were found as the worst case and were shown in this report.

Frequency and Channel list for 802.11b/g/n (HT20):

Channel	Frequency(MHz)
1	2412
2	2417
...	...
5	2432
6	2437
...	...
10	2457
11	2462

Note:  $f_c=2412\text{MHz}+k \times 5\text{MHz}$   $k=0$  to 10



The following summary table is showing all test modes to demonstrate in compliance with the standard.

<b>For AC Conducted Emission</b>	
Final Test Mode	Description
Mode 1	normal link mode

Note: AC power line Conducted Emission was tested under maximum output power.

<b>For Radiated Test Cases</b>	
Final Test Mode	Description
Mode 1	802.11b CH1/ CH6/ CH11
Mode 2	802.11g CH1/ CH6/ CH11
Mode 3	802.11n HT20 CH1/ CH6/ CH11
Mode 4	802.11n HT40 CH1/ CH6/ CH11

Note: For radiated test cases, the worst mode data rate was reported only, because this data rate has the highest RF output power at preliminary tests, and no other significantly frequencies found in conducted spurious emission.

<b>For Conducted Test Cases</b>	
Final Test Mode	Description
Mode 1	802.11b CH1/ CH6/ CH11
Mode 2	802.11g CH1/ CH6/ CH11
Mode 3	802.11n HT20 CH1/ CH6/ CH11
Mode 4	802.11n HT40 CH1/ CH6/ CH11

Note: The engineering test program was provided and the EUT was programmed to be in continuously transmitting mode.


## 6 SETUP OF EQUIPMENT UNDER TEST

### 6.1 BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM


For AC Conducted Emission Mode



For Radiated Test Cases



For Conducted Test Cases



**6.2 SUPPORT EQUIPMENT**

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	FCC ID	Note
1.	HOMTOM Smart phone	HOMTOM	HT7	2AH8Q-HT7	EUT
2.	Adapter	N/A	HT6	N/A	Peripherals
3.	Earphone	N/A	L662	N/A	Peripherals
4.	N/A	N/A	N/A	N/A	Auxiliary equipment

Item	Cable Type	Shielded Type	Ferrite Core	Length
C-1	USB Cable	NO	NO	1.0m
C-2	Earphone	NO	NO	0.8m
C-3	RF Cable	NO	NO	0.5m

**Notes:**

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (3) “YES” is means “shielded” “with core”; “NO” is means “unshielded” “without core”.

### 6.3 EQUIPMENTS LIST FOR ALL TEST ITEMS

#### Radiation Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	MXA Signal Analyzer	Agilent	N9020A	MY49100060	2015.11.19	2016.11.18	1 year
2	Test Receiver	R&S	ESPI	101318	2015.06.07	2016.06.06	1 year
3	Bilog Antenna	TESEQ	CBL6111D	31216	2015.07.06	2016.07.05	1 year
4	Horn Antenna	EM	EM-AH-10180	2011071402	2015.07.06	2016.07.05	1 year
5	Horn Ant	Schwarzbeck	BBHA 9170	9170-181	2015.07.06	2016.07.05	1 year
6	Loop Antenna	ARA	PLA-1030/B	1029	2015.06.08	2016.06.07	1 year
7	Amplifier	EM	EM-30180	060538	2015.12.22	2016.12.21	1 year
8	50Ω Coaxial Switch	Anritsu	MP59B	6200264416	2015.06.07	2016.06.06	1 year
9	Power Meter	R&S	NRVS	100696	2015.07.06	2016.07.05	1 year
10	Power Sensor	R&S	URV5-Z4	0395.1619.05	2015.07.06	2016.07.05	1 year
11	Test Cable	N/A	R-01	N/A	2015.07.06	2016.07.05	1 year
12	Test Cable	N/A	R-02	N/A	2015.07.06	2016.07.05	1 year
13	Test Cable	N/A	R-03	N/A	2015.06.29	2016.06.28	1 year
14	Signal Generator	Agilent	E4438C	MY45093347	2015.06.28	2016.06.27	1 year

#### Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Test Receiver	R&S	ESCI	101160	2015.06.06	2016.06.05	1 year
2	LISN	R&S	ENV216	101313	2015.08.24	2016.08.23	1 year
3	LISN	EMCO	3816/2	00042990	2015.08.24	2016.08.23	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264417	2015.06.07	2016.06.06	1 year
5	Passive Voltage Probe	R&S	ESH2-Z3	100196	2015.06.07	2016.06.06	1 year
6	Absorbing clamp	R&S	MDS-21	100423	2015.06.08	2016.06.07	1 year
7	Test Cable	N/A	C01	N/A	2015.06.08	2016.06.07	1 year
8	Test Cable	N/A	C02	N/A	2015.06.08	2016.06.07	1 year
9	Test Cable	N/A	C03	N/A	2015.06.08	2016.06.07	1 year
1	Attenuation	MCE	24-10-34	BN9258	2015.06.08	2016.06.07	1 year

Note: Each piece of equipment is scheduled for calibration once a year.

## 7 TEST REQUIREMENTS

### 7.1 CONDUCTED EMISSIONS TEST

#### 7.1.1 Applicable Standard

According to FCC Part 15.207(a) and KDB 174176 D01 Line Conducted FAQ v01r01

#### 7.1.2 Conformance Limit


Frequency(MHz)	Conducted Emission Limit	
	Quasi-peak	Average
0.15-0.5	66-56*	56-46*
0.5-5.0	56	46
5.0-30.0	60	50

Note: 1. \*Decreases with the logarithm of the frequency  
 2. The lower limit shall apply at the transition frequencies  
 3. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

#### 7.1.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

#### 7.1.4 Test Configuration




#### 7.1.5 Test Procedure

According to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 Conducted emissions the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.


1. The EUT was placed 0.4 meter from the conducting wall of the shielding room.
2. The EUT was placed on a table which is 0.8m above ground plane.
3. Connect EUT to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
4. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40cm long.
5. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
6. LISN at least 80 cm from nearest part of EUT chassis.
7. The frequency range from 150KHz to 30MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth(IF bandwidth=9KHz) with Maximum Hold Mode
9. For the actual test configuration, please refer to the related Item –EUT Test Photos.

7.1.6 Test Results




Site: Phase: **L1** Temperature: 22  
 Limit: FCC Part 15B (0.15-30MHz) Main QP Power: AC 120V/60Hz Humidity: 51 %  
 Mode: TX  
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV	dBuV	dB		
1	*	0.1940	32.78	10.13	42.91	63.86	-20.95	QP	
2		0.1940	15.41	10.13	25.54	53.86	-28.32	AVG	
3		0.3140	22.21	10.13	32.34	59.86	-27.52	QP	
4		0.3140	5.68	10.13	15.81	49.86	-34.05	AVG	
5		0.8059	23.94	9.80	33.74	56.00	-22.26	QP	
6		0.8059	12.73	9.80	22.53	46.00	-23.47	AVG	
7		1.7900	21.48	9.76	31.24	56.00	-24.76	QP	
8		1.7900	8.90	9.76	18.66	46.00	-27.34	AVG	
9		2.6739	19.35	9.74	29.09	56.00	-26.91	QP	
10		2.6739	7.91	9.74	17.65	46.00	-28.35	AVG	
11		20.8140	26.10	9.95	36.05	60.00	-23.95	QP	
12		20.8140	8.60	9.95	18.55	50.00	-31.45	AVG	



Site: Phase: **N** Temperature: 22  
 Limit: FCC Part 15B (0.15-30MHz) Main OP Power: AC 120V/60Hz Humidity: 51 %  
 Mode: TX  
 Note:


No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1859	31.70	10.04	41.74	64.21	-22.47	QP	
2		0.1859	11.87	10.04	21.91	54.21	-32.30	AVG	
3		0.2819	20.74	10.11	30.85	60.76	-29.91	QP	
4		0.2819	5.71	10.11	15.82	50.76	-34.94	AVG	
5		0.5779	22.18	9.82	32.00	56.00	-24.00	QP	
6		0.5779	9.06	9.82	18.88	46.00	-27.12	AVG	
7	*	0.8020	24.53	9.83	34.36	56.00	-21.64	QP	
8		0.8020	11.02	9.83	20.85	46.00	-25.15	AVG	
9		1.7059	21.32	9.79	31.11	56.00	-24.89	QP	
10		1.7059	9.51	9.79	19.30	46.00	-26.70	AVG	
11		3.4900	18.72	9.73	28.45	56.00	-27.55	QP	
12		3.4900	6.79	9.73	16.52	46.00	-29.48	AVG	



Site: \_\_\_\_\_ Phase: **L1** Temperature: 22  
 Limit: FCC Part 15B (0.15-30MHz) Main QP Power: AC 240V/50Hz Humidity: 51 %  
 Mode: TX  
 Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.2300	29.97	10.13	40.10	62.45	-22.35	QP	
2		0.2300	15.07	10.13	25.20	52.45	-27.25	AVG	
3		0.5737	22.02	9.79	31.81	56.00	-24.19	QP	
4		0.5737	10.82	9.79	20.61	46.00	-25.39	AVG	
5	*	0.8739	23.90	9.82	33.72	56.00	-22.28	QP	
6		0.8739	11.59	9.82	21.41	46.00	-24.59	AVG	
7		1.7980	20.25	9.75	30.00	56.00	-26.00	QP	
8		1.7980	9.55	9.75	19.30	46.00	-26.70	AVG	
9		2.7418	18.71	9.74	28.45	56.00	-27.55	QP	
10		2.7418	7.56	9.74	17.30	46.00	-28.70	AVG	
11		19.9298	23.76	9.94	33.70	60.00	-26.30	QP	
12		19.9298	8.37	9.94	18.31	50.00	-31.69	AVG	





Site: \_\_\_\_\_ Phase: **N** Temperature: 22  
 Limit: FCC Part 15B (0.15-30MHz) Main OP Power: AC 240V/50Hz Humidity: 51 %  
 Mode: TX  
 Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.2083	31.37	10.03	41.40	63.27	-21.87	QP	
2		0.2083	15.39	10.03	25.42	53.27	-27.85	AVG	
3	*	0.8137	25.87	9.83	35.70	56.00	-20.30	QP	
4		0.8137	14.15	9.83	23.98	46.00	-22.02	AVG	
5		1.7057	21.32	9.79	31.11	56.00	-24.89	QP	
6		1.7057	9.59	9.79	19.38	46.00	-26.62	AVG	
7		2.6579	19.55	9.74	29.29	56.00	-26.71	QP	
8		2.6579	7.70	9.74	17.44	46.00	-28.56	AVG	
9		6.1539	12.12	9.73	21.85	60.00	-38.15	QP	
10		6.1539	-0.75	9.73	8.98	50.00	-41.02	AVG	
11		20.1700	25.22	9.91	35.13	60.00	-24.87	QP	
12		20.1700	9.25	9.91	19.16	50.00	-30.84	AVG	

**7.2 RADIATED SPURIOUS EMISSION**

**7.2.1 Applicable Standard**

According to FCC Part 15.247(d) and 15.209 and DA 00-705

**7.2.2 Conformance Limit**

According to FCC Part 15.247(d): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).  
According to FCC Part15.205, Restricted bands

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Restricted Frequency(MHz)	Field Strength (µV/m)	Field Strength (dBµV/m)	Measurement Distance
0.009~0.490	2400/F(KHz)	20 log (uV/m)	300
0.490~1.705	2400/F(KHz)	20 log (uV/m)	30
1.705~30.0	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

Limits of Radiated Emission Measurement(Above 1000MHz)

Frequency(MHz)	Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54


- Remark :1. Emission level in dBuV/m=20 log (uV/m)  
 2. Measurement was performed at an antenna to the closed point of EUT distance of meters.  
 3. Distance extrapolation factor =40log(Specific distance/ test distance)( dB);  
 Limit line=Specific limits(dBuV) + distance extrapolation factor.

**7.2.3 Measuring Instruments**


The Measuring equipment is listed in the section 6.3 of this test report.

**7.2.4 Test Configuration**


(a) For radiated emissions below 30MHz



(b) For radiated emissions from 30MHz to 1000MHz



(c) For radiated emissions above 1000MHz



**7.2.5 Test Procedure**

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.10-2013. The test distance is 3m. The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 and CAN/CSA-CEI/IEC CISPR 22.

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT.

Use the following spectrum analyzer settings:

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 0.8 m for below 1GHz and 1.5m for above 1GHz the ground at a 3 meter. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 0.8 m for below 1GHz and 1.5m for above 1GHz; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:

Frequency Band (MHz)	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	QP	120 kHz	300 kHz
Above 1000	Peak	1 MHz	1 MHz
	Average	1 MHz	10 Hz

Note: for the frequency ranges below 30 MHz, a narrower RBW is used for these ranges but the measured value should add a RBW correction factor (RBWCF) where  $RBWCF [dB] = 10 \cdot \lg(100 [kHz] / \text{narrower RBW [kHz]})$ . , the narrower RBW is 1 kHz and RBWCF is 20 dB for the frequency 9 kHz to 150 kHz, and the narrower RBW is 10 kHz and RBWCF is 10 dB for the frequency 150 kHz to 30 MHz.

**7.2.6 Test Results**

■ Spurious Emission below 30MHz (9KHz to 30MHz)

EUT:	HOMTOM Smart phone	Model No.:	HT7
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode1/Mode2/Mode3/Mode4	Test By:	Susan Su


Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
--	--	--	--	--	--	--	--

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Distance extrapolation factor = $20\log(\text{Specific distance/ test distance})$ ( dB);


Limit line=Specific limits(dBuV) + distance extrapolation factor

- Spurious Emission below 1GHz (30MHz to 1GHz)  
All the modulation modes have been tested, and the worst result was report as below:



Site: Polarization: **Vertical** Temperature: 24  
 Limit: FCC PART15 B 03m QP Power: AC 120V/60Hz Humidity: 50 %  
 Mode: TX  
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	!	32.6340	17.17	18.43	35.60	40.00	-4.40	QP		
2	*	46.1779	25.36	10.54	35.90	40.00	-4.10	QP		
3		61.3462	27.86	5.94	33.80	40.00	-6.20	QP		
4		69.8448	21.85	8.85	30.70	40.00	-9.30	QP		
5		88.9637	15.64	9.66	25.30	43.50	-18.20	QP		
6		184.4898	14.78	11.82	26.60	43.50	-16.90	QP		



Site

Limit: FCC PART15 B 03m QP  
Mode: TX

Note:

Polarization: *Horizontal*

Power: AC 120V/60Hz

Temperature: 24

Humidity: 50 %

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Antenna Height cm	Table Degree degree	Comment
1	*	31.0701	6.92	19.18	26.10	40.00	-13.90	QP			
2		41.1319	12.06	13.94	26.00	40.00	-14.00	QP			
3		55.6094	12.45	6.95	19.40	40.00	-20.60	QP			
4		72.3375	11.62	9.68	21.30	40.00	-18.70	QP			
5		183.8437	13.86	11.84	25.70	43.50	-17.80	QP			
6		213.0149	11.77	11.03	22.80	43.50	-20.70	QP			

■ Spurious Emission Above 1GHz (1GHz to 27GHz)

EUT:	HOMTOM Smart phone	Model No.:	HT7
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode1/Mode2/Mode3/Mode4	Test By:	Susan Su

All the modulation modes have been tested, and the worst result was report as below:

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Remark	Comment
Low Channel (2412 MHz)-Above 1G							
4824.072	50.27	10.44	60.71	74.00	-13.29	Pk	Vertical
4824.072	35.75	10.44	46.19	54.00	-7.81	AV	Vertical
7236.165	47.58	12.39	59.97	74.00	-14.03	Pk	Vertical
7236.165	32.15	12.39	44.54	54.00	-9.46	AV	Vertical
4824.286	52.27	10.44	62.71	74.00	-11.29	Pk	Horizontal
4824.286	34.34	10.44	44.78	54.00	-9.22	AV	Horizontal
7236.402	45.66	12.39	58.05	74.00	-15.95	Pk	Horizontal
7236.402	31.57	12.39	43.96	54.00	-10.04	AV	Horizontal
Mid Channel (2437 MHz)-Above 1G							
4874.318	50.42	10.40	60.82	74.00	-13.18	Pk	Vertical
4874.318	32.63	10.40	43.03	54.00	-10.97	AV	Vertical
7311.306	48.64	12.75	61.39	74.00	-12.61	Pk	Vertical
7311.306	29.35	12.75	42.10	54.00	-11.90	AV	Vertical
4874.238	50.38	10.40	60.78	74.00	-13.22	Pk	Horizontal
4874.238	34.66	10.40	45.06	54.00	-8.94	AV	Horizontal
7311.102	49.82	12.75	62.57	74.00	-11.43	Pk	Horizontal
7311.102	30.51	12.75	43.26	54.00	-10.74	AV	Horizontal
High Channel (2462 MHz)- Above 1G							
4924.269	50.84	10.39	61.23	74.00	-12.77	Pk	Vertical
4924.269	35.48	10.39	45.87	54.00	-8.13	AV	Vertical
7386.421	48.65	12.68	61.33	74.00	-12.67	Pk	Vertical
7386.421	28.57	12.68	41.25	54.00	-12.75	AV	Vertical
4924.185	50.31	10.39	60.70	74.00	-13.30	Pk	Horizontal
4924.185	35.24	10.39	45.63	54.00	-8.37	AV	Horizontal
7386.225	49.63	12.68	62.31	74.00	-11.69	Pk	Horizontal
7386.225	31.24	12.68	43.92	54.00	-10.08	AV	Horizontal

- Note: (1) All Readings are Peak Value (VBW=3MHz) and Peak Value (VBW=10Hz).  
 (2) Emission Level= Reading Level+Probe Factor +Cable Loss.  
 (3)All other emissions more than 20dB below the limit.  
 (4) Data of measurement within this frequency range shown “ -- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.



■ Spurious Emission in Band Edge

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type	Comment
802.11b							
2345.54	60.68	-13.06	47.62	74.00	-26.38	Pk	Vertical
2345.54	54.82	-13.06	41.76	54.00	-12.24	AV	Vertical
2400	63.49	-13.06	50.43	74.00	-23.57	Pk	Vertical
2400	55.22	-13.06	42.16	54.00	-11.84	AV	Vertical
2387.49	60.57	-13.06	47.51	74.00	-26.49	Pk	Horizontal
2387.49	54.76	-13.06	41.7	54.00	-12.3	AV	Horizontal
2400	63.78	-13.06	50.72	74.00	-23.28	Pk	Horizontal
2400	54.84	-13.06	41.78	54.00	-12.22	AV	Horizontal
2483.5	62.32	-12.78	49.54	74.00	-24.46	Pk	Vertical
2483.5	61.24	-12.78	48.46	54.00	-5.54	AV	Vertical
2483.5	60.68	-13.06	47.62	74.00	-26.38	Pk	Horizontal
2483.5	54.82	-13.06	41.76	54.00	-12.24	AV	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type	Comment
802.11g							
2366.26	60.52	-13.06	47.46	74.00	-26.54	Pk	Vertical
2366.26	54.66	-13.06	41.60	54.00	-12.40	AV	Vertical
2400	63.33	-13.06	50.27	74.00	-23.73	Pk	Vertical
2400	55.06	-13.06	42.00	54.00	-12.00	AV	Vertical
2357.67	60.41	-13.06	47.35	74.00	-26.65	Pk	Horizontal
2357.67	54.60	-13.06	41.54	54.00	-12.46	AV	Horizontal
2400	63.62	-13.06	50.56	74.00	-23.44	Pk	Horizontal
2400	54.68	-13.06	41.62	54.00	-12.38	AV	Horizontal
2483.5	62.16	-12.78	49.38	74.00	-24.62	Pk	Vertical
2483.5	61.08	-12.78	48.30	54.00	-5.70	AV	Vertical
2483.5	62.09	-12.78	49.31	74.00	-24.69	Pk	Horizontal
2483.5	60.98	-12.78	48.20	54.00	-5.80	AV	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type	Comment
802.11n(20)							
2378.64	60.99	-13.06	47.93	74.00	-26.07	Pk	Vertical
2378.64	54.20	-13.06	41.14	54.00	-12.86	AV	Vertical
2400	63.87	-13.06	50.81	74.00	-23.19	Pk	Vertical
2400	53.95	-13.06	40.89	54.00	-13.11	AV	Vertical
2359.88	60.88	-13.06	47.82	74.00	-26.18	Pk	Horizontal
2359.88	54.01	-13.06	40.95	54.00	-13.05	AV	Horizontal
2400	63.79	-13.06	50.73	74.00	-23.27	Pk	Horizontal
2400	54.89	-13.06	41.83	54.00	-12.17	AV	Horizontal
2483.5	62.18	-12.78	49.40	74.00	-24.60	Pk	Vertical
2483.5	61.19	-12.78	48.41	54.00	-5.59	AV	Vertical
2483.5	61.96	-12.78	49.18	74.00	-24.82	Pk	Horizontal
2483.5	61.05	-12.78	48.27	54.00	-5.73	AV	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type	Comment
802.11n(40)							
2377.48	61.40	-13.06	48.34	74.00	-25.66	Pk	Vertical
2377.48	54.10	-13.06	41.04	54.00	-12.96	AV	Vertical
2400	63.96	-13.06	50.90	74.00	-23.10	Pk	Vertical
2400	54.87	-13.06	41.81	54.00	-12.19	AV	Vertical
2384.51	60.97	-13.06	47.91	74.00	-26.09	Pk	Horizontal
2384.51	54.63	-13.06	41.57	54.00	-12.43	AV	Horizontal
2400	64.38	-13.06	51.32	74.00	-22.68	Pk	Horizontal
2400	54.00	-13.06	40.94	54.00	-13.06	AV	Horizontal
2483.5	62.32	-12.78	49.54	74.00	-24.46	Pk	Vertical
2483.5	61.44	-12.78	48.66	54.00	-5.34	AV	Vertical
2483.5	62.26	-12.78	49.48	74.00	-24.52	Pk	Horizontal
2483.5	61.32	-12.78	48.54	54.00	-5.46	AV	Horizontal

Note: (1) All other emissions more than 20dB below the limit.

■ Spurious Emission in Restricted Bands 3260MHz- 18000MHz

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type	Comment
802.11b							
3260	60.84	-13.06	47.78	74	-26.22	Pk	Vertical
3260	52.98	-13.06	39.92	54	-14.08	AV	Vertical
3260	60.73	-13.06	47.67	74	-26.33	Pk	Horizontal
3260	52.92	-13.06	39.86	54	-14.14	AV	Horizontal
3332	62.48	-12.78	49.7	74	-24.3	Pk	Vertical
3332	51.4	-12.78	38.62	54	-15.38	AV	Vertical
3332	62.41	-12.78	49.63	74	-24.37	Pk	Horizontal
3332	51.3	-12.78	38.52	54	-15.48	AV	Horizontal
17815	63.56	-12.24	51.32	74	-22.68	Pk	Vertical
17815	51.27	-12.24	39.03	54	-14.97	AV	Vertical
17854	63.04	-12.24	50.8	74	-23.20	Pk	Horizontal
17854	52.27	-12.24	40.03	54	-13.97	AV	Horizontal
802.11g							
3260	61.08	-13.06	48.02	74	-25.98	Pk	Vertical
3260	51.9	-13.06	38.84	54	-15.16	AV	Vertical
3260	61	-13.06	47.94	74	-26.06	Pk	Horizontal
3260	51.85	-13.06	38.79	54	-15.21	AV	Horizontal
3332	62.41	-12.78	49.63	74	-24.37	Pk	Vertical
3332	51.44	-12.78	38.66	54	-15.34	AV	Vertical
3332	62.07	-12.78	49.29	74	-24.71	Pk	Horizontal
3332	51.26	-12.78	38.48	54	-15.52	AV	Horizontal
17795	63.07	-12.24	50.83	74	-23.17	Pk	Vertical
17795	52.49	-12.24	40.25	54	-13.75	AV	Vertical
17828	62.86	-12.24	50.62	74	-23.38	Pk	Horizontal
17828	53.12	-12.24	40.88	54	-13.12	AV	Horizontal

802.11n(20)							
3260	61.31	-13.06	48.25	74	-25.75	Pk	Vertical
3260	50.19	-13.06	37.13	54	-16.87	AV	Vertical
3260	61.2	-13.06	48.14	74	-25.86	Pk	Horizontal
3260	50.12	-13.06	37.06	54	-16.94	AV	Horizontal
3332	62.5	-12.78	49.72	74	-24.28	Pk	Vertical
3332	51.51	-12.78	38.73	54	-15.27	AV	Vertical
3332	62.28	-12.78	49.5	74	-24.50	Pk	Horizontal
3332	51.37	-12.78	38.59	54	-15.41	AV	Horizontal
17874	63.01	-12.24	50.77	74	-23.23	Pk	Vertical
17874	52.54	-12.24	40.3	54	-13.70	AV	Vertical
17935	62.94	-12.24	50.7	74	-23.30	Pk	Horizontal
17935	52.68	-12.24	40.44	54	-13.56	AV	Horizontal
802.11n(40)							
3260	61.72	-13.06	48.66	74	-25.34	Pk	Vertical
3260	50.42	-13.06	37.36	54	-16.64	AV	Vertical
3260	61.29	-13.06	48.23	74	-25.77	Pk	Horizontal
3260	49.95	-13.06	36.89	54	-17.11	AV	Horizontal
3332	62.64	-12.78	49.86	74	-24.14	Pk	Vertical
3332	51.76	-12.78	38.98	54	-15.02	AV	Vertical
3332	62.58	-12.78	49.8	74	-24.20	Pk	Horizontal
3332	51.64	-12.78	38.86	54	-15.14	AV	Horizontal
17788	63.16	-12.24	50.92	74	-23.08	Pk	Vertical
17788	52.64	-12.24	40.4	54	-13.60	AV	Vertical
17917	63.05	-12.24	50.81	74	-23.19	Pk	Horizontal
17917	52.78	-12.24	40.54	54	-13.46	AV	Horizontal

Note: (1) All other emissions more than 20dB below the limit.

### **7.3 6DB BANDWIDTH**

#### **7.3.1 Applicable Standard**

According to FCC Part 15.247(a)(2) and KDB 558074 DTS 01 Meas. Guidance v03r04

#### **7.3.2 Conformance Limit**

The minimum permissible 6dB bandwidth is 500 kHz.

#### **7.3.3 Measuring Instruments**

The Measuring equipment is listed in the section 6.3 of this test report.

#### **7.3.4 Test Setup**

Please refer to Section 6.1 of this test report.

#### **7.3.5 Test Procedure**

The testing follows KDB 558074 DTS 01 Meas. Guidance v03r04

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT was operating in controlled its channel.

Use the following spectrum analyzer settings:

Span = the frequency band of operation

RBW = 100KHz

VBW  $\geq$  3\*RBW

Sweep = auto

Detector function = peak

Trace = max hold


**7.3.6 Test Results**

EUT:	HOMTOM Smart phone	Model No.:	HT7
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode1/Mode2/Mode3/Mode4	Test By:	Susan Su

Channel	Frequency (MHz)	6dB bandwidth (kHz)	Limit (kHz)	Result
802.11b				
1	2412	10070.000	500	Pass
6	2437	10070.000	500	Pass
11	2462	10070.000	500	Pass
802.11g				
1	2412	15150.000	500	Pass
6	2437	15160.000	500	Pass
11	2462	15160.000	500	Pass
802.11n HT20				
1	2412	15150.000	500	Pass
6	2437	15160.000	500	Pass
11	2462	15150.000	500	Pass
802.11n HT40				
3	2422	35210.000	500	Pass
6	2437	35210.000	500	Pass
9	2452	35350.000	500	Pass


6dB Bandwidth plot on channel 1

802.11b




6dB Bandwidth plot on channel 6

802.11b




6dB Bandwidth plot on channel 11

802.11b



6dB Bandwidth plot on channel 1


802.11g






6dB Bandwidth plot on channel 6

802.11g




6dB Bandwidth plot on channel 11

802.11g




6dB Bandwidth plot on channel 1

802.11n HT20




6dB Bandwidth plot on channel 6

802.11n HT20




6dB Bandwidth plot on channel 11

802.11n HT20




6dB Bandwidth plot on channel 3

802.11n HT40




6dB Bandwidth plot on channel 6

802.11n HT40



6dB Bandwidth plot on channel 9

802.11n HT40



## **7.4 20DB BANDWIDTH**

### **7.4.1 Applicable Standard**

According to FCC Part 15.247(a)(2) and KDB 558074 DTS 01 Meas. Guidance v03r04

### **7.4.2 Conformance Limit**

No limit requirement.

### **7.4.3 Measuring Instruments**

The Measuring equipment is listed in the section 6.3 of this test report.

### **7.4.4 Test Setup**

Please refer to Section 6.1 of this test report.

### **7.4.5 Test Procedure**

The testing follows KDB 558074 DTS 01 Meas. Guidance v03r04

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT was operating in controlled its channel.

Use the following spectrum analyzer settings:

Span = the frequency band of operation

RBW = 100KHz

VBW  $\geq$  3\*RBW

Sweep = auto

Detector function = peak

Trace = max hold

**7.4.6 Test Results**


EUT:	HOMTOM Smart phone	Model No.:	HT7
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode1/Mode2/Mode3/Mode4	Test By:	Susan Su

All the bands and channels were tested, the data of the worst mode are described in the following table

Band	Frequency/Channel (MHz)	20dB bandwidth (kHz)	Limit (kHz)	Result
802.11b	2437MHz/CH6	15110.000	N/A	Pass
802.11g	2437MHz/CH6	17760.000	N/A	Pass
802.11n HT20	2437MHz/CH6	18470.000	N/A	Pass
802.11n HT40	2437MHz/CH6	37280.000	N/A	Pass


20dB Bandwidth plot on channel 6

802.11b




20dB Bandwidth plot on channel 6

802.11g




20dB Bandwidth plot on channel 6

802.11n HT20



20dB Bandwidth plot on channel 6

802.11n HT40





## 7.5 DUTY CYCLE

### 7.5.1 Applicable Standard

According to KDB 558074)6)b), issued 06/09/2015

### 7.5.2 Conformance Limit

No limit requirement.

### 7.5.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

### 7.5.4 Test Setup

Please refer to Section 6.1 of this test report.

### 7.5.5 Test Procedure

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on and off times of the transmitted signal. Set the center frequency of the instrument to the center frequency of the transmission. Set  $RBW \geq OBW$  if possible; otherwise, set RBW to the largest available value. Set  $VBW \geq RBW$ . Set detector = peak or average. The zero-span measurement method shall not be used unless both RBW and VBW are  $> 50/T$  and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring duty cycle shall not be used if  $T \leq 16.7$  microseconds.)

The transmitter output is connected to the Spectrum Analyzer. We tested according to the zero-span measurement method, 6.0)b) in KDB 558074(issued 06/09/2015)

The largest available value of RBW is 8 MHz and VBW is 50 MHz. The zero-span method of measuring duty cycle shall not be used if  $T \leq 6.25$  microseconds. ( $50/6.25 = 8$ )

The zero-span method was used because all measured T data are  $> 6.25$  microseconds and both RBW and VBW are  $> 50/T$ .

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT was operating in controlled its channel.

Use the following spectrum analyzer settings:

Span = Zero Span

RBW = 8MHz(the largest available value)

VBW = 8MHz ( $\geq$  RBW)

Number of points in Sweep  $> 100$

Detector function = peak

Trace = Clear write

Measure  $T_{total}$  and  $T_{on}$

Calculate Duty Cycle =  $T_{on} / T_{total}$  and Duty Cycle Factor= $10 \cdot \log(1/\text{Duty Cycle})$

**7.5.6 Test Results**

EUT:	HOMTOM Smart phone	Model No.:	HT7
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode1/Mode2/Mode3/Mode4	Test By:	Susan Su

Mode	Data rate	Channel	T <sub>on</sub>	T <sub>total</sub>	Duty Cycle	Duty Cycle Factor (dB)
802.11b	1Mbps	6	8.22	8.24	0.9976	0.011
802.11g	6Mbps	6	1.368	1.398	0.9785	0.094
802.11n HT20	MCS0	6	1.278	1.308	0.9771	0.101
802.11n HT40	MCS0	6	638.0	668.0	0.9551	0.200

Note: All the modulation modes were tested, the data of the worst mode are described in the following table.


Duty Cycle plot on channel 6

802.11b




Duty Cycle plot on channel 6

802.11g




Duty Cycle plot on channel 6

802.11n HT20



Duty Cycle plot on channel 6

802.11n HT40



## 7.6 MAXIMUM OUTPUT POWER

### 7.6.1 Applicable Standard

According to FCC Part 15.247(b)(3) and KDB 558074 DTS 01 Meas. Guidance v03r04

### 7.6.2 Conformance Limit

The maximum peak conducted output power of the intentional radiator for systems using digital modulation in the 2400 - 2483.5 MHz bands shall not exceed: 1 Watt (30dBm). If transmitting antenna of directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

### 7.6.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

### 7.6.4 Test Setup

Please refer to Section 6.1 of this test report.

### 7.6.5 Test Procedure

The testing follows KDB 558074 DTS 01 Meas. Guidance v03r04 section 9.2.2

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT was operating in controlled its channel.

a) Set instrument center frequency to DTS channel center frequency.

b) Set span to at least 1.5 times the OBW.

c) Set RBW = 1-5% of the OBW, not to exceed 1MHz.

d) Set VBW  $\geq 3 \times$  RBW.

e) Number of points in sweep  $\geq 2 \times$  span / RBW.

(This gives bin-to-bin spacing  $\leq$  RBW/2, so that narrowband signals are not lost between frequency bins.)

f) Sweep time = auto.

g) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.

h) If transmit duty cycle  $< 98 \%$ , use a sweep trigger with the level set to enable triggering only on full power pulses. The transmitter shall operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle  $\geq 98 \%$ , and if each transmission is entirely at the maximum power control level, then the trigger shall be set to "free run".

i) Trace average at least 100 traces in power averaging (i.e., RMS) mode.

j) Compute power by integrating the spectrum across the OBW of the signal using the instrument's band power measurement function, with band limits set equal to the OBW band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.


**7.6.6 Test Results**

EUT:	HOMTOM Smart phone	Model No.:	HT7
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode1/Mode2/Mode3/Mode4	Test By:	Susan Su

Test Channel	Frequency (MHz)	Power Setting	Average Output Power (dBm)	LIMIT (dBm)	Verdict
<b>802.11b</b>					
1	2412	MAXIMUM	11.49	30	PASS
6	2437	MAXIMUM	11.84	30	PASS
11	2462	MAXIMUM	12.62	30	PASS
<b>802.11g</b>					
1	2412	MAXIMUM	10.46	30	PASS
6	2437	MAXIMUM	11.13	30	PASS
11	2462	MAXIMUM	11.82	30	PASS
<b>802.11n HT20</b>					
1	2412	MAXIMUM	10.89	30	PASS
6	2437	MAXIMUM	11.24	30	PASS
11	2462	MAXIMUM	11.67	30	PASS
<b>802.11n HT40</b>					
3	2422	MAXIMUM	11.90	30	PASS
6	2437	MAXIMUM	11.91	30	PASS
9	2452	MAXIMUM	12.06	30	PASS


Output Power plot on channel 1

802.11b




Output Power plot on channel 6

802.11b




Output Power plot on channel 11

802.11b



Output Power plot on channel 1


802.11g






Output Power plot on channel 6

802.11g




Output Power plot on channel 11

802.11g




Output Power plot on channel 1

802.11n HT20




Output Power plot on channel 6

802.11n HT20



Output Power plot on channel 11

802.11n HT20




Output Power plot on channel 3

802.11n HT40




Output Power plot on channel 6

802.11n HT40



Output Power plot on channel 9

802.11n HT40



## 7.7 POWER SPECTRAL DENSITY

### 7.7.1 Applicable Standard

According to FCC Part 15.247(e) and KDB 558074 DTS 01 Meas. Guidance v03r04

### 7.7.2 Conformance Limit

The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

### 7.7.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

### 7.7.4 Test Setup

Please refer to Section 6.1 of this test report.

### 7.7.5 Test Procedure

The testing follows Measurement Procedure 10.3 Method AVGPSD of FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r04

This procedure may be used when the maximum (average) conducted output power was used to demonstrate compliance to the output power limit. This is the baseline method for determining the maximum (average) conducted PSD level. If the instrument has an RMS power averaging detector, it must be used; otherwise, use the sample detector. The EUT must be configured to transmit continuously (duty cycle  $\geq 98\%$ ); otherwise sweep triggering/signal gating must be implemented to ensure that measurements are made only when the EUT is transmitting at its maximum power control level (no transmitter off time is to be considered).

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT was operating in controlled its channel.

a) Set instrument center frequency to DTS channel center frequency.

b) Set span to at least 1.5 times the OBW.

c) Set RBW to:  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ .

d) Set VBW  $\geq 3 \times \text{RBW}$ .

e) Detector = power averaging (RMS) or sample detector (when RMS not available).

f) Ensure that the number of measurement points in the sweep  $\geq 2 \times \text{span}/\text{RBW}$ .

g) Sweep time = auto couple.

h) Employ trace averaging (RMS) mode over a minimum of 100 traces.

i) Use the peak marker function to determine the maximum amplitude level.

j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat (note that this may require zooming in on the emission of interest and reduc

**7.7.6 Test Results**

EUT:	HOMTOM Smart phone	Model No.:	HT7
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode1/Mode2/Mode3/Mode4	Test By:	Susan Su

Test Channel	Frequency (MHz)	Power Density (dBm/3KHz)	Limit (dBm/3KHz)	Verdict
<b>802.11b</b>				
1	2412	-20.35	8	PASS
6	2437	-19.40	8	PASS
11	2462	-18.73	8	PASS
<b>802.11g</b>				
1	2412	-24.93	8	PASS
6	2437	-22.50	8	PASS
11	2462	-24.58	8	PASS
<b>802.11n HT20</b>				
1	2412	-24.00	8	PASS
6	2437	-22.58	8	PASS
11	2462	-23.50	8	PASS
<b>802.11n HT40</b>				
3	2422	-29.95	8	PASS
6	2437	-25.50	8	PASS
9	2452	-28.64	8	PASS











Power spectral density plot on channel 1

802.11n HT20



Power spectral density plot on channel 6


802.11n HT20






Power spectral density plot on channel 6

802.11n HT40



Power spectral density plot on channel 9

802.11n HT40



## **7.8 CONDUCTED BAND EDGE MEASUREMENT**

### **7.8.1 Applicable Standard**

According to FCC Part 15.247(d) and KDB 558074 DTS 01 Meas. Guidance v03r04

### **7.8.2 Conformance Limit**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

### **7.8.3 Measuring Instruments**

The Measuring equipment is listed in the section 6.3 of this test report.

### **7.8.4 Test Setup**

Please refer to Section 6.1 of this test report.

### **7.8.5 Test Procedure**

The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r04.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT was operating in controlled its channel.

Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.

Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.

Repeat above procedures until all measured frequencies were complete.

**7.8.6 Test Results**

EUT:	HOMTOM Smart phone	Model No.:	HT7
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode1/Mode2/Mode3/Mode4	Test By:	Susan Su

Frequency Band	Delta Peak to band emission(dBc)	>Limit(dBc)	Verdict
802.11b			
2400	65.453	20	Pass
2483.5	47.825	20	Pass
802.11g			
2400	38.805	20	Pass
2483.5	47.323	20	Pass
802.11n HT20			
2400	39.403	20	Pass
2483.5	42.228	20	Pass
802.11n HT40			
2400	43.162	20	Pass
2483.5	42.760	20	Pass







802.11n HT20: Band Edge-Low Channel



802.11n HT20: Band Edge-High Channel





## **7.9 ANTENNA APPLICATION**

### **7.9.1 Antenna Requirement**

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

### **7.9.2 Result**

The EUT antenna is permanent attached antenna. It comply with the standard requirement.

END OF REPORT