



# TEST REPORT

**Reference No.**..... : WTF21F03020086W002  
**FCC ID** ..... : 2AH9L-EVAWIFI  
**Applicant**..... : Stadler Form Aktiengesellschaft  
**Address**..... : Chamerstrasse 1746300 Zug, Switzerland  
**Manufacturer** ..... : Foshan Shunde Esite Electrical Appliances Co., Ltd  
**Address**..... : NO.4, Xingye Road, Beijiao Industrial Park, Beijiao, Shunde, Foshan, Guangdong, China  
**Product Name**..... : Humidifier  
**Model No**..... : EVA WIFI  
**Standards**..... : FCC CFR47 Part 15 Subpart C (Section 15.247): 2019  
**Date of Receipt sample** .... : 2021-03-15  
**Date of Test** ..... : 2021-05-20  
**Date of Issue**..... : 2021-07-21  
**Test Result**..... : **Pass**

## Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

## Prepared By:

**Waltek Testing Group (Foshan) Co., Ltd.**

Address: No.13-19, 2/F., 2nd Building, Sunlink International Machinery City,  
Chencun, Shunde District, Foshan, Guangdong, China

Tel: +86-757-23811398

Fax: +86-757-23811381

E-mail: info@waltek.com.cn

Compiled by:

Roy Hong / Project Engineer

Approved by:

Danny Zhou / Manager



## 1 Revision History

| Test Report No.    | Date of Issue | Description | Status |
|--------------------|---------------|-------------|--------|
| WTF21F03020086W002 | 2021-07-21    | Original    | Valid  |

# WALTEK



## 2 Contents

|                                            | Page |
|--------------------------------------------|------|
| 1 REVISION HISTORY.....                    | 2    |
| 2 CONTENTS.....                            | 3    |
| 3 GENERAL INFORMATION.....                 | 4    |
| 3.1 GENERAL DESCRIPTION OF E.U.T .....     | 4    |
| 3.2 TECHNICAL CHARACTERISTICS OF EUT ..... | 4    |
| 4 MAXIMUM PERMISSIBLE EXPOSURE (MPE).....  | 5    |
| 4.1 STANDARD APPLICABLE.....               | 5    |
| 4.2 MPE CALCULATION METHOD.....            | 6    |
| 4.3 MPE CALCULATION RESULT.....            | 6    |

# WALTEK





### 3 General Information

#### 3.1 General Description of E.U.T

Product Name ..... : Humidifier  
Model No. .... : EVA WiFi  
Model Description ..... : ---  
Rated Voltage..... : AC 120V, 60Hz, 95W  
Battery Capacity ..... : ---  
Power Adapter ..... : ---

#### 3.2 Technical Characteristics of EUT

Support Standards ..... : 802.11b, 802.11g, 802.11n  
Frequency Range ..... : 2412-2462MHz for 802.11b/g/n(HT20)  
RF Output Power ..... : 16.45dBm (Conducted )  
Modulation ..... : 802.11b: DSSS(DBPSK/DQPSK/CCK)  
802.11g/n: OFDM (BPSK/QPSK/16QAM/64QAM)  
Data Rate ..... : 1Mbps for 802.11b; 6Mbps for 802.11g;MCS0 for 802.11n  
Quantity of Channels ..... : 11 for 802.11b/g/n(HT20)  
Channel Separation..... : 5MHz  
Type of Antenna ..... : PCB Printed Antenna  
Antenna Gain ..... : 3dBi  
Lowest Oscillation..... : 40MHz



## 4 MAXIMUM PERMISSIBLE EXPOSURE (MPE)

### 4.1 Standard Applicable

According to §1.1307(b)(1) and KDB 447498 D01 General RF Exposure Guidance v06, system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

#### (a) Limits for Occupational / Controlled Exposure

| Frequency range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/cm <sup>2</sup> ) | Averaging Times   E   <sup>2</sup> ,   H   <sup>2</sup> or S (minutes) |
|-----------------------|-----------------------------------|-----------------------------------|-----------------------------------------|------------------------------------------------------------------------|
| 0.3-3.0               | 614                               | 1.63                              | (100)*                                  | 6                                                                      |
| 3.0-30                | 1842/f                            | 4.89/f                            | (900/f)*                                | 6                                                                      |
| 30-300                | 61.4                              | 0.163                             | 1.0                                     | 6                                                                      |
| 300-1500              | /                                 | /                                 | F/300                                   | 6                                                                      |
| 1500-100000           | /                                 | /                                 | 5                                       | 6                                                                      |

#### (b) Limits for General Population / Uncontrolled Exposure

| Frequency range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/cm <sup>2</sup> ) | Averaging Times   E   <sup>2</sup> ,   H   <sup>2</sup> or S (minutes) |
|-----------------------|-----------------------------------|-----------------------------------|-----------------------------------------|------------------------------------------------------------------------|
| 0.3-1.34              | 614                               | 1.63                              | (100)*                                  | 30                                                                     |
| 1.34-30               | 824/f                             | 2.19/f                            | (180/f)*                                | 30                                                                     |
| 30-300                | 27.5                              | 0.073                             | 0.2                                     | 30                                                                     |
| 300-1500              | /                                 | /                                 | F/1500                                  | 30                                                                     |
| 1500-100000           | /                                 | /                                 | 1                                       | 30                                                                     |

Note: f = frequency in MHz; \* = Plane-wave equivalents power density



## 4.2 MPE Calculation Method

$$S = (30 \cdot P \cdot G) / (377 \cdot R^2)$$

S = power density (in appropriate units, e.g., mW/cm<sup>2</sup>)

P = power input to the antenna (in appropriate units, e.g., mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor is normally numeric gain.

R = distance to the center of radiation of the antenna (in appropriate units, e.g., cm)

## 4.3 MPE Calculation Result

| Prediction distance (mm) | Prediction frequency (MHz) | Antenna Gain (dBi) | Numeric gain | Maximum Tune-up output power (dBm) | Maximum peak output power (mW) | PD (mW/cm <sup>2</sup> ) | Limit (mW/cm <sup>2</sup> ) |
|--------------------------|----------------------------|--------------------|--------------|------------------------------------|--------------------------------|--------------------------|-----------------------------|
| >200                     | 2462                       | 3.0                | 2.00         | 16.45                              | 44.16                          | 0.0175275                | 1.0                         |

Result: Pass

=====End of Report=====

# WALTEK