

TEST REPORT

Reference No..... : WTX23X02016597W003
FCC ID : 2AHAF-MDT865
Applicant : TOPICON HK LIMITED
Address : Room 2314-2316, Tower C, Huangdu Plaza, Yitian Road, Futian District,
Shenzhen, China
Manufacturer : The same as Applicant
Address : The same as Applicant
Product Name : Tablet
Model No..... : MDT865
Standards : FCC Part 2.1093
IEEE Std C95.1: 2019
IEEE Std C95.3: 2002 + Rev. 2008
IEEE 1528:2013
Date of Receipt sample : 2023-02-24
Date of Test..... : 2023-02-24 to 2023-02-28
Date of Issue : 2023-02-28
Test Report Form No. : WTX_IEEE_1528_2013W
Test Result..... : **Pass**

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of approver.

Prepared By:

Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road,
Block 70 Bao'an District, Shenzhen, Guangdong, China
Tel.: +86-755-33663308 Fax.: +86-755-33663309 Email: sem@waltek.com.cn

Tested by:

Jack Sun

Jack Sun

Approved by:

Silin Chen

Silin Chen

TABLE OF CONTENTS

1. General Information4

 1.1 Product Description for Equipment Under Test (EUT)4

 1.2 Test Standards6

 1.3 Test Methodology6

 1.4 Test Facility6

2. Summary of Test Results7

3. Specific Absorption Rate (SAR).....8

 3.1 Introduction.....8

 3.2 SAR Definition8

4. SAR Measurement System9

 4.1 The Measurement System9

 4.2 Probe.....9

 4.3 Probe Calibration Process.....11

 4.4 Phantom12

 4.5 Device Holder.....12

 4.6 Test Equipment List13

5. Tissue Simulating Liquids.....14

 5.1 Composition of Tissue Simulating Liquid14

 5.2 Tissue Dielectric Parameters for Head and Body Phantoms15

 5.3 Tissue Calibration Result.....16

6. SAR Measurement Evaluation17

 6.1 Purpose of System Performance Check.....17

 6.2 System Setup17

 6.3 Validation Results.....18

7. EUT Testing Position19

 7.1 Define Two Imaginary Lines on The Handset.....19

 7.2 Cheek Position20

 7.3 Tilted Position20

 7.4 Body Position21

 7.5 EUT Antenna Position21

 7.6 EUT Testing Position.....22

8. SAR Measurement Procedures23

 8.1 Measurement Procedures23

 8.2 Spatial Peak SAR Evaluation23

 8.3 Area & Zoom Scan Procedures.....24

 8.4 Volume Scan Procedures.....24

 8.5 SAR Averaged Methods24

 8.6 Power Drift Monitoring.....24

9. SAR Test Result25

 9.1 Conducted RF Output Power25

 9.2 Test Results for Standalone SAR Test.....52

10. Measurement Uncertainty54

 10.1 Uncertainty for SAR Test.....54

Annex A. Plots of System Performance Check56

Annex B. Plots of SAR Measurement64

Annex C. EUT Photos74

Annex D. Test Setup Photos76

Annex E. Calibration Certificate.....78

Report version

Version No.	Date of issue	Description
Rev.00	2023-03-01	Original
/	/	/

1. General Information

1.1 Product Description for Equipment Under Test (EUT)

General Description of EUT:	
Product Name:	Tablet
Brand Name:	/
Model No.:	MDT865
Adding Model(s):	PaceBlade MDT-801, OBC865, M865A, M865B, MDT865D
Rated Voltage:	DC3.8V
Adapter Model:	/
Test Sample No.:	WTX23X02016597W003#
Software Version:	mdt865_gms_0.6.7
Hardware Version:	MDT1065-MB-V30
<i>Note: The test data is gathered from a production sample provided by the manufacturer. The appearance of others models listed in the report is different from main-test model MDT865, but the circuit and the electronic construction do not change, declared by the manufacturer.</i>	

Technical Characteristics of EUT:	
4G	
Support Networks:	FDD-LTE
Support Band:	FDD-LTE Band 2, 4, 5, 12, 17,
Uplink Frequency:	FDD-LTE Band 2: Tx: 1850-1910MHz, FDD-LTE Band 4: Tx: 1710-1755MHz, FDD-LTE Band 5: Tx: 824-849MHz, FDD-LTE Band 12: Tx: 699-716MHz, FDD-LTE Band 17: Tx: 704-716MHz
Downlink Frequency:	FDD-LTE Band 2: Rx: 1930-1990MHz, FDD-LTE Band 4: Rx: 2110-2155MHz, FDD-LTE Band 5: Rx: 869-894MHz, FDD-LTE Band 12: Rx: 729-746MHz, FDD-LTE Band 17: Rx: 734-746MHz
RF Output Power:	FDD-LTE Band 2: 23.12dBm, FDD-LTE Band 4: 22.05dBm, FDD-LTE Band 5: 23.85dBm, FDD-LTE Band 12: 25.12dBm, FDD-LTE Band 17: 24.36dBm
Type of Modulation:	QPSK, 16QAM
Antenna Type:	PCB Antenna
Antenna Gain:	FDD-LTE Band 2: 1.83dBi, FDD-LTE Band 4: 1dBi, FDD-LTE Band 5: -0.16dBi, FDD-LTE Band 12: -2.28dBi, FDD-LTE Band 17: -2.28dBi

1.2 Test Standards

The following report is accordance with FCC 47 CFR Part 2.1093, IEEE Std C95.1: 2019, IEEE Std C95.3: 2002 + Rev. 2008, IEEE 1528:2013, KDB 447498 D01 v06, KDB 648474 D04 v01r03, KDB 248227 D01 v02r02, KDB 941225 D01 v03r01, KDB 941225 D05 v02r05 , and KDB 865664 D01 v01r04 and KDB 865664 D02 v01r02.

The objective is to determine compliance with FCC Part 2.1093 of the Federal Communication Commissions rules.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which is result in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with KDB 865664 D01 v01r04 and KDB 865664 D02 v01r02. The public notice KDB 447498 D01 v06 for Mobile and Portable Devices RF Exposure Procedure also.

1.4 Test Facility

Address of the test laboratory

Laboratory: Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road,Block 70 Bao'an District, Shenzhen, Guangdong, China

FCC – Registration No.: 125990

Waltek Testing Group (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. The Designation Number is CN5010. Test Firm Registration Number is 125990.

Industry Canada (IC) Registration No.: 11464A

The 3m Semi-anechoic chamber of Waltek Testing Group (Shenzhen) Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A and the CAB identifier is CN0057.

2. Summary of Test Results

The maximum results of Specific Absorption Rate (SAR) have found during testing are as follows:

Frequency Band	Body (0mm Gap)	SAR _{1g} Limit (W/kg)
	Maximum SAR _{1g} (W/kg)	
LTE	0.797	1.6

Class II Permissive Change: The device has updated the software to turns off the NFC, Bluetooth, Wi-Fi, GSM, WCDMA and LTE Band 7, 38, 40, 66.

Note: Report is for Class II Permissive Change only, and all items are retested.

The device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg) specified in FCC 47 CFR Part 2.1093 and IEEE Std C95.1: 2019 and had been tested in accordance with the measurement methods and procedure specified in IEEE 1528:2013 and KDB 865664 D01 v01r04 and KDB 865664 D02 v01r02.

3. Specific Absorption Rate (SAR)

3.1 Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

3.2 SAR Definition

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$\text{SAR} = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg)

SAR measurement can be either related to the temperature elevation in tissue by

$$\text{SAR} = C \left(\frac{\delta T}{\delta t} \right)$$

Where: C is the specific heat capacity, δT is the temperature rise and δt is the exposure duration, or related to the electrical field in the tissue by

$$\text{SAR} = \frac{\sigma |E|^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of the tissue and E is the RMS electrical field strength.

However for evaluating SAR of low power transmitter, electrical field measurement is typically applied.

4. SAR Measurement System

4.1 The Measurement System

Comosar is a system that is able to determine the SAR distribution inside a phantom of human being according to different standards. The Comosar system consists of the following items:

- Main computer to control all the system
- 6 axis robot
- Data acquisition system
- Miniature E-field probe
- Phone holder
- Head simulating tissue

The following figure shows the system.




The EUT under test operating at the maximum power level is placed in the phone holder, under the phantom, which is filled with head simulating liquid. The E-Field probe measures the electric field inside the phantom. The OpenSAR software computes the results to give a SAR value in a 1g or 10g mass.

4.2 Probe

For the measurements the Specific Dosimetric E-Field Probe SSE2 SN 18/21 EPGO356, and refer to the calibration report for probe parameters.

Probe calibration is realized, in compliance with EN 62209-1 and IEEE 1528:2013 STD, with CALISAR, Antenna proprietary calibration system. The calibration is performed with the EN 62209-1 annexes technique using reference guide at the five frequencies.



$$SAR = \frac{4(P_{fw} - P_{bw})}{ab\delta} \cos^2\left(\pi \frac{y}{a}\right) e^{-2z/\delta}$$

Where :

P_{fw} = Forward Power

P_{bw} = Backward Power

a and b = Waveguide dimensions

l = Skin depth

Keithley configuration:

Rate = Medium; Filter = ON; RDGS = 10; Filter type = Moving Average; Range auto after each calibration, a SAR measurement is performed on a validation dipole and compared with a NPL calibrated probe, to verify it.

The calibration factors, CF(N), for the 3 sensors corresponding to dipole 1, dipole 2 and dipole 3 are:

$$CF(N) = SAR(N) / V_{lin}(N) \quad (N=1,2,3)$$

The linearised output voltage V_{lin}(N) is obtained from the displayed output voltage V(N) using

$$V_{lin}(N) = V(N) * (1 + V(N) / DCP(N)) \quad (N=1,2,3)$$

where DCP is the diode compression point in mV.

4.3 Probe Calibration Process

Dosimetric Assessment Procedure

Each E-Probe/Probe Amplifier combination has unique calibration parameters. SATIMO Probe calibration procedure is conducted to determine the proper amplifier settings to enter in the probe parameters. The amplifier settings are determined for a given frequency by subjecting the probe to a known E-field density (1 mW/cm²) using an with CALISAR, Antenna proprietary calibration system.

Free Space Assessment Procedure

The free space E-field from amplified probe outputs is determined in a test chamber. This calibration can be performed in a TEM cell if the frequency is below 1 GHz and in a waveguide or other methodologies above 1 GHz for free space. For the free space calibration, the probe is placed in the volumetric center of the cavity and at the proper orientation with the field. The probe is rotated 360 degrees until the three channels show the maximum reading. The power density readings equates to 1mW/cm².

Temperature Assessment Procedure

E-field temperature correlation calibration is performed in a flat phantom filled with the appropriate simulated head tissue. The E-field in the medium correlates with the temperature rise in the dielectric medium. For temperature correlation calibration a RF transparent thermistor-based temperature probe is used in conjunction with the E-field probe.

$$SAR = C \frac{\Delta T}{\Delta t}$$

Where:

Δt = exposure time (30 seconds),

C = heat capacity of tissue (brain or muscle),

ΔT = temperature increase due to RF exposure.

SAR is proportional to $\Delta T/\Delta t$, the initial rate of tissue heating, before thermal diffusion takes place. The electric field in the simulated tissue can be used to estimate SAR by equating the thermally derived SAR to that with the E- field component.

$$SAR = \frac{|E|^2 \cdot \sigma}{\rho}$$

Where:

σ = simulated tissue conductivity,


ρ = Tissue density (1.25 g/cm³ for brain tissue)

4.4 Phantom

For the measurements the Specific Anthropomorphic Mannequin (SAM) defined by the IEEE SCC-34/SC2 group is used. The phantom is a polyurethane shell integrated in a wooden table. The thickness of the phantom amounts to 2mm +/- 0.2mm. It enables the dosimetric evaluation of left and right phone usage and includes an additional flat phantom part for the simplified performance check. The phantom set-up includes a cover, which prevents the evaporation of the liquid.

4.5 Device Holder

The positioning system allows obtaining cheek and tilting position with a very good accuracy. In compliance with CENELEC, the tilt angle uncertainty is lower than 1°.



System Material	Permittivity	Loss Tangent
Delrin	3.7	0.005


4.6 Test Equipment List

Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
E-Field Probe	MVG	SSE2	SN 18/21 EPGO356	2022-07-08	2023-07-07
750MHz Dipole	MVG	SID750	SN 47/12 DIP	2020-03-11	2023-03-10
835MHz Dipole	MVG	SID835	SN 47/12 DIP	2020-03-11	2023-03-10
900MHz Dipole	MVG	SID900	SN 47/12 DIP	2020-03-11	2023-03-10
1800MHz Dipole	MVG	SID1800	SN 47/12 DIP	2020-03-11	2023-03-10
1900MHz Dipole	MVG	SID1900	SN 47/12 DIP	2020-03-11	2023-03-10
2000MHz Dipole	MVG	SID2000	SN 47/12 DIP	2020-03-11	2023-03-10
2450MHz Dipole	MVG	SID2450	SN 13/15 DIP	2020-03-11	2023-03-10
2600MHz Dipole	MVG	SID2600	SN 28/21 DIP	2021-07-16	2024-07-15
5 GHz Dipole	MVG	SWG5500	SN 49/16 WGA45	2020-07-03	2023-07-02
Dielectric Probe	SATIMO	SCLMP	SN 47/12 OCPG49	2022-03-22	2023-03-21
SAM Phantom	SATIMO	SAM	SN/ 47/12 SAM95	N/A	N/A
Multi Meter	Keithley	Keithley 2000	4006367	2022-03-22	2023-03-21
Power meter	Keithley	3500	JC-2017-09-001	2022-03-22	2023-03-21
Power meter	Keithley	3500	JC-2017-09-001	2022-03-22	2023-03-21
Power Sensor	HP	11636B	JC-2017-10-002	2022-03-22	2023-03-21
MXG X-Series RF Vector Signal Generato	KEYSIGHT	N5182B	MY57300664	2022-03-22	2023-03-21
Universal Tester	Rohde & Schwarz	CMU200	112315	2022-03-22	2023-03-21
Universal Radio Communication Tester	Rohde & Schwarz	CMW500	148650	2022-03-22	2023-03-21
Network Analyzer	HP	8753C	2901A00831	2022-03-22	2023-03-21

5. Tissue Simulating Liquids

5.1 Composition of Tissue Simulating Liquid

For the measurement of the field distribution inside the SAM phantom with SMTIMO, the phantom must be filled with around 25 liters of homogeneous body tissue simulating liquid. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm. Please see the following photos for the liquid height.



Liquid Height for Head/Body SAR

The Composition of Tissue Simulating Liquid

Frequency (MHz)	Water (%)	Salt (%)	Sugar (%)	HEC (%)	Preventol (%)	DGBE (%)
Head/Body						
750	41.1	1.4	57.0	0.2	0.3	0
835	40.3	1.4	57.9	0.2	0.2	0
1700-1900	55.2	0.3	0	0	0	44.5
2300	55.0	0.2	0	0	0	44.8
2450	55.0	0.1	0	0	0	44.9
2600	54.9	0.1	0	0	0	45.0

5.2 Tissue Dielectric Parameters for Head and Body Phantoms

According to FCC KDBs, IEEE 1528:2013 and CEI/IEC 62209 standards state that the system validation measurements must be performed using a reference dipole meeting the fore mentioned return loss and mechanical dimension requirements. The validation measurement must be performed against a liquid filled flat phantom, with the phantom constructed as outlined in the fore mentioned standards. Per the standards, the dipole shall be positioned below the bottom of the phantom, with the dipole length centered and parallel to the longest dimension of the flat phantom, with the top surface of the dipole at the described distance from the bottom surface of the phantom.

Target Frequency (MHz)	Head		Body	
	Conductivity (σ)	Permittivity (ϵ_r)	Conductivity (σ)	Permittivity (ϵ_r)
150	0.76	52.3	0.80	61.9
300	0.87	45.3	0.92	58.2
450	0.87	43.5	0.94	56.7
750	0.89	41.9	0.96	55.5
835	0.90	41.5	0.97	55.2
900	0.97	41.5	1.05	55.0
915	0.98	41.5	1.06	55.0
1450	1.20	40.5	1.30	54.0
1610	1.29	40.3	1.40	53.8
1800-2000	1.40	40.0	1.52	53.3
2300	1.67	39.5	1.81	52.9
2450	1.80	39.2	1.95	52.7
2600	1.96	39.0	2.16	52.5
3000	2.40	38.5	2.73	52.0
5200	4.66	36.0	5.30	49.0
5400	4.86	35.8	5.53	48.7
5600	5.07	35.5	5.77	48.5
5800	5.27	35.3	6.00	48.2

5.3 Tissue Calibration Result

The dielectric parameters of the liquids were verified prior to the SAR evaluation using COMOSAR Dielectric Probe Kit and an Agilent Network Analyzer.

Calibration Result for Dielectric Parameters of Tissue Simulating Liquid

Body Tissue Simulating Liquid									
Freq. MHz.	Temp. (°C)	Conductivity			Permittivity			Limit (%)	Date
		Reading (σ)	Target (σ)	Delta (%)	Reading (ϵ_r)	Target (ϵ_r)	Delta (%)		
750	23.5	0.95	0.96	-1.04	54.34	55.5	-2.09	±5	2023-02-28
835	23.5	0.94	0.97	-3.09	54.46	55.2	-1.34	±5	2023-02-28
1800	23.7	1.50	1.52	-1.32	54.67	53.3	2.57	±5	2023-02-27
1900	23.7	1.53	1.52	0.66	54.54	53.3	2.33	±5	2023-02-27


6. SAR Measurement Evaluation

6.1 Purpose of System Performance Check

The system performance check verifies that the system operates within its specifications. System and operator errors can be detected and corrected. It is recommended that the system performance check be performed prior to any usage of the system in order to guarantee reproducible results. The system performance check uses normal SAR measurements in a simplified setup with a well characterized source. This setup was selected to give a high sensitivity to all parameters that might fail or vary over time. The system check does not intend to replace the calibration of the components, but indicates situations where the system uncertainty is exceeded due to drift or failure.

6.2 System Setup

In the simplified setup for system evaluation, the EUT is replaced by a calibrated dipole and the power source is replaced by a continuous wave which comes from a signal generator at frequency 750MHz, 835MHz, 1800MHz, 1900MHz, 2300MHz, 2450MHz, and 2600MHz. The calibrated dipole must be placed beneath the flat phantom section of the SAM twin phantom with the correct distance holder. The distance holder should touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom.



System Verification Setup Block Diagram



Setup Photo of Dipole Antenna

The output power on dipole port must be calibrated to 24 dBm(250 mW) before dipole is connected.
 The output power on 5 GHz Waveguide must be calibrated to 20 dBm (100mW) before 5 GHz Waveguide is connected.

6.3 Validation Results

Comparing to the original SAR value provided by SATIMO, the validation data should be within its specification of 10 %. Table 6.1 shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance check can meet the variation criterion.

Frequency	Targeted SAR _{1g}	Measured SAR _{1g}	Normalized SAR _{1g}	Tolerance	Date
MHz	(W/kg)	(W/kg)	(W/kg)	(%)	
Body					
750	8.40	2.12	8.48	0.95	2023-02-28
835	9.36	2.35	9.4	0.43	2023-02-28
1800	38.29	9.58	38.32	0.08	2023-02-27
1900	39.01	9.78	39.12	0.28	2023-02-27

Remark: Referring to IEEE 1528:2013, Section 8.2, the system check shall be performed at a test frequency that is within $\pm 10\%$ or ± 100 MHz of the compliance test mid-band frequency, so the 1750 MHz system verification is made of 1800MHz Dipole.

Targeted and Measurement SAR

Please refer to Annex A for the plots of system performance check.

7. EUT Testing Position

7.1 Define Two Imaginary Lines on The Handset

(a) The vertical centerline passes through two points on the front side of the handset - the midpoint of the width w_t of the handset at the level of the acoustic output, and the midpoint of the width w_b of the bottom of the handset.

(b) The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output. The horizontal line is also tangential to the face of the handset at point A.

(c) The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily parallel to the front face of the handset, especially for clamshell handsets, handsets with flip covers, and other irregularly shaped handsets.




Illustration for Handset Vertical and Horizontal Reference Lines

7.2 Cheek Position

(a) To position the device with the vertical center line of the body of the device and the horizontal line crossing the center piece in a plane parallel to the sagittal plane of the phantom. While maintaining the device in this plane, align the vertical center line with the reference plane containing the three ear and mouth reference point (M: Mouth, RE: Right Ear, and LE: Left Ear) and align the center of the ear piece with the line RE-LE.

(b) To move the device towards the phantom with the ear piece aligned with the line LE-RE until the phone touched the ear. While maintaining the device in the reference plane and maintaining the phone contact with the ear, move the bottom of the phone until any point on the front side is in contact with the cheek of the phantom or until contact with the ear is lost (see Fig. 7.2).




Illustration for Cheek Position

7.3 Tilted Position

(a) To position the device in the “cheek” position described above.

(b) While maintaining the device the reference plane described above and pivoting against the ear, moves it outward away from the mouth by an angle of 15 degrees or until contact with the ear is lost (see Fig. 7.3).




Illustration for Tilted Position

7.4 Body Position

- (a) To position the device parallel to the phantom surface with each side.
- (b) To adjust the device parallel to the flat phantom.
- (c) To adjust the distance between the device surface and the flat phantom to 0mm.





Illustration for Body Position

7.5 EUT Antenna Position



Block Diagram for EUT Antenna Position

Distance of EUT antenna-to-edge/surface(mm), Test distance:0mm						
Antennas	Back side	Front side	Left Edge	Right Edge	Top Edge	Bottom Edge
WWAN	<25	<25	190	<25	<25	140

7.6 EUT Testing Position

Body mode SAR assessments are required for this device. This EUT was tested in different positions for different SAR test modes, more information as below:

Body SAR tests, Test distance: 0mm						
Antennas	Back	Front	Left Side	Right Side	Top Side	Bottom Side
WWAN	Yes	/	No	Yes	Yes	No

Remark:

- Referring to KDB 447498 D01 v06, KDB 616217 D04 v01r02, and KDB 248227 D01 v02r02, this device is overall diagonal dimension (>20cm) tablet, tested in direct contact (no gap) with flat phantom.
- Referring to KDB 616217 D04 v01r02, Exposures from antennas through the front (top) surface of the display section of a full-size tablet, away from the edges, are generally limited to the user's hands. Exposures to hands for typical consumer transmitters used in tablets are not expected to exceed the extremity SAR limit; therefore, SAR evaluation for the front surface of tablet display screens are generally not necessary.
- Referring to KDB 648474 D04 Handset SAR v01r03, 10-g extremity SAR is required only for the surfaces and edges with hotspot mode 1-g reported SAR > 1.2 W/kg.
- When using the accessory vehicle bracket or desktop docking station, the tablet will not touch the human body, additional SAR evaluation for this configuration is not required.

Please refer to Annex D for the EUT test setup photos.

8. SAR Measurement Procedures

8.1 Measurement Procedures

The measurement procedures are as follows:

- (a) Use base station simulator (if applicable) or engineering software to transmit RF power continuously (continuous Tx) in the highest power channel.
- (b) Keep EUT to radiate maximum output power or 100% factor (if applicable)
- (c) Measure output power through RF cable and power meter.
- (d) Place the EUT in the positions as Annex D demonstrates.
- (e) Set scan area, grid size and other setting on the SATIMO software.
- (f) Measure SAR results for the highest power channel on each testing position.
- (g) Find out the largest SAR result on these testing positions of each band
- (h) Measure SAR results for other channels in worst SAR testing position if the SAR of highest power channel is larger than 0.8 W/kg

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

8.2 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The SATIMO software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine. The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values from the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

8.3 Area & Zoom Scan Procedures

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan measures 5x5x7 points with step size 8, 8 and 5 mm for 300 MHz to 3 GHz, and 8x8x8 points with step size 4, 4 and 2.5 mm for 3 GHz to 6 GHz. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g.

8.4 Volume Scan Procedures

The volume scan is used for assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing (step-size is 4, 4 and 2.5 mm). When all volume scan were completed, the software can combine and subsequently superpose these measurement data to calculating the multiband SAR.

8.5 SAR Averaged Methods

The local SAR inside the phantom is measured using small dipole sensing elements inside a probe body. The probe tip must not be in contact with the phantom surface in order to minimize measurements errors, but the highest local SAR will occur at the surface of the phantom.

An extrapolation is using to determinate this highest local SAR values. The extrapolation is based on a fourth-order least-square polynomial fit of measured data. The local SAR value is then extrapolated from the liquid surface with a 1mm step.

The measurements have to be performed over a limited time (due to the duration of the battery) so the step of measurement is high. It could vary between 5 and 8 mm. To obtain an accurate assessment of the maximum SAR averaged over 10g and 1 g requires a very fine resolution in the three dimensional scanned data array.

8.6 Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In SATIMO measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drift more than 5%, the SAR will be retested.

9. SAR Test Result

9.1 Conducted RF Output Power

Band	Bandwidth	Modulation	Channel	RB Configuration	Result(dBm)	Tune-up power (dBm)	Verdict
Band2	1.4MHz	QPSK	18607	1RB#0	22.65	23.5	PASS
Band2	1.4MHz	QPSK	18607	1RB#2	22.86	23.5	PASS
Band2	1.4MHz	QPSK	18607	1RB#5	22.70	23.5	PASS
Band2	1.4MHz	QPSK	18607	3RB#0	22.73	23.5	PASS
Band2	1.4MHz	QPSK	18607	3RB#1	22.72	23.5	PASS
Band2	1.4MHz	QPSK	18607	3RB#3	22.76	23.5	PASS
Band2	1.4MHz	QPSK	18607	6RB#0	21.78	23.5	PASS
Band2	1.4MHz	QPSK	18900	1RB#0	22.61	23.5	PASS
Band2	1.4MHz	QPSK	18900	1RB#2	22.77	23.5	PASS
Band2	1.4MHz	QPSK	18900	1RB#5	22.56	23.5	PASS
Band2	1.4MHz	QPSK	18900	3RB#0	22.68	23.5	PASS
Band2	1.4MHz	QPSK	18900	3RB#1	22.72	23.5	PASS
Band2	1.4MHz	QPSK	18900	3RB#3	22.71	23.5	PASS
Band2	1.4MHz	QPSK	18900	6RB#0	21.65	23.5	PASS
Band2	1.4MHz	QPSK	19193	1RB#0	22.36	23.5	PASS
Band2	1.4MHz	QPSK	19193	1RB#2	22.41	23.5	PASS
Band2	1.4MHz	QPSK	19193	1RB#5	22.32	23.5	PASS
Band2	1.4MHz	QPSK	19193	3RB#0	22.43	23.5	PASS
Band2	1.4MHz	QPSK	19193	3RB#1	22.48	23.5	PASS
Band2	1.4MHz	QPSK	19193	3RB#3	22.42	23.5	PASS
Band2	1.4MHz	QPSK	19193	6RB#0	21.38	23.5	PASS
Band2	1.4MHz	16QAM	18607	1RB#0	21.68	23.5	PASS
Band2	1.4MHz	16QAM	18607	1RB#2	21.87	23.5	PASS
Band2	1.4MHz	16QAM	18607	1RB#5	21.65	23.5	PASS
Band2	1.4MHz	16QAM	18607	3RB#0	21.58	23.5	PASS
Band2	1.4MHz	16QAM	18607	3RB#1	21.55	23.5	PASS
Band2	1.4MHz	16QAM	18607	3RB#3	21.54	23.5	PASS
Band2	1.4MHz	16QAM	18607	6RB#0	20.80	23.5	PASS
Band2	1.4MHz	16QAM	18900	1RB#0	21.70	23.5	PASS
Band2	1.4MHz	16QAM	18900	1RB#2	21.88	23.5	PASS

Band2	1.4MHz	16QAM	18900	1RB#5	21.60	23.5	PASS
Band2	1.4MHz	16QAM	18900	3RB#0	21.59	23.5	PASS
Band2	1.4MHz	16QAM	18900	3RB#1	21.63	23.5	PASS
Band2	1.4MHz	16QAM	18900	3RB#3	21.57	23.5	PASS
Band2	1.4MHz	16QAM	18900	6RB#0	20.80	23.5	PASS
Band2	1.4MHz	16QAM	19193	1RB#0	21.35	23.5	PASS
Band2	1.4MHz	16QAM	19193	1RB#2	21.48	23.5	PASS
Band2	1.4MHz	16QAM	19193	1RB#5	21.39	23.5	PASS
Band2	1.4MHz	16QAM	19193	3RB#0	21.35	23.5	PASS
Band2	1.4MHz	16QAM	19193	3RB#1	21.36	23.5	PASS
Band2	1.4MHz	16QAM	19193	3RB#3	21.28	23.5	PASS
Band2	1.4MHz	16QAM	19193	6RB#0	20.47	23.5	PASS
Band2	3MHz	QPSK	18615	1RB#0	22.77	23.5	PASS
Band2	3MHz	QPSK	18615	1RB#8	22.73	23.5	PASS
Band2	3MHz	QPSK	18615	1RB#14	22.72	23.5	PASS
Band2	3MHz	QPSK	18615	8RB#0	21.83	23.5	PASS
Band2	3MHz	QPSK	18615	8RB#4	21.84	23.5	PASS
Band2	3MHz	QPSK	18615	8RB#7	21.81	23.5	PASS
Band2	3MHz	QPSK	18615	15RB#0	21.74	23.5	PASS
Band2	3MHz	QPSK	18900	1RB#0	22.69	23.5	PASS
Band2	3MHz	QPSK	18900	1RB#8	22.67	23.5	PASS
Band2	3MHz	QPSK	18900	1RB#14	22.69	23.5	PASS
Band2	3MHz	QPSK	18900	8RB#0	21.73	23.5	PASS
Band2	3MHz	QPSK	18900	8RB#4	21.72	23.5	PASS
Band2	3MHz	QPSK	18900	8RB#7	21.73	23.5	PASS
Band2	3MHz	QPSK	18900	15RB#0	21.69	23.5	PASS
Band2	3MHz	QPSK	19185	1RB#0	22.40	23.5	PASS
Band2	3MHz	QPSK	19185	1RB#8	22.41	23.5	PASS
Band2	3MHz	QPSK	19185	1RB#14	22.41	23.5	PASS
Band2	3MHz	QPSK	19185	8RB#0	21.42	23.5	PASS
Band2	3MHz	QPSK	19185	8RB#4	21.44	23.5	PASS
Band2	3MHz	QPSK	19185	8RB#7	21.42	23.5	PASS
Band2	3MHz	QPSK	19185	15RB#0	21.44	23.5	PASS
Band2	3MHz	16QAM	18615	1RB#0	21.91	23.5	PASS
Band2	3MHz	16QAM	18615	1RB#8	21.80	23.5	PASS
Band2	3MHz	16QAM	18615	1RB#14	21.82	23.5	PASS
Band2	3MHz	16QAM	18615	8RB#0	20.90	23.5	PASS

Band2	3MHz	16QAM	18615	8RB#4	20.86	23.5	PASS
Band2	3MHz	16QAM	18615	8RB#7	20.82	23.5	PASS
Band2	3MHz	16QAM	18615	15RB#0	20.80	23.5	PASS
Band2	3MHz	16QAM	18900	1RB#0	21.95	23.5	PASS
Band2	3MHz	16QAM	18900	1RB#8	21.87	23.5	PASS
Band2	3MHz	16QAM	18900	1RB#14	21.82	23.5	PASS
Band2	3MHz	16QAM	18900	8RB#0	20.88	23.5	PASS
Band2	3MHz	16QAM	18900	8RB#4	20.86	23.5	PASS
Band2	3MHz	16QAM	18900	8RB#7	20.82	23.5	PASS
Band2	3MHz	16QAM	18900	15RB#0	20.76	23.5	PASS
Band2	3MHz	16QAM	19185	1RB#0	21.62	23.5	PASS
Band2	3MHz	16QAM	19185	1RB#8	21.55	23.5	PASS
Band2	3MHz	16QAM	19185	1RB#14	21.49	23.5	PASS
Band2	3MHz	16QAM	19185	8RB#0	20.54	23.5	PASS
Band2	3MHz	16QAM	19185	8RB#4	20.58	23.5	PASS
Band2	3MHz	16QAM	19185	8RB#7	20.55	23.5	PASS
Band2	3MHz	16QAM	19185	15RB#0	20.55	23.5	PASS
Band2	5MHz	QPSK	18625	1RB#0	22.67	23.5	PASS
Band2	5MHz	QPSK	18625	1RB#12	22.79	23.5	PASS
Band2	5MHz	QPSK	18625	1RB#24	22.62	23.5	PASS
Band2	5MHz	QPSK	18625	12RB#0	21.65	23.5	PASS
Band2	5MHz	QPSK	18625	12RB#6	21.62	23.5	PASS
Band2	5MHz	QPSK	18625	12RB#13	21.64	23.5	PASS
Band2	5MHz	QPSK	18625	25RB#0	21.63	23.5	PASS
Band2	5MHz	QPSK	18900	1RB#0	22.60	23.5	PASS
Band2	5MHz	QPSK	18900	1RB#12	22.71	23.5	PASS
Band2	5MHz	QPSK	18900	1RB#24	22.56	23.5	PASS
Band2	5MHz	QPSK	18900	12RB#0	21.68	23.5	PASS
Band2	5MHz	QPSK	18900	12RB#6	21.67	23.5	PASS
Band2	5MHz	QPSK	18900	12RB#13	21.56	23.5	PASS
Band2	5MHz	QPSK	18900	25RB#0	21.63	23.5	PASS
Band2	5MHz	QPSK	19175	1RB#0	22.36	23.5	PASS
Band2	5MHz	QPSK	19175	1RB#12	22.48	23.5	PASS
Band2	5MHz	QPSK	19175	1RB#24	22.32	23.5	PASS
Band2	5MHz	QPSK	19175	12RB#0	21.35	23.5	PASS
Band2	5MHz	QPSK	19175	12RB#6	21.40	23.5	PASS
Band2	5MHz	QPSK	19175	12RB#13	21.30	23.5	PASS

Band2	5MHz	QPSK	19175	25RB#0	21.39	23.5	PASS
Band2	5MHz	16QAM	18625	1RB#0	21.59	23.5	PASS
Band2	5MHz	16QAM	18625	1RB#12	21.66	23.5	PASS
Band2	5MHz	16QAM	18625	1RB#24	21.55	23.5	PASS
Band2	5MHz	16QAM	18625	12RB#0	20.64	23.5	PASS
Band2	5MHz	16QAM	18625	12RB#6	20.66	23.5	PASS
Band2	5MHz	16QAM	18625	12RB#13	20.68	23.5	PASS
Band2	5MHz	16QAM	18625	25RB#0	20.71	23.5	PASS
Band2	5MHz	16QAM	18900	1RB#0	21.63	23.5	PASS
Band2	5MHz	16QAM	18900	1RB#12	21.72	23.5	PASS
Band2	5MHz	16QAM	18900	1RB#24	21.57	23.5	PASS
Band2	5MHz	16QAM	18900	12RB#0	20.75	23.5	PASS
Band2	5MHz	16QAM	18900	12RB#6	20.67	23.5	PASS
Band2	5MHz	16QAM	18900	12RB#13	20.63	23.5	PASS
Band2	5MHz	16QAM	18900	25RB#0	20.78	23.5	PASS
Band2	5MHz	16QAM	19175	1RB#0	21.35	23.5	PASS
Band2	5MHz	16QAM	19175	1RB#12	21.44	23.5	PASS
Band2	5MHz	16QAM	19175	1RB#24	21.27	23.5	PASS
Band2	5MHz	16QAM	19175	12RB#0	20.45	23.5	PASS
Band2	5MHz	16QAM	19175	12RB#6	20.49	23.5	PASS
Band2	5MHz	16QAM	19175	12RB#13	20.43	23.5	PASS
Band2	5MHz	16QAM	19175	25RB#0	20.52	23.5	PASS
Band2	10MHz	QPSK	18650	1RB#0	22.69	23.5	PASS
Band2	10MHz	QPSK	18650	1RB#24	22.85	23.5	PASS
Band2	10MHz	QPSK	18650	1RB#49	22.68	23.5	PASS
Band2	10MHz	QPSK	18650	25RB#0	21.75	23.5	PASS
Band2	10MHz	QPSK	18650	25RB#12	21.72	23.5	PASS
Band2	10MHz	QPSK	18650	25RB#25	21.70	23.5	PASS
Band2	10MHz	QPSK	18650	50RB#0	21.76	23.5	PASS
Band2	10MHz	QPSK	18900	1RB#0	22.62	23.5	PASS
Band2	10MHz	QPSK	18900	1RB#24	22.79	23.5	PASS
Band2	10MHz	QPSK	18900	1RB#49	22.53	23.5	PASS
Band2	10MHz	QPSK	18900	25RB#0	21.78	23.5	PASS
Band2	10MHz	QPSK	18900	25RB#12	21.78	23.5	PASS
Band2	10MHz	QPSK	18900	25RB#25	21.65	23.5	PASS
Band2	10MHz	QPSK	18900	50RB#0	21.77	23.5	PASS
Band2	10MHz	QPSK	19150	1RB#0	22.44	23.5	PASS

Band2	10MHz	QPSK	19150	1RB#24	22.52	23.5	PASS
Band2	10MHz	QPSK	19150	1RB#49	22.30	23.5	PASS
Band2	10MHz	QPSK	19150	25RB#0	21.63	23.5	PASS
Band2	10MHz	QPSK	19150	25RB#12	21.60	23.5	PASS
Band2	10MHz	QPSK	19150	25RB#25	21.38	23.5	PASS
Band2	10MHz	QPSK	19150	50RB#0	21.49	23.5	PASS
Band2	10MHz	16QAM	18650	1RB#0	21.77	23.5	PASS
Band2	10MHz	16QAM	18650	1RB#24	21.89	23.5	PASS
Band2	10MHz	16QAM	18650	1RB#49	21.79	23.5	PASS
Band2	10MHz	16QAM	18650	25RB#0	20.73	23.5	PASS
Band2	10MHz	16QAM	18650	25RB#12	20.80	23.5	PASS
Band2	10MHz	16QAM	18650	25RB#25	20.74	23.5	PASS
Band2	10MHz	16QAM	18650	50RB#0	20.77	23.5	PASS
Band2	10MHz	16QAM	18900	1RB#0	21.82	23.5	PASS
Band2	10MHz	16QAM	18900	1RB#24	21.98	23.5	PASS
Band2	10MHz	16QAM	18900	1RB#49	21.70	23.5	PASS
Band2	10MHz	16QAM	18900	25RB#0	20.87	23.5	PASS
Band2	10MHz	16QAM	18900	25RB#12	20.89	23.5	PASS
Band2	10MHz	16QAM	18900	25RB#25	20.73	23.5	PASS
Band2	10MHz	16QAM	18900	50RB#0	20.83	23.5	PASS
Band2	10MHz	16QAM	19150	1RB#0	21.57	23.5	PASS
Band2	10MHz	16QAM	19150	1RB#24	21.75	23.5	PASS
Band2	10MHz	16QAM	19150	1RB#49	21.44	23.5	PASS
Band2	10MHz	16QAM	19150	25RB#0	20.64	23.5	PASS
Band2	10MHz	16QAM	19150	25RB#12	20.64	23.5	PASS
Band2	10MHz	16QAM	19150	25RB#25	20.47	23.5	PASS
Band2	10MHz	16QAM	19150	50RB#0	20.52	23.5	PASS
Band2	15MHz	QPSK	18675	1RB#0	22.45	23.5	PASS
Band2	15MHz	QPSK	18675	1RB#38	22.74	23.5	PASS
Band2	15MHz	QPSK	18675	1RB#74	22.53	23.5	PASS
Band2	15MHz	QPSK	18675	38RB#0	21.76	23.5	PASS
Band2	15MHz	QPSK	18675	38RB#18	21.79	23.5	PASS
Band2	15MHz	QPSK	18675	38RB#37	21.79	23.5	PASS
Band2	15MHz	QPSK	18675	75RB#0	21.80	23.5	PASS
Band2	15MHz	QPSK	18900	1RB#0	22.50	23.5	PASS
Band2	15MHz	QPSK	18900	1RB#38	22.64	23.5	PASS
Band2	15MHz	QPSK	18900	1RB#74	22.29	23.5	PASS

Band2	15MHz	QPSK	18900	38RB#0	21.64	23.5	PASS
Band2	15MHz	QPSK	18900	38RB#18	21.64	23.5	PASS
Band2	15MHz	QPSK	18900	38RB#37	21.63	23.5	PASS
Band2	15MHz	QPSK	18900	75RB#0	21.66	23.5	PASS
Band2	15MHz	QPSK	19125	1RB#0	22.27	23.5	PASS
Band2	15MHz	QPSK	19125	1RB#38	22.45	23.5	PASS
Band2	15MHz	QPSK	19125	1RB#74	22.15	23.5	PASS
Band2	15MHz	QPSK	19125	38RB#0	21.52	23.5	PASS
Band2	15MHz	QPSK	19125	38RB#18	21.55	23.5	PASS
Band2	15MHz	QPSK	19125	38RB#37	21.51	23.5	PASS
Band2	15MHz	QPSK	19125	75RB#0	21.53	23.5	PASS
Band2	15MHz	16QAM	18675	1RB#0	21.63	23.5	PASS
Band2	15MHz	16QAM	18675	1RB#38	21.84	23.5	PASS
Band2	15MHz	16QAM	18675	1RB#74	21.61	23.5	PASS
Band2	15MHz	16QAM	18675	38RB#0	21.77	23.5	PASS
Band2	15MHz	16QAM	18675	38RB#18	21.78	23.5	PASS
Band2	15MHz	16QAM	18675	38RB#37	21.79	23.5	PASS
Band2	15MHz	16QAM	18675	75RB#0	20.68	23.5	PASS
Band2	15MHz	16QAM	18900	1RB#0	21.70	23.5	PASS
Band2	15MHz	16QAM	18900	1RB#38	21.79	23.5	PASS
Band2	15MHz	16QAM	18900	1RB#74	21.45	23.5	PASS
Band2	15MHz	16QAM	18900	38RB#0	21.67	23.5	PASS
Band2	15MHz	16QAM	18900	38RB#18	21.67	23.5	PASS
Band2	15MHz	16QAM	18900	38RB#37	21.68	23.5	PASS
Band2	15MHz	16QAM	18900	75RB#0	20.65	23.5	PASS
Band2	15MHz	16QAM	19125	1RB#0	21.37	23.5	PASS
Band2	15MHz	16QAM	19125	1RB#38	21.54	23.5	PASS
Band2	15MHz	16QAM	19125	1RB#74	21.31	23.5	PASS
Band2	15MHz	16QAM	19125	38RB#0	21.51	23.5	PASS
Band2	15MHz	16QAM	19125	38RB#18	21.53	23.5	PASS
Band2	15MHz	16QAM	19125	38RB#37	21.48	23.5	PASS
Band2	15MHz	16QAM	19125	75RB#0	20.51	23.5	PASS
Band2	20MHz	QPSK	18700	1RB#0	22.55	23.5	PASS
Band2	20MHz	QPSK	18700	1RB#49	23.12	23.5	PASS
Band2	20MHz	QPSK	18700	1RB#99	22.50	23.5	PASS
Band2	20MHz	QPSK	18700	50RB#0	21.65	23.5	PASS
Band2	20MHz	QPSK	18700	50RB#25	21.68	23.5	PASS

Band2	20MHz	QPSK	18700	50RB#50	21.71	23.5	PASS
Band2	20MHz	QPSK	18700	100RB#0	21.71	23.5	PASS
Band2	20MHz	QPSK	18900	1RB#0	22.56	23.5	PASS
Band2	20MHz	QPSK	18900	1RB#49	22.85	23.5	PASS
Band2	20MHz	QPSK	18900	1RB#99	22.21	23.5	PASS
Band2	20MHz	QPSK	18900	50RB#0	21.70	23.5	PASS
Band2	20MHz	QPSK	18900	50RB#25	21.70	23.5	PASS
Band2	20MHz	QPSK	18900	50RB#50	21.45	23.5	PASS
Band2	20MHz	QPSK	18900	100RB#0	21.57	23.5	PASS
Band2	20MHz	QPSK	19100	1RB#0	22.00	23.5	PASS
Band2	20MHz	QPSK	19100	1RB#49	22.69	23.5	PASS
Band2	20MHz	QPSK	19100	1RB#99	22.16	23.5	PASS
Band2	20MHz	QPSK	19100	50RB#0	21.41	23.5	PASS
Band2	20MHz	QPSK	19100	50RB#25	21.45	23.5	PASS
Band2	20MHz	QPSK	19100	50RB#50	21.30	23.5	PASS
Band2	20MHz	QPSK	19100	100RB#0	21.45	23.5	PASS
Band2	20MHz	16QAM	18700	1RB#0	21.49	23.5	PASS
Band2	20MHz	16QAM	18700	1RB#49	21.96	23.5	PASS
Band2	20MHz	16QAM	18700	1RB#99	21.53	23.5	PASS
Band2	20MHz	16QAM	18700	50RB#0	20.73	23.5	PASS
Band2	20MHz	16QAM	18700	50RB#25	20.70	23.5	PASS
Band2	20MHz	16QAM	18700	50RB#50	20.71	23.5	PASS
Band2	20MHz	16QAM	18700	100RB#0	20.73	23.5	PASS
Band2	20MHz	16QAM	18900	1RB#0	21.74	23.5	PASS
Band2	20MHz	16QAM	18900	1RB#49	21.95	23.5	PASS
Band2	20MHz	16QAM	18900	1RB#99	21.31	23.5	PASS
Band2	20MHz	16QAM	18900	50RB#0	20.84	23.5	PASS
Band2	20MHz	16QAM	18900	50RB#25	20.85	23.5	PASS
Band2	20MHz	16QAM	18900	50RB#50	20.57	23.5	PASS
Band2	20MHz	16QAM	18900	100RB#0	20.67	23.5	PASS
Band2	20MHz	16QAM	19100	1RB#0	21.00	23.5	PASS
Band2	20MHz	16QAM	19100	1RB#49	21.69	23.5	PASS
Band2	20MHz	16QAM	19100	1RB#99	21.14	23.5	PASS
Band2	20MHz	16QAM	19100	50RB#0	20.50	23.5	PASS
Band2	20MHz	16QAM	19100	50RB#25	20.52	23.5	PASS
Band2	20MHz	16QAM	19100	50RB#50	20.43	23.5	PASS
Band2	20MHz	16QAM	19100	100RB#0	20.48	23.5	PASS

Band	Bandwidth	Modulation	Channel	RB Configuration	Result(dBm)	Tune-up power (dBm)	Verdict
Band4	1.4MHz	QPSK	19957	1RB#0	21.82	22.5	PASS
Band4	1.4MHz	QPSK	19957	1RB#2	21.96	22.5	PASS
Band4	1.4MHz	QPSK	19957	1RB#5	21.83	22.5	PASS
Band4	1.4MHz	QPSK	19957	3RB#0	21.99	22.5	PASS
Band4	1.4MHz	QPSK	19957	3RB#1	21.93	22.5	PASS
Band4	1.4MHz	QPSK	19957	3RB#3	22.01	22.5	PASS
Band4	1.4MHz	QPSK	19957	6RB#0	20.93	22.5	PASS
Band4	1.4MHz	QPSK	20175	1RB#0	21.43	22.5	PASS
Band4	1.4MHz	QPSK	20175	1RB#2	21.47	22.5	PASS
Band4	1.4MHz	QPSK	20175	1RB#5	21.38	22.5	PASS
Band4	1.4MHz	QPSK	20175	3RB#0	21.47	22.5	PASS
Band4	1.4MHz	QPSK	20175	3RB#1	21.42	22.5	PASS
Band4	1.4MHz	QPSK	20175	3RB#3	21.47	22.5	PASS
Band4	1.4MHz	QPSK	20175	6RB#0	20.46	22.5	PASS
Band4	1.4MHz	QPSK	20393	1RB#0	21.19	22.5	PASS
Band4	1.4MHz	QPSK	20393	1RB#2	21.38	22.5	PASS
Band4	1.4MHz	QPSK	20393	1RB#5	21.21	22.5	PASS
Band4	1.4MHz	QPSK	20393	3RB#0	21.38	22.5	PASS
Band4	1.4MHz	QPSK	20393	3RB#1	21.38	22.5	PASS
Band4	1.4MHz	QPSK	20393	3RB#3	21.44	22.5	PASS
Band4	1.4MHz	QPSK	20393	6RB#0	20.41	22.5	PASS
Band4	1.4MHz	16QAM	19957	1RB#0	20.98	22.5	PASS
Band4	1.4MHz	16QAM	19957	1RB#2	21.15	22.5	PASS
Band4	1.4MHz	16QAM	19957	1RB#5	20.94	22.5	PASS
Band4	1.4MHz	16QAM	19957	3RB#0	20.84	22.5	PASS
Band4	1.4MHz	16QAM	19957	3RB#1	20.83	22.5	PASS
Band4	1.4MHz	16QAM	19957	3RB#3	20.83	22.5	PASS
Band4	1.4MHz	16QAM	19957	6RB#0	20.87	22.5	PASS
Band4	1.4MHz	16QAM	20175	1RB#0	20.47	22.5	PASS
Band4	1.4MHz	16QAM	20175	1RB#2	20.62	22.5	PASS
Band4	1.4MHz	16QAM	20175	1RB#5	20.48	22.5	PASS
Band4	1.4MHz	16QAM	20175	3RB#0	20.34	22.5	PASS

Band4	1.4MHz	16QAM	20175	3RB#1	20.35	22.5	PASS
Band4	1.4MHz	16QAM	20175	3RB#3	20.36	22.5	PASS
Band4	1.4MHz	16QAM	20175	6RB#0	20.40	22.5	PASS
Band4	1.4MHz	16QAM	20393	1RB#0	20.34	22.5	PASS
Band4	1.4MHz	16QAM	20393	1RB#2	20.65	22.5	PASS
Band4	1.4MHz	16QAM	20393	1RB#5	20.34	22.5	PASS
Band4	1.4MHz	16QAM	20393	3RB#0	20.39	22.5	PASS
Band4	1.4MHz	16QAM	20393	3RB#1	20.38	22.5	PASS
Band4	1.4MHz	16QAM	20393	3RB#3	20.44	22.5	PASS
Band4	1.4MHz	16QAM	20393	6RB#0	20.40	22.5	PASS
Band4	3MHz	QPSK	19965	1RB#0	21.89	22.5	PASS
Band4	3MHz	QPSK	19965	1RB#8	21.84	22.5	PASS
Band4	3MHz	QPSK	19965	1RB#14	21.81	22.5	PASS
Band4	3MHz	QPSK	19965	8RB#0	20.94	22.5	PASS
Band4	3MHz	QPSK	19965	8RB#4	20.95	22.5	PASS
Band4	3MHz	QPSK	19965	8RB#7	20.84	22.5	PASS
Band4	3MHz	QPSK	19965	15RB#0	20.89	22.5	PASS
Band4	3MHz	QPSK	20175	1RB#0	21.43	22.5	PASS
Band4	3MHz	QPSK	20175	1RB#8	21.39	22.5	PASS
Band4	3MHz	QPSK	20175	1RB#14	21.37	22.5	PASS
Band4	3MHz	QPSK	20175	8RB#0	20.47	22.5	PASS
Band4	3MHz	QPSK	20175	8RB#4	20.49	22.5	PASS
Band4	3MHz	QPSK	20175	8RB#7	20.43	22.5	PASS
Band4	3MHz	QPSK	20175	15RB#0	20.41	22.5	PASS
Band4	3MHz	QPSK	20385	1RB#0	21.32	22.5	PASS
Band4	3MHz	QPSK	20385	1RB#8	21.31	22.5	PASS
Band4	3MHz	QPSK	20385	1RB#14	21.38	22.5	PASS
Band4	3MHz	QPSK	20385	8RB#0	20.42	22.5	PASS
Band4	3MHz	QPSK	20385	8RB#4	20.43	22.5	PASS
Band4	3MHz	QPSK	20385	8RB#7	20.42	22.5	PASS
Band4	3MHz	QPSK	20385	15RB#0	20.40	22.5	PASS
Band4	3MHz	16QAM	19965	1RB#0	21.15	22.5	PASS
Band4	3MHz	16QAM	19965	1RB#8	21.03	22.5	PASS
Band4	3MHz	16QAM	19965	1RB#14	20.97	22.5	PASS
Band4	3MHz	16QAM	19965	8RB#0	20.43	22.5	PASS
Band4	3MHz	16QAM	19965	8RB#4	20.43	22.5	PASS
Band4	3MHz	16QAM	19965	8RB#7	20.98	22.5	PASS

Band4	3MHz	16QAM	19965	15RB#0	20.93	22.5	PASS
Band4	3MHz	16QAM	20175	1RB#0	20.64	22.5	PASS
Band4	3MHz	16QAM	20175	1RB#8	20.60	22.5	PASS
Band4	3MHz	16QAM	20175	1RB#14	20.54	22.5	PASS
Band4	3MHz	16QAM	20175	8RB#0	20.59	22.5	PASS
Band4	3MHz	16QAM	20175	8RB#4	20.59	22.5	PASS
Band4	3MHz	16QAM	20175	8RB#7	20.53	22.5	PASS
Band4	3MHz	16QAM	20175	15RB#0	20.50	22.5	PASS
Band4	3MHz	16QAM	20385	1RB#0	20.48	22.5	PASS
Band4	3MHz	16QAM	20385	1RB#8	20.45	22.5	PASS
Band4	3MHz	16QAM	20385	1RB#14	20.46	22.5	PASS
Band4	3MHz	16QAM	20385	8RB#0	20.40	22.5	PASS
Band4	3MHz	16QAM	20385	8RB#4	20.43	22.5	PASS
Band4	3MHz	16QAM	20385	8RB#7	20.42	22.5	PASS
Band4	3MHz	16QAM	20385	15RB#0	20.49	22.5	PASS
Band4	5MHz	QPSK	19975	1RB#0	21.80	22.5	PASS
Band4	5MHz	QPSK	19975	1RB#12	21.85	22.5	PASS
Band4	5MHz	QPSK	19975	1RB#24	21.70	22.5	PASS
Band4	5MHz	QPSK	19975	12RB#0	20.76	22.5	PASS
Band4	5MHz	QPSK	19975	12RB#6	20.78	22.5	PASS
Band4	5MHz	QPSK	19975	12RB#13	20.74	22.5	PASS
Band4	5MHz	QPSK	19975	25RB#0	20.74	22.5	PASS
Band4	5MHz	QPSK	20175	1RB#0	21.38	22.5	PASS
Band4	5MHz	QPSK	20175	1RB#12	21.44	22.5	PASS
Band4	5MHz	QPSK	20175	1RB#24	21.21	22.5	PASS
Band4	5MHz	QPSK	20175	12RB#0	20.39	22.5	PASS
Band4	5MHz	QPSK	20175	12RB#6	20.37	22.5	PASS
Band4	5MHz	QPSK	20175	12RB#13	20.56	22.5	PASS
Band4	5MHz	QPSK	20175	25RB#0	20.69	22.5	PASS
Band4	5MHz	QPSK	20375	1RB#0	21.13	22.5	PASS
Band4	5MHz	QPSK	20375	1RB#12	21.32	22.5	PASS
Band4	5MHz	QPSK	20375	1RB#24	21.25	22.5	PASS
Band4	5MHz	QPSK	20375	12RB#0	20.56	22.5	PASS
Band4	5MHz	QPSK	20375	12RB#6	20.58	22.5	PASS
Band4	5MHz	QPSK	20375	12RB#13	20.51	22.5	PASS
Band4	5MHz	QPSK	20375	25RB#0	20.46	22.5	PASS
Band4	5MHz	16QAM	19975	1RB#0	20.83	22.5	PASS

Band4	5MHz	16QAM	19975	1RB#12	20.86	22.5	PASS
Band4	5MHz	16QAM	19975	1RB#24	20.68	22.5	PASS
Band4	5MHz	16QAM	19975	12RB#0	20.79	22.5	PASS
Band4	5MHz	16QAM	19975	12RB#6	20.79	22.5	PASS
Band4	5MHz	16QAM	19975	12RB#13	20.75	22.5	PASS
Band4	5MHz	16QAM	19975	25RB#0	20.81	22.5	PASS
Band4	5MHz	16QAM	20175	1RB#0	20.47	22.5	PASS
Band4	5MHz	16QAM	20175	1RB#12	20.44	22.5	PASS
Band4	5MHz	16QAM	20175	1RB#24	20.20	22.5	PASS
Band4	5MHz	16QAM	20175	12RB#0	20.41	22.5	PASS
Band4	5MHz	16QAM	20175	12RB#6	20.42	22.5	PASS
Band4	5MHz	16QAM	20175	12RB#13	20.58	22.5	PASS
Band4	5MHz	16QAM	20175	25RB#0	20.42	22.5	PASS
Band4	5MHz	16QAM	20375	1RB#0	20.33	22.5	PASS
Band4	5MHz	16QAM	20375	1RB#12	20.52	22.5	PASS
Band4	5MHz	16QAM	20375	1RB#24	20.49	22.5	PASS
Band4	5MHz	16QAM	20375	12RB#0	20.56	22.5	PASS
Band4	5MHz	16QAM	20375	12RB#6	20.49	22.5	PASS
Band4	5MHz	16QAM	20375	12RB#13	20.35	22.5	PASS
Band4	5MHz	16QAM	20375	25RB#0	20.32	22.5	PASS
Band4	10MHz	QPSK	20000	1RB#0	21.77	22.5	PASS
Band4	10MHz	QPSK	20000	1RB#24	21.89	22.5	PASS
Band4	10MHz	QPSK	20000	1RB#49	21.66	22.5	PASS
Band4	10MHz	QPSK	20000	25RB#0	20.73	22.5	PASS
Band4	10MHz	QPSK	20000	25RB#12	20.80	22.5	PASS
Band4	10MHz	QPSK	20000	25RB#25	20.85	22.5	PASS
Band4	10MHz	QPSK	20000	50RB#0	20.83	22.5	PASS
Band4	10MHz	QPSK	20175	1RB#0	21.43	22.5	PASS
Band4	10MHz	QPSK	20175	1RB#24	21.51	22.5	PASS
Band4	10MHz	QPSK	20175	1RB#49	20.99	22.5	PASS
Band4	10MHz	QPSK	20175	25RB#0	20.45	22.5	PASS
Band4	10MHz	QPSK	20175	25RB#12	20.47	22.5	PASS
Band4	10MHz	QPSK	20175	25RB#25	20.40	22.5	PASS
Band4	10MHz	QPSK	20175	50RB#0	20.36	22.5	PASS
Band4	10MHz	QPSK	20350	1RB#0	21.01	22.5	PASS
Band4	10MHz	QPSK	20350	1RB#24	21.24	22.5	PASS
Band4	10MHz	QPSK	20350	1RB#49	21.16	22.5	PASS

Band4	10MHz	QPSK	20350	25RB#0	20.59	22.5	PASS
Band4	10MHz	QPSK	20350	25RB#12	20.59	22.5	PASS
Band4	10MHz	QPSK	20350	25RB#25	20.43	22.5	PASS
Band4	10MHz	QPSK	20350	50RB#0	20.48	22.5	PASS
Band4	10MHz	16QAM	20000	1RB#0	20.97	22.5	PASS
Band4	10MHz	16QAM	20000	1RB#24	21.10	22.5	PASS
Band4	10MHz	16QAM	20000	1RB#49	20.87	22.5	PASS
Band4	10MHz	16QAM	20000	25RB#0	20.88	22.5	PASS
Band4	10MHz	16QAM	20000	25RB#12	20.86	22.5	PASS
Band4	10MHz	16QAM	20000	25RB#25	20.92	22.5	PASS
Band4	10MHz	16QAM	20000	50RB#0	20.88	22.5	PASS
Band4	10MHz	16QAM	20175	1RB#0	20.52	22.5	PASS
Band4	10MHz	16QAM	20175	1RB#24	20.68	22.5	PASS
Band4	10MHz	16QAM	20175	1RB#49	20.41	22.5	PASS
Band4	10MHz	16QAM	20175	25RB#0	20.52	22.5	PASS
Band4	10MHz	16QAM	20175	25RB#12	20.55	22.5	PASS
Band4	10MHz	16QAM	20175	25RB#25	20.40	22.5	PASS
Band4	10MHz	16QAM	20175	50RB#0	20.37	22.5	PASS
Band4	10MHz	16QAM	20350	1RB#0	20.50	22.5	PASS
Band4	10MHz	16QAM	20350	1RB#24	20.40	22.5	PASS
Band4	10MHz	16QAM	20350	1RB#49	20.38	22.5	PASS
Band4	10MHz	16QAM	20350	25RB#0	20.33	22.5	PASS
Band4	10MHz	16QAM	20350	25RB#12	20.33	22.5	PASS
Band4	10MHz	16QAM	20350	25RB#25	20.38	22.5	PASS
Band4	10MHz	16QAM	20350	50RB#0	20.69	22.5	PASS
Band4	15MHz	QPSK	20025	1RB#0	21.59	22.5	PASS
Band4	15MHz	QPSK	20025	1RB#38	21.74	22.5	PASS
Band4	15MHz	QPSK	20025	1RB#74	21.45	22.5	PASS
Band4	15MHz	QPSK	20025	38RB#0	20.71	22.5	PASS
Band4	15MHz	QPSK	20025	38RB#18	20.72	22.5	PASS
Band4	15MHz	QPSK	20025	38RB#37	20.71	22.5	PASS
Band4	15MHz	QPSK	20025	75RB#0	20.74	22.5	PASS
Band4	15MHz	QPSK	20175	1RB#0	21.35	22.5	PASS
Band4	15MHz	QPSK	20175	1RB#38	21.32	22.5	PASS
Band4	15MHz	QPSK	20175	1RB#74	20.71	22.5	PASS
Band4	15MHz	QPSK	20175	38RB#0	20.30	22.5	PASS
Band4	15MHz	QPSK	20175	38RB#18	20.48	22.5	PASS

Band4	15MHz	QPSK	20175	38RB#37	20.50	22.5	PASS
Band4	15MHz	QPSK	20175	75RB#0	20.37	22.5	PASS
Band4	15MHz	QPSK	20325	1RB#0	20.79	22.5	PASS
Band4	15MHz	QPSK	20325	1RB#38	21.29	22.5	PASS
Band4	15MHz	QPSK	20325	1RB#74	21.18	22.5	PASS
Band4	15MHz	QPSK	20325	38RB#0	20.41	22.5	PASS
Band4	15MHz	QPSK	20325	38RB#18	20.42	22.5	PASS
Band4	15MHz	QPSK	20325	38RB#37	20.44	22.5	PASS
Band4	15MHz	QPSK	20325	75RB#0	20.53	22.5	PASS
Band4	15MHz	16QAM	20025	1RB#0	20.82	22.5	PASS
Band4	15MHz	16QAM	20025	1RB#38	20.98	22.5	PASS
Band4	15MHz	16QAM	20025	1RB#74	20.64	22.5	PASS
Band4	15MHz	16QAM	20025	38RB#0	20.68	22.5	PASS
Band4	15MHz	16QAM	20025	38RB#18	20.71	22.5	PASS
Band4	15MHz	16QAM	20025	38RB#37	20.73	22.5	PASS
Band4	15MHz	16QAM	20025	75RB#0	20.76	22.5	PASS
Band4	15MHz	16QAM	20175	1RB#0	20.51	22.5	PASS
Band4	15MHz	16QAM	20175	1RB#38	20.55	22.5	PASS
Band4	15MHz	16QAM	20175	1RB#74	20.89	22.5	PASS
Band4	15MHz	16QAM	20175	38RB#0	20.29	22.5	PASS
Band4	15MHz	16QAM	20175	38RB#18	20.31	22.5	PASS
Band4	15MHz	16QAM	20175	38RB#37	20.29	22.5	PASS
Band4	15MHz	16QAM	20175	75RB#0	20.41	22.5	PASS
Band4	15MHz	16QAM	20325	1RB#0	20.95	22.5	PASS
Band4	15MHz	16QAM	20325	1RB#38	20.51	22.5	PASS
Band4	15MHz	16QAM	20325	1RB#74	20.39	22.5	PASS
Band4	15MHz	16QAM	20325	38RB#0	20.42	22.5	PASS
Band4	15MHz	16QAM	20325	38RB#18	20.44	22.5	PASS
Band4	15MHz	16QAM	20325	38RB#37	20.40	22.5	PASS
Band4	15MHz	16QAM	20325	75RB#0	20.42	22.5	PASS
Band4	20MHz	QPSK	20050	1RB#0	21.87	22.5	PASS
Band4	20MHz	QPSK	20050	1RB#49	22.05	22.5	PASS
Band4	20MHz	QPSK	20050	1RB#99	21.22	22.5	PASS
Band4	20MHz	QPSK	20050	50RB#0	20.51	22.5	PASS
Band4	20MHz	QPSK	20050	50RB#25	20.49	22.5	PASS
Band4	20MHz	QPSK	20050	50RB#50	20.54	22.5	PASS
Band4	20MHz	QPSK	20050	100RB#0	20.54	22.5	PASS

Band4	20MHz	QPSK	20175	1RB#0	21.40	22.5	PASS
Band4	20MHz	QPSK	20175	1RB#49	21.50	22.5	PASS
Band4	20MHz	QPSK	20175	1RB#99	20.46	22.5	PASS
Band4	20MHz	QPSK	20175	50RB#0	20.43	22.5	PASS
Band4	20MHz	QPSK	20175	50RB#25	20.46	22.5	PASS
Band4	20MHz	QPSK	20175	50RB#50	20.89	22.5	PASS
Band4	20MHz	QPSK	20175	100RB#0	20.40	22.5	PASS
Band4	20MHz	QPSK	20300	1RB#0	21.21	22.5	PASS
Band4	20MHz	QPSK	20300	1RB#49	21.45	22.5	PASS
Band4	20MHz	QPSK	20300	1RB#99	21.19	22.5	PASS
Band4	20MHz	QPSK	20300	50RB#0	20.59	22.5	PASS
Band4	20MHz	QPSK	20300	50RB#25	20.50	22.5	PASS
Band4	20MHz	QPSK	20300	50RB#50	20.54	22.5	PASS
Band4	20MHz	QPSK	20300	100RB#0	20.51	22.5	PASS
Band4	20MHz	16QAM	20050	1RB#0	20.49	22.5	PASS
Band4	20MHz	16QAM	20050	1RB#49	20.79	22.5	PASS
Band4	20MHz	16QAM	20050	1RB#99	20.17	22.5	PASS
Band4	20MHz	16QAM	20050	50RB#0	20.62	22.5	PASS
Band4	20MHz	16QAM	20050	50RB#25	20.57	22.5	PASS
Band4	20MHz	16QAM	20050	50RB#50	20.61	22.5	PASS
Band4	20MHz	16QAM	20050	100RB#0	20.62	22.5	PASS
Band4	20MHz	16QAM	20175	1RB#0	20.41	22.5	PASS
Band4	20MHz	16QAM	20175	1RB#49	20.51	22.5	PASS
Band4	20MHz	16QAM	20175	1RB#99	20.55	22.5	PASS
Band4	20MHz	16QAM	20175	50RB#0	20.52	22.5	PASS
Band4	20MHz	16QAM	20175	50RB#25	20.50	22.5	PASS
Band4	20MHz	16QAM	20175	50RB#50	20.70	22.5	PASS
Band4	20MHz	16QAM	20175	100RB#0	20.57	22.5	PASS
Band4	20MHz	16QAM	20300	1RB#0	20.66	22.5	PASS
Band4	20MHz	16QAM	20300	1RB#49	20.38	22.5	PASS
Band4	20MHz	16QAM	20300	1RB#99	20.41	22.5	PASS
Band4	20MHz	16QAM	20300	50RB#0	20.63	22.5	PASS
Band4	20MHz	16QAM	20300	50RB#25	20.31	22.5	PASS
Band4	20MHz	16QAM	20300	50RB#50	20.33	22.5	PASS
Band4	20MHz	16QAM	20300	100RB#0	20.33	22.5	PASS

Band	Bandwidth	Modulation	Channel	RB Configuration	Result(dBm)	Tune-up power (dBm)	Verdict
Band5	1.4MHz	QPSK	20407	1RB#0	23.66	24.0	PASS
Band5	1.4MHz	QPSK	20407	1RB#2	23.76	24.0	PASS
Band5	1.4MHz	QPSK	20407	1RB#5	23.56	24.0	PASS
Band5	1.4MHz	QPSK	20407	3RB#0	23.76	24.0	PASS
Band5	1.4MHz	QPSK	20407	3RB#1	23.77	24.0	PASS
Band5	1.4MHz	QPSK	20407	3RB#3	23.79	24.0	PASS
Band5	1.4MHz	QPSK	20407	6RB#0	22.69	24.0	PASS
Band5	1.4MHz	QPSK	20525	1RB#0	23.42	24.0	PASS
Band5	1.4MHz	QPSK	20525	1RB#2	23.52	24.0	PASS
Band5	1.4MHz	QPSK	20525	1RB#5	23.34	24.0	PASS
Band5	1.4MHz	QPSK	20525	3RB#0	23.49	24.0	PASS
Band5	1.4MHz	QPSK	20525	3RB#1	23.47	24.0	PASS
Band5	1.4MHz	QPSK	20525	3RB#3	23.57	24.0	PASS
Band5	1.4MHz	QPSK	20525	6RB#0	22.49	24.0	PASS
Band5	1.4MHz	QPSK	20643	1RB#0	23.36	24.0	PASS
Band5	1.4MHz	QPSK	20643	1RB#2	23.62	24.0	PASS
Band5	1.4MHz	QPSK	20643	1RB#5	23.42	24.0	PASS
Band5	1.4MHz	QPSK	20643	3RB#0	23.55	24.0	PASS
Band5	1.4MHz	QPSK	20643	3RB#1	23.60	24.0	PASS
Band5	1.4MHz	QPSK	20643	3RB#3	23.56	24.0	PASS
Band5	1.4MHz	QPSK	20643	6RB#0	22.44	24.0	PASS
Band5	1.4MHz	16QAM	20407	1RB#0	22.81	24.0	PASS
Band5	1.4MHz	16QAM	20407	1RB#2	22.91	24.0	PASS
Band5	1.4MHz	16QAM	20407	1RB#5	22.70	24.0	PASS
Band5	1.4MHz	16QAM	20407	3RB#0	22.65	24.0	PASS
Band5	1.4MHz	16QAM	20407	3RB#1	22.64	24.0	PASS
Band5	1.4MHz	16QAM	20407	3RB#3	22.61	24.0	PASS
Band5	1.4MHz	16QAM	20407	6RB#0	21.78	24.0	PASS
Band5	1.4MHz	16QAM	20525	1RB#0	22.59	24.0	PASS
Band5	1.4MHz	16QAM	20525	1RB#2	22.77	24.0	PASS
Band5	1.4MHz	16QAM	20525	1RB#5	22.56	24.0	PASS
Band5	1.4MHz	16QAM	20525	3RB#0	22.37	24.0	PASS
Band5	1.4MHz	16QAM	20525	3RB#1	22.41	24.0	PASS

Band5	1.4MHz	16QAM	20525	3RB#3	22.45	24.0	PASS
Band5	1.4MHz	16QAM	20525	6RB#0	21.39	24.0	PASS
Band5	1.4MHz	16QAM	20643	1RB#0	22.39	24.0	PASS
Band5	1.4MHz	16QAM	20643	1RB#2	22.49	24.0	PASS
Band5	1.4MHz	16QAM	20643	1RB#5	22.35	24.0	PASS
Band5	1.4MHz	16QAM	20643	3RB#0	22.39	24.0	PASS
Band5	1.4MHz	16QAM	20643	3RB#1	22.42	24.0	PASS
Band5	1.4MHz	16QAM	20643	3RB#3	22.42	24.0	PASS
Band5	1.4MHz	16QAM	20643	6RB#0	21.50	24.0	PASS
Band5	3MHz	QPSK	20415	1RB#0	23.72	24.0	PASS
Band5	3MHz	QPSK	20415	1RB#8	23.69	24.0	PASS
Band5	3MHz	QPSK	20415	1RB#14	23.64	24.0	PASS
Band5	3MHz	QPSK	20415	8RB#0	22.80	24.0	PASS
Band5	3MHz	QPSK	20415	8RB#4	22.77	24.0	PASS
Band5	3MHz	QPSK	20415	8RB#7	22.71	24.0	PASS
Band5	3MHz	QPSK	20415	15RB#0	22.70	24.0	PASS
Band5	3MHz	QPSK	20525	1RB#0	23.50	24.0	PASS
Band5	3MHz	QPSK	20525	1RB#8	23.46	24.0	PASS
Band5	3MHz	QPSK	20525	1RB#14	23.51	24.0	PASS
Band5	3MHz	QPSK	20525	8RB#0	22.43	24.0	PASS
Band5	3MHz	QPSK	20525	8RB#4	22.44	24.0	PASS
Band5	3MHz	QPSK	20525	8RB#7	22.49	24.0	PASS
Band5	3MHz	QPSK	20525	15RB#0	22.49	24.0	PASS
Band5	3MHz	QPSK	20635	1RB#0	23.49	24.0	PASS
Band5	3MHz	QPSK	20635	1RB#8	23.52	24.0	PASS
Band5	3MHz	QPSK	20635	1RB#14	23.52	24.0	PASS
Band5	3MHz	QPSK	20635	8RB#0	22.45	24.0	PASS
Band5	3MHz	QPSK	20635	8RB#4	22.50	24.0	PASS
Band5	3MHz	QPSK	20635	8RB#7	22.44	24.0	PASS
Band5	3MHz	QPSK	20635	15RB#0	22.46	24.0	PASS
Band5	3MHz	16QAM	20415	1RB#0	22.98	24.0	PASS
Band5	3MHz	16QAM	20415	1RB#8	22.91	24.0	PASS
Band5	3MHz	16QAM	20415	1RB#14	22.89	24.0	PASS
Band5	3MHz	16QAM	20415	8RB#0	21.84	24.0	PASS
Band5	3MHz	16QAM	20415	8RB#4	21.83	24.0	PASS
Band5	3MHz	16QAM	20415	8RB#7	21.72	24.0	PASS
Band5	3MHz	16QAM	20415	15RB#0	21.74	24.0	PASS

Band5	3MHz	16QAM	20525	1RB#0	22.71	24.0	PASS
Band5	3MHz	16QAM	20525	1RB#8	22.69	24.0	PASS
Band5	3MHz	16QAM	20525	1RB#14	22.71	24.0	PASS
Band5	3MHz	16QAM	20525	8RB#0	21.52	24.0	PASS
Band5	3MHz	16QAM	20525	8RB#4	21.52	24.0	PASS
Band5	3MHz	16QAM	20525	8RB#7	21.61	24.0	PASS
Band5	3MHz	16QAM	20525	15RB#0	21.48	24.0	PASS
Band5	3MHz	16QAM	20635	1RB#0	22.76	24.0	PASS
Band5	3MHz	16QAM	20635	1RB#8	22.77	24.0	PASS
Band5	3MHz	16QAM	20635	1RB#14	22.68	24.0	PASS
Band5	3MHz	16QAM	20635	8RB#0	21.57	24.0	PASS
Band5	3MHz	16QAM	20635	8RB#4	21.60	24.0	PASS
Band5	3MHz	16QAM	20635	8RB#7	21.55	24.0	PASS
Band5	3MHz	16QAM	20635	15RB#0	21.42	24.0	PASS
Band5	5MHz	QPSK	20425	1RB#0	23.63	24.0	PASS
Band5	5MHz	QPSK	20425	1RB#12	23.71	24.0	PASS
Band5	5MHz	QPSK	20425	1RB#24	23.57	24.0	PASS
Band5	5MHz	QPSK	20425	12RB#0	22.73	24.0	PASS
Band5	5MHz	QPSK	20425	12RB#6	22.70	24.0	PASS
Band5	5MHz	QPSK	20425	12RB#13	22.60	24.0	PASS
Band5	5MHz	QPSK	20425	25RB#0	22.69	24.0	PASS
Band5	5MHz	QPSK	20525	1RB#0	23.45	24.0	PASS
Band5	5MHz	QPSK	20525	1RB#12	23.54	24.0	PASS
Band5	5MHz	QPSK	20525	1RB#24	23.46	24.0	PASS
Band5	5MHz	QPSK	20525	12RB#0	22.36	24.0	PASS
Band5	5MHz	QPSK	20525	12RB#6	22.37	24.0	PASS
Band5	5MHz	QPSK	20525	12RB#13	22.42	24.0	PASS
Band5	5MHz	QPSK	20525	25RB#0	22.44	24.0	PASS
Band5	5MHz	QPSK	20625	1RB#0	23.36	24.0	PASS
Band5	5MHz	QPSK	20625	1RB#12	23.55	24.0	PASS
Band5	5MHz	QPSK	20625	1RB#24	23.36	24.0	PASS
Band5	5MHz	QPSK	20625	12RB#0	22.46	24.0	PASS
Band5	5MHz	QPSK	20625	12RB#6	22.44	24.0	PASS
Band5	5MHz	QPSK	20625	12RB#13	22.51	24.0	PASS
Band5	5MHz	QPSK	20625	25RB#0	22.52	24.0	PASS
Band5	5MHz	16QAM	20425	1RB#0	22.69	24.0	PASS
Band5	5MHz	16QAM	20425	1RB#12	22.74	24.0	PASS

Band5	5MHz	16QAM	20425	1RB#24	22.56	24.0	PASS
Band5	5MHz	16QAM	20425	12RB#0	21.71	24.0	PASS
Band5	5MHz	16QAM	20425	12RB#6	21.67	24.0	PASS
Band5	5MHz	16QAM	20425	12RB#13	21.54	24.0	PASS
Band5	5MHz	16QAM	20425	25RB#0	21.67	24.0	PASS
Band5	5MHz	16QAM	20525	1RB#0	22.45	24.0	PASS
Band5	5MHz	16QAM	20525	1RB#12	22.57	24.0	PASS
Band5	5MHz	16QAM	20525	1RB#24	22.52	24.0	PASS
Band5	5MHz	16QAM	20525	12RB#0	21.31	24.0	PASS
Band5	5MHz	16QAM	20525	12RB#6	21.30	24.0	PASS
Band5	5MHz	16QAM	20525	12RB#13	21.42	24.0	PASS
Band5	5MHz	16QAM	20525	25RB#0	21.46	24.0	PASS
Band5	5MHz	16QAM	20625	1RB#0	22.70	24.0	PASS
Band5	5MHz	16QAM	20625	1RB#12	22.84	24.0	PASS
Band5	5MHz	16QAM	20625	1RB#24	22.75	24.0	PASS
Band5	5MHz	16QAM	20625	12RB#0	21.49	24.0	PASS
Band5	5MHz	16QAM	20625	12RB#6	21.52	24.0	PASS
Band5	5MHz	16QAM	20625	12RB#13	21.49	24.0	PASS
Band5	5MHz	16QAM	20625	25RB#0	21.52	24.0	PASS
Band5	10MHz	QPSK	20450	1RB#0	23.85	24.0	PASS
Band5	10MHz	QPSK	20450	1RB#24	23.77	24.0	PASS
Band5	10MHz	QPSK	20450	1RB#49	23.45	24.0	PASS
Band5	10MHz	QPSK	20450	25RB#0	22.83	24.0	PASS
Band5	10MHz	QPSK	20450	25RB#12	22.80	24.0	PASS
Band5	10MHz	QPSK	20450	25RB#25	22.65	24.0	PASS
Band5	10MHz	QPSK	20450	50RB#0	22.77	24.0	PASS
Band5	10MHz	QPSK	20525	1RB#0	23.47	24.0	PASS
Band5	10MHz	QPSK	20525	1RB#24	23.59	24.0	PASS
Band5	10MHz	QPSK	20525	1RB#49	23.62	24.0	PASS
Band5	10MHz	QPSK	20525	25RB#0	22.39	24.0	PASS
Band5	10MHz	QPSK	20525	25RB#12	22.35	24.0	PASS
Band5	10MHz	QPSK	20525	25RB#25	22.48	24.0	PASS
Band5	10MHz	QPSK	20525	50RB#0	22.46	24.0	PASS
Band5	10MHz	QPSK	20600	1RB#0	23.55	24.0	PASS
Band5	10MHz	QPSK	20600	1RB#24	23.59	24.0	PASS
Band5	10MHz	QPSK	20600	1RB#49	23.39	24.0	PASS
Band5	10MHz	QPSK	20600	25RB#0	22.84	24.0	PASS

Band5	10MHz	QPSK	20600	25RB#12	22.91	24.0	PASS
Band5	10MHz	QPSK	20600	25RB#25	22.55	24.0	PASS
Band5	10MHz	QPSK	20600	50RB#0	22.71	24.0	PASS
Band5	10MHz	16QAM	20450	1RB#0	22.85	24.0	PASS
Band5	10MHz	16QAM	20450	1RB#24	22.90	24.0	PASS
Band5	10MHz	16QAM	20450	1RB#49	22.64	24.0	PASS
Band5	10MHz	16QAM	20450	25RB#0	21.87	24.0	PASS
Band5	10MHz	16QAM	20450	25RB#12	21.85	24.0	PASS
Band5	10MHz	16QAM	20450	25RB#25	21.67	24.0	PASS
Band5	10MHz	16QAM	20450	50RB#0	21.76	24.0	PASS
Band5	10MHz	16QAM	20525	1RB#0	22.83	24.0	PASS
Band5	10MHz	16QAM	20525	1RB#24	22.78	24.0	PASS
Band5	10MHz	16QAM	20525	1RB#49	22.82	24.0	PASS
Band5	10MHz	16QAM	20525	25RB#0	21.39	24.0	PASS
Band5	10MHz	16QAM	20525	25RB#12	21.43	24.0	PASS
Band5	10MHz	16QAM	20525	25RB#25	21.44	24.0	PASS
Band5	10MHz	16QAM	20525	50RB#0	21.49	24.0	PASS
Band5	10MHz	16QAM	20600	1RB#0	22.71	24.0	PASS
Band5	10MHz	16QAM	20600	1RB#24	22.85	24.0	PASS
Band5	10MHz	16QAM	20600	1RB#49	22.62	24.0	PASS
Band5	10MHz	16QAM	20600	25RB#0	21.92	24.0	PASS
Band5	10MHz	16QAM	20600	25RB#12	21.94	24.0	PASS
Band5	10MHz	16QAM	20600	25RB#25	21.64	24.0	PASS
Band5	10MHz	16QAM	20600	50RB#0	21.78	24.0	PASS

Band	Bandwidth	Modulation	Channel	RB Configuration	Result(dBm)	Tune-up power (dBm)	Verdict
Band12	1.4MHz	QPSK	23017	1RB#0	24.96	25.5	PASS
Band12	1.4MHz	QPSK	23017	1RB#2	25.05	25.5	PASS
Band12	1.4MHz	QPSK	23017	1RB#5	24.89	25.5	PASS
Band12	1.4MHz	QPSK	23017	3RB#0	24.98	25.5	PASS
Band12	1.4MHz	QPSK	23017	3RB#1	24.98	25.5	PASS
Band12	1.4MHz	QPSK	23017	3RB#3	24.98	25.5	PASS
Band12	1.4MHz	QPSK	23017	6RB#0	23.95	25.5	PASS
Band12	1.4MHz	QPSK	23095	1RB#0	24.69	25.5	PASS

Band12	1.4MHz	QPSK	23095	1RB#2	24.89	25.5	PASS
Band12	1.4MHz	QPSK	23095	1RB#5	24.74	25.5	PASS
Band12	1.4MHz	QPSK	23095	3RB#0	24.81	25.5	PASS
Band12	1.4MHz	QPSK	23095	3RB#1	24.78	25.5	PASS
Band12	1.4MHz	QPSK	23095	3RB#3	24.87	25.5	PASS
Band12	1.4MHz	QPSK	23095	6RB#0	23.70	25.5	PASS
Band12	1.4MHz	QPSK	23173	1RB#0	24.68	25.5	PASS
Band12	1.4MHz	QPSK	23173	1RB#2	24.78	25.5	PASS
Band12	1.4MHz	QPSK	23173	1RB#5	24.67	25.5	PASS
Band12	1.4MHz	QPSK	23173	3RB#0	24.74	25.5	PASS
Band12	1.4MHz	QPSK	23173	3RB#1	24.78	25.5	PASS
Band12	1.4MHz	QPSK	23173	3RB#3	24.84	25.5	PASS
Band12	1.4MHz	QPSK	23173	6RB#0	23.70	25.5	PASS
Band12	1.4MHz	16QAM	23017	1RB#0	23.90	25.5	PASS
Band12	1.4MHz	16QAM	23017	1RB#2	24.12	25.5	PASS
Band12	1.4MHz	16QAM	23017	1RB#5	23.89	25.5	PASS
Band12	1.4MHz	16QAM	23017	3RB#0	23.87	25.5	PASS
Band12	1.4MHz	16QAM	23017	3RB#1	23.82	25.5	PASS
Band12	1.4MHz	16QAM	23017	3RB#3	23.76	25.5	PASS
Band12	1.4MHz	16QAM	23017	6RB#0	22.97	25.5	PASS
Band12	1.4MHz	16QAM	23095	1RB#0	23.67	25.5	PASS
Band12	1.4MHz	16QAM	23095	1RB#2	23.94	25.5	PASS
Band12	1.4MHz	16QAM	23095	1RB#5	23.72	25.5	PASS
Band12	1.4MHz	16QAM	23095	3RB#0	23.62	25.5	PASS
Band12	1.4MHz	16QAM	23095	3RB#1	23.67	25.5	PASS
Band12	1.4MHz	16QAM	23095	3RB#3	23.66	25.5	PASS
Band12	1.4MHz	16QAM	23095	6RB#0	22.72	25.5	PASS
Band12	1.4MHz	16QAM	23173	1RB#0	23.73	25.5	PASS
Band12	1.4MHz	16QAM	23173	1RB#2	23.92	25.5	PASS
Band12	1.4MHz	16QAM	23173	1RB#5	23.72	25.5	PASS
Band12	1.4MHz	16QAM	23173	3RB#0	23.60	25.5	PASS
Band12	1.4MHz	16QAM	23173	3RB#1	23.60	25.5	PASS
Band12	1.4MHz	16QAM	23173	3RB#3	23.65	25.5	PASS
Band12	1.4MHz	16QAM	23173	6RB#0	22.56	25.5	PASS
Band12	3MHz	QPSK	23025	1RB#0	25.00	25.5	PASS
Band12	3MHz	QPSK	23025	1RB#8	24.93	25.5	PASS
Band12	3MHz	QPSK	23025	1RB#14	24.95	25.5	PASS

Band12	3MHz	QPSK	23025	8RB#0	24.02	25.5	PASS
Band12	3MHz	QPSK	23025	8RB#4	24.01	25.5	PASS
Band12	3MHz	QPSK	23025	8RB#7	23.97	25.5	PASS
Band12	3MHz	QPSK	23025	15RB#0	23.95	25.5	PASS
Band12	3MHz	QPSK	23095	1RB#0	24.74	25.5	PASS
Band12	3MHz	QPSK	23095	1RB#8	24.81	25.5	PASS
Band12	3MHz	QPSK	23095	1RB#14	24.88	25.5	PASS
Band12	3MHz	QPSK	23095	8RB#0	23.77	25.5	PASS
Band12	3MHz	QPSK	23095	8RB#4	23.70	25.5	PASS
Band12	3MHz	QPSK	23095	8RB#7	23.79	25.5	PASS
Band12	3MHz	QPSK	23095	15RB#0	23.73	25.5	PASS
Band12	3MHz	QPSK	23165	1RB#0	24.78	25.5	PASS
Band12	3MHz	QPSK	23165	1RB#8	24.79	25.5	PASS
Band12	3MHz	QPSK	23165	1RB#14	24.75	25.5	PASS
Band12	3MHz	QPSK	23165	8RB#0	23.78	25.5	PASS
Band12	3MHz	QPSK	23165	8RB#4	23.83	25.5	PASS
Band12	3MHz	QPSK	23165	8RB#7	23.75	25.5	PASS
Band12	3MHz	QPSK	23165	15RB#0	23.73	25.5	PASS
Band12	3MHz	16QAM	23025	1RB#0	24.14	25.5	PASS
Band12	3MHz	16QAM	23025	1RB#8	24.02	25.5	PASS
Band12	3MHz	16QAM	23025	1RB#14	23.98	25.5	PASS
Band12	3MHz	16QAM	23025	8RB#0	23.07	25.5	PASS
Band12	3MHz	16QAM	23025	8RB#4	23.03	25.5	PASS
Band12	3MHz	16QAM	23025	8RB#7	22.96	25.5	PASS
Band12	3MHz	16QAM	23025	15RB#0	22.96	25.5	PASS
Band12	3MHz	16QAM	23095	1RB#0	23.84	25.5	PASS
Band12	3MHz	16QAM	23095	1RB#8	23.85	25.5	PASS
Band12	3MHz	16QAM	23095	1RB#14	23.94	25.5	PASS
Band12	3MHz	16QAM	23095	8RB#0	22.75	25.5	PASS
Band12	3MHz	16QAM	23095	8RB#4	22.72	25.5	PASS
Band12	3MHz	16QAM	23095	8RB#7	22.85	25.5	PASS
Band12	3MHz	16QAM	23095	15RB#0	22.69	25.5	PASS
Band12	3MHz	16QAM	23165	1RB#0	23.65	25.5	PASS
Band12	3MHz	16QAM	23165	1RB#8	23.67	25.5	PASS
Band12	3MHz	16QAM	23165	1RB#14	23.64	25.5	PASS
Band12	3MHz	16QAM	23165	8RB#0	22.78	25.5	PASS
Band12	3MHz	16QAM	23165	8RB#4	22.78	25.5	PASS

Band12	3MHz	16QAM	23165	8RB#7	22.75	25.5	PASS
Band12	3MHz	16QAM	23165	15RB#0	22.66	25.5	PASS
Band12	5MHz	QPSK	23035	1RB#0	24.91	25.5	PASS
Band12	5MHz	QPSK	23035	1RB#12	24.94	25.5	PASS
Band12	5MHz	QPSK	23035	1RB#24	24.73	25.5	PASS
Band12	5MHz	QPSK	23035	12RB#0	23.85	25.5	PASS
Band12	5MHz	QPSK	23035	12RB#6	23.86	25.5	PASS
Band12	5MHz	QPSK	23035	12RB#13	23.75	25.5	PASS
Band12	5MHz	QPSK	23035	25RB#0	23.80	25.5	PASS
Band12	5MHz	QPSK	23095	1RB#0	24.69	25.5	PASS
Band12	5MHz	QPSK	23095	1RB#12	24.77	25.5	PASS
Band12	5MHz	QPSK	23095	1RB#24	24.84	25.5	PASS
Band12	5MHz	QPSK	23095	12RB#0	23.64	25.5	PASS
Band12	5MHz	QPSK	23095	12RB#6	23.63	25.5	PASS
Band12	5MHz	QPSK	23095	12RB#13	23.81	25.5	PASS
Band12	5MHz	QPSK	23095	25RB#0	23.76	25.5	PASS
Band12	5MHz	QPSK	23155	1RB#0	24.92	25.5	PASS
Band12	5MHz	QPSK	23155	1RB#12	24.79	25.5	PASS
Band12	5MHz	QPSK	23155	1RB#24	24.67	25.5	PASS
Band12	5MHz	QPSK	23155	12RB#0	23.74	25.5	PASS
Band12	5MHz	QPSK	23155	12RB#6	23.72	25.5	PASS
Band12	5MHz	QPSK	23155	12RB#13	23.58	25.5	PASS
Band12	5MHz	QPSK	23155	25RB#0	23.65	25.5	PASS
Band12	5MHz	16QAM	23035	1RB#0	23.86	25.5	PASS
Band12	5MHz	16QAM	23035	1RB#12	23.85	25.5	PASS
Band12	5MHz	16QAM	23035	1RB#24	23.59	25.5	PASS
Band12	5MHz	16QAM	23035	12RB#0	22.79	25.5	PASS
Band12	5MHz	16QAM	23035	12RB#6	22.81	25.5	PASS
Band12	5MHz	16QAM	23035	12RB#13	22.71	25.5	PASS
Band12	5MHz	16QAM	23035	25RB#0	22.84	25.5	PASS
Band12	5MHz	16QAM	23095	1RB#0	23.84	25.5	PASS
Band12	5MHz	16QAM	23095	1RB#12	23.90	25.5	PASS
Band12	5MHz	16QAM	23095	1RB#24	23.97	25.5	PASS
Band12	5MHz	16QAM	23095	12RB#0	22.68	25.5	PASS
Band12	5MHz	16QAM	23095	12RB#6	22.67	25.5	PASS
Band12	5MHz	16QAM	23095	12RB#13	22.85	25.5	PASS
Band12	5MHz	16QAM	23095	25RB#0	22.75	25.5	PASS

Band12	5MHz	16QAM	23155	1RB#0	23.87	25.5	PASS
Band12	5MHz	16QAM	23155	1RB#12	23.75	25.5	PASS
Band12	5MHz	16QAM	23155	1RB#24	23.66	25.5	PASS
Band12	5MHz	16QAM	23155	12RB#0	22.73	25.5	PASS
Band12	5MHz	16QAM	23155	12RB#6	22.76	25.5	PASS
Band12	5MHz	16QAM	23155	12RB#13	22.63	25.5	PASS
Band12	5MHz	16QAM	23155	25RB#0	22.80	25.5	PASS
Band12	10MHz	QPSK	23060	1RB#0	24.85	25.5	PASS
Band12	10MHz	QPSK	23060	1RB#24	24.90	25.5	PASS
Band12	10MHz	QPSK	23060	1RB#49	24.64	25.5	PASS
Band12	10MHz	QPSK	23060	25RB#0	23.88	25.5	PASS
Band12	10MHz	QPSK	23060	25RB#12	23.91	25.5	PASS
Band12	10MHz	QPSK	23060	25RB#25	23.73	25.5	PASS
Band12	10MHz	QPSK	23060	50RB#0	23.82	25.5	PASS
Band12	10MHz	QPSK	23095	1RB#0	24.72	25.5	PASS
Band12	10MHz	QPSK	23095	1RB#24	24.90	25.5	PASS
Band12	10MHz	QPSK	23095	1RB#49	24.71	25.5	PASS
Band12	10MHz	QPSK	23095	25RB#0	23.76	25.5	PASS
Band12	10MHz	QPSK	23095	25RB#12	23.76	25.5	PASS
Band12	10MHz	QPSK	23095	25RB#25	23.96	25.5	PASS
Band12	10MHz	QPSK	23095	50RB#0	23.89	25.5	PASS
Band12	10MHz	QPSK	23130	1RB#0	24.62	25.5	PASS
Band12	10MHz	QPSK	23130	1RB#24	25.12	25.5	PASS
Band12	10MHz	QPSK	23130	1RB#49	24.63	25.5	PASS
Band12	10MHz	QPSK	23130	25RB#0	23.83	25.5	PASS
Band12	10MHz	QPSK	23130	25RB#12	23.85	25.5	PASS
Band12	10MHz	QPSK	23130	25RB#25	23.76	25.5	PASS
Band12	10MHz	QPSK	23130	50RB#0	23.84	25.5	PASS
Band12	10MHz	16QAM	23060	1RB#0	24.00	25.5	PASS
Band12	10MHz	16QAM	23060	1RB#24	24.02	25.5	PASS
Band12	10MHz	16QAM	23060	1RB#49	23.84	25.5	PASS
Band12	10MHz	16QAM	23060	25RB#0	22.90	25.5	PASS
Band12	10MHz	16QAM	23060	25RB#12	22.91	25.5	PASS
Band12	10MHz	16QAM	23060	25RB#25	22.76	25.5	PASS
Band12	10MHz	16QAM	23060	50RB#0	22.84	25.5	PASS
Band12	10MHz	16QAM	23095	1RB#0	23.82	25.5	PASS
Band12	10MHz	16QAM	23095	1RB#24	23.96	25.5	PASS

Band12	10MHz	16QAM	23095	1RB#49	23.85	25.5	PASS
Band12	10MHz	16QAM	23095	25RB#0	22.86	25.5	PASS
Band12	10MHz	16QAM	23095	25RB#12	22.83	25.5	PASS
Band12	10MHz	16QAM	23095	25RB#25	23.01	25.5	PASS
Band12	10MHz	16QAM	23095	50RB#0	22.91	25.5	PASS
Band12	10MHz	16QAM	23130	1RB#0	23.56	25.5	PASS
Band12	10MHz	16QAM	23130	1RB#24	24.06	25.5	PASS
Band12	10MHz	16QAM	23130	1RB#49	23.53	25.5	PASS
Band12	10MHz	16QAM	23130	25RB#0	22.93	25.5	PASS
Band12	10MHz	16QAM	23130	25RB#12	22.91	25.5	PASS
Band12	10MHz	16QAM	23130	25RB#25	22.83	25.5	PASS
Band12	10MHz	16QAM	23130	50RB#0	22.89	25.5	PASS

Band	Bandwidth	Modulation	Channel	RB Configuration	Result(dBm)	Tune-up power (dBm)	Verdict
Band17	5MHz	QPSK	23755	1RB#0	23.92	24.5	PASS
Band17	5MHz	QPSK	23755	1RB#12	24.10	24.5	PASS
Band17	5MHz	QPSK	23755	1RB#24	23.97	24.5	PASS
Band17	5MHz	QPSK	23755	12RB#0	22.97	24.5	PASS
Band17	5MHz	QPSK	23755	12RB#6	22.93	24.5	PASS
Band17	5MHz	QPSK	23755	12RB#13	23.09	24.5	PASS
Band17	5MHz	QPSK	23755	25RB#0	23.08	24.5	PASS
Band17	5MHz	QPSK	23790	1RB#0	24.00	24.5	PASS
Band17	5MHz	QPSK	23790	1RB#12	24.18	24.5	PASS
Band17	5MHz	QPSK	23790	1RB#24	24.17	24.5	PASS
Band17	5MHz	QPSK	23790	12RB#0	23.08	24.5	PASS
Band17	5MHz	QPSK	23790	12RB#6	23.05	24.5	PASS
Band17	5MHz	QPSK	23790	12RB#13	23.15	24.5	PASS
Band17	5MHz	QPSK	23790	25RB#0	23.21	24.5	PASS
Band17	5MHz	QPSK	23825	1RB#0	24.20	24.5	PASS
Band17	5MHz	QPSK	23825	1RB#12	24.18	24.5	PASS
Band17	5MHz	QPSK	23825	1RB#24	24.01	24.5	PASS
Band17	5MHz	QPSK	23825	12RB#0	23.16	24.5	PASS
Band17	5MHz	QPSK	23825	12RB#6	23.19	24.5	PASS
Band17	5MHz	QPSK	23825	12RB#13	22.98	24.5	PASS

Band17	5MHz	QPSK	23825	25RB#0	23.07	24.5	PASS
Band17	5MHz	16QAM	23755	1RB#0	22.91	24.5	PASS
Band17	5MHz	16QAM	23755	1RB#12	23.11	24.5	PASS
Band17	5MHz	16QAM	23755	1RB#24	23.05	24.5	PASS
Band17	5MHz	16QAM	23755	12RB#0	22.02	24.5	PASS
Band17	5MHz	16QAM	23755	12RB#6	22.03	24.5	PASS
Band17	5MHz	16QAM	23755	12RB#13	22.13	24.5	PASS
Band17	5MHz	16QAM	23755	25RB#0	22.14	24.5	PASS
Band17	5MHz	16QAM	23790	1RB#0	23.25	24.5	PASS
Band17	5MHz	16QAM	23790	1RB#12	23.40	24.5	PASS
Band17	5MHz	16QAM	23790	1RB#24	23.32	24.5	PASS
Band17	5MHz	16QAM	23790	12RB#0	22.18	24.5	PASS
Band17	5MHz	16QAM	23790	12RB#6	22.20	24.5	PASS
Band17	5MHz	16QAM	23790	12RB#13	22.23	24.5	PASS
Band17	5MHz	16QAM	23790	25RB#0	22.19	24.5	PASS
Band17	5MHz	16QAM	23825	1RB#0	23.23	24.5	PASS
Band17	5MHz	16QAM	23825	1RB#12	23.19	24.5	PASS
Band17	5MHz	16QAM	23825	1RB#24	23.05	24.5	PASS
Band17	5MHz	16QAM	23825	12RB#0	22.19	24.5	PASS
Band17	5MHz	16QAM	23825	12RB#6	22.20	24.5	PASS
Band17	5MHz	16QAM	23825	12RB#13	22.12	24.5	PASS
Band17	5MHz	16QAM	23825	25RB#0	22.25	24.5	PASS
Band17	10MHz	QPSK	23780	1RB#0	23.87	24.5	PASS
Band17	10MHz	QPSK	23780	1RB#24	24.21	24.5	PASS
Band17	10MHz	QPSK	23780	1RB#49	24.01	24.5	PASS
Band17	10MHz	QPSK	23780	25RB#0	23.08	24.5	PASS
Band17	10MHz	QPSK	23780	25RB#12	23.09	24.5	PASS
Band17	10MHz	QPSK	23780	25RB#25	23.22	24.5	PASS
Band17	10MHz	QPSK	23780	50RB#0	23.15	24.5	PASS
Band17	10MHz	QPSK	23790	1RB#0	23.95	24.5	PASS
Band17	10MHz	QPSK	23790	1RB#24	24.23	24.5	PASS
Band17	10MHz	QPSK	23790	1RB#49	23.97	24.5	PASS
Band17	10MHz	QPSK	23790	25RB#0	23.17	24.5	PASS
Band17	10MHz	QPSK	23790	25RB#12	23.10	24.5	PASS
Band17	10MHz	QPSK	23790	25RB#25	23.23	24.5	PASS
Band17	10MHz	QPSK	23790	50RB#0	23.17	24.5	PASS
Band17	10MHz	QPSK	23800	1RB#0	24.02	24.5	PASS

Band17	10MHz	QPSK	23800	1RB#24	24.36	24.5	PASS
Band17	10MHz	QPSK	23800	1RB#49	23.99	24.5	PASS
Band17	10MHz	QPSK	23800	25RB#0	23.09	24.5	PASS
Band17	10MHz	QPSK	23800	25RB#12	23.12	24.5	PASS
Band17	10MHz	QPSK	23800	25RB#25	23.14	24.5	PASS
Band17	10MHz	QPSK	23800	50RB#0	23.12	24.5	PASS
Band17	10MHz	16QAM	23780	1RB#0	23.07	24.5	PASS
Band17	10MHz	16QAM	23780	1RB#24	23.34	24.5	PASS
Band17	10MHz	16QAM	23780	1RB#49	23.18	24.5	PASS
Band17	10MHz	16QAM	23780	25RB#0	22.14	24.5	PASS
Band17	10MHz	16QAM	23780	25RB#12	22.18	24.5	PASS
Band17	10MHz	16QAM	23780	25RB#25	22.29	24.5	PASS
Band17	10MHz	16QAM	23780	50RB#0	22.21	24.5	PASS
Band17	10MHz	16QAM	23790	1RB#0	23.10	24.5	PASS
Band17	10MHz	16QAM	23790	1RB#24	23.38	24.5	PASS
Band17	10MHz	16QAM	23790	1RB#49	23.17	24.5	PASS
Band17	10MHz	16QAM	23790	25RB#0	22.22	24.5	PASS
Band17	10MHz	16QAM	23790	25RB#12	22.26	24.5	PASS
Band17	10MHz	16QAM	23790	25RB#25	22.34	24.5	PASS
Band17	10MHz	16QAM	23790	50RB#0	22.27	24.5	PASS
Band17	10MHz	16QAM	23800	1RB#0	22.91	24.5	PASS
Band17	10MHz	16QAM	23800	1RB#24	23.31	24.5	PASS
Band17	10MHz	16QAM	23800	1RB#49	22.94	24.5	PASS
Band17	10MHz	16QAM	23800	25RB#0	22.25	24.5	PASS
Band17	10MHz	16QAM	23800	25RB#12	22.27	24.5	PASS
Band17	10MHz	16QAM	23800	25RB#25	22.28	24.5	PASS
Band17	10MHz	16QAM	23800	50RB#0	22.20	24.5	PASS

Remark:

1. Per KDB941225 D05 v02r05, Start with the largest channel bandwidth then measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power among RB offsets at the upper edge, middle, and lower edge of each required test channel. When the reported SAR is ≤ 0.8 W/kg, testing of the remaining RB offset configurations and required test channels is not required for 1 RB allocation; otherwise, SAR is required for the remaining required test channels and only for the RB offset configuration with the highest output power for that channel. 6 When the reported SAR of a required test channel is > 1.45 W/kg, SAR is required for all three RB offset configurations for that required test channel.

2. Per KDB941225 D05 v02r05, the procedures required for 1 RB allocation in 5.2.1 are applied to measure

the SAR for QPSK with 50% RB allocation.

3. Per KDB941225 D05 v02r05, For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations, and the highest reported SAR for 1 RB and 50% RB allocation in 5.2.1 and 5.2.2 are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.

4. Per KDB941225 D05 v02r05, for each modulation besides QPSK; e.g., 16-QAM, 64-QAM, apply the QPSK procedures in 5.2.1, 5.2.2, and 5.2.3 to determine the QAM configurations that may need SAR measurement. For each configuration identified as required for testing, SAR is required only when the highest maximum output power for the configuration in the higher order modulation is $> \frac{1}{2}$ dB higher than the same configuration in QPSK or when the reported SAR for the QPSK configuration is > 1.45 W/kg.

9.2 Test Results for Standalone SAR Test

Body SAR

LTE Band 2–Body SAR Test (Gap: 0mm)								
Plot No.	Mode	Test Position Body	Frequency	Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR 1g (W/kg)	Scaled SAR1g (W/kg)
	Modulation, Bandwidth, RB		MHz					
1.	QPSK 20MHz 1RB	Back Face	1860	23.12	23.5	1.091	0.692	0.755
	QPSK 20MHz 1RB	Right Side	1860	23.12	23.5	1.091	0.567	0.619
	QPSK 20MHz 1RB	Top Side	1860	23.12	23.5	1.091	0.593	0.647
	QPSK 20MHz 50%RB	Back Face	1860	23.12	23.5	1.091	0.581	0.634
	QPSK 20MHz 50%RB	Right Side	1860	23.12	23.5	1.091	0.423	0.462
	QPSK 20MHz 50%RB	Top Side	1860	23.12	23.5	1.091	0.473	0.516

LTE Band 4–Body SAR Test (Gap: 0mm)								
Plot No.	Mode	Test Position Body	Frequency	Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR 1g (W/kg)	Scaled SAR1g (W/kg)
	Modulation, Bandwidth, RB		MHz					
2.	QPSK 20MHz 1RB	Back Face	1720.0	22.05	22.5	1.109	0.719	0.797
	QPSK 20MHz 1RB	Right Side	1720.0	22.05	22.5	1.109	0.423	0.469
	QPSK 20MHz 1RB	Top Side	1720.0	22.05	22.5	1.109	0.521	0.578
	QPSK 20MHz 50%RB	Back Face	1720.0	22.05	22.5	1.109	0.611	0.678
	QPSK 20MHz 50%RB	Right Side	1720.0	22.05	22.5	1.109	0.349	0.387
	QPSK 20MHz 50%RB	Top Side	1720.0	22.05	22.5	1.109	0.467	0.518

LTE Band 5–Body SAR Test (Gap: 0mm)								
Plot No.	Mode	Test Position Body	Frequency	Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR 1g (W/kg)	Scaled SAR1g (W/kg)
	Modulation, Bandwidth, RB		MHz					
3.	QPSK 10MHz 1RB	Back Face	829	23.85	24.0	1.035	0.566	0.586
	QPSK 10MHz 1RB	Right Side	829	23.85	24.0	1.035	0.273	0.283
	QPSK 10MHz 1RB	Top Side	829	23.85	24.0	1.035	0.303	0.314
	QPSK 10MHz 50%RB	Back Face	829	23.85	24.0	1.035	0.455	0.471
	QPSK 10MHz 50%RB	Right Side	829	23.85	24.0	1.035	0.242	0.251
	QPSK 10MHz 50%RB	Top Side	829	23.85	24.0	1.035	0.263	0.272

LTE Band 12–Body SAR Test (Gap: 0mm)								
Plot No.	Mode	Test Position Body	Frequency	Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR 1g (W/kg)	Scaled SAR1g (W/kg)
	Modulation, Bandwidth, RB		MHz					
4.	QPSK 10MHz 1RB	Back Face	711	25.12	25.5	1.091	0.195	0.213
	QPSK 10MHz 1RB	Right Side	711	25.12	25.5	1.091	0.101	0.110
	QPSK 10MHz 1RB	Top Side	711	25.12	25.5	1.091	0.106	0.116
	QPSK 10MHz 50%RB	Back Face	711	25.12	25.5	1.091	0.156	0.170
	QPSK 10MHz 50%RB	Right Side	711	25.12	25.5	1.091	0.087	0.095
	QPSK 10MHz 50%RB	Top Side	711	25.12	25.5	1.091	0.096	0.105

LTE Band 17–Body SAR Test (Gap: 0mm)								
Plot No.	Mode	Test Position Body	Frequency	Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR 1g (W/kg)	Scaled SAR1g (W/kg)
	Modulation, Bandwidth, RB		MHz					
5.	QPSK 10MHz 1RB	Back Face	711	24.36	24.5	1.033	0.194	0.200
	QPSK 10MHz 1RB	Right Side	711	24.36	24.5	1.033	0.097	0.100
	QPSK 10MHz 1RB	Top Side	711	24.36	24.5	1.033	0.104	0.107
	QPSK 10MHz 50%RB	Back Face	711	24.36	24.5	1.033	0.150	0.155
	QPSK 10MHz 50%RB	Right Side	711	24.36	24.5	1.033	0.083	0.086
	QPSK 10MHz 50%RB	Top Side	711	24.36	24.5	1.033	0.088	0.091

Remark:

- 1) Per KDB 447498 D01 v06, if the highest output channel SAR for each exposure position ≤ 0.8 W/kg other channels SAR tests are not necessary.
- 2) Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg; steps 2) through 4) do not apply.
- 3) When the original highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.
- 4) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is ≥ 1.45 W/kg ($\sim 10\%$ from the 1-g SAR limit).
- 5) Perform a third repeated measurement only if the original, first or second repeated measurement is ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .

10. Measurement Uncertainty

10.1 Uncertainty for SAR Test

a	b	c	d	e= f(d,k)	f	g	h= c*f/e	i= c*g/e	k
Uncertainty Component	Sec.	Tol (+- %)	Prob. Dist.	Div.	Ci (1g)	Ci (10g)	1g Ui (+-%)	10g Ui (+-%)	Vi
Measurement System									
Probe calibration	E.2.1	7.0	N		1	1	7.00	7.00	
Axial Isotropy	E.2.2	2.5	R		$(1_{-Cp})^{1/2}$	$(1_{-Cp})^{1/2}$	1.02	1.02	
Hemispherical Isotropy	E.2.2	4.0	R		$(Cp)^{1/2}$	$(Cp)^{1/2}$	1.63	1.63	
Boundary effect	E.2.3	1.0	R		1	1	0.58	0.58	
Linearity	E.2.4	5.0	R		1	1	2.89	2.89	
System detection limits	E.2.5	1.0	R		1	1	0.58	0.58	
Readout Electronics	E.2.6	0.02	N		1	1	0.02	0.02	
Reponse Time	E.2.7	3.0	R		1	1	1.73	1.73	
Integration Time	E.2.8	2.0	R		1	1	1.15	1.15	
RF ambient Conditions -	E.6.1	0	R		1	1	1.73	1.73	
RF ambient Conditions - Reflections	E.6.1	0	R		1	1	1.73	1.73	
Probe positioner Mechanical Tolerance	E.6.2	2.0	R		1	1	1.15	1.15	
Probe positioning with respect to Phantom Shell	E.6.3	0.05	R		1	1	0.03	0.03	
Extrapolation, interpolation and integration Algorithms for Max. SAR Evaluation	E.5	5.0	R		1	1	2.89	2.89	
Test Sample Related									
Test sample positioning	E.4.2	0.03	N		1	1	0.03	0.03	
Device Holder Uncertainty	E.4.1	5.00	N		1	1	5.00	5.00	
Output power Variation - SAR drift measurement	E.2.9	12.02	R		1	1	6.94	6.94	
SAR scaling	E6.5	0.0	R		1	1	0.0	0.0	
Phantom and Tissue Parameters									
Phantom Uncertainty (Shape and thickness tolerances)	E.3.1	0.05	R		1	1	0.03	0.03	

Uncertainty in SAR correction for deviations in permittivity and conductivity	E3.2	1.9	R		1	0.84	1.10	0.90	
Liquid conductivity - deviation from target value	E.3.2	5.00	R		0.64	0.43	1.85	1.24	
Liquid conductivity - measurement uncertainty	E.3.3	5.00	N		0.64	0.43	3.20	2.15	
Liquid permittivity - deviation from target value	E.3.2	0.37	R		0.6	0.49	0.13	0.10	
Liquid permittivity - measurement uncertainty	E.3.3	10.00	N		0.6	0.49	6.00	4.90	
Combined Standard Uncertainty			RSS				10.20	10.00	
Expanded Uncertainty (95% Confidence interval)			K=2				20.40	20.00	

Annex A. Plots of System Performance Check

MEASUREMENT 1

Type: Validation measurement (Fast, 75.00 %)

Date of measurement: 2023-02-28

Measurement duration: 7 minutes 21 seconds


E-field Probe: SSE2 - SN 18/21 EPGO356; ConvF: 1.76; Calibrated: 2022-07-08

A. Experimental conditions

Area Scan	dx=8mm dy=8mm
Zoom Scan	dx=5mm dy=5mm dz=4mm
Phantom	Validation plane
Device Position	Dipole
Band	CW750
Signal	Duty Cycle 1:1

B. SAR Measurement Results

Frequency (MHz)	750.000000
Relative Permittivity (real part)	55.54239
Conductivity (S/m)	0.950947
Power Variation (%)	1.074514
Ambient Temperature	23.5
Liquid Temperature	23.5





Maximum location: X=0.00, Y=0.00

SAR 10g (W/Kg)	1.300865
SAR 1g (W/Kg)	2.124211

Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	2.5132	1.1087	0.8214	0.5160	0.4875	0.4864



MEASUREMENT 2

Type: Validation measurement (Fast, 75.00 %)

Date of measurement: 2023-02-28

Measurement duration: 7 minutes 21 seconds


E-field Probe: SSE2 - SN 18/21 EPGO356; ConvF: 1.78; Calibrated: 2022-07-08

A. Experimental conditions

Area Scan	dx=8mm dy=8mm
Zoom Scan	dx=5mm dy=5mm dz=4mm
Phantom	Validation plane
Device Position	Dipole
Band	CW835
Signal	Duty Cycle 1:1

B. SAR Measurement Results

Frequency (MHz)	835.000000
Relative Permittivity (real part)	54.462418
Conductivity (S/m)	0.941236
Power Variation (%)	2.033756
Ambient Temperature	23.5
Liquid Temperature	23.5




Maximum location: X=0.00, Y=0.00

SAR 10g (W/Kg)	1.528956
SAR 1g (W/Kg)	2.354211

Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	2.5789	1.1300	0.8795	0.5940	0.5011	0.5100



3D screen shot	Hot spot position

MEASUREMENT 3

Type: Validation measurement (Fast, 75.00 %)

Date of measurement: 2023-02-27

Measurement duration: 12 minutes 21 seconds


E-field Probe: SSE2 - SN 18/21 EPGO356; ConvF: 2.15; Calibrated: 2022-07-08

A. Experimental conditions

Area Scan	dx=8mm dy=8mm
Zoom Scan	dx=5mm dy=5mm dz=4mm
Phantom	Validation plane
Device Position	Dipole
Band	CW1800
Signal	CW (Crest factor: 1.0)

B. SAR Measurement Results

Frequency (MHz)	1800.000000
Relative Permittivity (real part)	54.671023
Conductivity (S/m)	1.501296
Power Variation (%)	-1.469023
Ambient Temperature	23.7
Liquid Temperature	23.7




Maximum location: X=0.00, Y=0.00

SAR 10g (W/Kg)	5.221202
SAR 1g (W/Kg)	9.582560

Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	11.2425	9.4123	8.0345	6.9125	6.3092	3.9460



3D screen shot	Hot spot position

MEASUREMENT 4

Type: Validation measurement (Fast, 75.00 %)

Date of measurement: 2023-02-27

Measurement duration: 12 minutes 21 seconds


E-field Probe: SSE2 - SN 18/21 EPGO356; ConvF: 2.30; Calibrated: 2022-07-08

A. Experimental conditions

Area Scan	dx=8mm dy=8mm
Zoom Scan	dx=5mm dy=5mm dz=4mm
Phantom	Validation plane
Device Position	Dipole
Band	CW1900
Signal	Duty Cycle 1:1

B. SAR Measurement Results

Frequency (MHz)	1900.000000
Relative Permittivity (real part)	54.542493
Conductivity (S/m)	1.533629
Power Variation (%)	1.022540
Ambient Temperature	23.7
Liquid Temperature	23.7




Maximum location: X=0.00, Y=0.00

SAR 10g (W/Kg)	5.134651
SAR 1g (W/Kg)	9.781550

Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	10.2031	6.43001	4.9011	4.5325	3.1201	2.5024



3D screen shot	Hot spot position

Annex B. Plots of SAR Measurement

MEASUREMENT 1

Type: Phone measurement (Complete)

Date of measurement: 2023-02-27

Measurement duration: 12 minutes 3 seconds


A. Experimental conditions

Area Scan	dx=8mm dy=8mm
Zoom Scan	dx=4mm dy=4mm dz=2mm
Phantom	Flat Plane
Device Position	Back
Band	LTE Band 2
Channels	QPSK, 20MHz, 1RB, Low
Signal	Duty Cycle 1:1

B. SAR Measurement Results

Frequency (MHz)	1860.000000
Relative Permittivity (real part)	54.541247
Conductivity (S/m)	1.532136
Power Variation (%)	-1.210000
Ambient Temperature	23.7
Liquid Temperature	23.7

C. SAR Surface and Volume




Maximum location: X=2.00, Y=-5.00

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.343827
SAR 1g (W/Kg)	0.692448

E. Z Axis Scan

Z (mm)	0.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00	18.00
SAR (W/Kg)	1.5317	0.7236	0.4835	0.3796	0.2654	0.2064	0.1511	0.1182	0.0898



F. 3D Image



MEASUREMENT 2

Type: Phone measurement (Complete)
 Date of measurement: 2023-02-27
 Measurement duration: 12 minutes 3 seconds


A. Experimental conditions

Area Scan	dx=8mm dy=8mm
Zoom Scan	dx=4mm dy=4mm dz=2mm
Phantom	Flat Plane
Device Position	Back
Band	LTE Band 4
Channels	QPSK 20MHz 1RB, Low
Signal	Duty Cycle 1:1

B. SAR Measurement Results

Frequency (MHz)	1720.000000
Relative Permittivity (real part)	54.672375
Conductivity (S/m)	1.501747
Power Variation (%)	2.570000
Ambient Temperature	23.7
Liquid Temperature	23.7

C. SAR Surface and Volume




Maximum location: X=-1.00, Y=-3.00

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.306137
SAR 1g (W/Kg)	0.719460

E. Z Axis Scan

Z (mm)	0.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00	18.00
SAR (W/Kg)	1.1795	0.6675	0.4979	0.3693	0.2745	0.2044	0.1518	0.1118	0.0805



F. 3D Image



MEASUREMENT 3

Type: Phone measurement (Complete)
 Date of measurement: 2023-02-28
 Measurement duration: 12 minutes 3 seconds


A. Experimental conditions

Area Scan	dx=8mm dy=8mm
Zoom Scan	dx=4mm dy=4mm dz=2mm
Phantom	Flat Plane
Device Position	Back
Band	LTE Band 5
Channels	QPSK, 10MHz, 1RB, Low
Signal	Duty Cycle 1:1

B. SAR Measurement Results

Frequency (MHz)	829.000000
Relative Permittivity (real part)	54.342427
Conductivity (S/m)	0.944358
Power Variation (%)	1.230000
Ambient Temperature	23.5
Liquid Temperature	23.5

C. SAR Surface and Volume




Maximum location: X=5.00, Y=0.00

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.344526
SAR 1g (W/Kg)	0.566143

E. Z Axis Scan

Z (mm)	0.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00	18.00
SAR (W/Kg)	1.0344	0.5848	0.4449	0.4072	0.2997	0.2868	0.2065	0.2023	0.1424



F. 3D Image



MEASUREMENT 4

Type: Phone measurement (Complete)
 Date of measurement: 2023-02-28
 Measurement duration: 12 minutes 3 seconds


A. Experimental conditions

Area Scan	dx=8mm dy=8mm
Zoom Scan	dx=4mm dy=4mm dz=2mm
Phantom	Flat Plane
Device Position	Back
Band	LTE Band 12
Channels	QPSK, 10MHz, 1RB, High
Signal	Duty Cycle 1:1

B. SAR Measurement Results

Frequency (MHz)	711.0000000
Relative Permittivity (real part)	54.1342648
Conductivity (S/m)	0.953127
Power Variation (%)	3.120000
Ambient Temperature	23.5
Liquid Temperature	23.5

C. SAR Surface and Volume




Maximum location: X=8.00, Y=-7.00

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.110093
SAR 1g (W/Kg)	0.194686

E. Z Axis Scan

Z (mm)	0.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00	18.00
SAR (W/Kg)	0.3802	0.1951	0.1360	0.1196	0.0864	0.0795	0.0602	0.0579	0.0506



F. 3D Image



MEASUREMENT 5

Type: Phone measurement (Complete)
 Date of measurement: 2023-02-28
 Measurement duration: 12 minutes 3 seconds


A. Experimental conditions

Area Scan	dx=8mm dy=8mm
Zoom Scan	dx=4mm dy=4mm dz=2mm
Phantom	Flat Plane
Device Position	Back
Band	LTE Band 17
Channels	QPSK, 10MHz, 1RB, High
Signal	Duty Cycle 1:1

B. SAR Measurement Results

Frequency (MHz)	711.000000
Relative Permittivity (real part)	54.1342648
Conductivity (S/m)	0.953127
Power Variation (%)	1.150000
Ambient Temperature	23.5
Liquid Temperature	23.5

C. SAR Surface and Volume




Maximum location: X=8.00, Y=-6.00

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.115726
SAR 1g (W/Kg)	0.194029

E. Z Axis Scan

Z (mm)	0.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00	18.00
SAR (W/Kg)	0.3594	0.1935	0.1436	0.1288	0.0957	0.0907	0.0688	0.0675	0.0523



F. 3D Image



Annex C. EUT Photos


EUT View 1



EUT View 2



Antenna View



Annex D. Test Setup Photos

Body mode Exposure Conditions
Test distance: 0mm

Body Back



Body Right



Body Top



Annex E. Calibration Certificate

Please refer to the exhibit for the calibration certificate

****** END OF REPORT ******