

Operational Principle

1. The SE69D is a member of the low-cost, high-performance family of intelligent 2.4 GHz RF transceivers with embedded microcontrollers.
2. The SE69D is optimized to provide a single chip solution for Ultra Low Power (ULP) wireless applications. The combination of processing power, memory, low power oscillators, real-time counter and a range of power saving modes provides an ideal platform for implementation of RF protocols.
3. Benefits of using SE69D include tighter protocol timing, security, lower power consumption and improved co-existence performance. For the application layer the SE69D offers a rich set of peripherals including: USB, and so on. ANTENNA, The antenna is typically fed from the end of the monopole section by a plated through-hole via which is in turn connected to the RF output on the 2.4GHz band.

4. Frequency List

1CH	2402 MHz	21CH	2442 MHz
2CH	2404 MHz	22CH	2444 MHz
3CH	2406 MHz	23CH	2446 MHz
4CH	2408 MHz	24CH	2448 MHz
5CH	2410 MHz	25CH	2450 MHz
6CH	2412 MHz	26CH	2452 MHz
7CH	2414 MHz	27CH	2454 MHz
8CH	2416 MHz	28CH	2456 MHz
9CH	2418 MHz	29CH	2458 MHz
10CH	2420 MHz	30CH	2460 MHz
11CH	2422 MHz	31CH	2462 MHz
12CH	2424 MHz	32CH	2464 MHz
13CH	2426 MHz	33CH	2466 MHz
14CH	2428 MHz	34CH	2468 MHz
15CH	2430 MHz	35CH	2470 MHz
16CH	2432 MHz	36CH	2472 MHz
17CH	2434 MHz	37CH	2474 MHz
18CH	2436 MHz	38CH	2476 MHz
19CH	2438 MHz	39CH	2478 MHz
20CH	2440 MHz	40CH	2480 MHz