

---

# FCC Test Report

---

Report No.: AGC08409191201FE06

**FCC ID** : 2AHASBT10M  
**APPLICATION PURPOSE** : Original Equipment  
**PRODUCT DESIGNATION** : Bluetooth FM Transmitter  
**BRAND NAME** : ArmorAll, Monster  
**MODEL NAME** : BT10M, MCC9-1033-BLK  
**APPLICANT** : JEM ACCESSORIES,INC  
**DATE OF ISSUE** : Jan. 08, 2020  
**STANDARD(S)** : FCC Part 15.239  
**REPORT VERSION** : V1.0

Attestation of *Global Compliance*(Shenzhen) Co., Ltd

**CAUTION:**

This report shall not be reproduced except in full without the written permission of the test laboratory and shall not be quoted out of context.



Attestation of Global Compliance

Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, Sanwei Chaxi Industrial Park, Sanwei Community,  
Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755 2523 4088

E-mail: agc@agc-cert.com

Service Hotline:400 089 2118

### Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Jan. 08, 2020	Valid	Initial Release



## TABLE OF CONTENTS

<b>1. VERIFICATION OF CONFORMITY</b> .....	<b>4</b>
<b>2. GENERAL INFORMATION</b> .....	<b>5</b>
2.1. PRODUCT DESCRIPTION .....	5
<b>3. MEASUREMENT UNCERTAINTY</b> .....	<b>5</b>
<b>4. DESCRIPTION OF TEST MODES</b> .....	<b>5</b>
<b>5. SYSTEM TEST CONFIGURATION</b> .....	<b>6</b>
5.1. EQUIPMENT USED IN EUT SYSTEM .....	6
5.2. SUMMARY OF TEST RESULTS .....	6
<b>6. TEST FACILITY</b> .....	<b>7</b>
<b>7. RADIATED EMISSION</b> .....	<b>8</b>
7.1. MEASUREMENT PROCEDURE .....	8
7.2. TEST SETUP .....	9
7.3. TEST RESULT FOR FIELD STRENGTH OF FUNDAMENTAL .....	10
7.4. TEST RESULT FOR FIELD STRENGTH OF BAND EDGE EMISSION .....	10
7.5. TEST RESULT FOR SPURIOUS EMISSION .....	11
<b>8. BANDWIDTH</b> .....	<b>13</b>
8.1. MEASUREMENT PROCEDURE .....	13
8.2. TEST SETUP .....	13
8.3. TEST RESULT .....	14
<b>APPENDIX A: PHOTOGRAPHS OF TEST SETUP</b> .....	<b>16</b>
<b>APPENDIX B: PHOTOGRAPHS OF EUT</b> .....	<b>17</b>


### 1. VERIFICATION OF CONFORMITY

<b>Applicant</b>	JEM ACCESSORIES,INC
<b>Address</b>	32 Brunswick Avenue Edison NJ 08817
<b>Manufacturer</b>	JEM ACCESSORIES,INC
<b>Address</b>	32 Brunswick Avenue Edison NJ 08817
<b>Factory</b>	JME ACCESSORIES,INC
<b>Address</b>	32 Brunswick Avenue Edison NJ 08817
<b>Product Designation</b>	Bluetooth FM Transmitter
<b>Brand Name</b>	ArmorAll, Monster
<b>Test Model</b>	BT10M
<b>Series Model</b>	MCC9-1033-BLK
<b>Difference description</b>	All the same except for the brand name and model name.
<b>Date of test</b>	Dec. 10, 2019~Jan. 08, 2020
<b>Condition of Test Sample</b>	Normal
<b>Test Result</b>	Pass
<b>Report Template</b>	AGCRT-US-BR/RF (2013-03-01)

We hereby certify that:

The above equipment was tested by Attestation of Global Compliance (Shenzhen) Co., Ltd. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with radiated emission limits of FCC part 15.239.

Prepared By



Donjon Huang  
Project Engineer

Jan. 08, 2020

Reviewed By



Max Zhang  
Reviewer

Jan. 08, 2020

Approved By



Forrest Lei  
Authorized Officer

Jan. 08, 2020

## 2. GENERAL INFORMATION

### 2.1.PRODUCT DESCRIPTION

A major technical description of EUT is described as following

<b>Operation Frequency</b>	88.1MHz-107.9MHz
<b>Field Strength(3m)</b>	44.02dBuV/m(average)@3m
<b>Modulation</b>	FM
<b>Number of channels</b>	199(Channel spacing 100kHz)
<b>Hardware Version</b>	JMS_BT10M-V1.2 JMS_BT10M-PW-V1.0
<b>Software Version</b>	[MCC9-1033-BLK]_[sj_10M_tts]_[FM87.5-108.0]_20190617_CGF_SDK03B_V2.0
<b>Antenna Designation</b>	Internal Antenna (Met 15.203 Antenna requirement)
<b>Antenna Gain</b>	1.2dBi
<b>Power Supply</b>	DC 12 to 24V, 3A

**NOTE:** About the EUT, please refer to User's Manual.

## 3. MEASUREMENT UNCERTAINTY

Conducted measurement: +/- 3.18dB

Radiated measurement: +/- 3.91dB

## 4. DESCRIPTION OF TEST MODES

NO.	TEST MODE DESCRIPTION
1	FM Transmitter (Low channel)
2	FM Transmitter (Middle channel)
3	FM Transmitter (High channel)

Note: 1. For Radiated Emission, 3axis were chosen for testing for each applicable mode.  
2. All the requirements have been tested by modulating the transmitter with a 2.5 kHz tone at a fixed level which set to the manufacturer's maximum rated input to the modulator.  
3. Only the result of the worst case was recorded in the report, if no other cases.  
4.Tuning-Range confirmed 88.1 ~ 107.9 MHz

## 5. SYSTEM TEST CONFIGURATION

### 5.1. EQUIPMENT USED IN EUT SYSTEM

Item	Equipment	Model No.	ID or Specification	Remark
1	Bluetooth FM Transmitter	BT10M	2AHASBT10M	EUT
2	Car battery	N/A	12V 60Ah	AE
3	Car battery	N/A	12V 60Ah	AE
4	Control Box	N/A	USB-TTL	AE
5	Cable	N/A	0.6m	AE
6	U-Disk	Kingston	DT 101G2	AE
7	TF Card	Kingston	SDA10	AE
8	load	N/A	2.5ohm	AE

### 5.2. SUMMARY OF TEST RESULTS

FCC RULES	DESCRIPTION OF TEST	RESULT
15.239	Field Strength of Fundamental and Spurious Emission	Compliant
15.215	Bandwidth	Compliant
15.209	Line Conducted Emission	N/A

Note: N/A means it's not applicable to this item.



## 6. TEST FACILITY

<b>TestSite</b>	Attestation of Global Compliance(Shenzhen) Co., Ltd
<b>Location</b>	1-2/F,Building19,JunfengIndustrialPark,ChongqingRoad,HepingCommunity,Fuhai Street,Bao'anDistrict,Shenzhen,Guangdong,China
<b>Designation Number</b>	CN1259
<b>FCC Test Firm Registration Number</b>	975832
<b>A2LA Cert. No.</b>	5054.02
<b>Description</b>	Attestation of Global Compliance(Shenzhen) Co., Ltd is accredited by A2LA

## TEST EQUIPMENT OF RADIATED EMISSION TEST

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
TEST RECEIVER	R&S	ESCI	10096	Jun. 12, 2019	Jun. 11, 2020
EXA Signal Analyzer	Aglient	N9010A	MY53470504	Dec. 12, 2019	Dec. 11, 2020
Attenuator	ZHINAN	E-002	N/A	Sep. 09, 2019	Sep. 08, 2020
Active loop antenna (9K-30MHz)	ZHINAN	ZN30900C	18051	Jun. 13, 2018	Jun. 12, 2020
ANTENNA	SCHWARZBECK	VULB9168	494	Sep. 20, 2019	Sep. 19, 2021
Test software	FARA	EZ EMC( Ver. RA-03A)	N/A	N/A	N/A



## 7. RADIATED EMISSION

### 7.1. MEASUREMENT PROCEDURE

1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 0.8 meter above ground and opposite the horn antenna. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions below 1GHz, use 120KHz RBW and VBW>=3RBW for QP reading.
7. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High - Low scan is not required in this case.
8. Only the worst case is reported.

The following table is the setting of spectrum analyzer and receiver.


Receiver Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RBW 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RBW 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RBW 120KHz for QP






### 7.2.TEST SETUP

Radiated Emission Test-Setup Frequency Below 30MHz



RADIATED EMISSION TEST SETUP 30MHz-1000MHz



**7.3. TEST RESULT FOR FIELD STRENGTH OF FUNDAMENTAL**

Frequency MHz	Polarization	Level dB(uV/m) PK	Limit dB(uV/m) PK	Margin dB	Pass/Fail	Detector
88.100	H	45.48	67.96	21.48	Pass	PK
88.100	V	44.24	67.96	24.72	Pass	PK
98.000	H	46.04	67.96	22.57	Pass	PK
98.000	V	45.94	67.96	25.49	Pass	PK
107.900	H	45.89	67.96	22.07	Pass	PK
107.900	V	44.62	67.96	25.75	Pass	PK
Frequency MHz	Polarization	Level dB(uV/m) AV	Limit dB(uV/m) AV	Margin dB	Pass/Fail	Detector
88.100	H	43.52	47.96	3.44	Pass	AV
88.100	V	42.16	47.96	5.80	Pass	AV
98.000	H	44.02	47.96	3.49	Pass	AV
98.000	V	43.23	47.96	6.73	Pass	AV
107.900	H	43.76	47.96	3.50	Pass	AV
107.900	V	42.31	47.96	4.78	Pass	AV

**7.4. TEST RESULT FOR FIELD STRENGTH OF BAND EDGE EMISSION**

Frequency MHz	Polarization	Level dB(uV/m) QP	Limit dB(uV/m) QP	Margin dB	Pass/Fail	Detector
88.000	H	34.96	40	5.04	Pass	QP
88.000	V	32.42	40	7.58	Pass	QP
108.000	H	35.33	43.5	8.17	Pass	QP
108.000	V	30.42	43.5	13.08	Pass	QP


Note: The above two frequencies are the worst case for the band edge emission test.

### 7.5. TEST RESULT FOR SPURIOUS EMISSION

#### RADIATED EMISSION BELOW 30MHz

No emission found between lowest internal used/generated frequencies to 30MHz.

#### RADIATED EMISSION BELOW 1GHZ-Horizontal



No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		44.5499	5.95	19.93	25.88	40.00	-14.12	peak			
2	*	98.000	30.25	15.79	46.04			peak			
3	!	136.6999	19.72	19.02	38.74	43.50	-4.76	peak			
4	!	266.0332	23.16	18.80	41.96	46.00	-4.04	peak			
5		594.2165	8.35	26.84	35.19	46.00	-10.81	peak			
6		919.1666	4.86	31.86	36.72	46.00	-9.28	peak			

RESULT: PASS



Attestation of Global Compliance

Attestation of Global Compliance(Shenzhen)Co.,Ltd.


Add: 2/F., Building 2, Sanwei Chaxi Industrial Park, Sanwei Community,  
Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755 2523 4088

E-mail: agc@agc-cert.com

Service Hotline: 400 089 2118

RADIATED EMISSION BELOW 1GHZ-Vertical



No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		60.7167	11.25	18.74	29.99	40.00	-10.01	peak			
2	*	98.000	30.15	15.79	45.94			peak			
3		136.6999	17.87	19.02	36.89	43.50	-6.61	peak			
4		264.4166	17.88	18.67	36.55	46.00	-9.45	peak			
5		574.8165	7.32	26.46	33.78	46.00	-12.22	peak			
6		912.7000	3.45	31.81	35.26	46.00	-10.74	peak			

**RESULT: PASS**

**Note:** 1. Factor=Antenna Factor+ Cable loss-Amplifier gain, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.

3. All test modes had been tested. The mode2 is the worst case and recorded in the report.

## 8. BANDWIDTH

### 8.1. MEASUREMENT PROCEDURE

1. Set the parameters of SPA as below:

Centre frequency = Operation Frequency

RBW=3KHz

VBW=10KHz

Span: 300kHz

Sweep time: Auto

For the occupied bandwidth measurements, the input signal shall be a 2.5 kHz tone.


The level of the tone shall be 16 dB higher than that required to produce a frequency deviation of 75 kHz, or 50% of the manufacturer's rated deviation, whichever is less.

Alternatively, in the event that a 16 dB increase cannot be achieved, the level of the tone shall be set to the manufacturer's maximum rated input to the modulator.

2. Set the EUT to continue transmitting mode. Allow the trace to stabilize. Use the "N dB down" function of SPA to define the bandwidth.

3. Record the plots and Reported.


### 8.2. TEST SETUP




### 8.3. TEST RESULT

Channel	Channel Frequency(MHz)	-20dB bandwidth (kHz)	Limit(kHz)
Low	88.1	141.4	200
Middle	98.0	142.1	200
High	107.9	139.7	200


TEST PLOT OF BANDWIDTH FOR LOW CHANNEL




TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL



TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL



**APPENDIX A: PHOTOGRAPHS OF TEST SETUP**  
RADIATED EMISSION AND BANDWIDTH TEST SETUP






**APPENDIX B:PHOTOGRAPHS OF EUT**  
TOP VIEW OF EUT



**BOTTOM VIEW OF EUT**



FRONT VIEW OF EUT



BACK VIEW OF EUT



LEFT VIEW OF EUT




RIGHT VIEW OF EUT




OPEN VIEW OF EUT




INTERNAL VIEW OF EUT-1




INTERNAL VIEW OF EUT-2




INTERNAL VIEW OF EUT-3




INTERNAL VIEW OF EUT-4




INTERNAL VIEW OF EUT-5




INTERNAL VIEW OF EUT-6



INTERNAL VIEW OF EUT-7



INTERNAL VIEW OF EUT-8



INTERNAL VIEW OF EUT-9





INTERNAL VIEW OF EUT-10



---END OF REPORT---

