

## RF Exposure evaluation

According to 447498 D01 General RF Exposure Guidance v05  
The 1-g and 10-g SAR test exclusion thresholds for 100 MHz  
to 6 GHz at test separation distances  $\leq 50$  mm are determined  
by:

$$\left[ \frac{\text{max. power of channel, including tune-up tolerance, mW}}{\text{min. test separation distance, mm}} \right] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$$

for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

$f(\text{GHz})$  is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm  
before calculation

The result is rounded to one decimal place for comparison

$$\text{eirp} = \text{pt} \times \text{gt} = (\text{EXd})^2/30$$

where:

pt = transmitter output power in watts,

gt = numeric gain of the transmitting antenna (unitless),

E = electric field strength in V/m, ---  $10^{((\text{dBuV/m})/20)}/10^6$

d = measurement distance in meters (m)---3m

$$\text{So pt} = (\text{EXd})^2/30 \times \text{gt}$$

Field strength =86.90 dBuV/m @3m

Ant gain 0 dBi; so Ant numeric gain=1

$$\text{So pt} = \left\{ \left[ \frac{10^{(86.90/20)}}{10^6} \times 3 \right]^2 / 30 \times 1 \right\} \times 1000 \text{ mW} = 0.3 \text{ mW}$$

$$\text{So } (0.3\text{mW}/5\text{mm}) \times \sqrt{2.402 \text{ GHz}} = 0.10 < 3$$

Then SAR evaluation is not required