

RF Exposure Report

Report No.: SA190912E02A

FCC ID: 2AHBN-AP33

Test Model: AP32

Series Model: AP32E, AP33

Received Date: Sep. 26, 2019

Test Date: Dec. 04, 2019

Issued Date: Feb. 19, 2020

Applicant: Mist Systems, Inc.

Address: 1601 South De Anza Blvd. Suite 248 Cupertino California United States
95014

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Hsin Chu Laboratory

Lab Address: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan.

Test Location: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan.

**FCC Registration /
Designation Number:** 723255 / TW2022

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by any government agencies.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 RF Exposure	5
2.1 Limits For Maximum Permissible Exposure (MPE)	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
2.4 Antenna Gain	6
2.5 Calculation Result of Maximum Conducted Power	7

Release Control Record

Issue No.	Description	Date Issued
SA190912E02A	Original release.	Feb. 19, 2020

1 Certificate of Conformity

Product: Wi-Fi & BLE Array AP

Brand: Mist

Test Model: AP32

Series Model: AP32E, AP33

Applicant: Mist Systems, Inc.

Test Date: Dec. 04, 2019

Standards: FCC Part 2 (Section 2.1091)
IEEE C95.3-2002

References Test Guidance: KDB 447498 D01 General RF Exposure Guidance v06

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by :  , **Date:** Feb. 19, 2020
Claire Kuan / Specialist

Approved by :  , **Date:** Feb. 19, 2020
Clark Lin / Technical Manager

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	f/1500	30
1500-100,000	1.0	30

f = Frequency in MHz ; *Plane-wave equivalent power density

2.2 MPE Calculation Formula

$$Pd = (Pout * G) / (4 * \pi * r^2)$$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 40 cm away from the body of the user.

So, this device is classified as **Mobile Device**.

2.4 Antenna Gain

Model: AP32						
Antenna NO.	Brand	Model	Antenna Net Gain(dBi)	Frequency range	Antenna Type	Connector Type
Int Dual Ant 3 (WiFi 5G+BT)	-	-	5 6	2.4~2.4835GHz 5.15~5.85GHz	PIFA	Ipex
Int WiFi Dual Ant 1	-	-	4.5 5.4	2.4~2.4835GHz 5.15~5.85GHz	PIFA	Ipex
Int WiFi Dual Ant 0	-	-	4.6 5.7	2.4~2.4835GHz 5.15~5.85GHz	PIFA	Ipex
Int WiFi 5G Ant 2	-	-	5.8	5.15~5.85GHz	PIFA	Ipex
Scanning Ant	-	-	5 6	2.4~2.4835GHz 5.15~5.85GHz	PIFA	Ipex
Model: AP32E						
Antenna NO.	Brand	Model	Antenna Net Gain(dBi)	Frequency range	Antenna Type	Connector Type
Ext WiFi Dual Ant (2.4+5G)	AccelTex	ATS-OO-245-46-6RPSP-36	4 6	2.4~2.4835GHz 5.15~5.85GHz	omnidirectional	RPSMA Plug
Ext WiFi Dual Ant (2.4+5G)			4 6	2.4~2.4835GHz 5.15~5.85GHz	omnidirectional	RPSMA Plug
Ext WiFi Dual Ant (5G)			4 6	2.4~2.4835GHz 5.15~5.85GHz	omnidirectional	RPSMA Plug
Ext WiFi Dual Ant (5G)			4 6	2.4~2.4835GHz 5.15~5.85GHz	omnidirectional	RPSMA Plug
Ext WiFi Dual Ant (Scanning)			4 6	2.4~2.4835GHz (Scanning) 5.15~5.85GHz (Scanning)	omnidirectional	RPSMA Plug
Int Scanning Ant	-	-	5 6	2.4~2.4835GHz (Scanning) 5.15~5.85GHz (Scanning)	PIFA	Ipex
Int BT Ant	-	-	5	2.4~2.4835GHz	PIFA	Ipex
Model: AP33						
Antenna NO.	Brand	Model	Antenna Net Gain(dBi)	Frequency range	Antenna Type	Connector Type
Int WiFi Dual Ant 0	-	-	3.7 6	2.4~2.4835GHz 5.15~5.85GHz	PIFA	Ipex
Int WiFi Dual Ant 1	-	-	4.6 6	2.4~2.4835GHz 5.15~5.85GHz	PIFA	Ipex
Int WiFi 5G Ant 2	-	-	6	5.15~5.85GHz	PIFA	Ipex
Int WiFi 5G Ant 3	-	-	5.9	5.15~5.85GHz	PIFA	Ipex
Scanning Ant	-	-	5 6	2.4~2.4835GHz 5.15~5.85GHz	PIFA	Ipex
BT Slot_Direct Antenna	-	-	6	2.402~2.480GHz	Slot_Direct	Ipex
BT Array Antenna	-	-	Beam 1 :3.9 Beam 2 :3.9 Beam 3 :4.7 Beam 4 :4.4 Beam 5 :4.8 Beam 6 :5.1 Beam 7 :5.1 Beam 8 :4.2	2.402~2.480GHz	Array Antenna	Ipex

Note: The max. Antenna gain was selected for their final test of Antenna Port Conducted test items.

2.5 Calculation Result of Maximum Conducted Power

Operation Mode	Evaluation Frequency (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
WLAN 2.4GHz	2437	381.986	7.61	40	0.10958	1
WLAN U-NII-1	5230	493.303	12.02	40	0.39065	1
WLAN U-NII-3	5795	886.912	12.02	40	0.70234	1
Scanning Radio_2.4GHz	2462	193.642	5.00	40	0.03046	1
Scanning Radio_WLAN U-NII-1	5200	86.896	6.00	40	0.01721	1
Scanning Radio_WLAN U-NII-3	5795	111.429	6.00	40	0.02206	1
BT-LE	2402	2.312	6.00	40	0.00046	1

NOTE:

- Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.
- WLAN 2.4GHz: The directional gain $4.6 \text{ dBi} + 10\log(2) = 7.61 \text{ dBi}$
 WLAN 5GHz: Directional gain = $6\text{dBi} + 10\log(4) = 12.02\text{dBi}$

Conclusion:

The formula of calculated the MPE is:

$$\text{CPD1} / \text{LPD1} + \text{CPD2} / \text{LPD2} + \dots \text{etc.} < 1$$

CPD = Calculation power density

LPD = Limit of power density

$$\text{WLAN 2.4GHz} + \text{WLAN 5GHz} + \text{Scanning Radio_WLAN 2.4GHz} + \text{Scanning Radio_WLAN 5GHz} + \text{BT-LE} = 0.10958 / 1 + 0.70234 / 1 + 0.03046 / 1 + 0.02206 / 1 + 0.00046 / 1 = 0.86490$$

Therefore the maximum calculations of above situations are less than the "1" limit.

--- END ---