

FCC ID: 2AHCK-WD40FT2108 RF Exposure Report

Test Requirement: FCC Part 1.1307

Evaluation Method: FCC Part 2.1091 & KDB 447498 D01 General RF Exposure Guidance v06

Requirements

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2 m normally can be maintained between the user and the device.

The procedures / limit**(A) Limits for Occupational / Controlled Exposure**

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; *Plane-wave equivalent power density

MPE Calculation Method

$$S = \frac{P \times G}{4 \times \pi \times R^2}$$

S = power density (in appropriate units, e.g. mW/cm²)

P = output power to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

From the peak EUT RF output power, the minimum mobile separation distance, R=20cm, as well as the gain of the used antenna, the RF power density can be obtained

ANTA

Antenna Gain (dBi)	Antenna Gain (numeric)	Maximum conducted (average) output power (dBm)	Maximum conducted (average)output power (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)	Result
2.00	1.585	15.54	35.81	0.0113	1	Compliance

ANTB

Antenna Gain (dBi)	Antenna Gain (numeric)	Maximum conducted (average) output power (dBm)	Maximum conducted (average)output power (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)	Result
2.00	1.585	15.58	36.14	0.0114	1	Compliance

ANTA+ANTB

Antenna Gain (dBi)	Antenna Gain (numeric)	Maximum conducted (average) output power (dBm)	Maximum conducted (average)output power (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)	Result
2.00	1.585	14.93	31.12	0.0098	1	Compliance