

FCC §15.247 (i), §2.1091 - RF Exposure

FCC ID: 2AHCNLOCK100

Applied procedures / limit

According to FCC §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	eigth (E) Strength (H) Power Density (S		Averaging Time E ² , H ² or S (minutes)			
0.3-3.0	614	1.63	(100)*	6			
3.0-30	1842 / f	4.89 / f	(900 / f)*	6			
30-300	61.4	0.163	1.0	6			
300-1500			F/300	6			
1500-100,000			5	6			

Note: f is frequency in MHz

Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz

IEEE 802.11b

max possible output power (AV,conducted): 13±1dbm

IEEE 802.11g

max possible output power (AV,conducted): 12±1dbm

IEEE 802.11N(20)

max possible output power (AV,conducted): 10±1dbm

IEEE 802.11N(40)

max possible output power (AV,conducted): 9±1dbm

^{* =} Power density limit is applicable at frequencies greater than 100 MHz

^{* =} Plane-wave equivalent power density



The max possible output power (AV,conducted) of All (IEEE 802.11b, IEEE 802.11g) is IEEE 802.11b.

MPE PREDICTION

Predication of MPE limit at a given distance, Equation from OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna, R=20cm

Test Result of RF Exposure Evaluation

	Target power W/ tolerance (dBm)	Max tune up power toleranc e (dBm)	Total Output power to antenna (mW)	Antenna Gain(dBi)	Total Power Density at R=20cm (mW/cm²)	Limit (mW/cm²)	Result
802.11b	13±1.0	14.0	25.12	2.0 (1.585)	0.00793	1.0	Pass