



中认信通
CHINA CERTIFICATION ICT CO., LTD (DONGGUAN)



TEST REPORT

Applicant: AKUVOX (XIAMEN) NETWORKS CO., LTD.

Address: 10/F, No.56 Guanri Road, Software Park II, Xiamen 361009, China

FCC ID: 2AHCR-E12WV2

Product Name: Door Phone

Standard(s): 47 CFR Part 15, Subpart C(15.247)

ANSI C63.10-2013

KDB 558074 D01 15.247 Meas Guidance v05r02

The above equipment has been tested and found compliant with the requirement of the relative standards by China Certification ICT Co., Ltd (Dongguan)

Report Number: CR220944645-00A

Date Of Issue: 2023/3/10

Reviewed By: Sun Zhong

Sun Zhong

Title: Manager

Test Laboratory: China Certification ICT Co., Ltd (Dongguan)

No. 113, Pingkang Road, Dalang Town, Dongguan,

Guangdong, China

Tel: +86-769-82016888

Test Facility

The Test site used by China Certification ICT Co., Ltd (Dongguan) to collect test data is located on the No. 113, Pingkang Road, Dalang Town, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 442868, the FCC Designation No. : CN1314.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0123.

Declarations

China Certification ICT Co., Ltd (Dongguan) is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with a triangle symbol “▲”. Customer model name, addresses, names, trademarks etc. are not considered data.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

This report cannot be reproduced except in full, without prior written approval of the Company.

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report may contain data that are not covered by the accreditation scope and shall be marked with an asterisk “★”.

CONTENTS

TEST FACILITY	2
DECLARATIONS.....	2
DOCUMENT REVISION HISTORY	5
1. GENERAL INFORMATION.....	6
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	6
1.2 DESCRIPTION OF TEST CONFIGURATION.....	8
1.2.1 EUT Operation Condition:.....	8
1.2.2 Support Equipment List and Details	8
1.2.3 Support Cable List and Details	8
1.2.4 Block Diagram of Test Setup.....	9
1.3 MEASUREMENT UNCERTAINTY	12
2. SUMMARY OF TEST RESULTS.....	13
3. REQUIREMENTS AND TEST PROCEDURES	14
3.1 AC LINE CONDUCTED EMISSIONS.....	14
3.1.1 Applicable Standard.....	14
3.1.2 EUT Setup.....	15
3.1.3 EMI Test Receiver Setup	15
3.1.4 Test Procedure	16
3.1.5 Corrected Amplitude & Margin Calculation.....	16
3.2 RADIATION SPURIOUS EMISSIONS.....	17
3.2.1 Applicable Standard.....	17
3.2.2 EUT Setup.....	17
3.2.3 EMI Test Receiver & Spectrum Analyzer Setup	18
3.2.4 Test Procedure	18
3.2.5 Corrected Amplitude & Margin Calculation.....	18
3.3 6 DB EMISSION BANDWIDTH:.....	19
3.3.1 Applicable Standard.....	19
3.3.2 EUT Setup.....	19
3.3.3 Test Procedure	19
3.4 99% OCCUPIED BANDWIDTH:	20
3.4.1 EUT Setup.....	20
3.4.2 Test Procedure	20
3.5 MAXIMUM CONDUCTED OUTPUT POWER:.....	21
3.5.1 Applicable Standard.....	21
3.5.2 EUT Setup.....	21
3.5.3 Test Procedure	21
3.6 MAXIMUM POWER SPECTRAL DENSITY:	22
3.6.1 Applicable Standard.....	22
3.6.2 EUT Setup.....	22
3.6.3 Test Procedure	22
3.7 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE:	24

3.7.1 Applicable Standard.....24
3.7.2 EUT Setup.....24
3.7.3 Test Procedure24
3.8 DUTY CYCLE:.....25
3.8.1 EUT Setup.....25
3.8.2 Test Procedure25
3.9 ANTENNA REQUIREMENT.....25
3.9.1 Applicable Standard.....25
3.9.2 Judgment.....25
4. Test DATA AND RESULTS 26
4.1 AC LINE CONDUCTED EMISSIONS.....26
4.2 RADIATION SPURIOUS EMISSIONS31
4.3 6 dB EMISSION BANDWIDTH:42
4.4 99% OCCUPIED BANDWIDTH:47
4.5 MAXIMUM CONDUCTED OUTPUT POWER:52
4.6 MAXIMUM POWER SPECTRAL DENSITY:53
4.7 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE:58
4.8 DUTY CYCLE:.....63
5. RF EXPOSURE EVALUATION 66
5.1 APPLICABLE STANDARD.....66
5.2 CALCULATION FORMULA66
5.3 CALCULATED DATA:67

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
1.0	CR220944645-00A	Original Report	2023/3/10

1. GENERAL INFORMATION

1.1 Product Description for Equipment under Test (EUT)

EUT Name:	Door Phone
EUT Model:	E12W
Operation Frequency:	2412-2462 MHz(802.11b/g/n ht20), 2422-2452MHz(802.11n ht40)
Maximum Average Output Power (Conducted):	802.11b/g/n: 17.07dBm
Modulation Type:	802.11b: DSSS-DBPSK, DQPSK, CCK 802.11g/n: OFDM-BPSK, QPSK, 16QAM, 64QAM
Rated Input Voltage:	DC 12V or DC 48V from PoE
Serial Number:	CR220944645-RF-S1
EUT Received Date:	2022.10.09
EUT Received Status:	Good

Operation Frequency Detail: For 802.11b/g/n ht20:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437	/	/

Per section 15.31(m), the below frequencies were performed the test as below:

Test Channel	Frequency (MHz)
Lowest	2412
Middle	2437
Highest	2462

For 802.11n ht40:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
3	2422	7	2442
4	2427	8	2447
5	2432	9	2452
6	2437	/	/

Per section 15.31(m), the below frequencies were performed the test as below:

Test Channel	Frequency (MHz)
Lowest	2422
Middle	2437
Highest	2452

Antenna Information Detail▲:**For 802.11b/g/n:**

Antenna Manufacturer	Antenna Type	input impedance (Ohm)	Frequency Range	Antenna Gain
Word Easy Electronics Co.,Ltd.	FPC	50	2.4~2.5GHz	1.7 dBi

The Method of §15.203 Compliance:

- Antenna must be permanently attached to the unit.
 Antenna must use a unique type of connector to attach to the EUT.
 Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

Accessory Information:

Accessory Description	Manufacturer	Model	Parameters
/	/	/	/

1.2 Description of Test Configuration

1.2.1 EUT Operation Condition:

For 802.11b/g/n:

EUT Operation Mode:	The system was configured for testing in Engineering Mode, which was provided by the manufacturer.			
Equipment Modifications:	No			
EUT Exercise Software:	SecureCRT			
The software was provided by manufacturer. The maximum power was configured as below, that was provided by the manufacturer ▲:				
Test Modes	Data Rate	Power Level Setting		
		Lowest Channel	Middle Channel	Highest Channel
802.11b	1Mbps	Default	Default	Default
802.11g	6Mbps	28	Default	Default
802.11n ht20	MCS0	Default	Default	Default
802.11n ht40	MCS0	Default	Default	Default
The above are the worst-case data rates, which are determined for each mode based upon investigations by measuring the average power and PSD across all data rates, bandwidths, and modulations.				

1.2.2 Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
ZIONCOM	Router	MB-R210-00	EMZBWR21103001
AKUVOX	Indoor Monitor	C313W	E5ZFM85103024
TaoTimeClub	Load	100W40RJ	100W40RJ
TP-link	PoE Adapter	TL-SF1005P	1167604001685
ORIENTAL HERO ELE.FTY	Adapter	OH-101511201000U3- UL	E230964


1.2.3 Support Cable List and Details

Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
Adapter cable	No	No	1	EUT	Adapter
RJ45 cable	Yes	No	10	EUT	Router
Signal Cable	Yes	No	10	EUT	Indoor Monitor
RJ45 cable	Yes	No	2	EUT	POE
Load cable	No	No	1	EUT	Load


1.2.4 Block Diagram of Test Setup

AC line conducted emissions:


Adapter power mode:




PoE power mode:




Spurious Emissions:
Below 1GHz:
Adapter power mode:



PoE power mode:



Above 1GHz:



1.3 Measurement Uncertainty

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.61dB
Power Spectral Density, conducted	±0.61 dB
Unwanted Emissions, radiated	30M~200MHz: 4.15 dB,200M~1GHz: 5.61 dB,1G~6GHz: 5.14 dB, 6G~18GHz: 5.93 dB,18G~26.5G:5.47 dB,26.5G~40G:5.63 dB
Unwanted Emissions, conducted	±1.26 dB
Temperature	±1 °C
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%
AC Power Lines Conducted Emission	2.8 dB (150 kHz to 30 MHz)

2. SUMMARY OF TEST RESULTS

Standard(s) Section	Test Items	Result
§15.207(a)	AC line conducted emissions	Compliant
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliant
§15.247 (a)(2)	6 dB Bandwidth	Compliant
§15.247(b)(3)	Maximum Conducted Output Power	Compliant
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliant
§15.247(e)	Power Spectral Density	Compliant
§15.203	Antenna Requirement	Compliant
§15.247 (i) & §1.1307 & §2.1091	RF Exposure Evaluation	Compliant

3. REQUIREMENTS AND TEST PROCEDURES

3.1 AC Line Conducted Emissions

3.1.1 Applicable Standard

FCC§15.207(a).

(a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

(b) The limit shown in paragraph (a) of this section shall not apply to carrier current systems operating as intentional radiators on frequencies below 30 MHz. In lieu thereof, these carrier current systems shall be subject to the following standards:


(1) For carrier current system containing their fundamental emission within the frequency band 535-1705 kHz and intended to be received using a standard AM broadcast receiver: no limit on conducted emissions.

(2) For all other carrier current systems: 1000 μ V within the frequency band 535-1705 kHz, as measured using a 50 μ H/50 ohms LISN.

(3) Carrier current systems operating below 30 MHz are also subject to the radiated emission limits in §15.205, §15.209, §15.221, §15.223, or §15.227, as appropriate.

(c) Measurements to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines. Devices that include, or make provisions for, the use of battery chargers which permit operating while charging, AC adapters or battery eliminators or that connect to the AC power lines indirectly, obtaining their power through another device which is connected to the AC power lines, shall be tested to demonstrate compliance with the conducted limits.

3.1.2 EUT Setup



- Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter or EUT was connected to the main LISN with a 120 V/60 Hz AC power source.

3.1.3 EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

3.1.4 Test Procedure

The frequency and amplitude of the six highest ac power-line conducted emissions relative to the limit, measured over all the current-carrying conductors of the EUT power cords, and the operating frequency or frequency to which the EUT is tuned (if appropriate), should be reported, unless such emissions are more than 20 dB below the limit. AC power-line conducted emissions measurements are to be separately carried out only on each of the phase (“hot”) line(s) and (if used) on the neutral line(s), but not on the ground [protective earth] line(s). If less than six emission frequencies are within 20 dB of the limit, then the noise level of the measuring instrument at representative frequencies should be reported. The specific conductor of the power-line cord for each of the reported emissions should be identified. Measure the six highest emissions with respect to the limit on each current-carrying conductor of each power cord associated with the EUT (but not the power cords of associated or peripheral equipment that are part of the test configuration). Then, report the six highest emissions with respect to the limit from among all the measurements identifying the frequency and specific current-carrying conductor identified with the emission. The six highest emissions should be reported for each of the current-carrying conductors, or the six highest emissions may be reported over all the current-carrying conductors.

3.1.5 Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result = Reading + Factor

Factor = attenuation caused by cable loss + voltage division factor of AMN

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result

3.2 Radiation Spurious Emissions


3.2.1 Applicable Standard

FCC §15.247 (d);


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

3.2.2 EUT Setup

Below 1GHz:



Above 1GHz:



The radiated emissions were performed in the 3 meters distance, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

3.2.3 EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

30-1000MHz:

Measurement	RBW	Video B/W	IF B/W
QP	120 kHz	300 kHz	120kHz

1GHz- 25GHz:

Measurement	Duty cycle	RBW	Video B/W
PK	Any	1MHz	3 MHz
Ave.	>98%	1MHz	10 Hz
	<98%	1MHz	1/T

Note: T is minimum transmission duration

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

3.2.4 Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

3.2.5 Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result = Reading + Factor

Factor = Antenna Factor + Cable Loss- Amplifier Gain

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result


3.3 6 dB Emission Bandwidth:

3.3.1 Applicable Standard

FCC §15.247 (a)(2)

Systems using digital modulation techniques may operate in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

3.3.2 EUT Setup




3.3.3 Test Procedure

According to ANSI C63.10-2013 Section 11.8

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

3.4 99% Occupied Bandwidth:

3.4.1 EUT Setup



3.4.2 Test Procedure

According to ANSI C63.10-2013 Section 6.9.3

The occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5% of the total mean power of the given emission. The following procedure shall be used for measuring 99% power bandwidth:

- a) The instrument center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be between 1.5 times and 5.0 times the OBW.
- b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW, and VBW shall be approximately three times the RBW, unless otherwise specified by the applicable requirement.
- c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (OBW/RBW)]$ below the reference level. Specific guidance is given in 4.1.5.2.
- d) Step a) through step c) might require iteration to adjust within the specified range.
- e) Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
- f) Use the 99% power bandwidth function of the instrument (if available) and report the measured bandwidth.
- g) If the instrument does not have a 99% power bandwidth function, then the trace data points are recovered and directly summed in linear power terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5% of the total is reached; that frequency is recorded as the upper frequency. The 99% power bandwidth is the difference between these two frequencies.
- h) The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).


3.5 Maximum conducted output power:

3.5.1 Applicable Standard

FCC §15.247 (b)(3)

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

3.5.2 EUT Setup



3.5.3 Test Procedure

According to ANSI C63.10-2013 Section 11.9.2.3.2

Method AVGPM-G is a measurement using a gated RF average power meter.

Alternatively, measurements may be performed using a wideband gated RF power meter provided that the gate parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Because the measurement is made only during the ON time of the transmitter, no duty cycle correction factor is required.


3.6 Maximum power spectral density:

3.6.1 Applicable Standard

FCC §15.247 (e)

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

3.6.2 EUT Setup



3.6.3 Test Procedure

When Duty cycle $\geq 98\%$

Method AVGPS-1 uses trace averaging with EUT transmitting at full power throughout each sweep.

The following procedure may be used when the maximum (average) conducted output power was used to determine compliance to the fundamental output power limit. This is the baseline method for determining the maximum (average) conducted PSD level. If the instrument has a power averaging (rms) detector, then it must be used; otherwise, use the sample detector. The EUT must be configured to transmit continuously ($D \geq 98\%$), or else sweep triggering/signal gating must be implemented to ensure that measurements are made only when the EUT is transmitting at its maximum power control level (no transmitter OFF time to be considered):

- a) Set instrument center frequency to DTS channel center frequency.
- b) Set span to at least 1.5 times the OBW.
- c) Set RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- d) Set VBW $\geq [3 \times \text{RBW}]$.
- e) Detector = power averaging (rms) or sample detector (when rms not available).
- f) Ensure that the number of measurement points in the sweep $\geq [2 \times \text{span} / \text{RBW}]$.
- g) Sweep time = auto couple.
- h) Employ trace averaging (rms) mode over a minimum of 100 traces.
- i) Use the peak marker function to determine the maximum amplitude level.
- j) If the measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat (note that this may require zooming in on the emission of interest and reducing the span to meet the minimum measurement point requirement as the RBW is reduced).

When Duty cycle <98%

According to ANSI C63.10-2013 Section 11.10.7

Method AVGPS-3 uses rms detection across ON and OFF times of the EUT with max hold.

The following procedure is applicable when the EUT cannot be configured to transmit continuously (i.e., $D < 98\%$), when sweep triggering/signal gating cannot be used to measure only when the EUT is transmitting at its maximum power control level, and when the transmission duty cycle is not constant (i.e., duty cycle variations exceed $\pm 2\%$):

- a) Set the instrument span to a minimum of 1.5 times the OBW.
- b) Set sweep trigger to "free run."
- c) Set RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- d) Set VBW $\geq [3 \times \text{RBW}]$.
- e) Number of points in sweep $\geq [2 \times \text{span} / \text{RBW}]$. (This ensures that bin-to-bin spacing is $\leq \text{RBW} / 2$, so that narrowband signals are not lost between frequency bins.)
- f) Sweep time $\leq (\text{number of points in sweep}) \times T$, where T is defined in 11.6.
- g) Detector = RMS (power averaging).
- h) Trace mode = max hold.
- i) Allow max hold to run for at least 60 s or longer as needed to allow the trace to stabilize.
- j) Use the peak marker function to determine the maximum PSD level.
- k) If the measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat (note that this may require zooming in on the emission of interest and reducing the span to meet the minimum measurement point requirement as the RBW is reduced).


3.7 100 kHz Bandwidth of Frequency Band Edge:

3.7.1 Applicable Standard

FCC §15.247 (d);

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

3.7.2 EUT Setup



3.7.3 Test Procedure


According to ANSI C63.10-2013 Section 11.11

- a) Set the center frequency and span to encompass frequency range to be measured.
- b) Set the RBW = 100 kHz.
- c) Set the VBW $\geq [3 \times \text{RBW}]$.
- d) Detector = peak.
- e) Sweep time = auto couple.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11. Report the three highest emissions relative to the limit.

3.8 Duty Cycle:

3.8.1 EUT Setup



3.8.2 Test Procedure

According to ANSI C63.10-2013 Section 11.6

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the ON and OFF times of the transmitted signal:

- 1) Set the center frequency of the instrument to the center frequency of the transmission.
- 2) Set $RBW \geq OBW$ if possible; otherwise, set RBW to the largest available value.
- 3) Set $VBW \geq RBW$. Set detector = peak or average.
- 4) The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring the duty cycle shall not be used if $T \leq 16.7 \mu s$.)

3.9 Antenna Requirement

3.9.1 Applicable Standard

FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §§15.211, 15.213, 15.217, 15.219, 15.221, or §15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

3.9.2 Judgment

Compliant. Please refer to the Antenna Information detail in Section 1.

4. Test DATA AND RESULTS

4.1 AC Line Conducted Emissions

Serial Number:	CR220944645-RF-S1	Test Date:	2022/10/18
Test Site:	CE	Test Mode:	Transmitting (802.11b Middle channel was the worst)
Tester:	Vic Du	Test Result:	Pass

Environmental Conditions:


Temperature: (°C)	25.2	Relative Humidity: (%)	50	ATM Pressure: (kPa)	100.5
----------------------	------	---------------------------	----	------------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	LISN	ENV216	101134	2022/04/01	2023/03/31
R&S	EMI Test Receiver	ESR3	102726	2022/07/15	2023/07/14
MICRO-COAX	Coaxial Cable	UTIFLEX	C-0200-01	2022/08/07	2023/08/06
Audix	Test Software	E3	190306 (V9)	N/A	N/A


* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Adapter Power Mode:



Test Mode: Transmitting(Adapter)
 Port: neutral
 Note:

Date: 2022-10-18




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.152	12.26	9.61	21.87	55.90	34.03	Average
2	0.152	24.22	9.61	33.83	65.90	32.07	QP
3	0.300	25.64	9.61	35.25	50.24	14.99	Average
4	0.300	32.38	9.61	41.99	60.24	18.25	QP
5	0.408	15.02	9.61	24.63	47.69	23.06	Average
6	0.408	21.86	9.61	31.47	57.69	26.22	QP
7	0.619	8.60	9.62	18.22	46.00	27.78	Average
8	0.619	16.46	9.62	26.08	56.00	29.92	QP
9	4.075	11.51	9.65	21.16	46.00	24.84	Average
10	4.075	19.77	9.65	29.42	56.00	26.58	QP
11	7.755	12.00	9.67	21.67	50.00	28.33	Average
12	7.755	18.07	9.67	27.74	60.00	32.26	QP

PoE Power Mode:

Test Mode: Transmitting(POE)
 Port: Line
 Note:


Date: 2022-10-18



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.151	13.92	9.61	23.53	55.93	32.40	Average
2	0.151	35.10	9.61	44.71	65.93	21.22	QP
3	0.649	21.72	9.62	31.34	46.00	14.66	Average
4	0.649	31.41	9.62	41.03	56.00	14.97	QP
5	1.194	9.85	9.62	19.47	46.00	26.53	Average
6	1.194	20.53	9.62	30.15	56.00	25.85	QP
7	2.277	12.74	9.64	22.38	46.00	23.62	Average
8	2.277	23.48	9.64	33.12	56.00	22.88	QP
9	18.869	16.51	9.77	26.28	50.00	23.72	Average
10	18.869	24.25	9.77	34.02	60.00	25.98	QP
11	24.969	16.75	9.81	26.56	50.00	23.44	Average
12	24.969	23.11	9.81	32.92	60.00	27.08	QP

Test Mode: Transmitting(POE)
 Port: neutral
 Note:

Date: 2022-10-18



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.165	20.35	9.61	29.96	55.22	25.26	Average
2	0.165	36.22	9.61	45.83	65.22	19.39	QP
3	0.195	19.93	9.61	29.54	53.84	24.30	Average
4	0.195	35.21	9.61	44.82	63.84	19.02	QP
5	0.651	21.37	9.62	30.99	46.00	15.01	Average
6	0.651	31.18	9.62	40.80	56.00	15.20	QP
7	1.167	8.50	9.62	18.12	46.00	27.88	Average
8	1.167	19.35	9.62	28.97	56.00	27.03	QP
9	2.480	13.25	9.64	22.89	46.00	23.11	Average
10	2.480	25.22	9.64	34.86	56.00	21.14	QP
11	18.923	16.69	9.69	26.38	50.00	23.62	Average
12	18.923	24.03	9.69	33.72	60.00	26.28	QP

4.2 Radiation Spurious Emissions

Serial Number:	CR220944645-RF-S1	Test Date:	2022/10/19 (Above 1GHz) 2022/10/19~2023/2/7 (Below 1GHz)
Test Site:	966-1/966-2	Test Mode:	Transmitting
Tester:	Carl Xue, Mack Huang	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	23.4-26.4	Relative Humidity: (%)	46-63	ATM Pressure: (kPa)	101.2-101.5
----------------------	-----------	---------------------------	-------	------------------------	-------------

Test Equipment List and Details:


Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Sunol Sciences	Antenna	JB6	A082520-5	2020/10/19	2023/10/18
R&S	EMI Test Receiver	ESR3	102724	2022/07/15	2023/07/14
TIMES MICROWAVE	Coaxial Cable	LMR-600-UltraFlex	C-0470-02	2022/07/17	2023/07/16
TIMES MICROWAVE	Coaxial Cable	LMR-600-UltraFlex	C-0780-01	2022/07/17	2023/07/16
Sonoma	Amplifier	310N	186165	2022/07/17	2023/07/16
Audix	Test Software	E3	201021 (V9)	N/A	N/A
ETS-Lindgren	Horn Antenna	3115	9912-5985	2020/10/13	2023/10/12
R&S	Spectrum Analyzer	FSV40	101591	2022/07/15	2023/07/14
MICRO-COAX	Coaxial Cable	UFA210A-1-1200-70U300	217423-008	2022/08/07	2023/08/06
MICRO-COAX	Coaxial Cable	UFA210A-1-2362-300300	235780-001	2022/08/07	2023/08/06
Mini	Pre-amplifier	ZVA-183-S+	5969001149	2021/11/10	2022/11/09
PASTERNAK	Horn Antenna	PE9852/2F-20	112002	2021/02/05	2024/02/04
AH	Preamplifier	PAM-1840VH	190	2021/11/19	2022/11/18
MICRO-COAX	Coaxial Cable	UFB142A-1-2362-200200	235772-001	2022/08/07	2023/08/06
E-Microwave	Band Rejection Filter	2400-2483.5MHz	OE01902424	2022/08/07	2023/08/06
Mini Circuits	High Pass Filter	VHF-6010+	31119	2022/08/07	2023/08/06

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).


Test Data:

Please refer to the below table and plots.

1) 30MHz-1GHz(802.11b Low channel was the worst)
 Adapter Power Mode:



Test Mode: Transmitting
 Polarization: vertical
 Note:




Date: 2022-10-19

No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	30.853	36.57	-4.26	32.31	40.00	7.69	Peak
2	35.624	35.37	-7.96	27.41	40.00	12.59	Peak
3	47.994	42.65	-16.03	26.62	40.00	13.38	Peak
4	57.392	46.23	-17.33	28.90	40.00	11.10	Peak
5	400.432	39.81	-8.74	31.07	46.00	14.93	Peak
6	601.427	36.18	-5.03	31.15	46.00	14.85	Peak

PoE Power Mode:

Test Mode: Transmitting
 Polarization: horizontal
 Note:


Date: 2023-02-07



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	350.477	37.62	-10.03	27.59	46.00	18.41	Peak
2	400.432	40.83	-8.74	32.09	46.00	13.91	Peak
3	455.906	39.43	-6.76	32.67	46.00	13.33	Peak
4	601.427	35.73	-5.03	30.70	46.00	15.30	Peak
5	701.761	35.76	-3.52	32.24	46.00	13.76	Peak
6	793.396	34.91	-2.28	32.63	46.00	13.37	Peak

Test Mode: Transmitting
 Polarization: vertical
 Note:

Date: 2023-02-07



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	31.620	37.35	-4.83	32.52	40.00	7.48	Peak
2	38.752	38.10	-10.32	27.78	40.00	12.22	Peak
3	350.477	40.19	-10.03	30.16	46.00	15.84	Peak
4	408.946	42.66	-8.42	34.24	46.00	11.76	Peak
5	451.135	41.18	-6.91	34.27	46.00	11.73	Peak
6	601.427	40.10	-5.03	35.07	46.00	10.93	Peak

2) 1-25GHz(Adapter Power Mode was worst):
802.11b Mode:

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
	Reading (dB μ V)	Detector					
Low Channel: 2412 MHz							
2412.000	72.42	PK	H	31.53	103.95	N/A	N/A
2412.000	69.76	AV	H	31.53	101.29	N/A	N/A
2412.000	66.11	PK	V	31.53	97.64	N/A	N/A
2412.000	63.34	AV	V	31.53	94.87	N/A	N/A
2390.000	27.20	PK	H	31.46	58.66	74.00	15.34
2390.000	14.45	AV	H	31.46	45.91	54.00	8.09
4824.000	34.56	PK	H	10.94	45.50	74.00	28.50
4824.000	22.14	AV	H	10.94	33.08	54.00	20.92
7236.000	33.75	PK	H	14.44	48.19	74.00	25.81
7236.000	21.46	AV	H	14.44	35.90	54.00	18.10
Middle Channel: 2437 MHz							
2437.000	73.20	PK	H	31.60	104.80	N/A	N/A
2437.000	70.49	AV	H	31.60	102.09	N/A	N/A
2437.000	66.46	PK	V	31.60	98.06	N/A	N/A
2437.000	63.82	AV	V	31.60	95.42	N/A	N/A
4874.000	34.12	PK	H	11.05	45.17	74.00	28.83
4874.000	22.06	AV	H	11.05	33.11	54.00	20.89
7311.000	33.16	PK	H	14.80	47.96	74.00	26.04
7311.000	21.01	AV	H	14.80	35.81	54.00	18.19
High Channel: 2462MHz							
2462.000	75.33	PK	H	31.63	106.96	N/A	N/A
2462.000	72.62	AV	H	31.63	104.25	N/A	N/A
2462.000	68.59	PK	V	31.63	100.22	N/A	N/A
2462.000	65.95	AV	V	31.63	97.58	N/A	N/A
2483.500	29.68	PK	H	31.64	61.32	74.00	12.68
2483.500	18.08	AV	H	31.64	49.72	54.00	4.28
4924.000	32.86	PK	H	11.18	44.04	74.00	29.96
4924.000	20.14	AV	H	11.18	31.32	54.00	22.68
7386.000	35.45	PK	H	14.89	50.34	74.00	23.66
7386.000	22.34	AV	H	14.89	37.23	54.00	16.77

802.11g Mode:

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
	Reading (dB μ V)	Detector					
Low Channel: 2412 MHz							
2412.000	68.58	PK	H	31.53	100.11	N/A	N/A
2412.000	58.06	AV	H	31.53	89.59	N/A	N/A
2412.000	59.68	PK	V	31.53	91.21	N/A	N/A
2412.000	49.88	AV	V	31.53	81.41	N/A	N/A
2390.000	28.52	PK	H	31.46	59.98	74.00	14.02
2390.000	14.85	AV	H	31.46	46.31	54.00	7.69
4824.000	31.86	PK	H	10.94	42.80	74.00	31.20
4824.000	18.65	AV	H	10.94	29.59	54.00	24.41
7236.000	33.64	PK	H	14.44	48.08	74.00	25.92
7236.000	20.37	AV	H	14.44	34.81	54.00	19.19
Middle Channel: 2437 MHz							
2437.000	69.47	PK	H	31.60	101.07	N/A	N/A
2437.000	59.84	AV	H	31.60	91.44	N/A	N/A
2437.000	49.74	PK	V	31.60	81.34	N/A	N/A
2437.000	39.92	AV	V	31.60	71.52	N/A	N/A
4874.000	32.56	PK	H	11.05	43.61	74.00	30.39
4874.000	19.68	AV	H	11.05	30.73	54.00	23.27
7311.000	34.26	PK	H	14.80	49.06	74.00	24.94
7311.000	21.15	AV	H	14.80	35.95	54.00	18.05
High Channel: 2462MHz							
2462.000	69.84	PK	H	31.63	101.47	N/A	N/A
2462.000	60.11	AV	H	31.63	91.74	N/A	N/A
2462.000	50.12	PK	V	31.63	81.75	N/A	N/A
2462.000	40.29	AV	V	31.63	71.92	N/A	N/A
2483.500	30.29	PK	H	31.64	61.93	74.00	12.07
2483.500	16.15	AV	H	31.64	47.79	54.00	6.21
4924.000	32.67	PK	H	11.18	43.85	74.00	30.15
4924.000	19.86	AV	H	11.18	31.04	54.00	22.96
7386.000	33.59	PK	H	14.89	48.48	74.00	25.52
7386.000	20.47	AV	H	14.89	35.36	54.00	18.64


802.11n ht20 Mode:

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
	Reading (dB μ V)	Detector					
Low Channel: 2412 MHz							
2412.000	68.95	PK	H	31.53	100.48	N/A	N/A
2412.000	58.43	AV	H	31.53	89.96	N/A	N/A
2412.000	60.05	PK	V	31.53	91.58	N/A	N/A
2412.000	50.25	AV	V	31.53	81.78	N/A	N/A
2390.000	28.89	PK	H	31.46	60.35	74.00	13.65
2390.000	15.22	AV	H	31.46	46.68	54.00	7.32
4824.000	32.23	PK	H	10.94	43.17	74.00	30.83
4824.000	19.02	AV	H	10.94	29.96	54.00	24.04
7236.000	34.01	PK	H	14.44	48.45	74.00	25.55
7236.000	20.74	AV	H	14.44	35.18	54.00	18.82
Middle Channel: 2437 MHz							
2437.000	69.76	PK	H	31.60	101.36	N/A	N/A
2437.000	60.13	AV	H	31.60	91.73	N/A	N/A
2437.000	50.03	PK	V	31.60	81.63	N/A	N/A
2437.000	40.21	AV	V	31.60	71.81	N/A	N/A
4874.000	32.85	PK	H	11.05	43.90	74.00	30.10
4874.000	19.97	AV	H	11.05	31.02	54.00	22.98
7311.000	33.41	PK	H	14.80	48.21	74.00	25.79
7311.000	20.14	AV	H	14.80	34.94	54.00	19.06
High Channel: 2462MHz							
2462.000	69.61	PK	H	31.63	101.24	N/A	N/A
2462.000	59.98	AV	H	31.63	91.61	N/A	N/A
2462.000	49.88	PK	V	31.63	81.51	N/A	N/A
2462.000	30.06	AV	V	31.63	61.69	N/A	N/A
2483.500	30.06	PK	H	31.64	61.70	74.00	12.30
2483.500	15.92	AV	H	31.64	47.56	54.00	6.44
4924.000	32.44	PK	H	11.18	43.62	74.00	30.38
4924.000	19.63	AV	H	11.18	30.81	54.00	23.19
7386.000	33.36	PK	H	14.89	48.25	74.00	25.75
7386.000	20.24	AV	H	14.89	35.13	54.00	18.87


802.11n ht40 Mode:

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
	Reading (dB μ V)	Detector					
Low Channel: 2422 MHz							
2422.000	67.27	PK	H	31.56	98.83	N/A	N/A
2422.000	56.75	AV	H	31.56	88.31	N/A	N/A
2422.000	58.37	PK	V	31.56	89.93	N/A	N/A
2422.000	48.57	AV	V	31.56	80.13	N/A	N/A
2390.000	28.55	PK	H	31.46	60.01	74.00	13.99
2390.000	14.88	AV	H	31.46	46.34	54.00	7.66
4844.000	31.89	PK	H	10.96	42.85	74.00	31.15
4844.000	18.68	AV	H	10.96	29.64	54.00	24.36
7266.000	33.67	PK	H	14.63	48.30	74.00	25.70
7266.000	20.40	AV	H	14.63	35.03	54.00	18.97
Middle Channel: 2437 MHz							
2437.000	68.73	PK	H	31.60	100.33	N/A	N/A
2437.000	59.10	AV	H	31.60	90.70	N/A	N/A
2437.000	49.00	PK	V	31.60	80.60	N/A	N/A
2437.000	39.18	AV	V	31.60	70.78	N/A	N/A
4874.000	32.28	PK	H	11.05	43.33	74.00	30.67
4874.000	19.40	AV	H	11.05	30.45	54.00	23.55
7311.000	32.84	PK	H	14.80	47.64	74.00	26.36
7311.000	19.57	AV	H	14.80	34.37	54.00	19.63
High Channel: 2452MHz							
2452.000	68.48	PK	H	31.63	100.11	N/A	N/A
2452.000	58.85	AV	H	31.63	90.48	N/A	N/A
2452.000	48.75	PK	V	31.63	80.38	N/A	N/A
2452.000	38.93	AV	V	31.63	70.56	N/A	N/A
2483.500	28.93	PK	H	31.64	60.57	74.00	13.43
2483.500	14.79	AV	H	31.64	46.43	54.00	7.57
4904.000	31.71	PK	H	11.14	42.85	74.00	31.15
4904.000	18.90	AV	H	11.14	30.04	54.00	23.96
7356.000	32.63	PK	H	14.80	47.43	74.00	26.57
7356.000	19.51	AV	H	14.80	34.31	54.00	19.69

Worst Test plots(802.11b High channel was the worst)



Vertical



4.3 6 dB Emission Bandwidth:

Serial Number:	CR220944645-RF-S1	Test Date:	2022/11/08
Test Site:	RF	Test Mode:	Transmitting
Tester:	Claire Liu	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	24.6	Relative Humidity: (%)	52	ATM Pressure: (kPa)	101.1
----------------------	------	------------------------------	----	------------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU26	200256	2022/07/15	2023/07/14
zhuoxiang	Coaxial Cable	SMA-178	211002	Each time	N/A

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

Test Modes	Test Frequency (MHz)	6 dB Bandwidth (MHz)	Limit (MHz)
802.11b	2412	10.000	0.5
	2437	10.115	0.5
	2462	10.000	0.5
802.11g	2412	16.240	0.5
	2437	16.480	0.5
	2462	16.480	0.5
802.11n ht20	2412	17.760	0.5
	2437	17.440	0.5
	2462	17.680	0.5
802.11n ht40	2422	36.320	0.5
	2437	36.320	0.5
	2452	36.320	0.5

6dB Emission Bandwidth	
802.11b Lowest Channel	<p> * RBW 100 kHz Delta 1 [T1] 0.10 dB * VBW 300 kHz * Att 35 dB 10.00000000 MHz Ref 30 dBm Offset 0.4 dB Marker 1 [T1] 1.67 dBm 2.40704000 GHz D1 7.15 dBm D2 1.15 dBm Center 2.412 GHz 4 MHz/ Span 40 MHz </p> <p>Date: 8.NOV.2022 11:25:54</p>
802.11b Middle Channel	<p> * RBW 100 kHz Marker 1 [T1] 1.94 dBm * VBW 300 kHz 2.431941538 GHz * Att 35 dB 10.00000000 MHz Ref 30 dBm Offset 0.4 dB Delta 1 [T1] 0.12 dB 30.11538615 MHz D1 7.43 dBm D2 1.43 dBm Center 2.437 GHz 4 MHz/ Span 40 MHz </p> <p>Date: 8.NOV.2022 11:31:18</p>
802.11b Highest Channel	<p> * RBW 100 kHz Delta 1 [T1] 0.25 dB * VBW 300 kHz 10.00000000 MHz * Att 35 dB 10.00000000 MHz Ref 30 dBm Offset 0.4 dB Marker 1 [T1] 1.81 dBm 2.45704000 GHz D1 7.49 dBm D2 1.49 dBm Center 2.462 GHz 4 MHz/ Span 40 MHz </p> <p>Date: 8.NOV.2022 11:27:02</p>

6dB Emission Bandwidth	
802.11g Lowest Channel	<p style="text-align: center;">Date: 8.NOV.2022 11:20:50</p>
802.11g Middle Channel	<p style="text-align: center;">Date: 8.NOV.2022 11:24:16</p>
802.11g Highest Channel	<p style="text-align: center;">Date: 8.NOV.2022 11:22:31</p>

6dB Emission Bandwidth	
<p>802.11n ht20 Lowest Channel</p>	<p>Ref 30 dBm * Att 35 dB * RBW 100 kHz Delta 1 [T1] 0.03 dB * VBW 300 kHz 17.760000000 MHz SWT 15 ms</p> <p>30 Offset 0.4 dB Marker 1 [T1] -1.22 dBm 2.403120000 GHz</p> <p>D1 4.04 dBm D2 -1.96 dBm</p> <p>Center 2.412 GHz 4 MHz/ Span 40 MHz</p> <p>Date: 8.NOV.2022 11:16:22</p>
<p>802.11n ht20 Middle Channel</p>	<p>Ref 30 dBm * Att 35 dB * RBW 100 kHz Delta 1 [T1] 1.87 dB * VBW 300 kHz 17.440000000 MHz SWT 15 ms</p> <p>30 Offset 0.4 dB Marker 1 [T1] -1.53 dBm 2.428160000 GHz</p> <p>D1 4.86 dBm D2 -1.14 dBm</p> <p>Center 2.437 GHz 4 MHz/ Span 40 MHz</p> <p>Date: 8.NOV.2022 11:19:09</p>
<p>802.11n ht20 Highest Channel</p>	<p>Ref 30 dBm * Att 35 dB * RBW 100 kHz Delta 1 [T1] 2.67 dB * VBW 300 kHz 17.680000000 MHz SWT 15 ms</p> <p>30 Offset 0.4 dB Marker 1 [T1] -1.54 dBm 2.453120000 GHz</p> <p>D1 4.75 dBm D2 -1.25 dBm</p> <p>Center 2.462 GHz 4 MHz/ Span 40 MHz</p> <p>Date: 8.NOV.2022 11:17:45</p>

6dB Emission Bandwidth	
802.11n ht40 Lowest Channel	<p>Ref: 30 dBm, Att: 35 dB, RBW: 100 kHz, VBW: 300 kHz, SWT: 10 ms, Delta 1 [T1]: 0.44 dB, 36.320000000 MHz</p> <p>Marker 1 [T1]: -1.64 dBm, 2.403920000 GHz</p> <p>D1: 2.26 dBm, D2: -0.74 dBm</p> <p>Center: 2.422 GHz, Span: 80 MHz</p> <p>Date: 8.NOV.2022 11:13:41</p>
802.11n ht40 Middle Channel	<p>Ref: 30 dBm, Att: 35 dB, RBW: 100 kHz, VBW: 300 kHz, SWT: 10 ms, Delta 1 [T1]: 0.12 dB, 36.320000000 MHz</p> <p>Marker 1 [T1]: -0.75 dBm, 2.418920000 GHz</p> <p>D1: 1.81 dBm, D2: -0.19 dBm</p> <p>Center: 2.437 GHz, Span: 80 MHz</p> <p>Date: 8.NOV.2022 11:10:11</p>
802.11n ht40 Highest Channel	<p>Ref: 30 dBm, Att: 35 dB, RBW: 100 kHz, VBW: 300 kHz, SWT: 10 ms, Delta 1 [T1]: 0.32 dB, 36.320000000 MHz</p> <p>Marker 1 [T1]: -1.94 dBm, 2.433920000 GHz</p> <p>D1: 2.56 dBm, D2: -0.44 dBm</p> <p>Center: 2.452 GHz, Span: 80 MHz</p> <p>Date: 8.NOV.2022 11:07:32</p>

4.4 99% Occupied Bandwidth:

Serial Number:	CR220944645-RF-S1	Test Date:	2022/11/08
Test Site:	RF	Test Mode:	Transmitting
Tester:	Claire Liu	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	24.6	Relative Humidity: (%)	52	ATM Pressure: (kPa)	101.1
----------------------	------	------------------------------	----	------------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU26	200256	2022/07/15	2023/07/14
zhuoxiang	Coaxial Cable	SMA-178	211002	Each time	N/A

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

Test Modes	Test Frequency (MHz)	99% Occupied Bandwidth (MHz)
802.11b	2412	15.28
	2437	15.28
	2462	15.36
802.11g	2412	17.6
	2437	17.76
	2462	17.84
802.11n ht20	2412	18.4
	2437	18.56
	2462	18.72
802.11n ht40	2422	37.28
	2437	37.28
	2452	37.44

99% Occupied Bandwidth

<p>802.11b Lowest Channel</p>	<p>Ref 30 dBm *Att 35 dB *RBW 300 kHz Marker 1 [T1] 8.70 dBm *VSW 1 MHz 2.411040000 GHz SWT 2.5 ms</p> <p>30 Offset 0.4 dB 2.280000000 MHz Temp 1 [T1] [OHW] -1.79 dBm 2.404400000 GHz Temp 2 [T1] [OHW] -3.50 dBm 2.419680000 GHz</p> <p>Center 2.412 GHz 4 MHz/ Span 40 MHz</p> <p>Date: 8.NOV.2022 11:26:04</p>
<p>802.11b Middle Channel</p>	<p>Ref 30 dBm *Att 35 dB *RBW 300 kHz Marker 1 [T1] 8.87 dBm *VSW 1 MHz 2.436040000 GHz SWT 2.5 ms</p> <p>30 Offset 0.4 dB 2.280000000 MHz Temp 1 [T1] [OHW] -1.77 dBm 2.429400000 GHz Temp 2 [T1] [OHW] -3.44 dBm 2.444680000 GHz</p> <p>Center 2.437 GHz 4 MHz/ Span 40 MHz</p> <p>Date: 8.NOV.2022 11:28:53</p>
<p>802.11b Highest Channel</p>	<p>Ref 30 dBm *Att 35 dB *RBW 300 kHz Marker 1 [T1] 9.01 dBm *VSW 1 MHz 2.461040000 GHz SWT 2.5 ms</p> <p>30 Offset 0.4 dB 2.360000000 MHz Temp 1 [T1] [OHW] -1.23 dBm 2.454320000 GHz Temp 2 [T1] [OHW] -3.28 dBm 2.469680000 GHz</p> <p>Center 2.462 GHz 4 MHz/ Span 40 MHz</p> <p>Date: 8.NOV.2022 11:27:12</p>

99% Occupied Bandwidth

<p>802.11g Lowest Channel</p>	<p>Ref 30 dBm *Att 35 dB *RBW 300 kHz Marker 1 [T1] 7.17 dBm *VBW 1 MHz 2.416000000 GHz SWT 2.5 ms</p> <p>30 Offset 0.4 dB</p> <p>30 Offset 0.4 dB</p> <p>2.403200000 GHz 7.600000000 MHz</p> <p>Temp 1 [T1] 0dBW -1.99 dBm</p> <p>2.403200000 GHz 2.403200000 GHz</p> <p>Temp 2 [T1] 0dBW -5.60 dBm</p> <p>2.420800000 GHz 2.420800000 GHz</p> <p>Center 2.412 GHz 4 MHz/ Span 40 MHz</p> <p>Date: 8.NOV.2022 11:21:06</p>
<p>802.11g Middle Channel</p>	<p>Ref 30 dBm *Att 35 dB *RBW 300 kHz Marker 1 [T1] 7.40 dBm *VBW 1 MHz 2.435400000 GHz SWT 2.5 ms</p> <p>30 Offset 0.4 dB</p> <p>30 Offset 0.4 dB</p> <p>2.426000000 MHz 2.760000000 MHz</p> <p>Temp 1 [T1] 0dBW -1.18 dBm</p> <p>2.428120000 GHz 2.428120000 GHz</p> <p>Temp 2 [T1] 0dBW -1.99 dBm</p> <p>2.445880000 GHz 2.445880000 GHz</p> <p>Center 2.437 GHz 4 MHz/ Span 40 MHz</p> <p>Date: 8.NOV.2022 11:24:33</p>
<p>802.11g Highest Channel</p>	<p>Ref 30 dBm *Att 35 dB *RBW 300 kHz Marker 1 [T1] 7.50 dBm *VBW 1 MHz 2.466080000 GHz SWT 2.5 ms</p> <p>30 Offset 0.4 dB</p> <p>30 Offset 0.4 dB</p> <p>2.453120000 GHz 2.840000000 MHz</p> <p>Temp 1 [T1] 0dBW -1.81 dBm</p> <p>2.453120000 GHz 2.453120000 GHz</p> <p>Temp 2 [T1] 0dBW -1.18 dBm</p> <p>2.470960000 GHz 2.470960000 GHz</p> <p>Center 2.462 GHz 4 MHz/ Span 40 MHz</p> <p>Date: 8.NOV.2022 11:22:47</p>

99% Occupied Bandwidth

<p>802.11n ht20 Lowest Channel</p>	<p>Ref 30 dBm *Att 35 dB *RBW 300 kHz Marker 1 [T1] 6.91 dBm *VBW 1 MHz 2.417520000 GHz SWT 2.5 ms</p> <p>30 Offset 0.4 dB</p> <p>MAX</p> <p>MIN</p> <p>OBW 2.400000000 MHz Temp 1 [T1] 0dBW -53 dBm</p> <p>2.402880000 GHz Temp 2 [T1] 0dBW -50 dBm</p> <p>2.421280000 GHz</p> <p>Center 2.412 GHz 4 MHz/ Span 40 MHz</p> <p>Date: 8.NOV.2022 11:16:38</p>
<p>802.11n ht20 Middle Channel</p>	<p>Ref 30 dBm *Att 35 dB *RBW 300 kHz Marker 1 [T1] 6.80 dBm *VBW 1 MHz 2.442520000 GHz SWT 2.5 ms</p> <p>30 Offset 0.4 dB</p> <p>MAX</p> <p>MIN</p> <p>OBW 2.456000000 MHz Temp 1 [T1] 0dBW -53 dBm</p> <p>2.427800000 GHz Temp 2 [T1] 0dBW -53 dBm</p> <p>2.446360000 GHz</p> <p>Center 2.437 GHz 4 MHz/ Span 40 MHz</p> <p>Date: 8.NOV.2022 11:19:25</p>
<p>802.11n ht20 Highest Channel</p>	<p>Ref 30 dBm *Att 35 dB *RBW 300 kHz Marker 1 [T1] 7.16 dBm *VBW 1 MHz 2.456240000 GHz SWT 2.5 ms</p> <p>30 Offset 0.4 dB</p> <p>MAX</p> <p>MIN</p> <p>OBW 2.472000000 MHz Temp 1 [T1] 0dBW -52 dBm</p> <p>2.452800000 GHz Temp 2 [T1] 0dBW -51 dBm</p> <p>2.471520000 GHz</p> <p>Center 2.462 GHz 4 MHz/ Span 40 MHz</p> <p>Date: 8.NOV.2022 11:18:02</p>

99% Occupied Bandwidth

<p>802.11n ht40 Lowest Channel</p>	<p>Ref 30 dBm *Att 35 dB *RBW 500 kHz Marker 1 [T1] 6.80 dBm *VBW 2 MHz 2.409680000 GHz SWT 2.5 ms</p> <p>30 Offset 0.4 dB</p> <p>30 Offset 0.4 dB</p> <p>MAX</p> <p>Temp 1 [T1] 0dBW 7.280000000 MHz Temp 2 [T1] 0dBW 2.403440000 GHz Temp 3 [T1] 0dBW 2.440720000 GHz</p> <p>LVL</p> <p>30dB</p> <p>Center 2.422 GHz 8 MHz/ Span 80 MHz</p> <p>Date: 8.NOV.2022 11:12:15</p>
<p>802.11n ht40 Middle Channel</p>	<p>Ref 30 dBm *Att 35 dB *RBW 500 kHz Marker 1 [T1] 7.04 dBm *VBW 2 MHz 2.424840000 GHz SWT 2.5 ms</p> <p>30 Offset 0.4 dB</p> <p>30 Offset 0.4 dB</p> <p>MAX</p> <p>Temp 1 [T1] 0dBW 7.280000000 MHz Temp 2 [T1] 0dBW 2.418440000 GHz Temp 3 [T1] 0dBW 2.455720000 GHz</p> <p>LVL</p> <p>30dB</p> <p>Center 2.437 GHz 8 MHz/ Span 80 MHz</p> <p>Date: 8.NOV.2022 11:10:27</p>
<p>802.11n ht40 Highest Channel</p>	<p>Ref 30 dBm *Att 35 dB *RBW 500 kHz Marker 1 [T1] 7.01 dBm *VBW 2 MHz 2.439840000 GHz SWT 2.5 ms</p> <p>30 Offset 0.4 dB</p> <p>30 Offset 0.4 dB</p> <p>MAX</p> <p>Temp 1 [T1] 0dBW 7.440000000 MHz Temp 2 [T1] 0dBW 2.433440000 GHz Temp 3 [T1] 0dBW 2.470880000 GHz</p> <p>LVL</p> <p>30dB</p> <p>Center 2.452 GHz 8 MHz/ Span 80 MHz</p> <p>Date: 8.NOV.2022 11:07:50</p>

4.5 Maximum Conducted Output Power:

Serial Number:	CR220944645-RF-S1	Test Date:	2022/11/08
Test Site:	RF	Test Mode:	Transmitting
Tester:	Claire Liu	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	24.6	Relative Humidity: (%)	52	ATM Pressure: (kPa)	101.1
----------------------	------	------------------------------	----	------------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
zhuoxiang	Coaxial Cable	SMA-178	211002	Each time	N/A
eastsheep	Coaxial Attenuator	2W-SMA-JK-18G	21060302	Each time	N/A
Agilent	USB Wideband Power Sensor	U2021XA	MY54080015	2022/07/15	2023/07/14

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

For 802.11b/g/n:

Test Modes	Test Frequency (MHz)	Maximum Conducted Average Output Power (dBm)	Limit (dBm)
802.11b	2412	16.82	30
	2437	16.93	30
	2462	17.07	30
802.11g	2412	14.46	30
	2437	14.3	30
	2462	14.66	30
802.11n ht20	2412	13.66	30
	2437	14.24	30
	2462	14.27	30
802.11n ht40	2422	13.05	30
	2437	13.22	30
	2452	13.39	30

4.6 Maximum power spectral density:

Serial Number:	CR220944645-RF-S1	Test Date:	2023/2/25
Test Site:	RF	Test Mode:	Transmitting
Tester:	Claire Liu	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	26.6	Relative Humidity: (%)	62	ATM Pressure: (kPa)	101.8
----------------------	------	------------------------------	----	------------------------	-------

Test Equipment List and Details:




Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU26	200256	2022/07/15	2023/07/14
zhuoxiang	Coaxial Cable	SMA-178	211002	Each time	N/A

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).




Test Data:

Test Modes	Test Frequency (MHz)	Average Power Spectral Density (dBm/10kHz)	Limit (dBm/3kHz)
802.11b	2412	-14.27	8.00
	2437	-14.03	8.00
	2462	-14.37	8.00
802.11g	2412	-9.07	8.00
	2437	-9.43	8.00
	2462	-9.02	8.00
802.11n ht20	2412	-18.22	8.00
	2437	-18.01	8.00
	2462	-18.31	8.00
802.11n ht40	2422	-11.78	8.00
	2437	-11.14	8.00
	2452	-11.90	8.00

Maximum power spectral density


<p>802.11b Lowest Channel</p>	 <p>Ref 20 dBm *Att 25 dB RBW 10 kHz Marker 1 [T1] -14.27 dBm VBW 30 kHz SWT 300 ms 2.412603000 GHz</p> <p>20 Offset 0.4 dB</p> <p>1 RBW AVG</p> <p>Center 2.412 GHz 3 MHz/ Span 30 MHz</p> <p>Date: 25.FEB.2023 15:51:39</p>
<p>802.11b Middle Channel</p>	 <p>Ref 20 dBm *Att 25 dB RBW 10 kHz Marker 1 [T1] -14.03 dBm VBW 30 kHz SWT 300 ms 2.435146000 GHz</p> <p>20 Offset 0.4 dB</p> <p>1 RBW AVG</p> <p>Center 2.437 GHz 3 MHz/ Span 30 MHz</p> <p>Date: 25.FEB.2023 15:53:29</p>
<p>802.11b Highest Channel</p>	 <p>Ref 20 dBm *Att 25 dB RBW 10 kHz Marker 1 [T1] -14.37 dBm VBW 30 kHz SWT 300 ms 2.462732000 GHz</p> <p>20 Offset 0.4 dB</p> <p>1 RBW AVG</p> <p>Center 2.462 GHz 3 MHz/ Span 30 MHz</p> <p>Date: 25.FEB.2023 15:54:54</p>

Maximum power spectral density


<p>802.11g Lowest Channel</p>	 <p>Ref 20 dBm *Att 25 dB *RBW 10 kHz Marker 1 [T1] -9.07 dBm *VBW 30 kHz *SWT 1 s 2.409213000 GHz</p> <p>20 Offset 0.4 dB</p> <p>1. RM MAXH</p> <p>EVL</p> <p>Center 2.412 GHz 3 MHz/ Span 30 MHz</p> <p>Date: 25.FEB.2023 16:07:48</p>
<p>802.11g Middle Channel</p>	 <p>Ref 20 dBm *Att 25 dB *RBW 10 kHz Marker 1 [T1] -9.43 dBm *VBW 30 kHz *SWT 1 s 2.434462000 GHz</p> <p>20 Offset 0.4 dB</p> <p>1. RM MAXH</p> <p>EVL</p> <p>Center 2.437 GHz 3 MHz/ Span 30 MHz</p> <p>Date: 25.FEB.2023 16:09:04</p>
<p>802.11g Highest Channel</p>	 <p>Ref 20 dBm *Att 25 dB *RBW 10 kHz Marker 1 [T1] -9.02 dBm *VBW 30 kHz *SWT 1 s 2.458211000 GHz</p> <p>20 Offset 0.4 dB</p> <p>1. RM MAXH</p> <p>EVL</p> <p>Center 2.462 GHz 3 MHz/ Span 30 MHz</p> <p>Date: 25.FEB.2023 16:10:28</p>

Maximum power spectral density


802.11n ht20
Lowest Channel



802.11n ht20
Middle Channel



802.11n ht20
Highest Channel



Maximum power spectral density

<p>802.11n ht40 Lowest Channel</p>	<p>Ref 20 dBm *Att 25 dB *RBW 10 kHz Marker 1 [T1] -11.78 dBm *VBW 30 kHz *SWT 1 s 2.429458000 GHz</p> <p>20 Offset 0.4 dB</p> <p>1. RM MAXH</p> <p>EVL</p> <p>Center 2.422 GHz 6 MHz/ Span 60 MHz</p> <p>Date: 25.FEB.2023 16:14:07</p>
<p>802.11n ht40 Middle Channel</p>	<p>Ref 20 dBm *Att 25 dB *RBW 10 kHz Marker 1 [T1] -11.14 dBm *VBW 30 kHz *SWT 1 s 2.439712000 GHz</p> <p>20 Offset 0.4 dB</p> <p>1. RM MAXH</p> <p>EVL</p> <p>Center 2.437 GHz 6 MHz/ Span 60 MHz</p> <p>Date: 25.FEB.2023 16:13:10</p>
<p>802.11n ht40 Highest Channel</p>	<p>Ref 20 dBm *Att 25 dB *RBW 10 kHz Marker 1 [T1] -11.90 dBm *VBW 30 kHz *SWT 1 s 2.449438000 GHz</p> <p>20 Offset 0.4 dB</p> <p>1. RM MAXH</p> <p>EVL</p> <p>Center 2.452 GHz 6 MHz/ Span 60 MHz</p> <p>Date: 25.FEB.2023 16:12:20</p>

4.7 100 kHz Bandwidth of Frequency Band Edge:

Serial Number:	CR220944645-RF-S1	Test Date:	2023/2/23~2023/2/24
Test Site:	RF	Test Mode:	Transmitting
Tester:	Claire Liu	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	24.6-26.6	Relative Humidity: (%)	42-62	ATM Pressure: (kPa)	101.2-101.8
----------------------	-----------	------------------------------	-------	------------------------	-------------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU26	200256	2022/07/15	2023/07/14
zhuoxiang	Coaxial Cable	SMA-178	211002	Each time	N/A


** Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*

Test Data:


All the emissions out of the operation band are under the fundamental more than 30dBc, please refer to the following plots:

100 kHz Bandwidth of Frequency Band Edge

802.11b
Lowest Band edge




802.11b
Highest Band edge




100 kHz Bandwidth of Frequency Band Edge

802.11g
Lowest Band edge




802.11g
Highest Band edge




100 kHz Bandwidth of Frequency Band Edge

802.11n ht20
Lowest Band edge



Date: 23.FEB.2023 16:28:06


802.11n ht20
Highest Band edge



Date: 24.FEB.2023 12:29:00


100 kHz Bandwidth of Frequency Band Edge

802.11n ht40
Lowest Band edge



Date: 23.FEB.2023 16:33:42

802.11n ht40
Highest Band edge



Date: 23.FEB.2023 16:36:56

4.8 Duty Cycle:

Serial Number:	CR220944645-RF-S1	Test Date:	2022/11/08
Test Site:	RF	Test Mode:	Transmitting
Tester:	Claire Liu	Test Result:	N/A

Environmental Conditions:

Temperature: (°C)	24.6	Relative Humidity: (%)	52	ATM Pressure: (kPa)	101.1
----------------------	------	------------------------------	----	------------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU26	200256	2022/07/15	2023/07/14
zhuoxiang	Coaxial Cable	SMA-178	211002	Each time	N/A


* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

Test Modes	Ton (ms)	Ton+off (ms)	Duty cycle (%)	1/T (Hz)
802.11b	100	100	100.00	/
802.11g	1.436	/	/	696
802.11n ht20	5.071	5.158	98.31	197
802.11n ht40	2.443	/	/	409
Note: 802.11g/n ht40 is not constant				


Duty Cycle

802.11b




Date: 8.NOV.2022 11:35:33

802.11g




Date: 8.NOV.2022 11:37:03

802.11n ht20



Date: 8.NOV.2022 11:39:48



5. RF EXPOSURE EVALUATION

5.1 Applicable Standard

According to subpart 15.247(i) and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	/	/	f/1500	30
1500–100,000	/	/	1.0	30

f = frequency in MHz;

* = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

5.2 Calculation formula

Prediction of power density at the distance of the applicable MPE limit

$S = PG/4\pi R^2$ = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

For simultaneously transmit system, the calculated power density should comply with:

$$\sum_i \frac{S_i}{S_{Limit,i}} \leq 1$$

5.3 Calculated Data:

Operation Mode	Frequency (MHz)	Antenna Gain (dBi)	Conducted output power including Tune-up Tolerance (dBm)	EIRP (dBm)	Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
WLAN	2412-2462	1.7	18	19.70	20.00	0.0186	1.0
BLE	2402-2480	-2	4	2.0	20.00	0.0003	1.0
NFC	13.56	/	/	-36	20.00	<0.0001	4.88

Note: the Conducted output power including Tune-up Tolerance was declared by manufacturer.
The manufacturer declared NFC EIRP power is -36dBm(=59.2dBμV/m@3m)

The NFC, WLAN and BLE can transmit simultaneously:

$$\sum_i \frac{S_i}{S_{Limit,i}}$$

$$=S_{WLAN}/S_{limit-WLAN} + S_{BLE}/S_{limit-BLE} + S_{NFC}/S_{limit-NFC}$$

$$=0.019$$

$$< 1.0$$

Result: The device meet FCC MPE at 20 cm distance

===== END OF REPORT =====