



TESTING LABORATORY  
CERTIFICATE#4323.01



## FCC PART 15C

## TEST REPORT

For

### AKUVOX (XIAMEN) NETWORKS CO., LTD.

10/F, No.56, Software Park II, Xiamen, China

**FCC ID: 2AHCR-R20B**

<b>Report Type:</b> Original Report	<b>Product Type:</b> Door Phone
<b>Test Engineer:</b>	Stone Zhang <i>Stone Zhang</i>
<b>Report Number:</b>	RXM201126052-00A
<b>Report Date:</b>	2020-12-18
<b>Reviewed By:</b>	Oscar Ye EMC Manager <i>Oscar Ye</i>
<b>Prepared By:</b>	Bay Area Compliance Laboratories Corp. (Kunshan) No.248 Chenghu Road, Kunshan, Jiangsu province, China Tel: +86-0512-86175000 Fax: +86-0512-88934268 <a href="http://www.baclcorp.com.cn">www.baclcorp.com.cn</a>

**TABLE OF CONTENTS**

**GENERAL INFORMATION.....3**

    PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....3

    OBJECTIVE .....3

    RELATED SUBMITTAL(S)/GRANT(S).....3

    TEST METHODOLOGY .....3

    MEASUREMENT UNCERTAINTY .....4

    TEST FACILITY .....4

**SYSTEM TEST CONFIGURATION.....5**

    JUSTIFICATION .....5

    EUT EXERCISE SOFTWARE .....5

    EQUIPMENT MODIFICATIONS .....5

    SUPPORT EQUIPMENT LIST AND DETAILS .....5

    EXTERNAL I/O CABLE.....6

    BLOCK DIAGRAM OF TEST SETUP .....6

**SUMMARY OF TEST RESULTS .....9**

**TEST EQUIPMENT LIST .....10**

**FCC§15.203 - ANTENNA REQUIREMENT.....11**

    APPLICABLE STANDARD .....11

    ANTENNA CONNECTED CONSTRUCTION .....11

**FCC §15.207 (A) – AC LINE CONDUCTED EMISSIONS .....12**

    APPLICABLE STANDARD .....12

    EUT SETUP .....12

    EMI TEST RECEIVER SETUP.....12

    TEST PROCEDURE .....12

    FACTOR & OVER LIMIT CALCULATION.....13

    TEST RESULTS SUMMARY .....13

    TEST DATA .....13

**FCC§15.225, §15.205 & §15.209 - RADIATED EMISSIONS TEST .....18**

    APPLICABLE STANDARD .....18

    EUT SETUP .....18

    EMI TEST RECEIVER SETUP.....19

    CORRECTED AMPLITUDE & MARGIN CALCULATION .....19

    TEST RESULTS SUMMARY .....19

    TEST DATA .....19

**FCC§15.225(E) - FREQUENCY STABILITY.....31**

    APPLICABLE STANDARD .....31

    TEST PROCEDURE .....31

    TEST DATA .....32

**§15.215(C) - 20DB EMISSION BANDWIDTH TESTING .....34**

    REQUIREMENT .....34

    TEST PROCEDURE .....34

    TEST DATA .....34

## GENERAL INFORMATION

### Product Description for Equipment under Test (EUT)

Applicant	AKUVOX (XIAMEN) NETWORKS CO., LTD.
Tested Model	R20BX5
Series Model	R20BX2, R20BX3, R20BX4
Model Difference	Appearance and the number of the buttons
Product Type	Door Phone
Power Supply	DC 12V power by external power supply or DC 48V power by POE
RF Function	RFID
Operating Band/Frequency	125kHz,13.56MHz
Antenna Type	125kHz: Coil antenna 13.56MHz: PCB antenna
*Antenna Gain	0.0 dBi

*Note\*: The antenna gain was provided by manufacturer.*

*All measurement and test data in this report was gathered from production sample serial number: 20201126052. (Assigned by the BACL. The EUT supplied by the applicant was received on 2020-11-26)*

### Objective

This Type approval report is prepared on behalf of *AKUVOX (XIAMEN) NETWORKS CO., LTD.* in accordance with Part 2- Subpart J, and Part 15-Subparts A and C of the Federal Communication Commission's rules.

The objective is to determine the Compliance of the EUT with FCC rules, sec 15.203, 15.205, 15.207, 15.209, 15.225,15.215.

### Related Submittal(s)/Grant(s)

No related submittal/grant.

### Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All radiated and conducted emissions measurement was performed at Bay Area Compliance Lab Corp. (Kunshan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

**Measurement Uncertainty**

Item		Uncertainty
AC Power Lines Conducted Emissions		3.19 dB
RF conducted test with spectrum		0.9dB
Radiated emission	9kHz~30MHz	6.07dB
	30MHz~1GHz	6.11dB
Occupied Bandwidth		0.5kHz
Temperature		1.0°C
Humidity		6%

**Test Facility**

The Test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the No.248 Chenghu Road, Kunshan, Jiangsu province, China.

Bay Area Compliance Laboratories Corp. (Kunshan) Lab is accredited to ISO/IEC 17025 by A2LA (Lab code: 4323.01), the FCC designation No. CN1185 under the FCC KDB 974614 D01 and CAB identifier CN0004 under the ISED requirement. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2014.

## SYSTEM TEST CONFIGURATION

### Justification

The system was configured for testing in a typical mode (as normally used by a typical user).

The device operates in 125 kHz and 13.56 MHz simultaneously for RFID detection

### EUT Exercise Software

The EUT was tested in the engineering mode.

### Equipment Modifications

No modification on the EUT.

### Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
ORIENTAL HERO ELECTRICITY	Adapter	OH-1015E12010003	/
NETGEAR	POE	GS308P	4F217B5000891
HP	Notebook	4441s	2CE3130VWY
MCH	DC Power Supply	MCH-303D-II	14070562
/	IC Card	/	/
TP-LINK	Router	EC26CA652860	1153145002998
AnYong	Load	RXLG	N/A
FuShi	Switch	AR22PR-310B	N/A
Weishi	Entrance guard system	/	/
Schneider Electric	Relay	RXM2LB2BD	/


**External I/O Cable**

Cable Description	Length (m)	From Port	To
Power Cable	1.2	EUT	DC Power Supply
RJ45 Cable	1.5	EUT	POE
Power Cable	1.2	POE	Adapter
RJ45 cable	10.0	EUT	Router
RJ45 cable	1.0	Router	Notebook
Signal Cable	5.0	EUT	Switch
Signal Cable	5.0	EUT	Relay
Signal Cable	5.0	EUT	Entrance Guard
Power supply cable	5.0	EUT	Load


**Block Diagram of Test Setup**

For Conducted Emissions:

*DC 12V power by External power supply:*




*DC 48V power by POE:*




For Radiated Emissions (Below 30 MHz & Above 30 MHz):

*DC 12V power by external power supply:*



DC 48V power by POE:





**SUMMARY OF TEST RESULTS**

<b>FCC Rules</b>	<b>Description of Test</b>	<b>Result</b>
§15.203	Antenna Requirement	Compliant
§15.207 (a)	AC Line Conducted Emissions	Compliant
§15.225 §15.209 §15.205	Radiated Emission Test	Compliant
§15.225(e)	Frequency Stability	Compliant
§15.215(c)	20dB Emission Bandwidth Testing	Compliant

**TEST EQUIPMENT LIST**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
<b>Radiated Emission Test</b>					
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2019-12-14	2020-12-13
Sunol Sciences	Broadband Antenna	JB3	A090413-1	2017-12-26	2020-12-25
Sonoma Instrument	Pre-amplifier	310N	171205	2020-08-15	2021-08-14
ETS-LINDGREN	Loop Antenna	6512	00108100	2019-04-25	2022-04-24
Rohde & Schwarz	Auto test Software	EMC32	100361	/	/
MICRO-COAX	Coaxial Cable	Cable-8	008	2020-08-15	2021-08-14
MICRO-COAX	Coaxial Cable	Cable-9	009	2020-08-15	2021-08-14
MICRO-COAX	Coaxial Cable	Cable-10	010	2020-08-15	2021-08-14
BACL	Temperature & Humidity Chamber	BTH-150	30023	2019-12-20	2020-12-19
<b>Conducted Emission Test</b>					
Rohde & Schwarz	EMI Test Receiver	ESR	1316.3003K03-101746-zn	2020-08-05	2021-08-04
Rohde & Schwarz	LISN	ENV216	101115	2019-12-14	2020-12-13
Audix	Test Software	e3	V9	/	/
Rohde & Schwarz	Pulse limiter	ESH3-Z2	357.8810.52	2020-01-10	2021-01-09
MICRO-COAX	Coaxial Cable	Cable-15	015	2020-08-15	2021-08-14

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

---

## **FCC§15.203 - ANTENNA REQUIREMENT**

---

### **Applicable Standard**

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

### **Antenna Connected Construction**

The EUT has two antennas, one for 13.56MHz, one for 125kHz and antenna gain are 0.0 dBi, which was permanently attached, fulfill the requirement of this section, please refer to the EUT photos.


**Result:** Compliant.

**FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS**

**Applicable Standard**

FCC§15.207(a)

**EUT Setup**



- Note: 1. Support units were connected to second LISN.  
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

**EMI Test Receiver Setup**

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

**Test Procedure**

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

### Factor & Over Limit Calculation

The factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

$$\text{Factor (dB)} = \text{LISN VDF (dB)} + \text{Cable Loss (dB)} + \text{Transient Limiter Attenuation (dB)}$$

The “**Over Limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an over Limit of 7 dB means the emission is 7 dB above the limit. The equation for over limit calculation is as follows:

$$\text{Over Limit (dB)} = \text{Read level (dB}\mu\text{V)} + \text{Factor (dB)} - \text{Limit (dB}\mu\text{V)}$$

### Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207.

### Test Data

#### Environmental Conditions


<b>Temperature:</b>	22.5 °C
<b>Relative Humidity:</b>	53 %
<b>ATM Pressure:</b>	101.5 kPa

*The testing was performed by Stone Zhang on 2020-12-02.*

*EUT operation mode: Transmitting*

DC 12V power by External power supply:


AC 120V/60 Hz, Line



	Freq	Read Level	Read Factor	Limit Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.247	-14.00	19.82	5.82	51.86	-46.04	Average
2	0.247	-0.50	19.82	19.32	61.86	-42.54	QP
3	0.337	-14.80	19.81	5.01	49.27	-44.26	Average
4	0.337	-1.10	19.81	18.71	59.27	-40.56	QP
5	0.461	-15.40	19.75	4.35	46.67	-42.32	Average
6	0.461	-3.20	19.75	16.55	56.67	-40.12	QP
7	0.549	-15.90	19.75	3.85	46.00	-42.15	Average
8	0.549	-3.20	19.75	16.55	56.00	-39.45	QP
9	12.318	-2.31	19.60	17.29	50.00	-32.71	Average
10	12.318	5.89	19.60	25.49	60.00	-34.51	QP
11	23.387	10.60	19.77	30.37	50.00	-19.63	Average
12	23.387	18.20	19.77	37.97	60.00	-22.03	QP

**AC 120V/60 Hz, Neutral**

Date: 2020-12-02




	Read	Limit	Over				
Freq	Level	Factor	Level	Line			
MHz	dBuV	dB	dBuV	dBuV			
1	0.243	-12.90	19.82	6.92	52.00	-45.08	Average
2	0.243	-0.40	19.82	19.42	62.00	-42.58	QP
3	0.332	-10.91	19.82	8.91	49.40	-40.49	Average
4	0.332	-1.21	19.82	18.61	59.40	-40.79	QP
5	0.383	-9.90	19.76	9.86	48.21	-38.35	Average
6	0.383	-2.20	19.76	17.56	58.21	-40.65	QP
7	0.552	-14.20	19.75	5.55	46.00	-40.45	Average
8	0.552	-4.00	19.75	15.75	56.00	-40.25	QP
9	12.318	-3.31	19.60	16.29	50.00	-33.71	Average
10	12.318	8.19	19.60	27.79	60.00	-32.21	QP
11	23.762	8.60	19.75	28.35	50.00	-21.65	Average
12	23.762	15.80	19.75	35.55	60.00	-24.45	QP

**Note:**

- 1) Factor (dB) = LISN VDF (dB) + Cable Loss (dB) + Transient Limiter Attenuation (dB)
- 2) Over Limit (dB) = Read level (dBuV) + Factor (dB) - Limit (dBuV)

DC 48V power by POE:


AC 120V/60 Hz, Line



	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.152	16.60	19.82	36.42	55.91	-19.49	Average
2	0.152	30.70	19.82	50.52	65.91	-15.39	QP
3	0.160	14.90	19.83	34.73	55.47	-20.74	Average
4	0.160	28.50	19.83	48.33	65.47	-17.14	QP
5	0.194	9.60	19.82	29.42	53.84	-24.42	Average
6	0.194	23.60	19.82	43.42	63.84	-20.42	QP
7	0.348	15.00	19.81	34.81	49.00	-14.19	Average
8	0.348	21.40	19.81	41.21	59.00	-17.79	QP
9	18.328	16.90	19.86	36.76	50.00	-13.24	Average
10	18.328	18.50	19.86	38.36	60.00	-21.64	QP
11	23.140	19.09	19.79	38.88	50.00	-11.12	Average
12	23.140	20.09	19.79	39.88	60.00	-20.12	QP



AC 120V/60 Hz, Neutral



	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.154	16.50	19.82	36.32	55.78	-19.46	Average
2	0.154	31.40	19.82	51.22	65.78	-14.56	QP
3	0.182	11.30	19.83	31.13	54.37	-23.24	Average
4	0.182	25.40	19.83	45.23	64.37	-19.14	QP
5	0.230	2.10	19.82	21.92	52.44	-30.52	Average
6	0.230	18.60	19.82	38.42	62.44	-24.02	QP
7	0.356	15.00	19.80	34.80	48.83	-14.03	Average
8	0.356	21.80	19.80	41.60	58.83	-17.23	QP
9	18.328	15.10	19.86	34.96	50.00	-15.04	Average
10	18.328	17.40	19.86	37.26	60.00	-22.74	QP
11	23.140	17.79	19.79	37.58	50.00	-12.42	Average
12	23.140	18.99	19.79	38.78	60.00	-21.22	QP

Note:

- 1) Factor (dB) = LISN VDF (dB) + Cable Loss (dB) + Transient Limiter Attenuation (dB)
- 2) Over Limit (dB) = Read level (dBμV) + Factor (dB) - Limit (dBμV)

**FCC§15.225, §15.205 & §15.209 - RADIATED EMISSIONS TEST**

**Applicable Standard**

As per FCC Part 15.225


(a) The field strength of any emissions within the band 13.553–13.567 MHz shall not exceed 15,848 microvolts/meter at 30 meters.

(b) Within the bands 13.410–13.553 MHz and 13.567–13.710 MHz, the field strength of any emissions shall not exceed 334 microvolts/meter at 30 meters.

(c) Within the bands 13.110–13.410 MHz and 13.710–14.010 MHz the field strength of any emissions shall not exceed 106 microvolts/meter at 30 meters.

(d) The field strength of any emissions appearing outside of the 13.110–14.010 MHz band shall not exceed the general radiated emission limits in §15.209.

**EUT Setup**



The radiated emission tests were performed in the 3-meter chamber a test site, using the setup accordance with the ANSI C63.10. The specification used was the FCC Part Subpart C limits.

The spacing between the peripherals was 10 cm.

## EMI Test Receiver Setup

According to FCC Rules, 47 CFR 15.33, the EUT emissions were investigated up to 1000 MHz.

During the radiated emission test, the EMI test Receiver was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
9 kHz – 150 kHz	200 Hz	1 kHz	/	QP/Average
150 kHz – 30 MHz	9 kHz	30 kHz	/	QP/Average
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP

## Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\begin{aligned} \text{Corrected Factor} &= \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain} \\ \text{Corrected Amplitude} &= \text{Meter Reading} + \text{Corrected Factor} \end{aligned}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

## Test Results Summary

According to the data in the following table, the EUT complied with the FCC Part 15.209, 15.205, 15.225.

## Test Data

### Environmental Conditions

<b>Temperature:</b>	22.8°C
<b>Relative Humidity:</b>	53 %
<b>ATM Pressure:</b>	101.5 kPa


*The testing was performed by Stone Zhang on 2020-12-04.*

*Test mode: Transmitting*

DC 12V power by external power supply:

1) Spurious Emissions (9 kHz~150 kHz):

125 kHz  
Fundamental




Date: 4.DEC.2020 01:34:52

Indicated		PK/QP/Ave.	Corrected Factor (dB/m)	FCC Part 15.225/15.209	
Frequency (kHz)	Corrected Amplitude (dBµV/m) @3m			Limit (dBµV/m) @3m	Margin (dB)
10	54.72	PK	56.36	127.60	72.88
62	51.37	PK	43.97	111.76	60.39
127	83.73	PK	50.58	105.53	21.80
136	37.95	PK	50.71	104.93	66.98

Note: The average emissions which fall into frequencies 9-90 kHz, 110-490 kHz was not recorded, because the peak emissions are below the average limit.

2) Spurious Emissions (150 kHz~30 MHz):




Date: 4.DEC.2020 01:44:52

Frequency (MHz)	Corrected Amplitude (dBμV/m)@3m	Detector PK/QP/Ave.	Corrected Factor (dB/m)	FCC Part 15.225/15.209	
				Limit (dBμV/m)@3m	Margin (dB)
2.111	56.31	PK	13.94	69.54	13.23
13.560	89.01	PK	6.12	124.00	34.99
28.904	30.05	PK	5.11	69.54	39.49

Note:


1. The average emissions which fall into frequencies 9-90 kHz, 110-490 kHz was not recorded, because the peak emissions are below the average limit.

3) Spurious Emissions (13.11MHz~13.41 MHz):




Date: 4.DEC.2020 02:07:25

Spurious Emissions (13.41MHz~13.553 MHz):




Date: 4.DEC.2020 02:14:51

Spurious Emissions (13.567MHz~13.710 MHz):



Date: 4.DEC.2020 02:19:45

Spurious Emissions (13.710MHz~14.010 MHz):




Date: 4.DEC.2020 02:28:57

Frequency (MHz)	Corrected Amplitude (dB $\mu$ V/m)@3m	Detector PK/QP/Ave.	Corrected Factor (dB/m)	FCC Part 15.225/15.209	
				Limit (dB $\mu$ V/m)@3m	Margin (dB)
13.350	67.65	PK	6.13	80.5	12.85
13.551	71.97	PK	6.12	90.5	18.53
13.567	77.23	PK	6.12	90.5	13.27
13.772	68.57	PK	6.08	80.5	11.93




4) Spurious Emissions (30 MHz ~1 GHz):



Frequency (MHz)	Corrected Amplitude	Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	QuasiPeak (dBμV/m)	Height (cm)	Polar (H/V)				
61.606950	20.87	100.0	V	289.0	-17.8	40.00	19.13
82.337100	22.76	100.0	V	79.0	-18.0	40.00	17.24
148.865700	23.00	100.0	V	116.0	-12.3	43.50	20.50
189.712400	18.35	100.0	V	43.0	-12.3	43.50	25.15
255.997100	22.22	100.0	V	149.0	-12.9	46.00	23.78
360.039800	37.29	100.0	H	272.0	-9.6	46.00	8.71

DC 48V power by POE:

1) Spurious Emissions (9 kHz~150 kHz):




Date: 4.DEC.2020 01:31:23

Frequency (kHz)	Corrected Amplitude (dBμV/m)@3m	Detector PK/QP/Ave.	Corrected Factor (dB/m)	FCC Part 15.225/15.209	
				Limit (dBμV/m) @3m	Margin (dB)
10	57.43	PK	56.36	127.60	70.17
62	48.02	PK	43.97	111.76	63.74
127	87.49	PK	50.58	105.53	18.04
136	36.57	PK	50.71	104.93	68.36

Note:

1. The average emissions which fall into frequencies 9-90 kHz, 110-490 kHz was not recorded, because the peak emissions are below the average limit.

2) Spurious Emissions (150 kHz~30 MHz):




Date: 4.DEC.2020 01:47:11

Frequency (MHz)	Corrected Amplitude (dBμV/m)@3m	Detector PK/QP/Ave.	Corrected Factor (dB/m)	FCC Part 15.225/15.209	
				Limit (dBμV/m) @3m	Margin (dB)
2.111	56.64	PK	13.94	69.54	12.90
13.560	89.24	PK	6.12	124.00	34.76
29.190	27.75	PK	5.08	69.54	41.79

Note:


1. The average emissions which fall into frequencies 9-90 kHz, 110-490 kHz was not recorded, because the peak emissions are below the average limit.

3) Spurious Emissions (13.11MHz~13.41 MHz):



Date: 4.DEC.2020 02:08:17

Spurious Emissions (13.41MHz~13.553 MHz):




Date: 4.DEC.2020 02:10:17

Spurious Emissions (13.567MHz~13.710 MHz):



Date: 4.DEC.2020 02:23:26


Spurious Emissions (13.710MHz~14.010 MHz):



Date: 4.DEC.2020 02:26:24

Frequency (MHz)	Corrected Amplitude (dBµV/m)@3m	Detector PK/QP/Ave.	Corrected Factor (dB/m)	FCC Part 15.225/15.209	
				Limit (dBµV/m)@3m	Margin (dB)
13.350	67.65	PK	6.13	80.5	12.85
13.550	70.85	PK	6.12	90.5	19.65
13.567	79.26	PK	6.12	90.5	11.24
13.773	68.83	PK	6.10	80.5	11.67

4) Spurious Emissions (30 MHz ~1 GHz):



Frequency (MHz)	Corrected Amplitude QuasiPeak (dBµV/m)	Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
		Height (cm)	Polar (H/V)				
47.805150	29.07	100.0	V	132.0	-16.5	40.00	10.93
85.244650	28.64	100.0	V	0.0	-17.8	40.00	11.36
107.198350	21.75	100.0	V	132.0	-13.9	43.50	21.75
244.949800	23.92	100.0	H	99.0	-13.3	46.00	22.08
360.036800	42.14	100.0	H	87.0	-9.6	46.00	3.86
504.078500	40.86	100.0	H	267.0	-6.0	46.00	5.14

## **FCC§15.225(e) - FREQUENCY STABILITY**

---

### **Applicable Standard**

The frequency tolerance of the carrier signal shall be maintained within  $\pm 0.01\%$  of the operating frequency over a temperature variation of  $-20$  degrees to  $+50$  degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

### **Test Procedure**

a) Supply the EUT with a nominal ac voltage or install a new or fully charged battery in the EUT. If possible, a dummy load shall be connected to the EUT because an antenna near the metallic walls of an environmental test chamber could affect the output frequency of the EUT. If the EUT is equipped with a permanently attached, adjustable-length antenna, then the EUT shall be placed in the center of the chamber with the antenna adjusted to the shortest length possible. Turn ON the EUT and tune it to one of the number of frequencies shown in 5.6.

b) Couple the unlicensed wireless device output to the measuring instrument by connecting an antenna to the measuring instrument with a suitable length of coaxial cable and placing the measuring antenna near the EUT (e.g., 15 cm away), or by connecting a dummy load to the measuring instrument, through an attenuator if necessary.

NOTE—An instrument that has an adequate level of accuracy as specified by the procuring or regulatory agency is the recommended measuring instrument.

c) Adjust the location of the measurement antenna and the controls on the measurement instrument to obtain a suitable signal level (i.e., a level that will not overload the measurement instrument but is strong enough to allow measurement of the operating or fundamental frequency of the EUT).

d) Turn the EUT OFF and place it inside the environmental temperature chamber. For devices that have oscillator heaters, energize only the heater circuit.

e) Set the temperature control on the chamber to the highest specified in the regulatory requirements for the type of device and allow the oscillator heater and the chamber temperature to stabilize.

f) While maintaining a constant temperature inside the environmental chamber, turn the EUT ON and record the operating frequency at startup, and at 2 minutes, 5 minutes, and 10 minutes after the EUT is energized. Four measurements in total are made.

g) Measure the frequency at each of frequencies specified in 5.6.

h) Switch OFF the EUT but do not switch OFF the oscillator heater.

i) Lower the chamber temperature by not more than  $10$  °C, and allow the temperature inside the chamber to stabilize.

j) Repeat step f) through step i) down to the lowest specified temperature.

**Test Data****Environmental Conditions**

<b>Temperature:</b>	22.8 °C
<b>Relative Humidity:</b>	53 %
<b>ATM Pressure:</b>	101.3 kPa

The testing was performed by Stone Zhang on 2020-12-03.

Test Mode: Transmitting.

Test Result: Compliant

DC 12V power by External power supply:

<b>F<sub>0</sub>=13.56MHz</b>				
<b>Power Supply(V<sub>DC</sub>)</b>	<b>Temperature (°C)</b>	<b>Measured Frequency (MHz)</b>	<b>Frequency Error (%)</b>	<b>Part 15.225 Limit</b>
12.0	-20	13.561309	0.00965	±0.01%
	-10	13.561315	0.00970	±0.01%
	0	13.561329	0.00980	±0.01%
	+10	13.561315	0.00970	±0.01%
	+20	13.561327	0.00979	±0.01%
	+30	13.561318	0.00972	±0.01%
	+40	13.561329	0.00980	±0.01%
	+50	13.561329	0.00980	±0.01%
10.2	+20	13.561318	0.00972	±0.01%
13.8	+20	13.561322	0.00975	±0.01%



Power by POE:

<b>F<sub>0</sub>=13.56MHz</b>				
<b>Power Supply(V<sub>DC</sub>)</b>	<b>Temperature (°C)</b>	<b>Measured Frequency (MHz)</b>	<b>Frequency Error (%)</b>	<b>Part 15.225 Limit</b>
48.0	-20	13.561319	0.00973	±0.01%
	-10	13.561318	0.00972	±0.01%
	0	13.561326	0.00978	±0.01%
	10	13.561317	0.00971	±0.01%
	20	13.561318	0.00972	±0.01%
	30	13.561324	0.00976	±0.01%
	40	13.561318	0.00972	±0.01%
	+50	13.561327	0.00979	±0.01%
40.8	+20	13.561315	0.00970	±0.01%
55.2	+20	13.561324	0.00976	±0.01%

## **§15.215(c) - 20dB EMISSION BANDWIDTH TESTING**

### **Requirement**

Per 15.215 (c) Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated. The requirement to contain the designated bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If a frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.

### **Test Procedure**

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.

### **Test Data**

#### **Environmental Conditions**

<b>Temperature:</b>	22.9 °C
<b>Relative Humidity:</b>	53 %
<b>ATM Pressure:</b>	101.4kPa


*The testing was performed by Stone Zhang on 2020-12-18.*

*Test Mode: Transmitting*

*Test Result: Compliant*


Frequency (MHz)	20 dB Bandwidth (kHz)
0.125	1.462
13.56	1.495

**20 dB Emission Bandwidth-125kHz**



Date: 18.DEC.2020 06:01:44

**20 dB Emission Bandwidth-13.56MHz**



Date: 18.DEC.2020 06:19:24

### **Declarations**

1: BACL is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk '\*'. Customer model name, addresses, names, trademarks etc. are not considered data.

2: Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

3: Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

4: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

5: This report cannot be reproduced except in full, without prior written approval of the Company.

6: This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

**\*\*\*\*\* END OF REPORT \*\*\*\*\***