



R27A Door Phone User Manual

About This Manual

Thank you for choosing Akuvox's products. In user manual, we provide all functions and configurations you want to know about R27A. Please verify the packaging content and network status before setting. This manual applies to firmware 26.0.2.170 or lower version.

Note: The old firmware may be a little different from 27.0.2.170 about some configuration. Please consult your administrator for more information.

FCC Caution:

Any Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions : (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Note : This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.


Content

1. Overview	1
1.1. Product Description	1
1.2. Features	2
1.3. Keypad	4
2. Configuration	5
2.1. Administrator interface	5
2.1.1 System Information	5
2.1.2 Admin Settings	5
2.1.3 System Setting	6
2.2. User interface	7
2.2.1 Public Pin Modif	7
2.2.2 Add User Cards	7
2.2.3 Add Private Pin	7
3. Basic Using	8
3.1. Make a call	8
3.2. Receive a call	8
3.3. Unlock	8
4. Web	9
4.1. Obtain IP address	9
4.2. Login the web	9
4.3. Status	10
4.3.1 Basic	10
4.4. Intercom	11
4.4.1 Basic	11
4.4.2 Advanced	12
4.4.3 Relay	13
4.4.4 Input	15
4.4.5 Live Stream	16
4.4.6 RTSP	17
4.4.7 ONVIF	18
4.4.8 Motion	18
4.4.9 Card Setting(R27A only)	19
4.4.10 Action	20
4.5. Account	22
4.5.1 Basic	22
4.5.2 Advanced	24
4.6. Network	27
4.6.1 Basic	27

4.6.2 Advanced.....	28
4.7. Phone	29
4.7.1 Time/Language	29
4.7.2 Call Feature	30
4.7.3 Voice.....	31
4.7.4 Dial Plan.....	32
4.7.5 Multicast.....	33
4.7.6 Call log.....	34
4.7.7 Door log.....	35
4.8. Upgrade	35
4.8.1 Basic	35
4.8.2 Advanced.....	36
4.9. Security.....	38
4.9.1 Basic	38

1. Overview

1.1. Product Description



R27A

Akuvox R27A is a SIP-compliant, hands-free and video outdoor phone. It can be connected with your Akuvox IP Phone for remote unlock control and monitor. You can operate the indoor handset to communicate with visitors via voice and video, and unlock the door if you wish. Users can also use RF card to unlock the door(R27A only). It's applicable in villas, office and so on.

1.2. Features

➤ **Highlight**

- Vandal resistant body, with a flush button
- Wild-angle camera:120°
- POE(IEEE802.3af, Power-over-Ethernet)
- Two-way audio communication over IP network with Echo cancel feature
- Complies with SIP Standard for easy integration in each SIP PBXes
- Complies with ONVIF standard for easy integration with any network surveillance system

➤ **Physical&Power**

- Body material: all-aluminum
- Camera: 3M pixels, automatic lighting
- Numeric keypad with extra buttons
- Infrared Sensor: Support
- Wiegand port: Support
- RF Card Reader:13.56MHz & 125kHz
- Output Relay: 3 output relays for door opener
- 802.3af Power-Over-Ethernet
- 12V DC connector(if not using POE)
- Water proof&Dust proof: IP65
- Installation: Flush-mounted & Wall-mounted
- Flush-mounted DIM:280x130x68mm
- Wall-mounted DIM:280x130x38mm

➤ **SIP Endpoint**

- SIP v1(RFC2543), SIP v2(RFC3261)
- Audio codecs: G.711a, G.711 μ , G.722, G.729
- Video codecs: H264
- Speech Quality: 7kHz Audio
- Echo Cancellation
- Voice Activation Detection
- Comfort Noise Generator

➤ **Video**

- Resolution: up to 720p
- Maximum image transfer rate:720p-30pfs
- High intensity IR LEDs for picture lighting during dark hours with internal light sensor
- Compatible with 3rd.Party.Video components,e.g.NVRs.

➤ **Door Entry Feature**





- Relay control individually by DTMF tones
- Camera permanently operational
- White Balance: Auto
- Auto-night mode with LED illumination
- Minimum illumination: 0.1LUX

➤ **Network Features**

- 1x10/100Mbps Ethernet Port

- Protocols support: IPv4, HTTP, HTTPS, FTP, SNMP, DNS, NTP, RTSP, RTP, TCP, UDP, ICMP, DHCP, ARP

1.3. Keypad

Key	Description
	Numeric Key
	Manage Center Key
	Dialing Key
	Delete Key

2. Configuration

2.1. Administrator interface

Press *2396# to enter administrator interface. Administrator interface provides some advanced permissions to administrators, including System Information, Admin Settings and System Settings.

2.1.1 System Information

Press 1 to enter System Information to check IP address, Mac address and Firmware version of the door phone.

2.1.2 Admin Settings

2.1.2.1 Admin card setting


Add admin card

Enter Admin Card Setting interface, and press 1 to quick add admin card. When you see “Please Swipe Admin Card...” , please place admin card in the RF card reader area. After the screen shows “An admin card is added +1” , it means adding successfully.


Clean admin card data

Enter Admin Card Setting interface, press 2 to delete the current admin card. When you see “Please Swipe Admin Card...”, and place the added admin card you want to delete in the RF card area. After the screen shows “An admin card is deleted”, it means deleting successfully.

2.1.2.2 Admin Code Setting


Admin code is used to enter administrator interface. The default code is 2396. Enter Admin Code Setting to input 4 digit new admin codes, click Dial key  to save.

2.1.2.3 Service Code Setting

Service Code Setting is used to enter user interface. The default code is 3888. Enter service code setting to input 4 digit new user codes, and click Dial key  to save.

2.1.3 System Setting

2.1.3.1 Network settings

Enter System Setting interface, and press 1 to enter Network setting. Select DHCP mode, door phone will access network automatically. Choose Static mode, users need to setup IP address, subnet mask and default gateway. Press Dial key  when you finish each step.

2.1.3.2 Station No.Settings

Users can setup the device ID to limit the unlock permissions.

(This function can not be used now. Akuvox will perfect it in next version)


2.1.3.3 Restore default

Enter System setting, and press 3 to enter restore interface. After you sure to make the device restore to factory setting, you can swipe your admin card or enter admin code, then the device will restore.

2.2. User interface

Press *3888# to enter user interface. User interface includes Public Pin Modif, Add User Cards and Add Private Pin. These functions can only be accessed by administrator.


2.2.1 Public Pin Modif

The default public Pin is 33333333. Before you modify public Pin, users need to swipe admin card or enter admin code, then you can enter 8 digit new Public Pin, click Dial key  to save.

2.2.2 Add User Cards

User card is used to unlock. Before adding users card, users need to swipe admin card or enter admin code, then you will see “Please Swipe IC Card...”, place user card in the RF card reader . Then the screen will show “Add IC Card +1”, it means adding successfully.

2.2.3 Add Private Pin

Users can also use private pin code to unlock. Before adding private pin , users need to swipe admin card or enter admin code. Then enter a 8 digit private pin, and click Dial key  to save.

3. Basic Using

3.1. Make a call

In the idle interface, press the account or IP address + Dial key  to make a call.

3.2. Receive a call

R27X will auto answer the incoming call by default. If users disable auto answer function, they can press dial key to answer the incoming call.

3.3. Unlock

Unlock by Pin code: Users can unlock the door by using predefined Public Pin or Private Pin. Press # + 8digit Pin Code + # to unlock, then you will hear “The door is now opened”. If users input the wrong Pin code, the screen will show “Incorrect Code”.

Unlock by RF Card(Only R27A): Place the predefined user card in RF card reader to unlock. Under normal conditions, the phone will announce “The door is now opened”. If the card has not been registered, the phone will show “ Unauthorized”.

Unlock by DTMF Code: During the talking, the president can press the predefined DTMF code to remote unlock the door. (Please refer to chapter 4.4.4 about DTMF code setting). Then you will also hear “ The door is now opened”.

4. Web

4.1. Obtain IP address


The Akuvox R27A use DHCP IP by default. Press *2396# to enter Administrator interface. Enter System Information to check the phone IP address.

4.2. Login the web

Open a Web Browser, and enter the corresponding IP address. Then, type the default user name and password as below to log in:

User name: admin

Password: admin



The screenshot shows a web browser window with a login page. The page has a blue header and a yellow border. The main content area is white and contains the following elements:

- A "Login" tab at the top left.
- A "Help" tab at the top right, with "Login Page" text below it.
- Two input fields: "User Name" and "Password".
- A checkbox labeled "Remember Username/Password".
- A "Login" button.

4.3. Status

4.3.1 Basic

Status, including product information, network information and account information, can be viewed from Status -> Basic.

Status	
Product Information	
Model	R27A
MAC Address	0C:11:05:05:63:AE
Firmware Version	27.0.2.170
Hardware Version	27.0.0.0.0.0.0
Network Information	
LAN Port Type	Static IP
LAN Link Status	Connected
LAN IP Address	192.168.35.2
LAN Subnet Mask	255.255.255.0
LAN Gateway	192.168.35.1
LAN DNS1	192.168.35.1
LAN DNS2	8.8.8.8
Account Information	
Account1	1009@192.168.35.250
	Registered
Account2	None@None
	Disabled

Sections	Description
Product Information	To display the device's information such as Model name, MAC address (IP device's physical address), Firmware version and Hardware firmware.
Network Information	To display the device's Networking status(LAN Port),such as Port Type(which could be DHCP/Static/PPPoE), Link Status, IP Address, Subnet Mask, Gateway, Primary DNS server, Secondary DNS server, Primary NTP server and Secondary NTP server(NTP server is used to synchronize time from INTERNET automatically).
Account Information	To display device's Account information and Registration status (account username, registered server's address, Register result).

4.4. Intercom

4.4.1 Basic

Go to the path: Intercom-Basic

Intercom-Basic

Public Key

Key Switch:
 Send Key:
 Key Value: (4-8 digit number)

Display Number

Display Number:

Speed Dial

Key	Number
Speed Dial	<input type="text"/>
Speed Dial2	<input type="text"/>
Speed Dial3	<input type="text"/>
Speed Dial4	<input type="text"/>

Call Event

Action to Execute: FTP Email Http URL
 Http URL:

Web Call

Web Call(Ready):

Max Call Time

Max Call Time: (2~30Minutes)

Max Dial Time

Dial In Time: (30~120Sec)
 Dial Out Time: (30~120Sec)

Sections	Description
Public Key	Public Key is used to unlock. <ul style="list-style-type: none"> ● Key Switch: Users can disable or enable this function. ● Key Value: The default public Key is 33333333. Users can modify by yourself.
Display Number	This function is used to hide or display the number when you operate in the phone. If you select “Disabled”, the phone will show “*” when you dial.
Speed Dial	This Feature is used to call out 4 numbers in the same time. After setup the number you need to call, press manage

	center key to call .
Web Call	To dial out or answer the phone from website.
Call Event	<p>This feature is similar with the Input event. Once users make a call , it will execute the action.</p> <p>It supports 3 types - FTP, Email, and HTTP</p> <p>To setup the FTP and Email in Action interface, the FTP server and Email will receive the capture picture when call out. If you choose HTTP mode, enter the URL format: http://http server IP address/any information (such as, http://192.168.35.48/mac=000).Then you will check this information which captures the network packet.</p>
Max Call Time	To configure the max call time.
Max Dial Time	<ul style="list-style-type: none"> ● Dial in Time: When other phone calls to R27A, if ring tone is over the Dial in Time without answer. The call will be hang up. ● Dial out Time: When R27A call to the other party, if the ringtone is over the Dial out Time without answer. R27A will continue to call to no answer call number in order.

4.4.2 Advanced

Intercom-Advanced

AEC Setting

AEC Level

Photoresistor

Photoresistor Setting - (0~100)

Tamper Alarm

Tamper Alarm ▼

Gravity Sensor Threshold (0~127)

Wiegand

WiegandType ▼

Sections	Description
AEC Level	AEC(Configurable Acoustic and Line Echo Cancelers) is used to adjust the echo effect during the communication. The default value is 700. Increase the level, the echo control is better.

Photoresistor	Photoresistor is used to sense the light intensity that R27A will auto enable infrared LED. Users can adjust the photosensitive value by yourselves.
Tamper Alarm	Enable the Tamper Alarm, if the gravity of R27A changes, the phone will alarm. The Threshold value is smaller, the faster the reaction of device.
Wiegand	Akuvox provides two Wiegand protocol. According to the corresponding wiegand access device to choose the suitable protocol.

4.4.3 Relay

Relay

Private Key(.xml)

Relay

Relay ID	RelayA ▼	RelayB ▼	RelayC ▼
Relay Type	Default state ▼	Default state ▼	Default state ▼
Relay Delay(sec)	3 ▼	3 ▼	1 ▼
DTMF Option	1 Digit DTMF ▼		
DTMF	0 ▼	0 ▼	0 ▼
Multiple DTMF	<input type="text"/>	<input type="text"/>	<input type="text"/>
Relay Status	<input type="text"/>		

Open Relay via HTTP

Switch	Disabled ▼
UserName	<input type="text"/>
Password	<input type="password" value="*****"/>

Sections	Description
Private Key	<ul style="list-style-type: none"> ● Import or Export the Private Key template.
Relay	<p>To configure some settings about unlock</p> <ul style="list-style-type: none"> ● Relay Select: R27A support 3 relays ● Relay Type: Different locks use different relay types, default state or invert state. If you connect the Lock in NO connector, select default state. Otherwise using invert

	<p>state.</p> <ul style="list-style-type: none"> ● Relay Delay(sec): Allows door remain “open” for certain period The range is from 1 to 10 seconds ● DTMF Option: R27A support 1、 2、 3、 4 digits DTMF unlock code. Please select one type and enter the corresponding code. ● DTMF: Setup 1 digit DTMF code for remote unlock ● Multiple DTMF: Setup multiple digits DTMF code for remote unlock. ● Status: the status will be changed by the relay state.
Open Relay via HTTP	<p>Users can use a URL to remote unlock the door.</p> <ul style="list-style-type: none"> ● Switch: Enable this function. Disable by default. ● Username & password: Users can setup the username and password for HTTP unlock. Null by default <p>URL format:http://192.168.1.102/fcgi/do?action=OpenDoor&UserName=&Password=&DoorNum=1</p>

4.4.4 Input

Input

Input A

Input Service: Disabled

Trigger Option: Low

Action to execute: FTP Email Sip Call HTTP

Http URL:

Action Delay: (0~300 Sec)

Open Relay: None

Door Status: DoorA: High

Light Status: LightA: Warning

Input B

InputB Service: Disabled

Trigger Option: Low

Action to execute: FTP Email Sip Call HTTP

Http URL:

Action Delay: (0~300 Sec)

Open Relay: None

Door Status: DoorB: High

Input C

InputC Service: Disabled

Trigger Option: Low

Action to execute: FTP Email Sip Call HTTP

Http URL:

Action Delay: (0~300 Sec)

Open Relay: None

Door Status: DoorC: High

Sections	Description
Input	<p>Input function is used to open the door from inside.</p> <ul style="list-style-type: none"> ● Trigger Option: According to different lock connection to choose different trigger mode. If users connect in normal open contact, select low. If you choose High, please connect in normal close contact. ● Action to execute: Choose one or more ways to receive the action message. ● Http URL: If you tick Http URL, then enter the Http server IP address in the HTTP URL area. When the Input is triggered, it will send Http message. URL format: http://http server IP address/any information (such as http://192.168.35.48/mac=000). Then you will check this

	<p>information which captures the network packet.</p> <ul style="list-style-type: none"> ● Action Delay: Setup the action delay time. After the delay time, the phone will send to the action information in the corresponding way. ● Open Relay: To choose a suitable relay for input connector.
--	---

4.4.5 Live Stream



Sections	Description
Live Stream	To check the real-time video from R27A.

4.4.6 RTSP

RTSP

RTSP Basic

RTSP Server Enabled

RTSP Stream

RTSP Audio Enabled

RTSP Video Enabled

RTSP Video Codec H.264 ▼

H.264 Video Parameters

Video Resolution VGA ▼

Video Framerate 30 fps ▼

Video Bitrate 2048 kbps ▼

MPEG4 Video Parameters

Video Resolution VGA ▼

Video Framerate 30 fps ▼

Video Bitrate 2048 kbps ▼

MJPEG Video Parameters

Video Resolution VGA ▼

Video Framerate 30 fps ▼

Video Quality 90 ▼

Sections	Description
RTSP Basic	To active the RTSP function, then R27A can be monitored. RTSP stream format : rtsp:// device IP/live/ch00_0
RTSP Stream	To enable RTSP video and select the video codec. R27A supports H264 video codec.
H.264 Video Parameters	H264: A video stream compression standard. Different from H263, it provides an approximately identical level of video stream quality but a half bit rate. This type of compression is sometimes called MPEG-4 part 10. To modify the resolution, framerate and bitrate of H264
MPEG4 Video Parameters	MPEG4: It is one of the network video image Compression standard. It supports the maximum Compression ratio 4000:1. It is an important and common video function with great communication application integration ability and less core program space. To modify the resolution, framerate and bitrate of MPEG4
MJPEG Video Parameters	MJPEG: called Motion Joint Photographic Experts Group. It is a video encoding format in which each image is compressed separately by JPEG. MJPEG compression can produce high

	<p>quality video image and has a flexible configuration in video definition and Compressed frames</p> <p>To modify the resolution, framerate and bitrate of MJPEG</p>
--	---

4.4.7 ONVIF

Sections	Description
Basic Setting	<p>To setup the ONVIF function parameters. It is used to connect with the corresponding ONVIF tool.</p> <ul style="list-style-type: none"> ● ONVIF Mode: Two modes - Discoverable and Non-discoverable. Discoverable by default. Only Discoverable mode, then Onvif software can search R27X ● User Name: To modify the user name you need. Admin by default. ● Password: To modify the password you want. Admin by default. <p>Note: User name and password is used for authentication.</p>

4.4.8 Motion

Sections	Description
Motion Detection	<p>Motion detection is used to record the change of the surrounding environment.</p> <ul style="list-style-type: none"> ● Motion Detection Options: Enable to active this

	<p>function.</p> <ul style="list-style-type: none"> Action to execute: Select a suitable way to receive the motion detection information. (FTP,EMAIL,SIP Call setting please refer to chapter4.4.10)
--	---

4.4.9 Card Setting(R27A only)

Sections	Description
Import/Export Card Data	To import or export the card data file. Only support .xml format.
Card Status	<ul style="list-style-type: none"> Normal: Choose Normal mode when reading card. Card Issuing: Choose Card Issuing mode when writing card.
Card Event	<p>This feature is similar with the Input event. Once users use card to unlock, it will execute the action.</p> <p>It supports 3 types - FTP, Email, HTTP</p> <p>To setup the FTP and Email in Action interface, the FTP server and Email will receive the capture picture when unlocking. If you choose HTTP mode, enter the URL format: http://http server IP address/any information (such as http://192.168.35.48/mac=000).Then you will check</p>

	this information which captures the network packet.
Card Setting	<ul style="list-style-type: none"> ● IC Key DoorNum: R27A can support to connect 3 relays Choose one and add the valid card for unlock. ● IC Key Day: To choose the valid day for the card you added. ● IC Key Time: Setup an accurate valid time for the card. ● IC Key Name: To setup corresponding name for the card. ● IC Key Code: Place the card in the R27A RF Card Read area, then click Obtain button. After R27A reads the card code, click Add, the card information will show in the Door Card Management list.
Door Card Management	Valid card information will show in the list. Users can tick the current card information then delete one or all in the list.

4.4.10 Action

Action

Email Notification

Sender's email address

Receiver's email address

SMTP server address

SMTP user name

SMTP password

Email subject

Email content

Email Test

FTP Notification

FTP Server

FTP User Name

FTP Password

FTP Test

SIP Call Notification

SIP Call Number

SIP Caller Name

Sections	Description
Email Notification	<ul style="list-style-type: none"> ● Sender Email Address: Input the sender email address ● Receiver Email Address: Input the receiver email address ● SMTP Server Address: Enter the SMTP server format

	<ul style="list-style-type: none"> ● SMTP User name: Enter the SMTP ● SMTP password: Enter the sender email password ● Email Subject: Enter the subject name. ● Email content: Enter the content name. ● Email test: Click test to make sure the parameters you enter is right.
FTP Notification	<ul style="list-style-type: none"> ● FTP Server: Enter the FTP server address. ● FTP User Name: Enter the FTP server user name. ● FTP Password: Enter the corresponding FTP server password. ● FTP test: Click test to make sure the parameters you enter is right.
SIP Call Notification	<p>When you enable SIP Call function of motion. Enter the number and name in the corresponding area. When the motion is triggered, the device will call out the number automatically.</p>

4.5. Account

4.5.1 Basic

Account-Basic

SIP Account

Status	Disabled	
Account	Account 1 ▼	
Account Active	Disabled ▼	
Display Label	<input type="text"/>	
Display Name	<input type="text"/>	
Register Name	<input type="text"/>	
User Name	<input type="text"/>	
Password	<input type="password" value="*****"/>	

SIP Server 1

Server IP	<input type="text"/>	Port	<input type="text" value="5060"/>
Registration Period	<input type="text" value="1800"/>		(30~65535s)

SIP Server 2

Server IP	<input type="text"/>	Port	<input type="text" value="5060"/>
Registration Period	<input type="text" value="1800"/>		(30~65535s)

Outbound Proxy Server

Enable Outbound	Disabled ▼		
Server IP	<input type="text"/>	Port	<input type="text" value="5060"/>
Backup Server IP	<input type="text"/>	Port	<input type="text" value="5060"/>

Transport Type

Transport Type	<input type="text" value="UDP"/>
----------------	----------------------------------

NAT

NAT	Disabled ▼		
Stun Server Address	<input type="text"/>	Port	<input type="text" value="3478"/>

Sections	Description
SIP Account	To display and configure the specific Account settings. <ul style="list-style-type: none"> ● Status: To display register result. ● Display Name: Which is sent to the other call party for display. ● Register Name: Allocated by SIP server provider, used for authentication. ● User Name: Allocated by your SIP server provide, used for authentication. ● Password: Used for authorization.
SIP Server 1	To display and configure Primary SIP server settings. <ul style="list-style-type: none"> ● Server IP: SIP server address, it could be an URL or IP address.

	<ul style="list-style-type: none"> ● Registration Period: The registration will expire after Registration period, the IP phone will re-register automatically within registration period.
SIP Server 2	<p>To display and configure Secondary SIP server settings. This is for redundancy, if registering to Primary SIP server fails, the IP phone will go to Secondary SIP server for registering.</p> <p>Note: Secondary SIP server is used for redundancy, it can be left blank if there is not redundancy SIP server in user's environment.</p>
Outbound Proxy Server	<p>To display and configure Outbound Proxy server settings. An outbound proxy server is used to receive all initiating request messages and route them to the designated SIP server.</p> <p>Note: If configured, all SIP request messages from the IP phone will be sent to the outbound proxy server forcefully.</p>
Transport Type	<p>To display and configure Transport type for SIP message</p> <ul style="list-style-type: none"> ● UDP: UDP is an unreliable but very efficient transport layer protocol. ● TCP: Reliable but less-efficient transport layer protocol. ● TLS: Secured and Reliable transport layer protocol. ● DNS-SRV: A DNS RR for specifying the location of services.
NAT	<p>To display and configure NAT(Net Address Translator) settings.</p> <ul style="list-style-type: none"> ● STUN: Short for Simple Traversal of UDP over NATS, a solution to solve NAT issues. <p>Note: By default, NAT is disabled.</p>

4.5.2 Advanced

Account-Advanced	
SIP Account	
Account	Account 1
Codecs	
Disabled Codecs	Enabled Codecs
	PCMU PCMA G722 G729
>>	↑
<<	↓
Video Codec	
Codec Name	<input checked="" type="checkbox"/> H264
Codec Resolution	4CIF
Codec Bitrate	2048
Codec Payload	104
Subscribe	
MWI Subscribe	Disabled
MWI Subscribe Period	1800 (120~65535s)
Voice Mail Number	
BLF Expire	1800 (120~65535s)
ACD Expire	1800 (120~65535s)
DTMF	
Type	RFC2833
How To Notify DTMF	Disabled
DTMF Payload	101 (96~127)
Call	
Max Local SIP Port	5062 (1024~65535)
Min Local SIP Port	5062 (1024~65535)
Caller ID Header	FROM
Auto Answer	Enabled
Provisional Response ACK	Disabled
Register with user=phone	Disabled
Invite with user=phone	Disabled
Anonymous Call	Disabled
Anonymous Call Rejection	Disabled
Missed Call Log	Enabled
Prevent SIP Hacking	Disabled
Session Timer	
Active	Disabled
Session Expire	1800 (90~7200s)
Session Refresher	UAC
BLFList	
BLFList URI	
BLFList Pickup Code	
BLFList BargeIn Code	
Encryption	
Voice Encryption(SRTP)	Disabled
NAT	
UDP Keep Alive Messages	Disabled
UDP Alive Msg Interval	30 (5~60s)
RPort	Disabled
User Agent	
User Agent	

Sections	Description
SIP Account	To display current Account settings or to select which account to display.
Codecs	To display and configure available/unavailable codecs list. Codec means coder-decoder which is used to transfer analog signal to digital signal or vice versa. Familiar codecs are PCMU(G711U), PCMA(G711A), G722 (wide-bandth codecs), G729 and so on.
Video Codec	To configure the video quality <ul style="list-style-type: none"> ● Codec Name: The default video codec is H264. ● Codec Resolution: It can support QCIF, CIF, VGA, 4CIF, 720P. ● Codec Bitrate: The lowest bitrate is 128, the highest bitrate is 2048. ● Codec payload: From 90-119.
Subscribe	To display and configure MWI, BLF, ACD subscription settings. <ul style="list-style-type: none"> ● MWI: Message Waiting Indicator which is used to indicate whether there is unread new voice message. ● BLF: BLF is short for Busy Lamp Field which is used to monitor the designated extension status. ● ACD: Automatic Call Distribution is often used in offices for customer service, such as call center. The setting here is to negotiate with the server about expire time of ACD subscription.
DTMF	To display and configure DTMF settings. <ul style="list-style-type: none"> ● Type: Support Inband, Info, RFC2833 or their combination. ● How To Notify DTMF: Only available when DTMF Type is Info. ● DTMF Payload: To configure payload type for DTMF. <p>Note: By default, DTMF type is RFC2833 which is the standard. Type Inband uses inband frequency to indicate DTMF tone which is most used to be compatible to traditional telephone server. Type Info use SIP Info message to indicate DTMF message.</p>
Call	To display and configure call-related features. <ul style="list-style-type: none"> ● Max Local SIP Port: To configure maximum local sip port for designated account. ● Min Local SIP Port: To configure minimum local sip port for designated account. ● Caller ID Header: To configure which Caller ID format to fetch for displaying on Phone UI. ● Auto Answer: If enabled, IP phone will be auto-answered

	<p>when there is an incoming call for designated account.</p> <ul style="list-style-type: none"> ● Ringtones: Choose the ringtone for each account. ● Provisioning Response ACK: 100% reliability for all provisional messages, this means it will send ACK every time the IP phone receives a provisional SIP message from SIP server. ● User=phone: If enabled, IP phone will send user=phone within SIP message. ● PTime: Interval time between two consecutive RTP packets. ● Anonymous Call: If enabled, all outgoing call for the designated account will be anonymous number. ● Anonymous Call Rejection: If enabled, all incoming anonymous-out call for the designated account will be rejected. ● Is escape non Ascii character: To transfer the symbol to Ascii character. ● Missed Call Log: To display the miss call log. ● Prevent SIP Hacking: Enable to prevent SIP from hacking.
Session Timer	<p>To display or configure session timer settings.</p> <ul style="list-style-type: none"> ● Active: To enable or disable this feature, if it is enabled, the ongoing call will be disconnected automatically once the session expired unless it's been refreshed by UAC or UAS. ● Session Expire: Configure session expire time. ● Session Refresher: It is used to configure who should be responded for refreshing a session. <p>Note: UAC means User Agent Client, here stands for IP phone. UAS means User Agent Server, here stands for SIP server.</p>
BLF List	<p>To display or configure BLF List URI address.</p> <ul style="list-style-type: none"> ● BLF List URI: BLF List is short for Busy Lamp Field List. ● BLFList PickUp Code: To set the BLF pick up code. ● BLFList BargelIn Code : To set the BLF barge in code.
Encryption	<p>To enable or disabled SRTP feature.</p> <ul style="list-style-type: none"> ● Voice Encryption(SRTP): If enabled, all audio signal (technically speaking it's RTP streams) will be encrypted for more security.
NAT	<p>To display NAT-related settings.</p> <ul style="list-style-type: none"> ● UDP Keep Alive message: If enabled, IP phone will send UDP keep-alive message periodically to router to keep NAT port alive. ● UDP Alive Msg Interval: Keepalive message interval. ● Rport: Remote Port, if enabled, it will add Remote Port

	into outgoing SIP message for designated account.
User Agent	One can customize User Agent field in the SIP message; if user agent is set to specific value, user can see the information from PCAP. If user agent is not set by default, users can see the company name, model number and firmware version from PCAP

4.6. Network

4.6.1 Basic

Network-Basic

LAN Port

DHCP
 Static IP

IP Address: 192.168.1.100
 Subnet Mask: 255.255.255.0
 Default Gateway: 192.168.1.1
 LAN DNS1: 8.8.8.8
 LAN DNS2:

Sections	Description
LAN Port	<p>To display and configure LAN Port settings.</p> <ul style="list-style-type: none"> ● DHCP: If selected, IP phone will get IP address, Subnet Mask, Default Gateway and DNS server address from DHCP server automatically. ● Static IP: If selected, you have to set IP address, Subnet Mask, Default Gateway and DNS server manually.

4.6.2 Advanced

Network-Advanced	
Local RTP	
Starting RTP Port	11800 (1024~65535)
Max RTP Port	12000 (1024~65535)
SNMP	
Active	Disabled
Port	(1024~65535)
Trusted IP	
VLAN	
LAN Port	Active: Disabled
	VID: 1 (1~4094)
	Priority: 0
TR069	
	Active: Disabled
	Version: 1.0
ACS	URL: <input type="text"/>
	User Name: <input type="text"/>
	Password: <input type="password"/>
Periodic Inform	Active: Disabled
	Periodic Interval: 1800 (3~24×3600s)
CPE	URL: <input type="text"/>
	User Name: <input type="text"/>
	Password: <input type="password"/>

Sections	Description
Local RTP	<p>To display and configure Local RTP settings.</p> <ul style="list-style-type: none"> ● Max RTP Port: Determine the maximum port that RTP stream can use. ● Starting RTP Port: Determine the minimum port that RTP stream can use.
SNMP	<p>To display and configure SNMP settings.</p> <ul style="list-style-type: none"> ● Active: To enable or disable SNMP feature. ● Port: To configure SNMP server's port. ● Trusted IP: To configure allowed SNMP server address, it could be an IP address or any valid URL domain name. <p>Note: SNMP (Simple Network Management Protocols) is Internet-standard protocol for managing devices on IP networks.</p>
VLAN	<p>To display and configure VLAN settings.</p> <ul style="list-style-type: none"> ● Active: To enable or disable VLAN feature for designated port. ● VID: To configure VLAN ID for designated port. ● Priority: To select VLAN priority for designated port. <p>Note: Please consult your administrator for specific VLAN settings in your networking environment.</p>

<p>TR069</p>	<p>To display and configure TR069 settings.</p> <ul style="list-style-type: none"> ● Active: To enable or disable TR069 feature. ● Version: To select supported TR069 version (version 1.0 or 1.1). ● ACS/CPE: ACS is short for Auto configuration servers as server side, CPE is short for Customer-premise equipment as client side devices. ● URL: To configure URL address for ACS or CPE. ● User name: To configure username for ACS or CPE. ● Password: To configure Password for ACS or CPE. ● Periodic Inform: To enable periodically inform. ● Periodic Interval: To configure interval for periodic inform. <p>Note: TR-069(Technical Report 069) is a technical specification entitled CPE WAN Management Protocol (CWMP).It defines an application layer protocol for remote management of end-user devices.</p>
---------------------	---

4.7. Phone

4.7.1 Time/Language

The screenshot shows a configuration page titled "Time/Lang" with a sub-section for "NTP". The settings are as follows:

NTP	
Time Zone	0 GMT
Primary Server	0.pool.ntp.org
Secondary Server	1.pool.ntp.org
Update Interval	3600 (>= 3600s)
System Time	03:40:44

Sections	Description
<p>NTP</p>	<p>To configure NTP server related settings.</p> <ul style="list-style-type: none"> ● Time Zone: To select local Time Zone for NTP server. ● Primary Server: To configure primary NTP server address. ● Secondary Server: To configure secondary NTP server address, it takes effect if primary NTP server is unreachable. ● Update interval: To configure interval between two consecutive NTP requests. <p>Note: NTP, Network Time Protocol is used to automatically</p>

	synchronized local time with INTERNET time, since NTP server only response GMT time, so that you need to specify the Time Zone for IP phone to decide the local time.
--	---

4.7.2 Call Feature

Phone-Call Feature

Mode Phone

Mode Phone Custom

DND

Account All Account ▼

DND Disabled ▼

Return Code When DND 486(Busy Here) ▼

DND On Code

DND Off Code

Intercom

Active Enabled ▼

Intercom Mute Disabled ▼

Others

Return Code When Refuse 486(Busy Here) ▼

Auto Answer Delay (0~5s)

Auto Answer Mode: Video ▼

Multicast Codec PCMU ▼

Direct IP Enabled ▼

Sections	Description
Mode	Mode: Select the desired mode.
DND	<p>DND (Do Not Disturb) allows IP phones to ignore any incoming calls.</p> <ul style="list-style-type: none"> ● Return Code when DND: Determine what response code should be sent back to server when there is an incoming call if DND on. ● DND On Code: The Code is used to turn on DND on server's side, if configured, IP phone will send a SIP message to server to turn on DND on server side if you press DND when DND is off. ● DND Off Code: The Code is used to turn off DND on server's side, if configured, IP phone will send a SIP message to server to turn off DND on server side if you press DND when DND is on.
Intercom	<p>Intercom allows users to establish a call directly with the callee.</p> <ul style="list-style-type: none"> ● Active: To enable or disable Intercom feature.

	<ul style="list-style-type: none"> ● Intercom Mute: If enabled, once the call established, the callee will be muted.
Others	<ul style="list-style-type: none"> ● Return Code When Refuse: Allows user to assign specific code as return code to SIP server when an incoming call is rejected. ● Auto Answer Delay: To configure delay time before an incoming call is automatically answered. ● Auto Answer Mode: To set video or audio mode for auto answer by default. ● Direct IP: Direct IP call without SIP proxy.

4.7.3 Voice

Voice

Mic Volume

Mic Volume

(1~15)

Speaker Volume

Speaker Volume

(1~15)

Open Door Warning

Open Door Warning

RingBack Upload

File Format: wav, size: < 200KB, samplerate: 16000, Bits: 16

Opendoor Tone Upload

File Format: wav, size: < 200KB, samplerate: 16000, Bits: 16

Sections	Description
Mic Volume	To configure Microphone volume, from 1-15. 8 by default.
Speaker Volume	To configure Speaker Volume, from 1-15,8 by default.
Open Door Warning	When the door is opened, users will hear that opendoor prompt voice. If you disable it, you won't hear the announcement.
RingBack Upload	During the calling, user will hear the ringback tone before the other party answer. User can upload the suitable RingBack

	Tone by yourselves. Please note the file format and size.
Opendoor Tone Upload	Choose a suitable opendoor warning tone to upload. Please not the file format and size.

4.7.4 Dial Plan

Dial Plan

Rules Management

Browse... Import Export

Index	Account	Prefix	Replace	<input type="checkbox"/>
1				<input type="checkbox"/>
2				<input type="checkbox"/>
3				<input type="checkbox"/>
4				<input type="checkbox"/>
5				<input type="checkbox"/>
6				<input type="checkbox"/>
7				<input type="checkbox"/>
8				<input type="checkbox"/>
9				<input type="checkbox"/>
10				<input type="checkbox"/>

Page: 1 Add Edit Delete Prev Next

Rules Modify >>

Account: Auto

Prefix:

Replace:

Submit Cancel

Sections	Description
Rules Management	For easy management, users can export and import the replace rule file directly. (The export file format is .tgz, users need to unzip it, then check the .XML file. The Import format is .XML)
Rules	Allow user to select Replace rule to display or edit.
Rules Modify	Allow user to modify selected rules information, for replace rule, you can modify related accounts, prefix and replace. Such as: Account:1 Prefix: 100 Replace: 110 Then users dial 100 with account1, the phone will call out 110 actually.

4.7.5 Multicast

Multicast

Multicast Setting

Paging Barge Disabled ▼

Paging Priority Active Enabled ▼

Priority List

IP Address	Listening Address	Label	Priority
1 IP Address	<input type="text"/>	<input type="text"/>	1
2 IP Address	<input type="text"/>	<input type="text"/>	2
3 IP Address	<input type="text"/>	<input type="text"/>	3
4 IP Address	<input type="text"/>	<input type="text"/>	4
5 IP Address	<input type="text"/>	<input type="text"/>	5
6 IP Address	<input type="text"/>	<input type="text"/>	6
7 IP Address	<input type="text"/>	<input type="text"/>	7
8 IP Address	<input type="text"/>	<input type="text"/>	8
9 IP Address	<input type="text"/>	<input type="text"/>	9
10 IP Address	<input type="text"/>	<input type="text"/>	10

Sections	Description
Multicast Setting	To display and configure the Multicast setting. <ul style="list-style-type: none"> ● Paging Barge: Choose the multicast number, the range is 1-10. ● Paging priority Active: Enable o disable the multicast.
Priority List	To setup the multicast parameters. <ul style="list-style-type: none"> ● Listening Address: Enter the IP address you need to listen. ● Label: Input the label for each listening address.

4.7.6 Call log

Call Log							
Call History							All ▼
Index	Type	Date	Time	Local Identity	Name	Number	<input type="checkbox"/>
1							<input type="checkbox"/>
2							<input type="checkbox"/>
3							<input type="checkbox"/>
4							<input type="checkbox"/>
5							<input type="checkbox"/>
6							<input type="checkbox"/>
7							<input type="checkbox"/>
8							<input type="checkbox"/>
9							<input type="checkbox"/>
10							<input type="checkbox"/>
11							<input type="checkbox"/>
12							<input type="checkbox"/>
13							<input type="checkbox"/>
14							<input type="checkbox"/>
15							<input type="checkbox"/>

Page 1 ▼ Prev Next Delete Delete All

Sections	Description
Call History	<p>To display call history records.</p> <p>Available call history types are All calls, Dialed calls, Received calls, Missed calls, Forwarded calls.</p> <p>Users can check the call history in detail. Tick the number to delete or delete all logs. R27A supports 100 call logs.</p>

4.7.7 Door log

Index	Name	Code	Date	Time	
1					<input type="checkbox"/>
2					<input type="checkbox"/>
3					<input type="checkbox"/>
4					<input type="checkbox"/>
5					<input type="checkbox"/>
6					<input type="checkbox"/>
7					<input type="checkbox"/>
8					<input type="checkbox"/>
9					<input type="checkbox"/>
10					<input type="checkbox"/>
11					<input type="checkbox"/>
12					<input type="checkbox"/>
13					<input type="checkbox"/>
14					<input type="checkbox"/>
15					<input type="checkbox"/>

1 ▾ Prev Next Delete DeleteAll

Sections	Description
Door Log	To display unlock history. This interface can only show the RF card unlock history now. Users can check the unlock information in detail. Users can delete one or all logs. The maximum door log is 500.

4.8. Upgrade

4.8.1 Basic

Upgrade-Basic

Firmware Version: 27.0.2.170
Hardware Version: 27.0.0.0.0.0.0.0

Upgrade:

Reset To Factory Setting:

Reboot:

Sections	Description
----------	-------------

Upgrade	To select upgrading zip file from local or a remote server automatically. Note: Please make sure it's right file format for right model.
Firmware version	To display firmware version, firmware version starts with MODEL name.
Hardware Version	To display Hardware version.
Reset to Factory Setting	To enable you to reset IP phone's setting to factory settings.
Reboot	To reboot IP phone remotely from Web UI.

4.8.2 Advanced

Upgrade-Advanced

PNP Option

PNP Config Enabled ▼

Manual Autop

URL

User Name

Password

Common AES Key

AES Key(MAC)

Automatic Autop

Mode Power On ▼

Schedule Sunday ▼

Hour(0~23)

Min(0~59)

Clear MD5

Export Autop Template

RebootSchedule

Mode Disabled ▼

Schedule Every Day ▼

Hour(0~23)

System Log


LogLevel 3 ▼

Export Log

Sections	Description
PNP Option	<p>To display and configure PNP setting for Auto Provisioning.</p> <ul style="list-style-type: none"> ● PNP: Plug and Play, once PNP is enabled, the phone will send SIP subscription message to PNP server automatically to get Auto Provisioning server's address. <p>By default, this SIP message is sent to multicast address 224.0.1.75(PNP server address by standard).</p>
Manual Autop	<p>To display and configure manual update server's settings.</p> <ul style="list-style-type: none"> ● URL: Auto provisioning server address. ● User name: Configure if server needs a username to access, otherwise left blank. ● Password: Configure if server needs a password to access, otherwise left blank. ● Common AES Key: Used for IP phone to decipher common Auto Provisioning configuration file. ● AES Key (MAC): Used for IP phone to decipher MAC-oriented auto provisioning configuration file(for example, file name can be 0c1105888888.cfg if IP phone's MAC address is 0c1105888888). <p>Note: AES is one of many encryption, it should be configure only configure file is ciphered with AES, otherwise left blank.</p>
Automatic Autop	<p>To display and configure Auto Provisioning mode settings.</p> <p>This Auto Provisioning mode is actually self-explanatory.</p> <p>For example, mode "Power on" means IP phone will go to do Provisioning every time when it powers on.</p>
System Log	<p>To display system log level and export system log file.</p> <ul style="list-style-type: none"> ● System log level: From level 0~7.The higher level means the more specific system log is saved to a temporary file. By default, it's level 3. ● Export Log: Click to export temporary system log file to local PC.

4.9. Security

4.9.1 Basic



The screenshot shows a web interface for modifying a password. It is titled 'Security-Basic' and 'Web Password Modify'. The form includes a dropdown menu for 'User Name' with 'admin' selected, and three text input fields for 'Current Password', 'New Password', and 'Confirm Password'.

Sections	Description
Web Password Modify	To modify user's password. <ul style="list-style-type: none">● Current Password: The current password you used.● New Password: Input new password you intend to use.● Confirm Password: Repeat the new password.