

## APPENDIX C - RF EXPOSURE EVALUATION

### Maximum Permissible Exposure (MPE)

#### Applicable Standard

According to subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission’s guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
<b>Frequency Range (MHz)</b>	<b>Electric Field Strength (V/m)</b>	<b>Magnetic Field Strength (A/m)</b>	<b>Power Density (mW/cm<sup>2</sup>)</b>	<b>Averaging Time (minutes)</b>
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30–300	27.5	0.073	0.2	30
300–1500	/	/	f/1500	30
1500–100,000	/	/	1.0	30

f = frequency in MHz; \* = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

#### Calculation formula:

Prediction of power density at the distance of the applicable MPE limit

$S = PG/4\pi R^2$  = power density (in appropriate units, e.g. mW/cm<sup>2</sup>);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

For simultaneously transmit system, the calculated power density should comply with:

$$\sum_i \frac{S_i}{S_{Limit,i}} \leq 1$$

**Calculated Data:**

Radio	Operation Modes	Frequency (MHz)	Antenna Gain		Conducted output power including Tune-up Tolerance		Evaluation Distance (cm)	Power Density (mW/cm <sup>2</sup> )	MPE Limit (mW/cm <sup>2</sup> )
			(dBi)	(numeric)	(dBm)	(mW)			
WiFi/BT Module	WiFi 2.4G	2412-2462	2.5	1.78	22	158.49	20.00	0.0561	1.0
	WiFi 5.2G	5150-5250	3.4	2.19	17	50.12	20.00	0.0218	1.0
	WiFi 5.3G	5250-5350	3.5	2.24	16	39.81	20.00	0.0177	1.0
	WiFi 5.6G	5470-5725	3.4	2.19	10	10.00	20.00	0.0044	1.0
	WiFi 5.8G	5725-5850	3.8	2.40	17	50.12	20.00	0.0239	1.0
	Bluetooth	2402-2480	2.5	1.78	7	5.01	20.00	0.0018	1.0
	BLE	2402-2480	2.5	1.78	1	1.26	20.00	0.0004	1.0
Zigbee Module	Zigbee	2405-2480	2.9	1.95	5	3.16	20.00	0.0012	1.0

The Conducted output power including Tune-up Tolerance provided by manufacturer

The WiFi/BT Module and Zigbee Module can transmit simultaneously, operation modes in WiFi/BT module can't transmit simultaneously:

$$\sum_i \frac{S_i}{S_{Limit,i}}$$

$$=S_{WiFi/BT}/S_{limit-WiFi/BT} + S_{Zigbee}/S_{limit-Zigbee}$$

$$=0.0561/1+0.0012/1$$

$$=0.0573$$

$$< 1.0$$

**Result:** The device meet FCC MPE at 20 cm distance

**\*\*\*\*\* END OF REPORT \*\*\*\*\***