



中认信通

CHINA CERTIFICATION ICT CO., LTD (DONGGUAN)



RF EXPOSURE EVALUATION

Applicant: AKUVOX (XIAMEN) NETWORKS CO., LTD.

Address: 10/F, No.56 Guanri Road, Software Park II, Xiamen 361009, China

FCC ID: 2AHCR-X915SV2

Product Name: Door Phone

Standard(s): 47 CFR §1.1310, 47 CFR §2.1091
447498 D01 General RF Exposure Guidance v06

The above equipment has been tested and found compliant with the requirement of the relative standards by China Certification ICT Co., Ltd (Dongguan)

Report Number: CR230738304-00E

Date Of Issue: 2023/12/5

Reviewed By: Julie Tan

Title: RF Engineer

Julie Tan

Approved By: Sun Zhong

Title: Manager

Sun Zhong

Test Laboratory: China Certification ICT Co., Ltd (Dongguan)

No. 113, Pingkang Road, Dalang Town, Dongguan,

Guangdong, China

Tel: +86-769-82016888

Test Facility

The Test site used by China Certification ICT Co., Ltd (Dongguan) to collect test data is located on the No. 113, Pingkang Road, Dalang Town, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 442868, the FCC Designation No. : CN1314.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0123.

Declarations

China Certification ICT Co., Ltd (Dongguan) is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with a triangle symbol “▲”. Customer model name, addresses, names, trademarks etc. are not considered data.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

This report cannot be reproduced except in full, without prior written approval of the Company.

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report may contain data that are not covered by the accreditation scope and shall be marked with an asterisk “★”.

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
1.0	CR230738304-00E	Original Report	2023/12/5

Applicable Standard

According to subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.


Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	/	/	f/1500	30
1500–100,000	/	/	1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Block Diagram of Test Setup For RFID



Calculation formula For Power Density:

Prediction of power density at the distance of the applicable MPE limit

$S = PG/4\pi R^2$ = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

Test Data For 125kHz RFID:

Serial Number:	27V8-7	Test Date:	2023/12/01
Test Site:	RF	Test Mode:	Transmitting
Tester:	David Huang	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.9	Relative Humidity: (%)	48	ATM Pressure: (kPa)	101.3
----------------------	------	------------------------------	----	------------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Narda	Electric and Magnetic Field Probe-Analyzer	EHP-200AC	180ZX10204	2021/06/07	2024/06/06

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:**H-Field Strength**

Frequency Range (kHz)	Position A Right (A/m)	Position B Bottom (A/m)	Position C Left (A/m)	Position D Top (A/m)	Position E Front (A/m)	Limit (A/m)
125	0.1049	0.1094	0.1086	0.1031	0.1127	1.63

Note: Test with 20cm distance from the center of the probe(s) to the edge of the device.

E-Field Strength

Frequency Range (kHz)	Position A Right (A/m)	Position B Bottom (A/m)	Position C Left (A/m)	Position D Top (A/m)	Position E Front (A/m)	Limit (V/m)
125	0.6954	0.6904	0.6594	0.5415	1.1094	614

Note: Test with 20cm distance from the center of the probe(s) to the edge of the device.

Power Density Calculation:

Operation Modes	Frequency (MHz)	Antenna Gain		Conducted output power including Tune-up Tolerance		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
		(dBi)	(numeric)	(dBm)	(mW)			
Bluetooth BDR/EDR	2402-2480	0.3	1.07	9	7.94	20.00	0.0016	1.0
Bluetooth LE	2402-2480	0.3	1.07	10	10	20.00	0.0021	1.0
NFC	13.56	0	1.00	-30.51	0.001	20	<<0.0001	0.98

Note:

1. The Above Parameters were provided by the manufacturer.
2. *NFC field strength is 64.69 μ V/m @ 3m = -30.51 dBm(0.0007mW) EIRP. That equal to antenna gain is 0dBi and used the EIRP value as conducted power.

Simultaneous transmission:

BDR/EDR can't transmission simultaneously with BLE, 125kHz RFID and NFC, Bluetooth can transmission simultaneously:

$$S_{BLE}/S_{limit-BLE} + S_{NFC}/S_{limit-NFC} + H_{RFID}/H_{limit}$$




$$=0.0021/1+0.0001/0.98+0.1094/1.63$$


$$=0.069$$

$$< 1.0$$

Result: The device meet FCC MPE at 20 cm distance

TEST SETUP PHOTOGRAPHS

<p>Right Side</p>	 A photograph showing the right side of a black mobile phone lying on a wooden workbench. A white measuring tape is placed vertically to the left of the phone, showing measurements in centimeters. The phone's screen is on, displaying a lock screen with the time 03:50 and various icons. A white cable is connected to the bottom of the phone.
<p>Bottom Side</p>	 A photograph showing the bottom side of the mobile phone on the wooden workbench. The measuring tape is now on the right side of the phone. The screen displays the time 03:37 and a lock screen with icons. A white cable is connected to the bottom of the phone.
<p>Left Side</p>	 A photograph showing the left side of the mobile phone on the wooden workbench. The measuring tape is on the right side of the phone. The screen displays the time 03:41 and a lock screen with icons. A white cable is connected to the bottom of the phone.



==== END OF REPORT ====