

# FCC REPORT

**Applicant:** NEXUS TELECOM SERVICES (HK) LIMITED

**Address of Applicant:** R112, 11/F Hollywood Plaza, Mangkok, Kowloon, Hong Kong

**Equipment Under Test (EUT)**

**Product Name:** 3G SMART PHONE

**Model No.:** GO401

**Trade mark:** GOMOBILE

**FCC ID:** 2AHDFGO401

**Applicable standards:** FCC CFR Title 47 Part 15 Subpart B

**Date of sample receipt:** 19 Apr., 2017

**Date of Test:** 19 Apr., to 15 May, 2017

**Date of report issued:** 16 May, 2017

**Test Result:** Pass \*

\* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Bruce Zhang  
Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the CCIS product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

## 2 Version

Version No.	Date	Description
00	16 May, 2017	Original

**Tested by:****Date:**

16 May, 2017

**Test Engineer****Reviewed by:****Date:**

16 May, 2017

**Project Engineer**

### 3 Contents

	Page
1 COVER PAGE.....	1
2 VERSION.....	2
3 CONTENTS .....	3
4 TEST SUMMARY.....	4
5 GENERAL INFORMATION .....	5
5.1 CLIENT INFORMATION .....	5
5.2 GENERAL DESCRIPTION OF E.U.T.....	5
5.3 TEST MODE.....	5
5.4 MEASUREMENT UNCERTAINTY.....	5
5.5 DESCRIPTION OF SUPPORT UNITS .....	6
5.6 LABORATORY FACILITY.....	6
5.7 LABORATORY LOCATION .....	6
5.8 TEST INSTRUMENTS LIST.....	7
6 TEST RESULTS AND MEASUREMENT DATA .....	8
6.1 CONDUCTED EMISSION.....	8
6.2 RADIATED EMISSION.....	11
7 TEST SETUP PHOTO.....	17
8 EUT CONSTRUCTIONAL DETAILS.....	18

## 4 Test Summary

Test Item	Section in CFR 47	Result
Conducted Emission	Part 15.107	Pass
Radiated Emission	Part 15.109	Pass

*Pass: The EUT complies with the essential requirements in the standard.*

## 5 General Information

### 5.1 Client Information

Applicant:	NEXUS TELECOM SERVICES (HK) LIMITED
Address of Applicant:	R112, 11/F Hollywood Plaza, Mangkok, Kowloon, Hong Kong
Manufacturer	FORTUNE SHIP INTERNATIONAL INDUSTRIAL LIMITED
Address of Manufacturer:	Suite A 11/F HO LEE COMM BLDG 38-44 D'AGUILAR ST CENTRAL HongKong
Factory:	GUIZHOU FORTUNE SHIP INTELLIGENT TERMINAL INDUSTRIAL PARK
Address of Factory:	GUIZHOU FORTUNE SHIP, XINPU ECONOMIC DEVELOPMENT ZONE, ZUNYI, GUIZHOU, CHINA

### 5.2 General Description of E.U.T.

Product Name:	3G SMART PHONE
Model No.:	GO401
Power supply:	Rechargeable Li-ion Battery DC3.7V-1500mAh
AC adapter :	Input: AC100-240V 50/60Hz 0.15A Output: DC 5.0V, 0.5A

### 5.3 Test Mode

Operating mode	Detail description
PC mode	Keep the EUT in Downloading mode(Worst case)
Charging+Recording mode	Keep the EUT in Charging+Recording mode
Charging+Playing mode	Keep the EUT in Charging+Playing mode
FM mode	Keep the EUT in FM receiver mode
GPS mode	Keep the EUT in GPS receiver mode

The sample was placed 0.8m above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.

### 5.4 Measurement Uncertainty

Items	Expanded Uncertainty (Confidence of 95%)
Conducted Emission (9kHz ~ 30MHz)	2.14 dB (k=2)
Radiated Emission (9kHz ~ 30MHz)	4.24 dB (k=2)
Radiated Emission (30MHz ~ 1000MHz)	4.35 dB (k=2)
Radiated Emission (1GHz ~ 18GHz)	4.44 dB (k=2)
Radiated Emission (18GHz ~ 26.5GHz)	4.56 dB (k=2)

## 5.5 Description of Support Units

Manufacturer	Description	Model	Serial Number	FCC ID/DoC
DELL	PC	OPTIPLEX745	N/A	DoC
DELL	MONITOR	E178FPC	N/A	DoC
DELL	KEYBOARD	SK-8115	N/A	DoC
DELL	MOUSE	MOC5UO	N/A	DoC
HP	Printer	CB495A	05257893	DoC
MERCURY	Wireless router	MW150R	12922104015	FCC ID
NAKAMICHI	Bluetooth earphone	T8	N/A	FCC ID

## 5.6 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **FCC - Registration No.: 817957**

Shenzhen Zhongjian Nanfang Testing Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in out files. Registration 817957, February 27, 2012.

- **IC - Registration No.: 10106A-1**

The 3m Semi-anechoic chamber of Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1.

- **CNAS - Registration No.: CNAS L6048**

Shenzhen Zhongjian Nanfang Testing Co., Ltd. is accredited to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L6048.

## 5.7 Laboratory Location

Shenzhen Zhongjian Nanfang Testing Co., Ltd.

Address: No. B-C, 1/F., Building 2, Laodong No.2 Industrial Park, Xixiang Road,  
Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755-23118282

Fax: +86-755-23116366

## 5.8 Test Instruments list

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
1	3m SAC	SAEMC	9(L)*6(W)* 6(H)	CCIS0001	08-23-2014	08-22-2017
2	BiConiLog Antenna	SCHWARZBECK	VULB9163	CCIS0005	02-25-2017	02-24-2018
3	Horn Antenna	SCHWARZBECK	BBHA9120D	CCIS0006	02-25-2017	02-24-2018
4	Pre-amplifier (10kHz-1.3GHz)	HP	8447D	CCIS0003	02-25-2017	02-24-2018
5	Pre-amplifier (1GHz-18GHz)	Compliance Direction Systems Inc.	PAP-1G18	CCIS0011	02-25-2017	02-24-2018
6	Spectrum analyzer 9k-30GHz	Rohde & Schwarz	FSP30	CCIS0023	02-25-2017	02-24-2018
7	EMI Test Receiver	Rohde & Schwarz	ESRP7	CCIS0167	02-25-2017	02-24-2018
8	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
9	Coaxial Cable	N/A	N/A	CCIS0018	02-25-2017	02-24-2018
10	Coaxial Cable	N/A	N/A	CCIS0020	02-25-2017	02-24-2018

Conducted Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Shielding Room	ZhongShuo Electron	11.0(L)x4.0(W)x3.0(H)	CCIS0061	08-23-2014	08-22-2017
2	EMI Test Receiver	Rohde & Schwarz	ESCI	CCIS0002	02-25-2017	02-24-2018
3	LISN	CHASE	MN2050D	CCIS0074	02-25-2017	02-24-2018
4	Coaxial Cable	CCIS	N/A	CCIS0086	02-25-2017	02-24-2018
5	EMI Test Software	AUDIX	E3	N/A	N/A	N/A


## 6 Test results and Measurement Data

### 6.1 Conducted Emission

Test Requirement:	FCC Part 15 B Section 15.107					
Test Method:	ANSI C63.4:2014					
Test Frequency Range:	150kHz to 30MHz					
Class / Severity:	Class B					
Receiver setup:	RBW=9kHz, VBW=30kHz					
Limit:	Frequency range (MHz)	Limit (dB $\mu$ V)				
		Quasi-peak	Average			
	0.15-0.5	66 to 56*	56 to 46*			
	0.5-5	56	46			
	0.5-30	60	50			
* Decreases with the logarithm of the frequency.						
Test setup:	<p>Reference Plane</p> <p>LISN</p> <p>40cm</p> <p>80cm</p> <p>AUX Equipment</p> <p>E.U.T</p> <p>Test table/Insulation plane</p> <p>EMI Receiver</p> <p>Filter</p> <p>AC power</p> <p>Remark: E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m</p>					
Test procedure	<ol style="list-style-type: none"> <li>The E.U.T and simulators are connected to the main power through a line impedance stabilization network(L.I.S.N.). They provide a 50ohm/50uH coupling impedance for the measuring equipment.</li> <li>The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs).</li> <li>Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4: 2014 on conducted measurement.</li> </ol>					
Test environment:	Temp.:	23 °C	Humid.:	56%	Press.:	101kPa
Test Instruments:	Refer to section 5.7 for details					
Test mode:	Refer to section 5.3 for details					
Test results:	Pass					

**Measurement data:**

Line:




Site : CCIS Shielding Room  
 Condition : FCC PART15 B QP LISN LINE  
 EUT : 3G SMART PHONE  
 Model : G0401  
 Test Mode : PC mode  
 Power Rating : AC120/60Hz  
 Environment : Temp: 23 °C Huni:56% Atmos:101KPa  
 Test Engineer: YT  
 Remark :

Freq	Read	LISN	Cable	Limit	Over	Remark
	Level	Factor	Loss	Level	Line	
MHz	dBuV		dB	dB	dBuV	dB
1	0.154	26.35	0.14	10.78	37.27	55.78 -18.51 Average
2	0.170	32.73	0.14	10.77	43.64	64.94 -21.30 QP
3	0.258	27.59	0.16	10.75	38.50	61.51 -23.01 QP
4	0.262	21.61	0.16	10.75	32.52	51.38 -18.86 Average
5	0.389	13.79	0.23	10.72	24.74	48.08 -23.34 Average
6	2.993	20.12	0.33	10.92	31.37	46.00 -14.63 Average
7	5.867	24.30	0.36	10.82	35.47	60.00 -24.53 QP
8	10.125	23.91	0.30	10.94	35.15	50.00 -14.85 Average
9	10.288	30.50	0.30	10.94	41.74	60.00 -18.26 QP
10	19.740	27.04	0.33	10.93	38.30	60.00 -21.70 QP
11	23.387	30.79	0.35	10.89	42.03	60.00 -17.97 QP
12	23.511	26.89	0.35	10.88	38.12	50.00 -11.88 Average

**Notes:**

- An initial pre-scan was performed on the line and neutral lines with peak detector.
- Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
- Final Level = Receiver Read level + LISN Factor + Cable Loss.

Neutral:



Site : CCIS Shielding Room  
 Condition : FCC PART15 B QP LISN NEUTRAL  
 EUT : 3G SMART PHONE  
 Model : G0401  
 Test Mode : PC mode  
 Power Rating : AC120/60Hz  
 Environment : Temp: 23 °C Huni:56% Atmos:101KPa  
 Test Engineer: YT  
 Remark :

	Read Freq	LISN Level	Cable Factor	Limit Loss	Line Level	Over Limit	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB
1	0.158	23.92	0.13	10.78	34.83	55.56	-20.73 Average
2	0.170	33.23	0.13	10.77	44.13	64.94	-20.81 QP
3	0.258	24.75	0.17	10.75	35.67	61.51	-25.84 QP
4	0.258	17.67	0.17	10.75	28.59	51.51	-22.92 Average
5	2.946	16.85	0.30	10.92	28.07	56.00	-27.93 QP
6	3.025	8.98	0.31	10.92	20.21	46.00	-25.79 Average
7	9.966	13.38	0.24	10.94	24.56	50.00	-25.44 Average
8	10.397	19.26	0.24	10.94	30.44	60.00	-29.56 QP
9	16.750	18.62	0.27	10.91	29.80	50.00	-20.20 Average
10	16.839	28.61	0.27	10.91	39.79	60.00	-20.21 QP
11	23.511	31.08	0.24	10.88	42.20	60.00	-17.80 QP
12	23.636	23.46	0.24	10.88	34.58	50.00	-15.42 Average

Notes:

- An initial pre-scan was performed on the line and neutral lines with peak detector.
- Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
- Final Level =Receiver Read level + LISN Factor + Cable Loss.


## 6.2 Radiated Emission

Test Requirement:	FCC Part 15 B Section 15.109				
Test Method:	ANSI C63.4:2014				
Test Frequency Range:	30MHz to 26000MHz				
Test site:	Measurement Distance: 3m (Semi-Anechoic Chamber)				
Receiver setup:	Frequency	Detector	RBW	VBW	Remark
	30MHz-1GHz	Quasi-peak	120kHz	300kHz	Quasi-peak Value
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
Limit:	Frequency	Limit (dBuV/m @3m)		Remark	
	30MHz-88MHz	40.0		Quasi-peak Value	
	88MHz-216MHz	43.5		Quasi-peak Value	
	216MHz-960MHz	46.0		Quasi-peak Value	
	960MHz-1GHz	54.0		Quasi-peak Value	
	Above 1GHz	54.0		Average Value	
		74.0		Peak Value	
Test setup:	<p>Below 1GHz</p> <p>Above 1GHz</p>				

Test Procedure:	1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.					
Test environment:	Temp.:	25 °C	Humid.:	55%	Press.:	1 01kPa
Test Instruments:	Refer to section 5.7 for details					
Test mode:	Refer to section 5.3 for details					
Test results:	Passed					
Remark:	All of the observed value above 6GHz were the noise floor , which were no recorded					

**Measurement Data:****Below 1GHz**


Horizontal:



Site : 3m chamber  
Condition : FCC PART15 CLASS B 3m VULB9163(30M3G) HORIZONTAL  
EUT : 3G SMART PHONE  
Model : G0401  
Test mode : PC Mode  
Power Rating : AC 120V/60Hz  
Environment : Temp:25.5°C Huni:55%  
Test Engineer: YT  
REMARK :

Freq	Read	Antenna	Cable	Preamp	Limit	Over	Remark
	MHz	Level	Factor	Loss	Level	Line	Limit
1	30.638	40.89	12.37	0.78	29.98	24.06	40.00 -15.94 QP
2	44.587	33.37	17.48	1.28	29.86	22.27	40.00 -17.73 QP
3	137.420	45.67	11.88	2.37	29.29	30.63	43.50 -12.87 QP
4	150.011	47.27	10.64	2.52	29.22	31.21	43.50 -12.29 QP
5	300.367	47.17	12.70	2.94	28.45	34.36	46.00 -11.64 QP
6	480.528	53.33	16.57	3.46	28.92	44.44	46.00 -1.56 QP

Vertical:




Site : 3m chamber  
Condition : FCC PART15 CLASS B 3m VULB9163(30M3G) VERTICAL  
EUT : 3G SMART PHONE  
Model : GO401  
Test mode : PC Mode  
Power Rating : AC 120V/60Hz  
Environment : Temp:25.5°C Huni:55%  
Test Engineer: YT  
REMARK :

Freq	Read	Antenna	Cable	Preamp	Limit	Over	Remark	
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	41.713	42.29	17.17	1.24	29.89	30.81	40.00	-9.19 QP
2	136.939	57.22	11.88	2.36	29.29	42.17	43.50	-1.33 QP
3	239.987	47.35	11.80	2.82	28.59	33.38	46.00	-12.62 QP
4	274.194	45.63	12.14	2.87	28.50	32.14	46.00	-13.86 QP
5	480.528	52.05	16.57	3.46	28.92	43.16	46.00	-2.84 QP
6	721.726	41.75	19.76	4.26	28.58	37.19	46.00	-8.81 QP

**Above 1GHz**


Horizontal:



Site : 3m chamber  
 Condition : FCC PART 15 (PK) 3m BBHA9120(1G18) HORIZONTAL  
 EUT : 3G SMART PHONE  
 Model : GO401  
 Test mode : PC Mode  
 Power Rating : AC 120V/60Hz  
 Environment : Temp:25.5°C Huni:55%  
 Test Engineer: YT  
 REMARK :

Freq	Read		Antenna		Cable	Preamp	Limit	Over	Line	Limit	Remark
	Level	Factor	Loss	Factor	Level	dBuV/m					
MHz	dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dBuV/m	dB	dB	dB
1	3322.198	50.38	27.05	5.54	41.37	41.60	74.00	-32.40	Peak		
2	3322.198	40.69	27.05	5.54	41.37	31.91	54.00	-22.09	Average		
3	4115.156	50.65	32.79	6.27	41.81	47.90	74.00	-26.10	Peak		
4	4115.156	40.27	32.79	6.27	41.81	37.52	54.00	-16.48	Average		
5	4941.121	50.18	36.64	6.90	41.86	51.86	74.00	-22.14	Peak		
6	4941.121	40.27	36.64	6.90	41.86	41.95	54.00	-12.05	Average		

Vertical:



Site : 3m chamber  
 Condition : FCC PART 15 (PK) 3m BBHA9120(1G18) VERTICAL  
 EUT : 3G SMART PHONE  
 Model : G0401  
 Test mode : PC Mode  
 Power Rating : AC 120V/60Hz  
 Environment : Temp:25.5°C Huni:55%  
 Test Engineer: YT  
 REMARK :

	Freq	Read	Antenna	Cable	Preamp	Limit	Over	Line	Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	dB	
1	3146.029	48.88	26.31	5.40	41.43	39.16	74.00	-34.84	Peak	
2	3146.029	38.25	26.31	5.40	41.43	28.53	54.00	-25.47	Average	
3	4163.484	49.39	33.01	6.34	41.81	46.93	74.00	-27.07	Peak	
4	4163.484	39.68	33.01	6.34	41.81	37.22	54.00	-16.78	Average	
5	4970.050	49.39	36.77	6.92	41.87	51.21	74.00	-22.79	Peak	
6	4970.050	39.62	36.77	6.92	41.87	41.44	54.00	-12.56	Average	