

FCC PART 15.247  
TEST REPORT

For

**NotAnotherOne Inc.**

100 Pine Street Suite 1250, San Francisco CA

**FCC ID: 2AHGD-ATMO-T01**

<b>Report Type:</b> Original Report	<b>Product Type:</b> The Portable Air Pollution Monitor
<b>Test Engineer:</b> Robin Zheng	<i>Robin Zheng</i>
<b>Report Number:</b> RDG160303008-00B	
<b>Report Date:</b> 2016-03-15	
<b>Reviewed By:</b> Dean Liu RF Engineer	<i>Dean Liu</i>
<b>Test Laboratory:</b>	Bay Area Compliance Laboratories Corp. (Dongguan) No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 <a href="http://www.baclcorp.com.cn">www.baclcorp.com.cn</a>

**Note:** This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Dongguan).

**TABLE OF CONTENTS**

**GENERAL INFORMATION.....4**

    PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....4

    OBJECTIVE.....4

    RELATED SUBMITTAL(S)/GRANT(S).....4

    TEST METHODOLOGY.....4

    TEST FACILITY.....4

**SYSTEM TEST CONFIGURATION.....5**

    DESCRIPTION OF TEST CONFIGURATION.....5

    EQUIPMENT MODIFICATIONS.....5

    EUT EXERCISE SOFTWARE.....5

    SUPPORT EQUIPMENT LIST AND DETAILS.....5

    EXTERNAL CABLE.....5

    BLOCK DIAGRAM OF TEST SETUP.....6

**SUMMARY OF TEST RESULTS.....8**

**FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE.....9**

    APPLICABLE STANDARD.....9

**FCC §15.203 - ANTENNA REQUIREMENT.....10**

    APPLICABLE STANDARD.....10

    ANTENNA CONNECTOR CONSTRUCTION.....10

**FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS.....11**

    APPLICABLE STANDARD.....11

    MEASUREMENT UNCERTAINTY.....11

    EUT SETUP.....11

    EMI TEST RECEIVER SETUP.....12

    TEST PROCEDURE.....12

    CORRECTED AMPLITUDE & MARGIN CALCULATION.....12

    TEST EQUIPMENT LIST AND DETAILS.....13

    TEST RESULTS SUMMARY.....13

    TEST DATA.....13

**FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS.....16**

    APPLICABLE STANDARD.....16

    MEASUREMENT UNCERTAINTY.....16

    EUT SETUP.....16

    EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP.....17

    TEST PROCEDURE.....17

    CORRECTED AMPLITUDE & MARGIN CALCULATION.....18

    TEST EQUIPMENT LIST AND DETAILS.....18

    TEST RESULTS SUMMARY.....18

    TEST DATA.....19

**FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH.....23**

    APPLICABLE STANDARD.....23

    TEST PROCEDURE.....23

    TEST EQUIPMENT LIST AND DETAILS.....23

    TEST DATA.....23

**FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER.....26**

APPLICABLE STANDARD .....26  
TEST PROCEDURE .....26  
TEST EQUIPMENT LIST AND DETAILS.....26  
TEST DATA .....26

**FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE.....28**

APPLICABLE STANDARD .....28  
TEST PROCEDURE .....28  
TEST EQUIPMENT LIST AND DETAILS.....28  
TEST DATA .....28

**FCC §15.247(e) - POWER SPECTRAL DENSITY .....30**

APPLICABLE STANDARD .....30  
TEST PROCEDURE .....30  
TEST EQUIPMENT LIST AND DETAILS.....30  
TEST DATA .....30



## GENERAL INFORMATION

---

### Product Description for Equipment under Test (EUT)

The *NotAnotherOne Inc.*'s product, model number: *Atmotube or (FCC ID: 2AHGD-ATMO-T01)* (the "EUT") in this report was a *The Portable Air Pollution Monitor*, which was measured approximately: 6.6 cm (L) x 2.2 cm (W) x 2.2 cm (H), rated input voltage: DC3.7V rechargeable Li-ion battery or DC5.0V charging from USB port.

*All measurement and test data in this report was gathered from production sample serial number: 160303008 (Assigned by BACL Dongguan). The EUT was received on 2016-03-04.*

### Objective

This report is prepared on behalf of *NotAnotherOne Inc.* in accordance with Part 2, Subpart J, Part 15, Subparts A, B and C of the Federal Communications Commission's rules

The tests were performed in order to determine the compliance of the EUT with FCC Part 15-Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

### Related Submittal(s)/Grant(s)

Not related submittal(s)/grant(s).

### Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Dongguan).

### Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China

Test site at Bay Area Compliance Laboratories Corp. (Dongguan) has been fully described in reports submitted to the Federal Communications Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 06, 2015.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 273710. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

## SYSTEM TEST CONFIGURATION

### Description of Test Configuration

The system was configured for testing in testing mode, which was provided by manufacturer.

For Bluetooth LE mode, 40 channels are provided for testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404	...	...
...	...	...	...
...	...	...	...
..	...	38	2478
19	2440	39	2480

EUT was tested with channel 0, 19 and 39.

The worst-case data rates are determined to be as follows for each mode based upon investigations by measuring the average power and PSD across all data rates bandwidths, and modulations.

### Equipment Modifications

No modification was made to the EUT tested.

### EUT Exercise Software

The worst condition (maximum power with 100% duty cycle) was setting by the software as following table:

Test Mode	Test Software Version	N/A		
BLE	Test Frequency	2402MHz	2440MHz	2480MHz
	BLE	N/A	N/A	N/A

### Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
Ktec	Adapter	KSA29B0500200HK	50052620

### External Cable

Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
USB Cable	No	No	0.6	USB Port of Adater	EUT


### Block Diagram of Test Setup

AC power-line conducted emissions:




**Radiated Emissions:**

Below 1GHz:



Above 1GHz:



**SUMMARY OF TEST RESULTS**

<b>FCC Rules</b>	<b>Description of Test</b>	<b>Result</b>
FCC §15.247 (i) & §1.1310 & §2.1093	RF Exposure	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	AC Line Conducted Emissions	Compliance
§15.247(d)	Spurious Emissions at Antenna Port	Compliance
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliance
§15.247(b)(3)	Maximum conducted output power	Compliance
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliance
§15.247(e)	Power Spectral Density	Compliance

## **FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE**

### **Applicable Standard**

According to §15.247(i) and §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB447498 D01 General RF Exposure Guidance v06:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

- $f(\text{GHz})$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

### **Measurement Result**

The tune-up conducted average power is -6.5 dBm (0.22mW).

$[(\text{max. power of channel, mW})/(\text{min. test separation distance, mm})][\sqrt{f(\text{GHz})}]$   
 $= 0.22/5 \cdot (\sqrt{2.48}) = 0.07 < 3.0$

**So the stand-alone SAR evaluation is not necessary.**

## **FCC §15.203 - ANTENNA REQUIREMENT**

---

### **Applicable Standard**

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

### **Antenna Connector Construction**

The EUT has one integral antenna arrangement for BT, and the antenna gain is -6 dBi, fulfill the requirement of this section. Please refer to the EUT photos.

**Result:** Compliance.

---

## **FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS**

---

### **Applicable Standard**

FCC§15.207

### **Measurement Uncertainty**

Compliance or non- compliance with a disturbance limit shall be determined in the following manner

FEMVAL

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter was connected to a 120 VAC/60 Hz power source

### EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

### Test Procedure

During the conducted emission test, the adapter was connected to the first LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

### Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

$$C_f = A_C + VDF$$

Herein,

$V_C$  (cord. Reading): corrected voltage amplitude

$V_R$ : reading voltage amplitude

$A_C$ : attenuation caused by cable loss

VDF: voltage division factor of AMN

$C_f$ : Correction Factor

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCS 30	830245/006	2015-12-10	2016-12-09
R&S	L.I.S.N	ESH2-Z5	892107/021	2015-07-16	2016-07-15
R&S	Two-line V-network	ENV 216	3560.6550.12	2015-11-26	2016-11-25
N/A	Coaxial Cable	1.8m	N/A	2015-05-06	2016-05-06
R&S	Test Software	EMC32	Version8.53.0	N/A	N/A

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

### Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207, with the worst margin reading of:

**8.0 dB at 0.545378 MHz in the Neutral conducted mode**

### Test Data


#### Environmental Conditions

<b>Temperature:</b>	25.1 °C
<b>Relative Humidity:</b>	55 %
<b>ATM Pressure:</b>	101 kPa

*The testing was performed by Robin Zheng on 2016-03-07.*

Test Mode:Charging& Transmitting


AC120 V, 60 Hz, Line:



Frequency (MHz)	QuasiPeak (dBµV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.495646	33.3	9.000	L1	9.8	22.8	56.1	Compliance
0.545378	36.9	9.000	L1	9.8	19.1	56.0	Compliance
0.665597	31.7	9.000	L1	9.8	24.3	56.0	Compliance
1.090848	32.7	9.000	L1	9.8	23.3	56.0	Compliance
1.209904	32.9	9.000	L1	9.8	23.1	56.0	Compliance
1.331304	33.9	9.000	L1	9.8	22.1	56.0	Compliance

Frequency (MHz)	Average (dBµV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.528270	25.0	9.000	L1	9.8	21.0	46.0	Compliance
0.545378	28.3	9.000	L1	9.8	17.7	46.0	Compliance
0.563041	23.1	9.000	L1	9.8	22.9	46.0	Compliance
0.681699	23.6	9.000	L1	9.8	22.4	46.0	Compliance
1.310256	24.5	9.000	L1	9.8	21.5	46.0	Compliance
1.430284	23.5	9.000	L1	9.8	22.5	46.0	Compliance

**AC120 V, 60 Hz, Neutral:**



Frequency (MHz)	QuasiPeak (dB $\mu$ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB $\mu$ V)	Comment
0.511698	36.4	9.000	N	9.7	19.6	56.0	Compliance
0.545378	40.8	9.000	N	9.7	15.2	56.0	Compliance
0.991374	33.1	9.000	N	9.8	22.9	56.0	Compliance
1.023481	33.4	9.000	N	9.8	22.6	56.0	Compliance
1.209904	32.9	9.000	N	9.8	23.1	56.0	Compliance
1.363512	30.8	9.000	N	9.8	25.2	56.0	Compliance

Frequency (MHz)	Average (dB $\mu$ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB $\mu$ V)	Comment
0.476287	27.6	9.000	N	9.7	18.8	46.4	Compliance
0.491712	29.0	9.000	N	9.7	17.1	46.1	Compliance
0.511698	33.1	9.000	N	9.7	12.9	46.0	Compliance
0.528270	37.2	9.000	N	9.7	8.8	46.0	Compliance
0.545378	38.0	9.000	N	9.7	8.0	46.0	Compliance
0.563041	33.1	9.000	N	9.7	12.9	46.0	Compliance

---

## **FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS**

---

### **Applicable Standard**


FCC §15.247 (d); §15.209; §15.205;

### **Measurement Uncertainty**

Compliance or non-compliance with a disturbance limit shall be determined in the following manner

FEMVA

**Above 1GHz:**



The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits. The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

The adapter was connected to a 120 VAC/60 Hz power source.

**EMI Test Receiver & Spectrum Analyzer Setup**

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz	/	Av

**Test Procedure**

During the radiated emission test, the adapter was connected to the first AC floor outlet and the other support equipments were connected to the second AC floor outlet.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

## Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Loss and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Loss} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

## Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCI	100224	2015-08-03	2016-08-02
Sunol Sciences	Antenna	JB3	A060611-3	2014-11-06	2017-11-05
HP	Amplifier	8447E	2434A02181	2015-09-01	2016-09-01
Agilent	Spectrum Analyzer	E4440A	SG43360054	2015-11-23	2016-11-22
ETS-Lindgren	Horn Antenna	3115	9808-5557	2015-09-06	2018-09-06
Mini-Circuit	Amplifier	ZVA-213-S+	054201245	2016-02-19	2017-02-19
R&S	Spectrum Analyzer	FSP 38	100478	2015-11-23	2016-11-22
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-01 1304	2014-06-16	2017-06-15
Quinstar	Amplifier	QLW- 18405536-JO	15964001001	2015-09-06	2016-09-06
N/A	Coaxial Cable	14m	N/A	2015-05-06	2016-05-06
N/A	Coaxial Cable	8m	N/A	2015-05-06	2016-05-06
N/A	Coaxial Cable	0.1m	N/A	2015-05-06	2016-05-06
E-Microwave	DC Blocking	EMDCB-00036	0E01201047	2015-05-06	2016-05-06

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

## Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Section 15.205, 15.209 and 15.247, with the worst margin reading of:

**5.3 dB at 798 MHz in the Horizontal polarization**

**Test Data**

**Environmental Conditions**

<b>Temperature:</b>	19.1°C
<b>Relative Humidity:</b>	41 %
<b>ATM Pressure:</b>	101.8 kPa

*\* The testing was performed by Robin Zheng on 2016-03-11..*


FEMVA

Test Mode: Transmitting


Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBµV/m)	Limit (dBµV/m)	Margin (dB)
	Reading (dBµV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)					
Low Channel: 2402 MHz									
2402	51.01	PK	H	25.65	3.66	0.00	80.32	N/A	N/A
2402	49.36	AV	H	25.65	3.66	0.00	78.67	N/A	N/A
2402	52.92	PK	V	25.65	3.66	0.00	82.23	N/A	N/A
2402	51.28	AV	V	25.65	3.66	0.00	80.59	N/A	N/A
2400	28.03	PK	V	25.64	3.65	0.00	57.32	74.00	16.68
2400	17.2	AV	V	25.64	3.65	0.00	46.49	54.00	7.51
4804	35.59	PK	V	30.59	5.06	27.41	43.83	74.00	30.17
4804	28.17	AV	V	30.59	5.06	27.41	36.41	54.00	17.59
7206	31.38	PK	V	34.09	6.61	25.91	46.17	74.00	27.83
7206	18.63	AV	V	34.09	6.61	25.91	33.42	54.00	20.58
9608	29.26	PK	V	35.96	8.53	27.55	46.20	74.00	27.80
9608	16.27	AV	V	35.96	8.53	27.55	33.21	54.00	20.79
3145	33.28	PK	V	27.66	6.97	27.41	40.50	74.00	33.50
3145	20.69	AV	V	27.66	6.97	27.41	27.91	54.00	26.09
798	37.7	QP	H	21.89	3.46	22.35	40.70	46.00	5.30
Middle Channel: 2440 MHz									
2440	50.96	PK	H	25.74	3.76	0.00	80.46	N/A	N/A
2440	49.21	AV	H	25.74	3.76	0.00	78.71	N/A	N/A
2440	52.86	PK	V	25.74	3.76	0.00	82.36	N/A	N/A
2440	51.13	AV	V	25.74	3.76	0.00	80.63	N/A	N/A
4880	39.62	PK	V	30.79	5.18	27.42	48.17	74.00	25.83
4880	32.44	AV	V	30.79	5.18	27.42	40.99	54.00	13.01
7320	32.59	PK	V	34.37	6.75	25.88	47.83	74.00	26.17
7320	19.22	AV	V	34.37	6.75	25.88	34.46	54.00	19.54
9760	29.39	PK	V	36.32	8.62	27.21	47.12	74.00	26.88
9760	16.43	AV	V	36.32	8.62	27.21	34.16	54.00	19.84
3145	33.41	PK	V	27.66	6.97	27.41	40.63	74.00	33.37
3145	20.82	AV	V	27.66	6.97	27.41	28.04	54.00	25.96
3730	33.13	PK	V	29.31	4.58	27.34	39.68	74.00	34.32
3730	20.52	AV	V	29.31	4.58	27.34	27.07	54.00	26.93
365.62	35.3	QP	H	15.70	2.32	21.68	31.64	46.00	14.36
High Channel: 2480 MHz									
2480	51.26	PK	H	25.85	3.68	0.00	80.79	N/A	N/A
2480	49.67	AV	H	25.85	3.68	0.00	79.20	N/A	N/A
2480	53.12	PK	V	25.85	3.68	0.00	82.65	N/A	N/A
2480	51.5	AV	V	25.85	3.68	0.00	81.03	N/A	N/A
2483.5	26.13	PK	V	25.86	3.67	0.00	55.66	74.00	18.34
2483.5	13.87	AV	V	25.86	3.67	0.00	43.40	54.00	10.60
4960	37.88	PK	V	31.00	5.34	27.43	46.79	74.00	27.21
4960	31.67	AV	V	31.00	5.34	27.43	40.58	54.00	13.42
7440	32.24	PK	V	34.66	6.89	25.97	47.82	74.00	26.18
7440	18.95	AV	V	34.66	6.89	25.97	34.53	54.00	19.47
9920	29.27	PK	V	36.71	8.71	26.66	48.03	74.00	25.97
9920	16.68	AV	V	36.71	8.71	26.66	35.44	54.00	18.56
3145	33.35	PK	V	27.66	6.97	27.41	40.57	74.00	33.43
3145	20.71	AV	V	27.66	6.97	27.41	27.93	54.00	26.07
216.24	36.2	QP	H	11.42	1.78	21.47	27.93	46.00	18.07

Conducted Spurious Emissions at Antenna Port

BLE Low Channel




BLE Middle Channel



### BLE High Channel

Ref Lvl 10 dBm  
Marker 2 [T1] -44.84 dBm  
4.93392786 GHz  
RBW 100 kHz RF Att 20 dB  
VBW 300 kHz  
SWT 6.4 s Unit dBm

Fundamental



---

## **FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH**

---

### **Applicable Standard**

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

### **Test Procedure**

According to KDB 558074 D01 DTS Meas Guidance v03r04

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW)

FEMVA


*Test Mode: Transmitting*

*Test Result: Compliant. Please refer to the following table and plots.*


Test mode	Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limit (MHz)
BLE	Low	2402	0.75	

FINAL

### BLE Middle Channel



### BLE High Channel



## FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER

### Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

### Test Procedure

According to KDB 558074 D01 DTS Meas Guidance v03r03

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to test equipment.
3. Add a correction factor to the display.



### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Agilent	Wideband Power Sensor	N1921A	MY54210016	2015-11-03	2016-11-03
Agilent	Wideband Power Sensor	N1921A	MY54170013	2015-11-03	2016-11-03
Agilent	P-Series Power Meter	N1912A	MY5000448	2015-11-03	2016-11-03
N/A	Coaxial Cable	0.1m	N/A	2015-05-06	2016-05-06
E-Microwave	DC Blocking	EMDCB-00036	0E01201047	2015-05-06	2016-05-06

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

### Test Data

#### Environmental Conditions

<b>Temperature:</b>	19.1°C
<b>Relative Humidity:</b>	41 %
<b>ATM Pressure:</b>	101.8 kPa

\* The testing was performed by Robin Zheng on 2016-03-11..

*Test Mode: Transmitting (BLE)*

Test mode	Channel	Frequency	Max Peak Conducted Output Power	Limit	Result
		(MHz)	(dBm)	(dBm)	
BLE	Low	2402	-7.28	30	Compliance
	Middle	2440	-7.91	30	Compliance
	High	2480	-6.78	30	Compliance

## **FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE**

### **Applicable Standard**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

### **Test Procedure**

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

### **Test Equipment List and Details**

<b>Manufacturer</b>	<b>Description</b>	<b>Model</b>	<b>Serial Number</b>	<b>Calibration Date</b>	<b>Calibration Due Date</b>
R&S	Spectrum Analyzer	FSEM	DE31388	2015-05-09	2016-05-09
N/A	Coaxial Cable	0.1m	N/A	2015-05-06	2016-05-06
E-Microwave	DC Blocking	EMDCB-00036	0E01201047	2015-05-06	2016-05-06

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

### **Test Data**

#### **Environmental Conditions**

<b>Temperature:</b>	19.1°C
<b>Relative Humidity:</b>	41 %
<b>ATM Pressure:</b>	101.8 kPa

\* The testing was performed by Robin Zheng on 2016-03-11..

*Test mode: Transmitting*

*Test Result: Compliant. Please refer to following plots.*

**BLE Band Edge**



---

**FCC §15.247(e) - POWER SPECTRAL DENSITY**

---

**Applicable Standard**

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

**Test Procedure**

According to KDB 558074 D01 DTS Meas Guidance v03r04

- a) Set analyzer center frequency to DTS channel center frequency.
- b) Set the span to 1.5 times the DTS bandwidth.
- c) Set the RBW to:  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ .
- d) Set the VBW  $\geq 3$


*Test Mode: Transmitting*

*Test Result: Compliant. Please refer to the following table and plots*

Test mode	Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)
BLE	Low	2402	-18.31	

FEMVA

**Power Spectral Density, BLE Middle Channel**



**Power Spectral Density, BLE High Channel**



\*\*\*\*\* END OF REPORT \*\*\*\*\*