

FCC PART 15.249


TEST REPORT

For

JM Manufacturing (HK) Ltd.

Unit G, 4/F Kaiser Estate, Phase 2, No. 47-53 Man Yue Street, Hung Hom, Kowloon, Hong Kong

FCC ID: 2AHGJJMSBJS9580-27

| | |
|--|---|
| Report Type: Original Report | Product Type: Radio Control Drift Climber Vehicle remote control |
| Report Number: RSZ200428831-00 | |
| Report Date: 2020-05-12 | |
| Reviewed By: RF Engineer | Jimmy Xiao  |
| Prepared By: | Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn |

Note: This report must not be used by the customer to claim product certification, approval, or endorsement by A2LA* or any agency of the Federal Government. This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk "★".

BACL is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk '*'. Customer model name, addresses, names, trademarks etc. are not considered data.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

TABLE OF CONTENTS

| | |
|---|-----------|
| GENERAL INFORMATION..... | 3 |
| PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) | 3 |
| OBJECTIVE | 3 |
| RELATED SUBMITTAL(S)/GRANT(S)..... | 3 |
| TEST METHODOLOGY | 3 |
| MEASUREMENT UNCERTAINTY..... | 4 |
| TEST FACILITY | 4 |
| SYSTEM TEST CONFIGURATION..... | 5 |
| JUSTIFICATION | 5 |
| EUT EXERCISE SOFTWARE | 5 |
| EQUIPMENT MODIFICATIONS | 5 |
| SUPPORT EQUIPMENT LIST AND DETAILS | 6 |
| SUPPORT CABLE DESCRIPTIONS..... | 6 |
| BLOCK DIAGRAM OF TEST SETUP | 6 |
| SUMMARY OF TEST RESULTS..... | 7 |
| TEST EQUIPMENT LIST | 8 |
| FCC§15.203 - ANTENNA REQUIREMENT..... | 9 |
| APPLICABLE STANDARD | 9 |
| ANTENNA CONNECTOR CONSTRUCTION | 9 |
| FCC§15.205, §15.209 & §15.249(D) - RADIATED EMISSIONS..... | 10 |
| APPLICABLE STANDARD | 10 |
| TEST EQUIPMENT SETUP..... | 10 |
| EUT SETUP..... | 11 |
| TEST PROCEDURE | 12 |
| CORRECTED AMPLITUDE & MARGIN CALCULATION | 12 |
| TEST RESULTS SUMMARY | 12 |
| TEST DATA | 12 |
| DUTY CYCLE | 16 |
| FCC§15.215(C) - 20DB EMISSION BANDWIDTH | 21 |
| APPLICABLE STANDARD | 21 |
| TEST PROCEDURE | 21 |
| TEST DATA | 21 |

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

| | |
|-----------------------|--|
| Product | Radio Control Drift Climber Vehicle remote control |
| Model | JMS-BJS9580 |
| Frequency Range | 2405~2479MHz |
| Antenna Specification | 4dBi |
| Voltage Range | DC 2*1.5V batteries |
| Date of Test | 2020/05/06~2020/05/07 |
| Sample serial number | RSZ200428831-RF-S1 (Assigned by BACL, Shenzhen) |
| Received date | 2020/04/28 |
| Sample/EUT Status | Good condition |

Objective

This type approval report is prepared on behalf of *JM Manufacturing (HK) Ltd.* in accordance with Part 2-Subpart J, and Part 15-Subparts A and C of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.209 and 15.249 rules.

Related Submittal(s)/Grant(s)

No Related Submittal(s)/Grant(s).

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All radiated and conducted emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

| Parameter | | Uncertainty |
|------------------------------------|------------|-------------|
| Occupied Channel Bandwidth | | ±5% |
| RF Output Power with Power meter | | ±0.73dB |
| RF conducted test with spectrum | | ±1.6dB |
| AC Power Lines Conducted Emissions | | ±1.95dB |
| Emissions, Radiated | Below 1GHz | ±4.75dB |
| | Above 1GHz | ±4.88dB |
| Temperature | | ±1 °C |
| Humidity | | ±6% |
| Supply voltages | | ±0.4% |

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 342867, the FCC Designation No.: CN1221.

The test site has been registered with ISED Canada under ISED Canada Registration Number 3062B.

SYSTEM TEST CONFIGURATION

Justification

The system was configured for testing by manufacturer.

Channel List:

| Channel | Frequency (MHz) | Channel | Frequency (MHz) |
|---------|-----------------|---------|-----------------|
| 0 | 2405 | 17 | 2456 |
| 2 | 2406 | 18 | 2457 |
| 3 | 2422 | 19 | 2458 |
| 4 | 2424 | 20 | 2459 |
| 5 | 2425 | 21 | 2467 |
| 6 | 2426 | 22 | 2468 |
| 7 | 2427 | 23 | 2469 |
| 8 | 2428 | 24 | 2470 |
| 9 | 2436 | 25 | 2471 |
| 10 | 2437 | 26 | 2472 |
| 11 | 2444 | 27 | 2473 |
| 12 | 2445 | 28 | 2474 |
| 13 | 2446 | 29 | 2476 |
| 14 | 2447 | 30 | 2477 |
| 15 | 2449 | 31 | 2479 |
| 16 | 2451 | | |

Channel 0, Channel 11 and Channel 31 were selected for testing.

EUT Exercise Software

No exercise software was used.

Equipment Modifications

No modifications were made to the unit tested.


Support Equipment List and Details

| Manufacturer | Description | Model | Serial Number |
|--------------|-------------|-------|---------------|
| / | / | / | / |

Support Cable Descriptions

| Cable Description | Length (m) | From/Port | To |
|-------------------|------------|-----------|----|
| / | / | / | / |

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

| FCC Rules | Description of Test | Result |
|-------------------------------|--|----------------|
| § 15.203 | Antenna Requirement | Compliance |
| § 15.207(a) | Conduction Emissions | Not Applicable |
| 15.205, § 15.209, § 15.249(d) | Radiated Emissions& Outside of Band Emission | Compliance |
| § 15.215 (c) | 20 dB Bandwidth | Compliance |

Not Applicable: The device is powered by battery only.

TEST EQUIPMENT LIST

| Manufacturer | Description | Model | Serial Number | Calibration Date | Calibration Due Date |
|-----------------------|--------------------|-------------------------|----------------|------------------|----------------------|
| R&S | EMI Test Receiver | ESR3 | 102455 | 2019/7/9 | 2020/7/8 |
| Sonoma instrument | Pre-amplifier | 310 N | 186238 | 2020/4/20 | 2021/4/19 |
| Sunol Sciences | Broadband Antenna | JB1 | A040904-1 | 2017/12/22 | 2020/12/21 |
| Unknown | Cable 2 | RF Cable 2 | F-03-EM197 | 2019/11/29 | 2020/11/28 |
| Unknown | Cable | Chamber Cable 1 | F-03-EM236 | 2019/11/29 | 2020/11/28 |
| Rohde & Schwarz | Auto test software | EMC 32 | V9.10 | NCR | NCR |
| Rohde & Schwarz | Spectrum Analyzer | FSV40-N | 102259 | 2019/7/22 | 2020/07/21 |
| COM-POWER | Pre-amplifier | PA-122 | 181919 | 2019/11/29 | 2020/11/28 |
| Quinstar | Amplifier | QLW-18405536-J0 | 15964001002 | 2019/11/29 | 2020/11/28 |
| Sunol Sciences | Horn Antenna | DRH-118 | A052604 | 2017/12/22 | 2020/12/21 |
| Insulted Wire Inc. | RF Cable | SPS-2503-3150 | 02222010 | 2019/11/29 | 2020/11/28 |
| Unknown | RF Cable | W1101-EQ1 OUT | F-19-EM005 | 2019/11/29 | 2020/11/28 |
| SNSD | Band Reject filter | BSF2402-2480MN-0898-001 | 2.4G filter | 2020/4/20 | 2021/4/19 |
| Ducommun Technologies | Horn antenna | ARH-4223-02 | 1007726-021304 | 2017/12/6 | 2020/12/5 |

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC§15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Antenna Connector Construction

The EUT has one internal antenna which was permanently attached and the antenna gain is 4 dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliance.

FCC§15.205, §15.209 & §15.249(d) - RADIATED EMISSIONS**Applicable Standard**

As per FCC§15.249 (a), except as provided in paragraph (b) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

| Fundamental frequency | Field strength of fundamental (millivolts/meter) | Field strength of harmonics (microvolts/meter) |
|-----------------------|--|--|
| 902–928 MHz | 50 | 500 |
| 2400–2483.5 MHz | 50 | 500 |
| 5725–5875 MHz | 50 | 500 |
| 24.0–24.25 GHz | 250 | 2500 |

As per FCC§15.249 (c), Field strength limits are specified at a distance of 3 meters.

As per FCC§15.249 (d), Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

Test Equipment Setup

The system was investigated from 30 MHz to 25 GHz.

| Frequency Range | RBW | Video B/W | IF B/W | Measurement |
|-------------------|---------|-----------|---------|-------------|
| 30 MHz – 1000 MHz | 100 kHz | 300 kHz | 120 kHz | QP |
| Above 1GHz | 1 MHz | 3 MHz | / | PK |


Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.


All final data was recorded in Quasi-peak detection mode for frequency range of 30 MHz -1 GHz and peak mode for frequencies above 1 GHz.

EUT Setup

Below 1GHz:



Above 1GHz:



The radiated emission and out of band emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209/15.205 and FCC 15.249 limits.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

The EUT is set 3 meter away from the testing antenna, which is varied from 1-4 meter, and the EUT is placed on a turntable, which is 0.8 meter above ground plane for below 1GHz or 1.5 meter for above 1GHz, the table shall be rotated for 360 degrees to find out the highest emission. The receiving antenna should be changed the polarization both of horizontal and vertical.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.205, 15.209 & §15.249


Test Data

Environmental Conditions

| | |
|---------------------------|-----------|
| Temperature: | 26 °C |
| Relative Humidity: | 60 % |
| ATM Pressure: | 101.0 kPa |

The testing was performed by Harris He on 2020-05-07 for below 1GHz and by Leven Gan on 2020-05-06 for above 1GHz.

Test Mode: Transmitting

30MHz – 1 GHz (worst case is low channel):

| Frequency (MHz) | Corrected Amplitude (dBμV/m) | Antenna height (cm) | Antenna Polarity | Turntable position (degree) | Correction Factor (dB/m) | Limit (dBμV/m) | Margin (dB) |
|-----------------|------------------------------|---------------------|------------------|-----------------------------|--------------------------|----------------|-------------|
| 30.727500 | 19.27 | 300.0 | H | 48.0 | -8.1 | 40.00 | 20.73 |
| 491.477500 | 22.51 | 300.0 | H | 261.0 | -5.7 | 46.00 | 23.49 |
| 580.353750 | 27.26 | 400.0 | V | 11.0 | -2.6 | 46.00 | 18.74 |
| 680.748750 | 27.77 | 100.0 | H | 0.0 | -1.4 | 46.00 | 18.23 |
| 834.251250 | 31.86 | 100.0 | H | 164.0 | 2.7 | 46.00 | 14.14 |
| 932.100000 | 34.32 | 100.0 | H | 0.0 | 4.8 | 46.00 | 11.68 |

Above 1 GHz:**Peak**

| Frequency (MHz) | Receiver | | Turntable Degree | Rx Antenna | | Corrected Factor (dB/m) | Corrected Amplitude (dBμV/m) | FCC Part 15.249&15.209 | |
|---------------------------|-------------------|------------|---------------------|---------------|----------------|-------------------------------|------------------------------------|---------------------------|----------------|
| | Reading (dBμV) | PK/QP/Ave. | | Height (m) | Polar (H/V) | | | Limit (dBμV/m) | Margin (dB) |
| Low Channel (2405 MHz) | | | | | | | | | |
| 2405.00 | 64.25 | PK | 308 | 1.8 | H | 31.87 | 96.12 | 114 | 17.9 |
| 2405.00 | 54.96 | PK | 134 | 1.9 | V | 31.87 | 86.83 | 114 | 27.2 |
| 2389.83 | 29.92 | PK | 310 | 1.9 | H | 31.87 | 61.79 | 74 | 12.21 |
| 2400.00 | 30.86 | PK | 213 | 2.4 | H | 31.87 | 62.73 | 74 | 11.27 |
| 2483.67 | 28.27 | PK | 44 | 1.7 | H | 32.13 | 60.40 | 74 | 13.60 |
| 4810.00 | 57.62 | PK | 285 | 1.2 | H | 6.28 | 63.90 | 74 | 10.10 |
| 7215.00 | 56.62 | PK | 212 | 1.8 | H | 11.93 | 68.55 | 74 | 5.45 |
| Middle Channel (2444 MHz) | | | | | | | | | |
| 2444.00 | 62.06 | PK | 80 | 2.1 | H | 31.97 | 94.03 | 114 | 20.0 |
| 2444.00 | 53.89 | PK | 227 | 2.4 | V | 31.97 | 85.86 | 114 | 28.1 |
| 4888.00 | 55.37 | PK | 357 | 1.2 | H | 6.76 | 62.13 | 74 | 11.87 |
| 7332.00 | 56.85 | PK | 124 | 1.4 | H | 11.66 | 68.51 | 74 | 5.49 |
| High Channel (2479 MHz) | | | | | | | | | |
| 2479.00 | 64.68 | PK | 136 | 1.0 | H | 32.13 | 96.81 | 114 | 17.2 |
| 2479.00 | 53.55 | PK | 232 | 1.4 | V | 32.13 | 85.68 | 114 | 28.3 |
| 2386.69 | 28.35 | PK | 81 | 1.4 | H | 31.87 | 60.22 | 74 | 13.78 |
| 2483.67 | 40.73 | PK | 317 | 2.3 | H | 32.13 | 72.86 | 74 | 1.14 |
| 4958.00 | 53.64 | PK | 40 | 1.9 | H | 6.80 | 60.44 | 74 | 13.56 |
| 7437.00 | 55.94 | PK | 76 | 1.5 | H | 12.39 | 68.33 | 74 | 5.67 |

Note:

Corrected Amplitude = Corrected Factor + Reading

Corrected Factor=Antenna factor (RX) +cable loss – amplifier factor

Margin = Limit- Corr. Amplitude

The emission more than 4dB below the limit was not required to be recorded.

Average

| Frequency | Peak value@3m | Rx Antenna | Corrected Factor (dB) | Corrected Amplitude (dBμV/m) | FCC Part 15.249&15.209 | |
|--------------------------|------------------|------------------|-----------------------------|------------------------------------|---------------------------|----------------|
| (MHz) | | Polar (H / V) | | | Limit (dBμV/m) | Margin (dB) |
| Low Channel(2405 MHz) | | | | | | |
| 2405.00 | 96.12 | H | -27.49 | 68.63 | 94 | 25.37 |
| 2405.00 | 86.83 | V | -27.49 | 59.34 | 94 | 34.66 |
| 2389.83 | 61.79 | H | -27.49 | 34.30 | 54 | 19.7 |
| 2400.00 | 62.73 | H | -27.49 | 35.24 | 54 | 18.76 |
| 2483.67 | 60.40 | H | -27.49 | 32.91 | 54 | 21.09 |
| 4810.00 | 63.90 | H | -27.49 | 36.41 | 54 | 17.59 |
| 7215.00 | 68.55 | H | -27.49 | 41.06 | 54 | 12.94 |
| Middle Channel(2444 MHz) | | | | | | |
| 2444.00 | 94.03 | H | -27.49 | 66.54 | 94 | 27.46 |
| 2444.00 | 85.86 | V | -27.49 | 58.37 | 94 | 35.63 |
| 4888.00 | 62.13 | H | -27.49 | 34.64 | 54 | 19.36 |
| 7332.00 | 68.51 | H | -27.49 | 41.02 | 54 | 12.98 |
| High Channel(2479 MHz) | | | | | | |
| 2479.00 | 96.81 | H | -27.49 | 69.32 | 94 | 24.68 |
| 2479.00 | 85.68 | V | -27.49 | 58.19 | 94 | 35.81 |
| 2386.69 | 60.22 | H | -27.49 | 32.73 | 54 | 21.27 |
| 2483.67 | 72.86 | H | -27.49 | 45.37 | 54 | 8.63 |
| 4958.00 | 60.44 | H | -27.49 | 32.95 | 54 | 21.05 |
| 7437.00 | 68.33 | H | -27.49 | 40.84 | 54 | 13.16 |

Note:

Corrected Amplitude = Corrected Factor + Reading

Corrected Factor=Antenna factor (RX) +cable loss – amplifier factor

Margin = Limit- Corr. Amplitude


Duty Cycle = Ton/Tp*100%, Ton =7* (Ton1+Ton2+Ton3+Ton4) =4.22ms, Tp= 100ms

Duty Cycle Factor = 20lg(Duty Cycle) = -27.49

AV=PK+20*lg(Duty Cycle)


Duty cycle

DC-Tp




Date: 6.MAY.2020 21:03:40

DC-Ton1




Date: 6.MAY.2020 21:07:59

DC-Ton2




Date: 6.MAY.2020 21:08:33

DC-Ton3




Date: 6.MAY.2020 21:09:13

DC-Ton4




Date: 6.MAY.2020 21:09:38

Pre-scan with high channel Peak Horizontal




Date: 6.MAY.2020 22:06:17




Date: 6.MAY.2020 22:42:43

Vertical



Date: 6.MAY.2020 22:11:05



Date: 6.MAY.2020 22:47:09

FCC§15.215(c) - 20DB EMISSION BANDWIDTH**Applicable Standard**

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in § 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

Test Procedure

Per ANSI C63.10-2013 §6.4 & §6.9.

Test Data**Environmental Conditions**

| | |
|---------------------------|-----------|
| Temperature: | 23 °C |
| Relative Humidity: | 65 % |
| ATM Pressure: | 101.0 kPa |


The testing was performed by Leven Gan on 2020-05-06.

Test Mode: Transmitting

Please refer to the following table and plots.


| Channel | Frequency (MHz) | 20dB Bandwidth (MHz) |
|----------------|------------------------|-----------------------------|
| Low | 2405 | 1.22 |
| Middle | 2444 | 1.22 |
| High | 2479 | 1.23 |

Low Channel




Date: 6.MAY.2020 21:31:55

Middle Channel



Date: 6.MAY.2020 21:34:48

High Channel



Date: 6.MAY.2020 21:54:09

***** END OF REPORT *****