

RF Exposure evaluation

Product Description: Plant Pot Speaker

Model Number: PLTPTSPK

FCC ID: 2AHHEPLTPTSPK

According to 447498 D01 General RF Exposure Guidance v05 The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by: $[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

According to the follow transmitter output power (P_t) formula:

$$P_t = (E \times d)^2 / (30 \times g_t)$$

P_t =transmitter output power in watts

g_t =numeric gain of the transmitting antenna (unitless)

E =electric field strength in V/m

d =measurement distance in meters (m)

According to the formula described above:

$$E_{\text{max}} = 87.69 \text{ dBuV/m} = 0.024 \text{ V/m}, d = 3 \text{ m}, g_t = 2.14$$

$$P_t = (E \times d)^2 / (30 \times g_t) = (0.024 \times 3)^2 / (30 \times 2.14) = 8.07476636 \text{ W} = 8.07 \text{ mW}$$

The result is rounded to one decimal place for comparison

Worse case is as below: [2402MHz 6.67 mW output power]

$$(8.07 \text{ mW} / 5 \text{ mm}) \cdot [\sqrt{2.402 \text{ GHz}}] = 2.50 < 3.0 \text{ for 1-g SAR}$$

Then SAR evaluation is not required

NOTE: For the maximum power, you can refer FCC test report.