



849 NW STATE ROAD 45  
NEWBERRY, FL 32669 USA  
PH: 888.472.2424 OR  
352.472.5500  
FAX: 352.472.2030  
EMAIL: [INFO@TIMCOENGR.COM](mailto:INFO@TIMCOENGR.COM)  
[HTTP:// WWW.TIMCOENGR.COM](http://WWW.TIMCOENGR.COM)

---

## RF Exposure Evaluation Report

<b>APPLICANT</b>	COMTRONIX COMMUNICATIONS INC.
	42327 RIO NEDO, SUITE A TEMECULA CA 92590 USA
<b>FCC ID</b>	2AHIALBR100C
<b>IC</b>	21255-LBR100C
<b>MODEL NUMBER</b>	LBR-100
<b>PRODUCT DESCRIPTION</b>	VHF LOW BAND REPEATER
<b>STANDARD APPLIED</b>	CFR 47 Part 2.1091
<b>PREPARED BY</b>	CORY LEVERETT

We, TIMCO ENGINEERING, INC. would like to declare that the device has been evaluated in accordance with 47 CFR Part 2.1091 and meets the requirements.

The attached report shall not be reproduced except in full without the written approval of TIMCO ENGINEERING, INC.

## GENERAL REMARKS

### Attestations

This equipment has been evaluated in accordance with the standards identified in this report. To the best of my knowledge and belief, these evaluations were performed using the procedures described in this report.

I attest that the necessary evaluations were made, under my supervision, at:

**Timco Engineering Inc.**  
**849 NW State Road 45**  
**Newberry, FL 32669**



**Authorized Signatory Name:** \_\_\_\_\_

Cory Leverett

Engineering Project Manager

**Date:** 3/31/2016

Applicant: COMTRONIX COMMUNICATIONS INC.  
FCC ID: 2AHIALBR100C  
Report: V:\C\COMTRONIX\514AUT16\514AUT16RF EXP MPE RPT\_REV3.DOCX

# RF Exposure Requirements

## General information

Device type: VHF LOW BAND REPEATER

Devices that operate under Part 90 of this chapter are subject to RF exposure evaluation prior to equipment authorization or use.

## Antenna

The manufacturer does not specify an antenna, but a typical antenna has a gain of 0 dBi.

Configuration	Antenna p/n	Type	Max. Gain (dBi)
Fixed mounted to permanent structures.	Any	omni	0

## Operating configuration and exposure conditions:

The conducted output power is shown in the table below.

## MPE Calculation:

The minimum separation distance is calculated as follows:

$$E(V/m) = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power density: } P_d(mW/cm^2) = \frac{E^2}{3770}$$

The limit for general uncontrolled exposure environment is shown in FCC rule Part 1.11310, Table 1.

Minimum Separation Distance for Mobile or Fixed Devices General Population/Uncontrolled Exposure						
Insert values in yellow highlighted boxes to determine Minimum Separation Distance						
Max Power	123.02	W	<i>equals</i>	Max Power	123020	mW
Duty Cycle	50.00	%	<i>equals</i>	Duty Factor	0.5	numeric
Antenna Gain	0	dBi	<i>equals</i>	Gain numeric	1	numeric
Coax Loss	0	dB		Gain - Coax Loss	1	numeric
Power Density	0.2	mW/cm <sup>2</sup>				
<b>Enter power Density from the chart to the right</b>				<b>Rule Part 1.1310, Table 1 (B)</b>		
Frequency	50	MHz		Frequency range	Power density	Enter this value
				MHz	mW/cm <sup>2</sup>	mW/cm <sup>2</sup>
				0.3-1.34	100	100
				1.34-30	180/f <sup>2</sup>	0.1
				30-300	0.2	0.2
				300-1,500	f/1500	0.0
				1,500-100,000	1	1
				f = frequency in MHz		
<b>Minimum Separation Distance</b>				<b>156 cm</b>		<b>1.56 m</b>
Minimum Separation in Inches	61.54422		Inches			

Applicant: COMTRONIX COMMUNICATIONS INC.

FCC ID: 2AHIALBR100C

Report: V:\C\COMTRONIX\514AUT16\514AUT16RF EXP MPE RPT\_REV3.DOCX