



Prüfbericht-Nr.: <i>Test report no.:</i>	60448574-002	Auftrags-Nr.: <i>Order no.:</i>	23870393 030	Seite 1 von 19 <i>Page 1 of 19</i>
Kunden-Referenz-Nr.: <i>Client reference no.:</i>	-	Auftragsdatum: <i>Order date:</i>	2020.06.24	
Auftraggeber: <i>Client:</i>	Sensative			
Prüfgegenstand: <i>Test item:</i>	Multi sensor strip			
Bezeichnung / Typ-Nr.: <i>Identification / Type no.:</i>	FCC ID: 2AHIR-004			
Auftrags-Inhalt: <i>Order content:</i>	Accredited testing			
Prüfgrundlage: <i>Test specification:</i>	FCC 47 CFR Part 15B with parts 15.107 & 15.109 ANSI C63.4: 2014			
Wareneingangsdatum: <i>Date of sample receipt:</i>	2020.06.24			
Prüfmuster-Nr.: <i>Test sample no.:</i>	A003003480-001			
Prüfzeitraum: <i>Testing period:</i>	2021.03.05 – 2021.03.10			
Ort der Prüfung: <i>Place of testing:</i>	Lund, Sweden			
Prüflaboratorium: <i>Testing laboratory:</i>	TÜV Rheinland Sweden			
Prüfergebnis*: <i>Test result*:</i>	Pass			
überprüft von: <i>reviewed by:</i>		genehmigt von: <i>authorized by:</i>		
Datum: 2021.09.29 <i>Date:</i>	Signed by: Sam Ebadeh	Datum: 2021.09.29 <i>Date:</i>	Signed by: Per Isacson	
Stellung / Position:	Technical Expert	Stellung / Position:	Managing Director	
Sonstiges / Other:				
Zustand des Prüfgegenstandes bei Anlieferung: <i>Condition of the test item at delivery:</i>		Prüfmuster vollständig und unbeschädigt <i>Test item complete and undamaged</i>		
* Legende:	1 = sehr gut P(ass) = entspricht o.g. Prüfgrundlage(n)	2 = gut F(ail) = entspricht nicht o.g. Prüfgrundlage(n)	3 = befriedigend N/A = nicht anwendbar	4 = ausreichend N/T = nicht getestet
* Legend:	1 = very good P(ass) = passed a.m. test specification(s)	2 = good F(ail) = failed a.m. test specification(s)	3 = satisfactory N/A = not applicable	4 = sufficient N/T = not tested
<p>Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts.</i></p>				

Revision History⁶⁰⁴⁴⁸⁵⁷⁴⁻⁰⁰²⁶⁰⁴⁴⁸⁵⁷⁴⁻⁰⁰²

REVISION	DATE	REMARKS	AUTHOR
001	2021.08.27	First release	Sam Ebadeh
002	2021.09.29	Updated highest frequency and FCC ID	Sam Ebadeh

Note: Latest revision report will replace all previous reports
This report based on FCC Part 15B no JBP Template version 1.1

Summary of Test Results

FCC 47 CFR Rule Part	Test Description	Applicability	Report Section	RESULT	REMARKS
15.107	AC Power Line Conducted Emissions (Unintentional Radiators)	NO	4.1	N/A	No AC power input
15.109	Radiated Emissions (Unintentional Radiators)	YES	4.2	PASS	

Possible test case verdicts:

- Test case does not apply to the test object: N/A
- Test object complies with the requirement: PASS or COMPLIANT
- Test object does not meet the requirement: FAIL or NOT COMPLIANT
- Test case not performed on the test object: N.P.

Table of Contents

1. GENERAL INFORMATION	4
1.1 Test Site	4
1.2 Client Information	4
2. PRODUCT INFORMATION.....	5
2.1 General Description.....	5
2.2 Device Characteristics.....	5
2.3 Test Samples	5
2.4 Wireless Technologies and Bands Supported by the EUT.....	5
2.5 Antenna Information.....	6
2.6 Wireless Technology Details	6
2.7 Ancillary Equipment.....	6
2.8 EUT Diagrams.....	6
3. TEST METHODS	7
3.1 Test Standards.....	7
3.2 Additional references.....	7
3.3 Limits	8
3.4 Description of Test Methods and Equipment Setup	9
3.5 EUT Configuration During Test.....	12
3.6 EUT Operation Modes.....	12
3.7 Deviations from the Test Standard	12
3.8 Environmental Conditions.....	13
4. TEST RESULTS	14
4.1 Test Results – AC Power Line Conducted Emissions (Unintentional Trans.)	14
4.2 Test Results – Radiated Emissions (Unintentional Transmitter).....	14
5. TEST EQUIPMENT STATUS.....	17
5.1 List of Hardware with Calibration Dates	17
5.2 Software / Firmware Versions.....	18
6. MEASUREMENT UNCERTAINTY	18
6.1 Measurement Uncertainty for Conducted Emissions	18
6.2 Measurement Uncertainty for SAC 5 (Radiated Emissions & Band Edge)	18
7. PHOTOGRAPHS.....	19
7.1 Photographs of the EUT.....	19

1. GENERAL INFORMATION

1.1 Test Site

Test Facility:	TÜV Rheinland Sweden AB
Address:	Mobilvägen 10
	223 62 Lund
	Sweden
Swedac Registration Number:	10325
FCC Test Firm Registration Number:	517458
ISED Test Site Registration Number:	24753

1.2 Client Information

Company Name:	Sensitive AB
Address:	Mobilvägen 10
	223 62 Lund
	Sweden
Contact Person:	Lars Jonsson
Contact e-Mail / Telephone	Lars.Jonsson@sensitive.com / +46 70 302 37 67

2. PRODUCT INFORMATION

2.1 General Description

Model name:	Multi sensors strip
Manufacturer:	Sensitive AB
Model number / Marketing name:	1300002, 1301002, 1302002, 1303002, 1304002, 1305002, 1306002
FCC ID:	FCC ID: 2AHIR-004
Description:	Multi sensors using LoRa radio technology
Ancillary Equipment:	None.

2.2 Device Characteristics

Device Class for 47 CFR Part 15 B	Class B
Type of Power Supply	External
Nominal Supply Voltage	DC
Supply Voltage Range	1.71 V to 3.6 V
Operating Temperature Range	-20°C to +60°C
Operating Air Humidity Range	0-80% RH
Highest Internal Frequency Source	914.9 MHz

2.3 Test Samples

EUT #	EUT ID	Description	Used For:
1	A003003480-001	Standard test sample	Radiated Emissions

2.4 Wireless Technologies and Bands Supported by the EUT

Technology	Band	Frequency Range (Tx)	Evaluation Performed*
LoRa	900 MHz	902.3 MHz – 914.9 MHz	YES

*This statement refers only to this report. Other wireless technologies may be covered by other reports.

2.5 Antenna Information

Technology	Band	Number of Antennas	Antenna Type(s)	Gain
LoRa	900 MHz	1	PCB Antenna	+2.3 dBi

2.6 Wireless Technology Details

Technology	Band	Modulation Type(s)	No. of Channels	Channel Spacing	Adaptivity
LoRa (DTS)	900 MHz	CSS	8	1.6 MHz	N/A
LoRa (FHSS)	900 MHz	CSS	64	200 kHz	N/A

2.7 Ancillary Equipment

None

2.8 EUT Diagrams

N/A

3. TEST METHODS

3.1 Test Standards

Testing was performed according to the following standards / references

Standard	Version	Description
FCC 47 CFR 15.107	-	Conducted limits
FCC 47 CFR 15.109	-	Radiated emission limits

3.2 Additional references

The following standards / references were also considered for the testing

Standard	Version	Description
ANSI C63.4	2014	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz

3.3 Limits

FCC 47 CFR Rule Part	Test Description	Limit Reference (FCC 47 CFR Reference)
15.107	AC Power Line Conducted Emissions (Unintentional Radiators)	15.107 §(a) for Class B Devices§
15.109	Radiated Emissions (Unintentional Radiators)	15.109 §(a) for Class B Devices§ *See Note 1

Note 1

Radiated Emissions limits in the tables from 47 CFR sections 15.109 are presented in $\mu\text{V}/\text{m}$. Measurements on the test system are made in $\text{dB}\mu\text{V}/\text{m}$. To convert between these, the following adjustment is used:

$$\text{New Limit} = 20 \log \left(\frac{\text{Original Limit}}{10^6} \right) + 120$$

Example: from 15.209(a) the limit for 30MHz – 88MHz is $100\mu\text{V}/\text{m}$ at 3m. This gives:

$$\text{New Limit} = 20 \log \left(\frac{100}{10^6} \right) + 120 = 40\text{dB}\mu\text{V}/\text{m} \text{ at } 3\text{m}$$

Additionally, in some cases testing has been performed at distances other than those specified in the tables. When this has occurred, the limits have been adjusted in accordance with the requirements in 47 CFR 15.31, using an extrapolation factor of 40dB/decade at frequencies below 30MHz and 20dB/decade at or above 30MHz

Example: from 15.209(a) the limit for 1.705MHz – 30MHz is $30\mu\text{V}/\text{m}$ (=29.54 $\text{dB}\mu\text{V}/\text{m}$) at 30m

$$\text{Limit@3m} = \text{Limit@30m} + 40 \log \left(\frac{30}{3} \right) = 29.54 + 40.00 = 69.54 \text{ dB}\mu\text{V}/\text{m} \text{ at } 3\text{m}$$

Example: from 15.209(a) the limit for 1GHz – 18GHz is $500\mu\text{V}/\text{m}$ (=53.98 $\text{dB}\mu\text{V}/\text{m}$) at 3m

$$\text{Limit@1m} = \text{Limit@3m} + 20 \log \left(\frac{3}{1} \right) = 53.98 + 9.54 = 63.52 \text{ dB}\mu\text{V}/\text{m} \text{ at } 1\text{m}$$

3.4 Description of Test Methods and Equipment Setup

3.4.1 General Description

Testing was performed in accordance with the various requirements of ANSI C63.4 and ANSI C63.10. Any deviations from the test methods are described in section 3.7


Where different arrangements of equipment were used for different types of measurements, these are tabulated in section 3.4.2 and details of each arrangement are included in subsequent sections

3.4.2 Test Equipment Setup Used by Test Type

FCC 47 CFR Rule Part	Test Description	Test Equipment Used
15.107	AC Power Line Conducted Emissions (Unintentional Radiators)	Conducted Emissions
15.109	Radiated Emissions (Unintentional Radiators)	SAC5

3.4.3 Test Equipment Setup – Conducted Emissions


- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The LISNs provide 50Ω/ 50μH of coupling impedance for the measuring instrument.
- The lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150 kHz to 30 MHz was searched. Emission levels over 10 dB under the prescribed limits could not be reported.




3.4.4 Test Equipment Setup – SAC 5 (Radiated Emissions)

- For frequency range 30MHz-1GHz Log-Periodic Antenna was used. Antenna elevated from 100 cm from floor to 400 cm from floor, and was placed at 3 m from center of turntable in tilted position. The equipment under test (EUT) was placed at the middle of the turntable at 150 cm height from floor. The antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations. Repeat the measurement steps until the maximum emissions were obtained.
- For frequency range 1GHz-18GHz horn Antenna was used. Antenna elevated from 100 cm from floor to 200 cm from floor, and was placed at 3 m from center of turntable. The equipment under test (EUT) was placed at the middle of the turntable at 150 cm height from floor. The antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations. Repeat the measurement steps until the maximum emissions were obtained.
- For frequency range 18GHz-40GHz double horn Antenna was used. Antenna's height was adjusted to 150 cm from floor, and 1 m distance to center of turntable. The equipment under test (EUT) was placed at the middle of the turntable on at 150 cm height from floor.
- For all frequency ranges the turntable was rotated 360° for obtaining the maximum emission.


SAC 5 Test Setup Configuration 30MHz – 1GHz



SAC 5 Test Setup Configuration 1GHz – 18GHz



SAC 5 Test Setup Configuration 18GHz – 40GHz



3.5 EUT Configuration During Test

N/A

3.6 EUT Operation Modes

Operation mode	Description
RX	Unit was powered up and set to RX mode.

3.7 Deviations from the Test Standard

None

3.8 Environmental Conditions

3.8.1 Environmental Conditions – SAC5 (Radiated Emissions)

Environmental Conditions Log – SAC5

Date	Time	Temperature (°C)	Relative Humidity (%)
2021.03.05	07:25	18.3	33
2021.03.10	08:45	18.6	27

4. TEST RESULTS

4.1 Test Results – AC Power Line Conducted Emissions (Unintentional Trans.)

4.1.1 AC Power Line Conducted Emissions (Unintentional) – Test Summary

Requirement not applicable as the device have no AC Power input.

4.2 Test Results – Radiated Emissions (Unintentional Transmitter)


4.2.1 Radiated Emissions (Unintentional) – Test Summary

Test Specification	FCC 47 CFR 15.109 (Part 15 Subpart B)	
Test Engineer & Date	Sam Ebadeh	2021.03.05
EUT and Ancillary Equipment IDs	A003003480-001	N/A
EUT Operation Mode(s)	RX	
EUT Wireless Configuration(s)	RX	
EUT Hardware Configuration(s)	N/A	
Overall Result	PASS	
Test Parameter	Frequency Range	Result*
Radiated Emissions - Idle Mode	30 MHz – 1 GHz	PASS
Radiated Emissions - Idle Mode	1 GHz – 18 GHz	PASS

* For detailed measurements, see tables and graphs in sections below

4.2.2 Radiated Emissions (Unintentional) – Test Details
30MHz – 1GHz


Test mode condition	RX	
Antenna orientation	Horizontal and Vertical	
Sweep frequency	30 MHz – 1 GHz	
Standard	47 CFR FCC Part 15 subpart B	
EUT	A003003480-001	
Ancillary Equipment	N/A	
Test Engineer	Sam Ebadeh	Date: 2021-03-05
Chamber details	Chamber: SAC 5	



Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)
30.510493	16.53	40.00	23.47	1000.0	120.000	154.0	V	296.0
39.727920	10.62	40.00	29.38	1000.0	120.000	320.0	V	266.0
50.389880	4.05	40.00	35.95	1000.0	120.000	270.0	V	64.0
79.906080	5.70	40.00	34.30	1000.0	120.000	204.0	V	142.0
85.394400	5.71	40.00	34.29	1000.0	120.000	100.0	H	252.0
117.045240	7.01	43.52	36.51	1000.0	120.000	221.0	V	53.0
434.382200	10.24	46.02	35.78	1000.0	120.000	125.0	H	335.0
566.118480	12.83	46.02	33.19	1000.0	120.000	220.0	H	158.0
762.744680	17.45	46.02	28.57	1000.0	120.000	270.0	H	158.0
959.240800	17.71	46.02	28.31	1000.0	120.000	225.0	H	202.0

1GHz – 18GHz

Test mode condition	RX	
Antenna orientation	Horizontal and Vertical	
Sweep frequency	1 GHz – 18 GHz	
Standard	47 CFR FCC Part 15 subpart B	
EUT	A003003480-001	
Ancillary Equipment	N/A	
Test Engineer	Sam Ebadeh	Date: 2021-03-10
Chamber details	Chamber: SAC 5	



Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)
1205.401000	37.33	---	73.98	36.65	1000.0	1000.000	100.0	H	98.0
1223.148000	---	25.18	53.98	28.80	1000.0	1000.000	293.0	H	-8.0
2357.475000	43.72	---	73.98	30.26	1000.0	1000.000	293.0	V	52.0
2371.620000	---	30.80	53.98	23.17	1000.0	1000.000	293.0	V	8.0
3129.086000	---	36.57	53.98	17.40	1000.0	1000.000	393.0	V	222.0
3137.324000	49.30	---	73.98	24.68	1000.0	1000.000	108.0	V	42.0
5892.332000	55.60	---	73.98	18.38	1000.0	1000.000	385.0	H	308.0
5981.525000	---	44.00	53.98	9.98	1000.0	1000.000	243.0	H	8.0
8271.564000	---	31.78	53.98	22.20	1000.0	1000.000	385.0	H	8.0
9743.455000	45.47	---	73.98	28.51	1000.0	1000.000	385.0	V	96.0
17990.880000	54.93	---	73.98	19.05	1000.0	1000.000	265.0	H	278.0
17992.113000	---	41.79	53.98	12.19	1000.0	1000.000	185.0	H	172.0

5. TEST EQUIPMENT STATUS

5.1 List of Hardware with Calibration Dates

5.1.1 Hardware List – Conducted Emissions System

Type	Manufacturer	Model	Serial Number / ID	Calibration Date	Calibration Due
Two-Line V-network	Rohde & Schwarz	ENV216	101090 2704076	2020.07.16	2021.07.16
Test Receiver 9KHz to 3.5 GHz	Rohde & Schwarz	ESR3	101674 2704016	2020.07.17	2021.07.17

5.1.2 Hardware List – SAC5 System

Type	Manufacturer	Model	Serial Number / ID	Calibration Date	Calibration Due
EMI Test Receiver	Rohde & Schwarz	ESW44	101760 2881044	2020.07.17	2021.07.17
Ultra Broadband Antenna	Rohde & Schwarz	HL562E	100988 2823181	2019.07.23	2021.07.23
Double Ridged Waveguide Horn Antenna	Rohde & Schwarz	HF907	102678 2823164	2019.07.15	2021.07.15
Control Device	Maturo	NCD	NCD/393/2372.01	N/A	N/A
Open Switch & Control Unit	Rohde & Schwarz	OSP150	100081 2884198	2020.08.04	2021.08.04
Open Switch & Control Unit	Rohde & Schwarz	OSP120	100084 2761253	2020.08.04	2021.08.04
Shielded Filter Unit	Rohde & Schwarz	OSP-F Extension	101333 2761265	2020.08.04	2021.08.04
Shielded Filter Unit	Rohde & Schwarz	OSP-F Extension	101335 2761266	2020.08.04	2021.08.04
Shielded Filter Unit	Rohde & Schwarz	OSP-F Base Unit	101330 2761262	2020.08.04	2021.08.04
Humidity Temperature Probe	Lufft	OPUS 20	1236.0118.0802.033 2771042	2020.07.31	2022.07.31

5.2 Software / Firmware Versions

Equipment	Software / Firmware Name	Version
Conducted Emissions System	EMC 32	V10.60.10
SAC 5	EMC 32	V10.60.10

6. MEASUREMENT UNCERTAINTY

6.1 Measurement Uncertainty for Conducted Emissions

Parameter	Uncertainty (Coverage Factor k=2)
Conducted emissions with LISN 150KHz to 30 MHz	2.98 dB

6.2 Measurement Uncertainty for SAC 5 (Radiated Emissions & Band Edge)

Parameter	Uncertainty (Coverage Factor k=2)
Field Strength 10 Hz -9 kHz	3.38 dB
Field Strength 9 kHz -30 MHz	3.38 dB
Field Strength 30 MHz -1000 MHz	3.38 dB
Field Strength 1 GHz -18 GHz	4.88 dB
Field Strength 18 GHz - 40 GHz	5.14 dB

7. PHOTOGRAPHS

7.1 Photographs of the EUT

For photographs see appendix.