



Test Report No.: RF170410W004-5



# FCC TEST REPORT (PART 27)

**Product:** LTE Digital Mobile Phone

**Model Name:** NX597J

**FCC ID:** 2AHJO-NX597J

**Applicant:** Nubia Technology Co., Ltd.

**Address:** 10/F, Tower A, Hans Innovation Mansion, North Ring Rd., No. 9018, Hi-Tech Industrial Park, Nanshan District, Shenzhen, P.R.China

**Manufacturer:** Nubia Technology Co., Ltd.

**Address:** 10/F, Tower A, Hans Innovation Mansion, North Ring Rd., No. 9018, Hi-Tech Industrial Park, Nanshan District, Shenzhen, P.R.China

**Prepared by:** Bureau Veritas Shenzhen Co., Ltd. Dongguan Branch

**Lab Location:** No. 34, Chenwulu Section, Guantai Rd., Houjie Town, Dongguan City, Guangdong 523942, China

**TEL:** +86 769 8593 5656

**FAX:** +86 769 8593 1080

**E-MAIL:** [customerservice.dg@cn.bureauveritas.com](mailto:customerservice.dg@cn.bureauveritas.com)

**Report No.:** RF170410W004-5

**Received Date:** Apr. 10, 2017

**Test Date:** Apr. 11, 2017 ~ Apr. 25, 2017

**Issued Date:** Apr. 26, 2017

This report should not be used by the client to claim product certification, approval, or endorsement by A2LA or any government agencies.

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification

Bureau Veritas Shenzhen Co., Ltd.  
Dongguan Branch

No. 34, Chenwulu Section, Guantai Rd.,  
Houjie Town, Dongguan City,  
Guangdong 523942, China

Tel: +86 769 8593 5656  
Fax: +86 769 8593 1080  
Email: [customerservice.dg@cn.bureauveritas.com](mailto:customerservice.dg@cn.bureauveritas.com)



Test Report No.: RF170410W004-5

## TABLE OF CONTENTS

|                                                                |           |
|----------------------------------------------------------------|-----------|
| <b>RELEASE CONTROL RECORD .....</b>                            | <b>4</b>  |
| <b>1 CERTIFICATION .....</b>                                   | <b>5</b>  |
| <b>2 SUMMARY OF TEST RESULTS .....</b>                         | <b>6</b>  |
| 2.1 MEASUREMENT UNCERTAINTY .....                              | 6         |
| 2.2 TEST SITE AND INSTRUMENTS .....                            | 7         |
| <b>3 GENERAL INFORMATION.....</b>                              | <b>8</b>  |
| 3.1 GENERAL DESCRIPTION OF EUT .....                           | 8         |
| 3.2 CONFIGURATION OF SYSTEM UNDER TEST .....                   | 11        |
| 3.3 DESCRIPTION OF SUPPORT UNITS .....                         | 12        |
| 3.4 DESCRIPTION OF TEST MODES.....                             | 12        |
| 3.5 GENERAL DESCRIPTION OF APPLIED STANDARDS .....             | 18        |
| <b>4 TEST TYPES AND RESULTS .....</b>                          | <b>19</b> |
| 4.1 OUTPUT POWER MEASUREMENT .....                             | 19        |
| 4.1.1 LIMITS OF OUTPUT POWER MEASUREMENT .....                 | 19        |
| 4.1.2 TEST PROCEDURES .....                                    | 19        |
| 4.1.3 TEST SETUP .....                                         | 20        |
| 4.1.4 TEST RESULTS .....                                       | 21        |
| 4.2 FREQUENCY STABILITY MEASUREMENT .....                      | 37        |
| 4.2.1 LIMITS OF FREQUENCY STABILITY MEASUREMENT .....          | 37        |
| 4.2.2 TEST PROCEDURE .....                                     | 37        |
| 4.2.3 TEST SETUP .....                                         | 37        |
| 4.2.4 TEST RESULTS .....                                       | 38        |
| 4.3 OCCUPIED BANDWIDTH MEASUREMENT .....                       | 51        |
| 4.3.1 LIMITS OF OCCUPIED BANDWIDTH MEASUREMENT .....           | 51        |
| 4.3.2 TEST SETUP .....                                         | 51        |
| 4.3.3 TEST PROCEDURES .....                                    | 51        |
| 4.3.4 TEST RESULTS .....                                       | 52        |
| 4.4 PEAK TO AVERAGE RATIO .....                                | 59        |
| 4.4.1 LIMITS OF PEAK TO AVERAGE RATIO MEASUREMENT .....        | 59        |
| 4.4.2 TEST SETUP .....                                         | 59        |
| 4.4.3 TEST PROCEDURES .....                                    | 59        |
| 4.4.4 TEST RESULTS .....                                       | 60        |
| 4.5 BAND EDGE MEASUREMENT .....                                | 67        |
| 4.5.1 LIMITS OF BAND EDGE MEASUREMENT .....                    | 67        |
| 4.5.2 TEST SETUP .....                                         | 67        |
| 4.5.3 TEST PROCEDURES .....                                    | 68        |
| 4.5.4 TEST RESULTS .....                                       | 69        |
| 4.6 CONDUCTED SPURIOUS EMISSIONS.....                          | 82        |
| 4.6.1 LIMITS OF CONDUCTED SPURIOUS EMISSIONS MEASUREMENT ..... | 82        |
| 4.6.2 TEST PROCEDURE .....                                     | 82        |
| 4.6.3 TEST SETUP .....                                         | 82        |
| 4.6.4 TEST RESULTS .....                                       | 83        |
| 4.7 RADIATED EMISSION MEASUREMENT .....                        | 96        |
| 4.7.1 LIMITS OF RADIATED EMISSION MEASUREMENT .....            | 96        |
| 4.7.2 TEST PROCEDURES .....                                    | 96        |
| 4.7.3 DEVIATION FROM TEST STANDARD .....                       | 96        |



Test Report No.: RF170410W004-5

|       |                                                                                             |     |
|-------|---------------------------------------------------------------------------------------------|-----|
| 4.7.4 | TEST SETUP.....                                                                             | 97  |
| 4.7.5 | TEST RESULTS .....                                                                          | 98  |
| 5     | INFORMATION ON THE TESTING LABORATORIES .....                                               | 142 |
| 6     | APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT<br>BY THE LAB ..... | 143 |



Test Report No.: RF170410W004-5

## RELEASE CONTROL RECORD

| ISSUE NO.      | REASON FOR CHANGE | DATE ISSUED   |
|----------------|-------------------|---------------|
| RF170410W004-5 | Original release  | Apr. 26, 2017 |



Test Report No.: RF170410W004-5

## 1 CERTIFICATION

**PRODUCT:** LTE Digital Mobile Phone  
**BRAND NAME:** nubia  
**MODEL NAME:** NX597J  
**APPLICANT:** Nubia Technology Co., Ltd.  
**TESTED:** Apr. 11, 2017 ~ Apr. 25, 2017  
**TEST SAMPLE:** Identical Prototype  
**TEST STANDARDS:** **FCC Part 27, Subpart C, L**  
**FCC Part 2**  
**ANSI/TIE/EIA-603-D**

The above equipment has been tested by **Bureau Veritas Shenzhen Co., Ltd. Dongguan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

**PREPARED BY :** \_\_\_\_\_ , **DATE:** Apr. 26, 2017  
(Harry Li/ Engineer)

**APPROVED BY :** \_\_\_\_\_ , **DATE:** Apr. 26, 2017  
( Sam Tung / Manager)

## 2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

| APPLIED STANDARD: FCC Part 27 & Part 2 |                              |        |                                                                                   |
|----------------------------------------|------------------------------|--------|-----------------------------------------------------------------------------------|
| STANDARD SECTION                       | TEST TYPE AND LIMIT          | RESULT | REMARK                                                                            |
| 2.1046<br>27.50(d)(4)                  | Maximum Peak Output Power    | PASS   | Meet the requirement of limit.                                                    |
| 2.1055<br>27.54                        | Frequency Stability          | PASS   | Meet the requirement of limit.                                                    |
| 2.1049<br>27.53(h)                     | Occupied Bandwidth           | PASS   | Meet the requirement of limit.                                                    |
| 27.50(d)(5)                            | Peak to average ratio        | PASS   | Meet the requirement of limit.                                                    |
| 27.53(h)                               | Band Edge Measurements       | PASS   | Meet the requirement of limit.                                                    |
| 2.1051<br>27.53(h)                     | Conducted Spurious Emissions | PASS   | Meet the requirement of limit.                                                    |
| 2.1053<br>27.53(h)                     | Radiated Spurious Emissions  | PASS   | Meet the requirement of limit.<br>Minimum passing margin is -23.33dB at 30.97MHz. |

### 2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

| MEASUREMENT         | FREQUENCY     | UNCERTAINTY |
|---------------------|---------------|-------------|
| Conducted emissions | 9kHz~30MHz    | 2.70dB      |
| Radiated emissions  | 9KHz ~ 30MHz  | 2.90dB      |
|                     | 30MHz ~ 1GMHz | 4.06dB      |
|                     | 1GHz ~ 18GHz  | 4.58dB      |
|                     | 18GHz ~ 40GHz | 1.94dB      |

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.



Test Report No.: RF170410W004-5

## 2.2 TEST SITE AND INSTRUMENTS

| Equipment                        | Manufacturer  | Model No.                | Serial No.  | Last Cal.   | Next Cal.   |
|----------------------------------|---------------|--------------------------|-------------|-------------|-------------|
| EMI Test Receiver                | Rohde&Schwarz | ESR7                     | 101494      | Mar. 05,17  | Mar. 04,18  |
| Signal and Spectrum Analyzer     | Rohde&Schwarz | FSV7                     | 102331      | Nov. 04,16  | Nov. 03,17  |
| Signal and Spectrum Analyzer     | Rohde&Schwarz | FSV40                    | 101094      | Mar. 05,17  | Mar. 04,18  |
| Bilog Antenna 1                  | Teseq         | CBL 6111D                | 30643       | Jul. 14, 16 | Jul. 13, 17 |
| Bilog Antenna 2                  | Teseq         | CBL 6111D                | 27089       | Jul. 14, 16 | Jul. 13, 17 |
| Loop antenna                     | Daze          | ZN30900A                 | 0708        | Nov. 28, 16 | Nov. 27, 17 |
| Horn Antenna (1GHz -18GHz)       | ETS -Lindgren | 3117                     | 00062558    | May 18,16   | May 17,17   |
| Horn Antenna (1GHz -18GHz)       | ETS -Lindgren | 3117                     | 00062557    | May 18,16   | May 17,17   |
| 10m Semi-anechoic Chamber        | CHANGLING     | 21.4m*12.1m*8.8m         | NSEMC006    | Mar. 12,16  | Mar. 11,18  |
| Test Software                    | E3            | V 9.160323               | N/A         | N/A         | N/A         |
| Test Software                    | ADT           | ADT_Radiated_V7.6.15.9.2 | N/A         | N/A         | N/A         |
| 10dB Attenuator                  | JFW/USA       | 50HF-010-SM A            | 1505        | Jul. 27, 16 | Jul. 26, 17 |
| Horn Antenna (15GHz-40GHz)       | SCHWARZBECK   | BBHA 9170                | BBHA9170147 | Mar. 02,17  | Mar. 01,18  |
| Horn Antenna (15GHz-40GHz)       | SCHWARZBECK   | BBHA 9170                | BBHA9170242 | Mar. 02,17  | Mar. 01,18  |
| Amplifier                        | Burgeon       | BPA-530                  | 100220      | Mar. 05,17  | Mar. 04,18  |
| Amplifier (9kHz-1GHz)            | SONOMA        | 310D                     | 186955      | Feb. 10,17  | Feb. 09,18  |
| Pre-Amplifier(1-18G)             | HP            | 8449B                    | 3008A00409  | Apr. 16,16  | Apr. 15,18  |
| Pre-Amplifier (18GHz-40GHz)      | EMCI          | EMC 184045               | 980102      | Nov. 04,16  | Nov. 03,17  |
| Humid & Temp Programmable Tester | Haida         | HD-2257                  | 110807201   | Sep.05,16   | Sep. 04,17  |
| Signal Generator                 | Agilent       | N5183A                   | MY50140980  | Nov. 04,16  | Nov. 03,17  |

- NOTE:**
1. The calibration interval of the above test instruments is 12 months or 24 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
  2. The test was performed in 10m Semi-anechoic Chamber and RF Oven Room.
  3. The horn antenna is used only for the measurement of emission frequency above 1GHz if tested.
  4. The FCC Site Registration No. is 502831.

### 3 GENERAL INFORMATION

#### 3.1 GENERAL DESCRIPTION OF EUT

|                              |                                                                |                       |
|------------------------------|----------------------------------------------------------------|-----------------------|
| <b>PRODUCT</b>               | LTE Digital Mobile Phone                                       |                       |
| <b>MODEL NAME</b>            | NX597J                                                         |                       |
| <b>POWER SUPPLY</b>          | 5.0Vdc (adapter or host equipment)<br>3.8Vdc (Li-ion, battery) |                       |
| <b>MODULATION TECHNOLOGY</b> | <b>WCDMA IV</b>                                                | BPSK                  |
|                              | <b>LTE</b>                                                     | QPSK, 16QAM           |
| <b>FREQUENCY RANGE</b>       | <b>WCDMA IV</b>                                                | 1712.4MHz ~ 1752.6MHz |
|                              | <b>LTE Band 4<br/>Channel Bandwidth: 1.4MHz</b>                | 1710.7MHz ~ 1754.3MHz |
|                              | <b>LTE Band 4<br/>Channel Bandwidth: 3MHz</b>                  | 1711.5MHz ~ 1753.5MHz |
|                              | <b>LTE Band 4<br/>Channel Bandwidth: 5MHz</b>                  | 1712.5MHz ~ 1752.5MHz |
|                              | <b>LTE Band 4<br/>Channel Bandwidth: 10MHz</b>                 | 1715.0MHz ~ 1750.0MHz |
|                              | <b>LTE Band 4<br/>Channel Bandwidth: 15MHz</b>                 | 1717.5MHz ~ 1747.5MHz |
|                              | <b>LTE Band 4<br/>Channel Bandwidth: 20MHz</b>                 | 1720.0MHz ~ 1745.0MHz |
|                              | <b>LTE Band 12<br/>Channel Bandwidth: 1.4MHz</b>               | 699.7MHz ~ 715.3MHz   |
|                              | <b>LTE Band 12<br/>Channel Bandwidth: 3MHz</b>                 | 700.5MHz ~ 714.5MHz   |
|                              | <b>LTE Band 12<br/>Channel Bandwidth: 5MHz</b>                 | 701.5MHz ~ 713.5MHz   |
|                              | <b>LTE Band 12<br/>Channel Bandwidth: 10MHz</b>                | 704.0MHz ~ 711.0MHz   |
|                              | <b>LTE Band 17<br/>Channel Bandwidth: 5MHz</b>                 | 706.5MHz ~ 713.5MHz   |
|                              | <b>LTE Band 17<br/>Channel Bandwidth: 10MHz</b>                | 709.0MHz ~ 711.0MHz   |
| <b>EMISSION DESIGNATOR</b>   | <b>WCDMA IV</b>                                                | 4M22F9W               |
|                              | <b>LTE Band 4<br/>Channel Bandwidth: 1.4MHz</b>                | QPSK: 1M09G7D         |
|                              |                                                                | 16QAM: 1M09W7D        |
|                              | <b>LTE Band 4<br/>Channel Bandwidth: 3MHz</b>                  | QPSK: 2M69G7D         |
|                              |                                                                | 16QAM: 2M68W7D        |
|                              | <b>LTE Band 4<br/>Channel Bandwidth: 5MHz</b>                  | QPSK: 4M49G7D         |
|                              |                                                                | 16QAM: 4M48W7D        |
|                              | <b>LTE Band 4<br/>Channel Bandwidth: 10MHz</b>                 | QPSK: 8M94G7D         |
|                              |                                                                | 16QAM: 8M94W7D        |

|                                |                                                  |                                 |
|--------------------------------|--------------------------------------------------|---------------------------------|
| <b>EMISSION<br/>DESIGNATOR</b> | <b>LTE Band 4<br/>Channel Bandwidth: 15MHz</b>   | QPSK: 13M4G7D<br>16QAM: 13M4W7D |
|                                | <b>LTE Band 4<br/>Channel Bandwidth: 20MHz</b>   | QPSK: 17M9G7D<br>16QAM: 17M9W7D |
|                                | <b>LTE Band 12<br/>Channel Bandwidth: 1.4MHz</b> | QPSK: 1M09G7D<br>16QAM: 1M09W7D |
|                                | <b>LTE Band 12<br/>Channel Bandwidth: 3MHz</b>   | QPSK: 2M69G7D<br>16QAM: 2M69W7D |
|                                | <b>LTE Band 12<br/>Channel Bandwidth: 5MHz</b>   | QPSK: 4M50G7D<br>16QAM: 4M49W7D |
|                                | <b>LTE Band 12<br/>Channel Bandwidth: 10MHz</b>  | QPSK: 8M95G7D<br>16QAM: 8M97W7D |
|                                | <b>LTE Band 17<br/>Channel Bandwidth: 5MHz</b>   | QPSK: 4M49G7D<br>16QAM: 4M48W7D |
|                                | <b>LTE Band 17<br/>Channel Bandwidth: 10MHz</b>  | QPSK: 9M00G7D<br>16QAM: 8M98W7D |
| <b>MAX. ERP/EIRP<br/>POWER</b> | <b>WCDMA IV</b>                                  | 101mW                           |
|                                | <b>LTE Band 4<br/>Channel Bandwidth: 1.4MHz</b>  | 235mW                           |
|                                | <b>LTE Band 4<br/>Channel Bandwidth: 3MHz</b>    | 237mW                           |
|                                | <b>LTE Band 4<br/>Channel Bandwidth: 5MHz</b>    | 246mW                           |
|                                | <b>LTE Band 4<br/>Channel Bandwidth: 10MHz</b>   | 258mW                           |
|                                | <b>LTE Band 4<br/>Channel Bandwidth: 15MHz</b>   | 242mW                           |
|                                | <b>LTE Band 4<br/>Channel Bandwidth: 20MHz</b>   | 207mW                           |
|                                | <b>LTE Band 12<br/>Channel Bandwidth: 1.4MHz</b> | 176mW                           |
|                                | <b>LTE Band 12<br/>Channel Bandwidth: 3MHz</b>   | 178mW                           |
|                                | <b>LTE Band 12<br/>Channel Bandwidth: 5MHz</b>   | 175mW                           |
|                                | <b>LTE Band 12<br/>Channel Bandwidth: 10MHz</b>  | 158mW                           |
|                                | <b>LTE Band 17<br/>Channel Bandwidth: 5MHz</b>   | 151mW                           |

|                         |                                                       |                                     |
|-------------------------|-------------------------------------------------------|-------------------------------------|
|                         | <b>LTE Band 17</b><br><b>Channel Bandwidth: 10MHz</b> | 136mW                               |
| <b>ANTENNA TYPE</b>     | <b>WCDMA IV</b>                                       | Fixed External Antenna with -3dBi   |
|                         | <b>LTE Band 4</b>                                     | Fixed External Antenna with -2.6dBi |
|                         | <b>LTE Band 12</b>                                    | Fixed External Antenna with -3.4dBi |
|                         | <b>LTE Band 17</b>                                    | Fixed External Antenna with -3.4dBi |
| <b>HW VERSION</b>       | MB6735_05A_V1BMB_B                                    |                                     |
| <b>SW VERSION</b>       | NX597J_USCommon_7.00                                  |                                     |
| <b>ACCESSORY DEVICE</b> | Refer to note as below                                |                                     |
| <b>DATA CABLE</b>       | USB cable: non-shielded, detachable, 1.0m             |                                     |

**NOTE:**

- For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
- The EUT was powered by the following adapter:

| <b>ADAPTER</b> |                    |
|----------------|--------------------|
| <b>BRAND:</b>  | nubia              |
| <b>MODEL:</b>  | STC-A515A-Z        |
| <b>INPUT:</b>  | AC 100-240V, 300mA |
| <b>OUTPUT:</b> | DC 5V, 1500mA      |


- The EUT matched the following USB cable:

| <b>USB CABLE</b>    |             |
|---------------------|-------------|
| <b>RAND:</b>        | LIXUN       |
| <b>MODEL:</b>       | ZXMT1511003 |
| <b>SIGNAL LINE:</b> | 1.0 METER   |


- For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.

### 3.2 CONFIGURATION OF SYSTEM UNDER TEST

#### FOR RADIATION EMISSION TEST



#### FOR E.R.P./E.I.R.P TEST



### 3.3 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

| NO. | PRODUCT   | BRAND    | MODEL NO. | SERIAL NO. | FCC ID |
|-----|-----------|----------|-----------|------------|--------|
| 1   | DC source | LONG WEI | PS-6403D  | 010934269  | N/A    |
| 2   | PC        | HP       | A6608CN   | 3CR83825X3 | N/A    |

| NO. | SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS |
|-----|-----------------------------------------------------|
| 1   | DC Line: Unshielded, Detachable 1.0m                |
| 2   | AC Line: Unshielded, Detachable 1.5m                |

**NOTE:**

1. All power cords of the above support units are non shielded (1.8m).

### 3.4 DESCRIPTION OF TEST MODES

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports. The worst case in ERP/EIRP and radiated emission was found when positioned on X-plane for WCDMA and X-plane for LTE. Following channel(s) was (were) selected for the final test as listed below:

| EUT<br>CONFIGURE<br>MODE | DESCRIPTION                                      |
|--------------------------|--------------------------------------------------|
| A                        | EUT + Adapter + USB Cable with WCDMA or LTE link |
| B                        | EUT + Battery with WCDMA or LTE link             |



Test Report No.: RF170410W004-5

#### WCDMA MODE

| EUT<br>CONFIGURE<br>MODE | TEST ITEM             | AVAILABLE CHANNEL | TESTED CHANNEL   | MODE  |
|--------------------------|-----------------------|-------------------|------------------|-------|
| B                        | EIRP                  | 1312 to 1513      | 1312, 1413, 1513 | WCDMA |
| B                        | FREQUENCY STABILITY   | 1312 to 1513      | 1312, 1513       | WCDMA |
| B                        | OCCUPIED BANDWIDTH    | 1312 to 1513      | 1312, 1413, 1513 | WCDMA |
| B                        | BAND EDGE             | 1312 to 1513      | 1312, 1513       | WCDMA |
| B                        | PEAK TO AVERAGE RATIO | 1312 to 1513      | 1413             | WCDMA |
| B                        | CONDCUDED EMISSION    | 1312 to 1513      | 1312, 1413, 1513 | WCDMA |
| A                        | RADIATED EMISSION     | 1312 to 1513      | 1312, 1413, 1513 | WCDMA |

#### LTE BAND 4

| EUT CONFIGURE MODE | TEST ITEM             | AVAILABLE CHANNEL | TESTED CHANNEL      | CHANNEL BANDWIDTH | MODULATION  | MODE                 |
|--------------------|-----------------------|-------------------|---------------------|-------------------|-------------|----------------------|
| B                  | EIRP                  | 19957 to 20393    | 19957, 20175, 20393 | 1.4MHz            | QPSK, 16QAM | 1 RB / 0 RB Offset   |
|                    |                       | 19965 to 20385    | 19965, 20175, 20385 | 3MHz              | QPSK, 16QAM | 1 RB / 0 RB Offset   |
|                    |                       | 19975 to 20375    | 19975, 20175, 20375 | 5MHz              | QPSK, 16QAM | 1 RB / 0 RB Offset   |
|                    |                       | 20000 to 20350    | 20000, 20175, 20350 | 10MHz             | QPSK, 16QAM | 1 RB / 0 RB Offset   |
|                    |                       | 20025 to 20325    | 20025, 20175, 20325 | 15MHz             | QPSK, 16QAM | 1 RB / 0 RB Offset   |
|                    |                       | 20050 to 20300    | 20050, 20175, 20300 | 20MHz             | QPSK, 16QAM | 1 RB / 0 RB Offset   |
| B                  | FREQUENCY STABILITY   | 19957 to 20393    | 19957, 20393        | 1.4MHz            | QPSK        | 1 RB / 0 RB Offset   |
|                    |                       | 19965 to 20385    | 19965, 20385        | 3MHz              | QPSK        | 1 RB / 0 RB Offset   |
|                    |                       | 19975 to 20375    | 19975, 20375        | 5MHz              | QPSK        | 1 RB / 0 RB Offset   |
|                    |                       | 20000 to 20350    | 20000, 20350        | 10MHz             | QPSK        | 1 RB / 0 RB Offset   |
|                    |                       | 20025 to 20325    | 20025, 20325        | 15MHz             | QPSK        | 1 RB / 0 RB Offset   |
|                    |                       | 20050 to 20300    | 20050, 20300        | 20MHz             | QPSK        | 1 RB / 0 RB Offset   |
| B                  | OCCUPIED BANDWIDTH    | 19957 to 20393    | 19957, 20175, 20393 | 1.4MHz            | QPSK, 16QAM | 6 RB / 0 RB Offset   |
|                    |                       | 19965 to 20385    | 19965, 20175, 20385 | 3MHz              | QPSK, 16QAM | 15 RB / 0 RB Offset  |
|                    |                       | 19975 to 20375    | 19975, 20175, 20375 | 5MHz              | QPSK, 16QAM | 25 RB / 0 RB Offset  |
|                    |                       | 20000 to 20350    | 20000, 20175, 20350 | 10MHz             | QPSK, 16QAM | 50 RB / 0 RB Offset  |
|                    |                       | 20025 to 20325    | 20025, 20175, 20325 | 15MHz             | QPSK, 16QAM | 75 RB / 0 RB Offset  |
|                    |                       | 20050 to 20300    | 20050, 20175, 20300 | 20MHz             | QPSK, 16QAM | 100 RB / 0 RB Offset |
| B                  | PEAK TO AVERAGE RATIO | 19957 to 20393    | 19957, 20175, 20393 | 1.4MHz            | QPSK, 16QAM | 1 RB / 0 RB Offset   |
|                    |                       | 19965 to 20385    | 19965, 20175, 20385 | 3MHz              | QPSK, 16QAM | 1 RB / 0 RB Offset   |
|                    |                       | 19975 to 20375    | 19975, 20175, 20375 | 5MHz              | QPSK, 16QAM | 1 RB / 0 RB Offset   |
|                    |                       | 20000 to 20350    | 20000, 20175, 20350 | 10MHz             | QPSK, 16QAM | 1 RB / 0 RB Offset   |
|                    |                       | 20025 to 20325    | 20025, 20175, 20325 | 15MHz             | QPSK, 16QAM | 1 RB / 0 RB Offset   |
|                    |                       | 20050 to 20300    | 20050, 20175, 20300 | 20MHz             | QPSK, 16QAM | 1 RB / 0 RB Offset   |
| B                  | BAND EDGE             | 19957 to 20393    | 19957               | 1.4MHz            | QPSK        | 1 RB / 0 RB Offset   |
|                    |                       |                   |                     |                   |             | 6 RB / 0 RB Offset   |
|                    |                       | 19965 to 20385    | 20393               | 1.4MHz            | QPSK        | 1 RB / 5 RB Offset   |
|                    |                       |                   |                     |                   |             | 6 RB / 0 RB Offset   |
|                    |                       | 19975 to 20375    | 19965               | 3MHz              | QPSK        | 1 RB / 0 RB Offset   |
|                    |                       |                   |                     |                   |             | 15 RB / 0 RB Offset  |
|                    |                       | 20000 to 20350    | 20385               | 3MHz              | QPSK        | 1 RB / 14 RB Offset  |
|                    |                       |                   |                     |                   |             | 15 RB / 0 RB Offset  |
|                    |                       | 20025 to 20325    | 19975               | 5MHz              | QPSK        | 1 RB / 0 RB Offset   |
|                    |                       |                   |                     |                   |             | 25 RB / 0 RB Offset  |
|                    |                       | 20050 to 20300    | 20375               | 5MHz              | QPSK        | 1 RB / 24 RB Offset  |
|                    |                       |                   |                     |                   |             | 25 RB / 0 RB Offset  |
|                    |                       | 20000 to 20350    | 20000               | 10MHz             | QPSK        | 1 RB / 0 RB Offset   |
|                    |                       |                   |                     |                   |             | 50 RB / 0 RB Offset  |
|                    |                       | 20025 to 20325    | 20350               | 10MHz             | QPSK        | 1 RB / 49 RB Offset  |
|                    |                       |                   |                     |                   |             | 50 RB / 0 RB Offset  |

|   |                      |                |                     |        |      |                      |
|---|----------------------|----------------|---------------------|--------|------|----------------------|
| B | BAND EDGE            | 20025 to 20325 | 20025               | 15MHz  | QPSK | 1 RB / 0 RB Offset   |
|   |                      |                | 20325               | 15MHz  | QPSK | 75 RB / 0 RB Offset  |
|   |                      | 20050 to 20300 | 20050               | 20MHz  | QPSK | 1 RB / 74 RB Offset  |
|   |                      |                | 20300               | 20MHz  | QPSK | 75 RB / 0 RB Offset  |
|   |                      |                |                     |        |      | 1 RB / 0 RB Offset   |
|   |                      |                |                     |        |      | 100 RB / 0 RB Offset |
| B | CONDCUDETED EMISSION | 19957 to 20393 | 19957, 20175, 20393 | 1.4MHz | QPSK | 1 RB / 0 RB Offset   |
|   |                      | 19965 to 20385 | 19965, 20175, 20385 | 3MHz   | QPSK | 1 RB / 0 RB Offset   |
|   |                      | 19975 to 20375 | 19975, 20175, 20375 | 5MHz   | QPSK | 1 RB / 0 RB Offset   |
|   |                      | 20000 to 20350 | 20000, 20175, 20350 | 10MHz  | QPSK | 1 RB / 0 RB Offset   |
|   |                      | 20025 to 20325 | 20025, 20175, 20325 | 15MHz  | QPSK | 1 RB / 0 RB Offset   |
|   |                      | 20050 to 20300 | 20050, 20175, 20300 | 20MHz  | QPSK | 1 RB / 0 RB Offset   |
| A | RADIATED EMISSION    | 19957 to 20393 | 20175               | 1.4MHz | QPSK | 1 RB / 0 RB Offset   |
|   |                      | 19965 to 20385 | 20175               | 3MHz   | QPSK | 1 RB / 0 RB Offset   |
|   |                      | 19975 to 20375 | 20175               | 5MHz   | QPSK | 1 RB / 0 RB Offset   |
|   |                      | 20000 to 20350 | 20000, 20175, 20350 | 10MHz  | QPSK | 1 RB / 0 RB Offset   |
|   |                      | 20025 to 20325 | 20175               | 15MHz  | QPSK | 1 RB / 0 RB Offset   |
|   |                      | 20050 to 20300 | 20175               | 20MHz  | QPSK | 1 RB / 0 RB Offset   |

**Note:** This device was tested under all bandwidths, RB configurations and modulations. The worst case was found in QPSK modulation.

**LTE BAND 12**

| EUT CONFIGURE MODE | TEST ITEM             | AVAILABLE CHANNEL | TESTED CHANNEL       | CHANNEL BANDWIDTH | MODULATION  | MODE                |
|--------------------|-----------------------|-------------------|----------------------|-------------------|-------------|---------------------|
| B                  | ERP                   | 23017 to 23173    | 23017, 23095 , 23173 | 1.4MHz            | QPSK,16QAM  | 1 RB / 0 RB Offset  |
|                    |                       | 23025 to 23165    | 23025, 23095 ,23165  | 3MHz              | QPSK,16QAM  | 1 RB / 0 RB Offset  |
|                    |                       | 23035 to 23155    | 23035, 23095 ,23155  | 5MHz              | QPSK,16QAM  | 1 RB / 0 RB Offset  |
|                    |                       | 23060 to 23130    | 23060, 23095 ,23130  | 10MHz             | QPSK,16QAM  | 1 RB / 0 RB Offset  |
| B                  | FREQUENCY STABILITY   | 23017 to 23173    | 23017, 23173         | 1.4MHz            | QPSK        | 1 RB / 0 RB Offset  |
|                    |                       | 23025 to 23165    | 23025, 23165         | 3MHz              | QPSK        | 1 RB / 0 RB Offset  |
|                    |                       | 23035 to 23155    | 23035, 23155         | 5MHz              | QPSK        | 1 RB / 0 RB Offset  |
|                    |                       | 23060 to 23130    | 23060, 23130         | 10MHz             | QPSK        | 1 RB / 0 RB Offset  |
| B                  | OCCUPIED BANDWIDTH    | 23017 to 23173    | 23017, 23095 , 23173 | 1.4MHz            | QPSK,16QAM  | 6 RB / 0 RB Offset  |
|                    |                       | 23025 to 23165    | 23025, 23095 ,23165  | 3MHz              | QPSK,16QAM  | 15 RB / 0 RB Offset |
|                    |                       | 23035 to 23155    | 23035, 23095 ,23155  | 5MHz              | QPSK,16QAM  | 25 RB / 0 RB Offset |
|                    |                       | 23060 to 23130    | 23060, 23095 ,23130  | 10MHz             | QPSK,16QAM  | 50 RB / 0 RB Offset |
| B                  | PEAK TO AVERAGE RATIO | 23017 to 23173    | 23017, 23095 , 23173 | 1.4MHz            | QPSK, 16QAM | 1 RB / 0 RB Offset  |
|                    |                       | 23025 to 23165    | 23025, 23095 ,23165  | 3MHz              | QPSK, 16QAM | 1 RB / 0 RB Offset  |
|                    |                       | 23035 to 23155    | 23035, 23095 ,23155  | 5MHz              | QPSK, 16QAM | 1 RB / 0 RB Offset  |
|                    |                       | 23060 to 23130    | 23060, 23095 ,23130  | 10MHz             | QPSK, 16QAM | 1 RB / 0 RB Offset  |
| B                  | BAND EDGE             | 23017 to 23173    | 23017                | 1.4MHz            | QPSK        | 1 RB / 0 RB Offset  |
|                    |                       |                   |                      |                   |             | 6 RB / 0 RB Offset  |
|                    |                       | 23025 to 23165    | 23173                | 1.4MHz            | QPSK        | 1 RB / 5 RB Offset  |
|                    |                       |                   |                      |                   |             | 6 RB / 0 RB Offset  |
|                    |                       | 23035 to 23155    | 23025                | 3MHz              | QPSK        | 1 RB / 0 RB Offset  |
|                    |                       |                   |                      |                   |             | 15 RB / 0 RB Offset |
|                    |                       | 23060 to 23130    | 23165                | 3MHz              | QPSK        | 1 RB / 14 RB Offset |
|                    |                       |                   |                      |                   |             | 15 RB / 0 RB Offset |
|                    |                       | 23017 to 23173    | 23035                | 5MHz              | QPSK        | 1 RB / 0 RB Offset  |
|                    |                       |                   |                      |                   |             | 25 RB / 0 RB Offset |
|                    |                       | 23025 to 23165    | 23155                | 5MHz              | QPSK        | 1 RB / 24 RB Offset |
|                    |                       |                   |                      |                   |             | 25 RB / 0 RB Offset |
| B                  | CONDCUDED EMISSION    | 23017 to 23173    | 23017, 23095 , 23173 | 1.4MHz            | QPSK        | 1 RB / 0 RB Offset  |
|                    |                       | 23025 to 23165    | 23025, 23095 ,23165  | 3MHz              | QPSK        | 1 RB / 0 RB Offset  |
|                    |                       | 23035 to 23155    | 23035, 23095 ,23155  | 5MHz              | QPSK        | 1 RB / 0 RB Offset  |
|                    |                       | 23060 to 23130    | 23060, 23095 ,23130  | 10MHz             | QPSK        | 1 RB / 0 RB Offset  |
| A                  | RADIATED EMISSION     | 23017 to 23173    | 23095                | 1.4MHz            | QPSK        | 1 RB / 0 RB Offset  |
|                    |                       | 23025 to 23165    | 23095                | 3MHz              | QPSK        | 1 RB / 0 RB Offset  |
|                    |                       | 23035 to 23155    | 23095                | 5MHz              | QPSK        | 1 RB / 0 RB Offset  |
|                    |                       | 23060 to 23130    | 23060, 23095 ,23130  | 10MHz             | QPSK        | 1 RB / 0 RB Offset  |

## LTE BAND 17

| EUT CONFIGURE MODE | TEST ITEM             | AVAILABLE CHANNEL | TESTED CHANNEL      | CHANNEL BANDWIDTH | MODULATION  | MODE                |
|--------------------|-----------------------|-------------------|---------------------|-------------------|-------------|---------------------|
| B                  | ERP                   | 23755 to 23825    | 23755, 23790, 23825 | 5MHz              | QPSK, 16QAM | 1 RB / 0 RB Offset  |
|                    |                       | 23780 to 23800    | 23780, 23790, 23800 | 10MHz             | QPSK, 16QAM | 1 RB / 0 RB Offset  |
| B                  | FREQUENCY STABILITY   | 23755 to 23825    | 23790               | 5MHz              | QPSK        | 1 RB / 0 RB Offset  |
|                    |                       | 23780 to 23800    | 23790               | 10MHz             | QPSK        | 1 RB / 0 RB Offset  |
| B                  | OCCUPIED BANDWIDTH    | 23755 to 23825    | 23755, 23790, 23825 | 5MHz              | QPSK, 16QAM | 25 RB / 0 RB Offset |
|                    |                       | 23780 to 23800    | 23780, 23790, 23800 | 10MHz             | QPSK, 16QAM | 50 RB / 0 RB Offset |
| B                  | PEAK TO AVERAGE RATIO | 23755 to 23825    | 23755, 23790, 23825 | 5MHz              | QPSK, 16QAM | 1 RB / 0 RB Offset  |
|                    |                       | 23780 to 23800    | 23780, 23790, 23800 | 10MHz             | QPSK, 16QAM | 1 RB / 0 RB Offset  |
| B                  | BAND EDGE             | 23755 to 23825    | 23755               | 5MHz              | QPSK        | 1 RB / 0 RB Offset  |
|                    |                       |                   |                     |                   |             | 25 RB / 0 RB Offset |
|                    |                       | 23780 to 23800    | 23825               | 5MHz              | QPSK        | 1 RB / 24 RB Offset |
|                    |                       |                   |                     |                   |             | 25 RB / 0 RB Offset |
|                    |                       | 23780 to 23800    | 23780               | 10MHz             | QPSK        | 1 RB / 0 RB Offset  |
|                    |                       |                   | 23800               | 10MHz             | QPSK        | 50 RB / 0 RB Offset |
| B                  | CONDCUDED EMISSION    | 23755 to 23825    | 23755, 23790, 23825 | 5MHz              | QPSK        | 1 RB / 0 RB Offset  |
|                    |                       | 23780 to 23800    | 23780, 23790, 23800 | 10MHz             | QPSK        | 1 RB / 0 RB Offset  |
| A                  | RADIATED EMISSION     | 23755 to 23825    | 23790               | 5MHz              | QPSK        | 1 RB / 0 RB Offset  |
|                    |                       | 23780 to 23800    | 23780, 23790, 23800 | 10MHz             | QPSK        | 1 RB / 0 RB Offset  |

**Note:** This device was tested under all bandwidths, RB configurations and modulations. The worst case was found in QPSK modulation.

## TEST CONDITION:

| TEST ITEM             | ENVIRONMENTAL CONDITIONS | INPUT POWER         | TESTED BY   |
|-----------------------|--------------------------|---------------------|-------------|
| EIRP(ERP)             | 24deg. C, 60%RH          | 3.8Vdc from Battery | Wenliang Wu |
| FREQUENCY STABILITY   | 24deg. C, 61%RH          | 3.8Vdc from Battery | Wenliang Wu |
| OCCUPIED BANDWIDTH    | 24deg. C, 61%RH          | 3.8Vdc from Battery | Wenliang Wu |
| PEAK TO AVERAGE RATIO | 24deg. C, 61%RH          | 3.8Vdc from Battery | Moon Xiong  |
| BAND EDGE             | 24deg. C, 61%RH          | 3.8Vdc from Battery | Moon Xiong  |
| CONDCUDED EMISSION    | 24deg. C, 61%RH          | 3.8Vdc from Battery | Moon Xiong  |
| RADIATED EMISSION     | 23deg. C, 60%RH          | 5Vdc from adapter   | Tony Zou    |



Test Report No.: RF170410W004-5

### 3.5 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**FCC 47 CFR Part 2**

**FCC 47 CFR Part 27**

**KDB 971168 D01 Power Meas License Digital Systems v02r02**

**ANSI/TIA/EIA-603-D**

**NOTE:** All test items have been performed and recorded as per the above standards.



## 4 TEST TYPES AND RESULTS

### 4.1 OUTPUT POWER MEASUREMENT

#### 4.1.1 LIMITS OF OUTPUT POWER MEASUREMENT

Fixed, mobile, and portable (hand-held) stations operating in the 1710–1755 MHz band are limited to 1 watt EIRP.

Portable stations (hand-held devices) operating in the 699-716 MHz bands are limited to 3 watts ERP.

#### 4.1.2 TEST PROCEDURES

##### **EIRP / ERP MEASUREMENT:**


- a. The EUT was set up for the maximum power with LTE link data modulation. The power was measured with R&S Spectrum Analyzer. All measurements were done at 3 channels (low, middle and high operational frequency range). RBW and VBW is 10MHz for LTE.
- b. E.I.R.P power measurement. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The “Read Value” is the spectrum reading the maximum power value.
- c. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to “Read Value” of step a. Record the power level of S.G
- d.  $EIRP = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn}$
- e.  $E.R.P = E.I.R.P - 2.15 \text{ dB}$

##### **CONDUCTED POWER MEASUREMENT:**

- a. The EUT was set up for the maximum power with LTE link data modulation and link up with simulator.
- b. Set the EUT to transmit under low, middle and high channel and record the power level shown on simulator.


#### 4.1.3 TEST SETUP

##### EIRP / ERP MEASUREMENT:



For the actual test configuration, please refer to the attached file (Test Setup Photo).

##### CONDUCTED POWER MEASUREMENT:



For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.1.4 TEST RESULTS

##### AVERAGE CONDUCTED OUTPUT POWER (dBm)

| Band            | WCDMA IV |        |        |
|-----------------|----------|--------|--------|
| Channel         | 1312     | 1413   | 1513   |
| Frequency (MHz) | 1712.4   | 1732.6 | 1752.6 |
| RMC 12.2K       | 23.03    | 22.92  | 23.01  |
| HSPA            |          |        |        |
| HSDPA Subtest-1 | 22.08    | 21.97  | 22.06  |
| HSDPA Subtest-2 | 22.04    | 21.93  | 22.02  |
| HSDPA Subtest-3 | 21.57    | 21.46  | 21.55  |
| HSDPA Subtest-4 | 21.52    | 21.41  | 21.50  |
| HSUPA Subtest-1 | 21.92    | 21.81  | 21.90  |
| HSUPA Subtest-2 | 19.98    | 19.87  | 19.96  |
| HSUPA Subtest-3 | 20.94    | 20.83  | 20.92  |
| HSUPA Subtest-4 | 19.96    | 19.85  | 19.94  |
| HSUPA Subtest-5 | 21.98    | 21.89  | 21.96  |

| LTE Band 4 |            |         |           |                         |                         |                         |     |
|------------|------------|---------|-----------|-------------------------|-------------------------|-------------------------|-----|
| BW         | Modulation | RB Size | RB Offset | Low CH<br>19957         | Mid CH<br>20175         | High CH<br>20393        | MPR |
|            |            |         |           | Frequency<br>1710.7 MHz | Frequency<br>1732.5 MHz | Frequency<br>1754.3 MHz |     |
| 1.4MHz     | QPSK       | 1       | 0         | 22.80                   | 22.75                   | 22.76                   | 0   |
|            |            | 1       | 2         | 22.77                   | 22.72                   | 22.73                   | 0   |
|            |            | 1       | 5         | 22.60                   | 22.55                   | 22.56                   | 0   |
|            |            | 3       | 0         | 22.78                   | 22.73                   | 22.74                   | 0   |
|            |            | 3       | 1         | 22.75                   | 22.70                   | 22.71                   | 0   |
|            |            | 3       | 3         | 22.58                   | 22.53                   | 22.54                   | 0   |
|            |            | 6       | 0         | 21.90                   | 21.85                   | 21.86                   | 1   |
|            | 16QAM      | 1       | 0         | 21.87                   | 21.82                   | 21.83                   | 1   |
|            |            | 1       | 2         | 21.85                   | 21.80                   | 21.81                   | 1   |
|            |            | 1       | 5         | 21.82                   | 21.77                   | 21.78                   | 1   |
|            |            | 3       | 0         | 21.86                   | 21.81                   | 21.82                   | 1   |
|            |            | 3       | 1         | 21.84                   | 21.79                   | 21.80                   | 1   |
|            |            | 3       | 3         | 21.81                   | 21.76                   | 21.77                   | 1   |
|            |            | 6       | 0         | 20.81                   | 20.76                   | 20.77                   | 2   |
| BW         | Modulation | RB Size | RB Offset | Low CH<br>19965         | Mid CH<br>20175         | High CH<br>20385        | MPR |
|            |            |         |           | Frequency<br>1711.5 MHz | Frequency<br>1732.5 MHz | Frequency<br>1753.5 MHz |     |
| 3 MHz      | QPSK       | 1       | 0         | 22.81                   | 22.76                   | 22.77                   | 0   |
|            |            | 1       | 7         | 22.78                   | 22.73                   | 22.74                   | 0   |
|            |            | 1       | 14        | 22.61                   | 22.56                   | 22.57                   | 0   |
|            |            | 8       | 0         | 21.97                   | 21.92                   | 21.93                   | 1   |
|            |            | 8       | 3         | 21.93                   | 21.88                   | 21.89                   | 1   |
|            |            | 8       | 7         | 21.90                   | 21.85                   | 21.86                   | 1   |
|            |            | 15      | 0         | 21.91                   | 21.86                   | 21.87                   | 1   |
|            | 16QAM      | 1       | 0         | 21.88                   | 21.83                   | 21.84                   | 1   |
|            |            | 1       | 7         | 21.86                   | 21.81                   | 21.82                   | 1   |
|            |            | 1       | 14        | 21.83                   | 21.78                   | 21.79                   | 1   |
|            |            | 8       | 0         | 20.87                   | 20.82                   | 20.83                   | 2   |
|            |            | 8       | 3         | 20.84                   | 20.79                   | 20.80                   | 2   |
|            |            | 8       | 7         | 20.82                   | 20.77                   | 20.78                   | 2   |
|            |            | 15      | 0         | 20.82                   | 20.77                   | 20.78                   | 2   |

| LTE Band 4 |            |         |           |                         |                         |                         |     |
|------------|------------|---------|-----------|-------------------------|-------------------------|-------------------------|-----|
| BW         | Modulation | RB Size | RB Offset | Low CH<br>19975         | Mid CH<br>20175         | High CH<br>20375        | MPR |
|            |            |         |           | Frequency<br>1712.5 MHz | Frequency<br>1732.5 MHz | Frequency<br>1752.5 MHz |     |
| 5 MHz      | QPSK       | 1       | 0         | 22.84                   | 22.79                   | 22.80                   | 0   |
|            |            | 1       | 12        | 22.81                   | 22.76                   | 22.77                   | 0   |
|            |            | 1       | 24        | 22.64                   | 22.59                   | 22.60                   | 0   |
|            |            | 12      | 0         | 22.00                   | 21.95                   | 21.96                   | 1   |
|            |            | 12      | 6         | 21.96                   | 21.91                   | 21.92                   | 1   |
|            |            | 12      | 13        | 21.93                   | 21.88                   | 21.89                   | 1   |
|            |            | 25      | 0         | 21.94                   | 21.89                   | 21.90                   | 1   |
|            | 16QAM      | 1       | 0         | 21.91                   | 21.86                   | 21.87                   | 1   |
|            |            | 1       | 12        | 21.89                   | 21.84                   | 21.85                   | 1   |
|            |            | 1       | 24        | 21.86                   | 21.81                   | 21.82                   | 1   |
|            |            | 12      | 0         | 20.90                   | 20.85                   | 20.86                   | 2   |
|            |            | 12      | 6         | 20.87                   | 20.82                   | 20.83                   | 2   |
|            |            | 12      | 13        | 20.85                   | 20.80                   | 20.81                   | 2   |
|            |            | 25      | 0         | 20.85                   | 20.80                   | 20.81                   | 2   |
| BW         | Modulation | RB Size | RB Offset | Low CH<br>20000         | Mid CH<br>20175         | High CH<br>20350        | MPR |
|            |            |         |           | Frequency<br>1715 MHz   | Frequency<br>1732.5 MHz | Frequency<br>1750 MHz   |     |
| 10 MHz     | QPSK       | 1       | 0         | 22.88                   | 22.83                   | 22.84                   | 0   |
|            |            | 1       | 24        | 22.85                   | 22.80                   | 22.81                   | 0   |
|            |            | 1       | 49        | 22.68                   | 22.63                   | 22.64                   | 0   |
|            |            | 25      | 0         | 22.04                   | 21.99                   | 22.00                   | 1   |
|            |            | 25      | 12        | 22.00                   | 21.95                   | 21.96                   | 1   |
|            |            | 25      | 25        | 21.97                   | 21.92                   | 21.93                   | 1   |
|            |            | 50      | 0         | 21.98                   | 21.93                   | 21.94                   | 1   |
|            | 16QAM      | 1       | 0         | 21.95                   | 21.90                   | 21.91                   | 1   |
|            |            | 1       | 24        | 21.93                   | 21.88                   | 21.89                   | 1   |
|            |            | 1       | 49        | 21.90                   | 21.85                   | 21.86                   | 1   |
|            |            | 25      | 0         | 20.94                   | 20.89                   | 20.90                   | 2   |
|            |            | 25      | 12        | 20.91                   | 20.86                   | 20.87                   | 2   |
|            |            | 25      | 25        | 20.89                   | 20.84                   | 20.85                   | 2   |
|            |            | 50      | 0         | 20.89                   | 20.84                   | 20.85                   | 2   |

| LTE Band 4 |            |         |           |                      |                      |                      |     |
|------------|------------|---------|-----------|----------------------|----------------------|----------------------|-----|
| BW         | Modulation | RB Size | RB Offset | Low CH 20025         | Mid CH 20175         | High CH 20325        | MPR |
|            |            |         |           | Frequency 1717.5 MHz | Frequency 1732.5 MHz | Frequency 1747.5 MHz |     |
| 15 MHz     | QPSK       | 1       | 0         | 22.94                | 22.89                | 22.90                | 0   |
|            |            | 1       | 37        | 22.91                | 22.86                | 22.87                | 0   |
|            |            | 1       | 74        | 22.74                | 22.69                | 22.70                | 0   |
|            |            | 36      | 0         | 22.10                | 22.05                | 22.06                | 1   |
|            |            | 36      | 19        | 22.06                | 22.01                | 22.02                | 1   |
|            |            | 36      | 39        | 22.03                | 21.98                | 21.99                | 1   |
|            |            | 75      | 0         | 22.04                | 21.99                | 22.00                | 1   |
|            | 16QAM      | 1       | 0         | 22.01                | 21.96                | 21.97                | 1   |
|            |            | 1       | 37        | 21.99                | 21.94                | 21.95                | 1   |
|            |            | 1       | 74        | 21.96                | 21.91                | 21.92                | 1   |
|            |            | 36      | 0         | 21.00                | 20.95                | 20.96                | 2   |
|            |            | 36      | 19        | 20.97                | 20.92                | 20.93                | 2   |
|            |            | 36      | 39        | 20.95                | 20.90                | 20.91                | 2   |
|            |            | 75      | 0         | 20.95                | 20.90                | 20.91                | 2   |
| BW         | Modulation | RB Size | RB Offset | Low CH 20050         | Mid CH 20175         | High CH 20300        | MPR |
|            |            |         |           | Frequency 1720 MHz   | Frequency 1732.5 MHz | Frequency 1745 MHz   |     |
| 20MHz      | QPSK       | 1       | 0         | 22.97                | 22.92                | 22.93                | 0   |
|            |            | 1       | 50        | 22.94                | 22.89                | 22.90                | 0   |
|            |            | 1       | 99        | 22.77                | 22.72                | 22.73                | 0   |
|            |            | 50      | 0         | 22.13                | 22.08                | 22.09                | 1   |
|            |            | 50      | 25        | 22.09                | 22.04                | 22.05                | 1   |
|            |            | 50      | 50        | 22.06                | 22.01                | 22.02                | 1   |
|            |            | 100     | 0         | 22.07                | 22.02                | 22.03                | 1   |
|            | 16QAM      | 1       | 0         | 22.04                | 21.99                | 22.00                | 1   |
|            |            | 1       | 50        | 22.02                | 21.97                | 21.98                | 1   |
|            |            | 1       | 99        | 21.99                | 21.94                | 21.95                | 1   |
|            |            | 50      | 0         | 21.03                | 20.98                | 20.99                | 2   |
|            |            | 50      | 25        | 21.00                | 20.95                | 20.96                | 2   |
|            |            | 50      | 50        | 20.98                | 20.93                | 20.94                | 2   |
|            |            | 100     | 0         | 20.98                | 20.93                | 20.94                | 2   |

| LTE Band 12 |            |         |           |                     |                     |                     |     |
|-------------|------------|---------|-----------|---------------------|---------------------|---------------------|-----|
| BW          | Modulation | RB Size | RB Offset | Low CH 23017        | Mid CH 23095        | High CH 23173       | MPR |
|             |            |         |           | Frequency 699.7 MHz | Frequency 707.5 MHz | Frequency 715.3 MHz |     |
| 1.4 MHz     | QPSK       | 1       | 0         | 22.46               | 22.63               | 22.49               | 0   |
|             |            | 1       | 2         | 22.34               | 22.51               | 22.37               | 0   |
|             |            | 1       | 5         | 22.31               | 22.48               | 22.34               | 0   |
|             |            | 3       | 0         | 22.44               | 22.61               | 22.47               | 0   |
|             |            | 3       | 1         | 22.32               | 22.49               | 22.35               | 0   |
|             |            | 3       | 3         | 22.29               | 22.46               | 22.32               | 0   |
|             |            | 6       | 0         | 21.55               | 21.72               | 21.58               | 1   |
|             | 16QAM      | 1       | 0         | 21.53               | 21.70               | 21.56               | 1   |
|             |            | 1       | 2         | 21.49               | 21.66               | 21.52               | 1   |
|             |            | 1       | 5         | 21.43               | 21.60               | 21.46               | 1   |
|             |            | 3       | 0         | 21.52               | 21.69               | 21.55               | 1   |
|             |            | 3       | 1         | 21.48               | 21.65               | 21.51               | 1   |
|             |            | 3       | 3         | 21.42               | 21.59               | 21.45               | 1   |
|             |            | 6       | 0         | 20.54               | 20.71               | 20.57               | 2   |
| LTE Band 12 |            |         |           |                     |                     |                     |     |
| BW          | Modulation | RB Size | RB Offset | Low CH 23025        | Mid CH 23095        | High CH 23165       | MPR |
|             |            |         |           | Frequency 700.5 MHz | Frequency 707.5 MHz | Frequency 714.5 MHz |     |
| 3 MHz       | QPSK       | 1       | 0         | 22.50               | 22.67               | 22.53               | 0   |
|             |            | 1       | 7         | 22.38               | 22.55               | 22.41               | 0   |
|             |            | 1       | 14        | 22.35               | 22.52               | 22.38               | 0   |
|             |            | 8       | 0         | 21.55               | 21.72               | 21.58               | 1   |
|             |            | 8       | 3         | 21.52               | 21.69               | 21.55               | 1   |
|             |            | 8       | 7         | 21.48               | 21.65               | 21.51               | 1   |
|             |            | 15      | 0         | 21.59               | 21.76               | 21.62               | 1   |
|             | 16QAM      | 1       | 0         | 21.57               | 21.74               | 21.60               | 1   |
|             |            | 1       | 7         | 21.53               | 21.70               | 21.56               | 1   |
|             |            | 1       | 14        | 21.47               | 21.64               | 21.50               | 1   |
|             |            | 8       | 0         | 20.56               | 20.73               | 20.59               | 2   |
|             |            | 8       | 3         | 20.53               | 20.70               | 20.56               | 2   |
|             |            | 8       | 7         | 20.50               | 20.67               | 20.53               | 2   |
|             |            | 15      | 0         | 20.58               | 20.75               | 20.61               | 2   |

| LTE Band 12 |            |         |           |                     |                     |                     |     |
|-------------|------------|---------|-----------|---------------------|---------------------|---------------------|-----|
| BW          | Modulation | RB Size | RB Offset | Low CH 23035        | Mid CH 23095        | High CH 23155       | MPR |
|             |            |         |           | Frequency 701.5 MHz | Frequency 707.5 MHz | Frequency 713.5 MHz |     |
| 5 MHz       | QPSK       | 1       | 0         | 22.56               | 22.73               | 22.59               | 0   |
|             |            | 1       | 12        | 22.44               | 22.61               | 22.47               | 0   |
|             |            | 1       | 24        | 22.41               | 22.58               | 22.44               | 0   |
|             |            | 12      | 0         | 21.61               | 21.78               | 21.64               | 1   |
|             |            | 12      | 6         | 21.58               | 21.75               | 21.61               | 1   |
|             |            | 12      | 13        | 21.54               | 21.71               | 21.57               | 1   |
|             |            | 25      | 0         | 21.65               | 21.82               | 21.68               | 1   |
|             | 16QAM      | 1       | 0         | 21.63               | 21.80               | 21.66               | 1   |
|             |            | 1       | 12        | 21.59               | 21.76               | 21.62               | 1   |
|             |            | 1       | 24        | 21.53               | 21.70               | 21.56               | 1   |
|             |            | 12      | 0         | 20.62               | 20.79               | 20.65               | 2   |
|             |            | 12      | 6         | 20.59               | 20.76               | 20.62               | 2   |
|             |            | 12      | 13        | 20.56               | 20.73               | 20.59               | 2   |
|             |            | 25      | 0         | 20.64               | 20.81               | 20.67               | 2   |
| LTE Band 12 |            |         |           |                     |                     |                     |     |
| BW          | Modulation | RB Size | RB Offset | Low CH 23060        | Mid CH 23095        | High CH 23130       | MPR |
|             |            |         |           | Frequency 704 MHz   | Frequency 707.5 MHz | Frequency 711 MHz   |     |
| 10 MHz      | QPSK       | 1       | 0         | 22.59               | 22.76               | 22.62               | 0   |
|             |            | 1       | 24        | 22.47               | 22.64               | 22.50               | 0   |
|             |            | 1       | 49        | 22.44               | 22.61               | 22.47               | 0   |
|             |            | 25      | 0         | 21.64               | 21.81               | 21.67               | 1   |
|             |            | 25      | 12        | 21.61               | 21.78               | 21.64               | 1   |
|             |            | 25      | 25        | 21.57               | 21.74               | 21.60               | 1   |
|             |            | 50      | 0         | 21.68               | 21.85               | 21.71               | 1   |
|             | 16QAM      | 1       | 0         | 21.66               | 21.83               | 21.69               | 1   |
|             |            | 1       | 24        | 21.62               | 21.79               | 21.65               | 1   |
|             |            | 1       | 49        | 21.56               | 21.73               | 21.59               | 1   |
|             |            | 25      | 0         | 20.65               | 20.82               | 20.68               | 2   |
|             |            | 25      | 12        | 20.62               | 20.79               | 20.65               | 2   |
|             |            | 25      | 25        | 20.59               | 20.76               | 20.62               | 2   |
|             |            | 50      | 0         | 20.67               | 20.84               | 20.70               | 2   |

| LTE Band 17 |            |         |           |                        |                      |                        |     |
|-------------|------------|---------|-----------|------------------------|----------------------|------------------------|-----|
| BW          | Modulation | RB Size | RB Offset | Low CH<br>23755        | Mid CH<br>23790      | High CH<br>23825       | MPR |
|             |            |         |           | Frequency<br>706.5 MHz | Frequency<br>710 MHz | Frequency<br>713.5 MHz |     |
| 5 MHz       | QPSK       | 1       | 0         | 22.50                  | 22.60                | 22.47                  | 0   |
|             |            | 1       | 12        | 22.38                  | 22.48                | 22.35                  | 0   |
|             |            | 1       | 24        | 22.34                  | 22.44                | 22.31                  | 0   |
|             |            | 12      | 0         | 21.57                  | 21.67                | 21.54                  | 1   |
|             |            | 12      | 6         | 21.54                  | 21.64                | 21.51                  | 1   |
|             |            | 12      | 13        | 21.49                  | 21.59                | 21.46                  | 1   |
|             |            | 25      | 0         | 21.62                  | 21.72                | 21.59                  | 1   |
|             | 16QAM      | 1       | 0         | 21.53                  | 21.63                | 21.50                  | 1   |
|             |            | 1       | 12        | 21.50                  | 21.60                | 21.47                  | 1   |
|             |            | 1       | 24        | 21.47                  | 21.57                | 21.44                  | 1   |
|             |            | 12      | 0         | 20.49                  | 20.59                | 20.46                  | 2   |
|             |            | 12      | 6         | 20.45                  | 20.55                | 20.42                  | 2   |
|             |            | 12      | 13        | 20.43                  | 20.53                | 20.40                  | 2   |
|             |            | 25      | 0         | 20.54                  | 20.64                | 20.51                  | 2   |
| BW          | Modulation | RB Size | RB Offset | Low CH<br>23780        | Mid CH<br>23790      | High CH<br>23800       | MPR |
|             |            |         |           | Frequency<br>709 MHz   | Frequency<br>710 MHz | Frequency<br>711 MHz   |     |
| 10 MHz      | QPSK       | 1       | 0         | 22.54                  | 22.64                | 22.51                  | 0   |
|             |            | 1       | 24        | 22.42                  | 22.52                | 22.39                  | 0   |
|             |            | 1       | 49        | 22.38                  | 22.48                | 22.35                  | 0   |
|             |            | 25      | 0         | 21.61                  | 21.71                | 21.58                  | 1   |
|             |            | 25      | 12        | 21.58                  | 21.68                | 21.55                  | 1   |
|             |            | 25      | 25        | 21.53                  | 21.63                | 21.50                  | 1   |
|             |            | 50      | 0         | 21.66                  | 21.76                | 21.63                  | 1   |
|             | 16QAM      | 1       | 0         | 21.57                  | 21.67                | 21.54                  | 1   |
|             |            | 1       | 24        | 21.54                  | 21.64                | 21.51                  | 1   |
|             |            | 1       | 49        | 21.51                  | 21.61                | 21.48                  | 1   |
|             |            | 25      | 0         | 20.53                  | 20.63                | 20.50                  | 2   |
|             |            | 25      | 12        | 20.49                  | 20.59                | 20.46                  | 2   |
|             |            | 25      | 25        | 20.47                  | 20.57                | 20.44                  | 2   |
|             |            | 50      | 0         | 20.58                  | 20.68                | 20.55                  | 2   |



Test Report No.: RF170410W004-5

## EIRP

### WCDMA IV

| Channel | Frequency (MHz) | SPA LVL (dBm) | Correction Factor(dB) | EIRP(dBm) | EIRP(mW)      | Polarization (H/V) |
|---------|-----------------|---------------|-----------------------|-----------|---------------|--------------------|
| 1312    | 1712.4          | -26.56        | 41.39                 | 14.83     | 30.40         | H                  |
| 1413    | 1732.6          | -25.72        | 41.36                 | 15.64     | 36.64         | H                  |
| 1513    | 1752.6          | -24.86        | 42.63                 | 17.77     | 59.83         | H                  |
| 1312    | 1712.4          | -24.13        | 44.17                 | 20.04     | <b>100.83</b> | V                  |
| 1413    | 1732.6          | -24.18        | 44.20                 | 20.02     | 100.46        | V                  |
| 1513    | 1752.6          | -24.06        | 44.35                 | 20.29     | 106.78        | V                  |

**REMARKS:** 1. EIRP Output Power (dBm) = SPA LVL (dBm) + Correction Factor (dB).  
2. Correction factor (dB) = Free Space Loss + Antenna Factor + Cable Loss

### LTE BAND 4

#### CHANNEL BANDWIDTH: 1.4MHz QPSK

| Channel | Frequency (MHz) | SPA LVL (dBm) | Correction Factor(dB) | EIRP(dBm) | EIRP(mW)      | Polarization (H/V) | LIMIT (W) |
|---------|-----------------|---------------|-----------------------|-----------|---------------|--------------------|-----------|
| 19957   | 1710.7          | -21.84        | 41.29                 | 19.45     | 88.19         | H                  | 1         |
| 20175   | 1732.5          | -21.35        | 41.36                 | 20.01     | 100.23        | H                  | 1         |
| 20393   | 1754.3          | -22.22        | 42.74                 | 20.52     | 112.67        | H                  | 1         |
| 19957   | 1710.7          | -20.54        | 44.25                 | 23.71     | <b>234.69</b> | V                  | 1         |
| 20175   | 1732.5          | -21.33        | 44.20                 | 22.87     | 193.64        | V                  | 1         |
| 20393   | 1754.3          | -20.54        | 44.09                 | 23.55     | 226.20        | V                  | 1         |

#### CHANNEL BANDWIDTH: 1.4MHz 16QAM

| Channel | Frequency (MHz) | SPA LVL (dBm) | Correction Factor(dB) | EIRP(dBm) | EIRP(mW) | Polarization (H/V) | LIMIT (W) |
|---------|-----------------|---------------|-----------------------|-----------|----------|--------------------|-----------|
| 19957   | 1710.7          | -22.71        | 41.29                 | 18.58     | 72.18    | H                  | 1         |
| 20175   | 1732.5          | -22.28        | 41.36                 | 19.08     | 80.91    | H                  | 1         |
| 20393   | 1754.3          | -23.18        | 42.74                 | 19.56     | 90.32    | H                  | 1         |
| 19957   | 1710.7          | -21.41        | 44.25                 | 22.84     | 192.09   | V                  | 1         |
| 20175   | 1732.5          | -22.26        | 44.20                 | 21.94     | 156.31   | V                  | 1         |
| 20393   | 1754.3          | -21.50        | 44.09                 | 22.59     | 181.34   | V                  | 1         |

#### LTE BAND 4

##### CHANNEL BANDWIDTH: 3MHz QPSK

| Channel | Frequency (MHz) | SPA LVL (dBm) | Correction Factor(dB) | EIRP(dBm) | EIRP(mW)      | Polarization (H/V) | LIMIT (W) |
|---------|-----------------|---------------|-----------------------|-----------|---------------|--------------------|-----------|
| 19965   | 1711.5          | -21.82        | 41.27                 | 19.45     | 88.04         | H                  | 1         |
| 20175   | 1732.5          | -21.41        | 41.36                 | 19.95     | 98.86         | H                  | 1         |
| 20385   | 1753.5          | -22.17        | 42.76                 | 20.59     | 114.47        | H                  | 1         |
| 19965   | 1711.5          | -20.52        | 44.26                 | 23.74     | <b>236.70</b> | V                  | 1         |
| 20175   | 1732.5          | -21.39        | 44.20                 | 22.81     | 190.99        | V                  | 1         |
| 20385   | 1753.5          | -20.49        | 44.23                 | 23.74     | 236.70        | V                  | 1         |

##### CHANNEL BANDWIDTH: 3MHz 16QAM

| Channel | Frequency (MHz) | SPA LVL (dBm) | Correction Factor(dB) | EIRP(dBm) | EIRP(mW) | Polarization (H/V) | LIMIT (W) |
|---------|-----------------|---------------|-----------------------|-----------|----------|--------------------|-----------|
| 19965   | 1711.5          | -22.89        | 41.27                 | 18.38     | 68.82    | H                  | 1         |
| 20175   | 1732.5          | -22.30        | 41.36                 | 19.06     | 80.54    | H                  | 1         |
| 20385   | 1753.5          | -23.16        | 42.76                 | 19.60     | 91.14    | H                  | 1         |
| 19965   | 1711.5          | -21.59        | 44.26                 | 22.67     | 185.01   | V                  | 1         |
| 20175   | 1732.5          | -22.28        | 44.20                 | 21.92     | 155.60   | V                  | 1         |
| 20385   | 1753.5          | -21.48        | 44.23                 | 22.75     | 188.45   | V                  | 1         |

#### LTE BAND 4

##### CHANNEL BANDWIDTH: 5MHz QPSK

| Channel | Frequency (MHz) | SPA LVL (dBm) | Correction Factor(dB) | EIRP(dBm) | EIRP(mW)      | Polarization (H/V) | LIMIT (W) |
|---------|-----------------|---------------|-----------------------|-----------|---------------|--------------------|-----------|
| 19975   | 1712.5          | -21.88        | 41.39                 | 19.51     | 89.31         | H                  | 1         |
| 20175   | 1732.5          | -21.36        | 41.36                 | 20.00     | 100.00        | H                  | 1         |
| 20375   | 1752.5          | -22.12        | 42.63                 | 20.51     | 112.43        | H                  | 1         |
| 19975   | 1712.5          | -20.58        | 44.17                 | 23.59     | 228.35        | V                  | 1         |
| 20175   | 1732.5          | -21.34        | 44.20                 | 22.86     | 193.20        | V                  | 1         |
| 20375   | 1752.5          | -20.44        | 44.35                 | 23.91     | <b>245.75</b> | V                  | 1         |

CHANNEL BANDWIDTH: 5MHz 16QAM

| Channel | Frequency (MHz) | SPA LVL (dBm) | Correction Factor(dB) | EIRP(dBm) | EIRP(mW) | Polarization (H/V) | LIMIT (W) |
|---------|-----------------|---------------|-----------------------|-----------|----------|--------------------|-----------|
| 19975   | 1712.5          | -22.71        | 41.39                 | 18.68     | 73.77    | H                  | 1         |
| 20175   | 1732.5          | -22.38        | 41.36                 | 18.98     | 79.07    | H                  | 1         |
| 20375   | 1752.5          | -23.22        | 42.63                 | 19.41     | 87.28    | H                  | 1         |
| 19975   | 1712.5          | -21.41        | 44.17                 | 22.76     | 188.63   | V                  | 1         |
| 20175   | 1732.5          | -22.36        | 44.20                 | 21.84     | 152.76   | V                  | 1         |
| 20375   | 1752.5          | -21.54        | 44.35                 | 22.81     | 190.77   | V                  | 1         |

LTE BAND 4

CHANNEL BANDWIDTH: 10MHz QPSK

| Channel | Frequency (MHz) | SPA LVL (dBm) | Correction Factor(dB) | EIRP(dBm) | EIRP(mW)      | Polarization (H/V) | LIMIT (W) |
|---------|-----------------|---------------|-----------------------|-----------|---------------|--------------------|-----------|
| 20000   | 1715.0          | -21.69        | 41.49                 | 19.80     | 95.41         | H                  | 1         |
| 20175   | 1732.5          | -21.30        | 41.36                 | 20.06     | 101.39        | H                  | 1         |
| 20350   | 1750.0          | -21.99        | 42.28                 | 20.29     | 106.98        | H                  | 1         |
| 20000   | 1715.0          | -20.39        | 44.06                 | 23.67     | 232.97        | V                  | 1         |
| 20175   | 1732.5          | -21.28        | 44.20                 | 22.92     | 195.88        | V                  | 1         |
| 20350   | 1750.0          | -20.31        | 44.43                 | 24.12     | <b>258.23</b> | V                  | 1         |

CHANNEL BANDWIDTH: 10MHz 16QAM

| Channel | Frequency (MHz) | SPA LVL (dBm) | Correction Factor(dB) | EIRP(dBm) | EIRP(mW) | Polarization (H/V) | LIMIT (W) |
|---------|-----------------|---------------|-----------------------|-----------|----------|--------------------|-----------|
| 20000   | 1715.0          | -22.84        | 41.49                 | 18.65     | 73.21    | H                  | 1         |
| 20175   | 1732.5          | -22.40        | 41.36                 | 18.96     | 78.70    | H                  | 1         |
| 20350   | 1750.0          | -23.15        | 42.28                 | 19.13     | 81.90    | H                  | 1         |
| 20000   | 1715.0          | -21.54        | 44.06                 | 22.52     | 178.77   | V                  | 1         |
| 20175   | 1732.5          | -22.38        | 44.20                 | 21.82     | 152.05   | V                  | 1         |
| 20350   | 1750.0          | -21.47        | 44.43                 | 22.96     | 197.70   | V                  | 1         |



Test Report No.: RF170410W004-5

#### LTE BAND 4

##### CHANNEL BANDWIDTH: 15MHz QPSK

| Channel | Frequency (MHz) | SPA LVL (dBm) | Correction Factor(dB) | EIRP(dBm) | EIRP(mW)      | Polarization (H/V) | LIMIT (W) |
|---------|-----------------|---------------|-----------------------|-----------|---------------|--------------------|-----------|
| 20025   | 1717.5          | -21.70        | 41.34                 | 19.64     | 92.00         | H                  | 1         |
| 20175   | 1732.5          | -21.37        | 41.36                 | 19.99     | 99.77         | H                  | 1         |
| 20325   | 1747.5          | -22.06        | 42.09                 | 20.03     | 100.60        | H                  | 1         |
| 20025   | 1717.5          | -20.40        | 44.04                 | 23.64     | 231.42        | V                  | 1         |
| 20175   | 1732.5          | -21.35        | 44.20                 | 22.85     | 192.75        | V                  | 1         |
| 20325   | 1747.5          | -20.38        | 44.22                 | 23.84     | <b>241.82</b> | V                  | 1         |

##### CHANNEL BANDWIDTH: 15MHz 16QAM

| Channel | Frequency (MHz) | SPA LVL (dBm) | Correction Factor(dB) | EIRP(dBm) | EIRP(mW) | Polarization (H/V) | LIMIT (W) |
|---------|-----------------|---------------|-----------------------|-----------|----------|--------------------|-----------|
| 20025   | 1717.5          | -22.56        | 41.34                 | 18.78     | 75.47    | H                  | 1         |
| 20175   | 1732.5          | -22.24        | 41.36                 | 19.12     | 81.66    | H                  | 1         |
| 20325   | 1747.5          | -22.91        | 42.09                 | 19.18     | 82.72    | H                  | 1         |
| 20025   | 1717.5          | -21.26        | 44.04                 | 22.78     | 189.85   | V                  | 1         |
| 20175   | 1732.5          | -22.22        | 44.20                 | 21.98     | 157.76   | V                  | 1         |
| 20325   | 1747.5          | -21.23        | 44.22                 | 22.99     | 198.84   | V                  | 1         |

#### LTE BAND 4

##### CHANNEL BANDWIDTH: 20MHz QPSK

| Channel | Frequency (MHz) | SPA LVL (dBm) | Correction Factor(dB) | EIRP(dBm) | EIRP(mW)      | Polarization (H/V) | LIMIT (W) |
|---------|-----------------|---------------|-----------------------|-----------|---------------|--------------------|-----------|
| 20050   | 1720.0          | -22.28        | 41.28                 | 19.00     | 79.45         | H                  | 1         |
| 20175   | 1732.5          | -21.82        | 41.36                 | 19.54     | 89.97         | H                  | 1         |
| 20300   | 1745.0          | -22.64        | 41.96                 | 19.32     | 85.45         | H                  | 1         |
| 20050   | 1720.0          | -20.98        | 44.14                 | 23.16     | <b>206.78</b> | V                  | 1         |
| 20175   | 1732.5          | -21.80        | 44.20                 | 22.40     | 173.62        | V                  | 1         |
| 20300   | 1745.0          | -20.96        | 43.88                 | 22.92     | 195.97        | V                  | 1         |



Test Report No.: RF170410W004-5

#### CHANNEL BANDWIDTH: 20MHz 16QAM

| Channel | Frequency (MHz) | SPA LVL (dBm) | Correction Factor(dB) | EIRP(dBm) | EIRP(mW) | Polarization (H/V) | LIMIT (W) |
|---------|-----------------|---------------|-----------------------|-----------|----------|--------------------|-----------|
| 20050   | 1720.0          | -23.21        | 41.28                 | 18.07     | 64.14    | H                  | 1         |
| 20175   | 1732.5          | -22.89        | 41.36                 | 18.47     | 70.32    | H                  | 1         |
| 20300   | 1745.0          | -23.47        | 41.96                 | 18.49     | 70.58    | H                  | 1         |
| 20050   | 1720.0          | -21.91        | 44.14                 | 22.23     | 166.92   | V                  | 1         |
| 20175   | 1732.5          | -22.87        | 44.20                 | 21.33     | 135.71   | V                  | 1         |
| 20300   | 1745.0          | -21.79        | 43.88                 | 22.09     | 161.88   | V                  | 1         |

**REMARKS:** 1. EIRP Output Power (dBm) = SPA LVL (dBm) + Correction Factor (dB).  
2. Correction factor (dB) = Free Space Loss + Antenna Factor + Cable Loss

#### LTE BAND 12

#### CHANNEL BANDWIDTH: 1.4MHz QPSK

| Channel | Frequency (MHz) | SPA LVL (dBm) | Correction Factor(dB) | ERP(dBm) | ERP(mW)       | Polarization (H/V) | LIMIT (W) |
|---------|-----------------|---------------|-----------------------|----------|---------------|--------------------|-----------|
| 23017   | 699.7           | -9.46         | 32.77                 | 21.16    | 130.62        | H                  | 3         |
| 23095   | 707.5           | -8.63         | 33.23                 | 22.45    | <b>175.79</b> | H                  | 3         |
| 23173   | 715.3           | -8.95         | 33.14                 | 22.04    | 159.88        | H                  | 3         |
| 23017   | 699.7           | -18.77        | 32.42                 | 11.50    | 14.11         | V                  | 3         |
| 23095   | 707.5           | -18.18        | 32.60                 | 12.27    | 16.87         | V                  | 3         |
| 23173   | 715.3           | -19.04        | 32.19                 | 11.00    | 12.58         | V                  | 3         |

#### CHANNEL BANDWIDTH: 1.4MHz 16QAM

| Channel | Frequency (MHz) | SPA LVL (dBm) | Correction Factor(dB) | ERP(dBm) | ERP(mW) | Polarization (H/V) | LIMIT (W) |
|---------|-----------------|---------------|-----------------------|----------|---------|--------------------|-----------|
| 23017   | 699.7           | -10.29        | 32.77                 | 20.33    | 107.89  | H                  | 3         |
| 23095   | 707.5           | -9.65         | 33.23                 | 21.43    | 139.00  | H                  | 3         |
| 23173   | 715.3           | -10.05        | 33.14                 | 20.94    | 124.11  | H                  | 3         |
| 23017   | 699.7           | -19.60        | 32.42                 | 10.67    | 11.66   | V                  | 3         |
| 23095   | 707.5           | -19.20        | 32.60                 | 11.25    | 13.34   | V                  | 3         |
| 23173   | 715.3           | -20.14        | 32.19                 | 9.90     | 9.76    | V                  | 3         |



Test Report No.: RF170410W004-5

## LTE BAND 12

### CHANNEL BANDWIDTH: 3MHz QPSK

| Channel | Frequency (MHz) | SPA LVL (dBm) | Correction Factor(dB) | ERP(dBm) | ERP(mW)       | Polarization (H/V) | LIMIT (W) |
|---------|-----------------|---------------|-----------------------|----------|---------------|--------------------|-----------|
| 23025   | 700.5           | -9.27         | 32.63                 | 21.21    | 132.16        | H                  | 3         |
| 23095   | 707.5           | -8.57         | 33.23                 | 22.51    | <b>178.24</b> | H                  | 3         |
| 23165   | 714.5           | -8.82         | 33.21                 | 22.24    | 167.30        | H                  | 3         |
| 23025   | 700.5           | -18.58        | 32.33                 | 11.60    | 14.44         | V                  | 3         |
| 23095   | 707.5           | -18.12        | 32.60                 | 12.33    | 17.10         | V                  | 3         |
| 23165   | 714.5           | -18.91        | 32.30                 | 11.24    | 13.31         | V                  | 3         |

### CHANNEL BANDWIDTH: 3MHz 16QAM

| Channel | Frequency (MHz) | SPA LVL (dBm) | Correction Factor(dB) | ERP(dBm) | ERP(mW) | Polarization (H/V) | LIMIT (W) |
|---------|-----------------|---------------|-----------------------|----------|---------|--------------------|-----------|
| 23025   | 700.5           | -10.42        | 32.63                 | 20.06    | 101.41  | H                  | 3         |
| 23095   | 707.5           | -9.67         | 33.23                 | 21.41    | 138.36  | H                  | 3         |
| 23165   | 714.5           | -9.98         | 33.21                 | 21.08    | 128.09  | H                  | 3         |
| 23025   | 700.5           | -19.73        | 32.33                 | 10.45    | 11.08   | V                  | 3         |
| 23095   | 707.5           | -19.22        | 32.60                 | 11.23    | 13.27   | V                  | 3         |
| 23165   | 714.5           | -20.07        | 32.30                 | 10.08    | 10.19   | V                  | 3         |

## LTE BAND 12

### CHANNEL BANDWIDTH: 5MHz QPSK

| Channel | Frequency (MHz) | SPA LVL (dBm) | Correction Factor(dB) | ERP(dBm) | ERP(mW)       | Polarization (H/V) | LIMIT (W) |
|---------|-----------------|---------------|-----------------------|----------|---------------|--------------------|-----------|
| 23035   | 701.5           | -9.28         | 32.53                 | 21.10    | 128.68        | H                  | 3         |
| 23095   | 707.5           | -8.64         | 33.23                 | 22.44    | <b>175.31</b> | H                  | 3         |
| 23155   | 713.5           | -8.89         | 33.29                 | 22.25    | 167.76        | H                  | 3         |
| 23035   | 701.5           | -18.59        | 32.25                 | 11.51    | 14.17         | V                  | 3         |
| 23095   | 707.5           | -18.19        | 32.60                 | 12.26    | 16.83         | V                  | 3         |
| 23155   | 713.5           | -18.98        | 32.39                 | 11.26    | 13.35         | V                  | 3         |



Test Report No.: RF170410W004-5

**CHANNEL BANDWIDTH: 5MHz 16QAM**

| Channel | Frequency (MHz) | SPA LVL (dBm) | Correction Factor(dB) | ERP(dBm) | ERP(mW) | Polarization (H/V) | LIMIT (W) |
|---------|-----------------|---------------|-----------------------|----------|---------|--------------------|-----------|
| 23035   | 701.5           | -10.14        | 32.53                 | 20.24    | 105.56  | H                  | 3         |
| 23095   | 707.5           | -9.51         | 33.23                 | 21.57    | 143.48  | H                  | 3         |
| 23155   | 713.5           | -9.74         | 33.29                 | 21.40    | 137.94  | H                  | 3         |
| 23035   | 701.5           | -19.45        | 32.25                 | 10.65    | 11.63   | V                  | 3         |
| 23095   | 707.5           | -19.06        | 32.60                 | 11.39    | 13.77   | V                  | 3         |
| 23155   | 713.5           | -19.83        | 32.39                 | 10.41    | 10.98   | V                  | 3         |

**LTE BAND 12**

**CHANNEL BANDWIDTH: 10MHz QPSK**

| Channel | Frequency (MHz) | SPA LVL (dBm) | Correction Factor(dB) | ERP(dBm) | ERP(mW)       | Polarization (H/V) | LIMIT (W) |
|---------|-----------------|---------------|-----------------------|----------|---------------|--------------------|-----------|
| 23060   | 704.0           | -9.86         | 32.68                 | 20.67    | 116.76        | H                  | 3         |
| 23095   | 707.5           | -9.09         | 33.23                 | 21.99    | <b>158.12</b> | H                  | 3         |
| 23130   | 711.0           | -9.47         | 33.39                 | 21.77    | 150.21        | H                  | 3         |
| 23060   | 704.0           | -19.17        | 32.37                 | 11.05    | 12.73         | V                  | 3         |
| 23095   | 707.5           | -18.64        | 32.60                 | 11.81    | 15.17         | V                  | 3         |
| 23130   | 711.0           | -19.56        | 32.56                 | 10.85    | 12.15         | V                  | 3         |

**CHANNEL BANDWIDTH: 10MHz 16QAM**

| Channel | Frequency (MHz) | SPA LVL (dBm) | Correction Factor(dB) | ERP(dBm) | ERP(mW) | Polarization (H/V) | LIMIT (W) |
|---------|-----------------|---------------|-----------------------|----------|---------|--------------------|-----------|
| 23060   | 704.0           | -10.79        | 32.68                 | 19.74    | 94.25   | H                  | 3         |
| 23095   | 707.5           | -10.16        | 33.23                 | 20.92    | 123.59  | H                  | 3         |
| 23130   | 711.0           | -10.30        | 33.39                 | 20.94    | 124.08  | H                  | 3         |
| 23060   | 704.0           | -20.10        | 32.37                 | 10.12    | 10.28   | V                  | 3         |
| 23095   | 707.5           | -19.71        | 32.60                 | 10.74    | 11.86   | V                  | 3         |
| 23130   | 711.0           | -20.39        | 32.56                 | 10.02    | 10.03   | V                  | 3         |

**REMARKS:** 1. ERP Output Power (dBm) = SPA LVL (dBm) + Correction Factor (dB) -2.15(dB).  
2. Correction factor (dB) = Free Space Loss + Antenna Factor + Cable Loss



Test Report No.: RF170410W004-5

## LTE BAND 17

### CHANNEL BANDWIDTH: 5MHz QPSK

| Channel | Frequency (MHz) | SPA LVL (dBm) | Correction Factor(dB) | ERP(dBm) | ERP(mW)       | Polarization (H/V) | LIMIT (W) |
|---------|-----------------|---------------|-----------------------|----------|---------------|--------------------|-----------|
| 23755   | 706.5           | -8.85         | 32.64                 | 21.64    | 145.71        | H                  | 3         |
| 23790   | 710.0           | -8.97         | 32.92                 | 21.80    | <b>151.36</b> | H                  | 3         |
| 23825   | 713.5           | -9.07         | 32.83                 | 21.61    | 144.74        | H                  | 3         |
| 23755   | 706.5           | -17.20        | 32.14                 | 12.79    | 18.99         | V                  | 3         |
| 23790   | 710.0           | -17.45        | 32.18                 | 12.58    | 18.11         | V                  | 3         |
| 23825   | 713.5           | -17.73        | 31.95                 | 12.07    | 16.12         | V                  | 3         |

### CHANNEL BANDWIDTH: 5MHz 16QAM

| Channel | Frequency (MHz) | SPA LVL (dBm) | Correction Factor(dB) | ERP(dBm) | ERP(mW) | Polarization (H/V) | LIMIT (W) |
|---------|-----------------|---------------|-----------------------|----------|---------|--------------------|-----------|
| 23755   | 706.5           | -9.71         | 32.64                 | 20.78    | 119.54  | H                  | 3         |
| 23790   | 710.0           | -9.84         | 32.92                 | 20.93    | 123.88  | H                  | 3         |
| 23825   | 713.5           | -9.92         | 32.83                 | 20.76    | 119.01  | H                  | 3         |
| 23755   | 706.5           | -18.06        | 32.14                 | 11.93    | 15.58   | V                  | 3         |
| 23790   | 710.0           | -18.32        | 32.18                 | 11.71    | 14.83   | V                  | 3         |
| 23825   | 713.5           | -18.58        | 31.95                 | 11.22    | 13.26   | V                  | 3         |

## LTE BAND 17

### CHANNEL BANDWIDTH: 10MHz QPSK

| Channel | Frequency (MHz) | SPA LVL (dBm) | Correction Factor(dB) | ERP(dBm) | ERP(mW)       | Polarization (H/V) | LIMIT (W) |
|---------|-----------------|---------------|-----------------------|----------|---------------|--------------------|-----------|
| 23780   | 709.0           | -9.43         | 32.90                 | 21.32    | 135.36        | H                  | 3         |
| 23790   | 710.0           | -9.42         | 32.92                 | 21.35    | <b>136.40</b> | H                  | 3         |
| 23800   | 711.0           | -9.65         | 32.92                 | 21.12    | 129.45        | H                  | 3         |
| 23780   | 709.0           | -17.78        | 32.20                 | 12.27    | 16.85         | V                  | 3         |
| 23790   | 710.0           | -17.90        | 32.18                 | 12.13    | 16.34         | V                  | 3         |
| 23800   | 711.0           | -18.31        | 32.13                 | 11.67    | 14.69         | V                  | 3         |

### CHANNEL BANDWIDTH: 10MHz 16QAM

| Channel | Frequency (MHz) | SPA LVL (dBm) | Correction Factor(dB) | ERP(dBm) | ERP(mW) | Polarization (H/V) | LIMIT (W) |
|---------|-----------------|---------------|-----------------------|----------|---------|--------------------|-----------|
| 23780   | 709.0           | -10.36        | 32.90                 | 20.39    | 109.27  | H                  | 3         |
| 23790   | 710.0           | -10.49        | 32.92                 | 20.28    | 106.61  | H                  | 3         |
| 23800   | 711.0           | -10.48        | 32.92                 | 20.29    | 106.93  | H                  | 3         |
| 23780   | 709.0           | -18.71        | 32.20                 | 11.34    | 13.60   | V                  | 3         |
| 23790   | 710.0           | -18.97        | 32.18                 | 11.06    | 12.77   | V                  | 3         |
| 23800   | 711.0           | -19.14        | 32.13                 | 10.84    | 12.14   | V                  | 3         |

**REMARKS:** 1. ERP Output Power (dBm) = SPA LVL (dBm) + Correction Factor (dB) -2.15(dB).  
2. Correction factor (dB) = Free Space Loss + Antenna Factor + Cable Loss

## 4.2 FREQUENCY STABILITY MEASUREMENT

### 4.2.1 LIMITS OF FREQUENCY STABILITY MEASUREMENT


The frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation.

### 4.2.2 TEST PROCEDURE

- Device is placed at the oven room. The oven room could control the temperatures and humidity. Power warm up is at least 15 min and power applied should perform before recording frequency error.
- EUT is connected the external power supply to control the DC input power. The test voltage range is from minimum to maximum working voltage. Each step shall be record the frequency error rate.
- The temperature range step is 10 degrees in this test items. All temperature levels shall be hold the  $\pm 0.5^{\circ}\text{C}$  during the measurement testing. The each temperature step shall be at least 0.5 hours, consider the EUT could be test under the stability condition.

**NOTE:** The frequency error was recorded frequency error from the communication simulator.

### 4.2.3 TEST SETUP



## 4.2.4 TEST RESULTS

### WCDMA BAND IV

#### FREQUENCY ERROR VS. VOLTAGE

| VOLTAGE (Volts) | FREQUENCY ERROR (ppm) |              | LIMIT (ppm) |
|-----------------|-----------------------|--------------|-------------|
|                 | Low Channel           | High Channel |             |
| 3.85            | 0.0019                | 0.0017       | 2.5         |
| 3.3             | 0.0014                | 0.0013       | 2.5         |
| 4.4             | 0.0012                | 0.0011       | 2.5         |

**NOTE:** The applicant defined the normal working voltage of the battery is from 3.3Vdc to 4.4Vdc.

#### FREQUENCY ERROR vs. TEMPERATURE.

| TEMP. (°C) | FREQUENCY ERROR (ppm) |              | LIMIT (ppm) |
|------------|-----------------------|--------------|-------------|
|            | Low Channel           | High Channel |             |
| -30        | -0.0057               | -0.0054      | 2.5         |
| -20        | -0.0052               | -0.0050      | 2.5         |
| -10        | -0.0044               | -0.0042      | 2.5         |
| 0          | -0.0038               | -0.0036      | 2.5         |
| 10         | -0.0031               | -0.0029      | 2.5         |
| 20         | -0.0024               | -0.0023      | 2.5         |
| 30         | -0.0021               | -0.0020      | 2.5         |
| 40         | -0.0017               | -0.0015      | 2.5         |
| 50         | -0.0013               | -0.0012      | 2.5         |
| 60         | -0.0005               | -0.0004      | 2.5         |

## LTE BAND 4

### FREQUENCY ERROR VS. VOLTAGE

| VOLTAGE (Volts) | 1.4MHz                |              | LIMIT (ppm) |
|-----------------|-----------------------|--------------|-------------|
|                 | FREQUENCY ERROR (ppm) |              |             |
|                 | Low Channel           | High Channel |             |
| 3.85            | 0.0014                | 0.0016       | 2.5         |
| 3.3             | 0.0012                | 0.0014       | 2.5         |
| 4.4             | 0.0011                | 0.0013       | 2.5         |

**NOTE:** The applicant defined the normal working voltage of the battery is from 3.3Vdc to 4.4Vdc.

### FREQUENCY ERROR vs. TEMPERATURE.

| TEMP. (°C) | 1.4MHz                |              | LIMIT (ppm) |
|------------|-----------------------|--------------|-------------|
|            | FREQUENCY ERROR (ppm) |              |             |
|            | Low Channel           | High Channel |             |
| -30        | -0.0060               | -0.0062      | 2.5         |
| -20        | -0.0056               | -0.0057      | 2.5         |
| -10        | -0.0047               | -0.0048      | 2.5         |
| 0          | -0.0040               | -0.0041      | 2.5         |
| 10         | -0.0034               | -0.0034      | 2.5         |
| 20         | -0.0026               | -0.0027      | 2.5         |
| 30         | -0.0023               | -0.0023      | 2.5         |
| 40         | -0.0018               | -0.0019      | 2.5         |
| 50         | -0.0014               | -0.0015      | 2.5         |
| 60         | -0.0007               | -0.0007      | 2.5         |

#### FREQUENCY ERROR VS. VOLTAGE

| VOLTAGE (Volts) | 3MHz                  |              | LIMIT (ppm) |
|-----------------|-----------------------|--------------|-------------|
|                 | FREQUENCY ERROR (ppm) |              |             |
|                 | Low Channel           | High Channel |             |
| 3.85            | 0.0014                | 0.0015       | 2.5         |
| 3.3             | 0.0013                | 0.0013       | 2.5         |
| 4.4             | 0.0011                | 0.0012       | 2.5         |

**NOTE:** The applicant defined the normal working voltage of the battery is from 3.3Vdc to 4.4Vdc.

#### FREQUENCY ERROR vs. TEMPERATURE.

| TEMP. (°C) | 3MHz                  |              | LIMIT (ppm) |
|------------|-----------------------|--------------|-------------|
|            | FREQUENCY ERROR (ppm) |              |             |
|            | Low Channel           | High Channel |             |
| -30        | -0.0065               | -0.0064      | 2.5         |
| -20        | -0.0059               | -0.0058      | 2.5         |
| -10        | -0.0056               | -0.0055      | 2.5         |
| 0          | -0.0048               | -0.0047      | 2.5         |
| 10         | -0.0041               | -0.0040      | 2.5         |
| 20         | -0.0033               | -0.0032      | 2.5         |
| 30         | -0.0026               | -0.0025      | 2.5         |
| 40         | -0.0023               | -0.0022      | 2.5         |
| 50         | -0.0018               | -0.0018      | 2.5         |
| 60         | -0.0012               | -0.0011      | 2.5         |

#### FREQUENCY ERROR VS. VOLTAGE

| VOLTAGE (Volts) | 5MHz                  |              | LIMIT (ppm) |
|-----------------|-----------------------|--------------|-------------|
|                 | FREQUENCY ERROR (ppm) |              |             |
|                 | Low Channel           | High Channel |             |
| 3.85            | 0.0017                | 0.0017       | 2.5         |
| 3.3             | 0.0012                | 0.0015       | 2.5         |
| 4.4             | 0.0012                | 0.0012       | 2.5         |

**NOTE:** The applicant defined the normal working voltage of the battery is from 3.3Vdc to 4.4Vdc.

#### FREQUENCY ERROR vs. TEMPERATURE.

| TEMP. (°C) | 5MHz                  |              | LIMIT (ppm) |
|------------|-----------------------|--------------|-------------|
|            | FREQUENCY ERROR (ppm) |              |             |
|            | Low Channel           | High Channel |             |
| -30        | -0.0066               | -0.0063      | 2.5         |
| -20        | -0.0061               | -0.0058      | 2.5         |
| -10        | -0.0055               | -0.0053      | 2.5         |
| 0          | -0.0051               | -0.0049      | 2.5         |
| 10         | -0.0041               | -0.0039      | 2.5         |
| 20         | -0.0036               | -0.0034      | 2.5         |
| 30         | -0.0030               | -0.0029      | 2.5         |
| 40         | -0.0022               | -0.0021      | 2.5         |
| 50         | -0.0019               | -0.0018      | 2.5         |
| 60         | -0.0014               | -0.0013      | 2.5         |

#### FREQUENCY ERROR VS. VOLTAGE

| VOLTAGE (Volts) | 10MHz                 |              | LIMIT (ppm) |
|-----------------|-----------------------|--------------|-------------|
|                 | FREQUENCY ERROR (ppm) |              |             |
|                 | Low Channel           | High Channel |             |
| 3.85            | 0.0014                | 0.0015       | 2.5         |
| 3.3             | 0.0013                | 0.0011       | 2.5         |
| 4.4             | 0.0012                | 0.0008       | 2.5         |

**NOTE:** The applicant defined the normal working voltage of the battery is from 3.3Vdc to 4.4Vdc.

#### FREQUENCY ERROR vs. TEMPERATURE.

| TEMP. (°C) | 10MHz                 |              | LIMIT (ppm) |
|------------|-----------------------|--------------|-------------|
|            | FREQUENCY ERROR (ppm) |              |             |
|            | Low Channel           | High Channel |             |
| -30        | -0.0061               | -0.0063      | 2.5         |
| -20        | -0.0058               | -0.0059      | 2.5         |
| -10        | -0.0050               | -0.0052      | 2.5         |
| 0          | -0.0046               | -0.0048      | 2.5         |
| 10         | -0.0039               | -0.0039      | 2.5         |
| 20         | -0.0031               | -0.0032      | 2.5         |
| 30         | -0.0029               | -0.0030      | 2.5         |
| 40         | -0.0022               | -0.0023      | 2.5         |
| 50         | -0.0014               | -0.0015      | 2.5         |
| 60         | -0.0010               | -0.0010      | 2.5         |

#### FREQUENCY ERROR VS. VOLTAGE

| VOLTAGE (Volts) | 15MHz                 |              | LIMIT (ppm) |
|-----------------|-----------------------|--------------|-------------|
|                 | FREQUENCY ERROR (ppm) |              |             |
|                 | Low Channel           | High Channel |             |
| 3.85            | 0.0015                | 0.0016       | 2.5         |
| 3.3             | 0.0013                | 0.0013       | 2.5         |
| 4.4             | 0.0012                | 0.0011       | 2.5         |

**NOTE:** The applicant defined the normal working voltage of the battery is from 3.3Vdc to 4.4Vdc.

#### FREQUENCY ERROR vs. TEMPERATURE.

| TEMP. (°C) | 15MHz                 |              | LIMIT (ppm) |
|------------|-----------------------|--------------|-------------|
|            | FREQUENCY ERROR (ppm) |              |             |
|            | Low Channel           | High Channel |             |
| -30        | -0.0061               | -0.0062      | 2.5         |
| -20        | -0.0056               | -0.0057      | 2.5         |
| -10        | -0.0049               | -0.0050      | 2.5         |
| 0          | -0.0043               | -0.0043      | 2.5         |
| 10         | -0.0036               | -0.0037      | 2.5         |
| 20         | -0.0033               | -0.0034      | 2.5         |
| 30         | -0.0029               | -0.0029      | 2.5         |
| 40         | -0.0024               | -0.0024      | 2.5         |
| 50         | -0.0018               | -0.0019      | 2.5         |
| 60         | -0.0015               | -0.0015      | 2.5         |

#### FREQUENCY ERROR VS. VOLTAGE

| VOLTAGE (Volts) | 20MHz                 |              | LIMIT (ppm) |
|-----------------|-----------------------|--------------|-------------|
|                 | FREQUENCY ERROR (ppm) |              |             |
|                 | Low Channel           | High Channel |             |
| 3.85            | 0.0019                | 0.0013       | 2.5         |
| 3.3             | 0.0012                | 0.0013       | 2.5         |
| 4.4             | 0.0008                | 0.0011       | 2.5         |

**NOTE:** The applicant defined the normal working voltage of the battery is from 3.3Vdc to 4.4Vdc.

#### FREQUENCY ERROR vs. TEMPERATURE.

| TEMP. (°C) | 20MHz                 |              | LIMIT (ppm) |
|------------|-----------------------|--------------|-------------|
|            | FREQUENCY ERROR (ppm) |              |             |
|            | Low Channel           | High Channel |             |
| -30        | -0.0064               | -0.0064      | 2.5         |
| -20        | -0.0059               | -0.0060      | 2.5         |
| -10        | -0.0052               | -0.0053      | 2.5         |
| 0          | -0.0044               | -0.0045      | 2.5         |
| 10         | -0.0038               | -0.0038      | 2.5         |
| 20         | -0.0031               | -0.0032      | 2.5         |
| 30         | -0.0029               | -0.0029      | 2.5         |
| 40         | -0.0022               | -0.0022      | 2.5         |
| 50         | -0.0018               | -0.0018      | 2.5         |
| 60         | -0.0013               | -0.0013      | 2.5         |

## LTE BAND 12

### FREQUENCY ERROR VS. VOLTAGE

| VOLTAGE (Volts) | 1.4MHz                |              | LIMIT (ppm) |
|-----------------|-----------------------|--------------|-------------|
|                 | FREQUENCY ERROR (ppm) |              |             |
|                 | Low Channel           | High Channel |             |
| 3.85            | 0.0018                | 0.0019       | 2.5         |
| 3.3             | 0.0016                | 0.0015       | 2.5         |
| 4.4             | 0.0010                | 0.0012       | 2.5         |

**NOTE:** The applicant defined the normal working voltage of the battery is from 3.3Vdc to 4.4Vdc.

### FREQUENCY ERROR vs. TEMPERATURE.

| TEMP. (°C) | 1.4MHz                |              | LIMIT (ppm) |
|------------|-----------------------|--------------|-------------|
|            | FREQUENCY ERROR (ppm) |              |             |
|            | Low Channel           | High Channel |             |
| -30        | -0.0064               | -0.0065      | 2.5         |
| -20        | -0.0058               | -0.0059      | 2.5         |
| -10        | -0.0053               | -0.0054      | 2.5         |
| 0          | -0.0047               | -0.0048      | 2.5         |
| 10         | -0.0040               | -0.0041      | 2.5         |
| 20         | -0.0032               | -0.0033      | 2.5         |
| 30         | -0.0029               | -0.0030      | 2.5         |
| 40         | -0.0024               | -0.0024      | 2.5         |
| 50         | -0.0017               | -0.0017      | 2.5         |
| 60         | -0.0012               | -0.0012      | 2.5         |

**FREQUENCY ERROR VS. VOLTAGE**

| VOLTAGE (Volts) | 3MHz                  |              | LIMIT (ppm) |
|-----------------|-----------------------|--------------|-------------|
|                 | FREQUENCY ERROR (ppm) |              |             |
|                 | Low Channel           | High Channel |             |
| 3.85            | 0.0018                | 0.0017       | 2.5         |
| 3.3             | 0.0012                | 0.0013       | 2.5         |
| 4.4             | 0.0010                | 0.0010       | 2.5         |

**NOTE:** The applicant defined the normal working voltage of the battery is from 3.3Vdc to 4.4Vdc.

**FREQUENCY ERROR vs. TEMPERATURE.**

| TEMP. (°C) | 3MHz                  |              | LIMIT (ppm) |
|------------|-----------------------|--------------|-------------|
|            | FREQUENCY ERROR (ppm) |              |             |
|            | Low Channel           | High Channel |             |
| -30        | -0.0063               | -0.0062      | 2.5         |
| -20        | -0.0060               | -0.0060      | 2.5         |
| -10        | -0.0056               | -0.0055      | 2.5         |
| 0          | -0.0048               | -0.0047      | 2.5         |
| 10         | -0.0043               | -0.0042      | 2.5         |
| 20         | -0.0036               | -0.0035      | 2.5         |
| 30         | -0.0029               | -0.0028      | 2.5         |
| 40         | -0.0023               | -0.0023      | 2.5         |
| 50         | -0.0019               | -0.0018      | 2.5         |
| 60         | -0.0013               | -0.0012      | 2.5         |

#### FREQUENCY ERROR VS. VOLTAGE

| VOLTAGE (Volts) | 5MHz                  |              | LIMIT (ppm) |
|-----------------|-----------------------|--------------|-------------|
|                 | FREQUENCY ERROR (ppm) |              |             |
|                 | Low Channel           | High Channel |             |
| 3.85            | 0.0018                | 0.0018       | 2.5         |
| 3.3             | 0.0014                | 0.0015       | 2.5         |
| 4.4             | 0.0012                | 0.0012       | 2.5         |

**NOTE:** The applicant defined the normal working voltage of the battery is from 3.3Vdc to 4.4Vdc.

#### FREQUENCY ERROR vs. TEMPERATURE.

| TEMP. (°C) | 5MHz                  |              | LIMIT (ppm) |
|------------|-----------------------|--------------|-------------|
|            | FREQUENCY ERROR (ppm) |              |             |
|            | Low Channel           | High Channel |             |
| -30        | -0.0064               | -0.0061      | 2.5         |
| -20        | -0.0061               | -0.0058      | 2.5         |
| -10        | -0.0055               | -0.0053      | 2.5         |
| 0          | -0.0049               | -0.0047      | 2.5         |
| 10         | -0.0042               | -0.0040      | 2.5         |
| 20         | -0.0038               | -0.0036      | 2.5         |
| 30         | -0.0031               | -0.0029      | 2.5         |
| 40         | -0.0025               | -0.0024      | 2.5         |
| 50         | -0.0020               | -0.0019      | 2.5         |
| 60         | -0.0016               | -0.0015      | 2.5         |

#### FREQUENCY ERROR VS. VOLTAGE

| VOLTAGE (Volts) | 10MHz                 |              | LIMIT (ppm) |
|-----------------|-----------------------|--------------|-------------|
|                 | FREQUENCY ERROR (ppm) |              |             |
|                 | Low Channel           | High Channel |             |
| 3.85            | 0.0017                | 0.0018       | 2.5         |
| 3.3             | 0.0013                | 0.0015       | 2.5         |
| 4.4             | 0.0012                | 0.0013       | 2.5         |

**NOTE:** The applicant defined the normal working voltage of the battery is from 3.3Vdc to 4.4Vdc.

#### FREQUENCY ERROR vs. TEMPERATURE.

| TEMP. (°C) | 10MHz                 |              | LIMIT (ppm) |
|------------|-----------------------|--------------|-------------|
|            | FREQUENCY ERROR (ppm) |              |             |
|            | Low Channel           | High Channel |             |
| -30        | -0.0060               | -0.0061      | 2.5         |
| -20        | -0.0053               | -0.0055      | 2.5         |
| -10        | -0.0048               | -0.0049      | 2.5         |
| 0          | -0.0042               | -0.0043      | 2.5         |
| 10         | -0.0035               | -0.0036      | 2.5         |
| 20         | -0.0029               | -0.0030      | 2.5         |
| 30         | -0.0024               | -0.0025      | 2.5         |
| 40         | -0.0019               | -0.0019      | 2.5         |
| 50         | -0.0017               | -0.0018      | 2.5         |
| 60         | -0.0012               | -0.0012      | 2.5         |

## LTE BAND 17

### FREQUENCY ERROR VS. VOLTAGE

| VOLTAGE (Volts) | 5MHz                  |              | LIMIT (ppm) |
|-----------------|-----------------------|--------------|-------------|
|                 | FREQUENCY ERROR (ppm) |              |             |
|                 | Low Channel           | High Channel |             |
| 3.85            | 0.0042                | 0.0029       | 2.5         |
| 3.3             | 0.0034                | 0.0039       | 2.5         |
| 4.4             | 0.0028                | 0.0031       | 2.5         |

**NOTE:** The applicant defined the normal working voltage of the battery is from 3.3Vdc to 4.4Vdc.

### FREQUENCY ERROR vs. TEMPERATURE.

| TEMP. (°C) | 5MHz                  |              | LIMIT (ppm) |
|------------|-----------------------|--------------|-------------|
|            | FREQUENCY ERROR (ppm) |              |             |
|            | Low Channel           | High Channel |             |
| -30        | -0.0153               | -0.0139      | 2.5         |
| -20        | -0.0131               | -0.0127      | 2.5         |
| -10        | -0.0116               | -0.0117      | 2.5         |
| 0          | -0.0104               | -0.0094      | 2.5         |
| 10         | -0.0088               | -0.0090      | 2.5         |
| 20         | -0.0083               | -0.0082      | 2.5         |
| 30         | -0.0062               | -0.0073      | 2.5         |
| 40         | -0.0054               | -0.0062      | 2.5         |
| 50         | -0.0042               | -0.0052      | 2.5         |
| 60         | -0.0028               | -0.0037      | 2.5         |

#### FREQUENCY ERROR VS. VOLTAGE

| VOLTAGE (Volts) | 10MHz                 |              | LIMIT (ppm) |
|-----------------|-----------------------|--------------|-------------|
|                 | FREQUENCY ERROR (ppm) |              |             |
|                 | Low Channel           | High Channel |             |
| 3.85            | 0.0039                | 0.0041       | 2.5         |
| 3.3             | 0.0036                | 0.0036       | 2.5         |
| 4.4             | 0.0027                | 0.0031       | 2.5         |

**NOTE:** The applicant defined the normal working voltage of the battery is from 3.3Vdc to 4.4Vdc.

#### FREQUENCY ERROR vs. TEMPERATURE.


| TEMP. (°C) | 10MHz                 |              | LIMIT (ppm) |
|------------|-----------------------|--------------|-------------|
|            | FREQUENCY ERROR (ppm) |              |             |
|            | Low Channel           | High Channel |             |
| -30        | -0.0146               | -0.0143      | 2.5         |
| -20        | -0.0137               | -0.0134      | 2.5         |
| -10        | -0.0118               | -0.0115      | 2.5         |
| 0          | -0.0108               | -0.0106      | 2.5         |
| 10         | -0.0097               | -0.0095      | 2.5         |
| 20         | -0.0077               | -0.0075      | 2.5         |
| 30         | -0.0061               | -0.0060      | 2.5         |
| 40         | -0.0055               | -0.0053      | 2.5         |
| 50         | -0.0041               | -0.0041      | 2.5         |
| 60         | -0.0033               | -0.0032      | 2.5         |

### 4.3 OCCUPIED BANDWIDTH MEASUREMENT

#### 4.3.1 LIMITS OF OCCUPIED BANDWIDTH MEASUREMENT

The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 %of the total mean power of a given emission.

#### 4.3.2 TEST SETUP




#### 4.3.3 TEST PROCEDURES

- The conducted occupied bandwidth used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.
- Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth.

## 4.3.4 TEST RESULTS

### WCDMA BAND IV

| Channel | FREQ. (MHz) | 99% Occupied Bandwidth (MHz) | Channel | FREQ. (MHz) | 26dB Bandwidth (MHz) |
|---------|-------------|------------------------------|---------|-------------|----------------------|
|         |             | WCDMA                        |         |             | WCDMA                |
| 1312    | 1712.40     | 4.22                         | 1312    | 1712.40     | 4.89                 |
| 1413    | 1732.60     | 4.22                         | 1413    | 1732.60     | 4.86                 |
| 1513    | 1752.60     | 4.22                         | 1513    | 1752.60     | 4.89                 |



LTE BAND 4

| CHANNEL BANDWIDTH: 1.4MHz |                 |                              |       | CHANNEL BANDWIDTH: 3MHz |                 |                              |       |
|---------------------------|-----------------|------------------------------|-------|-------------------------|-----------------|------------------------------|-------|
| CHANNEL                   | Frequency (MHz) | 99% OCCUPIED Bandwidth (MHz) |       | CHANNEL                 | Frequency (MHz) | 99% OCCUPIED Bandwidth (MHz) |       |
|                           |                 | QPSK                         | 16QAM |                         |                 | QPSK                         | 16QAM |
| 19957                     | 1710.7          | 1.09                         | 1.09  | 19965                   | 1711.5          | 2.69                         | 2.68  |
| 20175                     | 1732.5          | 1.09                         | 1.09  | 20175                   | 1732.5          | 2.68                         | 2.68  |
| 20393                     | 1754.3          | 1.09                         | 1.09  | 20385                   | 1753.5          | 2.68                         | 2.68  |




## LTE BAND 4

| CHANNEL BANDWIDTH: 5MHz |                 |                              |       | CHANNEL BANDWIDTH: 10MHz |                 |                              |       |
|-------------------------|-----------------|------------------------------|-------|--------------------------|-----------------|------------------------------|-------|
| CHANNEL                 | Frequency (MHz) | 99% OCCUPIED Bandwidth (MHz) |       | CHANNEL                  | Frequency (MHz) | 99% OCCUPIED Bandwidth (MHz) |       |
|                         |                 | QPSK                         | 16QAM |                          |                 | QPSK                         | 16QAM |
| 19975                   | 1712.5          | 4.49                         | 4.48  | 20000                    | 1715            | 8.93                         | 8.92  |
| 20175                   | 1732.5          | 4.49                         | 4.48  | 20175                    | 1732.5          | 8.94                         | 8.94  |
| 20375                   | 1752.5          | 4.48                         | 4.48  | 20350                    | 1750            | 8.94                         | 8.94  |




## LTE BAND 4

| CHANNEL BANDWIDTH: 15MHz |                 |                              |       | CHANNEL BANDWIDTH: 20MHz |                 |                              |       |
|--------------------------|-----------------|------------------------------|-------|--------------------------|-----------------|------------------------------|-------|
| CHANNEL                  | FREQUENCY (MHz) | 99% OCCUPIED BANDWIDTH (MHz) |       | CHANNEL                  | FREQUENCY (MHz) | 99% OCCUPIED BANDWIDTH (MHz) |       |
|                          |                 | QPSK                         | 16QAM |                          |                 | QPSK                         | 16QAM |
| 20025                    | 1717.5          | 13.41                        | 13.42 | 20050                    | 1720            | 17.86                        | 17.87 |
| 20175                    | 1732.5          | 13.41                        | 13.42 | 20175                    | 1732.5          | 17.94                        | 17.90 |
| 20325                    | 1747.5          | 13.42                        | 13.40 | 20300                    | 1745            | 17.89                        | 17.86 |




## LTE BAND 12

| CHANNEL BANDWIDTH: 1.4MHz |                 |                              |       | CHANNEL BANDWIDTH: 3MHz |                 |                              |       |
|---------------------------|-----------------|------------------------------|-------|-------------------------|-----------------|------------------------------|-------|
| CHANNEL                   | FREQUENCY (MHz) | 99% OCCUPIED BANDWIDTH (MHz) |       | CHANNEL                 | FREQUENCY (MHz) | 99% OCCUPIED BANDWIDTH (MHz) |       |
|                           |                 | QPSK                         | 16QAM |                         |                 | QPSK                         | 16QAM |
| 23017                     | 699.7           | 1.09                         | 1.09  | 23025                   | 700.5           | 2.69                         | 2.69  |
| 23095                     | 707.5           | 1.09                         | 1.09  | 23095                   | 707.5           | 2.69                         | 2.68  |
| 23173                     | 715.3           | 1.09                         | 1.08  | 23165                   | 714.5           | 2.69                         | 2.68  |



## LTE BAND 12

| CHANNEL BANDWIDTH: 5MHz |                 |                              |       | CHANNEL BANDWIDTH: 10MHz |                 |                              |       |
|-------------------------|-----------------|------------------------------|-------|--------------------------|-----------------|------------------------------|-------|
| CHANNEL                 | Frequency (MHz) | 99% OCCUPIED Bandwidth (MHz) |       | CHANNEL                  | Frequency (MHz) | 99% OCCUPIED Bandwidth (MHz) |       |
|                         |                 | QPSK                         | 16QAM |                          |                 | QPSK                         | 16QAM |
| 23035                   | 701.5           | 4.49                         | 4.49  | 23060                    | 704             | 8.93                         | 8.93  |
| 23095                   | 707.5           | 4.48                         | 4.47  | 23095                    | 707.5           | 8.91                         | 8.90  |
| 23155                   | 713.5           | 4.50                         | 4.49  | 23130                    | 711             | 8.95                         | 8.97  |



## LTE BAND 17

| CHANNEL BANDWIDTH: 5MHz |                 |                              |       | CHANNEL BANDWIDTH: 10MHz |                 |                              |       |
|-------------------------|-----------------|------------------------------|-------|--------------------------|-----------------|------------------------------|-------|
| CHANNEL                 | Frequency (MHz) | 99% OCCUPIED Bandwidth (MHz) |       | CHANNEL                  | Frequency (MHz) | 99% OCCUPIED Bandwidth (MHz) |       |
|                         |                 | QPSK                         | 16QAM |                          |                 | QPSK                         | 16QAM |
| 23755                   | 706.5           | 4.49                         | 4.47  | 23780                    | 709             | 8.95                         | 8.92  |
| 23790                   | 710             | 4.49                         | 4.48  | 23790                    | 710             | 8.96                         | 8.95  |
| 23825                   | 713.5           | 4.48                         | 4.48  | 23800                    | 711             | 9.00                         | 8.98  |




## 4.4 PEAK TO AVERAGE RATIO

### 4.4.1 LIMITS OF PEAK TO AVERAGE RATIO MEASUREMENT

In measuring transmissions in this band using an average power technique, the peak to-average ratio (PAR) of the transmission may not exceed 13 dB

### 4.4.2 TEST SETUP




### 4.4.3 TEST PROCEDURES

1. Set resolution/measurement bandwidth  $\geq$  signal's occupied bandwidth;
2. Set the number of counts to a value that stabilizes the measured CCDF curve;
3. Record the maximum PAPR level associated with a probability of 0.1%.

#### 4.4.4 TEST RESULTS


##### WCDMA Band IV

| CHANNEL | FREQUENCY (MHz) | PEAK TO AVERAGE RATIO (dB) |
|---------|-----------------|----------------------------|
| 1413    | 1732.6          | 2.45                       |




LTE BAND 4


| CHANNEL BANDWIDTH: 1.4MHz |                 |                            |       | CHANNEL BANDWIDTH: 3MHz |                 |                            |       |
|---------------------------|-----------------|----------------------------|-------|-------------------------|-----------------|----------------------------|-------|
| CHANNEL                   | FREQUENCY (MHz) | PEAK TO AVERAGE RATIO (dB) |       | CHANNEL                 | FREQUENCY (MHz) | PEAK TO AVERAGE RATIO (dB) |       |
|                           |                 | QPSK                       | 16QAM |                         |                 | QPSK                       | 16QAM |
| 19957                     | 1710.7          | 4.88                       | 5.66  | 19965                   | 1711.5          | 5.02                       | 5.75  |
| 20175                     | 1732.5          | 4.74                       | 5.46  | 20175                   | 1732.5          | 4.91                       | 5.61  |
| 20393                     | 1754.3          | 4.62                       | 5.40  | 20385                   | 1753.5          | 4.79                       | 5.51  |



| CHANNEL BANDWIDTH: 5MHz |                 |                            |       | CHANNEL BANDWIDTH: 10MHz |                 |                            |       |
|-------------------------|-----------------|----------------------------|-------|--------------------------|-----------------|----------------------------|-------|
| CHANNEL                 | FREQUENCY (MHz) | PEAK TO AVERAGE RATIO (dB) |       | CHANNEL                  | FREQUENCY (MHz) | PEAK TO AVERAGE RATIO (dB) |       |
|                         |                 | QPSK                       | 16QAM |                          |                 | QPSK                       | 16QAM |
| 19975                   | 1712.5          | 5.28                       | 5.94  | 20000                    | 1715            | 4.90                       | 5.64  |
| 20175                   | 1732.5          | 5.16                       | 5.85  | 20175                    | 1732.5          | 4.83                       | 5.59  |
| 20375                   | 1752.5          | 5.13                       | 5.80  | 20350                    | 1750            | 4.94                       | 5.63  |




| CHANNEL BANDWIDTH: 15MHz |                 |                            |       | CHANNEL BANDWIDTH: 20MHz |                 |                            |       |
|--------------------------|-----------------|----------------------------|-------|--------------------------|-----------------|----------------------------|-------|
| CHANNEL                  | FREQUENCY (MHz) | PEAK TO AVERAGE RATIO (dB) |       | CHANNEL                  | FREQUENCY (MHz) | PEAK TO AVERAGE RATIO (dB) |       |
|                          |                 | QPSK                       | 16QAM |                          |                 | QPSK                       | 16QAM |
| 20025                    | 1717.5          | 5.02                       | 5.76  | 20050                    | 1720            | 5.15                       | 5.84  |
| 20175                    | 1732.5          | 5.07                       | 5.79  | 20175                    | 1732.5          | 5.21                       | 5.93  |
| 20325                    | 1747.5          | 5.10                       | 5.82  | 20300                    | 1745            | 5.23                       | 5.99  |




## LTE BAND 12

| CHANNEL BANDWIDTH: 1.4MHz |                 |                            |       | CHANNEL BANDWIDTH: 3MHz |                 |                            |       |
|---------------------------|-----------------|----------------------------|-------|-------------------------|-----------------|----------------------------|-------|
| CHANNEL                   | FREQUENCY (MHz) | PEAK TO AVERAGE RATIO (dB) |       | CHANNEL                 | FREQUENCY (MHz) | PEAK TO AVERAGE RATIO (dB) |       |
|                           |                 | QPSK                       | 16QAM |                         |                 | QPSK                       | 16QAM |
| 23017                     | 699.7           | 5.87                       | 6.65  | 23025                   | 700.5           | 6.18                       | 6.92  |
| 23095                     | 707.5           | 5.42                       | 6.26  | 23095                   | 707.5           | 5.58                       | 6.28  |
| 23173                     | 715.3           | 5.77                       | 6.42  | 23165                   | 714.5           | 6.03                       | 6.57  |




| CHANNEL BANDWIDTH: 5MHz |                 |                            |       | CHANNEL BANDWIDTH: 10MHz |                 |                            |       |
|-------------------------|-----------------|----------------------------|-------|--------------------------|-----------------|----------------------------|-------|
| CHANNEL                 | FREQUENCY (MHz) | PEAK TO AVERAGE RATIO (dB) |       | CHANNEL                  | FREQUENCY (MHz) | PEAK TO AVERAGE RATIO (dB) |       |
|                         |                 | QPSK                       | 16QAM |                          |                 | QPSK                       | 16QAM |
| 23035                   | 701.5           | 6.24                       | 6.84  | 23060                    | 704             | 5.97                       | 6.59  |
| 23095                   | 707.5           | 5.60                       | 6.31  | 23095                    | 707.5           | 5.70                       | 6.29  |
| 23155                   | 713.5           | 6.00                       | 6.62  | 23130                    | 711             | 5.95                       | 6.52  |



## LTE BAND 17

| CHANNEL BANDWIDTH: 5MHz |                 |                            |       | CHANNEL BANDWIDTH: 10MHz |                 |                            |       |
|-------------------------|-----------------|----------------------------|-------|--------------------------|-----------------|----------------------------|-------|
| CHANNEL                 | FREQUENCY (MHz) | PEAK TO AVERAGE RATIO (dB) |       | CHANNEL                  | FREQUENCY (MHz) | PEAK TO AVERAGE RATIO (dB) |       |
|                         |                 | QPSK                       | 16QAM |                          |                 | QPSK                       | 16QAM |
| 23755                   | 706.5           | 5.06                       | 5.77  | 23780                    | 709             | 5.08                       | 5.79  |
| 23790                   | 710             | 5.08                       | 5.80  | 23790                    | 710             | 5.08                       | 5.80  |
| 23825                   | 713.5           | 5.23                       | 5.96  | 23800                    | 711             | 5.11                       | 5.82  |




## 4.5 BAND EDGE MEASUREMENT

### 4.5.1 LIMITS OF BAND EDGE MEASUREMENT

The power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least  $43 + 10 \log (P)$  dB. Compliance with this provision is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kilohertz or greater.

However, in the 100 kilohertz bands immediately outside and adjacent to a licensee's frequency block, a resolution bandwidth of at least 30 kHz may be employed.

### 4.5.2 TEST SETUP



#### 4.5.3 TEST PROCEDURES


- a. The EUT was set up for the maximum peak power with LTE link data modulation. The power was measured with R&S Spectrum Analyzer. All measurements were done at 2 channels (low and high operational frequency range.).
- b. The band edge measurement used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.
- c. The center frequency of spectrum is the band edge frequency and span is 10MHz. RBW of the spectrum is 100kHz and VBW of the spectrum is 300kHz (WCDMA).
- d. The center frequency of spectrum is the band edge frequency and span is 1~5 MHz. RBW of the spectrum is 20kHz and VBW of the spectrum is 100 kHz. (LTE bandwidth 1.4MHz)
- e. The center frequency of spectrum is the band edge frequency and span is 1~5 MHz. RBW of the spectrum is 30kHz and VBW of the spectrum is 100kHz. (LTE bandwidth 3MHz)
- f. The center frequency of spectrum is the band edge frequency and span is 1~5 MHz. RBW of the spectrum is 50kHz and VBW of the spectrum is 200kHz. (LTE bandwidth 5MHz)
- g. The center frequency of spectrum is the band edge frequency and span is 1~5 MHz. RBW of the spectrum is 100kHz and VBW of the spectrum is 300kHz. (LTE bandwidth 10MHz)
- h. The center frequency of spectrum is the band edge frequency and span is 1~5 MHz. RBW of the spectrum is 200kHz and VBW of the spectrum is 1MHz. (LTE bandwidth 15MHz)
- i. The center frequency of spectrum is the band edge frequency and span is 1~5 MHz. RBW of the spectrum is 200kHz and VBW of the spectrum is 1MHz. (LTE bandwidth 20MHz)
- j. Record the max trace plot into the test report.




Test Report No.: RF170410W004-5

## 4.5.4 TEST RESULTS

### WCDMA BAND 4



**Channel Bandwidth: 1.4MHz**





Test Report No.: RF170410W004-5

## LTE BAND 4






Test Report No.: RF170410W004-5

## LTE BAND 4

### Channel Bandwidth: 5MHz





Test Report No.: RF170410W004-5

## LTE BAND 4

### Channel Bandwidth: 10MHz





Test Report No.: RF170410W004-5

## LTE BAND 4

### Channel Bandwidth: 15MHz






Test Report No.: RF170410W004-5

## LTE BAND 4

### Channel Bandwidth: 20MHz






Test Report No.: RF170410W004-5

## LTE BAND 12


### Channel Bandwidth: 1.4MHz





Test Report No.: RF170410W004-5


## LTE BAND 12





Test Report No.: RF170410W004-5

## LTE BAND 12






Test Report No.: RF170410W004-5

## LTE BAND 12

### Channel Bandwidth: 10MHz






Test Report No.: RF170410W004-5

## LTE BAND 17

### Channel Bandwidth: 5MHz





Test Report No.: RF170410W004-5

## LTE BAND 17

### Channel Bandwidth: 10MHz



## 4.6 CONDUCTED SPURIOUS EMISSIONS


### 4.6.1 LIMITS OF CONDUCTED SPURIOUS EMISSIONS MEASUREMENT

The power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least  $43 + 10 \log_{10}(P)$  dB. The limit of emission equal to  $-13\text{dBm}$

### 4.6.2 TEST PROCEDURE

- The EUT makes a phone call to the communication simulator. All measurements were done at middle operational frequency range.
- Measuring frequency range is from 30 MHz to 17.55GHz for WCDMA Band 4 & LTE Band 4, and 30 MHz to 8GHz for LTE Band 12 & LTE Band 17. 10dB attenuation pad is connected with spectrum. RBW=1MHz and VBW=3MHz are used for conducted emission measurement.


### 4.6.3 TEST SETUP





Test Report No.: RF170410W004-5


#### 4.6.4 TEST RESULTS





Test Report No.: RF170410W004-5

LTE BAND 4






Test Report No.: RF170410W004-5

### 3MHz / QPSK


#### CHANNEL 19965

FREQUENCY RANGE : 30MHz~17.55GHz



#### CHANNEL 20175

FREQUENCY RANGE : 30MHz~17.55GHz



#### CHANNEL 20385


FREQUENCY RANGE : 30MHz~17.55GHz



### 5MHz / QPSK


#### CHANNEL 19975

FREQUENCY RANGE : 30MHz~17.55GHz




#### CHANNEL 20175

FREQUENCY RANGE : 30MHz~17.55GHz



#### CHANNEL 20375

FREQUENCY RANGE : 30MHz~17.55GHz






Test Report No.: RF170410W004-5

### 10MHz / QPSK


#### CHANNEL 20000

FREQUENCY RANGE : 30MHz~17.55GHz




#### CHANNEL 20175

FREQUENCY RANGE : 30MHz~17.55GHz



#### CHANNEL 20350

FREQUENCY RANGE : 30MHz~17.55GHz






Test Report No.: RF170410W004-5

### 15MHz / QPSK


#### CHANNEL 20025

FREQUENCY RANGE : 30MHz~17.55GHz




#### CHANNEL 20175

FREQUENCY RANGE : 30MHz~17.55GHz



#### CHANNEL 20325

FREQUENCY RANGE : 30MHz~17.55GHz






Test Report No.: RF170410W004-5

## 20MHz / QPSK


### CHANNEL 20050

FREQUENCY RANGE : 30MHz~17.55GHz




### CHANNEL 20175

FREQUENCY RANGE : 30MHz~17.55GHz



### CHANNEL 20300

FREQUENCY RANGE : 30MHz~17.55GHz






Test Report No.: RF170410W004-5

## LTE BAND 12

### 1.4MHz / QPSK


#### CHANNEL 23017

FREQUENCY RANGE : 30MHz~8GHz




#### CHANNEL 23095

FREQUENCY RANGE : 30MHz~8GHz



#### CHANNEL 23173


FREQUENCY RANGE : 30MHz~8GHz



### 3MHz / QPSK


#### CHANNEL 23025

FREQUENCY RANGE : 30MHz~8GHz




#### CHANNEL 23095


FREQUENCY RANGE : 30MHz~8GHz



#### CHANNEL 23165

FREQUENCY RANGE : 30MHz~8GHz






### 10MHz / QPSK


#### CHANNEL 23060

FREQUENCY RANGE : 30MHz~8GHz




#### CHANNEL 23095

FREQUENCY RANGE : 30MHz~8GHz



#### CHANNEL 23130

FREQUENCY RANGE : 30MHz~8GHz






Test Report No.: RF170410W004-5

## LTE BAND 17

### 5MHz / QPSK

#### CHANNEL 23755

FREQUENCY RANGE : 30MHz~8GHz




#### CHANNEL 23790

FREQUENCY RANGE : 30MHz~8GHz



#### CHANNEL 23825


FREQUENCY RANGE : 30MHz~8GHz



### 10MHz / QPSK


#### CHANNEL 23780

FREQUENCY RANGE : 30MHz~8GHz




#### CHANNEL 23790

FREQUENCY RANGE : 30MHz~8GHz



#### CHANNEL 23800

FREQUENCY RANGE : 30MHz~8GHz



## 4.7 RADIATED EMISSION MEASUREMENT

### 4.7.1 LIMITS OF RADIATED EMISSION MEASUREMENT

The power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least  $43 + 10 \log_{10}(P)$  dB. The limit of emission equal to  $-13\text{dBm}$

### 4.7.2 TEST PROCEDURES

- Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value" of step a. Record the power level of S.G
- $\text{EIRP} = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn}.$
- E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole,  $\text{E.R.P power} = \text{E.I.P.R power} - 2.15\text{dBi}.$


**NOTE:** The resolution bandwidth of spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz.

### 4.7.3 DEVIATION FROM TEST STANDARD


No deviation

#### 4.7.4 TEST SETUP

##### <Below 30MHz>



##### <Above 30MHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

## 4.7.5 TEST RESULTS

### BELOW 1GHz WORST-CASE DATA


**9 KHz – 30 KHz data:** the amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required in the report.

**30 MHz – 1GHz data:**

**LTE Band 17:**

|                                                     |                  |                 |                    |
|-----------------------------------------------------|------------------|-----------------|--------------------|
| MODE                                                | TX channel 23790 | FREQUENCY RANGE | Below 1000MHz      |
| ENVIRONMENTAL CONDITIONS                            | 23deg. C, 60%RH  | INPUT POWER     | DC 5V from adapter |
| TESTED BY                                           | Tony Zou         |                 |                    |
| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                  |                 |                    |

|      | Freq    | Level  | Read Level | Limit Line | Over Limit | Factor | Remark | Pol/Phase  |
|------|---------|--------|------------|------------|------------|--------|--------|------------|
|      | MHz     | dBm/m  | dBm        | dBm/m      | dB         | dB/m   |        |            |
| 1 PP | 30.970  | -36.33 | -54.34     | -13.00     | -23.33     | 18.01  | Peak   | Horizontal |
| 2    | 76.560  | -60.18 | -50.92     | -13.00     | -47.18     | -9.26  | Peak   | Horizontal |
| 3    | 106.630 | -62.82 | -50.28     | -13.00     | -49.82     | -12.54 | Peak   | Horizontal |
| 4    | 144.460 | -68.98 | -49.80     | -13.00     | -55.98     | -19.18 | Peak   | Horizontal |
| 5    | 225.940 | -68.52 | -51.78     | -13.00     | -55.52     | -16.74 | Peak   | Horizontal |
| 6    | 339.430 | -70.08 | -57.59     | -13.00     | -57.08     | -12.49 | Peak   | Horizontal |






Test Report No.: RF170410W004-5

|                                                   |                  |                 |                    |
|---------------------------------------------------|------------------|-----------------|--------------------|
| MODE                                              | TX channel 23790 | FREQUENCY RANGE | Below 1000MHz      |
| ENVIRONMENTAL CONDITIONS                          | 23deg. C, 60%RH  | INPUT POWER     | DC 5V from adapter |
| TESTED BY                                         | Tony Zou         |                 |                    |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M |                  |                 |                    |

|      | Freq    | Level  | Read Level | Limit Line | Over Limit | Factor | Remark | Pol/Phase |
|------|---------|--------|------------|------------|------------|--------|--------|-----------|
|      | MHz     | dBm/m  | dBm        | dBm/m      | dB         | dB/m   |        |           |
| 1 PP | 47.460  | -39.79 | -35.85     | -13.00     | -26.79     | -3.94  | Peak   | Vertical  |
| 2    | 79.470  | -53.24 | -42.71     | -13.00     | -40.24     | -10.53 | Peak   | Vertical  |
| 3    | 96.930  | -55.96 | -45.33     | -13.00     | -42.96     | -10.63 | Peak   | Vertical  |
| 4    | 145.430 | -63.90 | -47.93     | -13.00     | -50.90     | -15.97 | Peak   | Vertical  |
| 5    | 229.820 | -68.52 | -57.36     | -13.00     | -55.52     | -11.16 | Peak   | Vertical  |
| 6    | 339.430 | -70.50 | -59.35     | -13.00     | -57.50     | -11.15 | Peak   | Vertical  |





Test Report No.: RF170410W004-5

## ABOVE 1GHz


**Note:** For higher frequency, the emission is too low to be detected.

## WCDMA Band IV:

## CH 1312

|                                                     |                 |                 |                    |
|-----------------------------------------------------|-----------------|-----------------|--------------------|
| MODE                                                | TX channel 1312 | FREQUENCY RANGE | Above 1000MHz      |
| ENVIRONMENTAL CONDITIONS                            | 23deg. C, 60%RH | INPUT POWER     | DC 5V from adapter |
| TESTED BY                                           | Tony Zou        |                 |                    |
| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                 |                 |                    |

|      | Freq     | Level  | Read Level | Limit Line | Over Limit | Factor | Remark | Pol/Phase  |
|------|----------|--------|------------|------------|------------|--------|--------|------------|
|      | MHz      | dBm/m  | dBm        | dBm/m      | dB         | dB/m   |        |            |
| 1    | 3425.000 | -53.25 | -55.12     | -13.00     | -40.25     | 1.87   | Peak   | Horizontal |
| 2 PP | 5137.000 | -45.68 | -54.22     | -13.00     | -32.68     | 8.54   | Peak   | Horizontal |






Test Report No.: RF170410W004-5

|                                                   |                 |                 |                    |
|---------------------------------------------------|-----------------|-----------------|--------------------|
| MODE                                              | TX channel 1312 | FREQUENCY RANGE | Above 1000MHz      |
| ENVIRONMENTAL CONDITIONS                          | 23deg. C, 60%RH | INPUT POWER     | DC 5V from adapter |
| TESTED BY                                         | Tony Zou        |                 |                    |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M |                 |                 |                    |

|      | Freq     | Level  | Read Level | Limit Line | Over Limit | Factor | Remark | Pol/Phase |
|------|----------|--------|------------|------------|------------|--------|--------|-----------|
|      | MHz      | dBm/m  | dBm        | dBm/m      | dB         | dB/m   |        |           |
| 1    | 3425.000 | -52.00 | -54.47     | -13.00     | -39.00     | 2.47   | Peak   | Vertical  |
| 2 PP | 5137.000 | -44.86 | -52.85     | -13.00     | -31.86     | 7.99   | Peak   | Vertical  |






Test Report No.: RF170410W004-5

# CH 1413

|                                                     |                 |                 |                    |
|-----------------------------------------------------|-----------------|-----------------|--------------------|
| MODE                                                | TX channel 1413 | FREQUENCY RANGE | Above 1000MHz      |
| ENVIRONMENTAL CONDITIONS                            | 23deg. C, 60%RH | INPUT POWER     | DC 5V from adapter |
| TESTED BY                                           | Tony Zou        |                 |                    |
| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                 |                 |                    |

|      | Freq     | Level  | Read Level | Limit Line | Over Limit | Factor | Remark | Pol/Phase  |
|------|----------|--------|------------|------------|------------|--------|--------|------------|
|      | MHz      | dBm/m  | dBm        | dBm/m      | dB         | dB/m   |        |            |
| 1    | 3470.000 | -53.12 | -55.17     | -13.00     | -40.12     | 2.05   | Peak   | Horizontal |
| 2 PP | 5197.800 | -44.89 | -53.50     | -13.00     | -31.89     | 8.61   | Peak   | Horizontal |






Test Report No.: RF170410W004-5

|                                                   |                 |                 |                    |
|---------------------------------------------------|-----------------|-----------------|--------------------|
| MODE                                              | TX channel 1413 | FREQUENCY RANGE | Above 1000MHz      |
| ENVIRONMENTAL CONDITIONS                          | 23deg. C, 60%RH | INPUT POWER     | DC 5V from adapter |
| TESTED BY                                         | Tony Zou        |                 |                    |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M |                 |                 |                    |

|      | Freq     | Level  | Read Level | Limit Line | Over Limit | Factor | Remark | Pol/Phase |
|------|----------|--------|------------|------------|------------|--------|--------|-----------|
|      | MHz      | dBm/m  | dBm        | dBm/m      | dB         | dB/m   |        |           |
| 1    | 3470.000 | -52.00 | -54.53     | -13.00     | -39.00     | 2.53   | Peak   | Vertical  |
| 2 PP | 5197.800 | -45.75 | -53.73     | -13.00     | -32.75     | 7.98   | Peak   | Vertical  |






Test Report No.: RF170410W004-5

# CH 1513

|                                                     |                 |                 |                    |
|-----------------------------------------------------|-----------------|-----------------|--------------------|
| MODE                                                | TX channel 1513 | FREQUENCY RANGE | Above 1000MHz      |
| ENVIRONMENTAL CONDITIONS                            | 23deg. C, 60%RH | INPUT POWER     | DC 5V from adapter |
| TESTED BY                                           | Tony Zou        |                 |                    |
| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                 |                 |                    |

|      | Freq     | Level  | Read Level | Limit Line | Over Limit | Factor | Remark | Pol/Phase  |
|------|----------|--------|------------|------------|------------|--------|--------|------------|
|      | MHz      | dBm/m  | dBm        | dBm/m      | dB         | dB/m   |        |            |
| 1    | 3508.000 | -52.40 | -54.60     | -13.00     | -39.40     | 2.20   | Peak   | Horizontal |
| 2 PP | 5258.000 | -45.49 | -54.17     | -13.00     | -32.49     | 8.68   | Peak   | Horizontal |






Test Report No.: RF170410W004-5

|                                                   |                 |                 |                    |
|---------------------------------------------------|-----------------|-----------------|--------------------|
| MODE                                              | TX channel 1513 | FREQUENCY RANGE | Above 1000MHz      |
| ENVIRONMENTAL CONDITIONS                          | 23deg. C, 60%RH | INPUT POWER     | DC 5V from adapter |
| TESTED BY                                         | Tony Zou        |                 |                    |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M |                 |                 |                    |

|      | Freq     | Level  | Read Level | Limit Line | Over Limit | Factor | Remark | Pol/Phase |
|------|----------|--------|------------|------------|------------|--------|--------|-----------|
|      | MHz      | dBm/m  | dBm        | dBm/m      | dB         | dB/m   |        |           |
| 1    | 3508.000 | -52.66 | -55.27     | -13.00     | -39.66     | 2.61   | Peak   | Vertical  |
| 2 PP | 5258.000 | -46.65 | -54.63     | -13.00     | -33.65     | 7.98   | Peak   | Vertical  |






Test Report No.: RF170410W004-5

## LTE BAND 4

CHANNEL BANDWIDTH: 1.4MHz / QPSK

|                                                     |                  |                 |                    |
|-----------------------------------------------------|------------------|-----------------|--------------------|
| MODE                                                | TX channel 20175 | FREQUENCY RANGE | Above 1000MHz      |
| ENVIRONMENTAL CONDITIONS                            | 23deg. C, 60%RH  | INPUT POWER     | DC 5V from adapter |
| TESTED BY                                           | Tony Zou         |                 |                    |
| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                  |                 |                    |

|      | Freq     | Level  | Read Level | Limit Line | Over Limit | Factor | Remark | Pol/Phase  |
|------|----------|--------|------------|------------|------------|--------|--------|------------|
|      | MHz      | dBm/m  | dBm        | dBm/m      | dB         | dB/m   |        |            |
| 1    | 3470.000 | -51.79 | -53.84     | -13.00     | -38.79     | 2.05   | Peak   | Horizontal |
| 2 PP | 5197.500 | -45.13 | -53.74     | -13.00     | -32.13     | 8.61   | Peak   | Horizontal |






Test Report No.: RF170410W004-5

|                                                   |                  |                 |                    |
|---------------------------------------------------|------------------|-----------------|--------------------|
| MODE                                              | TX channel 20175 | FREQUENCY RANGE | Above 1000MHz      |
| ENVIRONMENTAL CONDITIONS                          | 23deg. C, 60%RH  | INPUT POWER     | DC 5V from adapter |
| TESTED BY                                         | Tony Zou         |                 |                    |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M |                  |                 |                    |

|      | Freq     | Level  | Read Level | Limit Line | Over Limit | Factor | Remark | Pol/Phase |
|------|----------|--------|------------|------------|------------|--------|--------|-----------|
|      | MHz      | dBm/m  | dBm        | dBm/m      | dB         | dB/m   |        |           |
| 1    | 3470.000 | -52.38 | -54.91     | -13.00     | -39.38     | 2.53   | Peak   | Vertical  |
| 2 PP | 5197.500 | -46.16 | -54.14     | -13.00     | -33.16     | 7.98   | Peak   | Vertical  |






Test Report No.: RF170410W004-5

**CHANNEL BANDWIDTH: 3MHz / QPSK**

|                                                     |                  |                 |                    |
|-----------------------------------------------------|------------------|-----------------|--------------------|
| MODE                                                | TX channel 20175 | FREQUENCY RANGE | Above 1000MHz      |
| ENVIRONMENTAL CONDITIONS                            | 23deg. C, 60%RH  | INPUT POWER     | DC 5V from adapter |
| TESTED BY                                           | Tony Zou         |                 |                    |
| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                  |                 |                    |

|      | Freq     | Level  | Read Level | Limit Line | Over Limit | Factor | Remark | Pol/Phase  |
|------|----------|--------|------------|------------|------------|--------|--------|------------|
|      | MHz      | dBm/m  | dBm        | dBm/m      | dB         | dB/m   |        |            |
| 1    | 3470.000 | -52.84 | -54.89     | -13.00     | -39.84     | 2.05   | Peak   | Horizontal |
| 2 PP | 5197.500 | -45.23 | -53.84     | -13.00     | -32.23     | 8.61   | Peak   | Horizontal |






Test Report No.: RF170410W004-5

|                                                   |                  |                 |                    |
|---------------------------------------------------|------------------|-----------------|--------------------|
| MODE                                              | TX channel 20175 | FREQUENCY RANGE | Above 1000MHz      |
| ENVIRONMENTAL CONDITIONS                          | 23deg. C, 60%RH  | INPUT POWER     | DC 5V from adapter |
| TESTED BY                                         | Tony Zou         |                 |                    |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M |                  |                 |                    |

|      | Freq     | Level  | Read Level | Limit Line | Over Limit | Factor | Remark | Pol/Phase |
|------|----------|--------|------------|------------|------------|--------|--------|-----------|
|      | MHz      | dBm/m  | dBm        | dBm/m      | dB         | dB/m   |        |           |
| 1    | 3470.000 | -53.02 | -55.55     | -13.00     | -40.02     | 2.53   | Peak   | Vertical  |
| 2 PP | 5197.500 | -45.92 | -53.90     | -13.00     | -32.92     | 7.98   | Peak   | Vertical  |






Test Report No.: RF170410W004-5

CHANNEL BANDWIDTH: 5MHz / QPSK

|                                                     |                  |                 |                    |
|-----------------------------------------------------|------------------|-----------------|--------------------|
| MODE                                                | TX channel 20175 | FREQUENCY RANGE | Above 1000MHz      |
| ENVIRONMENTAL CONDITIONS                            | 23deg. C, 60%RH  | INPUT POWER     | DC 5V from adapter |
| TESTED BY                                           | Tony Zou         |                 |                    |
| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                  |                 |                    |

|      | Freq     | Level  | Read Level | Limit Line | Over Limit | Factor | Remark | Pol/Phase  |
|------|----------|--------|------------|------------|------------|--------|--------|------------|
|      | MHz      | dBm/m  | dBm        | dBm/m      | dB         | dB/m   |        |            |
| 1    | 3470.000 | -53.32 | -55.37     | -13.00     | -40.32     | 2.05   | Peak   | Horizontal |
| 2 PP | 5197.500 | -45.26 | -53.87     | -13.00     | -32.26     | 8.61   | Peak   | Horizontal |






Test Report No.: RF170410W004-5

|                                                   |                  |                 |                    |
|---------------------------------------------------|------------------|-----------------|--------------------|
| MODE                                              | TX channel 20175 | FREQUENCY RANGE | Above 1000MHz      |
| ENVIRONMENTAL CONDITIONS                          | 23deg. C, 60%RH  | INPUT POWER     | DC 5V from adapter |
| TESTED BY                                         | Tony Zou         |                 |                    |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M |                  |                 |                    |

|      | Freq     | Level  | Read Level | Limit Line | Over Limit | Factor | Remark | Pol/Phase |
|------|----------|--------|------------|------------|------------|--------|--------|-----------|
|      | MHz      | dBm/m  | dBm        | dBm/m      | dB         | dB/m   |        |           |
| 1    | 3470.000 | -51.86 | -54.39     | -13.00     | -38.86     | 2.53   | Peak   | Vertical  |
| 2 PP | 5197.500 | -45.58 | -53.56     | -13.00     | -32.58     | 7.98   | Peak   | Vertical  |






Test Report No.: RF170410W004-5

CHANNEL BANDWIDTH: 10MHz / QPSK

CH 20000

|                                                     |                  |                 |                    |
|-----------------------------------------------------|------------------|-----------------|--------------------|
| MODE                                                | TX channel 20000 | FREQUENCY RANGE | Above 1000MHz      |
| ENVIRONMENTAL CONDITIONS                            | 23deg. C, 60%RH  | INPUT POWER     | DC 5V from adapter |
| TESTED BY                                           | Tony Zou         |                 |                    |
| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                  |                 |                    |

|      | Freq     | Level  | Read Level | Limit Line | Over Limit | Factor | Remark | Pol/Phase  |
|------|----------|--------|------------|------------|------------|--------|--------|------------|
|      | MHz      | dBm/m  | dBm        | dBm/m      | dB         | dB/m   |        |            |
| 1    | 3418.000 | -54.04 | -55.89     | -13.00     | -41.04     | 1.85   | Peak   | Horizontal |
| 2 PP | 5130.000 | -44.47 | -53.00     | -13.00     | -31.47     | 8.53   | Peak   | Horizontal |






Test Report No.: RF170410W004-5

|                                                   |                  |                 |                    |
|---------------------------------------------------|------------------|-----------------|--------------------|
| MODE                                              | TX channel 20000 | FREQUENCY RANGE | Above 1000MHz      |
| ENVIRONMENTAL CONDITIONS                          | 23deg. C, 60%RH  | INPUT POWER     | DC 5V from adapter |
| TESTED BY                                         | Tony Zou         |                 |                    |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M |                  |                 |                    |

|      | Freq     | Level  | Read Level | Limit Line | Over Limit | Factor | Remark | Pol/Phase |
|------|----------|--------|------------|------------|------------|--------|--------|-----------|
|      | MHz      | dBm/m  | dBm        | dBm/m      | dB         | dB/m   |        |           |
| 1    | 3418.000 | -51.88 | -54.35     | -13.00     | -38.88     | 2.47   | Peak   | Vertical  |
| 2 PP | 5130.000 | -46.07 | -54.06     | -13.00     | -33.07     | 7.99   | Peak   | Vertical  |






Test Report No.: RF170410W004-5

# CH 20175

|                                                     |                  |                 |                    |
|-----------------------------------------------------|------------------|-----------------|--------------------|
| MODE                                                | TX channel 20175 | FREQUENCY RANGE | Above 1000MHz      |
| ENVIRONMENTAL CONDITIONS                            | 23deg. C, 60%RH  | INPUT POWER     | DC 5V from adapter |
| TESTED BY                                           | Tony Zou         |                 |                    |
| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                  |                 |                    |

|   | Freq        | Level  | Read Level | Limit Line | Over Limit | Factor | Remark | Pol/Phase  |
|---|-------------|--------|------------|------------|------------|--------|--------|------------|
|   | MHz         | dBm/m  | dBm        | dBm/m      | dB         | dB/m   |        |            |
| 1 | 3470.000    | -53.23 | -55.28     | -13.00     | -40.23     | 2.05   | Peak   | Horizontal |
| 2 | PP 5197.500 | -45.61 | -54.22     | -13.00     | -32.61     | 8.61   | Peak   | Horizontal |






Test Report No.: RF170410W004-5

|                                                   |                  |                 |                    |
|---------------------------------------------------|------------------|-----------------|--------------------|
| MODE                                              | TX channel 20175 | FREQUENCY RANGE | Above 1000MHz      |
| ENVIRONMENTAL CONDITIONS                          | 23deg. C, 60%RH  | INPUT POWER     | DC 5V from adapter |
| TESTED BY                                         | Tony Zou         |                 |                    |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M |                  |                 |                    |

|      | Freq     | Level  | Read Level | Limit Line | Over Limit | Factor | Remark | Pol/Phase |
|------|----------|--------|------------|------------|------------|--------|--------|-----------|
|      | MHz      | dBm/m  | dBm        | dBm/m      | dB         | dB/m   |        |           |
| 1    | 3470.000 | -53.45 | -55.98     | -13.00     | -40.45     | 2.53   | Peak   | Vertical  |
| 2 PP | 5197.500 | -45.23 | -53.21     | -13.00     | -32.23     | 7.98   | Peak   | Vertical  |






Test Report No.: RF170410W004-5

CH 20350

|                                                     |                  |                 |                    |
|-----------------------------------------------------|------------------|-----------------|--------------------|
| MODE                                                | TX channel 20350 | FREQUENCY RANGE | Above 1000MHz      |
| ENVIRONMENTAL CONDITIONS                            | 23deg. C, 60%RH  | INPUT POWER     | DC 5V from adapter |
| TESTED BY                                           | Tony Zou         |                 |                    |
| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                  |                 |                    |

|      | Freq     | Level  | Read Level | Limit Line | Over Limit | Factor | Remark | Pol/Phase  |
|------|----------|--------|------------|------------|------------|--------|--------|------------|
|      | MHz      | dBm/m  | dBm        | dBm/m      | dB         | dB/m   |        |            |
| 1    | 3496.000 | -53.33 | -55.48     | -13.00     | -40.33     | 2.15   | Peak   | Horizontal |
| 2 PP | 5250.000 | -45.56 | -54.23     | -13.00     | -32.56     | 8.67   | Peak   | Horizontal |






Test Report No.: RF170410W004-5

|                                                   |                  |                 |                    |
|---------------------------------------------------|------------------|-----------------|--------------------|
| MODE                                              | TX channel 20350 | FREQUENCY RANGE | Above 1000MHz      |
| ENVIRONMENTAL CONDITIONS                          | 23deg. C, 60%RH  | INPUT POWER     | DC 5V from adapter |
| TESTED BY                                         | Tony Zou         |                 |                    |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M |                  |                 |                    |

|      | Freq     | Level  | Read Level | Limit Line | Over Limit | Factor | Remark | Pol/Phase |
|------|----------|--------|------------|------------|------------|--------|--------|-----------|
|      | MHz      | dBm/m  | dBm        | dBm/m      | dB         | dB/m   |        |           |
| 1    | 3496.000 | -52.76 | -55.32     | -13.00     | -39.76     | 2.56   | Peak   | Vertical  |
| 2 PP | 5250.000 | -45.97 | -53.95     | -13.00     | -32.97     | 7.98   | Peak   | Vertical  |






Test Report No.: RF170410W004-5

CHANNEL BANDWIDTH: 15MHz / QPSK

|                                                     |                  |                 |                    |
|-----------------------------------------------------|------------------|-----------------|--------------------|
| MODE                                                | TX channel 20175 | FREQUENCY RANGE | Above 1000MHz      |
| ENVIRONMENTAL CONDITIONS                            | 23deg. C, 60%RH  | INPUT POWER     | DC 5V from adapter |
| TESTED BY                                           | Tony Zou         |                 |                    |
| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                  |                 |                    |

|      | Freq     | Level  | Read Level | Limit Line | Over Limit | Factor | Remark | Pol/Phase  |
|------|----------|--------|------------|------------|------------|--------|--------|------------|
|      | MHz      | dBm/m  | dBm        | dBm/m      | dB         | dB/m   |        |            |
| 1    | 3470.000 | -52.89 | -54.94     | -13.00     | -39.89     | 2.05   | Peak   | Horizontal |
| 2 PP | 5197.500 | -45.35 | -53.96     | -13.00     | -32.35     | 8.61   | Peak   | Horizontal |






Test Report No.: RF170410W004-5

|                                                   |                  |                 |                    |
|---------------------------------------------------|------------------|-----------------|--------------------|
| MODE                                              | TX channel 20175 | FREQUENCY RANGE | Above 1000MHz      |
| ENVIRONMENTAL CONDITIONS                          | 23deg. C, 60%RH  | INPUT POWER     | DC 5V from adapter |
| TESTED BY                                         | Tony Zou         |                 |                    |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M |                  |                 |                    |

|      | Freq     | Level  | Read Level | Limit Line | Over Limit | Factor | Remark | Pol/Phase |
|------|----------|--------|------------|------------|------------|--------|--------|-----------|
|      | MHz      | dBm/m  | dBm        | dBm/m      | dB         | dB/m   |        |           |
| 1    | 3470.000 | -52.42 | -54.95     | -13.00     | -39.42     | 2.53   | Peak   | Vertical  |
| 2 PP | 5197.500 | -45.62 | -53.60     | -13.00     | -32.62     | 7.98   | Peak   | Vertical  |






Test Report No.: RF170410W004-5

CHANNEL BANDWIDTH: 20MHz / QPSK

|                                                     |                  |                 |                    |
|-----------------------------------------------------|------------------|-----------------|--------------------|
| MODE                                                | TX channel 20175 | FREQUENCY RANGE | Above 1000MHz      |
| ENVIRONMENTAL CONDITIONS                            | 23deg. C, 60%RH  | INPUT POWER     | DC 5V from adapter |
| TESTED BY                                           | Tony Zou         |                 |                    |
| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                  |                 |                    |

|      | Freq     | Level  | Read Level | Limit Line | Over Limit | Factor | Remark | Pol/Phase  |
|------|----------|--------|------------|------------|------------|--------|--------|------------|
|      | MHz      | dBm/m  | dBm        | dBm/m      | dB         | dB/m   |        |            |
| 1    | 3470.000 | -53.65 | -55.70     | -13.00     | -40.65     | 2.05   | Peak   | Horizontal |
| 2 PP | 5197.500 | -45.84 | -54.45     | -13.00     | -32.84     | 8.61   | Peak   | Horizontal |






Test Report No.: RF170410W004-5

|                                                   |                  |                 |                    |
|---------------------------------------------------|------------------|-----------------|--------------------|
| MODE                                              | TX channel 20175 | FREQUENCY RANGE | Above 1000MHz      |
| ENVIRONMENTAL CONDITIONS                          | 23deg. C, 60%RH  | INPUT POWER     | DC 5V from adapter |
| TESTED BY                                         | Tony Zou         |                 |                    |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M |                  |                 |                    |

|      | Freq     | Level  | Read Level | Limit Line | Over Limit | Factor | Remark | Pol/Phase |
|------|----------|--------|------------|------------|------------|--------|--------|-----------|
|      | MHz      | dBm/m  | dBm        | dBm/m      | dB         | dB/m   |        |           |
| 1    | 3470.000 | -52.39 | -54.92     | -13.00     | -39.39     | 2.53   | Peak   | Vertical  |
| 2 PP | 5197.500 | -45.41 | -53.39     | -13.00     | -32.41     | 7.98   | Peak   | Vertical  |






Test Report No.: RF170410W004-5

## LTE BAND 12

CHANNEL BANDWIDTH: 1.4MHz / QPSK

|                                                     |                  |                 |                    |
|-----------------------------------------------------|------------------|-----------------|--------------------|
| MODE                                                | TX channel 23095 | FREQUENCY RANGE | Above 1000MHz      |
| ENVIRONMENTAL CONDITIONS                            | 23deg. C, 60%RH  | INPUT POWER     | DC 5V from adapter |
| TESTED BY                                           | Tony Zou         |                 |                    |
| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                  |                 |                    |

|   | Freq        | Level  | Read Level | Limit Line | Over Limit | Factor | Remark | Pol/Phase  |
|---|-------------|--------|------------|------------|------------|--------|--------|------------|
|   | MHz         | dBm/m  | dBm        | dBm/m      | dB         | dB/m   |        |            |
| 1 | 1416.000    | -55.13 | -48.41     | -13.00     | -42.13     | -6.72  | Peak   | Horizontal |
| 2 | PP 2122.500 | -37.95 | -36.02     | -13.00     | -24.95     | -1.93  | Peak   | Horizontal |






Test Report No.: RF170410W004-5

|                                                   |                  |                 |                    |
|---------------------------------------------------|------------------|-----------------|--------------------|
| MODE                                              | TX channel 23095 | FREQUENCY RANGE | Above 1000MHz      |
| ENVIRONMENTAL CONDITIONS                          | 23deg. C, 60%RH  | INPUT POWER     | DC 5V from adapter |
| TESTED BY                                         | Tony Zou         |                 |                    |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M |                  |                 |                    |

|      | Freq     | Level  | Read Level | Limit Line | Over Limit | Factor | Remark | Pol/Phase |
|------|----------|--------|------------|------------|------------|--------|--------|-----------|
|      | MHz      | dBm/m  | dBm        | dBm/m      | dB         | dB/m   |        |           |
| 1    | 1416.000 | -56.19 | -50.75     | -13.00     | -43.19     | -5.44  | Peak   | Vertical  |
| 2 PP | 2122.500 | -40.08 | -39.84     | -13.00     | -27.08     | -0.24  | Peak   | Vertical  |






Test Report No.: RF170410W004-5

CHANNEL BANDWIDTH: 3MHz / QPSK

|                                                     |                  |                 |                    |
|-----------------------------------------------------|------------------|-----------------|--------------------|
| MODE                                                | TX channel 23095 | FREQUENCY RANGE | Above 1000MHz      |
| ENVIRONMENTAL CONDITIONS                            | 23deg. C, 60%RH  | INPUT POWER     | DC 5V from adapter |
| TESTED BY                                           | Tony Zou         |                 |                    |
| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                  |                 |                    |

|      | Freq     | Level  | Read Level | Limit Line | Over Limit | Factor | Remark | Pol/Phase  |
|------|----------|--------|------------|------------|------------|--------|--------|------------|
|      | MHz      | dBm/m  | dBm        | dBm/m      | dB         | dB/m   |        |            |
| 1    | 1416.000 | -54.48 | -47.76     | -13.00     | -41.48     | -6.72  | Peak   | Horizontal |
| 2 PP | 2122.500 | -35.91 | -33.98     | -13.00     | -22.91     | -1.93  | Peak   | Horizontal |






Test Report No.: RF170410W004-5

|                                                   |                  |                 |                    |
|---------------------------------------------------|------------------|-----------------|--------------------|
| MODE                                              | TX channel 23095 | FREQUENCY RANGE | Above 1000MHz      |
| ENVIRONMENTAL CONDITIONS                          | 23deg. C, 60%RH  | INPUT POWER     | DC 5V from adapter |
| TESTED BY                                         | Tony Zou         |                 |                    |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M |                  |                 |                    |

|      | Freq     | Level  | Read Level | Limit Line | Over Limit | Factor | Remark | Pol/Phase |
|------|----------|--------|------------|------------|------------|--------|--------|-----------|
|      | MHz      | dBm/m  | dBm        | dBm/m      | dB         | dB/m   |        |           |
| 1    | 1416.000 | -58.67 | -53.23     | -13.00     | -45.67     | -5.44  | Peak   | Vertical  |
| 2 PP | 2122.500 | -41.13 | -40.89     | -13.00     | -28.13     | -0.24  | Peak   | Vertical  |






Test Report No.: RF170410W004-5

CHANNEL BANDWIDTH: 5MHz / QPSK

|                                                     |                  |                 |                    |
|-----------------------------------------------------|------------------|-----------------|--------------------|
| MODE                                                | TX channel 23095 | FREQUENCY RANGE | Above 1000MHz      |
| ENVIRONMENTAL CONDITIONS                            | 23deg. C, 60%RH  | INPUT POWER     | DC 5V from adapter |
| TESTED BY                                           | Tony Zou         |                 |                    |
| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                  |                 |                    |

|      | Freq     | Level  | Read Level | Limit Line | Over Limit | Factor | Remark | Pol/Phase  |
|------|----------|--------|------------|------------|------------|--------|--------|------------|
|      | MHz      | dBm/m  | dBm        | dBm/m      | dB         | dB/m   |        |            |
| 1    | 1416.000 | -57.85 | -51.13     | -13.00     | -44.85     | -6.72  | Peak   | Horizontal |
| 2 PP | 2122.500 | -37.39 | -35.46     | -13.00     | -24.39     | -1.93  | Peak   | Horizontal |






Test Report No.: RF170410W004-5

|                                                   |                  |                 |                    |
|---------------------------------------------------|------------------|-----------------|--------------------|
| MODE                                              | TX channel 23095 | FREQUENCY RANGE | Above 1000MHz      |
| ENVIRONMENTAL CONDITIONS                          | 23deg. C, 60%RH  | INPUT POWER     | DC 5V from adapter |
| TESTED BY                                         | Tony Zou         |                 |                    |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M |                  |                 |                    |

|      | Freq     | Level  | Read Level | Limit Line | Over Limit | Factor | Remark | Pol/Phase |
|------|----------|--------|------------|------------|------------|--------|--------|-----------|
|      | MHz      | dBm/m  | dBm        | dBm/m      | dB         | dB/m   |        |           |
| 1    | 1416.000 | -58.91 | -53.47     | -13.00     | -45.91     | -5.44  | Peak   | Vertical  |
| 2 PP | 2122.500 | -40.80 | -40.56     | -13.00     | -27.80     | -0.24  | Peak   | Vertical  |






Test Report No.: RF170410W004-5

CHANNEL BANDWIDTH: 10MHz / QPSK

CH 23060

|                                                     |                  |                 |                    |
|-----------------------------------------------------|------------------|-----------------|--------------------|
| MODE                                                | TX channel 23060 | FREQUENCY RANGE | Above 1000MHz      |
| ENVIRONMENTAL CONDITIONS                            | 23deg. C, 60%RH  | INPUT POWER     | DC 5V from adapter |
| TESTED BY                                           | Tony Zou         |                 |                    |
| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                  |                 |                    |

|      | Freq     | Level  | Read Level | Limit Line | Over Limit | Factor | Remark | Pol/Phase  |
|------|----------|--------|------------|------------|------------|--------|--------|------------|
|      | MHz      | dBm/m  | dBm        | dBm/m      | dB         | dB/m   |        |            |
| 1    | 1416.000 | -59.33 | -52.61     | -13.00     | -46.33     | -6.72  | Peak   | Horizontal |
| 2 PP | 2118.000 | -46.88 | -44.94     | -13.00     | -33.88     | -1.94  | Peak   | Horizontal |






Test Report No.: RF170410W004-5

|                                                   |                  |                 |                    |
|---------------------------------------------------|------------------|-----------------|--------------------|
| MODE                                              | TX channel 23060 | FREQUENCY RANGE | Above 1000MHz      |
| ENVIRONMENTAL CONDITIONS                          | 23deg. C, 60%RH  | INPUT POWER     | DC 5V from adapter |
| TESTED BY                                         | Tony Zou         |                 |                    |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M |                  |                 |                    |

|   | Freq        | Level  | Read Level | Limit Line | Over Limit | Factor | Remark | Pol/Phase |
|---|-------------|--------|------------|------------|------------|--------|--------|-----------|
|   | MHz         | dBm/m  | dBm        | dBm/m      | dB         | dB/m   |        |           |
| 1 | 1416.000    | -58.45 | -53.01     | -13.00     | -45.45     | -5.44  | Peak   | Vertical  |
| 2 | PP 2118.000 | -51.78 | -51.54     | -13.00     | -38.78     | -0.24  | Peak   | Vertical  |






Test Report No.: RF170410W004-5

# CH 23095

|                                                     |                  |                 |                    |
|-----------------------------------------------------|------------------|-----------------|--------------------|
| MODE                                                | TX channel 23095 | FREQUENCY RANGE | Above 1000MHz      |
| ENVIRONMENTAL CONDITIONS                            | 23deg. C, 60%RH  | INPUT POWER     | DC 5V from adapter |
| TESTED BY                                           | Tony Zou         |                 |                    |
| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                  |                 |                    |

|      | Freq     | Level  | Read Level | Limit Line | Over Limit | Factor | Remark | Pol/Phase  |
|------|----------|--------|------------|------------|------------|--------|--------|------------|
|      | MHz      | dBm/m  | dBm        | dBm/m      | dB         | dB/m   |        |            |
| 1    | 1416.000 | -58.88 | -52.16     | -13.00     | -45.88     | -6.72  | Peak   | Horizontal |
| 2 PP | 2122.500 | -41.84 | -39.91     | -13.00     | -28.84     | -1.93  | Peak   | Horizontal |






Test Report No.: RF170410W004-5

|                                                   |                  |                 |                    |
|---------------------------------------------------|------------------|-----------------|--------------------|
| MODE                                              | TX channel 23095 | FREQUENCY RANGE | Above 1000MHz      |
| ENVIRONMENTAL CONDITIONS                          | 23deg. C, 60%RH  | INPUT POWER     | DC 5V from adapter |
| TESTED BY                                         | Tony Zou         |                 |                    |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M |                  |                 |                    |

|   | Freq        | Level  | Read Level | Limit Line | Over Limit | Factor | Remark | Pol/Phase |
|---|-------------|--------|------------|------------|------------|--------|--------|-----------|
|   | MHz         | dBm/m  | dBm        | dBm/m      | dB         | dB/m   |        |           |
| 1 | 1416.000    | -56.66 | -51.22     | -13.00     | -43.66     | -5.44  | Peak   | Vertical  |
| 2 | PP 2122.500 | -38.62 | -38.38     | -13.00     | -25.62     | -0.24  | Peak   | Vertical  |






Test Report No.: RF170410W004-5

# CH 23130

|                                                     |                  |                 |                    |
|-----------------------------------------------------|------------------|-----------------|--------------------|
| MODE                                                | TX channel 23130 | FREQUENCY RANGE | Above 1000MHz      |
| ENVIRONMENTAL CONDITIONS                            | 23deg. C, 60%RH  | INPUT POWER     | DC 5V from adapter |
| TESTED BY                                           | Tony Zou         |                 |                    |
| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                  |                 |                    |

|      | Freq     | Level  | Read Level | Limit Line | Over Limit | Factor | Remark | Pol/Phase  |
|------|----------|--------|------------|------------|------------|--------|--------|------------|
|      | MHz      | dBm/m  | dBm        | dBm/m      | dB         | dB/m   |        |            |
| 1    | 1416.000 | -56.42 | -49.70     | -13.00     | -43.42     | -6.72  | Peak   | Horizontal |
| 2 PP | 2130.000 | -46.17 | -44.24     | -13.00     | -33.17     | -1.93  | Peak   | Horizontal |






Test Report No.: RF170410W004-5

|                                                   |                  |                 |                    |
|---------------------------------------------------|------------------|-----------------|--------------------|
| MODE                                              | TX channel 23130 | FREQUENCY RANGE | Above 1000MHz      |
| ENVIRONMENTAL CONDITIONS                          | 23deg. C, 60%RH  | INPUT POWER     | DC 5V from adapter |
| TESTED BY                                         | Tony Zou         |                 |                    |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M |                  |                 |                    |

|      | Freq     | Level  | Read Level | Limit Line | Over Limit | Factor | Remark | Pol/Phase |
|------|----------|--------|------------|------------|------------|--------|--------|-----------|
|      | MHz      | dBm/m  | dBm        | dBm/m      | dB         | dB/m   |        |           |
| 1    | 1416.000 | -58.06 | -52.62     | -13.00     | -45.06     | -5.44  | Peak   | Vertical  |
| 2 PP | 2130.000 | -52.22 | -51.98     | -13.00     | -39.22     | -0.24  | Peak   | Vertical  |






Test Report No.: RF170410W004-5

# LTE Band 17

## CHANNEL BANDWIDTH: 5MHz / QPSK

|                                                     |                  |                 |                    |
|-----------------------------------------------------|------------------|-----------------|--------------------|
| MODE                                                | TX channel 23790 | FREQUENCY RANGE | Above 1000MHz      |
| ENVIRONMENTAL CONDITIONS                            | 23deg. C, 60%RH  | INPUT POWER     | DC 5V from adapter |
| TESTED BY                                           | Tony Zou         |                 |                    |
| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                  |                 |                    |

|      | Freq     | Level  | Read Level | Limit Line | Over Limit | Factor | Remark | Pol/Phase  |
|------|----------|--------|------------|------------|------------|--------|--------|------------|
|      | MHz      | dBm/m  | dBm        | dBm/m      | dB         | dB/m   |        |            |
| 1    | 1416.000 | -54.91 | -48.19     | -13.00     | -41.91     | -6.72  | Peak   | Horizontal |
| 2 PP | 2130.000 | -43.64 | -41.71     | -13.00     | -30.64     | -1.93  | Peak   | Horizontal |






Test Report No.: RF170410W004-5

|                                                   |                  |                 |                    |
|---------------------------------------------------|------------------|-----------------|--------------------|
| MODE                                              | TX channel 23790 | FREQUENCY RANGE | Above 1000MHz      |
| ENVIRONMENTAL CONDITIONS                          | 23deg. C, 60%RH  | INPUT POWER     | DC 5V from adapter |
| TESTED BY                                         | Tony Zou         |                 |                    |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M |                  |                 |                    |

|      | Freq     | Level  | Read Level | Limit Line | Over Limit | Factor | Remark | Pol/Phase |
|------|----------|--------|------------|------------|------------|--------|--------|-----------|
|      | MHz      | dBm/m  | dBm        | dBm/m      | dB         | dB/m   |        |           |
| 1    | 1416.000 | -57.50 | -52.06     | -13.00     | -44.50     | -5.44  | Peak   | Vertical  |
| 2 PP | 2130.000 | -37.58 | -37.34     | -13.00     | -24.58     | -0.24  | Peak   | Vertical  |






Test Report No.: RF170410W004-5

CHANNEL BANDWIDTH: 10MHz / QPSK

CH 23780

|                                                     |                  |                 |                    |
|-----------------------------------------------------|------------------|-----------------|--------------------|
| MODE                                                | TX channel 23780 | FREQUENCY RANGE | Above 1000MHz      |
| ENVIRONMENTAL CONDITIONS                            | 23deg. C, 60%RH  | INPUT POWER     | DC 5V from adapter |
| TESTED BY                                           | Tony Zou         |                 |                    |
| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                  |                 |                    |

|      | Freq     | Level  | Read Level | Limit Line | Over Limit | Factor | Remark | Pol/Phase  |
|------|----------|--------|------------|------------|------------|--------|--------|------------|
|      | MHz      | dBm/m  | dBm        | dBm/m      | dB         | dB/m   |        |            |
| 1    | 1416.000 | -59.84 | -53.12     | -13.00     | -46.84     | -6.72  | Peak   | Horizontal |
| 2 PP | 2120.000 | -37.30 | -35.36     | -13.00     | -24.30     | -1.94  | Peak   | Horizontal |






Test Report No.: RF170410W004-5

|                                                   |                  |                 |                    |
|---------------------------------------------------|------------------|-----------------|--------------------|
| MODE                                              | TX channel 23780 | FREQUENCY RANGE | Above 1000MHz      |
| ENVIRONMENTAL CONDITIONS                          | 23deg. C, 60%RH  | INPUT POWER     | DC 5V from adapter |
| TESTED BY                                         | Tony Zou         |                 |                    |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M |                  |                 |                    |

|      | Freq     | Level  | Read Level | Limit Line | Over Limit | Factor | Remark | Pol/Phase |
|------|----------|--------|------------|------------|------------|--------|--------|-----------|
|      | MHz      | dBm/m  | dBm        | dBm/m      | dB         | dB/m   |        |           |
| 1    | 1416.000 | -59.36 | -53.92     | -13.00     | -46.36     | -5.44  | Peak   | Vertical  |
| 2 PP | 2120.000 | -36.40 | -36.16     | -13.00     | -23.40     | -0.24  | Peak   | Vertical  |






Test Report No.: RF170410W004-5

CH 23790

|                                                     |                  |                 |                    |
|-----------------------------------------------------|------------------|-----------------|--------------------|
| MODE                                                | TX channel 23790 | FREQUENCY RANGE | Above 1000MHz      |
| ENVIRONMENTAL CONDITIONS                            | 23deg. C, 60%RH  | INPUT POWER     | DC 5V from adapter |
| TESTED BY                                           | Tony Zou         |                 |                    |
| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                  |                 |                    |

|      | Freq     | Level  | Read Level | Limit Line | Over Limit | Factor | Remark | Pol/Phase  |
|------|----------|--------|------------|------------|------------|--------|--------|------------|
|      | MHz      | dBm/m  | dBm        | dBm/m      | dB         | dB/m   |        |            |
| 1    | 1416.000 | -59.24 | -52.52     | -13.00     | -46.24     | -6.72  | Peak   | Horizontal |
| 2 PP | 2130.000 | -40.27 | -38.34     | -13.00     | -27.27     | -1.93  | Peak   | Horizontal |






Test Report No.: RF170410W004-5

|                                                   |                  |                 |                    |
|---------------------------------------------------|------------------|-----------------|--------------------|
| MODE                                              | TX channel 23790 | FREQUENCY RANGE | Above 1000MHz      |
| ENVIRONMENTAL CONDITIONS                          | 23deg. C, 60%RH  | INPUT POWER     | DC 5V from adapter |
| TESTED BY                                         | Tony Zou         |                 |                    |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M |                  |                 |                    |

|      | Freq     | Level  | Read Level | Limit Line | Over Limit | Factor | Remark | Pol/Phase |
|------|----------|--------|------------|------------|------------|--------|--------|-----------|
|      | MHz      | dBm/m  | dBm        | dBm/m      | dB         | dB/m   |        |           |
| 1    | 1416.000 | -57.85 | -52.41     | -13.00     | -44.85     | -5.44  | Peak   | Vertical  |
| 2 PP | 2130.000 | -41.32 | -41.08     | -13.00     | -28.32     | -0.24  | Peak   | Vertical  |






Test Report No.: RF170410W004-5

# CH 23800

|                                                     |                  |                 |                    |
|-----------------------------------------------------|------------------|-----------------|--------------------|
| MODE                                                | TX channel 23800 | FREQUENCY RANGE | Above 1000MHz      |
| ENVIRONMENTAL CONDITIONS                            | 23deg. C, 60%RH  | INPUT POWER     | DC 5V from adapter |
| TESTED BY                                           | Tony Zou         |                 |                    |
| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                  |                 |                    |

|      | Freq     | Level  | Read Level | Limit Line | Over Limit | Factor | Remark | Pol/Phase  |
|------|----------|--------|------------|------------|------------|--------|--------|------------|
|      | MHz      | dBm/m  | dBm        | dBm/m      | dB         | dB/m   |        |            |
| 1    | 1416.000 | -56.04 | -49.32     | -13.00     | -43.04     | -6.72  | Peak   | Horizontal |
| 2 PP | 2130.000 | -43.73 | -41.80     | -13.00     | -30.73     | -1.93  | Peak   | Horizontal |






Test Report No.: RF170410W004-5

|                                                   |                  |                 |                    |
|---------------------------------------------------|------------------|-----------------|--------------------|
| MODE                                              | TX channel 23800 | FREQUENCY RANGE | Above 1000MHz      |
| ENVIRONMENTAL CONDITIONS                          | 23deg. C, 60%RH  | INPUT POWER     | DC 5V from adapter |
| TESTED BY                                         | Tony Zou         |                 |                    |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M |                  |                 |                    |

|      | Freq     | Level  | Read Level | Limit Line | Over Limit | Factor | Remark | Pol/Phase |
|------|----------|--------|------------|------------|------------|--------|--------|-----------|
|      | MHz      | dBm/m  | dBm        | dBm/m      | dB         | dB/m   |        |           |
| 1    | 1416.000 | -57.39 | -51.95     | -13.00     | -44.39     | -5.44  | Peak   | Vertical  |
| 2 PP | 2130.000 | -39.43 | -39.19     | -13.00     | -26.43     | -0.24  | Peak   | Vertical  |





Test Report No.: RF170410W004-5

## 5 INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Shenzhen Co., Ltd. Dongguan Branch, were founded in 2002 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

**Dongguan EMC/RF Lab:**

Tel: +86-769-85935656

Fax: +86-769-85931080

**Email:** [customerservice.dg@cn.bureauveritas.com](mailto:customerservice.dg@cn.bureauveritas.com)

**Web Site:** [www.adt.com.tw](http://www.adt.com.tw)

The address and road map of all our labs can be found in our web site also.



Test Report No.: RF170410W004-5

## 6 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No modifications were made to the EUT by the lab during the test.

---END---