

FCC REPORT

Applicant: APRIX LATINOAMERICA S.A.
Address of Applicant: ADVANCED 099 BLDG SUITE 4 C CALLE BEATRIZ M DE CABAL PANAMA

Equipment Under Test (EUT)

Product Name: Tablet PC
Model No.: Aprix Tab8ii
Trade mark: APRIX

FCC ID: 2AHJQ-APT8II

Applicable standards: FCC CFR Title 47 Part 15 Subpart B

Date of sample receipt: 01 Jun., 2017

Date of Test: 01 Jun., to 11Jul., 2017

Date of report issued: 11 Jul., 2017

Test Result: Pass *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Bruce Zhang
Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the CCIS product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

2 Version

Version No.	Date	Description
00	11 Jul., 2017	<p><i>This report was amended on FCC ID: 2AHJQ-APT8II follow FCC Class II Permissive Change which were tested and issued by Shenzhen Zhongjian Nanfang Testing Co., Ltd.</i></p> <p><i>The differences between them as below: Added HDMI mode, Base on the differences description, the FCC Part 15 Subpart B were re-tested.</i></p>

Tested by:

Carrey Chen

Date:

11 Jul., 2017

Test Engineer

Reviewed by:

Wimer Zhang

Date:

11 Jul., 2017

Project Engineer

3 Contents

	Page
1 COVER PAGE.....	1
2 VERSION	2
3 CONTENTS	3
4 TEST SUMMARY.....	4
5 GENERAL INFORMATION.....	5
5.1 CLIENT INFORMATION	5
5.2 GENERAL DESCRIPTION OF E.U.T.	5
5.3 TEST MODE.....	5
5.4 MEASUREMENT UNCERTAINTY.....	5
5.5 DESCRIPTION OF SUPPORT UNITS	6
5.6 LABORATORY FACILITY	6
5.7 LABORATORY LOCATION	6
5.8 TEST INSTRUMENTS LIST.....	7
6 TEST RESULTS AND MEASUREMENT DATA.....	8
6.1 CONDUCTED EMISSION.....	8
6.2 RADIATED EMISSION	13
7 TEST SETUP PHOTO	23
8 EUT CONSTRUCTIONAL DETAILS	27

4 Test Summary

Test Item	Section in CFR 47	Result
Conducted Emission	Part 15.107	Pass
Radiated Emission	Part 15.109	Pass

Pass: The EUT complies with the essential requirements in the standard.

5 General Information

5.1 Client Information

Applicant:	APRIX LATINOAMERICA S.A.
Address of Applicant:	ADVANCED 099 BLDG SUITE 4 C CALLE BEATRIZ M DE CABAL PANAMA
Manufacturer	Todos industrial limited
Address of Manufacturer:	Room 308, Building #5, Cofoc (Fuan) Robotics Industrial Park, No.90, Dayang Road, Fuyong Street, Shenzhen City, P.R. China

5.2 General Description of E.U.T.

Product Name:	Tablet PC
Model No.:	Aprix Tab8ii
Power supply:	Rechargeable Li-ion Battery DC3.8V-4000mAh
AC adapter :	Model: BY120502000 Input: AC100-240V, 50/60Hz, 0.3A Output: DC 5.0V, 2000mAh

5.3 Test Mode

Operating mode	Detail description
PC mode	Keep the EUT in Downloading mode(Worst case)
Charging+Recording mode	Keep the EUT in Charging+Recording mode
Charging+Playing mode	Keep the EUT in Charging+Playing mode
Charging+Recording(HDMI) mode	Keep the EUT in Charging+Recording(HDMI) mode(Worst case)
Charging+Playing(HDMI) mode	Keep the EUT in Charging+Playing(HDMI) mode
FM mode	Keep the EUT in FM receiver mode
GPS mode	Keep the EUT in GPS receiver mode

The sample was placed 0.8m above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.

5.4 Measurement Uncertainty

Items	Expanded Uncertainty (Confidence of 95%)
Conducted Emission (9kHz ~ 30MHz)	2.14 dB (k=2)
Radiated Emission (9kHz ~ 30MHz)	4.24 dB (k=2)
Radiated Emission (30MHz ~ 1000MHz)	4.35 dB (k=2)
Radiated Emission (1GHz ~ 18GHz)	4.44 dB (k=2)
Radiated Emission (18GHz ~ 26.5GHz)	4.56 dB (k=2)

5.5 Description of Support Units

Manufacturer	Description	Model	Serial Number	FCC ID/DoC
DELL	PC	OPTIPLEX745	N/A	DoC
DELL	MONITOR	E178FPC	N/A	DoC
DELL	KEYBOARD	SK-8115	N/A	DoC
DELL	MOUSE	MOC5UO	N/A	DoC
HP	Printer	CB495A	05257893	DoC
Skyworth	Color LCD TV	24E12HR	K026709	N/A

5.6 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **FCC - Registration No.: 817957**
 Shenzhen Zhongjian Nanfang Testing Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in out files. Registration 817957, February 27, 2012.
- **IC - Registration No.: 10106A-1**
 The 3m Semi-anechoic chamber of Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1.
- **CNAS - Registration No.: CNAS L6048**
 Shenzhen Zhongjian Nanfang Testing Co., Ltd. is accredited to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L6048.

5.7 Laboratory Location

Shenzhen Zhongjian Nanfang Testing Co., Ltd.
 Address: No. B-C, 1/F., Building 2, Laodong No.2 Industrial Park, Xixiang Road, Bao'an District, Shenzhen, Guangdong, China
 Website: <http://www.ccis-cb.com>
 Tel: +86-755-23118282
 Fax: +86-755-23116366
 Email: info@ccis-cb.com

5.8 Test Instruments list

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
1	3m SAC	SAEMC	9(L)*6(W)* 6(H)	CCIS0001	08-23-2014	08-22-2017
2	BiConiLog Antenna	SCHWARZBECK	VULB9163	CCIS0005	02-25-2017	02-24-2018
3	Horn Antenna	SCHWARZBECK	BBHA9120D	CCIS0006	02-25-2017	02-24-2018
4	Pre-amplifier (10kHz-1.3GHz)	HP	8447D	CCIS0003	02-25-2017	02-24-2018
5	Pre-amplifier (1GHz-18GHz)	Compliance Direction Systems Inc.	PAP-1G18	CCIS0011	02-25-2017	02-24-2018
6	Spectrum analyzer 9k-30GHz	Rohde & Schwarz	FSP30	CCIS0023	02-25-2017	02-24-2018
7	EMI Test Receiver	Rohde & Schwarz	ESRP7	CCIS0167	02-25-2017	02-24-2018
8	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
9	Coaxial Cable	N/A	N/A	CCIS0018	02-25-2017	02-24-2018
10	Coaxial Cable	N/A	N/A	CCIS0020	02-25-2017	02-24-2018


Conducted Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Shielding Room	ZhongShuo Electron	11.0(L)x4.0(W)x3.0(H)	CCIS0061	08-23-2014	08-22-2017
2	EMI Test Receiver	Rohde & Schwarz	ESCI	CCIS0002	02-25-2017	02-24-2018
3	LISN	CHASE	MN2050D	CCIS0074	02-25-2017	02-24-2018
4	Coaxial Cable	CCIS	N/A	CCIS0086	02-25-2017	02-24-2018
5	EMI Test Software	AUDIX	E3	N/A	N/A	N/A

6 Test results and Measurement Data

6.1 Conducted Emission

Test Requirement:	FCC Part 15 B Section 15.107					
Test Method:	ANSI C63.4:2014					
Test Frequency Range:	150kHz to 30MHz					
Class / Severity:	Class B					
Receiver setup:	RBW=9kHz, VBW=30kHz					
Limit:	Frequency range (MHz)	Limit (dB μ V)				
		Quasi-peak		Average		
	0.15-0.5	66 to 56*		56 to 46*		
	0.5-5	56		46		
	0.5-30	60		50		
* Decreases with the logarithm of the frequency.						
Test setup:	<p>Remark: E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m</p>					
Test procedure	<ol style="list-style-type: none"> 1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network(L.I.S.N.). The provide a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refers to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4: 2014 on conducted measurement. 					
Test environment:	Temp.:	23 °C	Humid.:	56%	Press.:	101kPa
Test Instruments:	Refer to section 5.7 for details					
Test mode:	Refer to section 5.3 for details					
Test results:	Pass					

Measurement data:
Test mode: PC
 Test Polarization: Line



Trace: 23


Site : CCIS Shielding Room
 Condition : FCC PART15 B QP LISN LINE
 EUT : Tablet PC
 Model : Aprix Tab8ii
 Test Mode : PC mode
 Power Rating : AC120/60Hz
 Environment : Temp: 23 °C Humi:56% Atmos:101KPa
 Test Engineer: Yaro
 Remark :

	Read Freq	Level	LISN Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.154	31.05	-0.56	10.78	41.27	55.78	-14.51	Average
2	0.170	40.41	-0.54	10.77	50.64	64.94	-14.30	QP
3	0.258	37.26	-0.51	10.75	47.50	61.51	-14.01	QP
4	0.262	28.28	-0.51	10.75	38.52	51.38	-12.86	Average
5	0.389	22.52	-0.50	10.72	32.74	48.08	-15.34	Average
6	2.474	31.90	-0.44	10.94	42.40	56.00	-13.60	QP
7	3.509	25.69	-0.36	10.90	36.23	46.00	-9.77	Average
8	3.642	33.50	-0.34	10.90	44.06	56.00	-11.94	QP
9	10.125	30.11	0.10	10.94	41.15	50.00	-8.85	Average
10	10.288	38.73	0.07	10.94	49.74	60.00	-10.26	QP
11	23.387	35.76	-0.62	10.89	46.03	60.00	-13.97	QP
12	23.511	30.86	-0.63	10.89	41.12	50.00	-8.88	Average

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Cable Loss.

Test Polarization: Neutral



Trace: 21

Site : CCIS Shielding Room
 Condition : FCC PART15 B QP LISN NEUTRAL
 EUT : Tablet PC
 Model : Aprix Tab8ii
 Test Mode : PC mode
 Power Rating : AC120/60Hz
 Environment : Temp: 23 °C Humi:56% Atmos:101KPa
 Test Engineer: Yaro
 Remark :

	Freq	Read Level	LISN Factor	Cable Loss	Level	Limit	Over	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.158	25.43	-0.37	10.77	35.83	55.56	-19.73	Average
2	0.169	40.98	-0.36	10.77	51.39	65.03	-13.64	QP
3	0.258	33.25	-0.33	10.75	43.67	61.51	-17.84	QP
4	0.258	24.17	-0.33	10.75	34.59	51.51	-16.92	Average
5	0.330	29.25	-0.32	10.73	39.66	59.44	-19.78	QP
6	0.389	13.87	-0.32	10.72	24.27	48.08	-23.81	Average
7	1.296	14.70	-0.28	10.90	25.32	46.00	-20.68	Average
8	2.334	27.27	-0.24	10.94	37.97	56.00	-18.03	QP
9	16.750	23.27	-0.38	10.91	33.80	50.00	-16.20	Average
10	16.839	34.26	-0.38	10.91	44.79	60.00	-15.21	QP
11	23.511	35.99	-0.68	10.89	46.20	60.00	-13.80	QP
12	23.636	26.38	-0.69	10.89	36.58	50.00	-13.42	Average


Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Cable Loss.

Measurement data:

Test mode: Charging+Recording(HDMI) mode

Test Polarization: Line



Trace: 55


Site : CCIS Shielding Room
 Condition : FCC PART15 B QP LISN LINE
 EUT : Tablet PC
 Model : Aprix Tab8ii
 Test Mode : HDMI mode
 Power Rating : AC120V/60Hz
 Environment : Temp: 23 °C Humi:56% Atmos:101KPa
 Test Engineer: Yaro
 Remark :

	Freq	Read Level	LISN Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.202	30.93	-0.52	10.76	41.17	53.54	-12.37	Average
2	0.307	29.24	-0.51	10.74	39.47	50.06	-10.59	Average
3	0.350	45.54	-0.50	10.73	55.77	58.96	-3.19	QP
4	0.486	43.91	-0.49	10.76	54.18	56.23	-2.05	QP
5	0.561	28.88	-0.49	10.76	39.15	46.00	-6.85	Average
6	0.767	28.05	-0.48	10.80	38.37	46.00	-7.63	Average
7	0.958	43.76	-0.49	10.86	54.13	56.00	-1.87	QP
8	1.060	28.38	-0.49	10.88	38.77	46.00	-7.23	Average
9	3.799	43.67	-0.32	10.90	54.25	56.00	-1.75	QP
10	5.476	46.59	-0.14	10.84	57.29	60.00	-2.71	QP
11	6.285	29.54	-0.06	10.81	40.29	50.00	-9.71	Average
12	6.733	47.04	-0.01	10.81	57.84	60.00	-2.16	QP

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Cable Loss.

Test Polarization: Neutral



Trace: 57
 Site : CCIS Shielding Room
 Condition : FCC PART15 B QP LISN NEUTRAL
 EUT : Tablet PC
 Model : Aprix Tab8ii
 Test Mode : HDMI mode
 Power Rating : AC120V/60Hz
 Environment : Temp: 23 °C Humi:56% Atmos:101KPa
 Test Engineer: Yaro
 Remark :

	Freq	Read Level	LISN Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.202	33.62	-0.34	10.76	44.04	53.54	-9.50	Average
2	0.206	44.96	-0.34	10.76	55.38	63.36	-7.98	QP
3	0.449	44.19	-0.31	10.74	54.62	56.89	-2.27	QP
4	0.494	30.65	-0.30	10.76	41.11	46.10	-4.99	Average
5	0.567	32.67	-0.30	10.76	43.13	46.00	-2.87	Average
6	0.767	31.45	-0.30	10.80	41.95	46.00	-4.05	Average
7	1.060	30.11	-0.29	10.88	40.70	46.00	-5.30	Average
8	1.317	43.29	-0.28	10.91	53.92	56.00	-2.08	QP
9	2.794	43.67	-0.21	10.93	54.39	56.00	-1.61	QP
10	5.713	46.79	-0.06	10.83	57.56	60.00	-2.44	QP
11	6.557	46.86	0.10	10.81	57.77	60.00	-2.23	QP
12	6.557	31.15	0.10	10.81	42.06	50.00	-7.94	Average

Notes:


- 4. An initial pre-scan was performed on the line and neutral lines with peak detector.
- 5. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
- 6. Final Level = Receiver Read level + LISN Factor + Cable Loss.

6.2 Radiated Emission

Test Requirement:	FCC Part 15 B Section 15.109				
Test Method:	ANSI C63.4:2014				
Test Frequency Range:	30MHz to 6000MHz				
Test site:	Measurement Distance: 3m (Semi-Anechoic Chamber)				
Receiver setup:	Frequency	Detector	RBW	VBW	Remark
	30MHz-1GHz	Quasi-peak	120kHz	300kHz	Quasi-peak Value
	Above 1GHz	Peak RMS	1MHz 1MHz	3MHz 3MHz	Peak Value Average Value
Limit:	Frequency	Limit (dBuV/m @3m)			Remark
	30MHz-88MHz	40.0			Quasi-peak Value
	88MHz-216MHz	43.5			Quasi-peak Value
	216MHz-960MHz	46.0			Quasi-peak Value
	960MHz-1GHz	54.0			Quasi-peak Value
	Above 1GHz	54.0			Average Value
		74.0			Peak Value
Test setup:	Below 1GHz				
	Above 1GHz				

<p>Test Procedure:</p>	<ol style="list-style-type: none"> 1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. 						
<p>Test environment:</p>	<table border="1"> <tr> <td>Temp.:</td> <td>25 °C</td> <td>Humid.:</td> <td>55%</td> <td>Press.:</td> <td>1 01kPa</td> </tr> </table>	Temp.:	25 °C	Humid.:	55%	Press.:	1 01kPa
Temp.:	25 °C	Humid.:	55%	Press.:	1 01kPa		
<p>Test Instruments:</p>	<p>Refer to section 5.7 for details</p>						
<p>Test mode:</p>	<p>Refer to section 5.3 for details</p>						
<p>Test results:</p>	<p>Passed</p>						
<p>Remark:</p>	<p>All of the observed value above 6GHz ware the niose floor , which were no recorded</p>						


Measurement Data:
Test Mode: PC mode
Below 1GHz
Test Polarization: Horizontal



Site : 3m chamber
 Condition : FCC PART15 CLASS B 3m VULB9163(30M2G) HORIZONTAL
 EUT : Tablet PC
 Model : Aprix Tab8ii
 Test mode : PC Mode
 Power Rating : AC120V/60Hz
 Environment : Temp:25.5°C Humi:55% 101KPa
 Test Engineer: Yaro
 REMARK :

	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit	Over	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	66.266	40.83	11.24	1.41	29.75	23.73	40.00	-16.27	QP
2	175.037	44.58	9.30	2.69	29.01	27.56	43.50	-15.94	QP
3	239.147	58.35	11.78	2.82	28.60	44.35	46.00	-1.65	QP
4	480.528	55.17	15.78	3.46	28.92	45.49	46.00	-0.51	QP
5	724.261	46.67	19.64	4.27	28.58	42.00	46.00	-4.00	QP
6	982.162	49.78	21.55	4.27	27.65	47.95	54.00	-6.05	QP


Test Polarization: Vertical



Site : 3m chamber
 Condition : FCC PART15 CLASS B 3m VULB9163(30M2G) VERTICAL
 EUT : Tablet PC
 Model : Aprix Tab8ii
 Test mode : PC Mode
 Power Rating : AC120V/60Hz
 Environment : Temp:25.5°C Humi:55% 101KPa
 Test Engineer: Yaro
 REMARK :

	Read	Antenna	Cable	Preamp	Limit	Over		
Freq	Level	Factor	Loss	Factor	Line	Limit	Remark	
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	73.876	43.49	9.52	1.61	29.69	24.93	40.00	-15.07 QP
2	104.170	42.25	12.12	1.99	29.50	26.86	43.50	-16.64 QP
3	243.377	45.62	11.92	2.82	28.58	31.78	46.00	-14.22 QP
4	480.528	52.80	15.78	3.46	28.92	43.12	46.00	-2.88 QP
5	721.726	44.51	19.58	4.26	28.58	39.77	46.00	-6.23 QP
6	962.162	44.74	21.55	4.27	27.65	42.91	54.00	-11.09 QP


Above 1GHz
 Test Polarization: Horizontal



Site : 3m chamber
 Condition : FCC PART 15 (PK) 3m BBHA9120(1G18G) HORIZONTAL
 EUT : Tablet PC
 Model : Aprix Tab8ii
 Test mode : PC Mode
 Power Rating : AC120V/60Hz
 Environment : Temp:25.5°C Humi:55%
 Test Engineer: Yaro
 REMARK :

	Freq	ReadAntenna	Cable	Preamp	Level	Limit	Over	Remark
	MHz	Level	Factor	Loss	Factor	Line	Limit	
		dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	3086.435	49.36	27.25	5.38	41.46	40.53	74.00	-33.47 Peak
2	3086.435	38.38	27.25	5.38	41.46	29.55	54.00	-24.45 Average
3	4215.562	54.37	28.79	6.43	41.82	47.77	74.00	-26.23 Peak
4	4215.562	44.17	28.79	6.43	41.82	37.57	54.00	-16.43 Average
5	5143.163	52.33	31.38	7.05	41.93	48.83	74.00	-25.17 Peak
6	5143.163	43.78	31.38	7.05	41.93	40.28	54.00	-13.72 Average


Test Polarization: Vertical



Site : 3m chamber
 Condition : FCC PART 15 (PK) 3m BBHA9120(1G18G) VERTICAL
 EUT : Tablet PC
 Model : Aprix Tab8ii
 Test mode : PC Mode
 Power Rating : AC120V/60Hz
 Environment : Temp:25.5°C Humi:55%
 Test Engineer: Yaro
 REMARK :

	Read	Antenna	Cable	Preamp	Limit	Over		
Freq	Level	Factor	Loss	Factor	Line	Limit	Remark	
-----MHz	-----dBUV	-----dB/m	-----dB	-----dB	-----dBUV/m	-----dBUV/m	-----dB	-----
1	2346.389	50.02	25.33	4.65	41.86	38.14	74.00	-35.86 Peak
2	2346.389	38.58	25.33	4.65	41.86	26.70	54.00	-27.30 Average
3	4536.905	52.66	29.47	6.84	42.08	46.89	74.00	-27.11 Peak
4	4536.905	41.04	29.47	6.84	42.08	35.27	54.00	-18.73 Average
5	4979.933	52.82	31.71	6.92	41.87	49.58	74.00	-24.42 Peak
6	4979.933	42.75	31.71	6.92	41.87	39.51	54.00	-14.49 Average


Measurement Data:
Test Mode: Charging+Recording(HDMI) mode
Below 1GHz
Test Polarization: Horizontal



Site : 3m chamber
 Condition : FCC PART15 CLASS B 3m VULB9163(30M2G) HORIZONTAL
 EUT : Tablet PC
 Model : Aprix Tab8ii
 Test mode : DHMI Mode
 Power Rating : AC120V/60Hz
 Environment : Temp:25.5°C Humi:55% 101KPa
 Test Engineer: Yaro
 REMARK :


	Freq	ReadLevel	Antenna Factor	Cable Loss	Preamp	Level	Limit	Over	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	148.441	55.45	8.46	2.50	29.23	37.18	43.50	-6.32	QP
2	297.224	55.80	13.34	2.93	28.46	43.61	46.00	-2.39	QP
3	444.851	53.64	15.60	3.19	28.86	43.57	46.00	-2.43	QP
4	742.259	48.28	19.55	4.33	28.51	43.65	46.00	-2.35	QP
5	824.597	43.34	20.24	4.27	28.10	39.75	46.00	-6.25	QP
6	890.728	47.80	20.85	3.80	27.90	44.55	46.00	-1.45	QP

Test Polarization: Vertical




Site : 3m chamber
 Condition : FCC PART15 CLASS B 3m VULB9163(30M2G) VERTICAL
 EUT : Tablet PC
 Model : Aprix Tab8ii
 Test mode : DHMI Mode
 Power Rating : AC120V/60Hz
 Environment : Temp:25.5°C Humi:55% 101KPa
 Test Engineer: Yaro
 REMARK :

	Freq	ReadAntenna	Cable	Preamp	Limit	Over	
	MHz	Level	Factor	Loss	Line	Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m
1	65.803	49.57	11.24	1.41	29.75	32.47	40.00 -7.53 QP
2	148.963	51.43	8.46	2.51	29.23	33.17	43.50 -10.33 QP
3	372.005	48.05	14.52	3.09	28.66	37.00	46.00 -9.00 QP
4	444.851	49.14	15.60	3.19	28.86	39.07	46.00 -6.93 QP
5	742.259	45.37	19.55	4.33	28.51	40.74	46.00 -5.26 QP
6	890.728	45.06	20.85	3.80	27.90	41.81	46.00 -4.19 QP



Test Polarization: Vertical



Site : 3m chamber
 Condition : FCC PART 15 (PK) 3m BBHA9120(1G18G) VERTICAL
 EUT : Tablet PC
 Model : Aprix Tab8ii
 Test mode : DHMI Mode
 Power Rating : AC120V/60Hz
 Environment : Temp:25.5°C Humi:55%
 Test Engineer: Yaro
 REMARK :

	Freq	ReadAntenna	Cable	Preamp	Limit	Over	
	MHz	Level	Factor	Loss	Line	Limit	Remark
		dBuV	dB/m	dB	dB	dBuV/m	dBuV/m
1	3199.044	48.94	27.31	5.42	41.41	40.26	74.00 -33.74 Peak
2	3199.044	38.19	27.31	5.42	41.41	29.51	54.00 -24.49 Average
3	4988.864	47.07	31.80	6.93	41.88	43.92	74.00 -30.08 Peak
4	4988.864	38.92	31.80	6.93	41.88	35.77	54.00 -18.23 Average
5	5768.088	49.62	31.12	7.79	41.98	46.55	74.00 -27.45 Peak
6	5768.088	40.19	31.12	7.79	41.98	37.12	54.00 -16.88 Average