

FCC ID: 2AHJX-03H16006

RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm²)	Average Time
(A) Limits for Occupational/Control Exposures				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
(B) Limits for General Population/Uncontrol Exposures				
300-1500	--	--	F/1500	6
1500-100000	--	--	1	30

11.1 Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = Power density in mW/cm²

P_{out} =output power to antenna in mW

G = Numeric gain of the antenna relative to isotropic antenna

π =3.1416

R = distance between observation point and center of the radiator in cm(20cm)

P_d the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

$mW = 10^{(dBm/10)}$

11.2 Measurement Result

Operation Frequency: WIFI 802.11b/g/n HT20: 2412-2462MHz,
 Power density limited: $1\text{mW}/\text{cm}^2$
 Antenna Type: FPCB Antenna
 Antenna gain: 3.63dBi,
 R=20cm
 $\text{mW}=10^{(\text{dBm}/10)}$
 802.11b/g/n:

Channel Freq. (MHz)	modulation	conducted power (mW)	conducted power (dBm)	Tune-up power (dBm)	Max tune-up power (dBm)	Antenna Gain Numeric	Evaluation result (mW/cm ²)	Power density Limits (mW/cm ²)
2412	802.11b	16.444	12.16	12±1	13	2.31	0.009156	1
2437	802.11b	15.631	11.94	12±1	13	2.31	0.009156	1
2462	802.11b	16.444	12.16	12±1	13	2.31	0.009156	1
2412	802.11g	15.346	11.86	12±1	13	2.31	0.009156	1
2437	802.11g	15.382	11.87	12±1	13	2.31	0.009156	1
2462	802.11g	16.749	12.24	12±1	13	2.31	0.009156	1
2412	802.11n H20	10.715	10.30	10±1	11	2.31	0.005777	1
2437	802.11n H20	10.990	10.41	10±1	11	2.31	0.005777	1
2462	802.11n H20	11.858	10.74	10±1	11	2.31	0.005777	1

Operation Frequency: 2402MHz~2480MHz
 Power density limited: $1\text{mW}/\text{cm}^2$
 Antenna Type: PCB Antenna
 Antenna gain: 3.63dBi,
 R=20cm
 $\text{mW}=10^{(\text{dBm}/10)}$

Bluetooth DSS:


Channel Freq. (MHz)	modulation	conducted power (mW)	conducted power (dBm)	Tune-up power (dBm)	Max tune-up power (dBm)	Antenna Gain Numeric	Evaluation result (mW/cm ²)	Power density Limits (mW/cm ²)
2402	GFSK	1.633	2.130	3±1	4	2.31	0.001153	1
2441		2.063	3.144	3±1	4	2.31	0.001153	1
2480		1.898	2.784	3±1	4	2.31	0.001153	1
2402	π/4-DQPSK	1.786	2.518	3±1	4	2.31	0.001153	1
2441		2.243	3.508	3±1	4	2.31	0.001153	1
2480		2.058	3.135	3±1	4	2.31	0.001153	1
2402	8DPSK	1.981	2.968	3±1	4	2.31	0.001153	1
2441		2.479	3.943	3±1	4	2.31	0.001153	1
2480		2.303	3.623	3±1	4	2.31	0.001153	1

Bluetooth DTS:

Channel Freq. (MHz)	modulation	conducted power (mW)	conducted power (dBm)	Tune-up power (dBm)	Max tune-up power (dBm)	Antenna Gain Numeric	Evaluation result (mW/cm ²)	Power density Limits (mW/cm ²)
2402	GFSK	0.809	-0.920	0±1	1	2.31	0.000578	1
2440		0.995	-0.022	0±1	1	2.31	0.000578	1
2480		1.041	0.174	0±1	1	2.31	0.000578	1

Conclusion:

For the max result : $0.009156 \leq 3.0$ for 1g SAR, No SAR is required.



Signature:

Date: 2016-9-13

NAME AND TITLE (Please print or type): Jason Chen/Manager

COMPANY (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen P.R. China.