



# RADIO EXPOSURE TEST REPORT

**FCC ID** : 2AHKM-NOVA1214  
**Equipment** : Wi-Fi 6 Voice GPON HGU  
**Brand Name** : Hitron  
**Model Name** : NOVA-1214  
**Applicant** : Hitron Technologies Inc.  
No. 1-8, Li-Hsin 1st Rd. Hsinchu Science Park,  
Hsinchu 30078, Taiwan  
**Manufacturer** : Hitron Technologies Inc.  
No. 1-8, Li-Hsin 1st Rd. Hsinchu Science Park,  
Hsinchu 30078, Taiwan  
**Standard** : 47 CFR Part 2.1091

The product was received on Dec. 08, 2022, and testing was started from Dec. 29, 2022 and completed on Feb. 27, 2023. We, Sporton International Inc. Hsinchu Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in 47 CFR Part 2.1091 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. Hsinchu Laboratory, the test report shall not be reproduced except in full.

Approved by: Sam Chen

**Sporton International Inc. Hsinchu Laboratory**

No.8, Ln. 724, Bo'ai St., Zhubei City, Hsinchu County 302010, Taiwan (R.O.C.)



## Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
<b>1 General Description .....</b>	<b>5</b>
1.1 EUT General Information .....	5
1.2 Antenna Information .....	6
1.3 Accessories .....	7
1.4 Applicable Standards .....	7
1.5 Testing Location .....	7
<b>2 Maximum Permissible Exposure .....</b>	<b>8</b>
2.1 Limit of Maximum Permissible Exposure .....	8
2.2 MPE Calculation Method .....	8
2.3 MPE Exemption .....	9
2.4 Calculated Result and Limit.....	10
<b>Photographs of EUT v01</b>	





## Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
2	-	Exposure evaluation	PASS	-

**Declaration of Conformity:**

1. The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers. It's means measurement values may risk exceeding the limit of regulation standards, if measurement uncertainty is include in test results.
2. The measurement uncertainty please refer to report "Measurement Uncertainty".

**Comments and Explanations:**

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Reviewed by: **Sam Chen**

Report Producer: **Penny Kao**



# 1 General Description

## 1.1 EUT General Information

RF General Information			
Evaluation Mode	Frequency Range (MHz)	Operating Frequency (MHz)	Modulation Type
2.4GHz WLAN	2400-2483.5	2412-2462	802.11b: DSSS (DBPSK, DQPSK, CCK) 802.11g/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) VHT: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM) 802.11ax: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM)
5GHz WLAN	5150-5250 5250-5350 5470-5725 5725-5850	5180-5250 5250-5320 5500-5720 5745-5825	802.11a/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM) 802.11ax: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM)



## 1.2 Antenna Information

Ant.	Port		Brand	Model Name	Antenna Type	Connector	Gain (dBi)
	WLAN 2.4GHz	WLAN 5GHz					
1	1	-	HONGBO	290-20512	PIFA	I-Pex	Note 1
2	2	-	HONGBO	290-20511	Dipole	I-Pex	
3	-	1	HONGBO	290-20513	Dipole	I-Pex	
4	-	2	HONGBO	290-20515	Dipole	I-Pex	
5	-	3	HONGBO	290-20514	Dipole	I-Pex	

Note 1:

### <Antenna Gain>

Ant.	Port		Antenna Gain (dBi)						
	WLAN 2.4GHz	WLAN 5GHz	WLAN 2.4GHz			WLAN 5GHz			
			2400MHz	2450MHz	2483.5MHz	UNII 1	UNII 2A	UNII 2C	UNII 3
1	1	-	1.98	2.11	1.82	-	-	-	-
2	2	-	1.45	1.13	1.01	-	-	-	-
3	-	1	-	-	-	2.06	2.01	2.62	2.37
4	-	2	-	-	-	3.72	2.34	2.92	2.76
5	-	3	-	-	-	2.87	3.4	3.65	4

### <Directional Gain>

Item	Directional Gain (dBi)						
	WLAN 2.4GHz			WLAN 5GHz			
	2400MHz	2450MHz	2483.5MHz	UNII 1	UNII 2A	UNII 2C	UNII 3
2T1S	2.07	2.5	3.56	-	-	-	-
3T1S	-	-	-	3.77	3.55	3.98	4.31

Note 2: The above information (except gain) was declared by manufacturer.

The directional gain is measured which follows the procedure of KDB 662911 D03.

Note 3: The EUT has five antennas.

#### <WLAN 2.4GHz function>

##### For IEEE 802.11b/g/n/VHT/ax (2TX/2RX):

Pot 1, Port 2 can be used as transmitting/receiving antenna.

Pot 1, Port 2 could transmit/receive simultaneously.

#### <WLAN 5GHz function>

##### For IEEE 802.11a/n/ac/ax mode (3TX/3RX)

Pot 1, Port 2 and Port 3 can be used as transmitting/receiving antenna.

Pot 1, Port 2 and Port 3 could transmit/receive simultaneously.



### 1.3 Accessories

Accessories			
Equipment Name	Brand Name	Model Name	Rating
Adapter 1	MOSO	MS-V2000R120-024Q0-US	Input: 100-240V~50/60Hz, 0.7A max. Output: 12.0V, 2.0A
Adapter 2	AMIGO	AMS200A-1202000FU	Input: 100-240V~ 50/60Hz, 0.8A Max Output: 12V, 2.0A
Others			
RJ-45 cable*1: Non-shielded, 1.5m			

### 1.4 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 2.1091
- ♦ KDB 447498 D04 Interim General RF Exposure Guidance v01

The following reference test guidance is not within the scope of accreditation of TAF.

- ♦ 47 CFR Part 1.1307
- ♦ 47 CFR Part 1.1310

### 1.5 Testing Location

Testing Location Information	
Test Lab. : Sporton International Inc. Hsinchu Laboratory	
Hsinchu	ADD: No.8, Ln. 724, Bo'ai St., Zhubei City, Hsinchu County 302010, Taiwan (R.O.C.)
(TAF: 3787)	TEL: 886-3-656-9065      FAX: 886-3-656-9085
Test site Designation No. TW3787 with FCC.	
Conformity Assessment Body Identifier (CABID) TW3787 with ISED.	



## 2 Maximum Permissible Exposure

### 2.1 Limit of Maximum Permissible Exposure

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	*(100)	<6
3.0-30	1842/f	4.89/f	*(900/f <sup>2</sup> )	<6
30-300	61.4	0.163	1.0	<6
300-1500	-	-	f/300	<6
1500-100,000	-	-	5	<6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	*(100)	<30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	<30
30-300	27.5	0.073	0.2	<30
300-1500	-	-	f/1500	<30
1500-100,000	-	-	1.0	<30

Note: f = frequency in MHz ; \*Plane-wave equivalent power density

### 2.2 MPE Calculation Method

The MPE was calculated at 20 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \qquad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

**E** = Electric field (V/m)

**P** = RF output power (W)

**G** = EUT Antenna numeric gain (numeric)

**d** = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$





### 2.3 MPE Exemption

Option (A): 1.1307(b)(3)(i)(A): Available maximum time-averaged power is < 1 mW

Option (B): 1.1307(b)(3)(i)(B): Device operates between 300 MHz and 6 GHz and the maximum time-averaged power or effective radiated power (ERP), whichever is greater, <= Pth.

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left( \frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

d = the separation distance (cm);

Option (C): 1.1307(b)(3)(i)(C): ERP is below a threshold calculated based on the distance R between the person and the antenna / radiating structure, where  $R > \lambda / 2 \pi$ .

Single RF Sources Subject to Routine Environmental Evaluation	
RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	$1,920 R^2$ .
1.34-30	$3,450 R^2/f^2$ .
30-300	$3.83 R^2$ .
300-1,500	$0.0128 R^2f$ .
1,500-100,000	$19.2R^2$ .

Note: R is in meters, f is in MHz.



## 2.4 Calculated Result and Limit

### Exposure Environment: General Population / Uncontrolled Exposure

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up EIRP (dBm)	Distance (cm)	S (mW/cm <sup>2</sup> )	S Limit (mW/cm <sup>2</sup> )	Option	TL EIRP (dBm)	TL Ratio
2.4G;D1D	3.56	25.37	28.93	0.50	29.43	20	0.17447	1.00000	B	37.006	0.1748
5.2G;D1D	3.77	28.83	32.60	0.50	33.10	20	0.40619	1.00000	B	37.006	0.4069
5.3G;D1D	3.55	23.73	27.28	0.50	27.78	20	0.11932	1.00000	B	37.006	0.1195
5.6G;D1D	3.98	23.94	27.92	0.50	28.42	20	0.13827	1.00000	B	37.006	0.1385
5.8G;D1D	4.31	29.77	34.08	0.50	34.58	20	0.57112	1.00000	B	37.006	0.5721

### Simultaneous Transmission Analysis Mode: WLAN 2.4GHz+WLAN 5GHz

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up EIRP (dBm)	Distance (cm)	S (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Option	TL EIRP (dBm)	TL Ratio
2.4G;D1D	3.56	25.37	28.93	0.50	29.43	20	0.17447	1.00000	B	37.006	0.1748
5.8G;D1D	4.31	29.77	34.08	0.50	34.58	20	0.57112	1.00000	B	37.006	0.5721
Sum TL Ratio_B	0.7469										
Ratio Limit	1										

————THE END————